Gateway Documentation - Static Maintenance

Oracle FLEXCUBE Universal Banking

Release FCUBS_12.0.87.1.0

[August] [2014]

Table Of Contents

1. BACKGROUND **1**

2. FCUBSSTService **2**

2.1. ReopenLMDCUSLT **2**

2.1.1. LM-ReopenLMDCUSLT-Req-Full-MSG.xsd *2*

2.1.2. LM-ReopenLMDCUSLT-Req-IO-MSG.xsd *20*

2.1.3. LM-ReopenLMDCUSLT-Res-Full-MSG.xsd *27*

2.1.4. LM-ReopenLMDCUSLT-Res-PK-MSG.xsd *47*

2.2. createSaveCLAppEntry **56**

2.2.1. OR-CreateSaveCLAppEntry-Req-Full-MSG.xsd *56*

2.2.2. OR-CreateSaveCLAppEntry-Req-IO-MSG.xsd *167*

2.2.3. OR-CreateSaveCLAppEntry-Res-Full-MSG.xsd *256*

2.2.4. OR-CreateSaveCLAppEntry-Res-PK-MSG.xsd *369*

2.3. AuthSTTypeMnt **458**

2.3.1. ST-AuthSTTypeMnt-Res-Full-MSG.xsd *458*

2.3.2. ST-AuthSTTypeMnt-Res-PK-MSG.xsd *472*

2.3.3. ST-AuthSTTypeMnt-Req-Full-MSG.xsd *486*

2.3.4. ST-AuthSTTypeMnt-Req-IO-MSG.xsd *497*

2.4. AuthorizeACRSMaint **504**

2.4.1. ST-AuthorizeACRSMaint-Req-Full-MSG.xsd *504*

2.4.2. ST-AuthorizeACRSMaint-Req-IO-MSG.xsd *515*

2.4.3. ST-AuthorizeACRSMaint-Res-Full-MSG.xsd *521*

2.4.4. ST-AuthorizeACRSMaint-Res-PK-MSG.xsd *533*

2.5. AuthorizeAccClasMaint **542**

2.5.1. ST-AuthorizeAccClasMaint-Req-Full-MSG.xsd *542*

2.5.2. ST-AuthorizeAccClasMaint-Req-IO-MSG.xsd *636*

2.5.3. ST-AuthorizeAccClasMaint-Res-Full-MSG.xsd *643*

2.5.4. ST-AuthorizeAccClasMaint-Res-PK-MSG.xsd *738*

2.6. AuthorizeBranch **747**

2.6.1. ST-AuthorizeBranch-Req-Full-MSG.xsd *747*

2.6.2. ST-AuthorizeBranch-Req-IO-MSG.xsd *794*

2.6.3. ST-AuthorizeBranch-Res-Full-MSG.xsd *801*

2.6.4. ST-AuthorizeBranch-Res-PK-MSG.xsd *850*

2.7. AuthorizeBranchTrfr **859**

2.7.1. ST-AuthorizeBranchTrfr-Req-Full-MSG.xsd *859*

2.7.2. ST-AuthorizeBranchTrfr-Req-IO-MSG.xsd *870*

2.7.3. ST-AuthorizeBranchTrfr-Res-Full-MSG.xsd *877*

2.7.4. ST-AuthorizeBranchTrfr-Res-PK-MSG.xsd *889*

2.8. AuthorizeCRSRequest **898**

2.8.1. ST-AuthorizeCRSRequest-Req-Full-MSG.xsd *898*

2.8.2. ST-AuthorizeCRSRequest-Req-IO-MSG.xsd *909*

2.8.3. ST-AuthorizeCRSRequest-Res-Full-MSG.xsd *915*

2.8.4. ST-AuthorizeCRSRequest-Res-PK-MSG.xsd *927*

2.9. AuthorizeCardAccount **936**

2.9.1. ST-AuthorizeCardAccount-Req-Full-MSG.xsd *936*

2.9.2. ST-AuthorizeCardAccount-Req-IO-MSG.xsd *946*

2.9.3. ST-AuthorizeCardAccount-Res-Full-MSG.xsd *953*

2.9.4. ST-AuthorizeCardAccount-Res-PK-MSG.xsd *966*

2.10. AuthorizeCardMaster **980**

2.10.1. ST-AuthorizeCardMaster-Req-Full-MSG.xsd *980*

2.10.2. ST-AuthorizeCardMaster-Req-IO-MSG.xsd *1001*

2.10.3. ST-AuthorizeCardMaster-Res-Full-MSG.xsd *1009*

2.10.4. ST-AuthorizeCardMaster-Res-PK-MSG.xsd *1031*

2.11. AuthorizeCustTrfr **1042**

2.11.1. ST-AuthorizeCustTrfr-Req-Full-MSG.xsd *1042*

ORACLE

2.11.2. ST-AuthorizeCustTrfr-Req-IO-MSG.xsd *1053*
2.11.3. ST-AuthorizeCustTrfr-Res-Full-MSG.xsd *1060*
2.11.4. ST-AuthorizeCustTrfr-Res-PK-MSG.xsd *1073*
2.12. AuthorizeExtDeal **1082**
2.12.1. ST-AuthorizeExtDeal-Req-Full-MSG.xsd *1082*
2.12.2. ST-AuthorizeExtDeal-Req-IO-MSG.xsd *1093*
2.12.3. ST-AuthorizeExtDeal-Res-Full-MSG.xsd *1099*
2.12.4. ST-AuthorizeExtDeal-Res-PK-MSG.xsd *1111*
2.13. AuthorizeJointHolderMaint **1120**
2.13.1. ST-AuthorizeJointHolderMaint-Req-Full-MSG.xsd *1120*
2.13.2. ST-AuthorizeJointHolderMaint-Req-IO-MSG.xsd *1131*
2.13.3. ST-AuthorizeJointHolderMaint-Res-Full-MSG.xsd *1138*
2.13.4. ST-AuthorizeJointHolderMaint-Res-PK-MSG.xsd *1151*
2.14. AuthorizeLMDCUSLT **1161**
2.14.1. LM-AuthorizeLMDCUSLT-Req-Full-MSG.xsd *1161*
2.14.2. LM-AuthorizeLMDCUSLT-Req-IO-MSG.xsd *1179*
2.14.3. LM-AuthorizeLMDCUSLT-Res-Full-MSG.xsd *1186*
2.14.4. LM-AuthorizeLMDCUSLT-Res-PK-MSG.xsd *1206*
2.15. CloseLMDCUSLT **1215**
2.15.1. LM-CloseLMDCUSLT-Req-Full-MSG.xsd *1215*
2.15.2. LM-CloseLMDCUSLT-Req-IO-MSG.xsd *1233*
2.15.3. LM-CloseLMDCUSLT-Res-Full-MSG.xsd *1240*
2.15.4. LM-CloseLMDCUSLT-Res-PK-MSG.xsd *1260*
2.16. CreateLMDCUSLT **1269**
2.16.1. LM-CreateLMDCUSLT-Req-Full-MSG.xsd *1269*
2.16.2. LM-CreateLMDCUSLT-Req-IO-MSG.xsd *1287*
2.16.3. LM-CreateLMDCUSLT-Res-Full-MSG.xsd *1301*
2.16.4. LM-CreateLMDCUSLT-Res-PK-MSG.xsd *1321*
2.17. DeleteLMDCUSLT **1337**
2.17.1. LM-DeleteLMDCUSLT-Req-Full-MSG.xsd *1337*
2.17.2. LM-DeleteLMDCUSLT-Req-IO-MSG.xsd *1355*
2.17.3. LM-DeleteLMDCUSLT-Res-Full-MSG.xsd *1361*
2.17.4. LM-DeleteLMDCUSLT-Res-PK-MSG.xsd *1381*
2.18. ModifyLMDCUSLT **1390**
2.18.1. LM-ModifyLMDCUSLT-Req-Full-MSG.xsd *1390*
2.18.2. LM-ModifyLMDCUSLT-Req-IO-MSG.xsd *1408*
2.18.3. LM-ModifyLMDCUSLT-Res-Full-MSG.xsd *1424*
2.18.4. LM-ModifyLMDCUSLT-Res-PK-MSG.xsd *1444*
2.19. QueryLMDCUSLT **1462**
2.19.1. LM-QueryLMDCUSLT-Req-IO-MSG.xsd *1462*
2.19.2. LM-QueryLMDCUSLT-Res-Full-MSG.xsd *1468*
2.20. CloseBranch **1488**
2.20.1. ST-CloseBranch-Res-Full-MSG.xsd *1488*
2.20.2. ST-CloseBranch-Res-PK-MSG.xsd *1537*
2.20.3. ST-CloseBranch-Req-Full-MSG.xsd *1546*
2.20.4. ST-CloseBranch-Req-IO-MSG.xsd *1593*
2.21. CloseBranchTrfr **1600**
2.21.1. ST-CloseBranchTrfr-Req-Full-MSG.xsd *1600*
2.21.2. ST-CloseBranchTrfr-Req-IO-MSG.xsd *1611*
2.21.3. ST-CloseBranchTrfr-Res-Full-MSG.xsd *1618*
2.21.4. ST-CloseBranchTrfr-Res-PK-MSG.xsd *1630*
2.22. CloseCRSRequest **1639**
2.22.1. ST-CloseCRSRequest-Req-Full-MSG.xsd *1639*
2.22.2. ST-CloseCRSRequest-Req-IO-MSG.xsd *1650*
2.22.3. ST-CloseCRSRequest-Res-Full-MSG.xsd *1657*
2.22.4. ST-CloseCRSRequest-Res-PK-MSG.xsd *1669*
2.23. CloseCardMaster **1678**
2.23.1. ST-CloseCardMaster-Req-Full-MSG.xsd *1678*

2.23.2. ST-CloseCardMaster-Req-IO-MSG.xsd *1699*
2.23.3. ST-CloseCardMaster-Res-Full-MSG.xsd *1707*
2.23.4. ST-CloseCardMaster-Res-PK-MSG.xsd *1729*
2.24. CloseCustTrfr **1740**
2.24.1. ST-CloseCustTrfr-Req-Full-MSG.xsd *1740*
2.24.2. ST-CloseCustTrfr-Req-IO-MSG.xsd *1751*
2.24.3. ST-CloseCustTrfr-Res-Full-MSG.xsd *1758*
2.24.4. ST-CloseCustTrfr-Res-PK-MSG.xsd *1771*
2.25. CloseExtDeal **1780**
2.25.1. ST-CloseExtDeal-Req-Full-MSG.xsd *1780*
2.25.2. ST-CloseExtDeal-Req-IO-MSG.xsd *1791*
2.25.3. ST-CloseExtDeal-Res-Full-MSG.xsd *1798*
2.25.4. ST-CloseExtDeal-Res-PK-MSG.xsd *1810*
2.26. CloseOnlineCharge **1819**
2.26.1. ST-CloseOnlineCharge-Req-Full-MSG.xsd *1819*
2.26.2. ST-CloseOnlineCharge-Req-IO-MSG.xsd *1828*
2.26.3. ST-CloseOnlineCharge-Res-Full-MSG.xsd *1835*
2.26.4. ST-CloseOnlineCharge-Res-PK-MSG.xsd *1846*
2.27. CloseSTDSTDOR **1855**
2.27.1. ST-CloseSTDSTDOR-Req-Full-MSG.xsd *1855*
2.27.2. ST-CloseSTDSTDOR-Req-IO-MSG.xsd *1866*
2.27.3. ST-CloseSTDSTDOR-Res-Full-MSG.xsd *1873*
2.27.4. ST-CloseSTDSTDOR-Res-PK-MSG.xsd *1885*
2.28. CreateACRSMaint **1895**
2.28.1. ST-CreateACRSMaint-Req-Full-MSG.xsd *1895*
2.28.2. ST-CreateACRSMaint-Req-IO-MSG.xsd *1906*
2.28.3. ST-CreateACRSMaint-Res-Full-MSG.xsd *1914*
2.28.4. ST-CreateACRSMaint-Res-PK-MSG.xsd *1926*
2.29. CreateAccClasMaint **1936**
2.29.1. ST-CreateAccClasMaint-Req-Full-MSG.xsd *1936*
2.29.2. ST-CreateAccClasMaint-Req-IO-MSG.xsd *2030*
2.29.3. ST-CreateAccClasMaint-Res-Full-MSG.xsd *2119*
2.29.4. ST-CreateAccClasMaint-Res-PK-MSG.xsd *2214*
2.30. CreateBranch **2306**
2.30.1. ST-CreateBranch-Req-Full-MSG.xsd *2306*
2.30.2. ST-CreateBranch-Req-IO-MSG.xsd *2353*
2.30.3. ST-CreateBranch-Res-Full-MSG.xsd *2392*
2.30.4. ST-CreateBranch-Res-PK-MSG.xsd *2441*
2.31. createSaveRLAppEntry **2482**
2.31.1. OR-CreateSaveRLAppEntry-Req-Full-MSG.xsd *2482*
2.31.2. OR-CreateSaveRLAppEntry-Req-IO-MSG.xsd *2585*
2.31.3. OR-CreateSaveRLAppEntry-Res-Full-MSG.xsd *2667*
2.31.4. OR-CreateSaveRLAppEntry-Res-PK-MSG.xsd *2771*
2.32. AuthCustCatMaint **2853**
2.32.1. ST-AuthCustCatMaint-Req-Full-MSG.xsd *2853*
2.32.2. ST-AuthCustCatMaint-Req-IO-MSG.xsd *2863*
2.32.3. ST-AuthCustCatMaint-Res-Full-MSG.xsd *2870*
2.32.4. ST-AuthCustCatMaint-Res-PK-MSG.xsd *2883*
2.33. AuthLocMaint **2896**
2.33.1. ST-AuthLocMaint-Req-Full-MSG.xsd *2896*
2.33.2. ST-AuthLocMaint-Req-IO-MSG.xsd *2906*
2.33.3. ST-AuthLocMaint-Res-Full-MSG.xsd *2913*
2.33.4. ST-AuthLocMaint-Res-PK-MSG.xsd *2926*
2.34. AuthManStatChangInp **2939**
2.34.1. ST-AuthManStatChangInp-Req-Full-MSG.xsd *2939*
2.34.2. ST-AuthManStatChangInp-Req-IO-MSG.xsd *2952*
2.34.3. ST-AuthManStatChangInp-Res-Full-MSG.xsd *2959*
2.34.4. ST-AuthManStatChangInp-Res-PK-MSG.xsd *2975*

2.35. AuthNoticePRD **2992**
2.35.1. ST-AuthNoticePRD-Req-Full-MSG.xsd *2992*
2.35.2. ST-AuthNoticePRD-Req-IO-MSG.xsd *3004*
2.35.3. ST-AuthNoticePRD-Res-Full-MSG.xsd *3011*
2.35.4. ST-AuthNoticePRD-Res-PK-MSG.xsd *3025*
2.36. CreateCustTrfr **3034**
2.36.1. ST-CreateCustTrfr-Res-Full-MSG.xsd *3034*
2.36.2. ST-CreateCustTrfr-Res-PK-MSG.xsd *3047*
2.36.3. ST-CreateCustTrfr-Req-Full-MSG.xsd *3058*
2.36.4. ST-CreateCustTrfr-Req-IO-MSG.xsd *3069*
2.37. CreateExtDeal **3078**
2.37.1. ST-CreateExtDeal-Req-Full-MSG.xsd *3078*
2.37.2. ST-CreateExtDeal-Req-IO-MSG.xsd *3089*
2.37.3. ST-CreateExtDeal-Res-Full-MSG.xsd *3097*
2.37.4. ST-CreateExtDeal-Res-PK-MSG.xsd *3109*
2.38. CreateLocMaint **3119**
2.38.1. ST-CreateLocMaint-Req-Full-MSG.xsd *3119*
2.38.2. ST-CreateLocMaint-Req-IO-MSG.xsd *3129*
2.38.3. ST-CreateLocMaint-Res-Full-MSG.xsd *3139*
2.38.4. ST-CreateLocMaint-Res-PK-MSG.xsd *3155*
2.39. CreateManStatChangInp **3172**
2.39.1. ST-CreateManStatChangInp-Req-Full-MSG.xsd *3172*
2.39.2. ST-CreateManStatChangInp-Req-IO-MSG.xsd *3185*
2.39.3. ST-CreateManStatChangInp-Res-Full-MSG.xsd *3197*
2.39.4. ST-CreateManStatChangInp-Res-PK-MSG.xsd *3218*
2.40. CreateManStatChange **3240**
2.40.1. ST-CreateManStatChange-Req-Full-MSG.xsd *3240*
2.40.2. ST-CreateManStatChange-Req-IO-MSG.xsd *3254*
2.40.3. ST-CreateManStatChange-Res-Full-MSG.xsd *3264*
2.40.4. ST-CreateManStatChange-Res-PK-MSG.xsd *3279*
2.41. CreateNoticePRD **3292**
2.41.1. ST-CreateNoticePRD-Req-Full-MSG.xsd *3292*
2.41.2. ST-CreateNoticePRD-Req-IO-MSG.xsd *3304*
2.41.3. ST-CreateNoticePRD-Res-Full-MSG.xsd *3316*
2.41.4. ST-CreateNoticePRD-Res-PK-MSG.xsd *3335*
2.42. CreateOnlineCharge **3349**
2.42.1. ST-CreateOnlineCharge-Req-Full-MSG.xsd *3349*
2.42.2. ST-CreateOnlineCharge-Req-IO-MSG.xsd *3358*
2.42.3. ST-CreateOnlineCharge-Res-Full-MSG.xsd *3365*
2.42.4. ST-CreateOnlineCharge-Res-PK-MSG.xsd *3376*
2.43. CreateSTDSTCDM **3385**
2.43.1. ST-CreateSTDSTCDM-Req-Full-MSG.xsd *3385*
2.43.2. ST-CreateSTDSTCDM-Req-IO-MSG.xsd *3394*
2.43.3. ST-CreateSTDSTCDM-Res-Full-MSG.xsd *3402*
2.43.4. ST-CreateSTDSTCDM-Res-PK-MSG.xsd *3413*
2.44. CreateSTDSTDOR **3423**
2.44.1. ST-CreateSTDSTDOR-Req-Full-MSG.xsd *3423*
2.44.2. ST-CreateSTDSTDOR-Req-IO-MSG.xsd *3434*
2.44.3. ST-CreateSTDSTDOR-Res-Full-MSG.xsd *3442*
2.44.4. ST-CreateSTDSTDOR-Res-PK-MSG.xsd *3454*
2.45. CreateSTTypeMnt **3465**
2.45.1. ST-CreateSTTypeMnt-Req-Full-MSG.xsd *3465*
2.45.2. ST-CreateSTTypeMnt-Req-IO-MSG.xsd *3476*
2.45.3. ST-CreateSTTypeMnt-Res-Full-MSG.xsd *3487*
2.45.4. ST-CreateSTTypeMnt-Res-PK-MSG.xsd *3505*
2.46. CreateServiceRequest **3524**
2.46.1. ST-CreateServiceRequest-Req-Full-MSG.xsd *3524*
2.46.2. ST-CreateServiceRequest-Req-IO-MSG.xsd *3537*

2.46.3. ST-CreateServiceRequest-Res-Full-MSG.xsd 3547
2.46.4. ST-CreateServiceRequest-Res-PK-MSG.xsd 3562
2.47. AuthorizeManStatChange **3574**
2.47.1. ST-AuthorizeManStatChange-Req-Full-MSG.xsd 3574
2.47.2. ST-AuthorizeManStatChange-Req-IO-MSG.xsd 3588
2.47.3. ST-AuthorizeManStatChange-Res-Full-MSG.xsd 3596
2.47.4. ST-AuthorizeManStatChange-Res-PK-MSG.xsd 3611
2.48. AuthorizeOnlineCharge **3621**
2.48.1. ST-AuthorizeOnlineCharge-Req-Full-MSG.xsd 3621
2.48.2. ST-AuthorizeOnlineCharge-Req-IO-MSG.xsd 3630
2.48.3. ST-AuthorizeOnlineCharge-Res-Full-MSG.xsd 3637
2.48.4. ST-AuthorizeOnlineCharge-Res-PK-MSG.xsd 3648
2.49. AuthorizeSTDSTCDM **3657**
2.49.1. ST-AuthorizeSTDSTCDM-Req-Full-MSG.xsd 3657
2.49.2. ST-AuthorizeSTDSTCDM-Req-IO-MSG.xsd 3666
2.49.3. ST-AuthorizeSTDSTCDM-Res-Full-MSG.xsd 3673
2.49.4. ST-AuthorizeSTDSTCDM-Res-PK-MSG.xsd 3684
2.50. AuthorizeSTDSTDOR **3693**
2.50.1. ST-AuthorizeSTDSTDOR-Req-Full-MSG.xsd 3693
2.50.2. ST-AuthorizeSTDSTDOR-Req-IO-MSG.xsd 3704
2.50.3. ST-AuthorizeSTDSTDOR-Res-Full-MSG.xsd 3711
2.50.4. ST-AuthorizeSTDSTDOR-Res-PK-MSG.xsd 3723
2.51. CloseACRSMaint **3733**
2.51.1. ST-CloseACRSMaint-Req-Full-MSG.xsd 3733
2.51.2. ST-CloseACRSMaint-Req-IO-MSG.xsd 3744
2.51.3. ST-CloseACRSMaint-Res-Full-MSG.xsd 3751
2.51.4. ST-CloseACRSMaint-Res-PK-MSG.xsd 3763
2.52. DeleteCustCatMaint **3772**
2.52.1. ST-DeleteCustCatMaint-Res-Full-MSG.xsd 3772
2.52.2. ST-DeleteCustCatMaint-Res-PK-MSG.xsd 3785
2.52.3. ST-DeleteCustCatMaint-Req-Full-MSG.xsd 3798
2.52.4. ST-DeleteCustCatMaint-Req-IO-MSG.xsd 3808
2.53. DeleteCustTrfr **3814**
2.53.1. ST-DeleteCustTrfr-Req-Full-MSG.xsd 3814
2.53.2. ST-DeleteCustTrfr-Req-IO-MSG.xsd 3825
2.53.3. ST-DeleteCustTrfr-Res-Full-MSG.xsd 3831
2.53.4. ST-DeleteCustTrfr-Res-PK-MSG.xsd 3844
2.54. DeleteJointHolderMaint **3853**
2.54.1. ST-DeleteJointHolderMaint-Req-Full-MSG.xsd 3853
2.54.2. ST-DeleteJointHolderMaint-Req-IO-MSG.xsd 3864
2.54.3. ST-DeleteJointHolderMaint-Res-Full-MSG.xsd 3871
2.54.4. ST-DeleteJointHolderMaint-Res-PK-MSG.xsd 3884
2.55. DeleteLocMaint **3893**
2.55.1. ST-DeleteLocMaint-Req-Full-MSG.xsd 3893
2.55.2. ST-DeleteLocMaint-Req-IO-MSG.xsd 3903
2.55.3. ST-DeleteLocMaint-Res-Full-MSG.xsd 3909
2.55.4. ST-DeleteLocMaint-Res-PK-MSG.xsd 3921
2.56. DeleteManStatChangInp **3934**
2.56.1. ST-DeleteManStatChangInp-Req-Full-MSG.xsd 3934
2.56.2. ST-DeleteManStatChangInp-Req-IO-MSG.xsd 3947
2.56.3. ST-DeleteManStatChangInp-Res-Full-MSG.xsd 3954
2.56.4. ST-DeleteManStatChangInp-Res-PK-MSG.xsd 3970
2.57. DeleteManStatChange **3987**
2.57.1. ST-DeleteManStatChange-Req-Full-MSG.xsd 3987
2.57.2. ST-DeleteManStatChange-Req-IO-MSG.xsd 4001
2.57.3. ST-DeleteManStatChange-Res-Full-MSG.xsd 4008
2.57.4. ST-DeleteManStatChange-Res-PK-MSG.xsd 4023
2.58. DeleteNoticePRD **4033**

2.58.1. ST-DeleteNoticePRD-Req-Full-MSG.xsd 4033
2.58.2. ST-DeleteNoticePRD-Req-IO-MSG.xsd 4045
2.58.3. ST-DeleteNoticePRD-Res-Full-MSG.xsd 4051
2.58.4. ST-DeleteNoticePRD-Res-PK-MSG.xsd 4065
2.59. DeleteOnlineCharge **4074**
2.59.1. ST-DeleteOnlineCharge-Req-Full-MSG.xsd 4074
2.59.2. ST-DeleteOnlineCharge-Req-IO-MSG.xsd 4083
2.59.3. ST-DeleteOnlineCharge-Res-Full-MSG.xsd 4089
2.59.4. ST-DeleteOnlineCharge-Res-PK-MSG.xsd 4100
2.60. DeleteSTDSTCDM **4108**
2.60.1. ST-DeleteSTDSTCDM-Req-Full-MSG.xsd 4108
2.60.2. ST-DeleteSTDSTCDM-Req-IO-MSG.xsd 4117
2.60.3. ST-DeleteSTDSTCDM-Res-Full-MSG.xsd 4124
2.60.4. ST-DeleteSTDSTCDM-Res-PK-MSG.xsd 4135
2.61. DeleteSTDSTDOR **4144**
2.61.1. ST-DeleteSTDSTDOR-Req-Full-MSG.xsd 4144
2.61.2. ST-DeleteSTDSTDOR-Req-IO-MSG.xsd 4155
2.61.3. ST-DeleteSTDSTDOR-Res-Full-MSG.xsd 4162
2.61.4. ST-DeleteSTDSTDOR-Res-PK-MSG.xsd 4174
2.62. DeleteSTTypeMnt **4183**
2.62.1. ST-DeleteSTTypeMnt-Req-Full-MSG.xsd 4183
2.62.2. ST-DeleteSTTypeMnt-Req-IO-MSG.xsd 4194
2.62.3. ST-DeleteSTTypeMnt-Res-Full-MSG.xsd 4200
2.62.4. ST-DeleteSTTypeMnt-Res-PK-MSG.xsd 4213
2.63. CreateBranchTrfr **4227**
2.63.1. ST-CreateBranchTrfr-Req-Full-MSG.xsd 4227
2.63.2. ST-CreateBranchTrfr-Req-IO-MSG.xsd 4238
2.63.3. ST-CreateBranchTrfr-Res-Full-MSG.xsd 4246
2.63.4. ST-CreateBranchTrfr-Res-PK-MSG.xsd 4258
2.64. CreateCRSRequest **4268**
2.64.1. ST-CreateCRSRequest-Req-Full-MSG.xsd 4268
2.64.2. ST-CreateCRSRequest-Req-IO-MSG.xsd 4279
2.64.3. ST-CreateCRSRequest-Res-Full-MSG.xsd 4287
2.64.4. ST-CreateCRSRequest-Res-PK-MSG.xsd 4299
2.65. CreateCardAccount **4309**
2.65.1. ST-CreateCardAccount-Req-Full-MSG.xsd 4309
2.65.2. ST-CreateCardAccount-Req-IO-MSG.xsd 4319
2.65.3. ST-CreateCardAccount-Res-Full-MSG.xsd 4329
2.65.4. ST-CreateCardAccount-Res-PK-MSG.xsd 4345
2.66. CreateCardMaster **4362**
2.66.1. ST-CreateCardMaster-Req-Full-MSG.xsd 4362
2.66.2. ST-CreateCardMaster-Req-IO-MSG.xsd 4383
2.66.3. ST-CreateCardMaster-Res-Full-MSG.xsd 4401
2.66.4. ST-CreateCardMaster-Res-PK-MSG.xsd 4423
2.67. CreateCustCatMaint **4444**
2.67.1. ST-CreateCustCatMaint-Req-Full-MSG.xsd 4444
2.67.2. ST-CreateCustCatMaint-Req-IO-MSG.xsd 4454
2.67.3. ST-CreateCustCatMaint-Res-Full-MSG.xsd 4464
2.67.4. ST-CreateCustCatMaint-Res-PK-MSG.xsd 4481
2.68. ModifyCardMaster **4498**
2.68.1. ST-ModifyCardMaster-Res-Full-MSG.xsd 4498
2.68.2. ST-ModifyCardMaster-Res-PK-MSG.xsd 4520
2.68.3. ST-ModifyCardMaster-Req-Full-MSG.xsd 4538
2.68.4. ST-ModifyCardMaster-Req-IO-MSG.xsd 4559
2.69. ModifyCustCatMaint **4574**
2.69.1. ST-ModifyCustCatMaint-Req-Full-MSG.xsd 4574
2.69.2. ST-ModifyCustCatMaint-Req-IO-MSG.xsd 4584
2.69.3. ST-ModifyCustCatMaint-Res-Full-MSG.xsd 4593

2.69.4. ST-ModifyCustCatMaint-Res-PK-MSG.xsd *4608*
2.70. ModifyCustTrfr **4623**
2.70.1. ST-ModifyCustTrfr-Req-Full-MSG.xsd *4623*
2.70.2. ST-ModifyCustTrfr-Req-IO-MSG.xsd *4634*
2.70.3. ST-ModifyCustTrfr-Res-Full-MSG.xsd *4643*
2.70.4. ST-ModifyCustTrfr-Res-PK-MSG.xsd *4656*
2.71. ModifyJointHolderMaint **4667**
2.71.1. ST-ModifyJointHolderMaint-Req-Full-MSG.xsd *4667*
2.71.2. ST-ModifyJointHolderMaint-Req-IO-MSG.xsd *4678*
2.71.3. ST-ModifyJointHolderMaint-Res-Full-MSG.xsd *4687*
2.71.4. ST-ModifyJointHolderMaint-Res-PK-MSG.xsd *4700*
2.72. ModifyLocMaint **4712**
2.72.1. ST-ModifyLocMaint-Req-Full-MSG.xsd *4712*
2.72.2. ST-ModifyLocMaint-Req-IO-MSG.xsd *4722*
2.72.3. ST-ModifyLocMaint-Res-Full-MSG.xsd *4730*
2.72.4. ST-ModifyLocMaint-Res-PK-MSG.xsd *4744*
2.73. ModifyManStatChangInp **4759**
2.73.1. ST-ModifyManStatChangInp-Req-Full-MSG.xsd *4759*
2.73.2. ST-ModifyManStatChangInp-Req-IO-MSG.xsd *4772*
2.73.3. ST-ModifyManStatChangInp-Res-Full-MSG.xsd *4781*
2.73.4. ST-ModifyManStatChangInp-Res-PK-MSG.xsd *4799*
2.74. ModifyManStatChange **4818**
2.74.1. ST-ModifyManStatChange-Req-Full-MSG.xsd *4818*
2.74.2. ST-ModifyManStatChange-Req-IO-MSG.xsd *4832*
2.74.3. ST-ModifyManStatChange-Res-Full-MSG.xsd *4842*
2.74.4. ST-ModifyManStatChange-Res-PK-MSG.xsd *4857*
2.75. ModifyOnlineCharge **4870**
2.75.1. ST-ModifyOnlineCharge-Req-Full-MSG.xsd *4870*
2.75.2. ST-ModifyOnlineCharge-Req-IO-MSG.xsd *4879*
2.75.3. ST-ModifyOnlineCharge-Res-Full-MSG.xsd *4887*
2.75.4. ST-ModifyOnlineCharge-Res-PK-MSG.xsd *4898*
2.76. ModifySTDSTCDM **4908**
2.76.1. ST-ModifySTDSTCDM-Req-Full-MSG.xsd *4908*
2.76.2. ST-ModifySTDSTCDM-Req-IO-MSG.xsd *4917*
2.76.3. ST-ModifySTDSTCDM-Res-Full-MSG.xsd *4925*
2.76.4. ST-ModifySTDSTCDM-Res-PK-MSG.xsd *4936*
2.77. ModifySTDSTDOR **4946**
2.77.1. ST-ModifySTDSTDOR-Req-Full-MSG.xsd *4946*
2.77.2. ST-ModifySTDSTDOR-Req-IO-MSG.xsd *4957*
2.77.3. ST-ModifySTDSTDOR-Res-Full-MSG.xsd *4966*
2.77.4. ST-ModifySTDSTDOR-Res-PK-MSG.xsd *4978*
2.78. ModifySTTypeMnt **4989**
2.78.1. ST-ModifySTTypeMnt-Req-Full-MSG.xsd *4989*
2.78.2. ST-ModifySTTypeMnt-Req-IO-MSG.xsd *5000*
2.78.3. ST-ModifySTTypeMnt-Res-Full-MSG.xsd *5009*
2.78.4. ST-ModifySTTypeMnt-Res-PK-MSG.xsd *5025*
2.79. DeleteAccClasMaint **5042**
2.79.1. ST-DeleteAccClasMaint-Req-Full-MSG.xsd *5042*
2.79.2. ST-DeleteAccClasMaint-Req-IO-MSG.xsd *5136*
2.79.3. ST-DeleteAccClasMaint-Res-Full-MSG.xsd *5142*
2.79.4. ST-DeleteAccClasMaint-Res-PK-MSG.xsd *5237*
2.80. DeleteBranch **5246**
2.80.1. ST-DeleteBranch-Req-Full-MSG.xsd *5246*
2.80.2. ST-DeleteBranch-Req-IO-MSG.xsd *5293*
2.80.3. ST-DeleteBranch-Res-Full-MSG.xsd *5299*
2.80.4. ST-DeleteBranch-Res-PK-MSG.xsd *5348*
2.81. DeleteBranchTrfr **5357**
2.81.1. ST-DeleteBranchTrfr-Req-Full-MSG.xsd *5357*

2.81.2. ST-DeleteBranchTrfr-Req-IO-MSG.xsd 5368
2.81.3. ST-DeleteBranchTrfr-Res-Full-MSG.xsd 5374
2.81.4. ST-DeleteBranchTrfr-Res-PK-MSG.xsd 5386
2.82. DeleteCardAccount 5395
2.82.1. ST-DeleteCardAccount-Req-Full-MSG.xsd 5395
2.82.2. ST-DeleteCardAccount-Req-IO-MSG.xsd 5405
2.82.3. ST-DeleteCardAccount-Res-Full-MSG.xsd 5412
2.82.4. ST-DeleteCardAccount-Res-PK-MSG.xsd 5425
2.83. DeleteCardMaster 5438
2.83.1. ST-DeleteCardMaster-Req-Full-MSG.xsd 5438
2.83.2. ST-DeleteCardMaster-Req-IO-MSG.xsd 5459
2.83.3. ST-DeleteCardMaster-Res-Full-MSG.xsd 5466
2.83.4. ST-DeleteCardMaster-Res-PK-MSG.xsd 5488
2.84. QueryCustTrfr 5498
2.84.1. ST-QueryCustTrfr-Req-IO-MSG.xsd 5498
2.84.2. ST-QueryCustTrfr-Res-Full-MSG.xsd 5504
2.85. QueryDealer 5517
2.85.1. ST-QueryDealer-Req-IO-MSG.xsd 5517
2.85.2. ST-QueryDealer-Res-Full-MSG.xsd 5523
2.86. QueryExtDeal 5535
2.86.1. ST-QueryExtDeal-Req-IO-MSG.xsd 5535
2.86.2. ST-QueryExtDeal-Res-Full-MSG.xsd 5541
2.87. QueryJointHolderMaint 5554
2.87.1. ST-QueryJointHolderMaint-Req-IO-MSG.xsd 5554
2.87.2. ST-QueryJointHolderMaint-Res-Full-MSG.xsd 5561
2.88. QueryLocMaint 5575
2.88.1. ST-QueryLocMaint-Req-IO-MSG.xsd 5575
2.88.2. ST-QueryLocMaint-Res-Full-MSG.xsd 5581
2.89. QueryManStatChangInp 5593
2.89.1. ST-QueryManStatChangInp-Req-IO-MSG.xsd 5593
2.89.2. ST-QueryManStatChangInp-Res-Full-MSG.xsd 5600
2.90. QueryManStatChange 5616
2.90.1. ST-QueryManStatChange-Req-IO-MSG.xsd 5616
2.90.2. ST-QueryManStatChange-Res-Full-MSG.xsd 5623
2.91. QueryNoticePRD 5640
2.91.1. ST-QueryNoticePRD-Req-IO-MSG.xsd 5640
2.91.2. ST-QueryNoticePRD-Res-Full-MSG.xsd 5646
2.92. QueryOnlineCharge 5660
2.92.1. ST-QueryOnlineCharge-Req-IO-MSG.xsd 5660
2.92.2. ST-QueryOnlineCharge-Res-Full-MSG.xsd 5667
2.93. QuerySTDSTCDM 5679
2.93.1. ST-QuerySTDSTCDM-Req-IO-MSG.xsd 5679
2.93.2. ST-QuerySTDSTCDM-Res-Full-MSG.xsd 5686
2.94. QuerySTDSTDOR 5698
2.94.1. ST-QuerySTDSTDOR-Req-IO-MSG.xsd 5698
2.94.2. ST-QuerySTDSTDOR-Res-Full-MSG.xsd 5705
2.95. QuerySTTypeMnt 5718
2.95.1. ST-QuerySTTypeMnt-Req-IO-MSG.xsd 5718
2.95.2. ST-QuerySTTypeMnt-Res-Full-MSG.xsd 5724
2.96. QueryServiceRequest 5737
2.96.1. ST-QueryServiceRequest-Req-IO-MSG.xsd 5737
2.96.2. ST-QueryServiceRequest-Res-Full-MSG.xsd 5743
2.97. QueryTransactionCodes 5758
2.97.1. ST-QueryTransactionCodes-Req-IO-MSG.xsd 5758
2.97.2. ST-QueryTransactionCodes-Res-Full-MSG.xsd 5764
2.98. ReopenACRSMaint 5782
2.98.1. ST-ReopenACRSMaint-Req-Full-MSG.xsd 5782

2.98.2. ST-ReopenACRSMaint-Req-IO-MSG.xsd 5793
2.98.3. ST-ReopenACRSMaint-Res-Full-MSG.xsd 5800
2.98.4. ST-ReopenACRSMaint-Res-PK-MSG.xsd 5812
2.99. ReopenBranch **5821**
2.99.1. ST-ReopenBranch-Req-Full-MSG.xsd 5821
2.99.2. ST-ReopenBranch-Req-IO-MSG.xsd 5868
2.99.3. ST-ReopenBranch-Res-Full-MSG.xsd 5875
2.99.4. ST-ReopenBranch-Res-PK-MSG.xsd 5924
2.100. ReopenBranchTrfr **5933**
2.100.1. ST-ReopenBranchTrfr-Req-Full-MSG.xsd 5933
2.100.2. ST-ReopenBranchTrfr-Req-IO-MSG.xsd 5944
2.100.3. ST-ReopenBranchTrfr-Res-Full-MSG.xsd 5951
2.100.4. ST-ReopenBranchTrfr-Res-PK-MSG.xsd 5963
2.101. ReopenCRSRequest **5972**
2.101.1. ST-ReopenCRSRequest-Req-Full-MSG.xsd 5972
2.101.2. ST-ReopenCRSRequest-Req-IO-MSG.xsd 5983
2.101.3. ST-ReopenCRSRequest-Res-Full-MSG.xsd 5990
2.101.4. ST-ReopenCRSRequest-Res-PK-MSG.xsd 6002
2.102. ModifyACRSMaint **6011**
2.102.1. ST-ModifyACRSMaint-Req-Full-MSG.xsd 6011
2.102.2. ST-ModifyACRSMaint-Req-IO-MSG.xsd 6022
2.102.3. ST-ModifyACRSMaint-Res-Full-MSG.xsd 6030
2.102.4. ST-ModifyACRSMaint-Res-PK-MSG.xsd 6042
2.103. ModifyAccClasMaint **6053**
2.103.1. ST-ModifyAccClasMaint-Req-Full-MSG.xsd 6053
2.103.2. ST-ModifyAccClasMaint-Req-IO-MSG.xsd 6147
2.103.3. ST-ModifyAccClasMaint-Res-Full-MSG.xsd 6234
2.103.4. ST-ModifyAccClasMaint-Res-PK-MSG.xsd 6329
2.104. ModifyBranch **6418**
2.104.1. ST-ModifyBranch-Req-Full-MSG.xsd 6418
2.104.2. ST-ModifyBranch-Req-IO-MSG.xsd 6465
2.104.3. ST-ModifyBranch-Res-Full-MSG.xsd 6503
2.104.4. ST-ModifyBranch-Res-PK-MSG.xsd 6552
2.105. ModifyBranchTrfr **6592**
2.105.1. ST-ModifyBranchTrfr-Req-Full-MSG.xsd 6592
2.105.2. ST-ModifyBranchTrfr-Req-IO-MSG.xsd 6603
2.105.3. ST-ModifyBranchTrfr-Res-Full-MSG.xsd 6611
2.105.4. ST-ModifyBranchTrfr-Res-PK-MSG.xsd 6623
2.106. ModifyCRSRequest **6634**
2.106.1. ST-ModifyCRSRequest-Req-Full-MSG.xsd 6634
2.106.2. ST-ModifyCRSRequest-Req-IO-MSG.xsd 6645
2.106.3. ST-ModifyCRSRequest-Res-Full-MSG.xsd 6653
2.106.4. ST-ModifyCRSRequest-Res-PK-MSG.xsd 6665
2.107. ReopenCardMaster **6675**
2.107.1. ST-ReopenCardMaster-Req-Full-MSG.xsd 6675
2.107.2. ST-ReopenCardMaster-Req-IO-MSG.xsd 6696
2.107.3. ST-ReopenCardMaster-Res-Full-MSG.xsd 6704
2.107.4. ST-ReopenCardMaster-Res-PK-MSG.xsd 6726
2.108. ReopenCustTrfr **6737**
2.108.1. ST-ReopenCustTrfr-Req-Full-MSG.xsd 6737
2.108.2. ST-ReopenCustTrfr-Req-IO-MSG.xsd 6748
2.108.3. ST-ReopenCustTrfr-Res-Full-MSG.xsd 6755
2.108.4. ST-ReopenCustTrfr-Res-PK-MSG.xsd 6768
2.109. ReopenOnlineCharge **6777**
2.109.1. ST-ReopenOnlineCharge-Req-Full-MSG.xsd 6777
2.109.2. ST-ReopenOnlineCharge-Req-IO-MSG.xsd 6786
2.109.3. ST-ReopenOnlineCharge-Res-Full-MSG.xsd 6793
2.109.4. ST-ReopenOnlineCharge-Res-PK-MSG.xsd 6804

2.110. ReopenSTDSTCDM **6813**
2.110.1. ST-ReopenSTDSTCDM-Req-Full-MSG.xsd *6813*
2.110.2. ST-ReopenSTDSTCDM-Req-IO-MSG.xsd *6822*
2.110.3. ST-ReopenSTDSTCDM-Res-Full-MSG.xsd *6829*
2.110.4. ST-ReopenSTDSTCDM-Res-PK-MSG.xsd *6840*
2.111. ReopenSTDSTDOR **6849**
2.111.1. ST-ReopenSTDSTDOR-Req-Full-MSG.xsd *6849*
2.111.2. ST-ReopenSTDSTDOR-Req-IO-MSG.xsd *6860*
2.111.3. ST-ReopenSTDSTDOR-Res-Full-MSG.xsd *6867*
2.111.4. ST-ReopenSTDSTDOR-Res-PK-MSG.xsd *6879*
2.112. ModifyServiceRequest **6889**
2.112.1. ST-ModifyServiceRequest-Req-Full-MSG.xsd *6889*
2.112.2. ST-ModifyServiceRequest-Req-IO-MSG.xsd *6902*
2.112.3. ST-ModifyServiceRequest-Res-Full-MSG.xsd *6911*
2.112.4. ST-ModifyServiceRequest-Res-PK-MSG.xsd *6926*
2.113. QueryACRSMaint **6937**
2.113.1. ST-QueryACRSMaint-Req-IO-MSG.xsd *6937*
2.113.2. ST-QueryACRSMaint-Res-Full-MSG.xsd *6943*
2.114. QueryAccClasMaint **6956**
2.114.1. ST-QueryAccClasMaint-Req-IO-MSG.xsd *6956*
2.114.2. ST-QueryAccClasMaint-Res-Full-MSG.xsd *6963*
2.115. QueryBranch **7059**
2.115.1. ST-QueryBranch-Req-IO-MSG.xsd *7059*
2.115.2. ST-QueryBranch-Res-Full-MSG.xsd *7066*
2.116. QueryBranchSysDates **7115**
2.116.1. ST-QueryBranchSysDates-Req-IO-MSG.xsd *7115*
2.116.2. ST-QueryBranchSysDates-Res-Full-MSG.xsd *7121*
2.117. QueryBranchTrfr **7134**
2.117.1. ST-QueryBranchTrfr-Req-IO-MSG.xsd *7134*
2.117.2. ST-QueryBranchTrfr-Res-Full-MSG.xsd *7140*
2.118. QueryCRSRequest **7153**
2.118.1. ST-QueryCRSRequest-Req-IO-MSG.xsd *7153*
2.118.2. ST-QueryCRSRequest-Res-Full-MSG.xsd *7159*
2.119. QueryCardAccount **7172**
2.119.1. ST-QueryCardAccount-Req-IO-MSG.xsd *7172*
2.119.2. ST-QueryCardAccount-Res-Full-MSG.xsd *7179*
2.120. QueryCardMaster **7192**
2.120.1. ST-QueryCardMaster-Req-IO-MSG.xsd *7192*
2.120.2. ST-QueryCardMaster-Res-Full-MSG.xsd *7199*
2.121. QueryCustCatMaint **7223**
2.121.1. ST-QueryCustCatMaint-Req-IO-MSG.xsd *7223*
2.121.2. ST-QueryCustCatMaint-Res-Full-MSG.xsd *7229*

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.
The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS
2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS
The following sections provide detailed XSD documentation of all operations available in FCUBSSTService of Core-Module

2.FCUBSSTService

Static MaintenanceStatic Maintenance

2.1.ReopenLMDCUSLT

ReopenLMDCUSLT

2.1.1.LM-ReopenLMDCUSLT-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*

UNCOLL_FUNDS_LIMIT

TOD_LIMIT

OFFLINE_LIMIT

CCY

DAY_LIM_AMT

SOD_NOT_PER

RN_FLG

NXT_RN_LI

RN_FREQ

RN_UN

AUTO_CR_POOL_LI

AC_DESC

CUSTNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Sttms-Cust-Acc-Limit-Coll

- *COLLTYPE*
- *ACCBRN*
- *AVAILABLE_AMOUNT*
- *LNKDAMT*
- *APP_INT_RATE*
- *INT_SPREAD*
- *RATE_OF_INT*
- *COLLCAT*
- *COLLHAIR*
- *COLL*

Od-Limit

- *CUSTOMER_NO*
- *LINKTYP*
- *LINKAGE_REF_NO*
- *PER_CONTRIBUTION*
- *LINKAGE_SEQUENCE_NUMBER*
- *LIABNO*
- *EFFECTIVE_DATE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length = 3; pattern = [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable = true
Restrictions	**Restrictions** / **Description**: pattern = [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable = true
Restrictions	**Restrictions** / **Description**: pattern = [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	Description
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Od-Limit

Attribute	**Description**
Name	Od-Limit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NO

Attribute	**Description**
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKTYP

Attribute	**Description**
Name	LINKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	**Description**
Name	LINKAGE_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

ORACLE

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.1.2.LM-ReopenLMDCUSLT-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-IO*
    - *ACNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.1.3.LM-ReopenLMDCUSLT-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*
    - *CCY*
    - *DAY_LIM_AMT*
    - *SOD_NOT_PER*

RN_FLG

NXT_RN_LI

RN_FREQ

RN_UN

AUTO_CR_POOL_LI

AC_DESC

CUSTNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Sttms-Cust-Acc-Limit-Coll

COLLTYPE

ACCBRN

AVAILABLE_AMOUNT

LNKDAMT

APP_INT_RATE

INT_SPREAD

RATE_OF_INT

COLLCAT

COLLHAIR

COLL

Od-Limit

CUSTOMER_NO

LINKTYP

LINKAGE_REF_NO

PER_CONTRIBUTION

LINKAGE_SEQUENCE_NUMBER

LIABNO

EFFECTIVE_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	Description
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Od-Limit

Attribute	**Description**
Name	Od-Limit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NO

Attribute	**Description**
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKTYP

Attribute	**Description**
Name	LINKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	**Description**
Name	LINKAGE_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.1.4.LM-ReopenLMDCUSLT-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Lmdcuslt-PK*
      - *ACNO*
    - *Lmdcuslt-IO*
      - *ACNO*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Lmdcuslt-PK

Attribute	Description
Name	Lmdcuslt-PK
Datatype	
Description	

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.createSaveCLAppEntry

Offline save of CLAPP entry

2.2.1.OR-CreateSaveCLAppEntry-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Applicationhead-Full*
    - *APPNO*
    - *DATE*
    - *PRDCD*
    - *CHNL*
    - *BRN*
    - *STAT*
    - *INTERCD*
    - *INTNAME*
    - *CUSTTYPE1*
    - *CCY*
    - *LEAD*
    - *CONT*
    - *PUR*
    - *USERREFNO*
    - *APPCAT*

ENQUIRY_ID
OFFAPPLNUM
Customer1
- *APPNO*
- *CUSTNO*
- *NATID*
- *LANG*
- *EXISTING*
- *CCY*
- *CTYPE*
- *ACLASS*
- *ACCNO*
- *SNAME*
- *CNTY*
- *NLTY*
- *CCAT*
- *NAME*
- *LINE1*
- *LINE2*
- *LINE3*
- *DATE*
- *CAPITAL*
- *NETWORTH*
- *BUSIDESC*
- *INCNTY*
- *RCNTY*
- *CCYAMT*
- *Customer3*
  - *EMAIL*
  - *CUSTNO*
  - *DIRNAME*
  - *LINE1*
  - *LINE2*
  - *LINE3*
  - *LINE4*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *CNTY*
  - *TEL*
  - *TAXID*
  - *MOBNO*
- *Customer2*
  - *APPNO*

- *CUSTNO*
- *ADDTYPE*
- *MAILING*
- *CONNO*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ZIP*
- *CNTY*

Financials1

- *CUSTNO*
- *FIXEDASSETS*
- *INTANGASSETS*
- *NONCURRASSETS*
- *SUBSIDYFRMGOV*
- *GENRESERVES*
- *TERMLIAB*
- *CURRLIAB*
- *ISSUEDCAP*
- *PAIDUPCAP*
- *CRBALINPL*
- *OPACT*
- *INVACT*
- *FINACT*
- *CURRASSETS*

Collat1

- *APPNO*
- *CUSTNO*
- *COLLCD*
- *COLLDESC*
- *COLLCCY*
- *COLLVL*
- *COLLSTDT*
- *COLLENDDT*
- *COLLCAT*
- *COLLHAIR*
- *COLLTYPE*
- *COLLREVDT*
- *COLLCHGDT*
- *COLLREVLDT*
- *COLLREVCHK*
- *SECUID*
- *NOMUNITVL*
- *CAPAMT*

- *GUAID*
- *RATIN*
- *LNKPCTNO*
- *LNKAMT*
- *Collat2*
  - *APPNO*
  - *CUSTNO*
  - *DUEDT*
  - *STMON*
  - *REM*
  - *COVNM*
  - *DESC*
  - *REVDT*
  - *MANDT*
  - *GRCDAY*
  - *NOTDAY*
  - *FREQ*
- *Vehdetails*
  - *VEH_IDNUM*
  - *VEH_YEAR*
  - *VEH_MAKE*
  - *VEH_MODEL*
  - *VEH_BDYSTYLE*
  - *VEH_USAGE*

Financials2

- *APPNO*
- *CUSTNO*
- *LIABTYP*
- *LIABSUB*
- *LIABFREQ*
- *LAIBAMT*
- *BAL*
- *REM*
- *LIABSTDT*
- *LIABENDDT*

Finsummary

- *MONSTATINC*
- *MONACTINC*
- *MONSTATDEBT*
- *MONACTDEBT*
- *GRADE*
- *SCORE*
- *ASSETWORTH*
- *LIABWORTH*

- *TOTWOR*
- *WHTPMT*
- *Finsummary2*
  - *RATNM*
  - *STATBF*
  - *STATAF*
  - *ACTBF*
  - *ACTAF*

Investi1

- *CUSTNO*
- *VERTYPE*
- *AGENCY*

Investi2

- *SPOKE*
- *ATTEMPTS*
- *CALLDT*
- *RESULT*
- *VERMAT*
- *REM*

Custdedupe

- *CTYPE*
- *NAME*
- *LSTNM*
- *SNAME*
- *NATID*
- *CNTY*
- *NLTY*
- *CCAT*
- *DOB*
- *LANG*
- *EMAIL*
- *EXISTING*
- *PASSNO*
- *MOBNO*
- *LANDNO*

Financials3

- *INCTYPE*
- *CCY*
- *AMT*
- *FREQ*

Cusudf

- *NAME*
- *VALUE*

Facility

- *LINECD*
- *LINESER*
- *LIABID*
- *POOLCD*
- *CUSTID*
- *CUSTNM*
- *LIMAMT*
- *PURPOSE*
- *APPNO*
- *MAINLINE*
- *CCYRES*
- *LINENCCY*
- *REVLINE*
- *LINESTDT*
- *LINEEXPDT*
- *LSTNEWUTLDT*
- *INTREM*
- *LMTAMT*
- *COLLTAMT*
- *LIABBR*
- *BRN*
- *LMTAMTBASIS*
- *INTREQD*
- *DSPEFFLINEAMT*
- *Factenor*
  - *LINECD*
  - *LINESER*
  - *LIABID*
  - *TNRMNEMONIC*
  - *TENOR*
  - *LIMIT*
  - *UTILIZATION*
- *Pool*
  - *LIABID*
  - *POOLCD*
  - *POOLDESC*
  - *POOLCCY*
  - *POOLAMT*
  - *POOLUTL*

Crapp

- *CUSTNO*
- *BORROWPRF*
- *FINPER*
- *BORRMKTPOS*

- *RSKMIT*
- *RSKDEPTMIT*
- *RSKDEPASSES*
- *FACPROP*
- *APRFAC*
- *RECOM*
- *TERMANDCOND*

Cust-Acct

- *CUSTNO*
- *ACCLS*
- *ACCCY*
- *ACODE*
- *CCYTYPE*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

Requested1

APPNO
PRDCD
REQAMT
REM
TENORM
INTRATE
DPMNTAMT
PROMO
CCY
SEQNO

Requested2

- *APPNO*
- *PRDCD*
- *ITEMIZATION*
- *REQAMT*
- *COMMENT*

Loan2

- *LOANCCY*
- *LOANAMT*
- *TENURE*
- *RATE*
- *DPMT*
- *TAX*
- *VALDT*
- *MATDT*
- *NOOFINST*
- *FREQUNIT*

- *FREQ*
- *SPREAD*
- *EFFRATE*
- *CLACCNO*
- *Loan3*
  - *NO1*
  - *FREQ*
  - *UNIT*
  - *FRSTDUEDT*
  - *AMT*
  - *SCHTYP*
  - *COMPNM*
- *Loan4*
  - *SCHNO*
  - *DUEDT*
  - *AMTDUE*
  - *EMI_AMOUNT*
  - *AMORPRI*
  - *INTEREST_AMOUNT*
  - *CAPI*
  - *WAIVE*
  - *COMPNM*

Comments

- *APPNO*
- *PRDCD*
- *SEQUENCENUMBER*
- *COMMENT*
- *COMMBY*
- *COMMDT*

Udf

- *L1*
- *L2*
- *L3*
- *L4*
- *L5*
- *L6*
- *L7*
- *L8*
- *L9*
- *L10*
- *L11*
- *L12*
- *L13*
- *L14*

- *L15*
- *L16*
- *L17*
- *L18*
- *L19*
- *L20*
- *F1*
- *F2*
- *F3*
- *F4*
- *F5*
- *F6*
- *F7*
- *F8*
- *F9*
- *F10*
- *F11*
- *F12*
- *F13*
- *F14*
- *F15*
- *F16*
- *F17*
- *F18*
- *F19*
- *F20*
- *B1*
- *B2*
- *B3*
- *B4*
- *B5*
- *B6*

Chklst1

- *CHKLSTID*
- *CHKLSTDESC*
- *VERIFY*
- *COMMENT*

Custudf

- *NAME*
- *DESC*

Tradein

- *ASSETTYP*
- *ASSETSUBTYP*
- *MAKE*

MODEL
MANYR
BODY
ASSETIDNO
ASSETDESC
ASSETWHVL
ASSETBSVL
PAYAMT
ASSETADDON1
TOTVAL
ASSETVLDT
ASSETSOURCE
ASSETSUPP
ASSETEDI
Loanoffers
OFFID
RATE
NOOFINST
FREQUNIT
FREQ
RATECD
SPREAD
EFFRATE
CHECK
Crdratout
EXTAGEN
RECOMM
Crdratin
CUSTNO
GRD
SCR
RULEID
Crratin2
APPNO
CUSTNO
QUES
ANS
CAT
Bureau
CUSTID
BUREAU
RPTTYP
STAT
Chgs

EVENTCD

CCY

AMT

AMTSETT

SCHDUEDT

WAIV

COMPNM

Loandedupe

CCY

VALDT

MATDT

CUSTNO

LOAN_ACCNO

AMT

OUTSTAMT

RATE

Riskfactor

RISKFAC

DESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Applicationhead-Full

Attribute	Description
Name	Applicationhead-Full
Datatype	
Description	

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DATE

Attribute	Description	
Name	DATE	
Datatype	Date	
Description	Indicates Incorporation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHNL

Attribute	Description
Name	CHNL
Datatype	String
Description	Indicates Originating Channel of Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / NEWAPP,VFYAPP,UNDERW,UNAPPR,CHKDOC,FIVERI,FUNDED

TOP

INTERCD

Attribute	Description
Name	INTERCD
Datatype	String
Description	Indicates Intermediary Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

INTNAME

Attribute	Description	
Name	INTNAME	
Datatype	String	
Description	Indicates Intermediary Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTTYPE1

Attribute	Description	
Name	CUSTTYPE1	
Datatype	String	
Description	Indicates Customer Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates Currency Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

LEAD

Attribute	Description	
Name	LEAD	
Datatype	String	
Description	Indicates Lead Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CONT

Attribute	Description
Name	CONT
Datatype	String
Description	Indicates Contact Person
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PUR

Attribute	Description
Name	PUR
Datatype	String
Description	Indicates Loan Purpose
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

APPCAT

Attribute	Description
Name	APPCAT
Datatype	String
Description	Indicates Application Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ENQUIRY_ID

Attribute	Description
Name	ENQUIRY_ID
Datatype	String
Description	Indicates Enquiry Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

OFFAPPLNUM

Attribute	Description
Name	OFFAPPLNUM
Datatype	String
Description	Indicates Offline Application Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Customer1

Attribute	Description
Name	Customer1
Datatype	
Description	Indicates Customer Details
Attributes	Attribute: minOccurs — Description: 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NATID

Attribute	**Description**	
Name	NATID	
Datatype	String	
Description	Indicates National Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

LANG

Attribute	**Description**	
Name	LANG	
Datatype	String	
Description	Indicates Customer Language	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXISTING

Attribute	**Description**	
Name	EXISTING	
Datatype	String	
Description	Indicates whether Existing Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CTYPE

Attribute	**Description**
Name	CTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACLASS

Attribute	**Description**
Name	ACLASS
Datatype	String
Description	Indicates Account Class of Loan Settlement Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACCNO

Attribute	**Description**
Name	ACCNO
Datatype	String
Description	Indicates Settlement Account Number for the Loan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

SNAME

Attribute	**Description**
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCAT

Attribute	Description
Name	CCAT
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

LINE1

Attribute	Description
Name	LINE1
Datatype	String
Description	Indicates Residence Address Line 1

ORACLE

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LINE2

Attribute	**Description**	
Name	LINE2	
Datatype	String	
Description	Indicates Residence Address Line 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LINE3

Attribute	**Description**	
Name	LINE3	
Datatype	String	
Description	Indicates Residence Address Line 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DATE

Attribute	**Description**	
Name	DATE	
Datatype	Date	
Description	Indicates Incorporation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CAPITAL

Attribute	**Description**	
Name	CAPITAL	
Datatype	Number	
Description	Indicates Customer Business Capital	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	Indicates Net worth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BUSIDESC

Attribute	Description
Name	BUSIDESC
Datatype	String
Description	Indicates Customer Business Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INCNTY

Attribute	Description
Name	INCNTY
Datatype	String
Description	Indicates Incorporation Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RCNTY

Attribute	Description
Name	RCNTY
Datatype	String
Description	Indicates Residence Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYAMT

Attribute	Description
Name	CCYAMT
Datatype	String
Description	Indicates Currency in which Financials are Declared

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Customer3

Attribute	Description	
Name	Customer3	
Datatype		
Description	Indicates Director Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description	Indicates Email	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description	Indicates Customer Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DIRNAME

Attribute	Description	
Name	DIRNAME	
Datatype	String	
Description	Indicates Director Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LINE1

Attribute	Description
Name	LINE1
Datatype	String
Description	Indicates Residence Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LINE2

Attribute	Description
Name	LINE2
Datatype	String
Description	Indicates Residence Address Line 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LINE3

Attribute	Description
Name	LINE3
Datatype	String
Description	Indicates Residence Address Line 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LINE4

Attribute	Description
Name	LINE4
Datatype	String
Description	Indicates Mailing Address Line 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Permanent Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Permanent Address Line 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Permanent Address Line 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TEL

Attribute	Description
Name	TEL

Datatype	String
Description	Indicates Telephone Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TAXID

Attribute	Description
Name	TAXID
Datatype	String
Description	Indicates Tax Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Customer2

Attribute	Description
Name	Customer2
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDTYPE

Attribute	Description
Name	ADDTYPE
Datatype	String
Description	Indicates Address Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,R,T,O

TOP

MAILING

Attribute	Description
Name	MAILING
Datatype	String
Description	Indicates whether Mailing Address
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONNO

Attribute	Description
Name	CONNO
Datatype	Number
Description	Indicates Contact Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDLN1

Attribute	Description
Name	ADDLN1

Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Financials1

Attribute	**Description**
Name	Financials1
Datatype	
Description	Indicates Customer Financial Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FIXEDASSETS

Attribute	**Description**
Name	FIXEDASSETS
Datatype	Number
Description	Indicates Fixed Assets
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTANGASSETS

Attribute	**Description**
Name	INTANGASSETS
Datatype	Number
Description	Indicates Intangible Assets
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONCURRASSETS

Attribute	**Description**
Name	NONCURRASSETS
Datatype	Number
Description	Indicates Non Current Assets

Attributes	Attribute	Description
	minOccurs	0

TOP

SUBSIDYFRMGOV

Attribute	Description
Name	SUBSIDYFRMGOV
Datatype	Number
Description	Indicates Subsidy Received from Government
Attributes	Attribute: minOccurs; Description: 0

TOP

GENRESERVES

Attribute	Description
Name	GENRESERVES
Datatype	Number
Description	Indicates General Reserves
Attributes	Attribute: minOccurs; Description: 0

TOP

TERMLIAB

Attribute	Description
Name	TERMLIAB
Datatype	Number
Description	Indicates Term Liabilities
Attributes	Attribute: minOccurs; Description: 0

TOP

CURRLIAB

Attribute	Description
Name	CURRLIAB
Datatype	Number
Description	Indicates Current Liabilities
Attributes	Attribute: minOccurs; Description: 0

TOP

ISSUEDCAP

Attribute	Description
Name	ISSUEDCAP
Datatype	Number
Description	Indicates Issued Capital
Attributes	Attribute: minOccurs; Description: 0

TOP

PAIDUPCAP

Attribute	Description
Name	PAIDUPCAP
Datatype	Number
Description	Indicates Paid Up Capital
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRBALINPL

Attribute	Description
Name	CRBALINPL
Datatype	Number
Description	Indicates Credit Balance in Profit and Loss
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OPACT

Attribute	Description
Name	OPACT
Datatype	Number
Description	Indicates Operations Activities
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVACT

Attribute	Description
Name	INVACT
Datatype	Number
Description	Indicates Investing Activities
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINACT

Attribute	Description
Name	FINACT
Datatype	Number
Description	Indicates Financing Activities
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRASSETS

Attribute	Description
Name	CURRASSETS
Datatype	Number
Description	Indicates Current Assets
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collat1

Attribute	Description
Name	Collat1
Datatype	
Description	Indicates Collateral Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLCD

Attribute	Description
Name	COLLCD
Datatype	String
Description	Indicates Collateral Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLDESC

Attribute	**Description**
Name	COLLDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLCCY

Attribute	**Description**
Name	COLLCCY
Datatype	String
Description	Indicates Collateral Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLVL

Attribute	**Description**
Name	COLLVL
Datatype	Number
Description	Indicates Collateral Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLSTDT

Attribute	**Description**
Name	COLLSTDT
Datatype	Date
Description	Indicates Collateral Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLENDDT

Attribute	Description
Name	COLLENDDT
Datatype	Date
Description	Indicates Collateral End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	Indicates Collateral Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	String
Description	Indicates Collateral Haircut Margin
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,M,G

TOP

COLLREVDT

Attribute	Description
Name	COLLREVDT
Datatype	Date
Description	Indicates Collateral Revision Date

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLCHGDT

Attribute	Description
Name	COLLCHGDT
Datatype	String
Description	Indicates Collateral Charge Date
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,L,P,H,A

TOP

COLLREVLDT

Attribute	Description
Name	COLLREVLDT
Datatype	Date
Description	Indicates Collateral Revaluation Date
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLREVCHK

Attribute	Description
Name	COLLREVCHK
Datatype	String
Description	Indicates whether Collateral Revaluation is Required
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

NOMUNITVL

Attribute	Description
Name	NOMUNITVL
Datatype	Number
Description	Indicates Nominal Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPAMT

Attribute	Description
Name	CAPAMT
Datatype	Number
Description	Indicates Cap Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GUAID

Attribute	Description
Name	GUAID
Datatype	String
Description	Indicates Guarantor Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RATIN

Attribute	Description
Name	RATIN
Datatype	String
Description	Indicates Rating
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LNKPCTNO

Attribute	Description
Name	LNKPCTNO
Datatype	Number
Description	Indicates Linkage Percentage
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKAMT

Attribute	Description
Name	LNKAMT
Datatype	Number
Description	Indicates Linkage Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collat2

Attribute	Description
Name	Collat2
Datatype	
Description	Indicates Collateral Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date

Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMON

Attribute	**Description**
Name	STMON
Datatype	String
Description	Indicates Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REM

Attribute	**Description**
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVNM

Attribute	**Description**
Name	COVNM
Datatype	String
Description	Indicates Covenant Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	Indicates Revision Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MANDT

Attribute	Description
Name	MANDT
Datatype	Date
Description	Indicates whether it is Mandatory
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRCDAY

Attribute	Description
Name	GRCDAY
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	Indicates Notice Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Vehdetails

Attribute	Description
Name	Vehdetails
Datatype	
Description	Indicates Vehicle Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_IDNUM

Attribute	Description
Name	VEH_IDNUM
Datatype	String
Description	Indicates Vehicle Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_YEAR

Attribute	Description
Name	VEH_YEAR
Datatype	Number
Description	Indicates Vehicle Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_MAKE

Attribute	Description
Name	VEH_MAKE
Datatype	String
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_MODEL

Attribute	Description
Name	VEH_MODEL
Datatype	String
Description	Indicates Vehicle Model

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

VEH_BDYSTYLE

Attribute	Description	
Name	VEH_BDYSTYLE	
Datatype	String	
Description	Indicates Vehicle Body Style	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

VEH_USAGE

Attribute	Description	
Name	VEH_USAGE	
Datatype	String	
Description	Indicates Vehicle Usage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Financials2

Attribute	Description	
Name	Financials2	
Datatype		
Description	Indicates Customer Liability Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABTYP

Attribute	Description
Name	LIABTYP
Datatype	String
Description	Indicates Liability Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LO,LE,RE,OT

TOP

LIABSUB

Attribute	Description
Name	LIABSUB
Datatype	String
Description	Indicates Liability Sub Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABFREQ

Attribute	Description
Name	LIABFREQ
Datatype	String
Description	Indicates Liability Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

LAIBAMT

Attribute	Description
Name	LAIBAMT
Datatype	Number
Description	Indicates Liability Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

BAL

Attribute	Description
Name	BAL
Datatype	Number
Description	Indicates Liability Outstanding Balance
Attributes	Attribute: minOccurs, Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

LIABSTDT

Attribute	Description
Name	LIABSTDT
Datatype	Date
Description	Indicates Liability Start Date
Attributes	Attribute: minOccurs, Description: 0

TOP

LIABENDDT

Attribute	Description
Name	LIABENDDT
Datatype	Date
Description	Indicates Liability End Date
Attributes	Attribute: minOccurs, Description: 0

TOP

Finsummary

Attribute	Description
Name	Finsummary
Datatype	
Description	Indicates Asset Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONSTATINC

Attribute	Description
Name	MONSTATINC
Datatype	Number
Description	Indicates Monthly Stated Income
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTINC

Attribute	Description
Name	MONACTINC
Datatype	Number
Description	Indicates Monthly Actual Income
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONSTATDEBT

Attribute	Description
Name	MONSTATDEBT
Datatype	Number
Description	Indicates Monthly Stated Debt
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTDEBT

Attribute	Description
Name	MONACTDEBT
Datatype	Number
Description	Indicates Monthly Actual Debt
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRADE

Attribute	Description
Name	GRADE
Datatype	String
Description	Indicates Internal Final Grade
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SCORE

Attribute	Description
Name	SCORE
Datatype	Number
Description	Indicates Internal Credit Score
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ASSETWORTH

Attribute	Description
Name	ASSETWORTH
Datatype	Number
Description	Indicates Asset Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABWORTH

Attribute	Description
Name	LIABWORTH
Datatype	Number
Description	Indicates Total Liabilities
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTWOR

Attribute	Description
Name	TOTWOR
Datatype	Number
Description	Indicates Total Net worth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WHTPMT

Attribute	Description
Name	WHTPMT
Datatype	Number
Description	Indicates What if Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Finsummary2

Attribute	Description
Name	Finsummary2
Datatype	
Description	Indicates Consolidated Financial Summary Information
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RATNM

Attribute	Description
Name	RATNM
Datatype	String
Description	Indicates Ratio Name
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STATBF

Attribute	Description
Name	STATBF
Datatype	String
Description	Indicates Ratio based on Stated Financials After Accounting for Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STATAF

Attribute	Description
Name	STATAF
Datatype	String

Description	Indicates Ratio based on Stated Financials After Accounting for Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACTBF

Attribute	**Description**
Name	ACTBF
Datatype	String
Description	Indicates Ratio based on Actual Financials Before Accounting for Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACTAF

Attribute	**Description**
Name	ACTAF
Datatype	String
Description	Indicates Ratio based on Actual Financials After Accounting for Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Investi1

Attribute	**Description**
Name	Investi1
Datatype	
Description	Indicates Investigation Summary
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VERTYPE

Attribute	**Description**
Name	VERTYPE
Datatype	String
Description	Indicates Verification Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGENCY

Attribute	**Description**
Name	AGENCY
Datatype	String
Description	Indicates Investigating Agency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Investi2

Attribute	**Description**
Name	Investi2
Datatype	
Description	Indicates Investigation Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOKE

Attribute	**Description**
Name	SPOKE
Datatype	String
Description	Indicates who the Agency Contacted
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ATTEMPTS

Attribute	Description
Name	ATTEMPTS
Datatype	Number
Description	Indicates No of Attempts
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CALLDT

Attribute	Description
Name	CALLDT
Datatype	Date
Description	Indicates Called Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESULT

Attribute	Description
Name	RESULT
Datatype	String
Description	Indicates Investigation Result
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERMAT

Attribute	Description
Name	VERMAT
Datatype	String
Description	Indicates whether Verification Matched
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Custdedupe

Attribute	Description	
Name	Custdedupe	
Datatype		
Description	Indicates Possible Duplicate Customer Names	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CTYPE

Attribute	Description	
Name	CTYPE	
Datatype	String	
Description	Indicates Customer Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

LSTNM

Attribute	Description	
Name	LSTNM	
Datatype	String	
Description	Indicates Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNAME

Attribute	Description

Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NATID

Attribute	**Description**
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CNTY

Attribute	**Description**
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCAT

Attribute	**Description**
Name	CCAT
Datatype	String
Description	Indicates Customer Category

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	Indicates Customer Date of Birth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	Indicates Email
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EXISTING

Attribute	Description
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASSNO

Attribute	Description
Name	PASSNO
Datatype	String
Description	Indicates Customer Passport Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Customer Landline Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Financials3

Attribute	Description
Name	Financials3
Datatype	
Description	Indicates Customer Income Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INCTYPE

Attribute	Description
Name	INCTYPE
Datatype	String
Description	Indicates Income Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,R,B,O

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Cusudf

Attribute	**Description**
Name	Cusudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**

Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

Facility

Attribute	Description	
Name	Facility	
Datatype		
Description	Indicates Facility Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LINECD

Attribute	Description	
Name	LINECD	
Datatype	String	
Description	Indicates Line Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINESER

Attribute	Description	
Name	LINESER	
Datatype	Number	
Description	Indicates Line Serial Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description	Indicates Liability Id	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTNM

Attribute	Description
Name	CUSTNM
Datatype	String
Description	Indicates Customer Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LIMAMT

Attribute	Description
Name	LIMAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

PURPOSE

Attribute	Description
Name	PURPOSE
Datatype	String
Description	Indicates Purpose
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

MAINLINE

Attribute	Description
Name	MAINLINE
Datatype	String
Description	Indicates Main Line
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

CCYRES

Attribute	Description
Name	CCYRES
Datatype	String
Description	Indicates Currency Restriction
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LINENCCY

Attribute	Description
Name	LINENCCY

Datatype	String
Description	Indicates Line Currency
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVLINE

Attribute	**Description**
Name	REVLINE
Datatype	String
Description	Indicates whether Revolving Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINESTDT

Attribute	**Description**
Name	LINESTDT
Datatype	Date
Description	Indicates Line Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINEEXPDT

Attribute	**Description**
Name	LINEEXPDT
Datatype	Date
Description	Indicates Line Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LSTNEWUTLDT

Attribute	**Description**
Name	LSTNEWUTLDT
Datatype	Date
Description	Indicates Last New Utilization Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREM

Attribute	Description
Name	INTREM
Datatype	String
Description	Indicates Internal Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABBR

Attribute	Description
Name	LIABBR
Datatype	String
Description	Indicates Liability Branch Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LMTAMTBASIS

Attribute	**Description**
Name	LMTAMTBASIS
Datatype	String
Description	Indicates Limit Amount Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L,M

TOP

INTREQD

Attribute	**Description**
Name	INTREQD
Datatype	String
Description	Indicates whether Fee needs to be Collected
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DSPEFFLINEAMT

Attribute	**Description**
Name	DSPEFFLINEAMT
Datatype	Number
Description	Indicates Effective Line Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Factenor

Attribute	**Description**
Name	Factenor
Datatype	
Description	Indicates Facility Tenor
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINECD

Attribute	**Description**

Name	LINECD
Datatype	String
Description	Indicates Line Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINESER

Attribute	Description
Name	LINESER
Datatype	Number
Description	Indicates Line Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TNRMNEMONIC

Attribute	Description
Name	TNRMNEMONIC
Datatype	String
Description	Indicates Tenor Mnemonic
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT

Attribute	Description
Name	LIMIT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UTILIZATION

Attribute	Description
Name	UTILIZATION
Datatype	Number
Description	Indicates Utilization
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Pool

Attribute	Description
Name	Pool
Datatype	
Description	Indicates Pool Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

POOLDESC

Attribute	Description
Name	POOLDESC
Datatype	String
Description	Indicates Pool Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

POOLCCY

Attribute	Description
Name	POOLCCY
Datatype	String
Description	Indicates Pool Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

POOLAMT

Attribute	Description
Name	POOLAMT
Datatype	Number
Description	Indicates Pool Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

POOLUTL

Attribute	Description
Name	POOLUTL
Datatype	Number
Description	Indicates Pool Utilization
Attributes	Attribute: minOccurs — Description: 0

TOP

Crapp

Attribute	Description
Name	Crapp

Datatype	
Description	Indicates Credit Application Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BORROWPRF

Attribute	Description
Name	BORROWPRF
Datatype	String
Description	Indicates Borrower Profile
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FINPER

Attribute	Description
Name	FINPER
Datatype	String
Description	Indicates Financial Performance
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BORRMKTPOS

Attribute	Description
Name	BORRMKTPOS
Datatype	String
Description	Indicates Borrower Market Position
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RSKMIT

Attribute	Description	
Name	RSKMIT	
Datatype	String	
Description	Indicates Risk Mitigants	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RSKDEPTMIT

Attribute	Description	
Name	RSKDEPTMIT	
Datatype	String	
Description	Indicates Risk Department Mitigants	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RSKDEPASSES

Attribute	Description	
Name	RSKDEPASSES	
Datatype	String	
Description	Indicates Risk Department Assessment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACPROP

Attribute	Description	
Name	FACPROP	
Datatype	String	
Description	Indicates Facilities Proposed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

APRFAC

Attribute	Description
Name	APRFAC
Datatype	String
Description	Indicates Approved Facilities
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RECOM

Attribute	Description
Name	RECOM
Datatype	String
Description	Indicates Recommendation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TERMANDCOND

Attribute	Description
Name	TERMANDCOND
Datatype	String
Description	Indicates Terms and Conditions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cust-Acct

Attribute	Description
Name	Cust-Acct
Datatype	
Description	Indicates Customer Account Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Account Class of Customer Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates Customer Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACODE

Attribute	Description
Name	ACODE
Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCYTYPE

Attribute	Description
Name	CCYTYPE
Datatype	String
Description	Indicates Currency Type

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 150
	minLength / 0

TOP

Requested1

Attribute	Description
Name	Requested1
Datatype	
Description	Indicates Overall Loan Details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

REQAMT

Attribute	Description
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TENORM

Attribute	Description
Name	TENORM

Datatype	Number
Description	Indicates Loan Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROMO

Attribute	Description
Name	PROMO
Datatype	String
Description	Indicates Promotion Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates Request Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Requested2

Attribute	Description
Name	Requested2
Datatype	
Description	Indicates Individual Request Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ITEMIZATION

Attribute	Description
Name	ITEMIZATION
Datatype	String
Description	Indicates Itemization Details

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REQAMT

Attribute	Description
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loan2

Attribute	Description
Name	Loan2
Datatype	
Description	Indicates Individual Loan Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANCCY

Attribute	Description
Name	LOANCCY
Datatype	String
Description	Indicates Loan Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	Indicates Loan Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TENURE

Attribute	Description
Name	TENURE
Datatype	Number
Description	Indicates Loan Tenure
Attributes	Attribute: minOccurs, Description: 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

DPMT

Attribute	Description
Name	DPMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TAX

Attribute	Description
Name	TAX
Datatype	Number
Description	Indicates Tax Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

VALDT

Attribute	Description

Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	**Description**
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFINST

Attribute	**Description**
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREQUNIT

Attribute	**Description**
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	Indicates CL Account Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Loan3

Attribute	Description
Name	Loan3
Datatype	
Description	Indicates Loan Schedule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NO1

Attribute	Description
Name	NO1

Datatype	Number
Description	Indicates No of Schedules
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHTYP

Attribute	Description
Name	SCHTYP

Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / P,D,R

TOP

COMPNM

Attribute	**Description**
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loan4

Attribute	**Description**
Name	Loan4
Datatype	
Description	Indicates Exploded Schedule Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHNO

Attribute	**Description**
Name	SCHNO
Datatype	Number
Description	Indicates Schedule No
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDT

Attribute	**Description**
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EMI_AMOUNT

Attribute	Description
Name	EMI_AMOUNT
Datatype	Number
Description	Indicates EMI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMORPRI

Attribute	Description
Name	AMORPRI
Datatype	Number
Description	Indicates Amortized Principal
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTEREST_AMOUNT

Attribute	Description
Name	INTEREST_AMOUNT
Datatype	Number
Description	Indicates Interest Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPI

Attribute	Description
Name	CAPI
Datatype	String
Description	Indicates Capitalized Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

WAIVE

Attribute	Description
Name	WAIVE
Datatype	String
Description	Indicates whether Schedule is Waived
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Comments

Attribute	Description
Name	Comments
Datatype	
Description	Indicates Comment Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRDCD

Attribute	Description

Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SEQUENCENUMBER

Attribute	**Description**
Name	SEQUENCENUMBER
Datatype	String
Description	Indicates Comment Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMENT

Attribute	**Description**
Name	COMMENT
Datatype	String
Description	Indicates Comment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMBY

Attribute	**Description**
Name	COMMBY
Datatype	String
Description	Indicates User who input Comment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMDT

Attribute	**Description**
Name	COMMDT
Datatype	Date
Description	Indicates Comment Date

Attributes	Attribute	Description
	minOccurs	0

TOP

Udf

Attribute	Description
Name	Udf
Datatype	
Description	Indicates UDF Details
Attributes	Attribute: minOccurs — Description: 0

TOP

L1

Attribute	Description
Name	L1
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L2

Attribute	Description
Name	L2
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L3

Attribute	Description
Name	L3
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L4

Attribute	Description
Name	L4
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L5

Attribute	Description
Name	L5
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L6

Attribute	Description
Name	L6
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L7

Attribute	Description
Name	L7
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L8

Attribute	Description
Name	L8

Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L9

Attribute	Description
Name	L9
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L10

Attribute	Description
Name	L10
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L11

Attribute	Description
Name	L11
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L12

Attribute	Description
Name	L12
Datatype	String
Description	Indicates User Defined Field

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L13

Attribute	**Description**	
Name	L13	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L14

Attribute	**Description**	
Name	L14	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L15

Attribute	**Description**	
Name	L15	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L16

Attribute	**Description**	
Name	L16	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

L17

Attribute	Description
Name	L17
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L18

Attribute	Description
Name	L18
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L19

Attribute	Description
Name	L19
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L20

Attribute	Description
Name	L20
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F1

Attribute	Description
Name	F1
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F2

Attribute	Description
Name	F2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F3

Attribute	Description
Name	F3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F4

Attribute	Description
Name	F4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F5

Attribute	Description
Name	F5
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F6

Attribute	Description
Name	F6
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F7

Attribute	Description
Name	F7
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F8

Attribute	Description
Name	F8
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F9

Attribute	Description
Name	F9

Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F10

Attribute	Description
Name	F10
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F11

Attribute	Description
Name	F11
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F12

Attribute	Description
Name	F12
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F13

Attribute	Description
Name	F13
Datatype	String
Description	Indicates User Defined Field

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F14

Attribute	**Description**	
Name	F14	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F15

Attribute	**Description**	
Name	F15	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F16

Attribute	**Description**	
Name	F16	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F17

Attribute	**Description**	
Name	F17	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

F18

Attribute	Description
Name	F18
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F19

Attribute	Description
Name	F19
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F20

Attribute	Description
Name	F20
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

B1

Attribute	Description
Name	B1
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

B2

Attribute	Description
Name	B2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B3

Attribute	Description
Name	B3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B4

Attribute	Description
Name	B4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B5

Attribute	Description
Name	B5
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B6

Attribute	Description
Name	B6
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Chklst1

Attribute	Description
Name	Chklst1
Datatype	
Description	Indicates Checklist Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHKLSTID

Attribute	Description
Name	CHKLSTID
Datatype	String
Description	Indicates Checklist Id
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKLSTDESC

Attribute	Description
Name	CHKLSTDESC
Datatype	String
Description	Indicates Checklist Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

VERIFY

Attribute	Description
Name	VERIFY
Datatype	String

Description	Indicates Verified By
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMMENT

Attribute	**Description**
Name	COMMENT
Datatype	String
Description	Indicates Comment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custudf

Attribute	**Description**
Name	Custudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tradein

Attribute	Description
Name	Tradein
Datatype	
Description	Indicates Trade In Asset Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ASSETTYP

Attribute	Description
Name	ASSETTYP
Datatype	String
Description	Indicates Asset Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETSUBTYP

Attribute	Description
Name	ASSETSUBTYP
Datatype	String
Description	Indicates Asset Sub Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKE

Attribute	Description
Name	MAKE
Datatype	Number
Description	Indicates Asset Make
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODEL

Attribute	Description
Name	MODEL
Datatype	String
Description	Indicates Asset Model

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MANYR

Attribute	Description
Name	MANYR
Datatype	Number
Description	Indicates Manufacture Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BODY

Attribute	Description
Name	BODY
Datatype	String
Description	Indicates Asset Body
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ASSETIDNO

Attribute	Description
Name	ASSETIDNO
Datatype	String
Description	Indicates Asset Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ASSETDESC

Attribute	Description
Name	ASSETDESC
Datatype	String
Description	Indicates Asset Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ASSETWHVL

Attribute	Description
Name	ASSETWHVL
Datatype	Number
Description	Indicates Wholesale Value
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETBSVL

Attribute	Description
Name	ASSETBSVL
Datatype	Number
Description	Indicates Asset Base Value
Attributes	Attribute: minOccurs, Description: 0

TOP

PAYAMT

Attribute	Description
Name	PAYAMT
Datatype	Number
Description	Indicates Asset Payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETADDON1

Attribute	Description
Name	ASSETADDON1
Datatype	Number
Description	Indicates Asset Add-on Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TOTVAL

Attribute	Description
Name	TOTVAL
Datatype	Number
Description	Indicates Asset Total Value
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETVLDT

Attribute	Description
Name	ASSETVLDT
Datatype	Date
Description	Indicates Asset Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ASSETSOURCE

Attribute	Description
Name	ASSETSOURCE
Datatype	String
Description	Indicates Asset Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETSUPP

Attribute	Description
Name	ASSETSUPP
Datatype	String
Description	Indicates Asset Supplier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETEDI

Attribute	Description
Name	ASSETEDI
Datatype	String
Description	Indicates Asset Edition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Loanoffers

Attribute	Description
Name	Loanoffers
Datatype	

Description	Indicates Loan Offer Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OFFID

Attribute	**Description**
Name	OFFID
Datatype	String
Description	Indicates Offer Id
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFINST

Attribute	**Description**
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREQUNIT

Attribute	**Description**
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Interest Rate Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECK

Attribute	Description
Name	CHECK

Datatype	String
Description	Indicates whether Offer Needs to be Applied
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Crdratout

Attribute	Description
Name	Crdratout
Datatype	
Description	Indicates External Credit Rating Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EXTAGEN

Attribute	Description
Name	EXTAGEN
Datatype	String
Description	Indicates External Credit Rating Agency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECOMM

Attribute	Description
Name	RECOMM
Datatype	String
Description	Indicates External Credit Rating Agency Final Recommendation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

Crdratin

Attribute	Description
Name	Crdratin
Datatype	
Description	Indicates Internal Credit Rating Details of Loan Application
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

GRD

Attribute	Description
Name	GRD
Datatype	String
Description	Indicates Final Internal Credit Rating Grade
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SCR

Attribute	Description
Name	SCR
Datatype	Number
Description	Indicates Internal Credit Rating Score
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	Indicates Internal Credit Rating Rule Id used
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Crratin2

Attribute	Description
Name	Crratin2

Datatype	
Description	Indicates Internal Credit Rating Details by Customer
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QUES

Attribute	**Description**
Name	QUES
Datatype	String
Description	Indicates Credit Rating Question
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ANS

Attribute	**Description**
Name	ANS
Datatype	String
Description	Indicates Answer to Credit Rating Question
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CAT

Attribute	**Description**
Name	CAT
Datatype	String
Description	Indicates Credit Rating Question Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Bureau

Attribute	**Description**
Name	Bureau
Datatype	
Description	Indicates Credit Bureau Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTID

Attribute	**Description**
Name	CUSTID
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BUREAU

Attribute	**Description**
Name	BUREAU
Datatype	String
Description	Indicates Credit Bureau
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RPTTYP

Attribute	Description
Name	RPTTYP
Datatype	String
Description	Indicates Bureau Report Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / NEWAPP,VFYAPP,UNDERW,UNAPPR,CHKDOC,FIVERI,FUNDED

TOP

Chgs

Attribute	Description
Name	Chgs
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Charge Collection Event
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTSETT

Attribute	Description
Name	AMTSETT
Datatype	Number
Description	Indicates Charge Amount Settled
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHDUEDT

Attribute	Description
Name	SCHDUEDT
Datatype	Date
Description	Indicates Charge Due Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

WAIV

Attribute	Description
Name	WAIV
Datatype	String
Description	Indicates whether Charge is Waived
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loandedupe

Attribute	Description
Name	Loandedupe
Datatype	
Description	Indicates Other Loan Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	Indicates Loan Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	Indicates Outstanding Loan Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE

Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Riskfactor

Attribute	Description
Name	Riskfactor
Datatype	
Description	Indicates Risk Factor Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RISKFAC

Attribute	Description
Name	RISKFAC
Datatype	String
Description	Indicates Risk Factor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

2.2.2.OR-CreateSaveCLAppEntry-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Applicationhead-IO*
    - *APPNO*
    - *DATE*
    - *PRDCD*
    - *CHNL*
    - *INTERCD*
    - *INTNAME*
    - *CUSTTYPE1*
    - *CCY*
    - *LEAD*
    - *CONT*
    - *PUR*
    - *USERREFNO*
    - *APPCAT*
    - *OFFAPPLNUM*
    - *Customer1*
      - *APPNO*
      - *CUSTNO*
      - *NATID*

LANG
EXISTING
CCY
CTYPE
ACLASS
ACCNO
SNAME
CNTY
NLTY
CCAT
NAME
LINE1
LINE2
DATE
CAPITAL
NETWORTH
BUSIDESC
INCNTY
RCNTY
CCYAMT
Customer3
- *EMAIL*
- *CUSTNO*
- *DIRNAME*
- *ADDR2*
- *ADDR3*
- *CNTY*

Customer2
- *APPNO*
- *CUSTNO*
- *ADDTYPE*
- *MAILING*
- *CONNO*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ZIP*
- *CNTY*

Financials1
- *CUSTNO*
- *FIXEDASSETS*
- *INTANGASSETS*
- *NONCURRASSETS*
- *SUBSIDYFRMGOV*

GENRESERVES
TERMLIAB
CURRLIAB
ISSUEDCAP
PAIDUPCAP
CRBALINPL
OPACT
INVACT
FINACT
CURRASSETS
Collat1
APPNO
CUSTNO
COLLCD
COLLDESC
COLLCCY
COLLVL
COLLSTDT
COLLENDDT
COLLCAT
COLLHAIR
COLLTYPE
COLLREVDT
COLLCHGDT
COLLREVLDT
COLLREVCHK
SECUID
NOMUNITVL
CAPAMT
GUAID
RATIN
LNKPCTNO
LNKAMT
Collat2
APPNO
CUSTNO
DUEDT
STMON
REM
COVNM
DESC
REVDT
MANDT
GRCDAY

NOTDAY

FREQ

Vehdetails

VEH_IDNUM

VEH_YEAR

VEH_MAKE

VEH_MODEL

VEH_BDYSTYLE

VEH_USAGE

Financials2

APPNO

CUSTNO

LIABTYP

LIABSUB

LIABFREQ

LAIBAMT

BAL

REM

LIABSTDT

LIABENDDT

Finsummary

MONACTINC

MONACTDEBT

GRADE

WHTPMT

Finsummary2

Investi1

CUSTNO

VERTYPE

AGENCY

Custdedupe

CTYPE

NAME

LSTNM

SNAME

NATID

CNTY

NLTY

CCAT

DOB

LANG

EMAIL

EXISTING

PASSNO

MOBNO
LANDNO
Financials3
INCTYPE
CCY
AMT
FREQ
Cusudf
NAME
VALUE
Facility
LINECD
LINESER
LIABID
POOLCD
CUSTID
CUSTNM
LIMAMT
PURPOSE
APPNO
MAINLINE
CCYRES
LINENCCY
REVLINE
LINESTDT
LINEEXPDT
LSTNEWUTLDT
INTREM
LMTAMT
COLLTAMT
LIABBR
BRN
LMTAMTBASIS
INTREQD
DSPEFFLINEAMT
Factenor
LINECD
LINESER
LIABID
TNRMNEMONIC
TENOR
LIMIT
UTILIZATION
Pool

- *LIABID*
- *POOLCD*
- *POOLCCY*
- *POOLAMT*
- *POOLUTL*

Crapp

- *CUSTNO*
- *BORROWPRF*
- *FINPER*
- *BORRMKTPOS*
- *RSKMIT*
- *RSKDEPTMIT*
- *RSKDEPASSES*
- *FACPROP*
- *APRFAC*
- *RECOM*
- *TERMANDCOND*

Cust-Acct

- *CUSTNO*
- *ACCLS*
- *ACCCY*
- *ACODE*
- *CCYTYPE*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

Requested1

- *APPNO*
- *PRDCD*
- *REQAMT*
- *REM*
- *TENORM*
- *INTRATE*
- *DPMNTAMT*
- *PROMO*
- *CCY*
- *SEQNO*

Requested2

- *APPNO*
- *PRDCD*
- *ITEMIZATION*
- *REQAMT*

Loan2

- *LOANCCY*

- *LOANAMT*
- *TENURE*
- *RATE*
- *DPMT*
- *TAX*
- *VALDT*
- *MATDT*
- *NOOFINST*
- *FREQUNIT*
- *FREQ*
- *SPREAD*
- *EFFRATE*
- *CLACCNO*
- *Loan3*
  - *NO1*
  - *FREQ*
  - *UNIT*
  - *FRSTDUEDT*
  - *AMT*
  - *SCHTYP*
  - *COMPNM*
- *Loan4*
  - *SCHNO*
  - *DUEDT*
  - *AMTDUE*
  - *EMI_AMOUNT*
  - *AMORPRI*
  - *INTEREST_AMOUNT*
  - *CAPI*
  - *WAIVE*
  - *COMPNM*

Comments

- *APPNO*
- *PRDCD*
- *SEQUENCENUMBER*
- *COMMENT*
- *COMMBY*
- *COMMDT*

Udf

- *B1*
- *B2*
- *B3*
- *B4*
- *B5*

- *B6*
- *Chklst1*
  - *CHKLSTID*
  - *CHKLSTDESC*
  - *VERIFY*
- *Custudf*
  - *NAME*
- *Tradein*
  - *ASSETTYP*
  - *ASSETWHVL*
  - *ASSETBSVL*
  - *PAYAMT*
  - *ASSETADDON1*
  - *TOTVAL*
- *Loanoffers*
  - *OFFID*
  - *RATE*
  - *NOOFINST*
  - *FREQUNIT*
  - *FREQ*
  - *RATECD*
  - *SPREAD*
  - *EFFRATE*
  - *CHECK*
- *Crdratout*
  - *EXTAGEN*
  - *RECOMM*
- *Crdratin*
  - *CUSTNO*
  - *APPNO*
  - *RULEID*
  - *Crratin2*
    - *APPNO*
    - *CUSTNO*
    - *QUES*
    - *ANS*
    - *CAT*
- *Bureau*
  - *CUSTID*
  - *BUREAU*
  - *RPTTYP*
  - *STAT*
- *Chgs*
  - *EVENTCD*

CCY

AMT

AMTSETT

SCHDUEDT

WAIV

COMPNM

Loandedupe

CCY

VALDT

MATDT

CUSTNO

LOAN_ACCNO

AMT

OUTSTAMT

RATE

Riskfactor

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Applicationhead-IO

Attribute	Description
Name	Applicationhead-IO
Datatype	
Description	

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DATE

Attribute	Description	
Name	DATE	
Datatype	Date	
Description	Indicates Incorporation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHNL

Attribute	Description
Name	CHNL
Datatype	String
Description	Indicates Originating Channel of Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INTERCD

Attribute	Description
Name	INTERCD
Datatype	String
Description	Indicates Intermediary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTNAME

Attribute	Description
Name	INTNAME
Datatype	String
Description	Indicates Intermediary Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTTYPE1

Attribute	Description
Name	CUSTTYPE1
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CCY

Attribute	Description

Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LEAD

Attribute	**Description**
Name	LEAD
Datatype	String
Description	Indicates Lead Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONT

Attribute	**Description**
Name	CONT
Datatype	String
Description	Indicates Contact Person
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PUR

Attribute	**Description**
Name	PUR
Datatype	String
Description	Indicates Loan Purpose
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

USERREFNO

Attribute	**Description**
Name	USERREFNO
Datatype	String
Description	Indicates User Reference Number

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

APPCAT

Attribute	**Description**
Name	APPCAT
Datatype	String
Description	Indicates Application Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OFFAPPLNUM

Attribute	**Description**
Name	OFFAPPLNUM
Datatype	String
Description	Indicates Offline Application Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Customer1

Attribute	**Description**
Name	Customer1
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NATID

Attribute	Description
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXISTING

Attribute	Description
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ACLASS

Attribute	Description
Name	ACLASS
Datatype	String
Description	Indicates Account Class of Loan Settlement Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	Indicates Settlement Account Number for the Loan
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 22

TOP

SNAME

Attribute	Description
Name	SNAME

Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CNTY

Attribute	**Description**
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCAT

Attribute	**Description**
Name	CCAT
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

LINE1

Attribute	Description
Name	LINE1
Datatype	String
Description	Indicates Residence Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LINE2

Attribute	Description
Name	LINE2
Datatype	String
Description	Indicates Residence Address Line 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	Indicates Incorporation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPITAL

Attribute	Description
Name	CAPITAL
Datatype	Number
Description	Indicates Customer Business Capital
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	Indicates Net worth

Attributes	Attribute	Description
	minOccurs	0

TOP

BUSIDESC

Attribute	Description
Name	BUSIDESC
Datatype	String
Description	Indicates Customer Business Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

INCNTY

Attribute	Description
Name	INCNTY
Datatype	String
Description	Indicates Incorporation Country
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RCNTY

Attribute	Description
Name	RCNTY
Datatype	String
Description	Indicates Residence Country
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CCYAMT

Attribute	Description
Name	CCYAMT
Datatype	String
Description	Indicates Currency in which Financials are Declared
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

Customer3

Attribute	Description
Name	Customer3
Datatype	
Description	Indicates Director Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	Indicates Email
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	Indicates Director Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDR2

Attribute	Description

Name	ADDR2
Datatype	String
Description	Indicates Permanent Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDR3

Attribute	**Description**
Name	ADDR3
Datatype	String
Description	Indicates Permanent Address Line 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	**Description**
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customer2

Attribute	**Description**
Name	Customer2
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDTYPE

Attribute	**Description**
Name	ADDTYPE
Datatype	String
Description	Indicates Address Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,T,O

TOP

MAILING

Attribute	**Description**
Name	MAILING
Datatype	String
Description	Indicates whether Mailing Address
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONNO

Attribute	**Description**
Name	CONNO
Datatype	Number
Description	Indicates Contact Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Financials1

Attribute	Description	
Name	Financials1	
Datatype		
Description	Indicates Customer Financial Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description	Indicates Customer Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FIXEDASSETS

Attribute	Description	
Name	FIXEDASSETS	
Datatype	Number	
Description	Indicates Fixed Assets	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTANGASSETS

Attribute	Description	
Name	INTANGASSETS	
Datatype	Number	
Description	Indicates Intangible Assets	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NONCURRASSETS

Attribute	Description
Name	NONCURRASSETS

Datatype	Number
Description	Indicates Non Current Assets
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBSIDYFRMGOV

Attribute	Description
Name	SUBSIDYFRMGOV
Datatype	Number
Description	Indicates Subsidy Received from Government
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENRESERVES

Attribute	Description
Name	GENRESERVES
Datatype	Number
Description	Indicates General Reserves
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TERMLIAB

Attribute	Description
Name	TERMLIAB
Datatype	Number
Description	Indicates Term Liabilities
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRLIAB

Attribute	Description
Name	CURRLIAB
Datatype	Number
Description	Indicates Current Liabilities
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSUEDCAP

Attribute	Description
Name	ISSUEDCAP
Datatype	Number
Description	Indicates Issued Capital

Attributes	Attribute	Description
	minOccurs	0

TOP

PAIDUPCAP

Attribute	Description
Name	PAIDUPCAP
Datatype	Number
Description	Indicates Paid Up Capital
Attributes	Attribute: minOccurs — Description: 0

TOP

CRBALINPL

Attribute	Description
Name	CRBALINPL
Datatype	Number
Description	Indicates Credit Balance in Profit and Loss
Attributes	Attribute: minOccurs — Description: 0

TOP

OPACT

Attribute	Description
Name	OPACT
Datatype	Number
Description	Indicates Operations Activities
Attributes	Attribute: minOccurs — Description: 0

TOP

INVACT

Attribute	Description
Name	INVACT
Datatype	Number
Description	Indicates Investing Activities
Attributes	Attribute: minOccurs — Description: 0

TOP

FINACT

Attribute	Description
Name	FINACT
Datatype	Number
Description	Indicates Financing Activities
Attributes	Attribute: minOccurs — Description: 0

TOP

CURRASSETS

Attribute	Description
Name	CURRASSETS
Datatype	Number
Description	Indicates Current Assets
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collat1

Attribute	Description
Name	Collat1
Datatype	
Description	Indicates Collateral Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLCD

Attribute	Description
Name	COLLCD
Datatype	String

Description	Indicates Collateral Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLDESC

Attribute	**Description**
Name	COLLDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLCCY

Attribute	**Description**
Name	COLLCCY
Datatype	String
Description	Indicates Collateral Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLVL

Attribute	**Description**
Name	COLLVL
Datatype	Number
Description	Indicates Collateral Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLSTDT

Attribute	**Description**
Name	COLLSTDT
Datatype	Date
Description	Indicates Collateral Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLENDDT

Attribute	Description
Name	COLLENDDT
Datatype	Date
Description	Indicates Collateral End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	Indicates Collateral Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	String
Description	Indicates Collateral Haircut Margin
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,M,G

TOP

COLLREVDT

Attribute	Description
Name	COLLREVDT
Datatype	Date

Description	Indicates Collateral Revision Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCHGDT

Attribute	Description
Name	COLLCHGDT
Datatype	String
Description	Indicates Collateral Charge Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,P,H,A

TOP

COLLREVLDT

Attribute	Description
Name	COLLREVLDT
Datatype	Date
Description	Indicates Collateral Revaluation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLREVCHK

Attribute	Description
Name	COLLREVCHK
Datatype	String
Description	Indicates whether Collateral Revaluation is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NOMUNITVL

Attribute	Description
Name	NOMUNITVL
Datatype	Number
Description	Indicates Nominal Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPAMT

Attribute	Description
Name	CAPAMT
Datatype	Number
Description	Indicates Cap Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GUAID

Attribute	Description
Name	GUAID
Datatype	String
Description	Indicates Guarantor Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RATIN

Attribute	Description
Name	RATIN
Datatype	String
Description	Indicates Rating
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LNKPCTNO

Attribute	Description
Name	LNKPCTNO
Datatype	Number
Description	Indicates Linkage Percentage

Attributes	Attribute	Description
	minOccurs	0

TOP

LNKAMT

Attribute	Description
Name	LNKAMT
Datatype	Number
Description	Indicates Linkage Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Collat2

Attribute	Description
Name	Collat2
Datatype	
Description	Indicates Collateral Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

DUEDT

Attribute	Description

Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STMON

Attribute	**Description**
Name	STMON
Datatype	String
Description	Indicates Start Month
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REM

Attribute	**Description**
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVNM

Attribute	**Description**
Name	COVNM
Datatype	String
Description	Indicates Covenant Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	Indicates Revision Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANDT

Attribute	Description
Name	MANDT
Datatype	Date
Description	Indicates whether it is Mandatory
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAY

Attribute	Description
Name	GRCDAY
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Vehdetails

Attribute	Description
Name	Vehdetails
Datatype	
Description	Indicates Vehicle Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_IDNUM

Attribute	Description
Name	VEH_IDNUM
Datatype	String
Description	Indicates Vehicle Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_YEAR

Attribute	Description
Name	VEH_YEAR
Datatype	Number
Description	Indicates Vehicle Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_MAKE

Attribute	Description
Name	VEH_MAKE
Datatype	String
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_MODEL

Attribute	Description
Name	VEH_MODEL
Datatype	String
Description	Indicates Vehicle Model

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

VEH_BDYSTYLE

Attribute	Description
Name	VEH_BDYSTYLE
Datatype	String
Description	Indicates Vehicle Body Style
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_USAGE

Attribute	Description
Name	VEH_USAGE
Datatype	String
Description	Indicates Vehicle Usage
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Financials2

Attribute	Description
Name	Financials2
Datatype	
Description	Indicates Customer Liability Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABTYP

Attribute	Description
Name	LIABTYP
Datatype	String
Description	Indicates Liability Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LO,LE,RE,OT

TOP

LIABSUB

Attribute	Description
Name	LIABSUB
Datatype	String
Description	Indicates Liability Sub Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABFREQ

Attribute	Description
Name	LIABFREQ
Datatype	String
Description	Indicates Liability Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

LAIBAMT

Attribute	Description
Name	LAIBAMT
Datatype	Number
Description	Indicates Liability Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

BAL

Attribute	Description
Name	BAL
Datatype	Number
Description	Indicates Liability Outstanding Balance
Attributes	Attribute: minOccurs, Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

LIABSTDT

Attribute	Description
Name	LIABSTDT
Datatype	Date
Description	Indicates Liability Start Date
Attributes	Attribute: minOccurs, Description: 0

TOP

LIABENDDT

Attribute	Description
Name	LIABENDDT
Datatype	Date
Description	Indicates Liability End Date
Attributes	Attribute: minOccurs, Description: 0

TOP

Finsummary

Attribute	Description
Name	Finsummary
Datatype	
Description	Indicates Asset Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTINC

Attribute	Description
Name	MONACTINC
Datatype	Number
Description	Indicates Monthly Actual Income
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTDEBT

Attribute	Description
Name	MONACTDEBT
Datatype	Number
Description	Indicates Monthly Actual Debt
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRADE

Attribute	Description
Name	GRADE
Datatype	String
Description	Indicates Internal Final Grade
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

WHTPMT

Attribute	Description
Name	WHTPMT
Datatype	Number
Description	Indicates What if Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Finsummary2

Attribute	Description
Name	Finsummary2
Datatype	
Description	Indicates Consolidated Financial Summary Information
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Investi1

Attribute	Description
Name	Investi1
Datatype	
Description	Indicates Investigation Summary
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VERTYPE

Attribute	Description
Name	VERTYPE
Datatype	String
Description	Indicates Verification Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGENCY

Attribute	Description
Name	AGENCY

Datatype	String
Description	Indicates Investigating Agency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custdedupe

Attribute	Description
Name	Custdedupe
Datatype	
Description	Indicates Possible Duplicate Customer Names
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

LSTNM

Attribute	Description
Name	LSTNM
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NATID

Attribute	Description
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCAT

Attribute	Description

Name	CCAT
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DOB

Attribute	**Description**
Name	DOB
Datatype	Date
Description	Indicates Customer Date of Birth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANG

Attribute	**Description**
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	Indicates Email
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EXISTING

Attribute	**Description**
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PASSNO

Attribute	Description	
Name	PASSNO	
Datatype	String	
Description	Indicates Customer Passport Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MOBNO

Attribute	Description	
Name	MOBNO	
Datatype	Number	
Description	Indicates Customer Mobile Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LANDNO

Attribute	Description	
Name	LANDNO	
Datatype	Number	
Description	Indicates Customer Landline Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Financials3

Attribute	Description	
Name	Financials3	
Datatype		
Description	Indicates Customer Income Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INCTYPE

Attribute	Description
Name	INCTYPE
Datatype	String

Description	Indicates Income Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,R,B,O

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Cusudf

Attribute	**Description**
Name	Cusudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

Facility

Attribute	Description	
Name	Facility	
Datatype		
Description	Indicates Facility Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LINECD

Attribute	Description	
Name	LINECD	
Datatype	String	
Description	Indicates Line Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINESER

Attribute	Description	
Name	LINESER	
Datatype	Number	
Description	Indicates Line Serial Number	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNM

Attribute	Description
Name	CUSTNM
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LIMAMT

Attribute	Description
Name	LIMAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PURPOSE

Attribute	Description
Name	PURPOSE
Datatype	String
Description	Indicates Purpose
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAINLINE

Attribute	Description
Name	MAINLINE
Datatype	String
Description	Indicates Main Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CCYRES

Attribute	Description
Name	CCYRES
Datatype	String
Description	Indicates Currency Restriction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINENCCY

Attribute	Description
Name	LINENCCY
Datatype	String
Description	Indicates Line Currency
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

REVLINE

Attribute	Description
Name	REVLINE
Datatype	String
Description	Indicates whether Revolving Line
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LINESTDT

Attribute	Description
Name	LINESTDT
Datatype	Date
Description	Indicates Line Start Date
Attributes	Attribute: minOccurs — Description: 0

TOP

LINEEXPDT

Attribute	Description
Name	LINEEXPDT
Datatype	Date
Description	Indicates Line Expiry Date
Attributes	Attribute: minOccurs — Description: 0

TOP

LSTNEWUTLDT

Attribute	Description
Name	LSTNEWUTLDT
Datatype	Date
Description	Indicates Last New Utilization Date
Attributes	Attribute: minOccurs — Description: 0

TOP

INTREM

Attribute	Description
Name	INTREM
Datatype	String
Description	Indicates Internal Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABBR

Attribute	Description
Name	LIABBR
Datatype	String
Description	Indicates Liability Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LMTAMTBASIS

Attribute	Description	
Name	LMTAMTBASIS	
Datatype	String	
Description	Indicates Limit Amount Basis	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,M

TOP

INTREQD

Attribute	Description	
Name	INTREQD	
Datatype	String	
Description	Indicates whether Fee needs to be Collected	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DSPEFFLINEAMT

Attribute	Description	
Name	DSPEFFLINEAMT	
Datatype	Number	
Description	Indicates Effective Line Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Factenor

Attribute	Description	
Name	Factenor	
Datatype		
Description	Indicates Facility Tenor	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LINECD

Attribute	Description
Name	LINECD
Datatype	String
Description	Indicates Line Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINESER

Attribute	Description
Name	LINESER
Datatype	Number
Description	Indicates Line Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TNRMNEMONIC

Attribute	Description
Name	TNRMNEMONIC
Datatype	String
Description	Indicates Tenor Mnemonic
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number

Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIMIT

Attribute	Description
Name	LIMIT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UTILIZATION

Attribute	Description
Name	UTILIZATION
Datatype	Number
Description	Indicates Utilization
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Pool

Attribute	Description
Name	Pool
Datatype	
Description	Indicates Pool Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String

Description	Indicates Pool Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

POOLCCY

Attribute	**Description**
Name	POOLCCY
Datatype	String
Description	Indicates Pool Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POOLAMT

Attribute	**Description**
Name	POOLAMT
Datatype	Number
Description	Indicates Pool Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLUTL

Attribute	**Description**
Name	POOLUTL
Datatype	Number
Description	Indicates Pool Utilization
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Crapp

Attribute	**Description**
Name	Crapp
Datatype	
Description	Indicates Credit Application Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	**Description**

Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BORROWPRF

Attribute	**Description**
Name	BORROWPRF
Datatype	String
Description	Indicates Borrower Profile
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FINPER

Attribute	**Description**
Name	FINPER
Datatype	String
Description	Indicates Financial Performance
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BORRMKTPOS

Attribute	**Description**
Name	BORRMKTPOS
Datatype	String
Description	Indicates Borrower Market Position
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RSKMIT

Attribute	**Description**
Name	RSKMIT
Datatype	String
Description	Indicates Risk Mitigants

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RSKDEPTMIT

Attribute	**Description**	
Name	RSKDEPTMIT	
Datatype	String	
Description	Indicates Risk Department Mitigants	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RSKDEPASSES

Attribute	**Description**	
Name	RSKDEPASSES	
Datatype	String	
Description	Indicates Risk Department Assessment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACPROP

Attribute	**Description**	
Name	FACPROP	
Datatype	String	
Description	Indicates Facilities Proposed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

APRFAC

Attribute	**Description**	
Name	APRFAC	
Datatype	String	
Description	Indicates Approved Facilities	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RECOM

Attribute	**Description**
Name	RECOM
Datatype	String
Description	Indicates Recommendation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TERMANDCOND

Attribute	**Description**
Name	TERMANDCOND
Datatype	String
Description	Indicates Terms and Conditions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Cust-Acct

Attribute	**Description**
Name	Cust-Acct
Datatype	
Description	Indicates Customer Account Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Account Class of Customer Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates Customer Account Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACODE

Attribute	Description
Name	ACODE
Datatype	String
Description	Indicates Account Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCYTYPE

Attribute	Description
Name	CCYTYPE
Datatype	String
Description	Indicates Currency Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Requested1

Attribute	Description
Name	Requested1
Datatype	
Description	Indicates Overall Loan Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

REQAMT

Attribute	Description
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TENORM

Attribute	Description
Name	TENORM
Datatype	Number
Description	Indicates Loan Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

PROMO

Attribute	Description
Name	PROMO
Datatype	String
Description	Indicates Promotion Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates Request Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

Requested2

Attribute	Description
Name	Requested2

Datatype	
Description	Indicates Individual Request Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ITEMIZATION

Attribute	**Description**
Name	ITEMIZATION
Datatype	String
Description	Indicates Itemization Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REQAMT

Attribute	**Description**
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loan2

Attribute	Description
Name	Loan2
Datatype	
Description	Indicates Individual Loan Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANCCY

Attribute	Description
Name	LOANCCY
Datatype	String
Description	Indicates Loan Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	Indicates Loan Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENURE

Attribute	Description
Name	TENURE
Datatype	Number
Description	Indicates Loan Tenure
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DPMT

Attribute	Description
Name	DPMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAX

Attribute	Description
Name	TAX
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFINST

Attribute	Description
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLACCNO

Attribute	Description
Name	CLACCNO

Datatype	String
Description	Indicates CL Account Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Loan3

Attribute	**Description**
Name	Loan3
Datatype	
Description	Indicates Loan Schedule Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NO1

Attribute	**Description**
Name	NO1
Datatype	Number
Description	Indicates No of Schedules
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNIT

Attribute	**Description**
Name	UNIT
Datatype	String
Description	Indicates Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ORACLE

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHTYP

Attribute	Description
Name	SCHTYP
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / P,D,R

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Loan4

Attribute	Description
Name	Loan4
Datatype	
Description	Indicates Exploded Schedule Details

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHNO

Attribute	Description	
Name	SCHNO	
Datatype	Number	
Description	Indicates Schedule No	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DUEDT

Attribute	Description	
Name	DUEDT	
Datatype	Date	
Description	Indicates Due Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTDUE

Attribute	Description	
Name	AMTDUE	
Datatype	Number	
Description	Indicates Amount Due	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EMI_AMOUNT

Attribute	Description	
Name	EMI_AMOUNT	
Datatype	Number	
Description	Indicates EMI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMORPRI

Attribute	Description
Name	AMORPRI
Datatype	Number
Description	Indicates Amortized Principal

Attributes	Attribute	Description
	minOccurs	0

TOP

INTEREST_AMOUNT

Attribute	Description
Name	INTEREST_AMOUNT
Datatype	Number
Description	Indicates Interest Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CAPI

Attribute	Description
Name	CAPI
Datatype	String
Description	Indicates Capitalized Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

WAIVE

Attribute	Description
Name	WAIVE
Datatype	String
Description	Indicates whether Schedule is Waived
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Comments

Attribute	Description
Name	Comments
Datatype	
Description	Indicates Comment Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SEQUENCENUMBER

Attribute	Description
Name	SEQUENCENUMBER
Datatype	String
Description	Indicates Comment Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String

Description	Indicates Comment Given
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COMMBY

Attribute	**Description**
Name	COMMBY
Datatype	String
Description	Indicates User who input Comment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COMMDT

Attribute	**Description**
Name	COMMDT
Datatype	Date
Description	Indicates Comment Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Udf

Attribute	**Description**
Name	Udf
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

B1

Attribute	**Description**
Name	B1
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B2

Attribute	Description
Name	B2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B3

Attribute	Description
Name	B3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B4

Attribute	Description
Name	B4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B5

Attribute	Description
Name	B5
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B6

Attribute	Description

Name	B6
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Chklst1

Attribute	Description
Name	Chklst1
Datatype	
Description	Indicates Checklist Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHKLSTID

Attribute	Description
Name	CHKLSTID
Datatype	String
Description	Indicates Checklist Id
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKLSTDESC

Attribute	Description
Name	CHKLSTDESC
Datatype	String
Description	Indicates Checklist Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

VERIFY

Attribute	Description
Name	VERIFY
Datatype	String
Description	Indicates Verified By
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Custudf

Attribute	Description	
Name	Custudf	
Datatype		
Description	Indicates Customer UDF Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

Tradein

Attribute	Description	
Name	Tradein	
Datatype		
Description	Indicates Trade In Asset Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ASSETTYP

Attribute	Description	
Name	ASSETTYP	
Datatype	String	
Description	Indicates Asset Type	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

TOP

ASSETWHVL

Attribute	Description
Name	ASSETWHVL
Datatype	Number
Description	Indicates Wholesale Value

Attributes	Attribute	Description
	minOccurs	0

TOP

ASSETBSVL

Attribute	Description
Name	ASSETBSVL
Datatype	Number
Description	Indicates Asset Base Value
Attributes	Attribute: minOccurs; Description: 0

TOP

PAYAMT

Attribute	Description
Name	PAYAMT
Datatype	Number
Description	Indicates Asset Payment Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

ASSETADDON1

Attribute	Description
Name	ASSETADDON1
Datatype	Number
Description	Indicates Asset Add-on Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

TOTVAL

Attribute	Description
Name	TOTVAL
Datatype	Number
Description	Indicates Asset Total Value
Attributes	Attribute: minOccurs; Description: 0

TOP

Loanoffers

Attribute	Description
Name	Loanoffers
Datatype	
Description	Indicates Loan Offer Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

OFFID

Attribute	Description	
Name	OFFID	
Datatype	String	
Description	Indicates Offer Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

TOP

RATE

Attribute	Description	
Name	RATE	
Datatype	Number	
Description	Indicates Interest Rate	
Attributes	Attribute	Description
	minOccurs	0

TOP

NOOFINST

Attribute	Description	
Name	NOOFINST	
Datatype	String	
Description	Indicates No of Installments	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

FREQUNIT

Attribute	Description	
Name	FREQUNIT	
Datatype	String	
Description	Indicates Schedule Frequency Unit	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y

TOP

ORACLE

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Interest Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECK

Attribute	Description
Name	CHECK
Datatype	String

Description	Indicates whether Offer Needs to be Applied
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Crdratout

Attribute	**Description**
Name	Crdratout
Datatype	
Description	Indicates External Credit Rating Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTAGEN

Attribute	**Description**
Name	EXTAGEN
Datatype	String
Description	Indicates External Credit Rating Agency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECOMM

Attribute	**Description**
Name	RECOMM
Datatype	String
Description	Indicates External Credit Rating Agency Final Recommendation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

Crdratin

Attribute	**Description**
Name	Crdratin
Datatype	
Description	Indicates Internal Credit Rating Details of Loan Application
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	Indicates Internal Credit Rating Rule Id used
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Crratin2

Attribute	Description
Name	Crratin2
Datatype	
Description	Indicates Internal Credit Rating Details by Customer
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	Description

Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

QUES

Attribute	**Description**
Name	QUES
Datatype	String
Description	Indicates Credit Rating Question
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ANS

Attribute	**Description**
Name	ANS
Datatype	String
Description	Indicates Answer to Credit Rating Question
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CAT

Attribute	**Description**
Name	CAT
Datatype	String
Description	Indicates Credit Rating Question Category

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Bureau

Attribute	Description	
Name	Bureau	
Datatype		
Description	Indicates Credit Bureau Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BUREAU

Attribute	Description	
Name	BUREAU	
Datatype	String	
Description	Indicates Credit Bureau	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RPTTYP

Attribute	Description	
Name	RPTTYP	
Datatype	String	
Description	Indicates Bureau Report Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Bureau Information Retrieval Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,C

TOP

Chgs

Attribute	Description
Name	Chgs
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Charge Collection Event
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description

Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTSETT

Attribute	**Description**
Name	AMTSETT
Datatype	Number
Description	Indicates Charge Amount Settled
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHDUEDT

Attribute	**Description**
Name	SCHDUEDT
Datatype	Date
Description	Indicates Charge Due Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

WAIV

Attribute	**Description**
Name	WAIV
Datatype	String
Description	Indicates whether Charge is Waived
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPNM

Attribute	**Description**
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loandedupe

Attribute	Description
Name	Loandedupe
Datatype	
Description	Indicates Other Loan Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	Indicates Loan Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUTSTAMT

Attribute	**Description**
Name	OUTSTAMT
Datatype	Number
Description	Indicates Outstanding Loan Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Riskfactor

Attribute	**Description**
Name	Riskfactor
Datatype	
Description	Indicates Risk Factor Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

2.2.3.OR-CreateSaveCLAppEntry-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Applicationhead-Full*
    - *APPNO*
    - *DATE*
    - *PRDCD*
    - *CHNL*
    - *BRN*
    - *STAT*
    - *INTERCD*
    - *INTNAME*
    - *CUSTTYPE1*
    - *CCY*
    - *LEAD*
    - *CONT*
    - *PUR*
    - *USERREFNO*
    - *APPCAT*
    - *ENQUIRY_ID*
    - *OFFAPPLNUM*
    - *Customer1*

APPNO
CUSTNO
NATID
LANG
EXISTING
CCY
CTYPE
ACLASS
ACCNO
SNAME
CNTY
NLTY
CCAT
NAME
LINE1
LINE2
LINE3
DATE
CAPITAL
NETWORTH
BUSIDESC
INCNTY
RCNTY
CCYAMT
Customer3
- *EMAIL*
- *CUSTNO*
- *DIRNAME*
- *LINE1*
- *LINE2*
- *LINE3*
- *LINE4*
- *ADDR1*
- *ADDR2*
- *ADDR3*
- *CNTY*
- *TEL*
- *TAXID*
- *MOBNO*

Customer2
- *APPNO*
- *CUSTNO*
- *ADDTYPE*
- *MAILING*

CONNO
ADDLN1
ADDLN2
ADDLN3
ZIP
CNTY
Financials1
CUSTNO
FIXEDASSETS
INTANGASSETS
NONCURRASSETS
SUBSIDYFRMGOV
GENRESERVES
TERMLIAB
CURRLIAB
ISSUEDCAP
PAIDUPCAP
CRBALINPL
OPACT
INVACT
FINACT
CURRASSETS
Collat1
APPNO
CUSTNO
COLLCD
COLLDESC
COLLCCY
COLLVL
COLLSTDT
COLLENDDT
COLLCAT
COLLHAIR
COLLTYPE
COLLREVDT
COLLCHGDT
COLLREVLDT
COLLREVCHK
SECUID
NOMUNITVL
CAPAMT
GUAID
RATIN
LNKPCTNO

- *LNKAMT*
- *Collat2*
  - *APPNO*
  - *CUSTNO*
  - *DUEDT*
  - *STMON*
  - *REM*
  - *COVNM*
  - *DESC*
  - *REVDT*
  - *MANDT*
  - *GRCDAY*
  - *NOTDAY*
  - *FREQ*
- *Vehdetails*
  - *VEH_IDNUM*
  - *VEH_YEAR*
  - *VEH_MAKE*
  - *VEH_MODEL*
  - *VEH_BDYSTYLE*
  - *VEH_USAGE*

Financials2

- *APPNO*
- *CUSTNO*
- *LIABTYP*
- *LIABSUB*
- *LIABFREQ*
- *LAIBAMT*
- *BAL*
- *REM*
- *LIABSTDT*
- *LIABENDDT*

Finsummary

- *MONSTATINC*
- *MONACTINC*
- *MONSTATDEBT*
- *MONACTDEBT*
- *GRADE*
- *SCORE*
- *ASSETWORTH*
- *LIABWORTH*
- *TOTWOR*
- *WHTPMT*
- *Finsummary2*

RATNM
STATBF
STATAF
ACTBF
ACTAF

Investi1
CUSTNO
VERTYPE
AGENCY

Investi2
SPOKE
ATTEMPTS
CALLDT
RESULT
VERMAT
REM

Custdedupe
CTYPE
NAME
LSTNM
SNAME
NATID
CNTY
NLTY
CCAT
DOB
LANG
EMAIL
EXISTING
PASSNO
MOBNO
LANDNO

Financials3
INCTYPE
CCY
AMT
FREQ

Cusudf
NAME
VALUE

Facility
LINECD
LINESER
LIABID

- *POOLCD*
- *CUSTID*
- *CUSTNM*
- *LIMAMT*
- *PURPOSE*
- *APPNO*
- *MAINLINE*
- *CCYRES*
- *LINENCCY*
- *REVLINE*
- *LINESTDT*
- *LINEEXPDT*
- *LSTNEWUTLDT*
- *INTREM*
- *LMTAMT*
- *COLLTAMT*
- *LIABBR*
- *BRN*
- *LMTAMTBASIS*
- *INTREQD*
- *DSPEFFLINEAMT*
- *Factenor*
  - *LINECD*
  - *LINESER*
  - *LIABID*
  - *TNRMNEMONIC*
  - *TENOR*
  - *LIMIT*
  - *UTILIZATION*
- *Pool*
  - *LIABID*
  - *POOLCD*
  - *POOLDESC*
  - *POOLCCY*
  - *POOLAMT*
  - *POOLUTL*

Crapp

- *CUSTNO*
- *BORROWPRF*
- *FINPER*
- *BORRMKTPOS*
- *RSKMIT*
- *RSKDEPTMIT*
- *RSKDEPASSES*

FACPROP
APRFAC
RECOM
TERMANDCOND
Cust-Acct
CUSTNO
ACCLS
ACCCY
ACODE
CCYTYPE
UDFDETAILS
FLDNAM
FLDVAL
Requested1
APPNO
PRDCD
REQAMT
REM
TENORM
INTRATE
DPMNTAMT
PROMO
CCY
SEQNO
Requested2
APPNO
PRDCD
ITEMIZATION
REQAMT
COMMENT
Loan2
LOANCCY
LOANAMT
TENURE
RATE
DPMT
TAX
VALDT
MATDT
NOOFINST
FREQUNIT
FREQ
SPREAD
EFFRATE

- *CLACCNO*
- *Loan3*
  - *NO1*
  - *FREQ*
  - *UNIT*
  - *FRSTDUEDT*
  - *AMT*
  - *SCHTYP*
  - *COMPNM*
- *Loan4*
  - *SCHNO*
  - *DUEDT*
  - *AMTDUE*
  - *EMI_AMOUNT*
  - *AMORPRI*
  - *INTEREST_AMOUNT*
  - *CAPI*
  - *WAIVE*
  - *COMPNM*

Comments

- *APPNO*
- *PRDCD*
- *SEQUENCENUMBER*
- *COMMENT*
- *COMMBY*
- *COMMDT*

Udf

- *L1*
- *L2*
- *L3*
- *L4*
- *L5*
- *L6*
- *L7*
- *L8*
- *L9*
- *L10*
- *L11*
- *L12*
- *L13*
- *L14*
- *L15*
- *L16*
- *L17*

- *L18*
- *L19*
- *L20*
- *F1*
- *F2*
- *F3*
- *F4*
- *F5*
- *F6*
- *F7*
- *F8*
- *F9*
- *F10*
- *F11*
- *F12*
- *F13*
- *F14*
- *F15*
- *F16*
- *F17*
- *F18*
- *F19*
- *F20*
- *B1*
- *B2*
- *B3*
- *B4*
- *B5*
- *B6*

Chklst1

- *CHKLSTID*
- *CHKLSTDESC*
- *VERIFY*
- *COMMENT*

Custudf

- *NAME*
- *DESC*

Tradein

- *ASSETTYP*
- *ASSETSUBTYP*
- *MAKE*
- *MODEL*
- *MANYR*
- *BODY*

- *ASSETIDNO*
- *ASSETDESC*
- *ASSETWHVL*
- *ASSETBSVL*
- *PAYAMT*
- *ASSETADDON1*
- *TOTVAL*
- *ASSETVLDT*
- *ASSETSOURCE*
- *ASSETSUPP*
- *ASSETEDI*

Loanoffers

- *OFFID*
- *RATE*
- *NOOFINST*
- *FREQUNIT*
- *FREQ*
- *RATECD*
- *SPREAD*
- *EFFRATE*
- *CHECK*

Crdratout

- *EXTAGEN*
- *RECOMM*

Crdratin

- *CUSTNO*
- *GRD*
- *SCR*
- *RULEID*
- *Crratin2*
  - *APPNO*
  - *CUSTNO*
  - *QUES*
  - *ANS*
  - *CAT*

Bureau

- *CUSTID*
- *BUREAU*
- *RPTTYP*
- *STAT*

Chgs

- *EVENTCD*
- *CCY*
- *AMT*

AMTSETT

SCHDUEDT

WAIV

COMPNM

Loandedupe

CCY

VALDT

MATDT

CUSTNO

LOAN_ACCNO

AMT

OUTSTAMT

RATE

Riskfactor

RISKFAC

DESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Applicationhead-Full

Attribute	Description
Name	Applicationhead-Full
Datatype	
Description	

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DATE

Attribute	Description	
Name	DATE	
Datatype	Date	
Description	Indicates Incorporation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description

Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHNL

Attribute	**Description**
Name	CHNL
Datatype	String
Description	Indicates Originating Channel of Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / NEWAPP,VFYAPP,UNDERW,UNAPPR,CHKDOC,FIVERI,FUNDED

TOP

INTERCD

Attribute	**Description**
Name	INTERCD
Datatype	String
Description	Indicates Intermediary Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTNAME

Attribute	Description
Name	INTNAME
Datatype	String
Description	Indicates Intermediary Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTTYPE1

Attribute	Description
Name	CUSTTYPE1
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LEAD

Attribute	Description
Name	LEAD
Datatype	String
Description	Indicates Lead Id
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CONT

Attribute	Description	
Name	CONT	
Datatype	String	
Description	Indicates Contact Person	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PUR

Attribute	Description	
Name	PUR	
Datatype	String	
Description	Indicates Loan Purpose	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

USERREFNO

Attribute	Description	
Name	USERREFNO	
Datatype	String	
Description	Indicates User Reference Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

TOP

APPCAT

Attribute	Description	
Name	APPCAT	
Datatype	String	
Description	Indicates Application Category	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ENQUIRY_ID

Attribute	Description
Name	ENQUIRY_ID
Datatype	String
Description	Indicates Enquiry Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OFFAPPLNUM

Attribute	Description
Name	OFFAPPLNUM
Datatype	String
Description	Indicates Offline Application Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Customer1

Attribute	Description
Name	Customer1
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NATID

Attribute	**Description**
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LANG

Attribute	**Description**
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXISTING

Attribute	**Description**
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	Indicates Currency Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CTYPE

Attribute	**Description**	
Name	CTYPE	
Datatype	String	
Description	Indicates Customer Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ACLASS

Attribute	**Description**	
Name	ACLASS	
Datatype	String	
Description	Indicates Account Class of Loan Settlement Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ACCNO

Attribute	**Description**	
Name	ACCNO	
Datatype	String	
Description	Indicates Settlement Account Number for the Loan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

SNAME

Attribute	**Description**	
Name	SNAME	
Datatype	String	
Description	Indicates Customer Short Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCAT

Attribute	Description
Name	CCAT
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

LINE1

Attribute	Description
Name	LINE1

Datatype	String
Description	Indicates Residence Address Line 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LINE2

Attribute	Description
Name	LINE2
Datatype	String
Description	Indicates Residence Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LINE3

Attribute	Description
Name	LINE3
Datatype	String
Description	Indicates Residence Address Line 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	Indicates Incorporation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPITAL

Attribute	Description
Name	CAPITAL
Datatype	Number
Description	Indicates Customer Business Capital
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	Indicates Net worth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BUSIDESC

Attribute	Description
Name	BUSIDESC
Datatype	String
Description	Indicates Customer Business Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

INCNTY

Attribute	Description
Name	INCNTY
Datatype	String
Description	Indicates Incorporation Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RCNTY

Attribute	Description
Name	RCNTY
Datatype	String
Description	Indicates Residence Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYAMT

Attribute	Description
Name	CCYAMT

Datatype	String
Description	Indicates Currency in which Financials are Declared
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Customer3

Attribute	**Description**
Name	Customer3
Datatype	
Description	Indicates Director Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	Indicates Email
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DIRNAME

Attribute	**Description**
Name	DIRNAME
Datatype	String
Description	Indicates Director Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LINE1

Attribute	**Description**
Name	LINE1
Datatype	String
Description	Indicates Residence Address Line 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LINE2

Attribute	**Description**
Name	LINE2
Datatype	String
Description	Indicates Residence Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LINE3

Attribute	**Description**
Name	LINE3
Datatype	String
Description	Indicates Residence Address Line 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LINE4

Attribute	**Description**
Name	LINE4
Datatype	String
Description	Indicates Mailing Address Line 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Permanent Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Permanent Address Line 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Permanent Address Line 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	Indicates Telephone Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TAXID

Attribute	Description
Name	TAXID
Datatype	String
Description	Indicates Tax Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Customer2

Attribute	Description
Name	Customer2
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDTYPE

Attribute	Description
Name	ADDTYPE
Datatype	String
Description	Indicates Address Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,R,T,O

TOP

MAILING

Attribute	Description
Name	MAILING
Datatype	String
Description	Indicates whether Mailing Address
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONNO

Attribute	Description
Name	CONNO
Datatype	Number
Description	Indicates Contact Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY

Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Financials1

Attribute	**Description**
Name	Financials1
Datatype	
Description	Indicates Customer Financial Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FIXEDASSETS

Attribute	**Description**
Name	FIXEDASSETS
Datatype	Number
Description	Indicates Fixed Assets
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTANGASSETS

Attribute	**Description**
Name	INTANGASSETS
Datatype	Number
Description	Indicates Intangible Assets
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NONCURRASSETS

Attribute	Description
Name	NONCURRASSETS
Datatype	Number
Description	Indicates Non Current Assets
Attributes	Attribute: minOccurs, Description: 0

TOP

SUBSIDYFRMGOV

Attribute	Description
Name	SUBSIDYFRMGOV
Datatype	Number
Description	Indicates Subsidy Received from Government
Attributes	Attribute: minOccurs, Description: 0

TOP

GENRESERVES

Attribute	Description
Name	GENRESERVES
Datatype	Number
Description	Indicates General Reserves
Attributes	Attribute: minOccurs, Description: 0

TOP

TERMLIAB

Attribute	Description
Name	TERMLIAB
Datatype	Number
Description	Indicates Term Liabilities
Attributes	Attribute: minOccurs, Description: 0

TOP

CURRLIAB

Attribute	Description
Name	CURRLIAB
Datatype	Number
Description	Indicates Current Liabilities
Attributes	Attribute: minOccurs, Description: 0

TOP

ISSUEDCAP

Attribute	Description

Name	ISSUEDCAP
Datatype	Number
Description	Indicates Issued Capital
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAIDUPCAP

Attribute	**Description**
Name	PAIDUPCAP
Datatype	Number
Description	Indicates Paid Up Capital
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRBALINPL

Attribute	**Description**
Name	CRBALINPL
Datatype	Number
Description	Indicates Credit Balance in Profit and Loss
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OPACT

Attribute	**Description**
Name	OPACT
Datatype	Number
Description	Indicates Operations Activities
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVACT

Attribute	**Description**
Name	INVACT
Datatype	Number
Description	Indicates Investing Activities
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FINACT

Attribute	**Description**
Name	FINACT
Datatype	Number
Description	Indicates Financing Activities

Attributes	Attribute	Description
	minOccurs	0

TOP

CURRASSETS

Attribute	Description
Name	CURRASSETS
Datatype	Number
Description	Indicates Current Assets
Attributes	Attribute: minOccurs — Description: 0

TOP

Collat1

Attribute	Description
Name	Collat1
Datatype	
Description	Indicates Collateral Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

COLLCD

Attribute	Description

Name	COLLCD
Datatype	String
Description	Indicates Collateral Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	Indicates Collateral Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	Indicates Collateral Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLSTDT

Attribute	Description
Name	COLLSTDT
Datatype	Date
Description	Indicates Collateral Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLENDDT

Attribute	Description
Name	COLLENDDT
Datatype	Date
Description	Indicates Collateral End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	Indicates Collateral Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	String
Description	Indicates Collateral Haircut Margin
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,M,G

TOP

COLLREVDT

Attribute	Description
Name	COLLREVDT

Datatype	Date
Description	Indicates Collateral Revision Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCHGDT

Attribute	Description
Name	COLLCHGDT
Datatype	String
Description	Indicates Collateral Charge Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,P,H,A

TOP

COLLREVLDT

Attribute	Description
Name	COLLREVLDT
Datatype	Date
Description	Indicates Collateral Revaluation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLREVCHK

Attribute	Description
Name	COLLREVCHK
Datatype	String
Description	Indicates whether Collateral Revaluation is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NOMUNITVL

Attribute	Description
Name	NOMUNITVL
Datatype	Number
Description	Indicates Nominal Unit Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPAMT

Attribute	Description
Name	CAPAMT
Datatype	Number
Description	Indicates Cap Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUAID

Attribute	Description
Name	GUAID
Datatype	String
Description	Indicates Guarantor Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RATIN

Attribute	Description
Name	RATIN
Datatype	String
Description	Indicates Rating
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LNKPCTNO

Attribute	Description
Name	LNKPCTNO
Datatype	Number
Description	Indicates Linkage Percentage

Attributes	Attribute	Description
	minOccurs	0

TOP

LNKAMT

Attribute	Description
Name	LNKAMT
Datatype	Number
Description	Indicates Linkage Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Collat2

Attribute	Description
Name	Collat2
Datatype	
Description	Indicates Collateral Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

DUEDT

Attribute	Description

Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STMON

Attribute	**Description**
Name	STMON
Datatype	String
Description	Indicates Start Month
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REM

Attribute	**Description**
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVNM

Attribute	**Description**
Name	COVNM
Datatype	String
Description	Indicates Covenant Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	Indicates Revision Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANDT

Attribute	Description
Name	MANDT
Datatype	Date
Description	Indicates whether it is Mandatory
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAY

Attribute	Description
Name	GRCDAY
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Vehdetails

Attribute	Description
Name	Vehdetails
Datatype	
Description	Indicates Vehicle Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_IDNUM

Attribute	Description
Name	VEH_IDNUM
Datatype	String
Description	Indicates Vehicle Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_YEAR

Attribute	Description
Name	VEH_YEAR
Datatype	Number
Description	Indicates Vehicle Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_MAKE

Attribute	Description
Name	VEH_MAKE
Datatype	String
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_MODEL

Attribute	Description
Name	VEH_MODEL
Datatype	String
Description	Indicates Vehicle Model

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VEH_BDYSTYLE

Attribute	**Description**
Name	VEH_BDYSTYLE
Datatype	String
Description	Indicates Vehicle Body Style
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VEH_USAGE

Attribute	**Description**
Name	VEH_USAGE
Datatype	String
Description	Indicates Vehicle Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Financials2

Attribute	**Description**
Name	Financials2
Datatype	
Description	Indicates Customer Liability Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABTYP

Attribute	Description
Name	LIABTYP
Datatype	String
Description	Indicates Liability Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LO,LE,RE,OT

TOP

LIABSUB

Attribute	Description
Name	LIABSUB
Datatype	String
Description	Indicates Liability Sub Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABFREQ

Attribute	Description
Name	LIABFREQ
Datatype	String
Description	Indicates Liability Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

LAIBAMT

Attribute	Description
Name	LAIBAMT
Datatype	Number
Description	Indicates Liability Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

BAL

Attribute	Description
Name	BAL
Datatype	Number
Description	Indicates Liability Outstanding Balance
Attributes	Attribute: minOccurs, Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

LIABSTDT

Attribute	Description
Name	LIABSTDT
Datatype	Date
Description	Indicates Liability Start Date
Attributes	Attribute: minOccurs, Description: 0

TOP

LIABENDDT

Attribute	Description
Name	LIABENDDT
Datatype	Date
Description	Indicates Liability End Date
Attributes	Attribute: minOccurs, Description: 0

TOP

Finsummary

Attribute	Description
Name	Finsummary
Datatype	
Description	Indicates Asset Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONSTATINC

Attribute	Description
Name	MONSTATINC
Datatype	Number
Description	Indicates Monthly Stated Income
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTINC

Attribute	Description
Name	MONACTINC
Datatype	Number
Description	Indicates Monthly Actual Income
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONSTATDEBT

Attribute	Description
Name	MONSTATDEBT
Datatype	Number
Description	Indicates Monthly Stated Debt
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTDEBT

Attribute	Description
Name	MONACTDEBT
Datatype	Number
Description	Indicates Monthly Actual Debt
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRADE

Attribute	Description
Name	GRADE
Datatype	String
Description	Indicates Internal Final Grade
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SCORE

Attribute	Description
Name	SCORE
Datatype	Number
Description	Indicates Internal Credit Score
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ASSETWORTH

Attribute	Description
Name	ASSETWORTH
Datatype	Number
Description	Indicates Asset Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABWORTH

Attribute	Description
Name	LIABWORTH
Datatype	Number
Description	Indicates Total Liabilities
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTWOR

Attribute	Description
Name	TOTWOR
Datatype	Number
Description	Indicates Total Net worth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WHTPMT

Attribute	Description
Name	WHTPMT
Datatype	Number
Description	Indicates What if Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Finsummary2

Attribute	Description
Name	Finsummary2
Datatype	
Description	Indicates Consolidated Financial Summary Information
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RATNM

Attribute	Description
Name	RATNM
Datatype	String
Description	Indicates Ratio Name
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STATBF

Attribute	Description
Name	STATBF
Datatype	String
Description	Indicates Ratio based on Stated Financials After Accounting for Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STATAF

Attribute	Description
Name	STATAF
Datatype	String

Description	Indicates Ratio based on Stated Financials After Accounting for Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACTBF

Attribute	**Description**
Name	ACTBF
Datatype	String
Description	Indicates Ratio based on Actual Financials Before Accounting for Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACTAF

Attribute	**Description**
Name	ACTAF
Datatype	String
Description	Indicates Ratio based on Actual Financials After Accounting for Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Investi1

Attribute	**Description**
Name	Investi1
Datatype	
Description	Indicates Investigation Summary
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

VERTYPE

Attribute	**Description**	
Name	VERTYPE	
Datatype	String	
Description	Indicates Verification Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGENCY

Attribute	**Description**	
Name	AGENCY	
Datatype	String	
Description	Indicates Investigating Agency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Investi2

Attribute	**Description**	
Name	Investi2	
Datatype		
Description	Indicates Investigation Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPOKE

Attribute	**Description**	
Name	SPOKE	
Datatype	String	
Description	Indicates who the Agency Contacted	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ATTEMPTS

Attribute	Description
Name	ATTEMPTS
Datatype	Number
Description	Indicates No of Attempts
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CALLDT

Attribute	Description
Name	CALLDT
Datatype	Date
Description	Indicates Called Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESULT

Attribute	Description
Name	RESULT
Datatype	String
Description	Indicates Investigation Result
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERMAT

Attribute	Description
Name	VERMAT
Datatype	String
Description	Indicates whether Verification Matched
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Custdedupe

Attribute	Description	
Name	Custdedupe	
Datatype		
Description	Indicates Possible Duplicate Customer Names	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CTYPE

Attribute	Description	
Name	CTYPE	
Datatype	String	
Description	Indicates Customer Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

LSTNM

Attribute	Description	
Name	LSTNM	
Datatype	String	
Description	Indicates Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNAME

Attribute	Description

Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NATID

Attribute	**Description**
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CNTY

Attribute	**Description**
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCAT

Attribute	**Description**
Name	CCAT
Datatype	String
Description	Indicates Customer Category

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	Indicates Customer Date of Birth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	Indicates Email
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EXISTING

Attribute	Description
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASSNO

Attribute	Description
Name	PASSNO
Datatype	String
Description	Indicates Customer Passport Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Customer Landline Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Financials3

Attribute	Description
Name	Financials3
Datatype	
Description	Indicates Customer Income Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INCTYPE

Attribute	Description
Name	INCTYPE
Datatype	String
Description	Indicates Income Type

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,R,B,O

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Cusudf

Attribute	Description
Name	Cusudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description

Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

Facility

Attribute	Description	
Name	Facility	
Datatype		
Description	Indicates Facility Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LINECD

Attribute	Description	
Name	LINECD	
Datatype	String	
Description	Indicates Line Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINESER

Attribute	Description	
Name	LINESER	
Datatype	Number	
Description	Indicates Line Serial Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIABID

Attribute	Description	
Name	LIABID	
Datatype	String	
Description	Indicates Liability Id	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTNM

Attribute	Description
Name	CUSTNM
Datatype	String
Description	Indicates Customer Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LIMAMT

Attribute	Description
Name	LIMAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

PURPOSE

Attribute	Description
Name	PURPOSE
Datatype	String
Description	Indicates Purpose
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

MAINLINE

Attribute	Description
Name	MAINLINE
Datatype	String
Description	Indicates Main Line
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

CCYRES

Attribute	Description
Name	CCYRES
Datatype	String
Description	Indicates Currency Restriction
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LINENCCY

Attribute	Description
Name	LINENCCY

Datatype	String
Description	Indicates Line Currency
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVLINE

Attribute	**Description**
Name	REVLINE
Datatype	String
Description	Indicates whether Revolving Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINESTDT

Attribute	**Description**
Name	LINESTDT
Datatype	Date
Description	Indicates Line Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINEEXPDT

Attribute	**Description**
Name	LINEEXPDT
Datatype	Date
Description	Indicates Line Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LSTNEWUTLDT

Attribute	**Description**
Name	LSTNEWUTLDT
Datatype	Date
Description	Indicates Last New Utilization Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREM

Attribute	Description
Name	INTREM
Datatype	String
Description	Indicates Internal Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABBR

Attribute	Description
Name	LIABBR
Datatype	String
Description	Indicates Liability Branch Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LMTAMTBASIS

Attribute	**Description**
Name	LMTAMTBASIS
Datatype	String
Description	Indicates Limit Amount Basis
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,L,M

TOP

INTREQD

Attribute	**Description**
Name	INTREQD
Datatype	String
Description	Indicates whether Fee needs to be Collected
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DSPEFFLINEAMT

Attribute	**Description**
Name	DSPEFFLINEAMT
Datatype	Number
Description	Indicates Effective Line Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Factenor

Attribute	**Description**
Name	Factenor
Datatype	
Description	Indicates Facility Tenor
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINECD

Attribute	**Description**

Name	LINECD
Datatype	String
Description	Indicates Line Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINESER

Attribute	Description
Name	LINESER
Datatype	Number
Description	Indicates Line Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TNRMNEMONIC

Attribute	Description
Name	TNRMNEMONIC
Datatype	String
Description	Indicates Tenor Mnemonic
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT

Attribute	Description
Name	LIMIT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UTILIZATION

Attribute	Description
Name	UTILIZATION
Datatype	Number
Description	Indicates Utilization
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pool

Attribute	Description
Name	Pool
Datatype	
Description	Indicates Pool Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

POOLDESC

Attribute	Description
Name	POOLDESC
Datatype	String
Description	Indicates Pool Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

POOLCCY

Attribute	Description
Name	POOLCCY
Datatype	String
Description	Indicates Pool Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

POOLAMT

Attribute	Description
Name	POOLAMT
Datatype	Number
Description	Indicates Pool Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

POOLUTL

Attribute	Description
Name	POOLUTL
Datatype	Number
Description	Indicates Pool Utilization
Attributes	Attribute: minOccurs — Description: 0

TOP

Crapp

Attribute	Description
Name	Crapp

Datatype	
Description	Indicates Credit Application Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BORROWPRF

Attribute	Description
Name	BORROWPRF
Datatype	String
Description	Indicates Borrower Profile
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FINPER

Attribute	Description
Name	FINPER
Datatype	String
Description	Indicates Financial Performance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BORRMKTPOS

Attribute	Description
Name	BORRMKTPOS
Datatype	String
Description	Indicates Borrower Market Position
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RSKMIT

Attribute	**Description**
Name	RSKMIT
Datatype	String
Description	Indicates Risk Mitigants
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RSKDEPTMIT

Attribute	**Description**
Name	RSKDEPTMIT
Datatype	String
Description	Indicates Risk Department Mitigants
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RSKDEPASSES

Attribute	**Description**
Name	RSKDEPASSES
Datatype	String
Description	Indicates Risk Department Assessment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACPROP

Attribute	**Description**
Name	FACPROP
Datatype	String
Description	Indicates Facilities Proposed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

APRFAC

Attribute	Description
Name	APRFAC
Datatype	String
Description	Indicates Approved Facilities
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RECOM

Attribute	Description
Name	RECOM
Datatype	String
Description	Indicates Recommendation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TERMANDCOND

Attribute	Description
Name	TERMANDCOND
Datatype	String
Description	Indicates Terms and Conditions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cust-Acct

Attribute	Description
Name	Cust-Acct
Datatype	
Description	Indicates Customer Account Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Account Class of Customer Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates Customer Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACODE

Attribute	Description
Name	ACODE
Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCYTYPE

Attribute	Description
Name	CCYTYPE
Datatype	String
Description	Indicates Currency Type

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 150
	minLength / 0

TOP

Requested1

Attribute	Description
Name	Requested1
Datatype	
Description	Indicates Overall Loan Details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

REQAMT

Attribute	Description
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TENORM

Attribute	Description
Name	TENORM

Datatype	Number
Description	Indicates Loan Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROMO

Attribute	Description
Name	PROMO
Datatype	String
Description	Indicates Promotion Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates Request Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Requested2

Attribute	Description
Name	Requested2
Datatype	
Description	Indicates Individual Request Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ITEMIZATION

Attribute	Description
Name	ITEMIZATION
Datatype	String
Description	Indicates Itemization Details

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REQAMT

Attribute	**Description**	
Name	REQAMT	
Datatype	Number	
Description	Indicates Overall Requested Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMMENT

Attribute	**Description**	
Name	COMMENT	
Datatype	String	
Description	Indicates Comment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Loan2

Attribute	**Description**	
Name	Loan2	
Datatype		
Description	Indicates Individual Loan Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOANCCY

Attribute	**Description**	
Name	LOANCCY	
Datatype	String	
Description	Indicates Loan Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	Indicates Loan Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TENURE

Attribute	Description
Name	TENURE
Datatype	Number
Description	Indicates Loan Tenure
Attributes	Attribute: minOccurs, Description: 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

DPMT

Attribute	Description
Name	DPMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TAX

Attribute	Description
Name	TAX
Datatype	Number
Description	Indicates Tax Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

VALDT

Attribute	Description

Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	**Description**
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFINST

Attribute	**Description**
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREQUNIT

Attribute	**Description**
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	Indicates CL Account Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Loan3

Attribute	Description
Name	Loan3
Datatype	
Description	Indicates Loan Schedule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NO1

Attribute	Description
Name	NO1

Datatype	Number
Description	Indicates No of Schedules
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHTYP

Attribute	Description
Name	SCHTYP

Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / P,D,R

TOP

COMPNM

Attribute	**Description**
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loan4

Attribute	**Description**
Name	Loan4
Datatype	
Description	Indicates Exploded Schedule Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHNO

Attribute	**Description**
Name	SCHNO
Datatype	Number
Description	Indicates Schedule No
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDT

Attribute	**Description**
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EMI_AMOUNT

Attribute	Description
Name	EMI_AMOUNT
Datatype	Number
Description	Indicates EMI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMORPRI

Attribute	Description
Name	AMORPRI
Datatype	Number
Description	Indicates Amortized Principal
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTEREST_AMOUNT

Attribute	Description
Name	INTEREST_AMOUNT
Datatype	Number
Description	Indicates Interest Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPI

Attribute	Description
Name	CAPI
Datatype	String
Description	Indicates Capitalized Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

WAIVE

Attribute	Description
Name	WAIVE
Datatype	String
Description	Indicates whether Schedule is Waived
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Comments

Attribute	Description
Name	Comments
Datatype	
Description	Indicates Comment Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	Description

Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SEQUENCENUMBER

Attribute	**Description**
Name	SEQUENCENUMBER
Datatype	String
Description	Indicates Comment Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMENT

Attribute	**Description**
Name	COMMENT
Datatype	String
Description	Indicates Comment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMBY

Attribute	**Description**
Name	COMMBY
Datatype	String
Description	Indicates User who input Comment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMDT

Attribute	**Description**
Name	COMMDT
Datatype	Date
Description	Indicates Comment Date

Attributes	Attribute	Description
	minOccurs	0

TOP

Udf

Attribute	Description	
Name	Udf	
Datatype		
Description	Indicates UDF Details	
Attributes	Attribute	Description
	minOccurs	0

TOP

L1

Attribute	Description	
Name	L1	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

L2

Attribute	Description	
Name	L2	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

L3

Attribute	Description	
Name	L3	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

L4

Attribute	Description
Name	L4
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L5

Attribute	Description
Name	L5
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L6

Attribute	Description
Name	L6
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L7

Attribute	Description
Name	L7
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L8

Attribute	Description
Name	L8

Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L9

Attribute	Description
Name	L9
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L10

Attribute	Description
Name	L10
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L11

Attribute	Description
Name	L11
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L12

Attribute	Description
Name	L12
Datatype	String
Description	Indicates User Defined Field

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L13

Attribute	**Description**	
Name	L13	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L14

Attribute	**Description**	
Name	L14	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L15

Attribute	**Description**	
Name	L15	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L16

Attribute	**Description**	
Name	L16	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

L17

Attribute	Description
Name	L17
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L18

Attribute	Description
Name	L18
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L19

Attribute	Description
Name	L19
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L20

Attribute	Description
Name	L20
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F1

Attribute	Description
Name	F1
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F2

Attribute	Description
Name	F2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F3

Attribute	Description
Name	F3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F4

Attribute	Description
Name	F4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F5

Attribute	Description
Name	F5
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F6

Attribute	Description
Name	F6
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F7

Attribute	Description
Name	F7
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F8

Attribute	Description
Name	F8
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F9

Attribute	Description
Name	F9

Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F10

Attribute	Description
Name	F10
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F11

Attribute	Description
Name	F11
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F12

Attribute	Description
Name	F12
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F13

Attribute	Description
Name	F13
Datatype	String
Description	Indicates User Defined Field

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F14

Attribute	Description	
Name	F14	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F15

Attribute	Description	
Name	F15	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F16

Attribute	Description	
Name	F16	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F17

Attribute	Description	
Name	F17	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F18

Attribute	**Description**
Name	F18
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F19

Attribute	**Description**
Name	F19
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F20

Attribute	**Description**
Name	F20
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B1

Attribute	**Description**
Name	B1
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B2

Attribute	Description
Name	B2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B3

Attribute	Description
Name	B3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B4

Attribute	Description
Name	B4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B5

Attribute	Description
Name	B5
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B6

Attribute	Description
Name	B6
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1000

TOP

Chklst1

Attribute	Description
Name	Chklst1
Datatype	
Description	Indicates Checklist Details
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CHKLSTID

Attribute	Description
Name	CHKLSTID
Datatype	String
Description	Indicates Checklist Id
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 35

TOP

CHKLSTDESC

Attribute	Description
Name	CHKLSTDESC
Datatype	String
Description	Indicates Checklist Description
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

VERIFY

Attribute	Description
Name	VERIFY
Datatype	String

Description	Indicates Verified By
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMMENT

Attribute	**Description**
Name	COMMENT
Datatype	String
Description	Indicates Comment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custudf

Attribute	**Description**
Name	Custudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tradein

Attribute	Description
Name	Tradein
Datatype	
Description	Indicates Trade In Asset Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ASSETTYP

Attribute	Description
Name	ASSETTYP
Datatype	String
Description	Indicates Asset Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETSUBTYP

Attribute	Description
Name	ASSETSUBTYP
Datatype	String
Description	Indicates Asset Sub Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKE

Attribute	Description
Name	MAKE
Datatype	Number
Description	Indicates Asset Make
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODEL

Attribute	Description
Name	MODEL
Datatype	String
Description	Indicates Asset Model

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MANYR

Attribute	Description
Name	MANYR
Datatype	Number
Description	Indicates Manufacture Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BODY

Attribute	Description
Name	BODY
Datatype	String
Description	Indicates Asset Body
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ASSETIDNO

Attribute	Description
Name	ASSETIDNO
Datatype	String
Description	Indicates Asset Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ASSETDESC

Attribute	Description
Name	ASSETDESC
Datatype	String
Description	Indicates Asset Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ASSETWHVL

Attribute	Description
Name	ASSETWHVL
Datatype	Number
Description	Indicates Wholesale Value
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETBSVL

Attribute	Description
Name	ASSETBSVL
Datatype	Number
Description	Indicates Asset Base Value
Attributes	Attribute: minOccurs, Description: 0

TOP

PAYAMT

Attribute	Description
Name	PAYAMT
Datatype	Number
Description	Indicates Asset Payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETADDON1

Attribute	Description
Name	ASSETADDON1
Datatype	Number
Description	Indicates Asset Add-on Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TOTVAL

Attribute	Description
Name	TOTVAL
Datatype	Number
Description	Indicates Asset Total Value
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETVLDT

Attribute	Description
Name	ASSETVLDT
Datatype	Date
Description	Indicates Asset Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ASSETSOURCE

Attribute	Description
Name	ASSETSOURCE
Datatype	String
Description	Indicates Asset Source
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETSUPP

Attribute	Description
Name	ASSETSUPP
Datatype	String
Description	Indicates Asset Supplier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETEDI

Attribute	Description
Name	ASSETEDI
Datatype	String
Description	Indicates Asset Edition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Loanoffers

Attribute	Description
Name	Loanoffers
Datatype	

Description	Indicates Loan Offer Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OFFID

Attribute	**Description**
Name	OFFID
Datatype	String
Description	Indicates Offer Id
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFINST

Attribute	**Description**
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREQUNIT

Attribute	**Description**
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Interest Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECK

Attribute	Description
Name	CHECK

Datatype	String
Description	Indicates whether Offer Needs to be Applied
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Crdratout

Attribute	Description
Name	Crdratout
Datatype	
Description	Indicates External Credit Rating Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTAGEN

Attribute	Description
Name	EXTAGEN
Datatype	String
Description	Indicates External Credit Rating Agency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECOMM

Attribute	Description
Name	RECOMM
Datatype	String
Description	Indicates External Credit Rating Agency Final Recommendation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

Crdratin

Attribute	Description
Name	Crdratin
Datatype	
Description	Indicates Internal Credit Rating Details of Loan Application
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

GRD

Attribute	Description
Name	GRD
Datatype	String
Description	Indicates Final Internal Credit Rating Grade
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SCR

Attribute	Description
Name	SCR
Datatype	Number
Description	Indicates Internal Credit Rating Score
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	Indicates Internal Credit Rating Rule Id used
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Crratin2

Attribute	Description
Name	Crratin2

Datatype	
Description	Indicates Internal Credit Rating Details by Customer
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QUES

Attribute	**Description**
Name	QUES
Datatype	String
Description	Indicates Credit Rating Question
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ANS

Attribute	**Description**
Name	ANS
Datatype	String
Description	Indicates Answer to Credit Rating Question
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CAT

Attribute	**Description**
Name	CAT
Datatype	String
Description	Indicates Credit Rating Question Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Bureau

Attribute	**Description**
Name	Bureau
Datatype	
Description	Indicates Credit Bureau Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTID

Attribute	**Description**
Name	CUSTID
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BUREAU

Attribute	**Description**
Name	BUREAU
Datatype	String
Description	Indicates Credit Bureau
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RPTTYP

Attribute	Description
Name	RPTTYP
Datatype	String
Description	Indicates Bureau Report Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / NEWAPP,VFYAPP,UNDERW,UNAPPR,CHKDOC,FIVERI,FUNDED

TOP

Chgs

Attribute	Description
Name	Chgs
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Charge Collection Event
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTSETT

Attribute	**Description**
Name	AMTSETT
Datatype	Number
Description	Indicates Charge Amount Settled
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHDUEDT

Attribute	**Description**
Name	SCHDUEDT
Datatype	Date
Description	Indicates Charge Due Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

WAIV

Attribute	**Description**
Name	WAIV
Datatype	String
Description	Indicates whether Charge is Waived
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loandedupe

Attribute	Description
Name	Loandedupe
Datatype	
Description	Indicates Other Loan Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description	Indicates Customer Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

LOAN_ACCNO

Attribute	Description	
Name	LOAN_ACCNO	
Datatype	String	
Description	Indicates Loan Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Income Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUTSTAMT

Attribute	Description	
Name	OUTSTAMT	
Datatype	Number	
Description	Indicates Outstanding Loan Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE

Attribute	Description
Name	RATE

Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Riskfactor

Attribute	Description
Name	Riskfactor
Datatype	
Description	Indicates Risk Factor Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RISKFAC

Attribute	Description
Name	RISKFAC
Datatype	String
Description	Indicates Risk Factor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.4.OR-CreateSaveCLAppEntry-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Applicationhead-PK*
      - *APPNO*
    - *Applicationhead-IO*
      - *APPNO*
      - *DATE*
      - *PRDCD*
      - *CHNL*
      - *INTERCD*
      - *INTNAME*
      - *CUSTTYPE1*
      - *CCY*
      - *LEAD*
      - *CONT*
      - *PUR*
      - *USERREFNO*
      - *APPCAT*
      - *OFFAPPLNUM*
      - *Customer1*

APPNO
CUSTNO
NATID
LANG
EXISTING
CCY
CTYPE
ACLASS
ACCNO
SNAME
CNTY
NLTY
CCAT
NAME
LINE1
LINE2
DATE
CAPITAL
NETWORTH
BUSIDESC
INCNTY
RCNTY
CCYAMT
Customer3
- *EMAIL*
- *CUSTNO*
- *DIRNAME*
- *ADDR2*
- *ADDR3*
- *CNTY*

Customer2
- *APPNO*
- *CUSTNO*
- *ADDTYPE*
- *MAILING*
- *CONNO*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ZIP*
- *CNTY*

Financials1
- *CUSTNO*
- *FIXEDASSETS*

INTANGASSETS
NONCURRASSETS
SUBSIDYFRMGOV
GENRESERVES
TERMLIAB
CURRLIAB
ISSUEDCAP
PAIDUPCAP
CRBALINPL
OPACT
INVACT
FINACT
CURRASSETS
Collat1
APPNO
CUSTNO
COLLCD
COLLDESC
COLLCCY
COLLVL
COLLSTDT
COLLENDDT
COLLCAT
COLLHAIR
COLLTYPE
COLLREVDT
COLLCHGDT
COLLREVLDT
COLLREVCHK
SECUID
NOMUNITVL
CAPAMT
GUAID
RATIN
LNKPCTNO
LNKAMT
Collat2
APPNO
CUSTNO
DUEDT
STMON
REM
COVNM
DESC

REVDT
MANDT
GRCDAY
NOTDAY
FREQ
Vehdetails
VEH_IDNUM
VEH_YEAR
VEH_MAKE
VEH_MODEL
VEH_BDYSTYLE
VEH_USAGE
Financials2
APPNO
CUSTNO
LIABTYP
LIABSUB
LIABFREQ
LAIBAMT
BAL
REM
LIABSTDT
LIABENDDT
Finsummary
MONACTINC
MONACTDEBT
GRADE
WHTPMT
Finsummary2
Investi1
CUSTNO
VERTYPE
AGENCY
Custdedupe
CTYPE
NAME
LSTNM
SNAME
NATID
CNTY
NLTY
CCAT
DOB
LANG

EMAIL
EXISTING
PASSNO
MOBNO
LANDNO
Financials3
INCTYPE
CCY
AMT
FREQ
Cusudf
NAME
VALUE
Facility
LINECD
LINESER
LIABID
POOLCD
CUSTID
CUSTNM
LIMAMT
PURPOSE
APPNO
MAINLINE
CCYRES
LINENCCY
REVLINE
LINESTDT
LINEEXPDT
LSTNEWUTLDT
INTREM
LMTAMT
COLLTAMT
LIABBR
BRN
LMTAMTBASIS
INTREQD
DSPEFFLINEAMT
Factenor
LINECD
LINESER
LIABID
TNRMNEMONIC
TENOR

LIMIT

UTILIZATION

Pool

LIABID

POOLCD

POOLCCY

POOLAMT

POOLUTL

Crapp

CUSTNO

BORROWPRF

FINPER

BORRMKTPOS

RSKMIT

RSKDEPTMIT

RSKDEPASSES

FACPROP

APRFAC

RECOM

TERMANDCOND

Cust-Acct

CUSTNO

ACCLS

ACCCY

ACODE

CCYTYPE

UDFDETAILS

FLDNAM

FLDVAL

Requested1

APPNO

PRDCD

REQAMT

REM

TENORM

INTRATE

DPMNTAMT

PROMO

CCY

SEQNO

Requested2

APPNO

PRDCD

ITEMIZATION

REQAMT

Loan2

LOANCCY

LOANAMT

TENURE

RATE

DPMT

TAX

VALDT

MATDT

NOOFINST

FREQUNIT

FREQ

SPREAD

EFFRATE

CLACCNO

Loan3

NO1

FREQ

UNIT

FRSTDUEDT

AMT

SCHTYP

COMPNM

Loan4

SCHNO

DUEDT

AMTDUE

EMI_AMOUNT

AMORPRI

INTEREST_AMOUNT

CAPI

WAIVE

COMPNM

Comments

APPNO

PRDCD

SEQUENCENUMBER

COMMENT

COMMBY

COMMDT

Udf

B1

B2

- *B3*
- *B4*
- *B5*
- *B6*

Chklst1

- *CHKLSTID*
- *CHKLSTDESC*
- *VERIFY*

Custudf

- *NAME*

Tradein

- *ASSETTYP*
- *ASSETWHVL*
- *ASSETBSVL*
- *PAYAMT*
- *ASSETADDON1*
- *TOTVAL*

Loanoffers

- *OFFID*
- *RATE*
- *NOOFINST*
- *FREQUNIT*
- *FREQ*
- *RATECD*
- *SPREAD*
- *EFFRATE*
- *CHECK*

Crdratout

- *EXTAGEN*
- *RECOMM*

Crdratin

- *CUSTNO*
- *APPNO*
- *RULEID*
- *Crratin2*
  - *APPNO*
  - *CUSTNO*
  - *QUES*
  - *ANS*
  - *CAT*

Bureau

- *CUSTID*
- *BUREAU*
- *RPTTYP*

STAT

Chgs

EVENTCD

CCY

AMT

AMTSETT

SCHDUEDT

WAIV

COMPNM

Loandedupe

CCY

VALDT

MATDT

CUSTNO

LOAN_ACCNO

AMT

OUTSTAMT

RATE

Riskfactor

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Applicationhead-PK

Attribute	Description
Name	Applicationhead-PK
Datatype	
Description	

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Applicationhead-IO

Attribute	Description
Name	Applicationhead-IO
Datatype	
Description	

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	Indicates Incorporation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHNL

Attribute	Description
Name	CHNL
Datatype	String
Description	Indicates Originating Channel of Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INTERCD

Attribute	Description
Name	INTERCD
Datatype	String

Description	Indicates Intermediary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTNAME

Attribute	**Description**
Name	INTNAME
Datatype	String
Description	Indicates Intermediary Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTTYPE1

Attribute	**Description**
Name	CUSTTYPE1
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LEAD

Attribute	**Description**
Name	LEAD
Datatype	String
Description	Indicates Lead Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONT

Attribute	**Description**
Name	CONT
Datatype	String
Description	Indicates Contact Person
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PUR

Attribute	**Description**
Name	PUR
Datatype	String
Description	Indicates Loan Purpose
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

USERREFNO

Attribute	**Description**
Name	USERREFNO
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

APPCAT

Attribute	**Description**
Name	APPCAT
Datatype	String
Description	Indicates Application Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OFFAPPLNUM

Attribute	Description
Name	OFFAPPLNUM
Datatype	String
Description	Indicates Offline Application Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Customer1

Attribute	Description
Name	Customer1
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NATID

Attribute	Description
Name	NATID

Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LANG

Attribute	**Description**
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXISTING

Attribute	**Description**
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CTYPE

Attribute	**Description**
Name	CTYPE
Datatype	String
Description	Indicates Customer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ACLASS

Attribute	**Description**	
Name	ACLASS	
Datatype	String	
Description	Indicates Account Class of Loan Settlement Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ACCNO

Attribute	**Description**	
Name	ACCNO	
Datatype	String	
Description	Indicates Settlement Account Number for the Loan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

SNAME

Attribute	**Description**	
Name	SNAME	
Datatype	String	
Description	Indicates Customer Short Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CNTY

Attribute	**Description**	
Name	CNTY	
Datatype	String	
Description	Indicates Customer Country	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CCAT

Attribute	Description
Name	CCAT
Datatype	String
Description	Indicates Customer Category
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

LINE1

Attribute	Description
Name	LINE1
Datatype	String
Description	Indicates Residence Address Line 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LINE2

Attribute	Description
Name	LINE2

Datatype	String
Description	Indicates Residence Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	Indicates Incorporation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPITAL

Attribute	Description
Name	CAPITAL
Datatype	Number
Description	Indicates Customer Business Capital
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	Indicates Net worth
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUSIDESC

Attribute	Description
Name	BUSIDESC
Datatype	String
Description	Indicates Customer Business Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

INCNTY

Attribute	Description
Name	INCNTY
Datatype	String
Description	Indicates Incorporation Country
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RCNTY

Attribute	Description
Name	RCNTY
Datatype	String
Description	Indicates Residence Country
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CCYAMT

Attribute	Description
Name	CCYAMT
Datatype	String
Description	Indicates Currency in which Financials are Declared
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

Customer3

Attribute	Description
Name	Customer3
Datatype	
Description	Indicates Director Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String

Description	Indicates Email
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DIRNAME

Attribute	**Description**
Name	DIRNAME
Datatype	String
Description	Indicates Director Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDR2

Attribute	**Description**
Name	ADDR2
Datatype	String
Description	Indicates Permanent Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDR3

Attribute	**Description**
Name	ADDR3
Datatype	String
Description	Indicates Permanent Address Line 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTY

Attribute	**Description**
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customer2

Attribute	**Description**
Name	Customer2
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDTYPE

Attribute	Description
Name	ADDTYPE
Datatype	String
Description	Indicates Address Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,R,T,O

TOP

MAILING

Attribute	Description
Name	MAILING
Datatype	String
Description	Indicates whether Mailing Address
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONNO

Attribute	Description
Name	CONNO
Datatype	Number
Description	Indicates Contact Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String

Description	Indicates Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN3

Attribute	**Description**
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ZIP

Attribute	**Description**
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CNTY

Attribute	**Description**
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Financials1

Attribute	**Description**
Name	Financials1
Datatype	
Description	Indicates Customer Financial Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FIXEDASSETS

Attribute	Description
Name	FIXEDASSETS
Datatype	Number
Description	Indicates Fixed Assets
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTANGASSETS

Attribute	Description
Name	INTANGASSETS
Datatype	Number
Description	Indicates Intangible Assets
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONCURRASSETS

Attribute	Description
Name	NONCURRASSETS
Datatype	Number
Description	Indicates Non Current Assets
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBSIDYFRMGOV

Attribute	Description
Name	SUBSIDYFRMGOV
Datatype	Number
Description	Indicates Subsidy Received from Government
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENRESERVES

Attribute	Description
Name	GENRESERVES
Datatype	Number
Description	Indicates General Reserves
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TERMLIAB

Attribute	Description
Name	TERMLIAB
Datatype	Number
Description	Indicates Term Liabilities
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRLIAB

Attribute	Description
Name	CURRLIAB
Datatype	Number
Description	Indicates Current Liabilities
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSUEDCAP

Attribute	Description
Name	ISSUEDCAP
Datatype	Number
Description	Indicates Issued Capital
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAIDUPCAP

Attribute	Description
Name	PAIDUPCAP
Datatype	Number
Description	Indicates Paid Up Capital
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRBALINPL

Attribute	Description
Name	CRBALINPL
Datatype	Number
Description	Indicates Credit Balance in Profit and Loss
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OPACT

Attribute	Description
Name	OPACT
Datatype	Number
Description	Indicates Operations Activities
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INVACT

Attribute	Description
Name	INVACT
Datatype	Number
Description	Indicates Investing Activities
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FINACT

Attribute	Description
Name	FINACT
Datatype	Number
Description	Indicates Financing Activities
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRASSETS

Attribute	Description
Name	CURRASSETS
Datatype	Number
Description	Indicates Current Assets
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collat1

Attribute	Description
Name	Collat1
Datatype	
Description	Indicates Collateral Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLCD

Attribute	Description
Name	COLLCD
Datatype	String
Description	Indicates Collateral Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String

Description	Indicates Collateral Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLCCY

Attribute	**Description**
Name	COLLCCY
Datatype	String
Description	Indicates Collateral Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLVL

Attribute	**Description**
Name	COLLVL
Datatype	Number
Description	Indicates Collateral Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLSTDT

Attribute	**Description**
Name	COLLSTDT
Datatype	Date
Description	Indicates Collateral Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLENDDT

Attribute	**Description**
Name	COLLENDDT
Datatype	Date
Description	Indicates Collateral End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCAT

Attribute	**Description**

Name	COLLCAT
Datatype	String
Description	Indicates Collateral Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	String
Description	Indicates Collateral Haircut Margin
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,M,G

TOP

COLLREVDT

Attribute	Description
Name	COLLREVDT
Datatype	Date
Description	Indicates Collateral Revision Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCHGDT

Attribute	Description
Name	COLLCHGDT
Datatype	String
Description	Indicates Collateral Charge Date
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,L,P,H,A

TOP

COLLREVLDT

Attribute	Description
Name	COLLREVLDT
Datatype	Date
Description	Indicates Collateral Revaluation Date
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLREVCHK

Attribute	Description
Name	COLLREVCHK
Datatype	String
Description	Indicates whether Collateral Revaluation is Required
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

NOMUNITVL

Attribute	Description
Name	NOMUNITVL
Datatype	Number
Description	Indicates Nominal Unit Value
Attributes	Attribute: minOccurs — Description: 0

TOP

CAPAMT

Attribute	Description
Name	CAPAMT

Datatype	Number
Description	Indicates Cap Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUAID

Attribute	Description
Name	GUAID
Datatype	String
Description	Indicates Guarantor Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RATIN

Attribute	Description
Name	RATIN
Datatype	String
Description	Indicates Rating
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LNKPCTNO

Attribute	Description
Name	LNKPCTNO
Datatype	Number
Description	Indicates Linkage Percentage
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKAMT

Attribute	Description
Name	LNKAMT
Datatype	Number
Description	Indicates Linkage Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collat2

Attribute	Description
Name	Collat2
Datatype	
Description	Indicates Collateral Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMON

Attribute	Description
Name	STMON
Datatype	String
Description	Indicates Start Month

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REM

Attribute	**Description**	
Name	REM	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVNM

Attribute	**Description**	
Name	COVNM	
Datatype	String	
Description	Indicates Covenant Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Covenant Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REVDT

Attribute	**Description**	
Name	REVDT	
Datatype	Date	
Description	Indicates Revision Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANDT

Attribute	Description
Name	MANDT
Datatype	Date
Description	Indicates whether it is Mandatory
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRCDAY

Attribute	Description
Name	GRCDAY
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	Indicates Notice Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Vehdetails

Attribute	Description
Name	Vehdetails
Datatype	
Description	Indicates Vehicle Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_IDNUM

Attribute	Description
Name	VEH_IDNUM
Datatype	String
Description	Indicates Vehicle Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VEH_YEAR

Attribute	Description
Name	VEH_YEAR
Datatype	Number
Description	Indicates Vehicle Year
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VEH_MAKE

Attribute	Description
Name	VEH_MAKE
Datatype	String
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VEH_MODEL

Attribute	Description
Name	VEH_MODEL
Datatype	String
Description	Indicates Vehicle Model
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VEH_BDYSTYLE

Attribute	Description
Name	VEH_BDYSTYLE
Datatype	String

Description	Indicates Vehicle Body Style
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VEH_USAGE

Attribute	**Description**
Name	VEH_USAGE
Datatype	String
Description	Indicates Vehicle Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Financials2

Attribute	**Description**
Name	Financials2
Datatype	
Description	Indicates Customer Liability Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

LIABTYP

Attribute	Description	
Name	LIABTYP	
Datatype	String	
Description	Indicates Liability Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	LO,LE,RE,OT

TOP

LIABSUB

Attribute	Description	
Name	LIABSUB	
Datatype	String	
Description	Indicates Liability Sub Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

LIABFREQ

Attribute	Description	
Name	LIABFREQ	
Datatype	String	
Description	Indicates Liability Frequency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y

TOP

LAIBAMT

Attribute	Description	
Name	LAIBAMT	
Datatype	Number	
Description	Indicates Liability Amount	
Attributes	Attribute	Description
	minOccurs	0

TOP

BAL

Attribute	Description
Name	BAL
Datatype	Number
Description	Indicates Liability Outstanding Balance
Attributes	Attribute: minOccurs, Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

LIABSTDT

Attribute	Description
Name	LIABSTDT
Datatype	Date
Description	Indicates Liability Start Date
Attributes	Attribute: minOccurs, Description: 0

TOP

LIABENDDT

Attribute	Description
Name	LIABENDDT
Datatype	Date
Description	Indicates Liability End Date
Attributes	Attribute: minOccurs, Description: 0

TOP

Finsummary

Attribute	Description
Name	Finsummary
Datatype	
Description	Indicates Asset Details
Attributes	Attribute: minOccurs, Description: 0

TOP

MONACTINC

Attribute	Description
Name	MONACTINC
Datatype	Number
Description	Indicates Monthly Actual Income
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTDEBT

Attribute	Description
Name	MONACTDEBT
Datatype	Number
Description	Indicates Monthly Actual Debt
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRADE

Attribute	Description
Name	GRADE
Datatype	String
Description	Indicates Internal Final Grade
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

WHTPMT

Attribute	Description
Name	WHTPMT
Datatype	Number
Description	Indicates What if Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Finsummary2

Attribute	Description
Name	Finsummary2
Datatype	
Description	Indicates Consolidated Financial Summary Information
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Investi1

Attribute	Description
Name	Investi1
Datatype	
Description	Indicates Investigation Summary
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VERTYPE

Attribute	Description
Name	VERTYPE
Datatype	String
Description	Indicates Verification Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGENCY

Attribute	Description
Name	AGENCY
Datatype	String
Description	Indicates Investigating Agency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custdedupe

Attribute	Description

Name	Custdedupe
Datatype	
Description	Indicates Possible Duplicate Customer Names
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CTYPE

Attribute	**Description**
Name	CTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

LSTNM

Attribute	**Description**
Name	LSTNM
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNAME

Attribute	**Description**
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NATID

Attribute	Description
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCAT

Attribute	Description
Name	CCAT
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	Indicates Customer Date of Birth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	Indicates Email
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EXISTING

Attribute	Description
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASSNO

Attribute	Description
Name	PASSNO
Datatype	String
Description	Indicates Customer Passport Number

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Customer Mobile Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Customer Landline Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Financials3

Attribute	Description
Name	Financials3
Datatype	
Description	Indicates Customer Income Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INCTYPE

Attribute	Description
Name	INCTYPE
Datatype	String
Description	Indicates Income Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,R,B,O

TOP

CCY

Attribute	Description

Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Cusudf

Attribute	**Description**
Name	Cusudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String

Description	

TOP

Facility

Attribute	Description
Name	Facility
Datatype	
Description	Indicates Facility Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINECD

Attribute	Description
Name	LINECD
Datatype	String
Description	Indicates Line Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINESER

Attribute	Description
Name	LINESER
Datatype	Number
Description	Indicates Line Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String

Description	Indicates Pool Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTID

Attribute	**Description**
Name	CUSTID
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNM

Attribute	**Description**
Name	CUSTNM
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LIMAMT

Attribute	**Description**
Name	LIMAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	Indicates Purpose
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAINLINE

Attribute	Description
Name	MAINLINE
Datatype	String
Description	Indicates Main Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CCYRES

Attribute	Description
Name	CCYRES
Datatype	String
Description	Indicates Currency Restriction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINENCCY

Attribute	Description
Name	LINENCCY
Datatype	String
Description	Indicates Line Currency
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVLINE

Attribute	Description
Name	REVLINE
Datatype	String
Description	Indicates whether Revolving Line
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

LINESTDT

Attribute	Description
Name	LINESTDT
Datatype	Date
Description	Indicates Line Start Date
Attributes	Attribute: minOccurs, Description: 0

TOP

LINEEXPDT

Attribute	Description
Name	LINEEXPDT
Datatype	Date
Description	Indicates Line Expiry Date
Attributes	Attribute: minOccurs, Description: 0

TOP

LSTNEWUTLDT

Attribute	Description
Name	LSTNEWUTLDT
Datatype	Date
Description	Indicates Last New Utilization Date
Attributes	Attribute: minOccurs, Description: 0

TOP

INTREM

Attribute	Description
Name	INTREM
Datatype	String
Description	Indicates Internal Remarks
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number
Description	Indicates Limit Amount
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABBR

Attribute	Description
Name	LIABBR
Datatype	String
Description	Indicates Liability Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LMTAMTBASIS

Attribute	Description
Name	LMTAMTBASIS
Datatype	String
Description	Indicates Limit Amount Basis

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,L,M

TOP

INTREQD

Attribute	Description	
Name	INTREQD	
Datatype	String	
Description	Indicates whether Fee needs to be Collected	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DSPEFFLINEAMT

Attribute	Description	
Name	DSPEFFLINEAMT	
Datatype	Number	
Description	Indicates Effective Line Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Factenor

Attribute	Description	
Name	Factenor	
Datatype		
Description	Indicates Facility Tenor	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LINECD

Attribute	Description	
Name	LINECD	
Datatype	String	
Description	Indicates Line Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINESER

Attribute	Description
Name	LINESER
Datatype	Number
Description	Indicates Line Serial Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TNRMNEMONIC

Attribute	Description
Name	TNRMNEMONIC
Datatype	String
Description	Indicates Tenor Mnemonic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIMIT

Attribute	Description
Name	LIMIT
Datatype	Number
Description	Indicates Limit Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

UTILIZATION

Attribute	Description
Name	UTILIZATION
Datatype	Number
Description	Indicates Utilization
Attributes	Attribute: minOccurs — Description: 0

TOP

Pool

Attribute	Description
Name	Pool
Datatype	
Description	Indicates Pool Details
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABID

Attribute	Description
Name	LIABID
Datatype	String
Description	Indicates Liability Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

POOLCCY

Attribute	Description
Name	POOLCCY

Datatype	String
Description	Indicates Pool Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POOLAMT

Attribute	Description
Name	POOLAMT
Datatype	Number
Description	Indicates Pool Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLUTL

Attribute	Description
Name	POOLUTL
Datatype	Number
Description	Indicates Pool Utilization
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Crapp

Attribute	Description
Name	Crapp
Datatype	
Description	Indicates Credit Application Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BORROWPRF

Attribute	Description
Name	BORROWPRF
Datatype	String
Description	Indicates Borrower Profile
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

FINPER

Attribute	Description
Name	FINPER
Datatype	String
Description	Indicates Financial Performance
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BORRMKTPOS

Attribute	Description
Name	BORRMKTPOS
Datatype	String
Description	Indicates Borrower Market Position
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RSKMIT

Attribute	Description
Name	RSKMIT
Datatype	String
Description	Indicates Risk Mitigants
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RSKDEPTMIT

Attribute	Description
Name	RSKDEPTMIT

Datatype	String
Description	Indicates Risk Department Mitigants
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RSKDEPASSES

Attribute	Description
Name	RSKDEPASSES
Datatype	String
Description	Indicates Risk Department Assessment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACPROP

Attribute	Description
Name	FACPROP
Datatype	String
Description	Indicates Facilities Proposed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

APRFAC

Attribute	Description
Name	APRFAC
Datatype	String
Description	Indicates Approved Facilities
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RECOM

Attribute	Description
Name	RECOM
Datatype	String
Description	Indicates Recommendation

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TERMANDCOND

Attribute	**Description**	
Name	TERMANDCOND	
Datatype	String	
Description	Indicates Terms and Conditions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Cust-Acct

Attribute	**Description**	
Name	Cust-Acct	
Datatype		
Description	Indicates Customer Account Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates Customer Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ACCLS

Attribute	**Description**	
Name	ACCLS	
Datatype	String	
Description	Indicates Account Class of Customer Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates Customer Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACODE

Attribute	Description
Name	ACODE
Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCYTYPE

Attribute	Description
Name	CCYTYPE
Datatype	String
Description	Indicates Currency Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Requested1

Attribute	**Description**
Name	Requested1
Datatype	
Description	Indicates Overall Loan Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

REQAMT

Attribute	Description
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TENORM

Attribute	Description
Name	TENORM
Datatype	Number
Description	Indicates Loan Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

PROMO

Attribute	Description
Name	PROMO
Datatype	String
Description	Indicates Promotion Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates Request Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

Requested2

Attribute	Description
Name	Requested2
Datatype	
Description	Indicates Individual Request Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

APPNO

Attribute	Description

Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ITEMIZATION

Attribute	**Description**
Name	ITEMIZATION
Datatype	String
Description	Indicates Itemization Details
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REQAMT

Attribute	**Description**
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Loan2

Attribute	**Description**
Name	Loan2
Datatype	
Description	Indicates Individual Loan Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANCCY

Attribute	Description
Name	LOANCCY
Datatype	String
Description	Indicates Loan Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	Indicates Loan Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENURE

Attribute	Description
Name	TENURE
Datatype	Number
Description	Indicates Loan Tenure
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DPMT

Attribute	Description
Name	DPMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAX

Attribute	Description
Name	TAX
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFINST

Attribute	Description
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	Number	
Description	Indicates Frequency	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREAD

Attribute	Description	
Name	SPREAD	
Datatype	String	
Description	Indicates Interest Spread	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

EFFRATE

Attribute	Description	
Name	EFFRATE	
Datatype	String	
Description	Indicates Effective Interest Rate	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

TOP

CLACCNO

Attribute	Description	
Name	CLACCNO	
Datatype	String	
Description	Indicates CL Account Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	50

TOP

Loan3

Attribute	Description
Name	Loan3
Datatype	
Description	Indicates Loan Schedule Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NO1

Attribute	Description
Name	NO1
Datatype	Number
Description	Indicates No of Schedules
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Frequency Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHTYP

Attribute	Description
Name	SCHTYP
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / P,D,R

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loan4

Attribute	Description
Name	Loan4
Datatype	
Description	Indicates Exploded Schedule Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHNO

Attribute	Description
Name	SCHNO
Datatype	Number

Description	Indicates Schedule No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EMI_AMOUNT

Attribute	Description
Name	EMI_AMOUNT
Datatype	Number
Description	Indicates EMI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMORPRI

Attribute	Description
Name	AMORPRI
Datatype	Number
Description	Indicates Amortized Principal
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTEREST_AMOUNT

Attribute	Description
Name	INTEREST_AMOUNT
Datatype	Number
Description	Indicates Interest Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

CAPI

Attribute	Description	
Name	CAPI	
Datatype	String	
Description	Indicates Capitalized Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

WAIVE

Attribute	Description	
Name	WAIVE	
Datatype	String	
Description	Indicates whether Schedule is Waived	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNM

Attribute	Description	
Name	COMPNM	
Datatype	String	
Description	Indicates Component Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Comments

Attribute	Description	
Name	Comments	
Datatype		
Description	Indicates Comment Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SEQUENCENUMBER

Attribute	Description
Name	SEQUENCENUMBER
Datatype	String
Description	Indicates Comment Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comment Given
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMBY

Attribute	Description

Name	COMMBY
Datatype	String
Description	Indicates User who input Comment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COMMDT

Attribute	Description
Name	COMMDT
Datatype	Date
Description	Indicates Comment Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Udf

Attribute	Description
Name	Udf
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

B1

Attribute	Description
Name	B1
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B2

Attribute	Description
Name	B2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B3

Attribute	Description
Name	B3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B4

Attribute	Description
Name	B4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B5

Attribute	Description
Name	B5
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B6

Attribute	Description
Name	B6
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Chklst1

Attribute	Description
Name	Chklst1
Datatype	
Description	Indicates Checklist Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CHKLSTID

Attribute	Description
Name	CHKLSTID
Datatype	String
Description	Indicates Checklist Id
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKLSTDESC

Attribute	Description
Name	CHKLSTDESC
Datatype	String
Description	Indicates Checklist Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

VERIFY

Attribute	Description
Name	VERIFY
Datatype	String
Description	Indicates Verified By
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Custudf

Attribute	Description
Name	Custudf
Datatype	

Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

Tradein

Attribute	Description
Name	Tradein
Datatype	
Description	Indicates Trade In Asset Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ASSETTYP

Attribute	Description
Name	ASSETTYP
Datatype	String
Description	Indicates Asset Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETWHVL

Attribute	Description
Name	ASSETWHVL
Datatype	Number
Description	Indicates Wholesale Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ASSETBSVL

Attribute	Description
Name	ASSETBSVL
Datatype	Number
Description	Indicates Asset Base Value

Attributes	Attribute	Description
	minOccurs	0

TOP

PAYAMT

Attribute	Description
Name	PAYAMT
Datatype	Number
Description	Indicates Asset Payment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

ASSETADDON1

Attribute	Description
Name	ASSETADDON1
Datatype	Number
Description	Indicates Asset Add-on Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

TOTVAL

Attribute	Description
Name	TOTVAL
Datatype	Number
Description	Indicates Asset Total Value
Attributes	Attribute: minOccurs — Description: 0

TOP

Loanoffers

Attribute	Description
Name	Loanoffers
Datatype	
Description	Indicates Loan Offer Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

OFFID

Attribute	Description
Name	OFFID
Datatype	String
Description	Indicates Offer Id

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFINST

Attribute	Description
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	Indicates Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Interest Rate Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECK

Attribute	Description
Name	CHECK
Datatype	String
Description	Indicates whether Offer Needs to be Applied
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Crdratout

Attribute	Description
Name	Crdratout

Datatype	
Description	Indicates External Credit Rating Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTAGEN

Attribute	**Description**
Name	EXTAGEN
Datatype	String
Description	Indicates External Credit Rating Agency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECOMM

Attribute	**Description**
Name	RECOMM
Datatype	String
Description	Indicates External Credit Rating Agency Final Recommendation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

Crdratin

Attribute	**Description**
Name	Crdratin
Datatype	
Description	Indicates Internal Credit Rating Details of Loan Application
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	Indicates Internal Credit Rating Rule Id used
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Crratin2

Attribute	Description
Name	Crratin2
Datatype	
Description	Indicates Internal Credit Rating Details by Customer
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description

Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

QUES

Attribute	Description
Name	QUES
Datatype	String
Description	Indicates Credit Rating Question
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ANS

Attribute	Description
Name	ANS
Datatype	String
Description	Indicates Answer to Credit Rating Question
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CAT

Attribute	Description
Name	CAT
Datatype	String
Description	Indicates Credit Rating Question Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Bureau

Attribute	Description
Name	Bureau
Datatype	
Description	Indicates Credit Bureau Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

BUREAU

Attribute	Description	
Name	BUREAU	
Datatype	String	
Description	Indicates Credit Bureau	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

RPTTYP

Attribute	Description	
Name	RPTTYP	
Datatype	String	
Description	Indicates Bureau Report Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates Bureau Information Retrieval Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,C

ORACLE

TOP

Chgs

Attribute	Description
Name	Chgs
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Charge Collection Event
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTSETT

Attribute	Description
Name	AMTSETT
Datatype	Number

Description	Indicates Charge Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDUEDT

Attribute	**Description**
Name	SCHDUEDT
Datatype	Date
Description	Indicates Charge Due Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

WAIV

Attribute	**Description**
Name	WAIV
Datatype	String
Description	Indicates whether Charge is Waived
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNM

Attribute	**Description**
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Loandedupe

Attribute	**Description**
Name	Loandedupe
Datatype	
Description	Indicates Other Loan Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	Indicates Loan Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Income Amount	
Attributes	Attribute	Description
	minOccurs	0

TOP

OUTSTAMT

Attribute	Description	
Name	OUTSTAMT	
Datatype	Number	
Description	Indicates Outstanding Loan Amount	
Attributes	Attribute	Description
	minOccurs	0

TOP

RATE

Attribute	Description	
Name	RATE	
Datatype	Number	
Description	Indicates Interest Rate	
Attributes	Attribute	Description
	minOccurs	0

TOP

Riskfactor

Attribute	Description	
Name	Riskfactor	
Datatype		
Description	Indicates Risk Factor Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

2.3.AuthSTTypeMnt

Authorization of Card Type Maintenance

2.3.1.ST-AuthSTTypeMnt-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *St-Debit-Card-Type-IO*
      - *CARDTYPE*
      - *MODNO*
    - *St-Debit-Card-Type-Full*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *CARDBIN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*

St-Debit-Card-Type-Detail

CARDTYPE

CARDBIN1

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

St-Debit-Card-Type-Full

Attribute	Description
Name	St-Debit-Card-Type-Full
Datatype	
Description	Include full details about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CARDBIN

Attribute	Description	
Name	CARDBIN	
Datatype	String	
Description	Indicates Card Bin	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Time when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User Id who has Authorized the creation\modification of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	**Description**
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.2.ST-AuthSTTypeMnt-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *St-Debit-Card-Type-PK*
      - *CARDTYPE*
    - *St-Debit-Card-Type-IO*
      - *CARDTYPE*
      - *MODNO*
    - *St-Debit-Card-Type-Full*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *CARDBIN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *St-Debit-Card-Type-Detail*

CARDTYPE

CARDBIN1

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

St-Debit-Card-Type-PK

Attribute	Description
Name	St-Debit-Card-Type-PK
Datatype	
Description	Includes primary key details about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Includes details about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

St-Debit-Card-Type-Full

Attribute	**Description**
Name	St-Debit-Card-Type-Full
Datatype	
Description	Includes Full details about debit card type.

TOP

CARDTYPE

Attribute	**Description**	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CARDBIN

Attribute	Description
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 2; Restrictions: minLength, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded; Attribute: minOccurs, Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.3.ST-AuthSTTypeMnt-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *St-Debit-Card-Type-Full*
    - *CARDTYPE*
    - *DESCRIPTION*
    - *CARDBIN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *St-Debit-Card-Type-Detail*
      - *CARDTYPE*
      - *CARDBIN1*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

St-Debit-Card-Type-Full

Attribute	Description

Name	St-Debit-Card-Type-Full
Datatype	
Description	Includes full details about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Cardtype
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CARDBIN

Attribute	Description
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORACLE

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Cardtype
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME

Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.3.4.ST-AuthSTTypeMnt-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *St-Debit-Card-Type-IO*
    - *CARDTYPE*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

2.4.AuthorizeACRSMaint

Authorization of Automatic Consolidated Statement Request

2.4.1.ST-AuthorizeACRSMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description

Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRANCD

Attribute	Description
Name	BRANCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREEQUENCY

Attribute	Description
Name	FREEQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,S,A

TOP

STARTMON

Attribute	Description
Name	STARTMON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LASTEXEDATE

Attribute	Description
Name	LASTEXEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	Description	
Name	CHARGEBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	Description	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

2.4.2.ST-AuthorizeACRSMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-IO*
    - *REFERENCENO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.4.3.ST-AuthorizeACRSMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description
Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCD

Attribute	Description	
Name	BRANCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date

Attributes	Attribute	Description
	minOccurs	0

TOP

FREEQUENCY

Attribute	Description	
Name	FREEQUENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,S,A

TOP

STARTMON

Attribute	Description	
Name	STARTMON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description	
Name	STARTON	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

LASTEXEDATE

Attribute	Description	
Name	LASTEXEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

E-STATEMENT

Attribute	Description

Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the Transaction Status O - Open C - Close	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Auto-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Auto-Crs-Master-IO*
      - *REFERENCENO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Auto-Crs-Master-PK

Attribute	Description
Name	Sttm-Auto-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.5.AuthorizeAccClasMaint

Authorisation of Account Class maintenance

2.5.1.ST-AuthorizeAccClasMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-Full*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *ACCTYPE*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*

ACCSTMNTTYPT
ACCSTMNTCYCL3
OFFLNLMT
AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS

DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS
MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE

BALRPTTYP
STARTDT
STMNTPARAM1
STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT

INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN
ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*

- *DR_CB*
- *DR_LINE*
- *DR_HO*
- *RBKPROVSN*
- *STAT*
- *TXTSTATDESC*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation

- *ACCCLS*
- *SEQNO*
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint

- *BLCKNGORDR*
- *PRDCD*
- *PRDDESC*

Products

- *PRDCD*
- *PRDDESC*
- *DRTXN*
- *CRTXN*

Transaction-Codes

- *TXNCD*
- *TRNDESC*
- *DRTXN*
- *CRTXN*

Branch-Restriction

- *BRNCD*

Ccy-Restriction

- *CCYCD*

Ccy-Preferences

- *CCYCD*
- *MINBAL*

- *ATMCSHLMT*
- *ATMTRNSLMT*
- *TRUSTACCASHLIMIT*
- *MINIMUM_OPENING_BALANCE*
- *ACCOUNT_OPENING_CHARGES*
- *THRESHOLD_AMOUNT*

Cat-Restriction

- *CUSTCAT*

Cust-Restriction

- *CUSTNO*
- *ALLWD*

Interim-Dramt

- *CCY*
- *AMT*

Interim-Cramt

- *CCY*
- *AMT*

Msg-Gentime

- *GENTIM*

Msg-Gentime1

- *GENTIM*

Notice-Pref

- *ADVINTREQD*
- *MNTHLYFREEAMT*
- *NOTCPRD*
- *VALDITYPRD*

Aclass-Doctype

- *CUSTOMER_TYPE*
- *DOCUMENT_TYPE*
- *MANDATORY*

Sttms-Accls-Minmax-Amt-Ccy

- *CCY*
- *MIN_AMOUNT*
- *MAX_AMOUNT*
- *TOPUP_UNITS*

Dep-Accls-Rest

- *AC_CLASS*
- *ADESC*

Denom-Deposit

- *DENOMINATION_ID*
- *DENOMINATION_DESC*
- *DENOMINATION_VALUE*
- *CURRENCY*

Deposit-Ccy-Pref

- *ACCCCY*
- *Deposit-Ccy-Pref-Dtl*
  - *CURRENCY*
  - *PAYIN*
  - *INT_PAYOUT_C*
  - *PRI_PAYOUT_C*
- *Exrate-Pref*
  - *PAYINOUT_C*
  - *MODE_TYPE_C*
  - *RATETYPE_C*
  - *RATECODE_C*
  - *VARIANCE_C*
- *Chan-Rest-C*
  - *CHANLID*
  - *CHANNDESC*
- *Minmax-Ccy-C*
  - *CURR*
  - *CHANLID*
  - *MIN_AMOUNT*
  - *MAX_AMOUNT*
  - *TOPUP_UNITS*
- *Dorm-Param*
  - *ACCOUNT_CLASS*
  - *LCY_BALANCE*
  - *FREQUENCY*
  - *DORM_PREP_SEL_METH*
  - *DORM_PREP_DATE*
  - *DORM_PREP_NTH*
  - *DORM_PREP_DAY*
  - *DORM_PREP_MONTH*
  - *DORM_PREP_ACTION*
  - *DORM_PROC_SEL_METH*
  - *DORM_PROC_DATE*
  - *DORM_PROC_NTH*
  - *DORM_PROC_DAY*
  - *DORM_PROC_MONTH*
  - *DORM_GL*
  - *DORM_TRN_CODE*
  - *DORM_ADV_GEN*
  - *DORM_STOP_IC*
- *UDFDETAILS*
  - *FLDNAM*
  - *FLDVAL*
- *Misaccdflt*

MISCODE2
MISCODE3
MISCODE4
MISCODE5
MISCODE6
MISCODE7
MISCODE8
MISCODE9
MISCODE10
COSTCODE1
COSTCODE2
COSTCODE3
COSTCODE4
COSTCODE5
ACCLASS
MISGROUP
POOLCODE
MISCODE1
MISCLASS1
MISCLASS2
MISCLASS3
MISCLASS4
MISCLASS5
MISCLASS6
MISCLASS7
MISCLASS8
MISCLASS9
MISCLASS10
LINKTOGROUP
Status-Control

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Account-Class-Master-Full

Attribute	Description
Name	Account-Class-Master-Full
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DESC

Attribute	Description
Name	DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCCD

Attribute	**Description**
Name	ACCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ENDDT

Attribute	**Description**
Name	ENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRMNCY

Attribute	**Description**
Name	DRMNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACSTFORMT

Attribute	**Description**
Name	ACSTFORMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

DRMNTPRM

Attribute	Description
Name	DRMNTPRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description
Name	ACCSTMNTCYCL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	**Description**
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	**Description**
Name	ACCSTMNTCYCL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	**Description**
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTPROVREQD

Attribute	**Description**
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVSNGFREQ

Attribute	**Description**
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,D

TOP

PROVCCYTYP

Attribute	**Description**
Name	PROVCCYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,A

TOP

EXPSRCAT

Attribute	**Description**
Name	EXPSRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EVNTCLSCD

Attribute	**Description**
Name	EVNTCLSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

DRINTUSNGRECV

Attribute	Description
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	Description
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	Description
Name	DRINTNOTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTLIQDAY

Attribute	Description
Name	DRINTLIQDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,A

TOP

CHGSTRTADV

Attribute	Description
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCDAYS

Attribute	Description
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREBNKNGDAYS

Attribute	Description
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDLST

Attribute	Description
Name	PRDLST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

CUSATLST

Attribute	Description
Name	CUSATLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	Description
Name	DEF_AUTODEP_AC_CLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

AUTDEPTRNCD

Attribute	Description
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AUTDEPCCY

Attribute	Description
Name	AUTDEPCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBALREQD

Attribute	**Description**
Name	MINBALREQD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPMLTPLOF

Attribute	**Description**
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKDEPOSITFRST

Attribute	**Description**
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDEPDERRATCD

Attribute	**Description**
Name	AUTDEPDERRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOROLL

Attribute	Description
Name	AUTOROLL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSONMATURTY

Attribute	Description
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRTLLIQDTN

Attribute	Description
Name	PRTLLIQDTN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	Description
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRACEPRD

Attribute	Description
Name	GRACEPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRDAYS

Attribute	Description
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRMNTHS

Attribute	Description
Name	MINTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRMNTHS

Attribute	Description

Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNRYRS

Attribute	**Description**
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDFLG

Attribute	**Description**
Name	RDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RDMVMATTOUNCLMD

Attribute	**Description**
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MOVEFUNDOVD

Attribute	**Description**
Name	MOVEFUNDOVD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LMTCHKREQD

Attribute	Description	
Name	LMTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OVRDRFTFACLTY

Attribute	Description	
Name	OVRDRFTFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASBKFACLTY

Attribute	Description	
Name	PASBKFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRCKRECBLE

Attribute	Description	
Name	TRCKRECBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCSTATS

Attribute	Description
Name	ACCSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description
Name	EXCLSAMDYRVRTRNSFMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description
Name	ALLWBCKPRDENTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CONSOLDTNREQD

Attribute	Description
Name	CONSOLDTNREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ICINCLSN

Attribute	Description
Name	ICINCLSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRCKACCREDIC

Attribute	Description
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

HASDRCRADV

Attribute	Description
Name	HASDRCRADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	**Description**
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	**Description**
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	**Description**
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	**Description**
Name	STATCHNGAUTMATIC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ILMAPPLICBL

Attribute	Description	
Name	ILMAPPLICBL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ATMFACLTY

Attribute	Description	
Name	ATMFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNT

Attribute	Description	
Name	GENINTRIMSTMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description	
Name	GENINTRIMSTMNTONMVMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GENBALRPT

Attribute	**Description**
Name	GENBALRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTRIMRPTSNCE

Attribute	**Description**
Name	INTRIMRPTSNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	**Description**
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	**Description**
Name	BALRPTSINCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 941,940,950,

TOP

BALRPTTYP

Attribute	Description
Name	BALRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STMNTPARAM1

Attribute	Description
Name	STMNTPARAM1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM2

Attribute	Description
Name	STMNTPARAM2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM3

Attribute	Description
Name	STMNTPARAM3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

ESCROWPROCESS

Attribute	**Description**
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNCODE

Attribute	**Description**
Name	TRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNREVCODE

Attribute	**Description**
Name	TRNREVCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINOR_MAJOR

Attribute	**Description**
Name	MINOR_MAJOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description	
Name	REPL_CUST_SIG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description	
Name	MAX_NO_CHEQUE_REJECTIONS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SAL_BLK_DAYS

Attribute	Description	
Name	SAL_BLK_DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description	
Name	DAYSUNAUTHNOACTIVITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description
Name	SETTLE_BRIDGE_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PCTXNCODE

Attribute	Description
Name	PCTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TDRATECHARTALLOW

Attribute	Description
Name	TDRATECHARTALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLUSTER_ID

Attribute	Description
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PROJECTACCNT

Attribute	Description
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	Description
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

LRGDRBALFLG

Attribute	Description	
Name	LRGDRBALFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNOVR_CODE

Attribute	Description	
Name	TRNOVR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FREQUENCY

Attribute	Description	
Name	FREQUENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y,

TOP

DAYS

Attribute	Description	
Name	DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SEND_NOTIFICATION

Attribute	Description	
Name	SEND_NOTIFICATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	Description	
Name	RT_CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SPDANLSYS

Attribute	Description	
Name	SPDANLSYS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description

Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	**Description**
Name	COMP_WISE_TRACKING_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENABLE_SWEEP_IN

Attribute	**Description**
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	**Description**
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEPACCCLS

Attribute	**Description**
Name	DEPACCCLS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

RATECHARTTENOR

Attribute	**Description**
Name	RATECHARTTENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,

TOP

HOLIDAYCALENDAR

Attribute	**Description**
Name	HOLIDAYCALENDAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	**Description**
Name	HOLIDAYMOVEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	**Description**
Name	MOVEACROSSMONTHS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	A,S,N,

TOP

ADHOCHOL

Attribute	Description	
Name	ADHOCHOL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description	
Name	APPLICABLEDEPTENOR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description	
Name	MONTHENDDEPOSIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DENM_DEPOSIT

Attribute	Description	
Name	DENM_DEPOSIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description
Name	REPCKUPACCLSTNRONROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFERREDBALUPD

Attribute	Description
Name	DEFERREDBALUPD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MULTICURRENCY

Attribute	Description
Name	MULTICURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MONTHS_C

Attribute	Description
Name	MONTHS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

INSTBASIS

Attribute	Description
Name	INSTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NOTICE_DEPOSIT

Attribute	Description
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	Description
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTICE_DAYS

Attribute	Description
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BONUS_INTEREST_C

Attribute	Description
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRANSACTION_CODE

Attribute	Description
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	Description
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UNCLAIMED_DAYS

Attribute	Description
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NC_DEPOSIT_C

Attribute	Description
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Status-Master

Attribute	Description	
Name	Status-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CR_CB

Attribute	Description	
Name	CR_CB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CR_LINE

Attribute	Description	
Name	CR_LINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CR_HO

Attribute	Description	
Name	CR_HO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DR_CB

Attribute	Description
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DR_LINE

Attribute	Description
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DR_HO

Attribute	Description
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TXTSTATDESC

Attribute	Description
Name	TXTSTATDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Status-Detail

Attribute	Description
Name	Status-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Status-Derivation

Attribute	Description
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	6

TOP

SEQNO

Attribute	Description	
Name	SEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

STATRUL1

Attribute	Description	
Name	STATRUL1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL2

Attribute	Description	
Name	STATRUL2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL3

Attribute	Description
Name	STATRUL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL4

Attribute	Description
Name	STATRUL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL5

Attribute	Description
Name	STATRUL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

COMPONENT_PRIORITY1

Attribute	Description
Name	COMPONENT_PRIORITY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	**Description**
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	**Description**
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BLCKNGORDR

Attribute	**Description**
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRTXN

Attribute	Description

Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Transaction-Codes

Attribute	**Description**
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TXNCD

Attribute	**Description**
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNDESC

Attribute	**Description**
Name	TRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DRTXN

Attribute	Description	
Name	DRTXN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CRTXN

Attribute	Description	
Name	CRTXN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Branch-Restriction

Attribute	Description	
Name	Branch-Restriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

Ccy-Restriction

Attribute	Description
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Interim-Cramt

Attribute	Description
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	Description
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MANDATORY

Attribute	**Description**
Name	MANDATORY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	**Description**
Name	Sttms-Accls-Minmax-Amt-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MIN_AMOUNT

Attribute	**Description**
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Denom-Deposit

Attribute	Description	
Name	Denom-Deposit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DENOMINATION_ID

Attribute	Description	
Name	DENOMINATION_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

DENOMINATION_DESC

Attribute	Description	
Name	DENOMINATION_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

DENOMINATION_VALUE

Attribute	Description	
Name	DENOMINATION_VALUE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	Description
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	Description
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYIN

Attribute	**Description**
Name	PAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_PAYOUT_C

Attribute	**Description**
Name	INT_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRI_PAYOUT_C

Attribute	**Description**
Name	PRI_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Exrate-Pref

Attribute	**Description**
Name	Exrate-Pref
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PAYINOUT_C

Attribute	Description	
Name	PAYINOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,O

TOP

MODE_TYPE_C

Attribute	Description	
Name	MODE_TYPE_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,S

TOP

RATETYPE_C

Attribute	Description	
Name	RATETYPE_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

TOP

RATECODE_C

Attribute	Description	
Name	RATECODE_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

TOP

VARIANCE_C

Attribute	Description
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	Description
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHANNDESC

Attribute	Description
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,W

TOP

DORM_PREP_DATE

Attribute	Description
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PREP_NTH

Attribute	Description
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PREP_DAY

Attribute	Description
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150 Restrictions: minLength — Description: 0

TOP

Misaccdflt

Attribute	Description

Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	**Description**
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	**Description**
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	**Description**
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	**Description**
Name	MISCODE5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCODE6

Attribute	Description
Name	MISCODE6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE7

Attribute	Description
Name	MISCODE7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE8

Attribute	Description
Name	MISCODE8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE9

Attribute	Description
Name	MISCODE9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE3

Attribute	Description
Name	COSTCODE3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE4

Attribute	Description
Name	COSTCODE4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE5

Attribute	Description
Name	COSTCODE5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ACCLASS

Attribute	Description
Name	ACCLASS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

MISGROUP

Attribute	Description
Name	MISGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE1

Attribute	**Description**
Name	MISCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS1

Attribute	**Description**
Name	MISCLASS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS2

Attribute	**Description**
Name	MISCLASS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS3

Attribute	**Description**
Name	MISCLASS3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS4

Attribute	Description
Name	MISCLASS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Status-Control

Attribute	Description
Name	Status-Control
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Account-Class-Master-IO
ACCCLS
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Account-Class-Master-IO

Attribute	Description
Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.5.3.ST-AuthorizeAccClasMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-Full*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *ACCTYPE*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*
    - *ACCSTMNTTYPT*
    - *ACCSTMNTCYCL3*
    - *OFFLNLMT*

AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS
DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS

MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE
BALRPTTYP
STARTDT
STMNTPARAM1

STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT
INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN

ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*
- *DR_CB*
- *DR_LINE*
- *DR_HO*

- *RBKPROVSN*
- *STAT*
- *TXTSTATDESC*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation
- *ACCCLS*
- *SEQNO*
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint
- *BLCKNGORDR*
- *PRDCD*
- *PRDDESC*

Products
- *PRDCD*
- *PRDDESC*
- *DRTXN*
- *CRTXN*

Transaction-Codes
- *TXNCD*
- *TRNDESC*
- *DRTXN*
- *CRTXN*

Branch-Restriction
- *BRNCD*

Ccy-Restriction
- *CCYCD*

Ccy-Preferences
- *CCYCD*
- *MINBAL*
- *ATMCSHLMT*
- *ATMTRNSLMT*
- *TRUSTACCASHLIMIT*

MINIMUM_OPENING_BALANCE
ACCOUNT_OPENING_CHARGES
THRESHOLD_AMOUNT
Cat-Restriction
CUSTCAT
Cust-Restriction
CUSTNO
ALLWD
Interim-Dramt
CCY
AMT
Interim-Cramt
CCY
AMT
Msg-Gentime
GENTIM
Msg-Gentime1
GENTIM
Notice-Pref
ADVINTREQD
MNTHLYFREEAMT
NOTCPRD
VALDITYPRD
Aclass-Doctype
CUSTOMER_TYPE
DOCUMENT_TYPE
MANDATORY
Sttms-Accls-Minmax-Amt-Ccy
CCY
MIN_AMOUNT
MAX_AMOUNT
TOPUP_UNITS
Dep-Accls-Rest
AC_CLASS
ADESC
Denom-Deposit
DENOMINATION_ID
DENOMINATION_DESC
DENOMINATION_VALUE
CURRENCY
Deposit-Ccy-Pref
ACCCCY
Deposit-Ccy-Pref-Dtl
CURRENCY

PAYIN

INT_PAYOUT_C

PRI_PAYOUT_C

Exrate-Pref

PAYINOUT_C

MODE_TYPE_C

RATETYPE_C

RATECODE_C

VARIANCE_C

Chan-Rest-C

CHANLID

CHANNDESC

Minmax-Ccy-C

CURR

CHANLID

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dorm-Param

ACCOUNT_CLASS

LCY_BALANCE

FREQUENCY

DORM_PREP_SEL_METH

DORM_PREP_DATE

DORM_PREP_NTH

DORM_PREP_DAY

DORM_PREP_MONTH

DORM_PREP_ACTION

DORM_PROC_SEL_METH

DORM_PROC_DATE

DORM_PROC_NTH

DORM_PROC_DAY

DORM_PROC_MONTH

DORM_GL

DORM_TRN_CODE

DORM_ADV_GEN

DORM_STOP_IC

UDFDETAILS

FLDNAM

FLDVAL

Misaccdflt

MISCODE2

MISCODE3

MISCODE4

MISCODE5
MISCODE6
MISCODE7
MISCODE8
MISCODE9
MISCODE10
COSTCODE1
COSTCODE2
COSTCODE3
COSTCODE4
COSTCODE5
ACCLASS
MISGROUP
POOLCODE
MISCODE1
MISCLASS1
MISCLASS2
MISCLASS3
MISCLASS4
MISCLASS5
MISCLASS6
MISCLASS7
MISCLASS8
MISCLASS9
MISCLASS10
LINKTOGROUP
Status-Control
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Account-Class-Master-Full

Attribute	Description
Name	Account-Class-Master-Full
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCCD

Attribute	**Description**
Name	ACCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ENDDT

Attribute	**Description**
Name	ENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRMNCY

Attribute	**Description**
Name	DRMNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACSTFORMT

Attribute	**Description**
Name	ACSTFORMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

DRMNTPRM

Attribute	Description
Name	DRMNTPRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description
Name	ACCSTMNTCYCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description	
Name	ACCSTMNTCYCL2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	Description	
Name	ACCSTMNTTYPT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,S,D

TOP

ACCSTMNTCYCL3

Attribute	Description	
Name	ACCSTMNTCYCL3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	Description	
Name	OFFLNLMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A

TOP

EXPSRCAT

Attribute	Description
Name	EXPSRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EVNTCLSCD

Attribute	Description
Name	EVNTCLSCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

DRINTUSNGRECV

Attribute	**Description**
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	**Description**
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	**Description**
Name	DRINTNOTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTLIQDAY

Attribute	**Description**
Name	DRINTLIQDAY
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,A

TOP

CHGSTRTADV

Attribute	Description
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVCDAYS

Attribute	Description
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FREBNKNGDAYS

Attribute	Description
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRDLST

Attribute	Description
Name	PRDLST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

CUSATLST

Attribute	Description
Name	CUSATLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	Description
Name	DEF_AUTODEP_AC_CLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

AUTDEPTRNCD

Attribute	Description
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

AUTDEPCCY

Attribute	Description
Name	AUTDEPCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MINBALREQD

Attribute	Description
Name	MINBALREQD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DEPMLTPLOF

Attribute	Description
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKDEPOSITFRST

Attribute	Description
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTDEPDERRATCD

Attribute	Description
Name	AUTDEPDERRATCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOROLL

Attribute	Description
Name	AUTOROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSONMATURTY

Attribute	Description
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTLLIQDTN

Attribute	Description
Name	PRTLLIQDTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	Description
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GRACEPRD

Attribute	Description
Name	GRACEPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNRDAYS

Attribute	Description
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNRMNTHS

Attribute	Description
Name	MINTNRMNTHS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXTNRMNTHS

Attribute	Description
Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRYRS

Attribute	Description
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDFLG

Attribute	Description
Name	RDFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RDMVMATTOUNCLMD

Attribute	Description
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MOVEFUNDOVD

Attribute	Description
Name	MOVEFUNDOVD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RDMINSCHDLDAYS

Attribute	**Description**
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	**Description**
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	**Description**
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	**Description**
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLYRS

Attribute	**Description**
Name	RDSCHDLYRS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCHKREQD

Attribute	Description
Name	LMTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVRDRFTFACLTY

Attribute	Description
Name	OVRDRFTFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASBKFACLTY

Attribute	Description
Name	PASBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECBLE

Attribute	Description
Name	TRCKRECBLE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCSTATS

Attribute	**Description**	
Name	ACCSTATS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	**Description**	
Name	EXCLSAMDYRVRTRNSFMSTMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBCKPRDENTRY

Attribute	**Description**	
Name	ALLWBCKPRDENTRY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONSOLDTNREQD

Attribute	**Description**	
Name	CONSOLDTNREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ICINCLSN

Attribute	**Description**
Name	ICINCLSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKACCREDIC

Attribute	**Description**
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HASDRCRADV

Attribute	**Description**
Name	HASDRCRADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACSTATDEPST

Attribute	**Description**
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ILMAPPLICBL

Attribute	Description
Name	ILMAPPLICBL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ATMFACLTY

Attribute	Description
Name	ATMFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNT

Attribute	Description
Name	GENINTRIMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENBALRPT

Attribute	**Description**
Name	GENBALRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRIMRPTSNCE

Attribute	**Description**
Name	INTRIMRPTSNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	**Description**
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	**Description**
Name	BALRPTSINCE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	941,940,950,

TOP

BALRPTTYP

Attribute	Description
Name	BALRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STMNTPARAM1

Attribute	Description
Name	STMNTPARAM1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM2

Attribute	Description
Name	STMNTPARAM2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM3

Attribute	Description
Name	STMNTPARAM3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

ESCROWPROCESS

Attribute	Description
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNCODE

Attribute	Description
Name	TRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNREVCODE

Attribute	Description
Name	TRNREVCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINOR_MAJOR

Attribute	Description
Name	MINOR_MAJOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description
Name	REPL_CUST_SIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description
Name	MAX_NO_CHEQUE_REJECTIONS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SAL_BLK_DAYS

Attribute	Description
Name	SAL_BLK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description
Name	DAYSUNAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description	
Name	SETTLE_BRIDGE_GL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRDCAT

Attribute	Description	
Name	PRDCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PCTXNCODE

Attribute	Description	
Name	PCTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TDRATECHARTALLOW

Attribute	Description	
Name	TDRATECHARTALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLUSTER_ID

Attribute	**Description**
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PROJECTACCNT

Attribute	**Description**
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	**Description**
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	**Description**
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

LRGDRBALFLG

Attribute	Description
Name	LRGDRBALFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description
Name	DAYLIGHTLIMIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRNOVR_CODE

Attribute	Description
Name	TRNOVR_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DAYS

Attribute	**Description**
Name	DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEND_NOTIFICATION

Attribute	**Description**
Name	SEND_NOTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	**Description**
Name	RT_CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SPDANLSYS

Attribute	**Description**
Name	SPDANLSYS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description
Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	Description
Name	COMP_WISE_TRACKING_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_SWEEP_IN

Attribute	Description
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	Description
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEPACCCLS

Attribute	Description
Name	DEPACCCLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

RATECHARTTENOR

Attribute	Description
Name	RATECHARTTENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

HOLIDAYCALENDAR

Attribute	Description
Name	HOLIDAYCALENDAR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	Description
Name	HOLIDAYMOVEMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	Description
Name	MOVEACROSSMONTHS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,N,

TOP

ADHOCHOL

Attribute	Description
Name	ADHOCHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description
Name	APPLICABLEDEPTENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description
Name	MONTHENDDEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENM_DEPOSIT

Attribute	Description
Name	DENM_DEPOSIT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description	
Name	REPCKUPACCLSTNRONROLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFERREDBALUPD

Attribute	Description	
Name	DEFERREDBALUPD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MULTICURRENCY

Attribute	Description	
Name	MULTICURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MONTHS_C

Attribute	Description	
Name	MONTHS_C	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

INSTBASIS

Attribute	Description
Name	INSTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_DEPOSIT

Attribute	Description
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	Description
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICE_DAYS

Attribute	Description
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BONUS_INTEREST_C

Attribute	Description
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRANSACTION_CODE

Attribute	Description
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	Description
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNCLAIMED_DAYS

Attribute	**Description**
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NC_DEPOSIT_C

Attribute	**Description**
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

ORACLE

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Status-Master

Attribute	Description
Name	Status-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CR_CB

Attribute	Description
Name	CR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CR_LINE

Attribute	Description
Name	CR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CR_HO

Attribute	Description
Name	CR_HO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_CB

Attribute	**Description**
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_LINE

Attribute	**Description**
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DR_HO

Attribute	**Description**
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RBKPROVSN

Attribute	**Description**
Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

TXTSTATDESC

Attribute	Description	
Name	TXTSTATDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

Status-Detail

Attribute	Description	
Name	Status-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCROL

Attribute	Description	
Name	ACCROL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Status-Derivation

Attribute	Description
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCLS

Attribute	Description
Name	ACCCLS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SEQNO

Attribute	**Description**
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATRUL1

Attribute	**Description**
Name	STATRUL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL2

Attribute	**Description**
Name	STATRUL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL3

Attribute	Description	
Name	STATRUL3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL4

Attribute	Description	
Name	STATRUL4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL5

Attribute	Description	
Name	STATRUL5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

COMPONENT_PRIORITY1

Attribute	Description	
Name	COMPONENT_PRIORITY1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	Description
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	Description
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BLCKNGORDR

Attribute	Description
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRTXN

Attribute	**Description**
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Transaction-Codes

Attribute	**Description**
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNCD

Attribute	**Description**
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRNDESC

Attribute	Description
Name	TRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRTXN

Attribute	Description
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	Description
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Restriction

Attribute	Description
Name	Branch-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Restriction

Attribute	**Description**
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	**Description**
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interim-Cramt

Attribute	**Description**
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	**Description**
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	Description	
Name	Sttms-Accls-Minmax-Amt-Ccy	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Denom-Deposit

Attribute	Description
Name	Denom-Deposit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DENOMINATION_ID

Attribute	Description
Name	DENOMINATION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

DENOMINATION_DESC

Attribute	Description
Name	DENOMINATION_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

DENOMINATION_VALUE

Attribute	Description

Name	DENOMINATION_VALUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	**Description**
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	**Description**
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYIN

Attribute	Description	
Name	PAYIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INT_PAYOUT_C

Attribute	Description	
Name	INT_PAYOUT_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRI_PAYOUT_C

Attribute	Description	
Name	PRI_PAYOUT_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Exrate-Pref

Attribute	Description
Name	Exrate-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAYINOUT_C

Attribute	Description
Name	PAYINOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O

TOP

MODE_TYPE_C

Attribute	Description
Name	MODE_TYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S

TOP

RATETYPE_C

Attribute	Description
Name	RATETYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RATECODE_C

Attribute	Description

Name	RATECODE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

VARIANCE_C

Attribute	**Description**
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	**Description**
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHANLID

Attribute	**Description**
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHANNDESC

Attribute	**Description**
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	Description
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	Description
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_DAY

Attribute	Description
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

Misaccdflt

Attribute	Description
Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	Description
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	Description
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	Description
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	Description
Name	MISCODE5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE6

Attribute	**Description**
Name	MISCODE6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE7

Attribute	**Description**
Name	MISCODE7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE8

Attribute	**Description**
Name	MISCODE8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE9

Attribute	**Description**
Name	MISCODE9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE3

Attribute	Description
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE4

Attribute	Description	
Name	COSTCODE4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE5

Attribute	Description	
Name	COSTCODE5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCLASS

Attribute	Description	
Name	ACCLASS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

TOP

MISGROUP

Attribute	Description	
Name	MISGROUP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS4

Attribute	Description
Name	MISCLASS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Status-Control

Attribute	Description	
Name	Status-Control	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Account-Class-Master-PK*
      - *ACCCLS*
    - *Account-Class-Master-IO*
      - *ACCCLS*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Account-Class-Master-PK

Attribute	Description
Name	Account-Class-Master-PK
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

Account-Class-Master-IO

Attribute	Description
Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.AuthorizeBranch

AuthorizeBranch

2.6.1.ST-AuthorizeBranch-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*

BRNADDR
BRNADDR2
BRNADDR3
SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC

EXTVAL
BRNAVALSTAT
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH

CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
  SWFTADRS
  DESC
Branch-Customer-Params
  STRTCUSTNO
  ENDCUSTNO
  STRTDUMMYCUSTNO
  ENDDUMMYCUSTNO
  START_PID_NO
  END_PID_NO
Branch-Functions
  FUNCID
Branch-Ccy
  CCYCD
  CCYDESC
Branch-Message-Type
  MODULE
  LCYMSGTYP
Dup-Chk
  MODULE1
  DUP_FLG
  DUP_DAY

Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description	
Name	PRNTBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REGNLOFC

Attribute	**Description**
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TIMLVL

Attribute	**Description**
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CNTRYCD

Attribute	**Description**
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

FUNDBRNCH

Attribute	Description
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CODATMBRN

Attribute	Description
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CODINSTID

Attribute	Description
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNADDR3

Attribute	Description
Name	BRNADDR3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SWFTADDR

Attribute	Description
Name	SWFTADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	**Description**
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	**Description**
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	**Description**
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	**Description**
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CONVGL

Attribute	Description
Name	CONVGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONVTXNCD

Attribute	Description
Name	CONVTXNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CURRCYCLE

Attribute	Description
Name	CURRCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLGBRNCD

Attribute	Description
Name	CLGBRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CLRBRN

Attribute	Description
Name	CLRBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

CNTRYCDDESC

Attribute	Description	
Name	CNTRYCDDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SUSPGLSLDESC

Attribute	Description	
Name	SUSPGLSLDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CONTSUSPGLSLDESC

Attribute	Description	
Name	CONTSUSPGLSLDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SUSPGLFCYDESC

Attribute	Description	
Name	SUSPGLFCYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CONTSUSPGLFCYDESC

Attribute	Description
Name	CONTSUSPGLFCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ATMSUSPGLDESC

Attribute	Description
Name	ATMSUSPGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVGLDESC

Attribute	Description
Name	CONVGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVTXNCDDESC

Attribute	Description
Name	CONVTXNCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EXTVAL

Attribute	Description
Name	EXTVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNAVALSTAT

Attribute	Description
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CLRACC

Attribute	**Description**
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OFFSTCLRACC

Attribute	**Description**
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

WEEKHOL1

Attribute	**Description**
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	**Description**
Name	WEELHOL2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description	
Name	CLRBNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MISCCYMISMATCHGRP

Attribute	Description	
Name	MISCCYMISMATCHGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

INTERDICTCHKREQD

Attribute	Description	
Name	INTERDICTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTERDICTTIMOUT

Attribute	Description	
Name	INTERDICTTIMOUT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENTGL

Attribute	Description
Name	ENTGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BCKVALCHKREQD

Attribute	Description
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BCKVALDAYS

Attribute	Description
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRCKPREVYRPRLS

Attribute	Description
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LDAPTEMP

Attribute	Description	
Name	LDAPTEMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

DRPRDDESC

Attribute	Description	
Name	DRPRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CRPRDDESC

Attribute	Description	
Name	CRPRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURRTAXCYCLE

Attribute	Description	
Name	CURRTAXCYCLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONSOLTXCERTREQD

Attribute	Description
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	Description
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUSENTRYREQ

Attribute	Description
Name	SUSENTRYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUSBATCHNO

Attribute	Description
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SUSTXNCODE

Attribute	Description
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVSUSENTRYDAYS

Attribute	Description
Name	REVSUSENTRYDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CASAAMTBLKTRNCODE

Attribute	**Description**
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOFFREQ

Attribute	**Description**
Name	HOFFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWCORPACS

Attribute	**Description**
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFER_TYPE

Attribute	**Description**
Name	TRANSFER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	P,R,

TOP

POSITION_ASSET_GL

Attribute	Description	
Name	POSITION_ASSET_GL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

POSITION_LIABILITY_GL

Attribute	Description	
Name	POSITION_LIABILITY_GL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

GL_CLASSS

Attribute	Description	
Name	GL_CLASSS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CHEQUESTALEDAYS

Attribute	Description	
Name	CHEQUESTALEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FILECONSTXNCODE

Attribute	Description	
Name	FILECONSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CNTRY_CKSUM_MASK

Attribute	Description	
Name	CNTRY_CKSUM_MASK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Branch-Swift-Address

Attribute	Description
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SWFTADRS

Attribute	Description
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYDESC

Attribute	**Description**
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Message-Type

Attribute	**Description**
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE

Attribute	**Description**
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

LCYMSGTYP

Attribute	**Description**
Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	S,M,P,

TOP

Dup-Chk

Attribute	Description	
Name	Dup-Chk	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MODULE1

Attribute	Description	
Name	MODULE1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

DUP_FLG

Attribute	Description	
Name	DUP_FLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DUP_DAY

Attribute	Description	
Name	DUP_DAY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Account-Params

Attribute	Description

Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	**Description**
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	**Description**
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	**Description**
Name	STRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.6.2.ST-AuthorizeBranch-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-IO*
    - *BRNCD*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.6.3.ST-AuthorizeBranch-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*
    - *BRNADDR*
    - *BRNADDR2*
    - *BRNADDR3*

SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC
EXTVAL
BRNAVALSTAT
NETSUSPGL

WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS

TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
- *BRNCD*
- *CUSTACCMSK*

CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description

Name	PRNTBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGNLOFC

Attribute	**Description**
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TIMLVL

Attribute	**Description**
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRYCD

Attribute	**Description**
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

FUNDBRNCH

Attribute	**Description**
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNLCY

Attribute	**Description**
Name	BRNLCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CODATMBRN

Attribute	**Description**
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CODINSTID

Attribute	**Description**
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR2

Attribute	Description	
Name	BRNADDR2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR3

Attribute	Description	
Name	BRNADDR3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SWFTADDR

Attribute	Description	
Name	SWFTADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

TELEXADDR

Attribute	Description	
Name	TELEXADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	Description
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	Description
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	Description
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ATMSUSPGL

Attribute	Description	
Name	ATMSUSPGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONVGL

Attribute	Description	
Name	CONVGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONVTXNCD

Attribute	Description	
Name	CONVTXNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CURRCYCLE

Attribute	Description	
Name	CURRCYCLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFSTMNTSTAT

Attribute	Description	
Name	DEFSTMNTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

GEN

Attribute	Description	
Name	GEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,

TOP

GEN103P

Attribute	Description	
Name	GEN103P	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFBNKOPCD

Attribute	Description	
Name	DEFBNKOPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLGBRNCD

Attribute	Description
Name	CLGBRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CLRBRN

Attribute	Description
Name	CLRBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNTRYCDDESC

Attribute	Description
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLSLDESC

Attribute	Description
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONTSUSPGLSLDESC

Attribute	Description
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLFCYDESC

Attribute	Description
Name	SUSPGLFCYDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONTSUSPGLFCYDESC

Attribute	**Description**	
Name	CONTSUSPGLFCYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ATMSUSPGLDESC

Attribute	**Description**	
Name	ATMSUSPGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVGLDESC

Attribute	**Description**	
Name	CONVGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVTXNCDDESC

Attribute	**Description**	
Name	CONVTXNCDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EXTVAL

Attribute	**Description**
Name	EXTVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRNAVALSTAT

Attribute	**Description**
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETSUSPGL

Attribute	**Description**
Name	NETSUSPGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

WALKINCUST

Attribute	**Description**
Name	WALKINCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description
Name	CLRBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

MISCCYMISMATCHGRP

Attribute	Description
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

INTERDICTCHKREQD

Attribute	Description
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTERDICTTIMOUT

Attribute	Description
Name	INTERDICTTIMOUT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ENTGL

Attribute	Description	
Name	ENTGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCKVALCHKREQD

Attribute	Description	
Name	BCKVALCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCKVALDAYS

Attribute	Description	
Name	BCKVALDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRCKPREVYRPRLS

Attribute	Description	
Name	TRCKPREVYRPRLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

DRPRDDESC

Attribute	Description
Name	DRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CRPRDDESC

Attribute	Description
Name	CRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRTAXCYCLE

Attribute	Description
Name	CURRTAXCYCLE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CONSOLTXCERTREQD

Attribute	**Description**
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	**Description**
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	**Description**
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	**Description**
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SUSENTRYREQ

Attribute	Description	
Name	SUSENTRYREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SUSBATCHNO

Attribute	Description	
Name	SUSBATCHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SUSTXNCODE

Attribute	Description	
Name	SUSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVSUSENTRYDAYS

Attribute	Description	
Name	REVSUSENTRYDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_TYPE

Attribute	Description
Name	TRANSFER_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,

TOP

POSITION_ASSET_GL

Attribute	**Description**
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	**Description**
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GL_CLASSS

Attribute	**Description**
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	**Description**
Name	CHEQUESTALEDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRY_CKSUM_MASK

Attribute	Description
Name	CNTRY_CKSUM_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Branch-Swift-Address

Attribute	**Description**
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Message-Type

Attribute	Description
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

LCYMSGTYP

Attribute	Description

Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,P,

TOP

Dup-Chk

Attribute	**Description**
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE1

Attribute	**Description**
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

DUP_FLG

Attribute	**Description**
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DUP_DAY

Attribute	**Description**
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	Description
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	Description
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	Description
Name	STRTACCNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDACCNO

Attribute	**Description**
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	**Description**
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDAUTOACCFLG

Attribute	**Description**
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOSTRTACCNO

Attribute	**Description**
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Branch-Details-PK*
      - *BRNCD*
    - *Branch-Details-IO*
      - *BRNCD*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Branch-Details-PK

Attribute	Description
Name	Branch-Details-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.7.AuthorizeBranchTrfr

AuthorizeBranchTrfr

2.7.1.ST-AuthorizeBranchTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Brn-Transfer-Full

Attribute	Description

Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TD_REQ

Attribute	Description

Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	**Description**
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	**Description**
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

2.7.2.ST-AuthorizeBranchTrfr-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-IO*
    - *TRANSFER_ID*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.7.3.ST-AuthorizeBranchTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Brn-Transfer-Full

Attribute	Description
Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description	
Name	TARGET_BRANCH_CODESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description	
Name	TRANSFER_LENDING_MODULE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CI_REQ

Attribute	Description	
Name	CI_REQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

MO_REQ

Attribute	Description	
Name	MO_REQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CASA_REQ

Attribute	Description	
Name	CASA_REQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TD_REQ

Attribute	Description
Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	Description
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	Description
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Sttms-Brn-Transfer-IO*
      - *TRANSFER_ID*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Brn-Transfer-PK

Attribute	Description
Name	Sttms-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.AuthorizeCRSRequest

Authorization of Adhoc Consolidated Statement Request

2.8.1.ST-AuthorizeCRSRequest-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Crs-Master-Full

Attribute	Description

Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description
Name	TO_DATE
Datatype	Date
Description	Specifies the To Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Specifies The Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS_DETAILS

Attribute	Description
Name	PROCESS_STATUS_DETAILS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

E-STATEMENT

Attribute	**Description**	
Name	E-STATEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	**Description**	
Name	CHARGEBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	**Description**	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.8.2.ST-AuthorizeCRSRequest-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-IO*
    - *REFERENCENO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.8.3.ST-AuthorizeCRSRequest-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Crs-Master-Full

Attribute	Description
Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description	
Name	TO_DATE	
Datatype	Date	
Description	Specifies the To Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUESTTYPE

Attribute	**Description**
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,L

TOP

FROMDATE

Attribute	**Description**
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESSSTAT

Attribute	**Description**
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REQUESTDATE

Attribute	**Description**
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESS_STATUS_DETAILS

Attribute	**Description**
Name	PROCESS_STATUS_DETAILS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	Description
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	Description
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the Transaction Status O - Open C - Close	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Crs-Master-IO*
      - *REFERENCENO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length = 3; pattern = [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs = 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Crs-Master-PK

Attribute	Description
Name	Sttm-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.9.AuthorizeCardAccount

Authorization of Card Accounts Detail

2.9.1.ST-AuthorizeCardAccount-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CardAccount-Full*
    - *BRNCODE*
    - *CUSTACNO*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the detail about card account.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255 Restrictions: minLength; Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 2 Restrictions: minLength; Description: 0

TOP

2.9.2.ST-AuthorizeCardAccount-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CardAccount-IO*
    - *BRNCODE*
    - *CUSTACNO*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates the card account information.

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.9.3.ST-AuthorizeCardAccount-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CardAccount-IO*
      - *BRNCODE*
      - *CUSTACNO*
      - *MODNO*
    - *CardAccount-Full*
      - *BRNCODE*
      - *CUSTACNO*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates the card input ouput details

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicates Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number

Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the total card details

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 2 Restrictions: minLength, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.9.4.ST-AuthorizeCardAccount-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CardAccount-PK*
      - *BRNCODE*
      - *CUSTACNO*
    - *CardAccount-IO*
      - *BRNCODE*
      - *CUSTACNO*
      - *MODNO*
    - *CardAccount-Full*
      - *BRNCODE*
      - *CUSTACNO*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CardAccount-PK

Attribute	Description
Name	CardAccount-PK
Datatype	
Description	it indicates the primary key in card account.

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicate Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO

Datatype	
Description	it indicates card account information.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the detail about card account.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE

Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACNO

Attribute	**Description**
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.AuthorizeCardMaster

AuthorizeCardMaster

2.10.1.ST-AuthorizeCardMaster-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*

CREDIT_CARD_LIMIT
PRIMARY_CARD
CARD_APPL_DATE
CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OWNER_ID_NO1

Attribute	**Description**
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADD_HOLDER_IDNO

Attribute	**Description**
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

OWNER_ID_TYPE

Attribute	**Description**
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	**Description**
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PLASTIC_TYPE

Attribute	Description	
Name	PLASTIC_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CREDIT_CARD_LIMIT

Attribute	Description	
Name	CREDIT_CARD_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CARD_APPL_DATE

Attribute	Description
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	Description
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N,

TOP

CARD_STATUS

Attribute	Description

Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	**Description**
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OPERATION

Attribute	**Description**
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BILL_CYCLE

Attribute	**Description**
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	Description	
Name	RENEWAL_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	Description	
Name	RENEWAL_CYCLE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_LIMIT_UNIT

Attribute	Description	
Name	ATM_LIMIT_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description	
Name	ATM_COUNT_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 19

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DEL_CHNL_PIN

Attribute	**Description**
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ADDL_HOLDER_DOB

Attribute	**Description**
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDL_HOLDER_RELATION

Attribute	**Description**
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DR_CR_INDICATOR

Attribute	**Description**
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Debit-Card-Master-IO
CUST_NO
CUST_AC_NO
BRANCH_CODE
REQ_REF_NO
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	**Description**
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.10.3.ST-AuthorizeCardMaster-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*
    - *CREDIT_CARD_LIMIT*
    - *PRIMARY_CARD*
    - *CARD_APPL_DATE*

CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CARD_PRODUCT

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description	
Name	REQ_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLD_BILL_INDICATOR

Attribute	Description	
Name	HOLD_BILL_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECOVERY_ACCOUNT

Attribute	Description	
Name	RECOVERY_ACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	20

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

OWNER_ID_NO1

Attribute	Description	
Name	OWNER_ID_NO1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

ADD_HOLDER_IDNO

Attribute	Description	
Name	ADD_HOLDER_IDNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

OWNER_ID_TYPE

Attribute	Description	
Name	OWNER_ID_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CARD_APPL_DATE

Attribute	**Description**
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	**Description**
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	**Description**
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N,

TOP

CARD_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

LAST_STATUS_UPDATED

Attribute	Description	
Name	LAST_STATUS_UPDATED	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

LAST_OPERATION

Attribute	Description	
Name	LAST_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

BILL_CYCLE

Attribute	Description	
Name	BILL_CYCLE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	**Description**
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	**Description**
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	**Description**
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	**Description**
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	19

TOP

DEL_CHNL_CARD

Attribute	Description	
Name	DEL_CHNL_CARD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

DEL_CHNL_PIN

Attribute	Description	
Name	DEL_CHNL_PIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

ADDL_HOLDER_DOB

Attribute	Description	
Name	ADDL_HOLDER_DOB	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

ADDL_HOLDER_RELATION

Attribute	Description	
Name	ADDL_HOLDER_RELATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DR_CR_INDICATOR

Attribute	Description
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.4.ST-AuthorizeCardMaster-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Debit-Card-Master-PK*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *CUST_NO*
      - *CUST_AC_NO*
    - *Sttms-Debit-Card-Master-IO*
      - *CUST_NO*
      - *CUST_AC_NO*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttms-Debit-Card-Master-PK

Attribute	Description
Name	Sttms-Debit-Card-Master-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description	
Name	REQ_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description

Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.AuthorizeCustTrfr

AuthorizeCustTrfr

2.11.1.ST-AuthorizeCustTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*

CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cust-Brn-Transfer-Full

Attribute	Description

Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description
Name	TRANSFER_MORTGAGES_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_CASA

Attribute	Description
Name	TRANSFER_CASA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	**Description**
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	**Description**
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	**Description**
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	**Description**
Name	TXT_CUSTNAME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cust-Brn-Transfer-IO
TRANSFER_ID
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.11.3.ST-AuthorizeCustTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cust-Brn-Transfer-Full

Attribute	Description
Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description	
Name	TRANSFER_MORTGAGES_MODULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFER_CASA

Attribute	Description	
Name	TRANSFER_CASA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	Description
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	Description
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cust-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Cust-Brn-Transfer-IO*
      - *TRANSFER_ID*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cust-Brn-Transfer-PK

Attribute	Description
Name	Cust-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.AuthorizeExtDeal

Authorize External Deal

2.12.1.ST-AuthorizeExtDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ext-Deal-Link-Full*
    - *DL_BOOK_DT1*
    - *DL_EXP_DT1*
    - *ACCCCY*
    - *EQ_AMT1*
    - *ACCOUNT_NUMBER*
    - *FCREFERENCE*
    - *EXTDLREF1*
    - *REKEYOFDEALAMOUNT*
    - *EXCHANGERATE*
    - *REKEYOFDEALCURRENCY*
    - *PRDREMRKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ext-Deal-Link-Full

Attribute	Description

Name	Ext-Deal-Link-Full
Datatype	
Description	

TOP

DL_BOOK_DT1

Attribute	Description
Name	DL_BOOK_DT1
Datatype	Date
Description	Indicates the Deal Booking Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DL_EXP_DT1

Attribute	Description
Name	DL_EXP_DT1
Datatype	Date
Description	Indicates the Deal Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates the Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EQ_AMT1

Attribute	Description
Name	EQ_AMT1
Datatype	Number
Description	Indicates the Equivalent Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	Indicates the Account Number

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTDLREF1

Attribute	Description
Name	EXTDLREF1
Datatype	String
Description	Indicates the External Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REKEYOFDEALAMOUNT

Attribute	Description
Name	REKEYOFDEALAMOUNT
Datatype	Number
Description	Indicates the Deal Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	Indicates the Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REKEYOFDEALCURRENCY

Attribute	Description
Name	REKEYOFDEALCURRENCY
Datatype	String
Description	Indicates the Deal Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PRDREMRKS

Attribute	Description
Name	PRDREMRKS
Datatype	String
Description	Indicates the Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker Identification
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	Indicates the Checker Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number i.e. the number of times the record has been modified
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	Indicates the Record Status Open :O Closed :C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status Authorized :A UnAuthorized :U
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

2.12.2.ST-AuthorizeExtDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ext-Deal-Link-IO*
    - *FCREFERENCE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ext-Deal-Link-IO

Attribute	Description
Name	Ext-Deal-Link-IO
Datatype	
Description	

TOP

FCREFERENCE

Attribute	Description	
Name	FCREFERENCE	
Datatype	String	
Description	Indicates the Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

2.12.3.ST-AuthorizeExtDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ext-Deal-Link-Full*
    - *DL_BOOK_DT1*
    - *DL_EXP_DT1*
    - *ACCCCY*
    - *EQ_AMT1*
    - *ACCOUNT_NUMBER*
    - *FCREFERENCE*
    - *EXTDLREF1*
    - *REKEYOFDEALAMOUNT*
    - *EXCHANGERATE*
    - *REKEYOFDEALCURRENCY*
    - *PRDREMRKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ext-Deal-Link-Full

Attribute	Description
Name	Ext-Deal-Link-Full
Datatype	
Description	

TOP

DL_BOOK_DT1

Attribute	Description	
Name	DL_BOOK_DT1	
Datatype	Date	
Description	Indicates the Deal Booking Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DL_EXP_DT1

Attribute	Description	
Name	DL_EXP_DT1	
Datatype	Date	
Description	Indicates the Deal Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates the Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EQ_AMT1

Attribute	Description	
Name	EQ_AMT1	
Datatype	Number	
Description	Indicates the Equivalent Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	Indicates the Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EXTDLREF1

Attribute	Description
Name	EXTDLREF1
Datatype	String
Description	Indicates the External Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REKEYOFDEALAMOUNT

Attribute	Description
Name	REKEYOFDEALAMOUNT
Datatype	Number
Description	Indicates the Deal Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number

Description	Indicates the Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYOFDEALCURRENCY

Attribute	**Description**
Name	REKEYOFDEALCURRENCY
Datatype	String
Description	Indicates the Deal Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDREMRKS

Attribute	**Description**
Name	PRDREMRKS
Datatype	String
Description	Indicates the Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	Indicates the Maker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number i.e. the number of times the record has been modified
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Record Status Open :O Closed :C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status Authorized :A UnAuthorized :U
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ext-Deal-Link-PK*
      - *FCREFERENCE*
    - *Ext-Deal-Link-IO*
      - *FCREFERENCE*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ext-Deal-Link-PK

Attribute	Description
Name	Ext-Deal-Link-PK
Datatype	
Description	

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Ext-Deal-Link-IO

Attribute	Description
Name	Ext-Deal-Link-IO
Datatype	
Description	

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.13.AuthorizeJointHolderMaint

Authorize Joint Holder Maintenance

2.13.1.ST-AuthorizeJointHolderMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Acc-Joint-Full*
    - *ACCOUNT_BRANCH*
    - *ACCOUNT_NUMBER*
    - *CUST_NO*
    - *ACCTYPE*
    - *OPMODE*
    - *ACCOUNT_CURRENCY*
    - *AC_DESC*
    - *CUSTNAME1*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

Acc-Joint-Holder

CUSTOMER_NUMBER

CUSTOMER_NAME

JNTHLDTYP

START_DATE

END_DATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Acc-Joint-Full

Attribute	Description
Name	Acc-Joint-Full
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,J

TOP

OPMODE

Attribute	**Description**	
Name	OPMODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,J,E,F,M,

TOP

ACCOUNT_CURRENCY

Attribute	**Description**	
Name	ACCOUNT_CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AC_DESC

Attribute	**Description**	
Name	AC_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTNAME1

Attribute	**Description**	
Name	CUSTNAME1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Acc-Joint-Holder

Attribute	Description
Name	Acc-Joint-Holder
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NUMBER

Attribute	Description
Name	CUSTOMER_NUMBER
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTOMER_NAME

Attribute	**Description**
Name	CUSTOMER_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

JNTHLDTYP

Attribute	**Description**
Name	JNTHLDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / AUS,CON,GUR,CUS,DEV,GUA,JAF,JAO,JOF,JOO,NOM,REL,SOL,SOW,THR,TRU,VAL,POA

TOP

START_DATE

Attribute	**Description**
Name	START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

END_DATE

Attribute	**Description**
Name	END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Acc-Joint-IO
ACCOUNT_BRANCH
ACCOUNT_NUMBER
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Acc-Joint-IO

Attribute	Description
Name	Acc-Joint-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.13.3.ST-AuthorizeJointHolderMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Acc-Joint-Full*
    - *ACCOUNT_BRANCH*
    - *ACCOUNT_NUMBER*
    - *CUST_NO*
    - *ACCTYPE*
    - *OPMODE*
    - *ACCOUNT_CURRENCY*
    - *AC_DESC*
    - *CUSTNAME1*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Acc-Joint-Holder*
      - *CUSTOMER_NUMBER*
      - *CUSTOMER_NAME*

JNTHLDTYP

START_DATE

END_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Acc-Joint-Full

Attribute	Description
Name	Acc-Joint-Full
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCOUNT_NUMBER

Attribute	Description	
Name	ACCOUNT_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,J

TOP

OPMODE

Attribute	Description
Name	OPMODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,J,E,F,M,

TOP

ACCOUNT_CURRENCY

Attribute	Description
Name	ACCOUNT_CURRENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CUSTNAME1

Attribute	Description

Name	CUSTNAME1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Acc-Joint-Holder

Attribute	**Description**
Name	Acc-Joint-Holder
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NUMBER

Attribute	Description
Name	CUSTOMER_NUMBER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTOMER_NAME

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

JNTHLDTYP

Attribute	Description
Name	JNTHLDTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: AUS,CON,GUR,CUS,DEV,GUA,JAF,JAO,JOF,JOO,NOM,REL,SOL,SOW,THR,TRU,VAL,POA

TOP

START_DATE

Attribute	Description
Name	START_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

END_DATE

Attribute	Description
Name	END_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Acc-Joint-PK*
      - *ACCOUNT_BRANCH*
      - *ACCOUNT_NUMBER*
    - *Acc-Joint-IO*
      - *ACCOUNT_BRANCH*
      - *ACCOUNT_NUMBER*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Acc-Joint-PK

Attribute	Description
Name	Acc-Joint-PK
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Acc-Joint-IO

Attribute	Description
Name	Acc-Joint-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.AuthorizeLMDCUSLT

AuthorizeLMDCUSLT

2.14.1.LM-AuthorizeLMDCUSLT-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*

- *CCY*
- *DAY_LIM_AMT*
- *SOD_NOT_PER*
- *RN_FLG*
- *NXT_RN_LI*
- *RN_FREQ*
- *RN_UN*
- *AUTO_CR_POOL_LI*
- *AC_DESC*
- *CUSTNAME*
- *MAKER*
- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *MODNO*
- *TXNSTAT*
- *AUTHSTAT*
- *Sttms-Cust-Acc-Limit-Coll*
  - *COLLTYPE*
  - *ACCBRN*
  - *AVAILABLE_AMOUNT*
  - *LNKDAMT*
  - *APP_INT_RATE*
  - *INT_SPREAD*
  - *RATE_OF_INT*
  - *COLLCAT*
  - *COLLHAIR*
  - *COLL*
- *Od-Limit*
  - *CUSTOMER_NO*
  - *LINKTYP*
  - *LINKAGE_REF_NO*
  - *PER_CONTRIBUTION*
  - *LINKAGE_SEQUENCE_NUMBER*
  - *LIABNO*
  - *EFFECTIVE_DATE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	Description
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description
Name	Od-Limit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKTYP

Attribute	Description
Name	LINKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description
Name	LINKAGE_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Lmdcuslt-IO
ACNO
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.14.3.LM-AuthorizeLMDCUSLT-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*
    - *CCY*
    - *DAY_LIM_AMT*
    - *SOD_NOT_PER*

RN_FLG

NXT_RN_LI

RN_FREQ

RN_UN

AUTO_CR_POOL_LI

AC_DESC

CUSTNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Sttms-Cust-Acc-Limit-Coll

COLLTYPE

ACCBRN

AVAILABLE_AMOUNT

LNKDAMT

APP_INT_RATE

INT_SPREAD

RATE_OF_INT

COLLCAT

COLLHAIR

COLL

Od-Limit

CUSTOMER_NO

LINKTYP

LINKAGE_REF_NO

PER_CONTRIBUTION

LINKAGE_SEQUENCE_NUMBER

LIABNO

EFFECTIVE_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	**Description**
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	**Description**
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description	
Name	Od-Limit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTYP

Attribute	Description	
Name	LINKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description	
Name	LINKAGE_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Lmdcuslt-PK*
      - *ACNO*
    - *Lmdcuslt-IO*
      - *ACNO*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Lmdcuslt-PK

Attribute	Description
Name	Lmdcuslt-PK
Datatype	
Description	

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.CloseLMDCUSLT

CloseLMDCUSLT

2.15.1.LM-CloseLMDCUSLT-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*

CCY
DAY_LIM_AMT
SOD_NOT_PER
RN_FLG
NXT_RN_LI
RN_FREQ
RN_UN
AUTO_CR_POOL_LI
AC_DESC
CUSTNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Sttms-Cust-Acc-Limit-Coll
COLLTYPE
ACCBRN
AVAILABLE_AMOUNT
LNKDAMT
APP_INT_RATE
INT_SPREAD
RATE_OF_INT
COLLCAT
COLLHAIR
COLL
Od-Limit
CUSTOMER_NO
LINKTYP
LINKAGE_REF_NO
PER_CONTRIBUTION
LINKAGE_SEQUENCE_NUMBER
LIABNO
EFFECTIVE_DATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	**Description**
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	**Description**
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	**Description**
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description	
Name	Od-Limit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTYP

Attribute	Description	
Name	LINKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description	
Name	LINKAGE_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Lmdcuslt-IO
ACNO
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.15.3.LM-CloseLMDCUSLT-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*
    - *CCY*
    - *DAY_LIM_AMT*
    - *SOD_NOT_PER*

RN_FLG

NXT_RN_LI

RN_FREQ

RN_UN

AUTO_CR_POOL_LI

AC_DESC

CUSTNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Sttms-Cust-Acc-Limit-Coll

COLLTYPE

ACCBRN

AVAILABLE_AMOUNT

LNKDAMT

APP_INT_RATE

INT_SPREAD

RATE_OF_INT

COLLCAT

COLLHAIR

COLL

Od-Limit

CUSTOMER_NO

LINKTYP

LINKAGE_REF_NO

PER_CONTRIBUTION

LINKAGE_SEQUENCE_NUMBER

LIABNO

EFFECTIVE_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	**Description**
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	**Description**
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	**Description**
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description	
Name	Od-Limit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTYP

Attribute	Description	
Name	LINKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description	
Name	LINKAGE_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Lmdcuslt-PK*
      - *ACNO*
    - *Lmdcuslt-IO*
      - *ACNO*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Lmdcuslt-PK

Attribute	Description
Name	Lmdcuslt-PK
Datatype	
Description	

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.CreateLMDCUSLT

CreateLMDCUSLT

2.16.1.LM-CreateLMDCUSLT-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*

- *CCY*
- *DAY_LIM_AMT*
- *SOD_NOT_PER*
- *RN_FLG*
- *NXT_RN_LI*
- *RN_FREQ*
- *RN_UN*
- *AUTO_CR_POOL_LI*
- *AC_DESC*
- *CUSTNAME*
- *MAKER*
- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *MODNO*
- *TXNSTAT*
- *AUTHSTAT*
- *Sttms-Cust-Acc-Limit-Coll*
  - *COLLTYPE*
  - *ACCBRN*
  - *AVAILABLE_AMOUNT*
  - *LNKDAMT*
  - *APP_INT_RATE*
  - *INT_SPREAD*
  - *RATE_OF_INT*
  - *COLLCAT*
  - *COLLHAIR*
  - *COLL*
- *Od-Limit*
  - *CUSTOMER_NO*
  - *LINKTYP*
  - *LINKAGE_REF_NO*
  - *PER_CONTRIBUTION*
  - *LINKAGE_SEQUENCE_NUMBER*
  - *LIABNO*
  - *EFFECTIVE_DATE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	**Description**
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	**Description**
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	**Description**
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description
Name	Od-Limit
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 9

TOP

LINKTYP

Attribute	Description
Name	LINKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	enumeration / L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description
Name	LINKAGE_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.16.2.LM-CreateLMDCUSLT-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-IO*
    - *ACNO*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*
    - *DAY_LIM_AMT*
    - *SOD_NOT_PER*
    - *RN_FLG*
    - *NXT_RN_LI*
    - *RN_FREQ*
    - *RN_UN*

AUTO_CR_POOL_LI

Sttms-Cust-Acc-Limit-Coll

COLLTYPE

LNKDAMT

INT_SPREAD

COLLCAT

COLLHAIR

COLL

Od-Limit

CUSTOMER_NO

LINKTYP

LINKAGE_REF_NO

PER_CONTRIBUTION

LINKAGE_SEQUENCE_NUMBER

EFFECTIVE_DATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CREDIT_TXN_LIMIT

Attribute	Description	
Name	CREDIT_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CR_LM_START_DATE

Attribute	Description	
Name	CR_LM_START_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CR_LM_REV_DATE

Attribute	Description

Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	**Description**
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	**Description**
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	**Description**
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	**Description**
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Od-Limit

Attribute	Description
Name	Od-Limit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKTYP

Attribute	Description
Name	LINKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description
Name	LINKAGE_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFECTIVE_DATE

Attribute	**Description**
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.16.3.LM-CreateLMDCUSLT-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*
    - *CCY*
    - *DAY_LIM_AMT*
    - *SOD_NOT_PER*

RN_FLG

NXT_RN_LI

RN_FREQ

RN_UN

AUTO_CR_POOL_LI

AC_DESC

CUSTNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Sttms-Cust-Acc-Limit-Coll

COLLTYPE

ACCBRN

AVAILABLE_AMOUNT

LNKDAMT

APP_INT_RATE

INT_SPREAD

RATE_OF_INT

COLLCAT

COLLHAIR

COLL

Od-Limit

CUSTOMER_NO

LINKTYP

LINKAGE_REF_NO

PER_CONTRIBUTION

LINKAGE_SEQUENCE_NUMBER

LIABNO

EFFECTIVE_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	Description
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description	
Name	Od-Limit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTYP

Attribute	Description	
Name	LINKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description	
Name	LINKAGE_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.4.LM-CreateLMDCUSLT-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Lmdcuslt-PK*
      - *ACNO*
    - *Lmdcuslt-IO*
      - *ACNO*
      - *CREDIT_TXN_LIMIT*
      - *CR_LM_START_DATE*
      - *CR_LM_REV_DATE*
      - *TOD_LIMIT_START_DATE*
      - *TOD_LIMIT_END_DATE*
      - *LIMIT_CCY*
      - *NETTING_REQUIRED*
      - *SUBLIMIT*
      - *UNCOLL_FUNDS_LIMIT*
      - *TOD_LIMIT*
      - *OFFLINE_LIMIT*
      - *DAY_LIM_AMT*
      - *SOD_NOT_PER*
      - *RN_FLG*

NXT_RN_LI

RN_FREQ

RN_UN

AUTO_CR_POOL_LI

Sttms-Cust-Acc-Limit-Coll

COLLTYPE

LNKDAMT

INT_SPREAD

COLLCAT

COLLHAIR

COLL

Od-Limit

CUSTOMER_NO

LINKTYP

LINKAGE_REF_NO

PER_CONTRIBUTION

LINKAGE_SEQUENCE_NUMBER

EFFECTIVE_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Lmdcuslt-PK

Attribute	Description
Name	Lmdcuslt-PK
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CREDIT_TXN_LIMIT

Attribute	Description	
Name	CREDIT_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CR_LM_START_DATE

Attribute	Description	
Name	CR_LM_START_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CR_LM_REV_DATE

Attribute	Description	
Name	CR_LM_REV_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOD_LIMIT_START_DATE

Attribute	Description

Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	**Description**
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	**Description**
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	**Description**
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	**Description**
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / T,C,U

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Od-Limit

Attribute	Description
Name	Od-Limit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKTYP

Attribute	Description
Name	LINKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description
Name	LINKAGE_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.DeleteLMDCUSLT

DeleteLMDCUSLT

2.17.1.LM-DeleteLMDCUSLT-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*

CCY
DAY_LIM_AMT
SOD_NOT_PER
RN_FLG
NXT_RN_LI
RN_FREQ
RN_UN
AUTO_CR_POOL_LI
AC_DESC
CUSTNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Sttms-Cust-Acc-Limit-Coll
COLLTYPE
ACCBRN
AVAILABLE_AMOUNT
LNKDAMT
APP_INT_RATE
INT_SPREAD
RATE_OF_INT
COLLCAT
COLLHAIR
COLL
Od-Limit
CUSTOMER_NO
LINKTYP
LINKAGE_REF_NO
PER_CONTRIBUTION
LINKAGE_SEQUENCE_NUMBER
LIABNO
EFFECTIVE_DATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	**Description**
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	**Description**
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description	
Name	Od-Limit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTYP

Attribute	Description	
Name	LINKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description	
Name	LINKAGE_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.17.2.LM-DeleteLMDCUSLT-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-IO*
    - *ACNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

2.17.3.LM-DeleteLMDCUSLT-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*
    - *CCY*
    - *DAY_LIM_AMT*
    - *SOD_NOT_PER*

RN_FLG

NXT_RN_LI

RN_FREQ

RN_UN

AUTO_CR_POOL_LI

AC_DESC

CUSTNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Sttms-Cust-Acc-Limit-Coll

COLLTYPE

ACCBRN

AVAILABLE_AMOUNT

LNKDAMT

APP_INT_RATE

INT_SPREAD

RATE_OF_INT

COLLCAT

COLLHAIR

COLL

Od-Limit

CUSTOMER_NO

LINKTYP

LINKAGE_REF_NO

PER_CONTRIBUTION

LINKAGE_SEQUENCE_NUMBER

LIABNO

EFFECTIVE_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	Description
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description	
Name	RN_FREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

RN_UN

Attribute	Description	
Name	RN_UN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTO_CR_POOL_LI

Attribute	Description	
Name	AUTO_CR_POOL_LI	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description	
Name	Od-Limit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTYP

Attribute	Description	
Name	LINKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description	
Name	LINKAGE_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Lmdcuslt-PK*
      - *ACNO*
    - *Lmdcuslt-IO*
      - *ACNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Lmdcuslt-PK

Attribute	Description
Name	Lmdcuslt-PK
Datatype	
Description	

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.18.ModifyLMDCUSLT

ModifyLMDCUSLT

2.18.1.LM-ModifyLMDCUSLT-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*

CCY
DAY_LIM_AMT
SOD_NOT_PER
RN_FLG
NXT_RN_LI
RN_FREQ
RN_UN
AUTO_CR_POOL_LI
AC_DESC
CUSTNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Sttms-Cust-Acc-Limit-Coll
COLLTYPE
ACCBRN
AVAILABLE_AMOUNT
LNKDAMT
APP_INT_RATE
INT_SPREAD
RATE_OF_INT
COLLCAT
COLLHAIR
COLL
Od-Limit
CUSTOMER_NO
LINKTYP
LINKAGE_REF_NO
PER_CONTRIBUTION
LINKAGE_SEQUENCE_NUMBER
LIABNO
EFFECTIVE_DATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	Description
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description	
Name	Od-Limit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTYP

Attribute	Description	
Name	LINKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description	
Name	LINKAGE_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.18.2.LM-ModifyLMDCUSLT-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-IO*
    - *ACNO*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *LINE_ID*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*
    - *CCY*
    - *DAY_LIM_AMT*
    - *SOD_NOT_PER*
    - *RN_FLG*
    - *NXT_RN_LI*

RN_FREQ

RN_UN

AUTO_CR_POOL_LI

MAKER

MAKERSTAMP

Sttms-Cust-Acc-Limit-Coll

COLLTYPE

ACCBRN

AVAILABLE_AMOUNT

LNKDAMT

APP_INT_RATE

INT_SPREAD

RATE_OF_INT

COLLCAT

COLLHAIR

COLL

Od-Limit

CUSTOMER_NO

LINKTYP

LINKAGE_REF_NO

PER_CONTRIBUTION

LINKAGE_SEQUENCE_NUMBER

EFFECTIVE_DATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CREDIT_TXN_LIMIT

Attribute	Description	
Name	CREDIT_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CR_LM_START_DATE

Attribute	Description

Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	**Description**
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	**Description**
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	**Description**
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIMIT_CCY

Attribute	**Description**
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINE_ID

Attribute	**Description**

Name	LINE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

NETTING_REQUIRED

Attribute	**Description**
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	**Description**
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	**Description**
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	**Description**
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	**Description**
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COLLTYPE

Attribute	**Description**
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / T,C,U

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Od-Limit

Attribute	Description
Name	Od-Limit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKTYP

Attribute	**Description**
Name	LINKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	**Description**
Name	LINKAGE_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PER_CONTRIBUTION

Attribute	**Description**
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	**Description**
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.18.3.LM-ModifyLMDCUSLT-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-Full*
    - *BRANCH_CODE*
    - *ACNO*
    - *CUST_NO*
    - *ACCOUNT_CLASS*
    - *CREDIT_TXN_LIMIT*
    - *CR_LM_START_DATE*
    - *CR_LM_REV_DATE*
    - *TOD_LIMIT_START_DATE*
    - *TOD_LIMIT_END_DATE*
    - *LIMIT_CCY*
    - *NETTING_REQUIRED*
    - *SUBLIMIT*
    - *UNCOLL_FUNDS_LIMIT*
    - *TOD_LIMIT*
    - *OFFLINE_LIMIT*
    - *CCY*
    - *DAY_LIM_AMT*
    - *SOD_NOT_PER*

RN_FLG

NXT_RN_LI

RN_FREQ

RN_UN

AUTO_CR_POOL_LI

AC_DESC

CUSTNAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Sttms-Cust-Acc-Limit-Coll

COLLTYPE

ACCBRN

AVAILABLE_AMOUNT

LNKDAMT

APP_INT_RATE

INT_SPREAD

RATE_OF_INT

COLLCAT

COLLHAIR

COLL

Od-Limit

CUSTOMER_NO

LINKTYP

LINKAGE_REF_NO

PER_CONTRIBUTION

LINKAGE_SEQUENCE_NUMBER

LIABNO

EFFECTIVE_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	Description
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	Description
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Od-Limit

Attribute	Description	
Name	Od-Limit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTYP

Attribute	Description	
Name	LINKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description	
Name	LINKAGE_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	Description
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.18.4.LM-ModifyLMDCUSLT-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Lmdcuslt-PK*
      - *ACNO*
    - *Lmdcuslt-IO*
      - *ACNO*
      - *CREDIT_TXN_LIMIT*
      - *CR_LM_START_DATE*
      - *CR_LM_REV_DATE*
      - *TOD_LIMIT_START_DATE*
      - *TOD_LIMIT_END_DATE*
      - *LIMIT_CCY*
      - *LINE_ID*
      - *NETTING_REQUIRED*
      - *SUBLIMIT*
      - *UNCOLL_FUNDS_LIMIT*
      - *TOD_LIMIT*
      - *OFFLINE_LIMIT*
      - *CCY*
      - *DAY_LIM_AMT*

SOD_NOT_PER
RN_FLG
NXT_RN_LI
RN_FREQ
RN_UN
AUTO_CR_POOL_LI
MAKER
MAKERSTAMP
Sttms-Cust-Acc-Limit-Coll
COLLTYPE
ACCBRN
AVAILABLE_AMOUNT
LNKDAMT
APP_INT_RATE
INT_SPREAD
RATE_OF_INT
COLLCAT
COLLHAIR
COLL
Od-Limit
CUSTOMER_NO
LINKTYP
LINKAGE_REF_NO
PER_CONTRIBUTION
LINKAGE_SEQUENCE_NUMBER
EFFECTIVE_DATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Lmdcuslt-PK

Attribute	Description
Name	Lmdcuslt-PK
Datatype	
Description	

TOP

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CREDIT_TXN_LIMIT

Attribute	Description	
Name	CREDIT_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CR_LM_START_DATE

Attribute	Description	
Name	CR_LM_START_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINE_ID

Attribute	Description
Name	LINE_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DAY_LIM_AMT

Attribute	**Description**
Name	DAY_LIM_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SOD_NOT_PER

Attribute	**Description**
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RN_FLG

Attribute	**Description**
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NXT_RN_LI

Attribute	**Description**
Name	NXT_RN_LI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description	
Name	Sttms-Cust-Acc-Limit-Coll	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COLLTYPE

Attribute	Description	
Name	COLLTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	T,C,U

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AVAILABLE_AMOUNT

Attribute	Description	
Name	AVAILABLE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LNKDAMT

Attribute	Description
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APP_INT_RATE

Attribute	Description
Name	APP_INT_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT_SPREAD

Attribute	Description
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE_OF_INT

Attribute	Description
Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Od-Limit

Attribute	Description
Name	Od-Limit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKTYP

Attribute	Description
Name	LINKTYP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	**Description**
Name	LINKAGE_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PER_CONTRIBUTION

Attribute	**Description**
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	**Description**
Name	LINKAGE_SEQUENCE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFECTIVE_DATE

Attribute	**Description**
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.19.QueryLMDCUSLT

QueryLMDCUSLT

2.19.1.LM-QueryLMDCUSLT-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Lmdcuslt-IO*
    - *ACNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

2.19.2.LM-QueryLMDCUSLT-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Lmdcuslt-IO*
      - *ACNO*
    - *Lmdcuslt-Full*
      - *BRANCH_CODE*
      - *ACNO*
      - *CUST_NO*
      - *ACCOUNT_CLASS*
      - *CREDIT_TXN_LIMIT*
      - *CR_LM_START_DATE*
      - *CR_LM_REV_DATE*
      - *TOD_LIMIT_START_DATE*
      - *TOD_LIMIT_END_DATE*
      - *LIMIT_CCY*
      - *NETTING_REQUIRED*
      - *SUBLIMIT*
      - *UNCOLL_FUNDS_LIMIT*
      - *TOD_LIMIT*
      - *OFFLINE_LIMIT*

CCY
DAY_LIM_AMT
SOD_NOT_PER
RN_FLG
NXT_RN_LI
RN_FREQ
RN_UN
AUTO_CR_POOL_LI
AC_DESC
CUSTNAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Sttms-Cust-Acc-Limit-Coll
COLLTYPE
ACCBRN
AVAILABLE_AMOUNT
LNKDAMT
APP_INT_RATE
INT_SPREAD
RATE_OF_INT
COLLCAT
COLLHAIR
COLL
Od-Limit
CUSTOMER_NO
LINKTYP
LINKAGE_REF_NO
PER_CONTRIBUTION
LINKAGE_SEQUENCE_NUMBER
LIABNO
EFFECTIVE_DATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Lmdcuslt-IO

Attribute	Description
Name	Lmdcuslt-IO
Datatype	
Description	

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Lmdcuslt-Full

Attribute	Description
Name	Lmdcuslt-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACNO

Attribute	Description	
Name	ACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CREDIT_TXN_LIMIT

Attribute	Description
Name	CREDIT_TXN_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_START_DATE

Attribute	Description
Name	CR_LM_START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_LM_REV_DATE

Attribute	Description
Name	CR_LM_REV_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TOD_LIMIT_START_DATE

Attribute	Description
Name	TOD_LIMIT_START_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOD_LIMIT_END_DATE

Attribute	Description
Name	TOD_LIMIT_END_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

NETTING_REQUIRED

Attribute	Description
Name	NETTING_REQUIRED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

SUBLIMIT

Attribute	Description
Name	SUBLIMIT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCOLL_FUNDS_LIMIT

Attribute	Description
Name	UNCOLL_FUNDS_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOD_LIMIT

Attribute	Description
Name	TOD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLINE_LIMIT

Attribute	Description
Name	OFFLINE_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DAY_LIM_AMT

Attribute	Description
Name	DAY_LIM_AMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SOD_NOT_PER

Attribute	Description
Name	SOD_NOT_PER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FLG

Attribute	Description
Name	RN_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NXT_RN_LI

Attribute	Description
Name	NXT_RN_LI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RN_FREQ

Attribute	Description
Name	RN_FREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

RN_UN

Attribute	Description
Name	RN_UN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTO_CR_POOL_LI

Attribute	Description
Name	AUTO_CR_POOL_LI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sttms-Cust-Acc-Limit-Coll

Attribute	Description
Name	Sttms-Cust-Acc-Limit-Coll
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / T,C,U

TOP

ACCBRN

Attribute	Description

Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AVAILABLE_AMOUNT

Attribute	**Description**
Name	AVAILABLE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKDAMT

Attribute	**Description**
Name	LNKDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APP_INT_RATE

Attribute	**Description**
Name	APP_INT_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_SPREAD

Attribute	**Description**
Name	INT_SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE_OF_INT

Attribute	**Description**

Name	RATE_OF_INT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLL

Attribute	Description
Name	COLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Od-Limit

Attribute	Description
Name	Od-Limit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKTYP

Attribute	Description
Name	LINKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGE_REF_NO

Attribute	Description
Name	LINKAGE_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PER_CONTRIBUTION

Attribute	Description
Name	PER_CONTRIBUTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKAGE_SEQUENCE_NUMBER

Attribute	Description
Name	LINKAGE_SEQUENCE_NUMBER

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABNO

Attribute	**Description**
Name	LIABNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EFFECTIVE_DATE

Attribute	**Description**
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.CloseBranch

CloseBranch

2.20.1.ST-CloseBranch-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*

BRNADDR
BRNADDR2
BRNADDR3
SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC

EXTVAL
BRNAVALSTAT
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH

CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description
Name	PRNTBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REGNLOFC

Attribute	Description
Name	REGNLOFC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TIMLVL

Attribute	Description
Name	TIMLVL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTRYCD

Attribute	Description
Name	CNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CIDIF

Attribute	Description
Name	CIDIF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

FUNDBRNCH

Attribute	**Description**
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRNLCY

Attribute	**Description**
Name	BRNLCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CODATMBRN

Attribute	**Description**
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CODINSTID

Attribute	**Description**
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CODIBTRNCD

Attribute	**Description**
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CODCUSTTRNS

Attribute	**Description**
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OFFSTHOURS

Attribute	**Description**
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OFFSTMINS

Attribute	**Description**
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRNADDR

Attribute	**Description**
Name	BRNADDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR2

Attribute	**Description**
Name	BRNADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR3

Attribute	**Description**
Name	BRNADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWFTADDR

Attribute	**Description**
Name	SWFTADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

HOSTNAM

Attribute	**Description**
Name	HOSTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

OFFSTHRS

Attribute	**Description**
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OFFSTMIN

Attribute	**Description**
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDOFINP

Attribute	**Description**
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONVGL

Attribute	Description
Name	CONVGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONVTXNCD

Attribute	Description
Name	CONVTXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURRCYCLE

Attribute	Description
Name	CURRCYCLE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROCWITHOUTFLOAT

Attribute	**Description**
Name	PROCWITHOUTFLOAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLGBRNCD

Attribute	**Description**
Name	CLGBRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRBRN

Attribute	**Description**
Name	CLRBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	**Description**	
Name	ROUTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

MSGGENDAY

Attribute	**Description**	
Name	MSGGENDAY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRNLCYDESC

Attribute	**Description**	
Name	BRNLCYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRNTBRNDESC

Attribute	**Description**	
Name	PRNTBRNDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNTRYCDDESC

Attribute	Description
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLSLDESC

Attribute	Description
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONTSUSPGLSLDESC

Attribute	Description
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLFCYDESC

Attribute	Description
Name	SUSPGLFCYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CONTSUSPGLFCYDESC

Attribute	Description
Name	CONTSUSPGLFCYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ATMSUSPGLDESC

Attribute	Description
Name	ATMSUSPGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CONVGLDESC

Attribute	Description
Name	CONVGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CONVTXNCDDESC

Attribute	Description
Name	CONVTXNCDDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EXTVAL

Attribute	**Description**
Name	EXTVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNAVALSTAT

Attribute	**Description**
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NETSUSPGL

Attribute	**Description**
Name	NETSUSPGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

WALKINCUST

Attribute	**Description**
Name	WALKINCUST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description
Name	CLRBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

MISCCYMISMATCHGRP

Attribute	Description
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

INTERDICTCHKREQD

Attribute	Description
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTERDICTTIMOUT

Attribute	Description
Name	INTERDICTTIMOUT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENTGL

Attribute	**Description**
Name	ENTGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	**Description**
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALDAYS

Attribute	**Description**
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	**Description**
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 500

TOP

DRPRDDESC

Attribute	Description
Name	DRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CRPRDDESC

Attribute	Description
Name	CRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRTAXCYCLE

Attribute	Description
Name	CURRTAXCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONSOLTXCERTREQD

Attribute	Description
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TAXCERTFREQ

Attribute	Description
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CIDIFDESC

Attribute	**Description**
Name	CIDIFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MINORAGE

Attribute	**Description**
Name	MINORAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTIFICATIONPERIOD

Attribute	**Description**
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXREALSUSAMT

Attribute	**Description**
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUSENTRYREQ

Attribute	Description
Name	SUSENTRYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUSBATCHNO

Attribute	Description
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SUSTXNCODE

Attribute	Description
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVSUSENTRYDAYS

Attribute	Description
Name	REVSUSENTRYDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRANSFER_TYPE

Attribute	Description
Name	TRANSFER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,

TOP

POSITION_ASSET_GL

Attribute	Description
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	Description
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GL_CLASSS

Attribute	Description
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	Description
Name	CHEQUESTALEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHQNO_MASK

Attribute	Description	
Name	CHQNO_MASK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

FILECONSTXNCODE

Attribute	Description	
Name	FILECONSTXNCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CNTRY_CKSUM_MASK

Attribute	Description	
Name	CNTRY_CKSUM_MASK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Branch-Swift-Address

Attribute	**Description**
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CCYCD

Attribute	Description	
Name	CCYCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

CCYDESC

Attribute	Description	
Name	CCYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

Branch-Message-Type

Attribute	Description	
Name	Branch-Message-Type	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	2

TOP

LCYMSGTYP

Attribute	Description
Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,P,

TOP

Dup-Chk

Attribute	Description
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE1

Attribute	Description
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

DUP_FLG

Attribute	Description
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DUP_DAY

Attribute	Description

Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Account-Params

Attribute	**Description**
Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	**Description**
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	**Description**
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	Description
Name	STRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Branch-Details-PK*
      - *BRNCD*
    - *Branch-Details-IO*
      - *BRNCD*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Branch-Details-PK

Attribute	Description
Name	Branch-Details-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.3.ST-CloseBranch-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*
    - *BRNADDR*
    - *BRNADDR2*
    - *BRNADDR3*

SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC
EXTVAL
BRNAVALSTAT
NETSUSPGL

WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS

TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
- *BRNCD*
- *CUSTACCMSK*

CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description	
Name	PRNTBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REGNLOFC

Attribute	Description
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TIMLVL

Attribute	Description
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRYCD

Attribute	Description
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIDIF

Attribute	Description
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

FUNDBRNCH

Attribute	Description
Name	FUNDBRNCH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRNLCY

Attribute	**Description**
Name	BRNLCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CODATMBRN

Attribute	**Description**
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CODINSTID

Attribute	**Description**
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CODIBTRNCD

Attribute	**Description**
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR3

Attribute	**Description**
Name	BRNADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWFTADDR

Attribute	**Description**
Name	SWFTADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

HOSTNAM

Attribute	**Description**
Name	HOSTNAM
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OFFSTHRS

Attribute	Description
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	Description
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	Description
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONVGL

Attribute	**Description**
Name	CONVGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONVTXNCD

Attribute	**Description**
Name	CONVTXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURRCYCLE

Attribute	**Description**
Name	CURRCYCLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRPERIOD

Attribute	**Description**
Name	CURRPERIOD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLGBRNCD

Attribute	**Description**
Name	CLGBRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRBRN

Attribute	**Description**
Name	CLRBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ROUTNO

Attribute	**Description**
Name	ROUTNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

MSGGENDAY

Attribute	**Description**
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRNLCYDESC

Attribute	**Description**
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRNTBRNDESC

Attribute	**Description**
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGNLOFCDESC

Attribute	**Description**
Name	REGNLOFCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTRYCDDESC

Attribute	Description
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SUSPGLSLDESC

Attribute	Description
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CONTSUSPGLSLDESC

Attribute	Description
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SUSPGLFCYDESC

Attribute	Description
Name	SUSPGLFCYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CONTSUSPGLFCYDESC

Attribute	Description
Name	CONTSUSPGLFCYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ATMSUSPGLDESC

Attribute	Description
Name	ATMSUSPGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CONVGLDESC

Attribute	Description
Name	CONVGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CONVTXNCDDESC

Attribute	Description
Name	CONVTXNCDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EXTVAL

Attribute	Description
Name	EXTVAL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNAVALSTAT

Attribute	**Description**
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NETSUSPGL

Attribute	**Description**
Name	NETSUSPGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

WALKINCUST

Attribute	**Description**
Name	WALKINCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INTSWAPCUST

Attribute	**Description**
Name	INTSWAPCUST
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CLRACC

Attribute	**Description**
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OFFSTCLRACC

Attribute	**Description**
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

WEEKHOL1

Attribute	**Description**
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	**Description**
Name	WEELHOL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	**Description**
Name	CLRBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MISCCYMISMATCHGRP

Attribute	**Description**
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INTERDICTCHKREQD

Attribute	**Description**
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTERDICTTIMOUT

Attribute	**Description**
Name	INTERDICTTIMOUT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENTGL

Attribute	Description
Name	ENTGL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	**Description**
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALDAYS

Attribute	**Description**
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	**Description**
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PLSPLITREQD

Attribute	**Description**
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRPRD

Attribute	**Description**
Name	DRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CRPRD

Attribute	**Description**
Name	CRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

IBANMSKBNKCD

Attribute	**Description**
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

IBANMSKACCNO

Attribute	**Description**
Name	IBANMSKACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 500

TOP

DRPRDDESC

Attribute	Description
Name	DRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CRPRDDESC

Attribute	Description
Name	CRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRTAXCYCLE

Attribute	Description
Name	CURRTAXCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONSOLTXCERTREQD

Attribute	Description
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TAXCERTFREQ

Attribute	Description
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MINORAGE

Attribute	**Description**
Name	MINORAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTIFICATIONPERIOD

Attribute	**Description**
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXREALSUSAMT

Attribute	**Description**
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTSUSAMT

Attribute	**Description**
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUSENTRYREQ

Attribute	**Description**
Name	SUSENTRYREQ

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SUSBATCHNO

Attribute	**Description**
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SUSTXNCODE

Attribute	**Description**
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REVSUSENTRYDAYS

Attribute	**Description**
Name	REVSUSENTRYDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSFER_BRANCH

Attribute	**Description**
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CASAAMTBLKTRNCODE

Attribute	Description	
Name	CASAAMTBLKTRNCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

HOFFREQ

Attribute	Description	
Name	HOFFREQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ALLWCORPACS

Attribute	Description	
Name	ALLWCORPACS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRANSFER_TYPE

Attribute	Description	
Name	TRANSFER_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,R,

TOP

POSITION_ASSET_GL

Attribute	Description
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	Description
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GL_CLASSS

Attribute	Description
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	Description
Name	CHEQUESTALEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ELCM_REPLICATION

Attribute	**Description**
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	**Description**
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPORT_DSN

Attribute	**Description**
Name	REPORT_DSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHQNO_MASK

Attribute	**Description**
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRY_CKSUM_MASK

Attribute	Description
Name	CNTRY_CKSUM_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Branch-Swift-Address

Attribute	**Description**
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Branch-Customer-Params

Attribute	**Description**
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	3

TOP

CCYDESC

Attribute	Description	
Name	CCYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

Branch-Message-Type

Attribute	Description	
Name	Branch-Message-Type	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	2

TOP

LCYMSGTYP

Attribute	Description	
Name	LCYMSGTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S,M,P,

TOP

Dup-Chk

Attribute	Description
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MODULE1

Attribute	Description
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

DUP_FLG

Attribute	Description
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUP_DAY

Attribute	Description
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCMSK

Attribute	Description	
Name	CUSTACCMSK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CHKSUMALGO

Attribute	Description	
Name	CHKSUMALGO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	Description	
Name	STRTACCNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 150 minLength: 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Branch-Details-IO
BRNCD
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.21.CloseBranchTrfr

CloseBranchTrfr

2.21.1.ST-CloseBranchTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Brn-Transfer-Full

Attribute	Description

Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TD_REQ

Attribute	Description

Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	**Description**
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	**Description**
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Brn-Transfer-IO
TRANSFER_ID
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.21.3.ST-CloseBranchTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Brn-Transfer-Full

Attribute	Description
Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description	
Name	TARGET_BRANCH_CODESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description	
Name	TRANSFER_LENDING_MODULE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CI_REQ

Attribute	Description	
Name	CI_REQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

MO_REQ

Attribute	Description	
Name	MO_REQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CASA_REQ

Attribute	Description	
Name	CASA_REQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TD_REQ

Attribute	Description
Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	Description
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	Description
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Sttms-Brn-Transfer-IO*
      - *TRANSFER_ID*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Brn-Transfer-PK

Attribute	Description
Name	Sttms-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.CloseCRSRequest

CloseCRSRequest

2.22.1.ST-CloseCRSRequest-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Crs-Master-Full

Attribute	Description

Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description
Name	TO_DATE
Datatype	Date
Description	Specifies the To Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Specifies The Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS_DETAILS

Attribute	Description
Name	PROCESS_STATUS_DETAILS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

E-STATEMENT

Attribute	**Description**
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.22.2.ST-CloseCRSRequest-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Crs-Master-IO
REFERENCENO
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.22.3.ST-CloseCRSRequest-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Crs-Master-Full

Attribute	Description
Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description	
Name	TO_DATE	
Datatype	Date	
Description	Specifies the To Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	Attribute: minOccurs — Description: 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PROCESS_STATUS_DETAILS

Attribute	Description
Name	PROCESS_STATUS_DETAILS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

E-STATEMENT

Attribute	**Description**
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Crs-Master-IO*
      - *REFERENCENO*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Crs-Master-PK

Attribute	Description
Name	Sttm-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	**Description**
maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	**Description**
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	**Description**
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.CloseCardMaster

CloseCardMaster

2.23.1.ST-CloseCardMaster-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*

CREDIT_CARD_LIMIT
PRIMARY_CARD
CARD_APPL_DATE
CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CARD_PRODUCT

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CARD_BIN

Attribute	Description	
Name	CARD_BIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OWNER_ID_NO1

Attribute	Description
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADD_HOLDER_IDNO

Attribute	Description
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

OWNER_ID_TYPE

Attribute	Description
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ISSUER

Attribute	**Description**
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PLASTIC_TYPE

Attribute	**Description**
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	**Description**
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRIMARY_CARD

Attribute	**Description**
Name	PRIMARY_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CARD_APPL_DATE

Attribute	Description
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	Description
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

CARD_STATUS

Attribute	Description

Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	**Description**
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OPERATION

Attribute	**Description**
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BILL_CYCLE

Attribute	**Description**
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	Description	
Name	RENEWAL_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	Description	
Name	RENEWAL_CYCLE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_LIMIT_UNIT

Attribute	Description	
Name	ATM_LIMIT_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description	
Name	ATM_COUNT_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 19

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DEL_CHNL_PIN

Attribute	**Description**
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ADDL_HOLDER_DOB

Attribute	**Description**
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDL_HOLDER_RELATION

Attribute	**Description**
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DR_CR_INDICATOR

Attribute	**Description**
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	D,C

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Debit-Card-Master-IO
CUST_NO
CUST_AC_NO
BRANCH_CODE
REQ_REF_NO
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	**Description**
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.23.3.ST-CloseCardMaster-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*
    - *CREDIT_CARD_LIMIT*
    - *PRIMARY_CARD*
    - *CARD_APPL_DATE*

CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR

ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	**Description**	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CARD_PRODUCT

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description	
Name	REQ_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLD_BILL_INDICATOR

Attribute	Description	
Name	HOLD_BILL_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECOVERY_ACCOUNT

Attribute	Description	
Name	RECOVERY_ACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	20

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

OWNER_ID_NO1

Attribute	Description
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

ADD_HOLDER_IDNO

Attribute	Description
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

OWNER_ID_TYPE

Attribute	Description
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CARD_APPL_DATE

Attribute	**Description**
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	**Description**
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	**Description**
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

CARD_STATUS

Attribute	**Description**
Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	**Description**
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LAST_OPERATION

Attribute	**Description**
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BILL_CYCLE

Attribute	**Description**
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	**Description**
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	**Description**
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	**Description**
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	**Description**
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	19

TOP

DEL_CHNL_CARD

Attribute	Description	
Name	DEL_CHNL_CARD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

DEL_CHNL_PIN

Attribute	Description	
Name	DEL_CHNL_PIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

ADDL_HOLDER_DOB

Attribute	Description	
Name	ADDL_HOLDER_DOB	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

ADDL_HOLDER_RELATION

Attribute	Description	
Name	ADDL_HOLDER_RELATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DR_CR_INDICATOR

Attribute	Description
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.4.ST-CloseCardMaster-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Debit-Card-Master-PK*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *CUST_NO*
      - *CUST_AC_NO*
    - *Sttms-Debit-Card-Master-IO*
      - *CUST_NO*
      - *CUST_AC_NO*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttms-Debit-Card-Master-PK

Attribute	Description
Name	Sttms-Debit-Card-Master-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description	
Name	REQ_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description

Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Debit-Card-Master-IO

Attribute	**Description**
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.CloseCustTrfr

CloseCustTrfr

2.24.1.ST-CloseCustTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*

CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable; Description: true
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cust-Brn-Transfer-Full

Attribute	Description

Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description
Name	TRANSFER_MORTGAGES_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_CASA

Attribute	Description
Name	TRANSFER_CASA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	**Description**
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	**Description**
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	**Description**
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	**Description**
Name	TXT_CUSTNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cust-Brn-Transfer-IO
TRANSFER_ID
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.24.3.ST-CloseCustTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cust-Brn-Transfer-Full

Attribute	Description
Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description	
Name	TRANSFER_MORTGAGES_MODULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFER_CASA

Attribute	Description	
Name	TRANSFER_CASA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	Description
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	Description
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cust-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Cust-Brn-Transfer-IO*
      - *TRANSFER_ID*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cust-Brn-Transfer-PK

Attribute	Description
Name	Cust-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.25.CloseExtDeal

Close External Deal

2.25.1.ST-CloseExtDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ext-Deal-Link-Full*
    - *DL_BOOK_DT1*
    - *DL_EXP_DT1*
    - *ACCCCY*
    - *EQ_AMT1*
    - *ACCOUNT_NUMBER*
    - *FCREFERENCE*
    - *EXTDLREF1*
    - *REKEYOFDEALAMOUNT*
    - *EXCHANGERATE*
    - *REKEYOFDEALCURRENCY*
    - *PRDREMRKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ext-Deal-Link-Full

Attribute	Description

Name	Ext-Deal-Link-Full
Datatype	
Description	

TOP

DL_BOOK_DT1

Attribute	Description
Name	DL_BOOK_DT1
Datatype	Date
Description	Indicates the Deal Booking Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DL_EXP_DT1

Attribute	Description
Name	DL_EXP_DT1
Datatype	Date
Description	Indicates the Deal Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates the Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EQ_AMT1

Attribute	Description
Name	EQ_AMT1
Datatype	Number
Description	Indicates the Equivalent Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	Indicates the Account Number

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTDLREF1

Attribute	Description
Name	EXTDLREF1
Datatype	String
Description	Indicates the External Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REKEYOFDEALAMOUNT

Attribute	Description
Name	REKEYOFDEALAMOUNT
Datatype	Number
Description	Indicates the Deal Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	Indicates the Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REKEYOFDEALCURRENCY

Attribute	Description
Name	REKEYOFDEALCURRENCY
Datatype	String
Description	Indicates the Deal Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PRDREMRKS

Attribute	Description
Name	PRDREMRKS
Datatype	String
Description	Indicates the Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker Identification
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	Indicates the Checker Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number i.e. the number of times the record has been modified
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	Indicates the Record Status Open :O Closed :C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status Authorized :A UnAuthorized :U
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

2.25.2.ST-CloseExtDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ext-Deal-Link-IO*
    - *FCREFERENCE*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ext-Deal-Link-IO

Attribute	Description
Name	Ext-Deal-Link-IO
Datatype	
Description	

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number i.e. the number of times the record has been modified

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

2.25.3.ST-CloseExtDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ext-Deal-Link-Full*
    - *DL_BOOK_DT1*
    - *DL_EXP_DT1*
    - *ACCCCY*
    - *EQ_AMT1*
    - *ACCOUNT_NUMBER*
    - *FCREFERENCE*
    - *EXTDLREF1*
    - *REKEYOFDEALAMOUNT*
    - *EXCHANGERATE*
    - *REKEYOFDEALCURRENCY*
    - *PRDREMRKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ext-Deal-Link-Full

Attribute	Description
Name	Ext-Deal-Link-Full
Datatype	
Description	

TOP

DL_BOOK_DT1

Attribute	Description	
Name	DL_BOOK_DT1	
Datatype	Date	
Description	Indicates the Deal Booking Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DL_EXP_DT1

Attribute	Description	
Name	DL_EXP_DT1	
Datatype	Date	
Description	Indicates the Deal Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates the Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EQ_AMT1

Attribute	Description	
Name	EQ_AMT1	
Datatype	Number	
Description	Indicates the Equivalent Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	Indicates the Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTDLREF1

Attribute	Description
Name	EXTDLREF1
Datatype	String
Description	Indicates the External Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REKEYOFDEALAMOUNT

Attribute	Description
Name	REKEYOFDEALAMOUNT
Datatype	Number
Description	Indicates the Deal Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number

Description	Indicates the Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYOFDEALCURRENCY

Attribute	Description
Name	REKEYOFDEALCURRENCY
Datatype	String
Description	Indicates the Deal Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDREMRKS

Attribute	Description
Name	PRDREMRKS
Datatype	String
Description	Indicates the Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number i.e. the number of times the record has been modified
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Record Status Open :O Closed :C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status Authorized :A UnAuthorized :U
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ext-Deal-Link-PK*
      - *FCREFERENCE*
    - *Ext-Deal-Link-IO*
      - *FCREFERENCE*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ext-Deal-Link-PK

Attribute	Description
Name	Ext-Deal-Link-PK
Datatype	
Description	

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Ext-Deal-Link-IO

Attribute	Description
Name	Ext-Deal-Link-IO
Datatype	
Description	

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number i.e. the number of times the record has been modified
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.26.CloseOnlineCharge

CloseOnlineCharge

2.26.1.ST-CloseOnlineCharge-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Onlinecharge-Master-Full

Attribute	Description
Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHARGE_EVENT

Attribute	Description
Name	CHARGE_EVENT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	**Description**
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

2.26.2.ST-CloseOnlineCharge-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-IO*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.26.3.ST-CloseOnlineCharge-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Onlinecharge-Master-Full

Attribute	Description

Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHARGE_EVENT

Attribute	**Description**	
Name	CHARGE_EVENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CHARGE_PRODUCT

Attribute	**Description**	
Name	CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Onlinecharge-Master-PK*
      - *SOURCE*
    - *Onlinecharge-Master-IO*
      - *SOURCE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Onlinecharge-Master-PK

Attribute	Description
Name	Onlinecharge-Master-PK
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.27.CloseSTDSTDOR

CloseSTDSTDOR

2.27.1.ST-CloseSTDSTDOR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Status-Full

Attribute	Description

Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Status-IO
ACCOUNT_BRANCH
AC_NO
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.27.3.ST-CloseSTDSTDOR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Status-Full

Attribute	Description
Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Status-PK*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
    - *Status-IO*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Status-PK

Attribute	Description
Name	Status-PK
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.CreateACRSMaint

Creation of Automatic Consolidated Statement Request

2.28.1.ST-CreateACRSMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description

Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCD

Attribute	Description
Name	BRANCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREEQUENCY

Attribute	Description
Name	FREEQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,S,A

TOP

STARTMON

Attribute	Description
Name	STARTMON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LASTEXEDATE

Attribute	Description
Name	LASTEXEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	Description	
Name	CHARGEBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	Description	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Auto-Crs-Master-IO
REFERENCENO
CUSTOMER_NO
EFFDATE
FREEQUENCY
STARTMON
STARTON
E-STATEMENT
CHARGEBRANCH
CHARGEACCOUNT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTOMER_NO

Attribute	**Description**
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREEQUENCY

Attribute	**Description**
Name	FREEQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,S,A

TOP

STARTMON

Attribute	**Description**
Name	STARTMON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	Description
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	Description
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

2.28.3.ST-CreateACRSMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description
Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCD

Attribute	Description	
Name	BRANCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date

Attributes	Attribute	Description
	minOccurs	0

TOP

FREEQUENCY

Attribute	Description	
Name	FREEQUENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,S,A

TOP

STARTMON

Attribute	Description	
Name	STARTMON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description	
Name	STARTON	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

LASTEXEDATE

Attribute	Description	
Name	LASTEXEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

E-STATEMENT

Attribute	Description

Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.4.ST-CreateACRSMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Auto-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Auto-Crs-Master-IO*
      - *REFERENCENO*
      - *CUSTOMER_NO*
      - *EFFDATE*
      - *FREEQUENCY*
      - *STARTMON*
      - *STARTON*
      - *E-STATEMENT*
      - *CHARGEBRANCH*
      - *CHARGEACCOUNT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttm-Auto-Crs-Master-PK

Attribute	Description
Name	Sttm-Auto-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	9

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	Attribute: minOccurs — Description: 0

TOP

FREEQUENCY

Attribute	Description
Name	FREEQUENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,Q,S,A

TOP

STARTMON

Attribute	Description
Name	STARTMON
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: enumeration — Description: JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

E-STATEMENT

Attribute	Description

Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.CreateAccClasMaint

Input of Account Class maintenance

2.29.1.ST-CreateAccClasMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-Full*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *ACCTYPE*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*

ACCSTMNTTYPT
ACCSTMNTCYCL3
OFFLNLMT
AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS

DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS
MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE

BALRPTTYP
STARTDT
STMNTPARAM1
STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT

INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN
ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*

- *DR_CB*
- *DR_LINE*
- *DR_HO*
- *RBKPROVSN*
- *STAT*
- *TXTSTATDESC*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation

- *ACCCLS*
- *SEQNO*
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint

- *BLCKNGORDR*
- *PRDCD*
- *PRDDESC*

Products

- *PRDCD*
- *PRDDESC*
- *DRTXN*
- *CRTXN*

Transaction-Codes

- *TXNCD*
- *TRNDESC*
- *DRTXN*
- *CRTXN*

Branch-Restriction

- *BRNCD*

Ccy-Restriction

- *CCYCD*

Ccy-Preferences

- *CCYCD*
- *MINBAL*

- *ATMCSHLMT*
- *ATMTRNSLMT*
- *TRUSTACCASHLIMIT*
- *MINIMUM_OPENING_BALANCE*
- *ACCOUNT_OPENING_CHARGES*
- *THRESHOLD_AMOUNT*

Cat-Restriction

- *CUSTCAT*

Cust-Restriction

- *CUSTNO*
- *ALLWD*

Interim-Dramt

- *CCY*
- *AMT*

Interim-Cramt

- *CCY*
- *AMT*

Msg-Gentime

- *GENTIM*

Msg-Gentime1

- *GENTIM*

Notice-Pref

- *ADVINTREQD*
- *MNTHLYFREEAMT*
- *NOTCPRD*
- *VALDITYPRD*

Aclass-Doctype

- *CUSTOMER_TYPE*
- *DOCUMENT_TYPE*
- *MANDATORY*

Sttms-Accls-Minmax-Amt-Ccy

- *CCY*
- *MIN_AMOUNT*
- *MAX_AMOUNT*
- *TOPUP_UNITS*

Dep-Accls-Rest

- *AC_CLASS*
- *ADESC*

Denom-Deposit

- *DENOMINATION_ID*
- *DENOMINATION_DESC*
- *DENOMINATION_VALUE*
- *CURRENCY*

Deposit-Ccy-Pref

- *ACCCCY*
- *Deposit-Ccy-Pref-Dtl*
  - *CURRENCY*
  - *PAYIN*
  - *INT_PAYOUT_C*
  - *PRI_PAYOUT_C*
- *Exrate-Pref*
  - *PAYINOUT_C*
  - *MODE_TYPE_C*
  - *RATETYPE_C*
  - *RATECODE_C*
  - *VARIANCE_C*
- *Chan-Rest-C*
  - *CHANLID*
  - *CHANNDESC*
- *Minmax-Ccy-C*
  - *CURR*
  - *CHANLID*
  - *MIN_AMOUNT*
  - *MAX_AMOUNT*
  - *TOPUP_UNITS*
- *Dorm-Param*
  - *ACCOUNT_CLASS*
  - *LCY_BALANCE*
  - *FREQUENCY*
  - *DORM_PREP_SEL_METH*
  - *DORM_PREP_DATE*
  - *DORM_PREP_NTH*
  - *DORM_PREP_DAY*
  - *DORM_PREP_MONTH*
  - *DORM_PREP_ACTION*
  - *DORM_PROC_SEL_METH*
  - *DORM_PROC_DATE*
  - *DORM_PROC_NTH*
  - *DORM_PROC_DAY*
  - *DORM_PROC_MONTH*
  - *DORM_GL*
  - *DORM_TRN_CODE*
  - *DORM_ADV_GEN*
  - *DORM_STOP_IC*
- *UDFDETAILS*
  - *FLDNAM*
  - *FLDVAL*
- *Misaccdflt*

MISCODE2
MISCODE3
MISCODE4
MISCODE5
MISCODE6
MISCODE7
MISCODE8
MISCODE9
MISCODE10
COSTCODE1
COSTCODE2
COSTCODE3
COSTCODE4
COSTCODE5
ACCLASS
MISGROUP
POOLCODE
MISCODE1
MISCLASS1
MISCLASS2
MISCLASS3
MISCLASS4
MISCLASS5
MISCLASS6
MISCLASS7
MISCLASS8
MISCLASS9
MISCLASS10
LINKTOGROUP
Status-Control

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Account-Class-Master-Full

Attribute	Description
Name	Account-Class-Master-Full
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DESC

Attribute	Description
Name	DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCCD

Attribute	Description
Name	ACCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

DRMNTPRM

Attribute	Description
Name	DRMNTPRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description
Name	ACCSTMNTCYCL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	**Description**
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	**Description**
Name	ACCSTMNTCYCL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	**Description**
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTPROVREQD

Attribute	**Description**
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PROVSNGFREQ

Attribute	Description	
Name	PROVSNGFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,D

TOP

PROVCCYTYP

Attribute	Description	
Name	PROVCCYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,A

TOP

EXPSRCAT

Attribute	Description	
Name	EXPSRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EVNTCLSCD

Attribute	Description	
Name	EVNTCLSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

DRINTUSNGRECV

Attribute	Description
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	Description
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	Description
Name	DRINTNOTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTLIQDAY

Attribute	Description
Name	DRINTLIQDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,A

TOP

CHGSTRTADV

Attribute	**Description**
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVCDAYS

Attribute	**Description**
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREBNKNGDAYS

Attribute	**Description**
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDLST

Attribute	**Description**
Name	PRDLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

CUSATLST

Attribute	Description
Name	CUSATLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	Description
Name	DEF_AUTODEP_AC_CLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

AUTDEPTRNCD

Attribute	Description
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AUTDEPCCY

Attribute	Description
Name	AUTDEPCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBALREQD

Attribute	**Description**
Name	MINBALREQD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPMLTPLOF

Attribute	**Description**
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKDEPOSITFRST

Attribute	**Description**
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDEPDERRATCD

Attribute	**Description**
Name	AUTDEPDERRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOROLL

Attribute	Description
Name	AUTOROLL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSONMATURTY

Attribute	Description
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRTLLIQDTN

Attribute	Description
Name	PRTLLIQDTN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	**Description**
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRACEPRD

Attribute	**Description**
Name	GRACEPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRDAYS

Attribute	**Description**
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRMNTHS

Attribute	**Description**
Name	MINTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXTNRMNTHS

Attribute	Description

Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRYRS

Attribute	**Description**
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDFLG

Attribute	**Description**
Name	RDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RDMVMATTOUNCLMD

Attribute	**Description**
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MOVEFUNDOVD

Attribute	**Description**
Name	MOVEFUNDOVD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LMTCHKREQD

Attribute	Description	
Name	LMTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OVRDRFTFACLTY

Attribute	Description	
Name	OVRDRFTFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASBKFACLTY

Attribute	Description	
Name	PASBKFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRCKRECBLE

Attribute	Description	
Name	TRCKRECBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCSTATS

Attribute	Description
Name	ACCSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description
Name	EXCLSAMDYRVRTRNSFMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description
Name	ALLWBCKPRDENTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CONSOLDTNREQD

Attribute	Description
Name	CONSOLDTNREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ICINCLSN

Attribute	Description
Name	ICINCLSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRCKACCREDIC

Attribute	Description
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

HASDRCRADV

Attribute	Description
Name	HASDRCRADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ILMAPPLICBL

Attribute	Description	
Name	ILMAPPLICBL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ATMFACLTY

Attribute	Description	
Name	ATMFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNT

Attribute	Description	
Name	GENINTRIMSTMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description	
Name	GENINTRIMSTMNTONMVMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

GENBALRPT

Attribute	Description	
Name	GENBALRPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTRIMRPTSNCE

Attribute	Description	
Name	INTRIMRPTSNCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	942,941,940,

TOP

INTRIMRPTTYP

Attribute	Description	
Name	INTRIMRPTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,S,T,

TOP

BALRPTSINCE

Attribute	Description	
Name	BALRPTSINCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	941,940,950,

TOP

BALRPTTYP

Attribute	Description
Name	BALRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STMNTPARAM1

Attribute	Description
Name	STMNTPARAM1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM2

Attribute	Description
Name	STMNTPARAM2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM3

Attribute	Description
Name	STMNTPARAM3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

ESCROWPROCESS

Attribute	**Description**
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNCODE

Attribute	**Description**
Name	TRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNREVCODE

Attribute	**Description**
Name	TRNREVCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINOR_MAJOR

Attribute	**Description**
Name	MINOR_MAJOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description	
Name	REPL_CUST_SIG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description	
Name	MAX_NO_CHEQUE_REJECTIONS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SAL_BLK_DAYS

Attribute	Description	
Name	SAL_BLK_DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description	
Name	DAYSUNAUTHNOACTIVITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description
Name	SETTLE_BRIDGE_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PCTXNCODE

Attribute	Description
Name	PCTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TDRATECHARTALLOW

Attribute	Description
Name	TDRATECHARTALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLUSTER_ID

Attribute	Description
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PROJECTACCNT

Attribute	Description
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	Description
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

LRGDRBALFLG

Attribute	Description	
Name	LRGDRBALFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNOVR_CODE

Attribute	Description	
Name	TRNOVR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FREQUENCY

Attribute	Description	
Name	FREQUENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y,

TOP

DAYS

Attribute	Description	
Name	DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SEND_NOTIFICATION

Attribute	Description	
Name	SEND_NOTIFICATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	Description	
Name	RT_CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SPDANLSYS

Attribute	Description	
Name	SPDANLSYS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description

Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	**Description**
Name	COMP_WISE_TRACKING_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENABLE_SWEEP_IN

Attribute	**Description**
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	**Description**
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEPACCCLS

Attribute	**Description**
Name	DEPACCCLS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

RATECHARTTENOR

Attribute	**Description**	
Name	RATECHARTTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

HOLIDAYCALENDAR

Attribute	**Description**	
Name	HOLIDAYCALENDAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	**Description**	
Name	HOLIDAYMOVEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	**Description**	
Name	MOVEACROSSMONTHS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	A,S,N,

TOP

ADHOCHOL

Attribute	Description	
Name	ADHOCHOL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description	
Name	APPLICABLEDEPTENOR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description	
Name	MONTHENDDEPOSIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DENM_DEPOSIT

Attribute	Description	
Name	DENM_DEPOSIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description
Name	REPCKUPACCLSTNRONROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFERREDBALUPD

Attribute	Description
Name	DEFERREDBALUPD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MULTICURRENCY

Attribute	Description
Name	MULTICURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MONTHS_C

Attribute	Description
Name	MONTHS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

INSTBASIS

Attribute	Description
Name	INSTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTICE_DEPOSIT

Attribute	**Description**
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	**Description**
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTICE_DAYS

Attribute	**Description**
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BONUS_INTEREST_C

Attribute	**Description**
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BONUS_FACTOR_C

Attribute	**Description**
Name	BONUS_FACTOR_C

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRANSACTION_CODE

Attribute	Description
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	Description
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UNCLAIMED_DAYS

Attribute	Description
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NC_DEPOSIT_C

Attribute	Description
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Status-Master

Attribute	Description	
Name	Status-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CR_CB

Attribute	Description	
Name	CR_CB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CR_LINE

Attribute	Description	
Name	CR_LINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CR_HO

Attribute	Description	
Name	CR_HO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DR_CB

Attribute	Description
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DR_LINE

Attribute	Description
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DR_HO

Attribute	Description
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TXTSTATDESC

Attribute	Description
Name	TXTSTATDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Status-Detail

Attribute	Description
Name	Status-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	**Description**
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	**Description**
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Status-Derivation

Attribute	**Description**
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCCLS

Attribute	**Description**
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	6

TOP

SEQNO

Attribute	Description	
Name	SEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

STATRUL1

Attribute	Description	
Name	STATRUL1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL2

Attribute	Description	
Name	STATRUL2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL3

Attribute	Description
Name	STATRUL3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

STATRUL4

Attribute	Description
Name	STATRUL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

STATRUL5

Attribute	Description
Name	STATRUL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

COMPONENT_PRIORITY1

Attribute	Description
Name	COMPONENT_PRIORITY1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	**Description**
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	**Description**
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BLCKNGORDR

Attribute	**Description**
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRTXN

Attribute	Description

Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Transaction-Codes

Attribute	**Description**
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TXNCD

Attribute	**Description**
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNDESC

Attribute	**Description**
Name	TRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRTXN

Attribute	**Description**
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Branch-Restriction

Attribute	**Description**
Name	Branch-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Restriction

Attribute	Description
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALLWD

Attribute	**Description**
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Interim-Dramt

Attribute	**Description**
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interim-Cramt

Attribute	Description
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	Description
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MANDATORY

Attribute	**Description**
Name	MANDATORY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	**Description**
Name	Sttms-Accls-Minmax-Amt-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MIN_AMOUNT

Attribute	**Description**
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Denom-Deposit

Attribute	Description	
Name	Denom-Deposit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DENOMINATION_ID

Attribute	Description	
Name	DENOMINATION_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

DENOMINATION_DESC

Attribute	Description	
Name	DENOMINATION_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

DENOMINATION_VALUE

Attribute	Description	
Name	DENOMINATION_VALUE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	Description
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	Description
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYIN

Attribute	**Description**
Name	PAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_PAYOUT_C

Attribute	**Description**
Name	INT_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRI_PAYOUT_C

Attribute	**Description**
Name	PRI_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Exrate-Pref

Attribute	**Description**
Name	Exrate-Pref
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PAYINOUT_C

Attribute	Description	
Name	PAYINOUT_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O

TOP

MODE_TYPE_C

Attribute	Description	
Name	MODE_TYPE_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S

TOP

RATETYPE_C

Attribute	Description	
Name	RATETYPE_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

RATECODE_C

Attribute	Description	
Name	RATECODE_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B

ORACLE

TOP

VARIANCE_C

Attribute	Description
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	Description
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHANNDESC

Attribute	Description
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description	
Name	DORM_PREP_SEL_METH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,W

TOP

DORM_PREP_DATE

Attribute	Description	
Name	DORM_PREP_DATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

DORM_PREP_NTH

Attribute	Description	
Name	DORM_PREP_NTH	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

DORM_PREP_DAY

Attribute	Description	
Name	DORM_PREP_DAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150 Restrictions: minLength — Description: 0

TOP

Misaccdflt

Attribute	Description

Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	**Description**
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	**Description**
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	**Description**
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	**Description**
Name	MISCODE5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCODE6

Attribute	Description
Name	MISCODE6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE7

Attribute	Description
Name	MISCODE7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE8

Attribute	Description
Name	MISCODE8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE9

Attribute	Description
Name	MISCODE9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE3

Attribute	Description
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE4

Attribute	Description
Name	COSTCODE4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE5

Attribute	Description
Name	COSTCODE5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ACCLASS

Attribute	Description
Name	ACCLASS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

MISGROUP

Attribute	Description
Name	MISGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS4

Attribute	Description	
Name	MISCLASS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS5

Attribute	Description	
Name	MISCLASS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS6

Attribute	Description	
Name	MISCLASS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS7

Attribute	Description	
Name	MISCLASS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Status-Control

Attribute	Description
Name	Status-Control
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.29.2.ST-CreateAccClasMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-IO*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *ACCTYPE*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*
    - *ACCSTMNTTYPT*
    - *ACCSTMNTCYCL3*
    - *OFFLNLMT*

AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS
DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS

MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE
BALRPTTYP
STARTDT
STMNTPARAM1
STMNTPARAM2

STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT
INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN
ENABLE_REV_SWEEP_IN

DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*
- *DR_CB*
- *DR_LINE*
- *DR_HO*
- *RBKPROVSN*
- *STAT*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation
- *STAT*

- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint

- *PRDCD*
- *PRDDESC*

Products

- *PRDCD*
- *DRTXN*
- *CRTXN*

Transaction-Codes

- *TXNCD*
- *DRTXN*
- *CRTXN*

Branch-Restriction

- *BRNCD*

Ccy-Restriction

- *CCYCD*

Ccy-Preferences

- *CCYCD*
- *MINBAL*
- *ATMCSHLMT*
- *ATMTRNSLMT*
- *TRUSTACCASHLIMIT*
- *MINIMUM_OPENING_BALANCE*
- *ACCOUNT_OPENING_CHARGES*
- *THRESHOLD_AMOUNT*

Cat-Restriction

- *CUSTCAT*

Cust-Restriction

- *CUSTNO*
- *ALLWD*

Interim-Dramt

- *CCY*
- *AMT*

Interim-Cramt

- *CCY*
- *AMT*

Msg-Gentime

GENTIM

Msg-Gentime1

GENTIM

Notice-Pref

ADVINTREQD

MNTHLYFREEAMT

NOTCPRD

VALDITYPRD

Aclass-Doctype

CUSTOMER_TYPE

DOCUMENT_TYPE

MANDATORY

Sttms-Accls-Minmax-Amt-Ccy

CCY

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dep-Accls-Rest

AC_CLASS

Denom-Deposit

DENOMINATION_ID

DENOMINATION_DESC

DENOMINATION_VALUE

CURRENCY

Deposit-Ccy-Pref

ACCCCY

Deposit-Ccy-Pref-Dtl

CURRENCY

PAYIN

INT_PAYOUT_C

PRI_PAYOUT_C

Exrate-Pref

PAYINOUT_C

MODE_TYPE_C

RATETYPE_C

RATECODE_C

VARIANCE_C

Chan-Rest-C

CHANLID

CHANNDESC

Minmax-Ccy-C

CURR

CHANLID

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dorm-Param

ACCOUNT_CLASS

LCY_BALANCE

FREQUENCY

DORM_PREP_SEL_METH

DORM_PREP_DATE

DORM_PREP_NTH

DORM_PREP_DAY

DORM_PREP_MONTH

DORM_PREP_ACTION

DORM_PROC_SEL_METH

DORM_PROC_DATE

DORM_PROC_NTH

DORM_PROC_DAY

DORM_PROC_MONTH

DORM_GL

DORM_TRN_CODE

DORM_ADV_GEN

DORM_STOP_IC

UDFDETAILS

FLDNAM

FLDVAL

Misaccdflt

MISCODE2

MISCODE3

MISCODE4

MISCODE5

MISCODE6

MISCODE7

MISCODE8

MISCODE9

MISCODE10

COSTCODE1

COSTCODE2

COSTCODE3

COSTCODE4

COSTCODE5

ACCLASS

MISGROUP

POOLCODE

MISCODE1

MISCLASS1

MISCLASS2
MISCLASS3
MISCLASS4
MISCLASS5
MISCLASS6
MISCLASS7
MISCLASS8
MISCLASS9
MISCLASS10
LINKTOGROUP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Account-Class-Master-IO

Attribute	Description
Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCCD

Attribute	Description	
Name	ACCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,C

TOP

DRMNTPRM

Attribute	Description
Name	DRMNTPRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description
Name	ACCSTMNTCYCL

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	Description
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	Description
Name	ACCSTMNTCYCL3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	Description	
Name	OFFLNLMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTPROVREQD

Attribute	Description	
Name	AUTPROVREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROVSNGFREQ

Attribute	Description	
Name	PROVSNGFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,D

TOP

PROVCCYTYP

Attribute	Description	
Name	PROVCCYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,A

TOP

EXPSRCAT

Attribute	Description
Name	EXPSRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EVNTCLSCD

Attribute	Description
Name	EVNTCLSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

DRINTUSNGRECV

Attribute	Description
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	Description
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	Description
Name	DRINTNOTC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRINTLIQDAY

Attribute	Description
Name	DRINTLIQDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,A

TOP

CHGSTRTADV

Attribute	Description
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVCDAYS

Attribute	Description
Name	ADVCDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

FREBNKNGDAYS

Attribute	Description
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRDLST

Attribute	Description
Name	PRDLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

CUSATLST

Attribute	Description
Name	CUSATLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	Description
Name	DEF_AUTODEP_AC_CLS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

AUTDEPTRNCD

Attribute	**Description**
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AUTDEPCCY

Attribute	**Description**
Name	AUTDEPCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBALREQD

Attribute	**Description**
Name	MINBALREQD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPMLTPLOF

Attribute	**Description**
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKDEPOSITFRST

Attribute	Description
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDEPDERRATCD

Attribute	Description
Name	AUTDEPDERRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOROLL

Attribute	Description
Name	AUTOROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSONMATURTY

Attribute	Description
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTLLIQDTN

Attribute	Description
Name	PRTLLIQDTN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	Description
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRACEPRD

Attribute	Description
Name	GRACEPRD
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MINTNRDAYS

Attribute	Description
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MINTNRMNTHS

Attribute	Description
Name	MINTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRMNTHS

Attribute	Description
Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRYRS

Attribute	Description
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDFLG

Attribute	Description
Name	RDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MOVEFUNDOVD

Attribute	Description
Name	MOVEFUNDOVD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LMTCHKREQD

Attribute	Description
Name	LMTCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

OVRDRFTFACLTY

Attribute	Description
Name	OVRDRFTFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PASBKFACLTY

Attribute	Description
Name	PASBKFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRCKRECBLE

Attribute	Description
Name	TRCKRECBLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACCSTATS

Attribute	Description
Name	ACCSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description
Name	EXCLSAMDYRVRTRNSFMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description
Name	ALLWBCKPRDENTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CONSOLDTNREQD

Attribute	Description
Name	CONSOLDTNREQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ICINCLSN

Attribute	Description
Name	ICINCLSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKACCREDIC

Attribute	Description
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASDRCRADV

Attribute	Description
Name	HASDRCRADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description	
Name	STATCHNGAUTMATIC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ILMAPPLICBL

Attribute	Description	
Name	ILMAPPLICBL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ATMFACLTY

Attribute	Description	
Name	ATMFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNT

Attribute	Description	
Name	GENINTRIMSTMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENBALRPT

Attribute	Description
Name	GENBALRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRIMRPTSNCE

Attribute	Description
Name	INTRIMRPTSNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	Description
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	Description
Name	BALRPTSINCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 941,940,950,

TOP

BALRPTTYP

Attribute	Description
Name	BALRPTTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,S,T,

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STMNTPARAM1

Attribute	Description
Name	STMNTPARAM1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 22

TOP

STMNTPARAM2

Attribute	Description
Name	STMNTPARAM2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM3

Attribute	**Description**	
Name	STMNTPARAM3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

ESCROWPROCESS

Attribute	**Description**	
Name	ESCROWPROCESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNCODE

Attribute	**Description**	
Name	TRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRNREVCODE

Attribute	**Description**	
Name	TRNREVCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

MINOR_MAJOR

Attribute	Description
Name	MINOR_MAJOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description
Name	REPL_CUST_SIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description
Name	MAX_NO_CHEQUE_REJECTIONS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SAL_BLK_DAYS

Attribute	Description
Name	SAL_BLK_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description
Name	DAYSUNAUTHNOACTIVITY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description
Name	SETTLE_BRIDGE_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PCTXNCODE

Attribute	Description
Name	PCTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TDRATECHARTALLOW

Attribute	Description
Name	TDRATECHARTALLOW

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLUSTER_ID

Attribute	**Description**
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PROJECTACCNT

Attribute	**Description**
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	**Description**
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	**Description**
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TURNOVER_RTOH_CODE

Attribute	Description	
Name	TURNOVER_RTOH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

LRGDRBALFLG

Attribute	Description	
Name	LRGDRBALFLG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRNOVR_CODE

Attribute	Description	
Name	TRNOVR_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEND_NOTIFICATION

Attribute	Description
Name	SEND_NOTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	Description
Name	RT_CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SPDANLSYS

Attribute	Description
Name	SPDANLSYS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPL_RATE

Attribute	**Description**
Name	SPL_RATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BLK_OPEN_DAYS

Attribute	**Description**
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLK_OPEN_MONTHS

Attribute	**Description**
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLK_MAT_DAYS

Attribute	**Description**
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description	
Name	INTRATE_CUMAMT_REQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	Description	
Name	COMP_WISE_TRACKING_REQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENABLE_SWEEP_IN

Attribute	Description	
Name	ENABLE_SWEEP_IN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	Description	
Name	ENABLE_REV_SWEEP_IN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DEPACCCLS

Attribute	Description	
Name	DEPACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

RATECHARTTENOR

Attribute	Description	
Name	RATECHARTTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

HOLIDAYCALENDAR

Attribute	Description	
Name	HOLIDAYCALENDAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	Description	
Name	HOLIDAYMOVEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	Description	
Name	MOVEACROSSMONTHS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,N,

TOP

ADHOCHOL

Attribute	Description	
Name	ADHOCHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description	
Name	APPLICABLEDEPTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description	
Name	MONTHENDDEPOSIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description
Name	REPCKUPACCLSTNRONROLL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEFERREDBALUPD

Attribute	Description
Name	DEFERREDBALUPD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MULTICURRENCY

Attribute	Description
Name	MULTICURRENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MONTHS_C

Attribute	Description
Name	MONTHS_C
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description	
Name	HIGH_VAL_DEPOSIT_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHANLIST

Attribute	Description	
Name	CHANLIST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

INSTBASIS

Attribute	Description	
Name	INSTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,L

TOP

MONTHEND_INST

Attribute	Description	
Name	MONTHEND_INST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTICE_DEPOSIT

Attribute	Description
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	Description
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICE_DAYS

Attribute	Description
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BONUS_INTEREST_C

Attribute	Description
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INT_EXPENSE_GL_C

Attribute	Description	
Name	INT_EXPENSE_GL_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TRANSACTION_CODE

Attribute	Description	
Name	TRANSACTION_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCCY_CHANGE_C

Attribute	Description	
Name	ACCCCY_CHANGE_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PREMAT_REDM_C

Attribute	Description	
Name	PREMAT_REDM_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UNCLAIMED_DAYS

Attribute	Description
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NC_DEPOSIT_C

Attribute	Description
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Status-Master

Attribute	Description
Name	Status-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CR_CB

Attribute	Description
Name	CR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CR_LINE

Attribute	Description
Name	CR_LINE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CR_HO

Attribute	**Description**
Name	CR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_CB

Attribute	**Description**
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_LINE

Attribute	**Description**
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DR_HO

Attribute	**Description**
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RBKPROVSN

Attribute	**Description**
Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Status-Detail

Attribute	**Description**
Name	Status-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROL

Attribute	**Description**
Name	ACCROL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Status-Derivation

Attribute	Description
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATRUL1

Attribute	Description
Name	STATRUL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL2

Attribute	Description
Name	STATRUL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL3

Attribute	Description
Name	STATRUL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL4

Attribute	Description
Name	STATRUL4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

STATRUL5

Attribute	Description	
Name	STATRUL5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

COMPONENT_PRIORITY1

Attribute	Description	
Name	COMPONENT_PRIORITY1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description	
Name	COMPONENT_PRIORITY2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	Description	
Name	COMPONENT_PRIORITY3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,P,I,C

TOP

Product-Maint

Attribute	**Description**
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	**Description**
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Products

Attribute	**Description**
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DRTXN

Attribute	Description
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	Description
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Transaction-Codes

Attribute	Description
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TXNCD

Attribute	Description
Name	TXNCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRTXN

Attribute	**Description**
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Branch-Restriction

Attribute	**Description**
Name	Branch-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	3

TOP

Ccy-Restriction

Attribute	Description	
Name	Ccy-Restriction	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCYCD

Attribute	Description	
Name	CCYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-Preferences

Attribute	Description	
Name	Ccy-Preferences	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCYCD

Attribute	Description	
Name	CCYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description

Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

THRESHOLD_AMOUNT

Attribute	**Description**
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Cat-Restriction

Attribute	**Description**
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTCAT

Attribute	**Description**
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Restriction

Attribute	**Description**
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Interim-Cramt

Attribute	**Description**
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Msg-Gentime

Attribute	**Description**
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	enumeration	I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	Description	
Name	Sttms-Accls-Minmax-Amt-Ccy	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Denom-Deposit

Attribute	Description
Name	Denom-Deposit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DENOMINATION_ID

Attribute	Description
Name	DENOMINATION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DENOMINATION_DESC

Attribute	Description
Name	DENOMINATION_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

DENOMINATION_VALUE

Attribute	Description
Name	DENOMINATION_VALUE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	**Description**
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	**Description**
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

PAYIN

Attribute	Description	
Name	PAYIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INT_PAYOUT_C

Attribute	Description	
Name	INT_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRI_PAYOUT_C

Attribute	Description	
Name	PRI_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Exrate-Pref

Attribute	Description	
Name	Exrate-Pref	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PAYINOUT_C

Attribute	Description
Name	PAYINOUT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,O

TOP

MODE_TYPE_C

Attribute	Description
Name	MODE_TYPE_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S

TOP

RATETYPE_C

Attribute	Description
Name	RATETYPE_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8

TOP

RATECODE_C

Attribute	Description
Name	RATECODE_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,B

TOP

VARIANCE_C

Attribute	Description

Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Chan-Rest-C

Attribute	**Description**
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHANLID

Attribute	**Description**
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHANNDESC

Attribute	**Description**
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Minmax-Ccy-C

Attribute	**Description**
Name	Minmax-Ccy-C
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 6

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	Attribute: Description minOccurs: 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description enumeration: D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description

Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	**Description**
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	**Description**
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_DAY

Attribute	**Description**
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_MONTH

Attribute	**Description**
Name	DORM_PREP_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_ACTION

Attribute	**Description**

Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	**Description**
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PROC_DATE

Attribute	**Description**
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_NTH

Attribute	**Description**
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_DAY

Attribute	**Description**
Name	DORM_PROC_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Misaccdflt

Attribute	Description
Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISCODE2

Attribute	Description
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	Description
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	Description
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	Description
Name	MISCODE5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE6

Attribute	Description
Name	MISCODE6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE7

Attribute	Description
Name	MISCODE7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE8

Attribute	Description
Name	MISCODE8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE9

Attribute	Description
Name	MISCODE9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE1

Attribute	**Description**
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE2

Attribute	**Description**
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE3

Attribute	**Description**
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE4

Attribute	**Description**
Name	COSTCODE4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCODE5

Attribute	Description
Name	COSTCODE5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCLASS

Attribute	Description
Name	ACCLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

MISGROUP

Attribute	Description
Name	MISGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS4

Attribute	Description
Name	MISCLASS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

2.29.3.ST-CreateAccClasMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-Full*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *ACCTYPE*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*
    - *ACCSTMNTTYPT*
    - *ACCSTMNTCYCL3*
    - *OFFLNLMT*

AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS
DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS

MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE
BALRPTTYP
STARTDT
STMNTPARAM1

STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT
INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN

ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*
- *DR_CB*
- *DR_LINE*
- *DR_HO*

- *RBKPROVSN*
- *STAT*
- *TXTSTATDESC*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation
- *ACCCLS*
- *SEQNO*
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint
- *BLCKNGORDR*
- *PRDCD*
- *PRDDESC*

Products
- *PRDCD*
- *PRDDESC*
- *DRTXN*
- *CRTXN*

Transaction-Codes
- *TXNCD*
- *TRNDESC*
- *DRTXN*
- *CRTXN*

Branch-Restriction
- *BRNCD*

Ccy-Restriction
- *CCYCD*

Ccy-Preferences
- *CCYCD*
- *MINBAL*
- *ATMCSHLMT*
- *ATMTRNSLMT*
- *TRUSTACCASHLIMIT*

MINIMUM_OPENING_BALANCE
ACCOUNT_OPENING_CHARGES
THRESHOLD_AMOUNT
Cat-Restriction
CUSTCAT
Cust-Restriction
CUSTNO
ALLWD
Interim-Dramt
CCY
AMT
Interim-Cramt
CCY
AMT
Msg-Gentime
GENTIM
Msg-Gentime1
GENTIM
Notice-Pref
ADVINTREQD
MNTHLYFREEAMT
NOTCPRD
VALDITYPRD
Aclass-Doctype
CUSTOMER_TYPE
DOCUMENT_TYPE
MANDATORY
Sttms-Accls-Minmax-Amt-Ccy
CCY
MIN_AMOUNT
MAX_AMOUNT
TOPUP_UNITS
Dep-Accls-Rest
AC_CLASS
ADESC
Denom-Deposit
DENOMINATION_ID
DENOMINATION_DESC
DENOMINATION_VALUE
CURRENCY
Deposit-Ccy-Pref
ACCCCY
Deposit-Ccy-Pref-Dtl
CURRENCY

PAYIN

INT_PAYOUT_C

PRI_PAYOUT_C

Exrate-Pref

PAYINOUT_C

MODE_TYPE_C

RATETYPE_C

RATECODE_C

VARIANCE_C

Chan-Rest-C

CHANLID

CHANNDESC

Minmax-Ccy-C

CURR

CHANLID

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dorm-Param

ACCOUNT_CLASS

LCY_BALANCE

FREQUENCY

DORM_PREP_SEL_METH

DORM_PREP_DATE

DORM_PREP_NTH

DORM_PREP_DAY

DORM_PREP_MONTH

DORM_PREP_ACTION

DORM_PROC_SEL_METH

DORM_PROC_DATE

DORM_PROC_NTH

DORM_PROC_DAY

DORM_PROC_MONTH

DORM_GL

DORM_TRN_CODE

DORM_ADV_GEN

DORM_STOP_IC

UDFDETAILS

FLDNAM

FLDVAL

Misaccdflt

MISCODE2

MISCODE3

MISCODE4

MISCODE5
MISCODE6
MISCODE7
MISCODE8
MISCODE9
MISCODE10
COSTCODE1
COSTCODE2
COSTCODE3
COSTCODE4
COSTCODE5
ACCLASS
MISGROUP
POOLCODE
MISCODE1
MISCLASS1
MISCLASS2
MISCLASS3
MISCLASS4
MISCLASS5
MISCLASS6
MISCLASS7
MISCLASS8
MISCLASS9
MISCLASS10
LINKTOGROUP
Status-Control
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 128 Restrictions: pattern; Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Account-Class-Master-Full

Attribute	Description
Name	Account-Class-Master-Full
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	Restrictions	Description
	maxLength	6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCCD

Attribute	Description
Name	ACCCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	**Description**
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	**Description**
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCTYPE

Attribute	**Description**
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	**Description**
Name	NATRLGLSGN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

DRMNTPRM

Attribute	**Description**	
Name	DRMNTPRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	**Description**	
Name	ACCSTMNTTYPP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,S,D

TOP

ACCSTMNTCYCL

Attribute	**Description**	
Name	ACCSTMNTCYCL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	**Description**	
Name	ACCSTMNTTYPS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	Description
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	Description
Name	ACCSTMNTCYCL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	Description
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A

TOP

EXPSRCAT

Attribute	Description
Name	EXPSRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EVNTCLSCD

Attribute	Description
Name	EVNTCLSCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

DRINTUSNGRECV

Attribute	**Description**
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	**Description**
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	**Description**
Name	DRINTNOTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTLIQDAY

Attribute	**Description**
Name	DRINTLIQDAY
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,A

TOP

CHGSTRTADV

Attribute	Description
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVCDAYS

Attribute	Description
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FREBNKNGDAYS

Attribute	Description
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRDLST

Attribute	Description
Name	PRDLST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

CUSATLST

Attribute	**Description**	
Name	CUSATLST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	**Description**	
Name	DEF_AUTODEP_AC_CLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

AUTDEPTRNCD

Attribute	**Description**	
Name	AUTDEPTRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

AUTDEPCCY

Attribute	Description	
Name	AUTDEPCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

MINBALREQD

Attribute	Description	
Name	MINBALREQD	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

DEPMLTPLOF

Attribute	Description	
Name	DEPMLTPLOF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

BRKDEPOSITFRST

Attribute	Description	
Name	BRKDEPOSITFRST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

AUTDEPDERRATCD

Attribute	Description
Name	AUTDEPDERRATCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	**Description**
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	**Description**
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	**Description**
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	**Description**
Name	PRVDINTONBRKNDEP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOROLL

Attribute	Description
Name	AUTOROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSONMATURTY

Attribute	Description
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTLLIQDTN

Attribute	Description
Name	PRTLLIQDTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVINTTOUNCLMD

Attribute	**Description**
Name	MVINTTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	**Description**
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GRACEPRD

Attribute	**Description**
Name	GRACEPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNRDAYS

Attribute	**Description**
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNRMNTHS

Attribute	**Description**
Name	MINTNRMNTHS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXTNRMNTHS

Attribute	Description
Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRYRS

Attribute	Description
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDFLG

Attribute	Description
Name	RDFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RDMVMATTOUNCLMD

Attribute	Description
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MOVEFUNDOVD

Attribute	Description
Name	MOVEFUNDOVD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RDMINSCHDLDAYS

Attribute	**Description**
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	**Description**
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	**Description**
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	**Description**
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLYRS

Attribute	**Description**
Name	RDSCHDLYRS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCHKREQD

Attribute	Description
Name	LMTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVRDRFTFACLTY

Attribute	Description
Name	OVRDRFTFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASBKFACLTY

Attribute	Description
Name	PASBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECBLE

Attribute	Description
Name	TRCKRECBLE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCSTATS

Attribute	Description
Name	ACCSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description
Name	EXCLSAMDYRVRTRNSFMSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description
Name	ALLWBCKPRDENTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONSOLDTNREQD

Attribute	Description
Name	CONSOLDTNREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ICINCLSN

Attribute	Description	
Name	ICINCLSN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRCKACCREDIC

Attribute	Description	
Name	TRCKACCREDIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

HASDRCRADV

Attribute	Description	
Name	HASDRCRADV	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ACSTATDEPST

Attribute	Description	
Name	ACSTATDEPST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ILMAPPLICBL

Attribute	Description
Name	ILMAPPLICBL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ATMFACLTY

Attribute	Description
Name	ATMFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNT

Attribute	Description
Name	GENINTRIMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENBALRPT

Attribute	**Description**
Name	GENBALRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRIMRPTSNCE

Attribute	**Description**
Name	INTRIMRPTSNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	**Description**
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	**Description**
Name	BALRPTSINCE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	941,940,950,

TOP

BALRPTTYP

Attribute	Description	
Name	BALRPTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,S,T,

TOP

STARTDT

Attribute	Description	
Name	STARTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STMNTPARAM1

Attribute	Description	
Name	STMNTPARAM1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM2

Attribute	Description	
Name	STMNTPARAM2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM3

Attribute	Description
Name	STMNTPARAM3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

ESCROWPROCESS

Attribute	Description
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNCODE

Attribute	Description
Name	TRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNREVCODE

Attribute	Description
Name	TRNREVCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINOR_MAJOR

Attribute	Description
Name	MINOR_MAJOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description
Name	REPL_CUST_SIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description
Name	MAX_NO_CHEQUE_REJECTIONS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SAL_BLK_DAYS

Attribute	Description
Name	SAL_BLK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description
Name	DAYSUNAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description	
Name	SETTLE_BRIDGE_GL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRDCAT

Attribute	Description	
Name	PRDCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PCTXNCODE

Attribute	Description	
Name	PCTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TDRATECHARTALLOW

Attribute	Description	
Name	TDRATECHARTALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CLUSTER_ID

Attribute	Description
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

PROJECTACCNT

Attribute	Description
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	Description
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

LRGDRBALFLG

Attribute	Description
Name	LRGDRBALFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description
Name	DAYLIGHTLIMIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRNOVR_CODE

Attribute	Description
Name	TRNOVR_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DAYS

Attribute	**Description**
Name	DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEND_NOTIFICATION

Attribute	**Description**
Name	SEND_NOTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	**Description**
Name	RT_CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SPDANLSYS

Attribute	**Description**
Name	SPDANLSYS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description
Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	Description
Name	COMP_WISE_TRACKING_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_SWEEP_IN

Attribute	Description
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	Description
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEPACCCLS

Attribute	Description
Name	DEPACCCLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

RATECHARTTENOR

Attribute	Description
Name	RATECHARTTENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

HOLIDAYCALENDAR

Attribute	Description
Name	HOLIDAYCALENDAR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	Description
Name	HOLIDAYMOVEMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	Description
Name	MOVEACROSSMONTHS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,N,

TOP

ADHOCHOL

Attribute	**Description**
Name	ADHOCHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	**Description**
Name	APPLICABLEDEPTENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,D,

TOP

MONTHENDDEPOSIT

Attribute	**Description**
Name	MONTHENDDEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENM_DEPOSIT

Attribute	**Description**
Name	DENM_DEPOSIT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description	
Name	REPCKUPACCLSTNRONROLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFERREDBALUPD

Attribute	Description	
Name	DEFERREDBALUPD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MULTICURRENCY

Attribute	Description	
Name	MULTICURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MONTHS_C

Attribute	Description	
Name	MONTHS_C	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

INSTBASIS

Attribute	Description
Name	INSTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_DEPOSIT

Attribute	Description
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	Description
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICE_DAYS

Attribute	Description
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BONUS_INTEREST_C

Attribute	Description
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRANSACTION_CODE

Attribute	Description
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	Description
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UNCLAIMED_DAYS

Attribute	**Description**
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NC_DEPOSIT_C

Attribute	**Description**
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Status-Master

Attribute	Description
Name	Status-Master
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CR_CB

Attribute	Description
Name	CR_CB
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CR_LINE

Attribute	Description
Name	CR_LINE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CR_HO

Attribute	Description
Name	CR_HO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_CB

Attribute	**Description**
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_LINE

Attribute	**Description**
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DR_HO

Attribute	**Description**
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RBKPROVSN

Attribute	**Description**
Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TXTSTATDESC

Attribute	Description
Name	TXTSTATDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Status-Detail

Attribute	Description
Name	Status-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Status-Derivation

Attribute	Description
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCLS

Attribute	Description
Name	ACCCLS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SEQNO

Attribute	**Description**
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATRUL1

Attribute	**Description**
Name	STATRUL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL2

Attribute	**Description**
Name	STATRUL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL3

Attribute	Description	
Name	STATRUL3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL4

Attribute	Description	
Name	STATRUL4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL5

Attribute	Description	
Name	STATRUL5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

COMPONENT_PRIORITY1

Attribute	Description	
Name	COMPONENT_PRIORITY1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	Description
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	Description
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BLCKNGORDR

Attribute	Description
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRTXN

Attribute	**Description**
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Transaction-Codes

Attribute	**Description**
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNCD

Attribute	**Description**
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRNDESC

Attribute	Description
Name	TRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRTXN

Attribute	Description
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	Description
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Restriction

Attribute	Description
Name	Branch-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Restriction

Attribute	**Description**
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	**Description**
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interim-Cramt

Attribute	**Description**
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	**Description**
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** enumeration / I,C,B

TOP

DOCUMENT_TYPE

Attribute	**Description**
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MANDATORY

Attribute	**Description**
Name	MANDATORY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	**Description**
Name	Sttms-Accls-Minmax-Amt-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Denom-Deposit

Attribute	Description
Name	Denom-Deposit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DENOMINATION_ID

Attribute	Description
Name	DENOMINATION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

DENOMINATION_DESC

Attribute	Description
Name	DENOMINATION_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

DENOMINATION_VALUE

Attribute	Description

Name	DENOMINATION_VALUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	**Description**
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	**Description**
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PAYIN

Attribute	Description	
Name	PAYIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INT_PAYOUT_C

Attribute	Description	
Name	INT_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRI_PAYOUT_C

Attribute	Description	
Name	PRI_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Exrate-Pref

Attribute	Description
Name	Exrate-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAYINOUT_C

Attribute	Description
Name	PAYINOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O

TOP

MODE_TYPE_C

Attribute	Description
Name	MODE_TYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S

TOP

RATETYPE_C

Attribute	Description
Name	RATETYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RATECODE_C

Attribute	Description

Name	RATECODE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

VARIANCE_C

Attribute	**Description**
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	**Description**
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHANLID

Attribute	**Description**
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHANNDESC

Attribute	**Description**
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	**Description**
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dorm-Param

Attribute	**Description**
Name	Dorm-Param
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCOUNT_CLASS

Attribute	**Description**
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

LCY_BALANCE

Attribute	**Description**
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQUENCY

Attribute	**Description**
Name	FREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	Description
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	Description
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_DAY

Attribute	Description
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

Misaccdflt

Attribute	Description
Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	Description
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	Description
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	Description
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	Description
Name	MISCODE5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE6

Attribute	**Description**
Name	MISCODE6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE7

Attribute	**Description**
Name	MISCODE7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE8

Attribute	**Description**
Name	MISCODE8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE9

Attribute	**Description**
Name	MISCODE9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE10

Attribute	**Description**
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE1

Attribute	**Description**
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE2

Attribute	**Description**
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE3

Attribute	**Description**
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE4

Attribute	Description	
Name	COSTCODE4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE5

Attribute	Description	
Name	COSTCODE5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCLASS

Attribute	Description	
Name	ACCLASS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

TOP

MISGROUP

Attribute	Description	
Name	MISGROUP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS4

Attribute	Description
Name	MISCLASS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS8

Attribute	**Description**
Name	MISCLASS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS9

Attribute	**Description**
Name	MISCLASS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS10

Attribute	**Description**
Name	MISCLASS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKTOGROUP

Attribute	**Description**
Name	LINKTOGROUP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Status-Control

Attribute	Description	
Name	Status-Control	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.4.ST-CreateAccClasMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Account-Class-Master-PK*
      - *ACCCLS*
    - *Account-Class-Master-IO*
      - *ACCCLS*
      - *DESC*
      - *ACCCD*
      - *ENDDT*
      - *DRMNCY*
      - *ACSTFORMT*
      - *DSPLYIBANINADV*
      - *INTRPY*
      - *ACCTYPE*
      - *NATRLGLSGN*
      - *DRMNTPRM*
      - *ACCSTMNTTYPP*
      - *ACCSTMNTCYCL*
      - *ACCSTMNTTYPS*
      - *ACCSTMNTCYCL2*

ACCSTMNTTYPT
ACCSTMNTCYCL3
OFFLNLMT
AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS

DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS
MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE
BALRPTTYP

STARTDT
STMNTPARAM1
STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT
INTRATE_CUMAMT_REQD

COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN
ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*
- *DR_CB*
- *DR_LINE*
- *DR_HO*
- *RBKPROVSN*
- *STAT*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*

GLDESC

Status-Derivation

STAT

STATRUL1

STATRUL2

STATRUL3

STATRUL4

STATRUL5

COMPONENT_PRIORITY1

COMPONENT_PRIORITY2

COMPONENT_PRIORITY3

Product-Maint

PRDCD

PRDDESC

Products

PRDCD

DRTXN

CRTXN

Transaction-Codes

TXNCD

DRTXN

CRTXN

Branch-Restriction

BRNCD

Ccy-Restriction

CCYCD

Ccy-Preferences

CCYCD

MINBAL

ATMCSHLMT

ATMTRNSLMT

TRUSTACCASHLIMIT

MINIMUM_OPENING_BALANCE

ACCOUNT_OPENING_CHARGES

THRESHOLD_AMOUNT

Cat-Restriction

CUSTCAT

Cust-Restriction

CUSTNO

ALLWD

Interim-Dramt

CCY

AMT

Interim-Cramt

CCY
AMT
Msg-Gentime
GENTIM
Msg-Gentime1
GENTIM
Notice-Pref
ADVINTREQD
MNTHLYFREEAMT
NOTCPRD
VALDITYPRD
Aclass-Doctype
CUSTOMER_TYPE
DOCUMENT_TYPE
MANDATORY
Sttms-Accls-Minmax-Amt-Ccy
CCY
MIN_AMOUNT
MAX_AMOUNT
TOPUP_UNITS
Dep-Accls-Rest
AC_CLASS
Denom-Deposit
DENOMINATION_ID
DENOMINATION_DESC
DENOMINATION_VALUE
CURRENCY
Deposit-Ccy-Pref
ACCCCY
Deposit-Ccy-Pref-Dtl
CURRENCY
PAYIN
INT_PAYOUT_C
PRI_PAYOUT_C
Exrate-Pref
PAYINOUT_C
MODE_TYPE_C
RATETYPE_C
RATECODE_C
VARIANCE_C
Chan-Rest-C
CHANLID
CHANNDESC
Minmax-Ccy-C

- *CURR*
- *CHANLID*
- *MIN_AMOUNT*
- *MAX_AMOUNT*
- *TOPUP_UNITS*

Dorm-Param

- *ACCOUNT_CLASS*
- *LCY_BALANCE*
- *FREQUENCY*
- *DORM_PREP_SEL_METH*
- *DORM_PREP_DATE*
- *DORM_PREP_NTH*
- *DORM_PREP_DAY*
- *DORM_PREP_MONTH*
- *DORM_PREP_ACTION*
- *DORM_PROC_SEL_METH*
- *DORM_PROC_DATE*
- *DORM_PROC_NTH*
- *DORM_PROC_DAY*
- *DORM_PROC_MONTH*
- *DORM_GL*
- *DORM_TRN_CODE*
- *DORM_ADV_GEN*
- *DORM_STOP_IC*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

Misaccdflt

- *MISCODE2*
- *MISCODE3*
- *MISCODE4*
- *MISCODE5*
- *MISCODE6*
- *MISCODE7*
- *MISCODE8*
- *MISCODE9*
- *MISCODE10*
- *COSTCODE1*
- *COSTCODE2*
- *COSTCODE3*
- *COSTCODE4*
- *COSTCODE5*
- *ACCLASS*
- *MISGROUP*

POOLCODE

MISCODE1

MISCLASS1

MISCLASS2

MISCLASS3

MISCLASS4

MISCLASS5

MISCLASS6

MISCLASS7

MISCLASS8

MISCLASS9

MISCLASS10

LINKTOGROUP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Account-Class-Master-PK

Attribute	Description
Name	Account-Class-Master-PK
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Account-Class-Master-IO

Attribute	Description
Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCCD

Attribute	Description
Name	ACCCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description	
Name	NATRLGLSGN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

DRMNTPRM

Attribute	Description	
Name	DRMNTPRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description	
Name	ACCSTMNTTYPP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description	
Name	ACCSTMNTCYCL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	Description
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	Description
Name	ACCSTMNTCYCL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	Description
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A

TOP

EXPSRCAT

Attribute	Description
Name	EXPSRCAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EVNTCLSCD

Attribute	**Description**	
Name	EVNTCLSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

DRINTUSNGRECV

Attribute	**Description**	
Name	DRINTUSNGRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VRFYFNDSFORDRINT

Attribute	**Description**	
Name	VRFYFNDSFORDRINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DRINTNOTC

Attribute	**Description**	
Name	DRINTNOTC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DRINTLIQDAY

Attribute	Description
Name	DRINTLIQDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,A

TOP

CHGSTRTADV

Attribute	Description
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVCDAYS

Attribute	Description
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FREBNKNGDAYS

Attribute	Description
Name	FREBNKNGDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDLST

Attribute	Description
Name	PRDLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,S,N

TOP

CCYLST

Attribute	**Description**
Name	CCYLST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

BRNLST

Attribute	**Description**
Name	BRNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

CUSATLST

Attribute	**Description**
Name	CUSATLST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	**Description**
Name	DEF_AUTODEP_AC_CLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AUTDEPTRNCD

Attribute	Description
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AUTDEPCCY

Attribute	Description
Name	AUTDEPCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBALREQD

Attribute	Description
Name	MINBALREQD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPMLTPLOF

Attribute	Description
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKDEPOSITFRST

Attribute	Description
Name	BRKDEPOSITFRST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDEPDERRATCD

Attribute	Description
Name	AUTDEPDERRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	**Description**
Name	PRVDINTONBRKNDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOROLL

Attribute	**Description**
Name	AUTOROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLSONMATURTY

Attribute	**Description**
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTLLIQDTN

Attribute	**Description**
Name	PRTLLIQDTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	Description
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRACEPRD

Attribute	Description
Name	GRACEPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRDAYS

Attribute	Description
Name	MINTNRDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRMNTHS

Attribute	**Description**
Name	MINTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRYRS

Attribute	**Description**
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRDAY

Attribute	**Description**
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRMNTHS

Attribute	**Description**
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRYRS

Attribute	**Description**
Name	DFLTTNRYRS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRMNTHS

Attribute	Description
Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRYRS

Attribute	Description
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDFLG

Attribute	Description
Name	RDFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MOVEFUNDOVD

Attribute	Description
Name	MOVEFUNDOVD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCHKREQD

Attribute	**Description**
Name	LMTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVRDRFTFACLTY

Attribute	**Description**
Name	OVRDRFTFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASBKFACLTY

Attribute	**Description**
Name	PASBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECBLE

Attribute	**Description**
Name	TRCKRECBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ACCSTATS

Attribute	Description	
Name	ACCSTATS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description	
Name	EXCLSAMDYRVRTRNSFMSTMNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description	
Name	ALLWBCKPRDENTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CONSOLDTNREQD

Attribute	Description	
Name	CONSOLDTNREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ICINCLSN

Attribute	Description
Name	ICINCLSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKACCREDIC

Attribute	Description
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASDRCRADV

Attribute	Description
Name	HASDRCRADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ILMAPPLICBL

Attribute	Description
Name	ILMAPPLICBL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATMFACLTY

Attribute	Description
Name	ATMFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENINTRIMSTMNT

Attribute	Description
Name	GENINTRIMSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENBALRPT

Attribute	Description
Name	GENBALRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRIMRPTSNCE

Attribute	Description
Name	INTRIMRPTSNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	Description
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	Description
Name	BALRPTSINCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 941,940,950,

TOP

BALRPTTYP

Attribute	**Description**
Name	BALRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,S,T,

TOP

STARTDT

Attribute	**Description**
Name	STARTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMNTPARAM1

Attribute	**Description**
Name	STMNTPARAM1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

STMNTPARAM2

Attribute	**Description**
Name	STMNTPARAM2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

STMNTPARAM3

Attribute	Description
Name	STMNTPARAM3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 22

TOP

ESCROWPROCESS

Attribute	Description
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRNCODE

Attribute	Description
Name	TRNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TRNREVCODE

Attribute	Description
Name	TRNREVCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MINOR_MAJOR

Attribute	Description
Name	MINOR_MAJOR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	**Description**
Name	REPL_CUST_SIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	**Description**
Name	MAX_NO_CHEQUE_REJECTIONS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SAL_BLK_DAYS

Attribute	**Description**
Name	SAL_BLK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	**Description**
Name	DAYSUNAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description
Name	SETTLE_BRIDGE_GL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

PCTXNCODE

Attribute	Description
Name	PCTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TDRATECHARTALLOW

Attribute	Description
Name	TDRATECHARTALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLUSTER_ID

Attribute	Description
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PROJECTACCNT

Attribute	Description
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	Description
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

LRGDRBALFLG

Attribute	**Description**
Name	LRGDRBALFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DAYLIGHTLIMIT

Attribute	**Description**
Name	DAYLIGHTLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNOVR_CODE

Attribute	**Description**
Name	TRNOVR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FREQUENCY

Attribute	**Description**
Name	FREQUENCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y,

TOP

DAYS

Attribute	Description	
Name	DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SEND_NOTIFICATION

Attribute	Description	
Name	SEND_NOTIFICATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	Description	
Name	RT_CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SPDANLSYS

Attribute	Description	
Name	SPDANLSYS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description
Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	Description
Name	COMP_WISE_TRACKING_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_SWEEP_IN

Attribute	Description
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	Description
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEPACCCLS

Attribute	Description
Name	DEPACCCLS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

RATECHARTTENOR

Attribute	**Description**
Name	RATECHARTTENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

HOLIDAYCALENDAR

Attribute	**Description**
Name	HOLIDAYCALENDAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	**Description**
Name	HOLIDAYMOVEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	**Description**
Name	MOVEACROSSMONTHS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,N,

TOP

ADHOCHOL

Attribute	Description	
Name	ADHOCHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description	
Name	APPLICABLEDEPTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description	
Name	MONTHENDDEPOSIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description	
Name	REPCKUPACCLSTNRONROLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEFERREDBALUPD

Attribute	**Description**
Name	DEFERREDBALUPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MULTICURRENCY

Attribute	**Description**
Name	MULTICURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MONTHS_C

Attribute	**Description**
Name	MONTHS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYS_C

Attribute	**Description**
Name	DAYS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	**Description**
Name	HIGH_VAL_DEPOSIT_C

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	**Description**
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

INSTBASIS

Attribute	**Description**
Name	INSTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L

TOP

MONTHEND_INST

Attribute	**Description**
Name	MONTHEND_INST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_DEPOSIT

Attribute	**Description**
Name	NOTICE_DEPOSIT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	Description
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICE_DAYS

Attribute	Description
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BONUS_INTEREST_C

Attribute	Description
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRANSACTION_CODE

Attribute	**Description**
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	**Description**
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	**Description**
Name	PREMAT_REDM_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UNCLAIMED_DAYS

Attribute	**Description**
Name	UNCLAIMED_DAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NC_DEPOSIT_C

Attribute	Description
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Status-Master

Attribute	Description
Name	Status-Master
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CR_CB

Attribute	Description
Name	CR_CB
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CR_LINE

Attribute	Description
Name	CR_LINE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CR_HO

Attribute	Description
Name	CR_HO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

DR_CB

Attribute	Description
Name	DR_CB
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

DR_LINE

Attribute	Description
Name	DR_LINE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

DR_HO

Attribute	Description
Name	DR_HO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RBKPROVSN

Attribute	Description

Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Status-Detail

Attribute	**Description**
Name	Status-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROL

Attribute	**Description**
Name	ACCROL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ROLDESC

Attribute	**Description**
Name	ROLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	**Description**
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	**Description**
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Status-Derivation

Attribute	**Description**
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STATRUL1

Attribute	Description
Name	STATRUL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL2

Attribute	Description
Name	STATRUL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL3

Attribute	Description
Name	STATRUL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL4

Attribute	Description
Name	STATRUL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL5

Attribute	Description

Name	STATRUL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

COMPONENT_PRIORITY1

Attribute	**Description**
Name	COMPONENT_PRIORITY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	**Description**
Name	COMPONENT_PRIORITY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	**Description**
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	**Description**
Name	Product-Maint
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

Products

Attribute	Description	
Name	Products	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

TOP

DRTXN

Attribute	Description
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	Description
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Transaction-Codes

Attribute	Description
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TXNCD

Attribute	Description
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRTXN

Attribute	Description

Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Restriction

Attribute	**Description**
Name	Branch-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Ccy-Restriction

Attribute	**Description**
Name	Ccy-Restriction
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CCYCD

Attribute	Description	
Name	CCYCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

Ccy-Preferences

Attribute	Description	
Name	Ccy-Preferences	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CCYCD

Attribute	Description	
Name	CCYCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

MINBAL

Attribute	Description	
Name	MINBAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

THRESHOLD_AMOUNT

Attribute	Description

Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Cat-Restriction

Attribute	**Description**
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTCAT

Attribute	**Description**
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Restriction

Attribute	**Description**
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Interim-Cramt

Attribute	Description
Name	Interim-Cramt
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	Description
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description

Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	**Description**
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	**Description**
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	**Description**
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	**Description**
Name	MNTHLYFREEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MANDATORY

Attribute	**Description**
Name	MANDATORY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	**Description**
Name	Sttms-Accls-Minmax-Amt-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MIN_AMOUNT

Attribute	**Description**
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	**Description**

Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOPUP_UNITS

Attribute	**Description**
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	**Description**
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AC_CLASS

Attribute	**Description**
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

Denom-Deposit

Attribute	**Description**
Name	Denom-Deposit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DENOMINATION_ID

Attribute	Description
Name	DENOMINATION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

DENOMINATION_DESC

Attribute	Description
Name	DENOMINATION_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

DENOMINATION_VALUE

Attribute	Description
Name	DENOMINATION_VALUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	Description

Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	**Description**
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYIN

Attribute	**Description**
Name	PAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INT_PAYOUT_C

Attribute	Description
Name	INT_PAYOUT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRI_PAYOUT_C

Attribute	Description
Name	PRI_PAYOUT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Exrate-Pref

Attribute	Description
Name	Exrate-Pref
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

PAYINOUT_C

Attribute	Description
Name	PAYINOUT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,O

TOP

MODE_TYPE_C

Attribute	Description
Name	MODE_TYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S

TOP

RATETYPE_C

Attribute	Description
Name	RATETYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

RATECODE_C

Attribute	Description
Name	RATECODE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

VARIANCE_C

Attribute	Description
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	Description
Name	Chan-Rest-C
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHANLID

Attribute	**Description**	
Name	CHANLID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CHANNDESC

Attribute	**Description**	
Name	CHANNDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Minmax-Ccy-C

Attribute	**Description**	
Name	Minmax-Ccy-C	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CURR

Attribute	**Description**	
Name	CURR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,W

TOP

DORM_PREP_DATE

Attribute	Description
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	Description
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_DAY

Attribute	Description
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 150 minLength: 0

TOP

Misaccdflt

Attribute	Description
Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MISCODE2

Attribute	Description
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCODE3

Attribute	Description
Name	MISCODE3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE4

Attribute	Description
Name	MISCODE4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE5

Attribute	Description
Name	MISCODE5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE6

Attribute	Description
Name	MISCODE6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE7

Attribute	Description
Name	MISCODE7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE8

Attribute	Description
Name	MISCODE8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE9

Attribute	Description
Name	MISCODE9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE3

Attribute	Description
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE4

Attribute	Description
Name	COSTCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE5

Attribute	Description
Name	COSTCODE5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCLASS

Attribute	**Description**
Name	ACCLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

MISGROUP

Attribute	**Description**
Name	MISGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCODE

Attribute	**Description**
Name	POOLCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE1

Attribute	**Description**
Name	MISCODE1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS1

Attribute	**Description**
Name	MISCLASS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS2

Attribute	**Description**
Name	MISCLASS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS3

Attribute	**Description**
Name	MISCLASS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS4

Attribute	**Description**
Name	MISCLASS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.30.CreateBranch

CreateBranch

2.30.1.ST-CreateBranch-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*

BRNADDR
BRNADDR2
BRNADDR3
SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC

EXTVAL
BRNAVALSTAT
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH

CASAAMTBLKTRNCODE

HOFFREQ

ALLWCORPACS

TRANSFER_TYPE

POSITION_ASSET_GL

POSITION_LIABILITY_GL

GL_CLASSS

CHEQUESTALEDAYS

TRANSACTION_CODE1

ELCM_REPLICATION

LMTEXP_NOTIFY_DAYS

REPORT_DSN

CHQNO_MASK

FILECONSTXNCODE

CNTRY_CKSUM_MASK

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Branch-Swift-Address

- *SWFTADRS*
- *DESC*

Branch-Customer-Params

- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions

- *FUNCID*

Branch-Ccy

- *CCYCD*
- *CCYDESC*

Branch-Message-Type

- *MODULE*
- *LCYMSGTYP*

Dup-Chk

- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description	
Name	PRNTBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REGNLOFC

Attribute	**Description**
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TIMLVL

Attribute	**Description**
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CNTRYCD

Attribute	**Description**
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

FUNDBRNCH

Attribute	Description
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CODATMBRN

Attribute	Description
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CODINSTID

Attribute	Description
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CODCUSTTRNS

Attribute	**Description**	
Name	CODCUSTTRNS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OFFSTHOURS

Attribute	**Description**	
Name	OFFSTHOURS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OFFSTMINS

Attribute	**Description**	
Name	OFFSTMINS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRNADDR

Attribute	**Description**	
Name	BRNADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNADDR3

Attribute	Description
Name	BRNADDR3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SWFTADDR

Attribute	Description
Name	SWFTADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	**Description**
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	**Description**
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	**Description**
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	**Description**
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CONVGL

Attribute	Description
Name	CONVGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONVTXNCD

Attribute	Description
Name	CONVTXNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CURRCYCLE

Attribute	Description
Name	CURRCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLGBRNCD

Attribute	Description
Name	CLGBRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CLRBRN

Attribute	Description
Name	CLRBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

CNTRYCDDESC

Attribute	Description	
Name	CNTRYCDDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SUSPGLSLDESC

Attribute	Description	
Name	SUSPGLSLDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CONTSUSPGLSLDESC

Attribute	Description	
Name	CONTSUSPGLSLDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SUSPGLFCYDESC

Attribute	Description	
Name	SUSPGLFCYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CONTSUSPGLFCYDESC

Attribute	Description
Name	CONTSUSPGLFCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ATMSUSPGLDESC

Attribute	Description
Name	ATMSUSPGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVGLDESC

Attribute	Description
Name	CONVGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVTXNCDDESC

Attribute	Description
Name	CONVTXNCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EXTVAL

Attribute	Description
Name	EXTVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNAVALSTAT

Attribute	Description
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CLRACC

Attribute	**Description**
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OFFSTCLRACC

Attribute	**Description**
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

WEEKHOL1

Attribute	**Description**
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	**Description**
Name	WEELHOL2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description	
Name	CLRBNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MISCCYMISMATCHGRP

Attribute	Description	
Name	MISCCYMISMATCHGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

INTERDICTCHKREQD

Attribute	Description	
Name	INTERDICTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTERDICTTIMOUT

Attribute	Description	
Name	INTERDICTTIMOUT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENTGL

Attribute	Description
Name	ENTGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	Description
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALDAYS

Attribute	Description
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	Description
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DRPRD

Attribute	**Description**	
Name	DRPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CRPRD

Attribute	**Description**	
Name	CRPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

IBANMSKBNKCD

Attribute	**Description**	
Name	IBANMSKBNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

IBANMSKACCNO

Attribute	**Description**	
Name	IBANMSKACCNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 500

TOP

DRPRDDESC

Attribute	Description
Name	DRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CRPRDDESC

Attribute	Description
Name	CRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRTAXCYCLE

Attribute	Description
Name	CURRTAXCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONSOLTXCERTREQD

Attribute	Description
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	Description
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SUSENTRYREQ

Attribute	Description
Name	SUSENTRYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUSBATCHNO

Attribute	Description
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SUSTXNCODE

Attribute	Description
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVSUSENTRYDAYS

Attribute	Description
Name	REVSUSENTRYDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CASAAMTBLKTRNCODE

Attribute	**Description**
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOFFREQ

Attribute	**Description**
Name	HOFFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWCORPACS

Attribute	**Description**
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFER_TYPE

Attribute	**Description**
Name	TRANSFER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	P,R,

TOP

POSITION_ASSET_GL

Attribute	Description
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

POSITION_LIABILITY_GL

Attribute	Description
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

GL_CLASSS

Attribute	Description
Name	GL_CLASSS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CHEQUESTALEDAYS

Attribute	Description
Name	CHEQUESTALEDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FILECONSTXNCODE

Attribute	Description	
Name	FILECONSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CNTRY_CKSUM_MASK

Attribute	Description	
Name	CNTRY_CKSUM_MASK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Branch-Swift-Address

Attribute	Description
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SWFTADRS

Attribute	Description
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYDESC

Attribute	**Description**
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Message-Type

Attribute	**Description**
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE

Attribute	**Description**
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

LCYMSGTYP

Attribute	**Description**
Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	S,M,P,

TOP

Dup-Chk

Attribute	Description
Name	Dup-Chk
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MODULE1

Attribute	Description
Name	MODULE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

DUP_FLG

Attribute	Description
Name	DUP_FLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DUP_DAY

Attribute	Description
Name	DUP_DAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Account-Params

Attribute	Description

Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACCMSK

Attribute	**Description**
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHKSUMALGO

Attribute	**Description**
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	**Description**
Name	STRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.30.2.ST-CreateBranch-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-IO*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*
    - *BRNADDR*
    - *BRNADDR2*
    - *BRNADDR3*
    - *SWFTADDR*

TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
EXTVAL
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS

TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
Branch-Swift-Address
- *SWFTADRS*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions

FUNCID
Branch-Ccy
CCYCD
Branch-Message-Type
LCYMSGTYP
Dup-Chk
MODULE1
DUP_FLG
DUP_DAY
Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description
Name	PRNTBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REGNLOFC

Attribute	Description
Name	REGNLOFC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRYCD

Attribute	Description
Name	CNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CIDIF

Attribute	Description
Name	CIDIF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

FUNDBRNCH

Attribute	Description
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CODATMBRN

Attribute	Description
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CODINSTID

Attribute	Description
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CODCUSTTRNS

Attribute	**Description**
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OFFSTHOURS

Attribute	**Description**
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OFFSTMINS

Attribute	**Description**
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRNADDR

Attribute	**Description**
Name	BRNADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNADDR3

Attribute	Description
Name	BRNADDR3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SWFTADDR

Attribute	Description
Name	SWFTADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	**Description**
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	**Description**
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PCCLRGBRN

Attribute	**Description**
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUSPGLSL

Attribute	**Description**
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONVGL

Attribute	Description
Name	CONVGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONVTXNCD

Attribute	Description
Name	CONVTXNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOAUTH

Attribute	**Description**
Name	AUTOAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GEN

Attribute	**Description**
Name	GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,

TOP

GEN103P

Attribute	**Description**
Name	GEN103P
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEFBNKOPCD

Attribute	**Description**
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLGBRNCD

Attribute	Description
Name	CLGBRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRBRN

Attribute	Description
Name	CLRBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXTVAL

Attribute	Description
Name	EXTVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description	
Name	WEELHOL2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description	
Name	CLRBNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MISCCYMISMATCHGRP

Attribute	Description	
Name	MISCCYMISMATCHGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

INTERDICTCHKREQD

Attribute	Description	
Name	INTERDICTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTERDICTTIMOUT

Attribute	Description
Name	INTERDICTTIMOUT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENTGL

Attribute	**Description**
Name	ENTGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	**Description**
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALDAYS

Attribute	**Description**
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	**Description**
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

CONSOLTXCERTREQD

Attribute	Description
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	Description
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUSENTRYREQ

Attribute	Description
Name	SUSENTRYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUSBATCHNO

Attribute	Description
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SUSTXNCODE

Attribute	Description
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVSUSENTRYDAYS

Attribute	Description
Name	REVSUSENTRYDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRANSFER_TYPE

Attribute	Description	
Name	TRANSFER_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,R,

TOP

POSITION_ASSET_GL

Attribute	Description	
Name	POSITION_ASSET_GL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

POSITION_LIABILITY_GL

Attribute	Description	
Name	POSITION_LIABILITY_GL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

GL_CLASSS

Attribute	Description	
Name	GL_CLASSS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CHEQUESTALEDAYS

Attribute	Description
Name	CHEQUESTALEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHQNO_MASK

Attribute	**Description**
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FILECONSTXNCODE

Attribute	**Description**
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Branch-Swift-Address

Attribute	**Description**
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Branch-Message-Type

Attribute	Description
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

LCYMSGTYP

Attribute	Description
Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,P,

TOP

Dup-Chk

Attribute	Description
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE1

Attribute	Description
Name	MODULE1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

DUP_FLG

Attribute	**Description**
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DUP_DAY

Attribute	**Description**
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Account-Params

Attribute	**Description**
Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	Description
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	Description
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	Description
Name	STRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.30.3.ST-CreateBranch-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*
    - *BRNADDR*
    - *BRNADDR2*
    - *BRNADDR3*

SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC
EXTVAL
BRNAVALSTAT
NETSUSPGL

WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS

TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
- *BRNCD*
- *CUSTACCMSK*

CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description

Name	PRNTBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGNLOFC

Attribute	**Description**
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TIMLVL

Attribute	**Description**
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRYCD

Attribute	**Description**
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

FUNDBRNCH

Attribute	**Description**
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNLCY

Attribute	**Description**
Name	BRNLCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CODATMBRN

Attribute	**Description**
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CODINSTID

Attribute	**Description**
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR2

Attribute	Description	
Name	BRNADDR2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR3

Attribute	Description	
Name	BRNADDR3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SWFTADDR

Attribute	Description	
Name	SWFTADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

TELEXADDR

Attribute	Description	
Name	TELEXADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	Description
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	Description
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	Description
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ATMSUSPGL

Attribute	Description	
Name	ATMSUSPGL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

CONVGL

Attribute	Description	
Name	CONVGL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CONVTXNCD

Attribute	Description	
Name	CONVTXNCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CURRCYCLE

Attribute	Description	
Name	CURRCYCLE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFSTMNTSTAT

Attribute	**Description**	
Name	DEFSTMNTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

GEN

Attribute	**Description**	
Name	GEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,

TOP

GEN103P

Attribute	**Description**	
Name	GEN103P	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFBNKOPCD

Attribute	**Description**	
Name	DEFBNKOPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	4

TOP

PROCWITHOUTFLOAT

Attribute	Description	
Name	PROCWITHOUTFLOAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLGBRNCD

Attribute	Description	
Name	CLGBRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECTORCD

Attribute	Description	
Name	SECTORCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CLRBRN

Attribute	Description	
Name	CLRBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNTRYCDDESC

Attribute	Description
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLSLDESC

Attribute	Description
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONTSUSPGLSLDESC

Attribute	Description
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLFCYDESC

Attribute	Description
Name	SUSPGLFCYDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONTSUSPGLFCYDESC

Attribute	**Description**	
Name	CONTSUSPGLFCYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ATMSUSPGLDESC

Attribute	**Description**	
Name	ATMSUSPGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVGLDESC

Attribute	**Description**	
Name	CONVGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVTXNCDDESC

Attribute	**Description**	
Name	CONVTXNCDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

EXTVAL

Attribute	Description
Name	EXTVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNAVALSTAT

Attribute	Description
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description
Name	CLRBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

MISCCYMISMATCHGRP

Attribute	Description
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

INTERDICTCHKREQD

Attribute	Description
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTERDICTTIMOUT

Attribute	Description
Name	INTERDICTTIMOUT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ENTGL

Attribute	**Description**
Name	ENTGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	**Description**
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BCKVALDAYS

Attribute	**Description**
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	**Description**
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LDAPTEMP

Attribute	**Description**
Name	LDAPTEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

DRPRDDESC

Attribute	**Description**
Name	DRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CRPRDDESC

Attribute	**Description**
Name	CRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRTAXCYCLE

Attribute	**Description**
Name	CURRTAXCYCLE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CONSOLTXCERTREQD

Attribute	**Description**
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	**Description**
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	**Description**
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	**Description**
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SUSENTRYREQ

Attribute	Description	
Name	SUSENTRYREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SUSBATCHNO

Attribute	Description	
Name	SUSBATCHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SUSTXNCODE

Attribute	Description	
Name	SUSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVSUSENTRYDAYS

Attribute	Description	
Name	REVSUSENTRYDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRANSFER_TYPE

Attribute	Description
Name	TRANSFER_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,

TOP

POSITION_ASSET_GL

Attribute	**Description**
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	**Description**
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GL_CLASSS

Attribute	**Description**
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	**Description**
Name	CHEQUESTALEDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRY_CKSUM_MASK

Attribute	Description
Name	CNTRY_CKSUM_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Branch-Swift-Address

Attribute	**Description**
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Message-Type

Attribute	Description
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

LCYMSGTYP

Attribute	Description

Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,M,P,

TOP

Dup-Chk

Attribute	**Description**
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MODULE1

Attribute	**Description**
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

DUP_FLG

Attribute	**Description**
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUP_DAY

Attribute	**Description**
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	Description
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	Description
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	Description
Name	STRTACCNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDACCNO

Attribute	**Description**
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	**Description**
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDAUTOACCFLG

Attribute	**Description**
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOSTRTACCNO

Attribute	**Description**
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.30.4.ST-CreateBranch-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Branch-Details-PK*
      - *BRNCD*
    - *Branch-Details-IO*
      - *BRNCD*
      - *BRNNAME*
      - *PRNTBRN*
      - *REGNLOFC*
      - *CNTRYCD*
      - *CIDIF*
      - *FUNDBRNCH*
      - *BRNLCY*
      - *CODATMBRN*
      - *CODINSTID*
      - *CODIBTRNCD*
      - *CODCUSTTRNS*
      - *OFFSTHOURS*
      - *OFFSTMINS*
      - *BRNADDR*

BRNADDR2
BRNADDR3
SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
EXTVAL
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT

ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
Branch-Swift-Address
- *SWFTADRS*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*

START_PID_NO

END_PID_NO

Branch-Functions

FUNCID

Branch-Ccy

CCYCD

Branch-Message-Type

LCYMSGTYP

Dup-Chk

MODULE1

DUP_FLG

DUP_DAY

Account-Params

BRNCD

CUSTACCMSK

CHKSUMALGO

STRTACCNO

ENDACCNO

ACAUTOGENFLG

LDAUTOACCFLG

AUTOSTRTACCNO

AUTOENDACCNO

CUSTACCALG

CUSTNOALG

FNDSTACNO

FNDEDACNO

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Branch-Details-PK

Attribute	Description
Name	Branch-Details-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRNTBRN

Attribute	Description
Name	PRNTBRN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REGNLOFC

Attribute	Description
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CNTRYCD

Attribute	Description
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIDIF

Attribute	Description
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

FUNDBRNCH

Attribute	Description
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODATMBRN

Attribute	Description
Name	CODATMBRN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CODINSTID

Attribute	Description
Name	CODINSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR3

Attribute	Description	
Name	BRNADDR3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SWFTADDR

Attribute	Description	
Name	SWFTADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

TELEXADDR

Attribute	Description	
Name	TELEXADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	14

TOP

HOSTNAM

Attribute	Description	
Name	HOSTNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

OFFSTHRS

Attribute	Description
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	Description
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONVGL

Attribute	Description
Name	CONVGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CONVTXNCD

Attribute	**Description**
Name	CONVTXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFHR

Attribute	**Description**
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFMIN

Attribute	**Description**
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

JOBSTAT

Attribute	**Description**
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOAUTH

Attribute	**Description**
Name	AUTOAUTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLGBRNCD

Attribute	Description
Name	CLGBRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRBRN

Attribute	Description
Name	CLRBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXTVAL

Attribute	Description
Name	EXTVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	**Description**
Name	CLRBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MISCCYMISMATCHGRP

Attribute	**Description**
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INTERDICTCHKREQD

Attribute	**Description**
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTERDICTTIMOUT

Attribute	**Description**
Name	INTERDICTTIMOUT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENTGL

Attribute	Description
Name	ENTGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	Description
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALDAYS

Attribute	Description
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	Description
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRPRD

Attribute	**Description**
Name	DRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CRPRD

Attribute	**Description**
Name	CRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

IBANMSKBNKCD

Attribute	**Description**
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

IBANMSKACCNO

Attribute	**Description**
Name	IBANMSKACCNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

LDAPTEMP

Attribute	**Description**	
Name	LDAPTEMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

CONSOLTXCERTREQD

Attribute	**Description**	
Name	CONSOLTXCERTREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDIVTAXVERTREQD

Attribute	**Description**	
Name	INDIVTAXVERTREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TAXCERTFREQ

Attribute	**Description**	
Name	TAXCERTFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SUSENTRYREQ

Attribute	Description	
Name	SUSENTRYREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SUSBATCHNO

Attribute	Description	
Name	SUSBATCHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SUSTXNCODE

Attribute	Description	
Name	SUSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVSUSENTRYDAYS

Attribute	Description	
Name	REVSUSENTRYDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRANSFER_TYPE

Attribute	Description
Name	TRANSFER_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,

TOP

POSITION_ASSET_GL

Attribute	**Description**
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	**Description**
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GL_CLASSS

Attribute	**Description**
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	**Description**
Name	CHEQUESTALEDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

Branch-Swift-Address

Attribute	Description
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SWFTADRS

Attribute	Description
Name	SWFTADRS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 12

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Branch-Message-Type

Attribute	**Description**
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

LCYMSGTYP

Attribute	**Description**
Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,P,

TOP

Dup-Chk

Attribute	**Description**
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE1

Attribute	**Description**
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

DUP_FLG

Attribute	Description
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DUP_DAY

Attribute	Description
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	Description
Name	CUSTACCMSK
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHKSUMALGO

Attribute	**Description**
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	**Description**
Name	STRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDACCNO

Attribute	**Description**
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	**Description**
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Attribute	Description
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.createSaveRLAppEntry

Offline save of RLAPP entry

2.31.1.OR-CreateSaveRLAppEntry-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Applicationhead-Full*
    - *APPNO*
    - *DATE*
    - *PRDCD*
    - *CHNL*
    - *BRN*
    - *STAT*
    - *INTERCD*
    - *INTNAME*
    - *CUSTTYPE1*
    - *CCY*
    - *LEAD*
    - *CONT*
    - *PUR*
    - *USERREFNO*
    - *APPCAT*

ENQUIRY_ID
OFFAPPLNUM
Customer1
- *CUSTNO*
- *SALUT*
- *FSTNM*
- *MIDNM*
- *LSTNM*
- *NATID*
- *DOB*
- *MOTHERNM*
- *LANG*
- *DEPEND*
- *EMAIL*
- *MARSTAT*
- *EXISTING*
- *PASSNO*
- *PASSISSDT*
- *PASSEXPDT*
- *MOBNO*
- *LANDNO*
- *OFFNO*
- *FAX*
- *CUSTTYPE*
- *FINCCY*
- *ACCLS*
- *ACCNUM*
- *GENDER*
- *SNAME*
- *CNTY*
- *NLTY*
- *CUST_CATEG*
- *Customer2*
  - *APPNO*
  - *CUSTNO*
  - *ADDTYPE*
  - *MAILING*
  - *CONNO*
  - *ADDLN1*
  - *ADDLN2*
  - *ADDLN3*
  - *ZIP*
  - *CNTY*
- *Customer3*

APPNO
CUSTNO
EMPTYPE
EMP
CUSTOCC
DESIG
ADDLN1
ADDLN2
ADDLN3
ZIP
CNTY
PHONE
EXTN
CONTACT
CONPHN
CONPHNEXTN
COMMENT
DEPT
EMPID
EMPYR
EMPMNTH
INCCCY
INCAMT
FREQ
CONTACT_NAME

Financials1

APPNO
CUSTNO
ASSETTYP
ASSETSUB
MAKE
MODEL
MANYR
BODY
HOUSENO
ASSETDESC
ASSETVL
ADDLN1
ADDLN2
ADDLN3
WIDTH
LENGTH
OCCUPANCY
REGNO

Financials2
- *LIABTYP*
- *LIABSUB*
- *LIABFREQ*
- *LAIBAMT*
- *BAL*
- *REM*
- *LIABSTDT*
- *LIABENDDT*

Finsummary
- *MONSTATINC*
- *MONACTINC*
- *MONSTATDEBT*
- *MONACTDEBT*
- *GRADE*
- *SCORE*
- *ASSETWORTH*
- *LIABWORTH*
- *TOTWOR*
- *WHTPMT*
- *Finsummary2*
  - *RATNM*
  - *STATBF*
  - *STATAF*
  - *ACTBF*
  - *ACTAF*

Investi1
- *CUSTNO*
- *VERTYPE*
- *AGENCY*

Investi2
- *SPOKE*
- *ATTEMPTS*
- *CALLDT*
- *RESULT*
- *VERMAT*
- *REM*

Custdedupe
- *CTYPE*
- *FSTNM*
- *LSTNM*
- *SNAME*
- *NATID*
- *CNT*

- *NAT*
- *CCAT*
- *DOB*
- *LANG*
- *EMAIL*
- *EXISTING*
- *PASSNO*
- *MOBNO*
- *LANDNO*

Financials3

- *APPNO*
- *CUSTNO*
- *INCTYPE*
- *CCY*
- *AMT*
- *FREQ*

Cusudf

- *NAME*
- *VALUE*

Cust-Acct

- *CUSTNO*
- *ACCLS*
- *ACCCY*
- *ACMASK*
- *CCYTYPE*
- *ACODE*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

Collat1

- *APPNO*
- *CUSTNO*
- *COLLCD*
- *COLLDESC*
- *COLLCCY*
- *COLLVL*
- *COLLSTDT*
- *COLLENDDT*
- *COLLCAT*
- *COLLHAIR*
- *COLLTYPE*
- *COLLREVDT*
- *COLLCHGDT*
- *COLLREVLDT*

- *COLLREVCHK*
- *SECUID*
- *NOMUNITVL*
- *CAPAMT*
- *GUAID*
- *RATIN*
- *Collat2*
  - *DUEDT*
  - *STMON*
  - *REM*
  - *COVNM*
  - *DESC*
  - *REVDT*
  - *MANDT*
  - *GRCDAY*
  - *NOTDAY*
  - *FREQ*
- *Veh-Details*
  - *VEH_IDNUM*
  - *VEH_YEAR*
  - *VEH_MAKE*
  - *VEH_MODEL*
  - *VEH_BDYSTYLE*
  - *VEH_USAGE*

Requested1

- *APPNO*
- *PRDCD*
- *REQAMT*
- *TENORM*
- *INTEREST_RATE_TYPE*
- *DPMNTAMT*
- *PROMO*
- *CCY*
- *Requested2*
  - *ITEMIZATION*
  - *REQAMT*
  - *COMMENT*

Comments

- *APPNO*
- *PRDCD*
- *SEQUENCENUMBER*
- *COMMENT*
- *COMMBY*
- *COMMDT*

Udf

- *L1*
- *L2*
- *L3*
- *L4*
- *L5*
- *L6*
- *L7*
- *L8*
- *L9*
- *L10*
- *L11*
- *L12*
- *L13*
- *L14*
- *L15*
- *L16*
- *L17*
- *L18*
- *L19*
- *L20*
- *F1*
- *F2*
- *F3*
- *F4*
- *F5*
- *F6*
- *F7*
- *F8*
- *F9*
- *F10*
- *F11*
- *F12*
- *F13*
- *F14*
- *F15*
- *F16*
- *F17*
- *F18*
- *F19*
- *F20*
- *B1*
- *B2*
- *B3*

- *B4*
- *B5*
- *B6*

Chklst1

- *CHKLSTID*
- *CHKLSTDESC*
- *VERIFY*
- *COMMENT*

Custudf

- *NAME*
- *DESC*

Tradein

- *ASSETTYP*
- *ASSETSUBTYP*
- *MAKE*
- *MODEL*
- *MANYR*
- *BODY*
- *ASSETIDNO*
- *ASSETDESC*
- *ASSETWHVL*
- *ASSETBSVL*
- *PAYAMT*
- *ASSETADDON1*
- *TOTVAL*
- *ASSETVLDT*
- *ASSETSOURCE*
- *ASSETSUPP*
- *ASSETEDI*
- *CURR*

Loanoffers

- *OFFID*
- *RATE*
- *NOOFINST*
- *FREQUNIT*
- *FREQ*
- *RATECD*
- *SPREAD*
- *EFFRATE*
- *CHECK*

Loan2

- *LOANCCY*
- *LOANAMT*
- *RATE*

DPMNTAMT
TAX
VALDT
MATDT
NOOFINST
FREQUNIT
FREQ
SPREAD
EFFRATE
CLACCNO
INSSTDT
Loan3
NO1
FREQ
UNIT
FRSTDUEDT
AMT
SCHTYP
COMPNM
Loan4
SCHNO
DUEDT
AMTDUE
EMI_AMOUNT
AMORPRI
INTEREST_AMOUNT
CAPI
WAIVE
COMPNM
Crdratout
EXTAGEN
RECOMM
Crdratin
CUSTNO
APPNO
GRD
SCR
RULEID
Crratin2
APPNO
CUSTNO
QUES
ANS
CAT

- *Bureau*
  - *CUSTID*
  - *BUREAU*
  - *RPTTYP*
  - *STAT*
- *Chgs*
  - *EVENTCD*
  - *CHGCCY*
  - *AMT*
  - *AMTSETT*
  - *SCHDUEDT*
  - *WAIV*
  - *COMPNM*
- *Loandedupe*
  - *CCY*
  - *VALDT*
  - *MATDT*
  - *CUSTNO*
  - *LOAN_ACCNO*
  - *AMT*
  - *OUTSTAMT*
  - *RATE*
- *Riskfactor*
  - *RISKFACT*
  - *DESC*
- *Chgs1*
- *Promotions*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Applicationhead-Full

Attribute	Description
Name	Applicationhead-Full
Datatype	
Description	

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	Indicates Incorporation Date

Attributes	Attribute	Description
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHNL

Attribute	Description	
Name	CHNL	
Datatype	String	
Description	Indicates Originating Channel of Application	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates the Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	NEWAPP,VFYAPP,UNDERW,UNAPPR,CHKDOC,FIVERI,FUNDED

TOP

INTERCD

Attribute	Description
Name	INTERCD
Datatype	String
Description	Indicates Intermediary Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTNAME

Attribute	Description
Name	INTNAME
Datatype	String
Description	Indicates Intermediary Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTTYPE1

Attribute	Description
Name	CUSTTYPE1
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LEAD

Attribute	Description
Name	LEAD
Datatype	String
Description	Indicates Lead Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CONT

Attribute	Description
Name	CONT
Datatype	String
Description	Indicates Contact Person
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PUR

Attribute	Description
Name	PUR
Datatype	String
Description	Indicates Loan Purpose
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	Indicates User Reference Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

APPCAT

Attribute	Description
Name	APPCAT

Datatype	String
Description	Indicates Application Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ENQUIRY_ID

Attribute	**Description**
Name	ENQUIRY_ID
Datatype	String
Description	Indicates Enquiry Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OFFAPPLNUM

Attribute	**Description**
Name	OFFAPPLNUM
Datatype	String
Description	Indicates Offline Application Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Customer1

Attribute	**Description**
Name	Customer1
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

SALUT

Attribute	Description
Name	SALUT
Datatype	String
Description	Indicates Salutation
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Mr,Mrs,Miss,Dr

TOP

FSTNM

Attribute	Description
Name	FSTNM
Datatype	String
Description	Indicates First Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MIDNM

Attribute	Description
Name	MIDNM
Datatype	String
Description	Indicates Middle Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LSTNM

Attribute	Description
Name	LSTNM
Datatype	String
Description	Indicates Last Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

NATID

Attribute	Description
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	Indicates Date of Birth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOTHERNM

Attribute	Description
Name	MOTHERNM
Datatype	String
Description	Indicates Mothers Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEPEND

Attribute	Description
Name	DEPEND

Datatype	Number
Description	Indicates No of Dependencies
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	Indicates Customer Email
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

MARSTAT

Attribute	Description
Name	MARSTAT
Datatype	String
Description	Indicates Marital Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,U,D

TOP

EXISTING

Attribute	Description
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASSNO

Attribute	Description
Name	PASSNO
Datatype	String
Description	Indicates Passport Number
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PASSISSDT

Attribute	Description
Name	PASSISSDT
Datatype	Date
Description	Indicates Passport Issue Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PASSEXPDT

Attribute	Description
Name	PASSEXPDT
Datatype	Date
Description	Indicates Passport Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Landline Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OFFNO

Attribute	Description
Name	OFFNO
Datatype	Number
Description	Indicates Office Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FAX

Attribute	Description
Name	FAX
Datatype	Number
Description	Indicates Customer Fax
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTTYPE

Attribute	Description
Name	CUSTTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

FINCCY

Attribute	Description
Name	FINCCY
Datatype	String
Description	Indicates Financial Details Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Settlement Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACCNUM

Attribute	Description
Name	ACCNUM

Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

GENDER

Attribute	**Description**
Name	GENDER
Datatype	String
Description	Indicates Customer Gender
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,F

TOP

SNAME

Attribute	**Description**
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CNTY

Attribute	**Description**
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CUST_CATEG

Attribute	Description
Name	CUST_CATEG
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Customer2

Attribute	Description
Name	Customer2
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDTYPE

Attribute	Description
Name	ADDTYPE
Datatype	String
Description	Indicates Address Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / P,H,W,T,O

TOP

MAILING

Attribute	Description
Name	MAILING
Datatype	String
Description	Indicates whether Mailing Address
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONNO

Attribute	Description
Name	CONNO
Datatype	Number
Description	Indicates Contact Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2

Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customer3

Attribute	Description
Name	Customer3
Datatype	
Description	Indicates Director Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EMPTYPE

Attribute	Description
Name	EMPTYPE
Datatype	String
Description	Indicates Employment Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PART,FULL,CONT

TOP

EMP

Attribute	Description
Name	EMP
Datatype	String
Description	Indicates Employer
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTOCC

Attribute	Description
Name	CUSTOCC
Datatype	String
Description	Indicates Customer Occupation
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

DESIG

Attribute	Description
Name	DESIG
Datatype	String
Description	Indicates Designation
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3

Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PHONE

Attribute	Description
Name	PHONE
Datatype	Number
Description	Indicates Phone Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXTN

Attribute	Description
Name	EXTN
Datatype	Number
Description	Indicates Customer Extension
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTACT

Attribute	Description
Name	CONTACT
Datatype	Number
Description	Indicates Customer Contact
Attributes	Attribute: minOccurs, Description: 0

TOP

CONPHN

Attribute	Description
Name	CONPHN
Datatype	Number
Description	Indicates Contact Phone Number
Attributes	Attribute: minOccurs, Description: 0

TOP

CONPHNEXTN

Attribute	Description
Name	CONPHNEXTN
Datatype	Number
Description	Indicates Contact Phone Extension
Attributes	Attribute: minOccurs, Description: 0

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comments
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

DEPT

Attribute	Description
Name	DEPT
Datatype	String
Description	Indicates Customer Department
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

EMPID

Attribute	Description
Name	EMPID
Datatype	String
Description	Indicates Employee Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EMPYR

Attribute	Description
Name	EMPYR
Datatype	Number
Description	Indicates Employed Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPMNTH

Attribute	Description
Name	EMPMNTH
Datatype	Number
Description	Indicates Employed Months
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCCCY

Attribute	Description
Name	INCCCY
Datatype	String
Description	Indicates Income Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INCAMT

Attribute	Description
Name	INCAMT
Datatype	Number
Description	Indicates Income Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates Income Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M,B,W

TOP

CONTACT_NAME

Attribute	Description	
Name	CONTACT_NAME	
Datatype	String	
Description	Indicates Customer Contact Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Financials1

Attribute	Description	
Name	Financials1	
Datatype		
Description	Indicates Customer Financial Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETTYP

Attribute	Description
Name	ASSETTYP
Datatype	String
Description	Indicates Asset Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / V,H,O

TOP

ASSETSUB

Attribute	Description
Name	ASSETSUB
Datatype	String
Description	Indicates Asset Sub Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKE

Attribute	Description
Name	MAKE
Datatype	Number
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODEL

Attribute	Description
Name	MODEL
Datatype	String

Description	Indicates Model Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MANYR

Attribute	**Description**
Name	MANYR
Datatype	Number
Description	Indicates Manufacture Year
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BODY

Attribute	**Description**
Name	BODY
Datatype	String
Description	Indicates Vehicle Body Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOUSENO

Attribute	**Description**
Name	HOUSENO
Datatype	String
Description	Indicates House Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETDESC

Attribute	**Description**
Name	ASSETDESC
Datatype	String
Description	Indicates Asset Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASSETVL

Attribute	Description
Name	ASSETVL
Datatype	Number
Description	Indicates Asset Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

WIDTH

Attribute	Description
Name	WIDTH

Datatype	Number
Description	Indicates Width
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LENGTH

Attribute	**Description**
Name	LENGTH
Datatype	Number
Description	Indicates Length
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OCCUPANCY

Attribute	**Description**
Name	OCCUPANCY
Datatype	Number
Description	Indicates Occupancy
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REGNO

Attribute	**Description**
Name	REGNO
Datatype	Number
Description	Indicates Registration Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Financials2

Attribute	**Description**
Name	Financials2
Datatype	
Description	Indicates Customer Liability Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

LIABTYP

Attribute	**Description**
Name	LIABTYP
Datatype	String
Description	Indicates Liability Type

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	LO,LE,RE,OT

TOP

LIABSUB

Attribute	Description	
Name	LIABSUB	
Datatype	String	
Description	Indicates Liability Sub Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

LIABFREQ

Attribute	Description	
Name	LIABFREQ	
Datatype	String	
Description	Indicates Liability Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y

TOP

LAIBAMT

Attribute	Description	
Name	LAIBAMT	
Datatype	Number	
Description	Indicates Liability Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BAL

Attribute	Description	
Name	BAL	
Datatype	Number	
Description	Indicates Liability Outstanding Balance	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LIABSTDT

Attribute	Description
Name	LIABSTDT
Datatype	Date
Description	Indicates Liability Start Date
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABENDDT

Attribute	Description
Name	LIABENDDT
Datatype	Date
Description	Indicates Liability End Date
Attributes	Attribute: minOccurs — Description: 0

TOP

Finsummary

Attribute	Description
Name	Finsummary
Datatype	
Description	Indicates Asset Details
Attributes	Attribute: minOccurs — Description: 0

TOP

MONSTATINC

Attribute	Description
Name	MONSTATINC
Datatype	Number
Description	Indicates Monthly Stated Income
Attributes	Attribute: minOccurs — Description: 0

TOP

MONACTINC

Attribute	Description
Name	MONACTINC
Datatype	Number
Description	Indicates Monthly Actual Income
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONSTATDEBT

Attribute	Description
Name	MONSTATDEBT
Datatype	Number
Description	Indicates Monthly Stated Debt
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTDEBT

Attribute	Description
Name	MONACTDEBT
Datatype	Number
Description	Indicates Monthly Actual Debt
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRADE

Attribute	Description
Name	GRADE
Datatype	String
Description	Indicates Internal Final Grade
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SCORE

Attribute	Description
Name	SCORE
Datatype	Number
Description	Indicates Internal Credit Score
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ASSETWORTH

Attribute	Description
Name	ASSETWORTH
Datatype	Number
Description	Indicates Asset Value
Attributes	Attribute: minOccurs, Description: 0

TOP

LIABWORTH

Attribute	Description
Name	LIABWORTH
Datatype	Number
Description	Indicates Total Liabilities
Attributes	Attribute: minOccurs, Description: 0

TOP

TOTWOR

Attribute	Description
Name	TOTWOR
Datatype	Number
Description	Indicates Total Net worth
Attributes	Attribute: minOccurs, Description: 0

TOP

WHTPMT

Attribute	Description
Name	WHTPMT
Datatype	Number
Description	Indicates What if Payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

Finsummary2

Attribute	Description
Name	Finsummary2
Datatype	
Description	Indicates Consolidated Financial Summary Information
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

RATNM

Attribute	Description
Name	RATNM
Datatype	String
Description	Indicates Ratio Name
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATBF

Attribute	Description
Name	STATBF
Datatype	String
Description	Indicates Ratio based on Stated Financials After Accounting for Payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATAF

Attribute	Description
Name	STATAF
Datatype	String
Description	Indicates Ratio based on Stated Financials After Accounting for Payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ACTBF

Attribute	Description
Name	ACTBF
Datatype	String
Description	Indicates Ratio based on Actual Financials Before Accounting for Payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ACTAF

Attribute	Description
Name	ACTAF
Datatype	String
Description	Indicates Ratio based on Actual Financials After Accounting for Payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Investi1

Attribute	Description
Name	Investi1
Datatype	
Description	Indicates Investigation Summary
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VERTYPE

Attribute	Description
Name	VERTYPE
Datatype	String
Description	Indicates Verification Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGENCY

Attribute	Description
Name	AGENCY
Datatype	String
Description	Indicates Investigating Agency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Investi2

Attribute	Description
Name	Investi2
Datatype	
Description	Indicates Investigation Details
Attributes	Attribute: minOccurs — Description: 0

TOP

SPOKE

Attribute	Description
Name	SPOKE
Datatype	String
Description	Indicates who the Agency Contacted
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ATTEMPTS

Attribute	Description
Name	ATTEMPTS
Datatype	Number
Description	Indicates No of Attempts
Attributes	Attribute: minOccurs — Description: 0

TOP

CALLDT

Attribute	Description
Name	CALLDT
Datatype	Date
Description	Indicates Called Date
Attributes	Attribute: minOccurs — Description: 0

TOP

RESULT

Attribute	Description
Name	RESULT
Datatype	String
Description	Indicates Investigation Result
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERMAT

Attribute	Description
Name	VERMAT
Datatype	String
Description	Indicates whether Verification Matched
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custdedupe

Attribute	Description
Name	Custdedupe
Datatype	
Description	Indicates Possible Duplicate Customer Names
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CTYPE

Attribute	Description

Name	CTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FSTNM

Attribute	**Description**
Name	FSTNM
Datatype	String
Description	Indicates First Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LSTNM

Attribute	**Description**
Name	LSTNM
Datatype	String
Description	Indicates Last Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNAME

Attribute	**Description**
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NATID

Attribute	**Description**
Name	NATID
Datatype	String
Description	Indicates National Id

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CNT

Attribute	Description
Name	CNT
Datatype	String
Description	Indicates Counter Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

NAT

Attribute	Description
Name	NAT
Datatype	String
Description	Indicates Nationality
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCAT

Attribute	Description
Name	CCAT
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	Indicates Date of Birth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	Indicates Customer Email
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

EXISTING

Attribute	Description
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASSNO

Attribute	Description
Name	PASSNO
Datatype	String
Description	Indicates Passport Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Landline Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Financials3

Attribute	Description
Name	Financials3
Datatype	
Description	Indicates Customer Income Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

INCTYPE

Attribute	Description
Name	INCTYPE
Datatype	String
Description	Indicates Income Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,R,B,O

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,M,B,W

TOP

Cusudf

Attribute	Description
Name	Cusudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

Cust-Acct

Attribute	Description
Name	Cust-Acct
Datatype	
Description	Indicates Customer Account Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACCLS

Attribute	Description
Name	ACCLS

Datatype	String
Description	Indicates Settlement Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates Customer Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACMASK

Attribute	Description
Name	ACMASK
Datatype	String
Description	Indicates Customer Account Mask
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CCYTYPE

Attribute	Description
Name	CCYTYPE
Datatype	String
Description	Indicates Currency Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACODE

Attribute	Description
Name	ACODE
Datatype	String
Description	Indicates Account Number

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 150
	minLength / 0

TOP

Collat1

Attribute	Description
Name	Collat1
Datatype	
Description	Indicates Collateral Details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLCD

Attribute	Description
Name	COLLCD
Datatype	String
Description	Indicates Collateral Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	Indicates Collateral Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	Indicates Collateral Value
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLSTDT

Attribute	Description
Name	COLLSTDT
Datatype	Date
Description	Indicates Collateral Start Date
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLENDDT

Attribute	Description
Name	COLLENDDT
Datatype	Date
Description	Indicates Collateral End Date
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	Indicates Collateral Category
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	Indicates Collateral Haircut Margin
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,M,G

TOP

COLLREVDT

Attribute	Description
Name	COLLREVDT
Datatype	Date
Description	Indicates Collateral Revision Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCHGDT

Attribute	Description
Name	COLLCHGDT
Datatype	String
Description	Indicates Collateral
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,L,P,H,A

TOP

COLLREVLDT

Attribute	Description
Name	COLLREVLDT
Datatype	Date
Description	Indicates Collateral Revaluation Date

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLREVCHK

Attribute	Description
Name	COLLREVCHK
Datatype	String
Description	Indicates whether Collateral Revaluation is Required
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

NOMUNITVL

Attribute	Description
Name	NOMUNITVL
Datatype	Number
Description	Indicates Nominal Unit Value
Attributes	Attribute: minOccurs; Description: 0

TOP

CAPAMT

Attribute	Description
Name	CAPAMT
Datatype	Number
Description	Indicates Collateral Cap Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

GUAID

Attribute	Description
Name	GUAID

Datatype	String
Description	Indicates Guarantor Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RATIN

Attribute	Description
Name	RATIN
Datatype	String
Description	Indicates Rating
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Collat2

Attribute	Description
Name	Collat2
Datatype	
Description	Indicates Collateral Covenant Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STMON

Attribute	Description
Name	STMON
Datatype	String
Description	Indicates Start Month
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVNM

Attribute	Description
Name	COVNM
Datatype	String
Description	Indicates Covenant Name
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	Indicates Revision Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MANDT

Attribute	Description
Name	MANDT

Datatype	Date
Description	Indicates whether Covenant is Mandatory
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAY

Attribute	**Description**
Name	GRCDAY
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDAY

Attribute	**Description**
Name	NOTDAY
Datatype	Number
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

Veh-Details

Attribute	**Description**
Name	Veh-Details
Datatype	
Description	Indicates Vehicle Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VEH_IDNUM

Attribute	**Description**
Name	VEH_IDNUM

Datatype	String
Description	Indicates Vehicle Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_YEAR

Attribute	Description
Name	VEH_YEAR
Datatype	Number
Description	Indicates Vehicle Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_MAKE

Attribute	Description
Name	VEH_MAKE
Datatype	String
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_MODEL

Attribute	Description
Name	VEH_MODEL
Datatype	String
Description	Indicates Vehicle Model
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_BDYSTYLE

Attribute	Description
Name	VEH_BDYSTYLE
Datatype	String
Description	Indicates Vehicle Body Style
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VEH_USAGE

Attribute	**Description**
Name	VEH_USAGE
Datatype	String
Description	Indicates Vehicle Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Requested1

Attribute	**Description**
Name	Requested1
Datatype	
Description	Indicates Overall Loan Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

REQAMT

Attribute	Description
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	Attribute: minOccurs, Description: 1

TOP

TENORM

Attribute	Description
Name	TENORM
Datatype	Number
Description	Indicates Loan Tenor
Attributes	Attribute: minOccurs, Description: 0

TOP

INTEREST_RATE_TYPE

Attribute	Description
Name	INTEREST_RATE_TYPE
Datatype	Number
Description	Indicates Interest Rate Type
Attributes	Attribute: minOccurs, Description: 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

PROMO

Attribute	Description
Name	PROMO
Datatype	String
Description	Indicates Promotion Id
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Requested2

Attribute	Description
Name	Requested2
Datatype	
Description	Indicates Individual Request Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ITEMIZATION

Attribute	Description
Name	ITEMIZATION
Datatype	String
Description	Indicates Itemization Details
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REQAMT

Attribute	Description
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comments

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Comments

Attribute	Description	
Name	Comments	
Datatype		
Description	Indicates Comment Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SEQUENCENUMBER

Attribute	Description	
Name	SEQUENCENUMBER	
Datatype	String	
Description	Indicates Comment Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMBY

Attribute	Description
Name	COMMBY
Datatype	String
Description	Indicates User who input Comment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMDT

Attribute	Description
Name	COMMDT
Datatype	Date
Description	Indicates Comment Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Udf

Attribute	Description
Name	Udf
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

L1

Attribute	Description
Name	L1
Datatype	String
Description	Indicates User Defined Field

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L2

Attribute	**Description**	
Name	L2	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L3

Attribute	**Description**	
Name	L3	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L4

Attribute	**Description**	
Name	L4	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

L5

Attribute	**Description**	
Name	L5	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L6

Attribute	**Description**
Name	L6
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L7

Attribute	**Description**
Name	L7
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L8

Attribute	**Description**
Name	L8
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L9

Attribute	**Description**
Name	L9
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L10

Attribute	Description
Name	L10
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

L11

Attribute	Description
Name	L11
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

L12

Attribute	Description
Name	L12
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

L13

Attribute	Description
Name	L13
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

L14

Attribute	Description
Name	L14
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L15

Attribute	Description
Name	L15
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L16

Attribute	Description
Name	L16
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L17

Attribute	Description
Name	L17
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L18

Attribute	Description
Name	L18

Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L19

Attribute	**Description**
Name	L19
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L20

Attribute	**Description**
Name	L20
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F1

Attribute	**Description**
Name	F1
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F2

Attribute	**Description**
Name	F2
Datatype	String
Description	Indicates User Defined Field

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F3

Attribute	**Description**
Name	F3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F4

Attribute	**Description**
Name	F4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F5

Attribute	**Description**
Name	F5
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F6

Attribute	**Description**
Name	F6
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

F7

Attribute	Description
Name	F7
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F8

Attribute	Description
Name	F8
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F9

Attribute	Description
Name	F9
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F10

Attribute	Description
Name	F10
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F11

Attribute	Description
Name	F11
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F12

Attribute	Description
Name	F12
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F13

Attribute	Description
Name	F13
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F14

Attribute	Description
Name	F14
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F15

Attribute	Description
Name	F15
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F16

Attribute	Description
Name	F16
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F17

Attribute	Description
Name	F17
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F18

Attribute	Description
Name	F18
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F19

Attribute	Description
Name	F19

Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F20

Attribute	Description
Name	F20
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B1

Attribute	Description
Name	B1
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B2

Attribute	Description
Name	B2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B3

Attribute	Description
Name	B3
Datatype	String
Description	Indicates User Defined Field

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

B4

Attribute	Description
Name	B4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B5

Attribute	Description
Name	B5
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B6

Attribute	Description
Name	B6
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Chklst1

Attribute	Description
Name	Chklst1
Datatype	
Description	Indicates Checklist Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHKLSTID

Attribute	Description
Name	CHKLSTID
Datatype	String
Description	Indicates Checklist Id
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKLSTDESC

Attribute	Description
Name	CHKLSTDESC
Datatype	String
Description	Indicates Checklist Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

VERIFY

Attribute	Description
Name	VERIFY
Datatype	String
Description	Indicates Verified By
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Custudf

Attribute	Description
Name	Custudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tradein

Attribute	Description
Name	Tradein
Datatype	
Description	Indicates Trade In Asset Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ASSETTYP

Attribute	Description
Name	ASSETTYP
Datatype	String
Description	Indicates Asset Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / V,H,O

TOP

ASSETSUBTYP

Attribute	Description
Name	ASSETSUBTYP
Datatype	String
Description	Indicates Asset Sub Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKE

Attribute	Description
Name	MAKE
Datatype	Number
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODEL

Attribute	Description
Name	MODEL
Datatype	String
Description	Indicates Model Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MANYR

Attribute	Description
Name	MANYR
Datatype	Number
Description	Indicates Manufacture Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BODY

Attribute	Description
Name	BODY
Datatype	String
Description	Indicates Vehicle Body Type

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ASSETIDNO

Attribute	Description
Name	ASSETIDNO
Datatype	String
Description	Indicates Asset Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ASSETDESC

Attribute	Description
Name	ASSETDESC
Datatype	String
Description	Indicates Asset Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ASSETWHVL

Attribute	Description
Name	ASSETWHVL
Datatype	Number
Description	Indicates Wholesale Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ASSETBSVL

Attribute	Description
Name	ASSETBSVL
Datatype	Number
Description	Indicates Asset Base Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYAMT

Attribute	Description
Name	PAYAMT
Datatype	Number
Description	Indicates Asset Payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETADDON1

Attribute	Description
Name	ASSETADDON1
Datatype	Number
Description	Indicates Asset Add-on Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TOTVAL

Attribute	Description
Name	TOTVAL
Datatype	Number
Description	Indicates Asset Total Value
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETVLDT

Attribute	Description
Name	ASSETVLDT
Datatype	Date
Description	Indicates Asset Value Date
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETSOURCE

Attribute	Description
Name	ASSETSOURCE
Datatype	String
Description	Indicates Asset Source
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

ASSETSUPP

Attribute	Description
Name	ASSETSUPP
Datatype	String
Description	Indicates Asset Supplier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETEDI

Attribute	Description
Name	ASSETEDI
Datatype	String
Description	Indicates Asset Edition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanoffers

Attribute	Description
Name	Loanoffers
Datatype	
Description	Indicates Loan Offer Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OFFID

Attribute	Description
Name	OFFID

Datatype	String
Description	Indicates Offer Id
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFINST

Attribute	**Description**
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREQUNIT

Attribute	**Description**
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	A,M,B,W

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Interest Rate Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SPREAD

Attribute	Description	
Name	SPREAD	
Datatype	String	
Description	Indicates Interest Spread	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

EFFRATE

Attribute	Description	
Name	EFFRATE	
Datatype	String	
Description	Indicates Effective Interest Rate	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECK

Attribute	Description	
Name	CHECK	
Datatype	String	
Description	Indicates whether Offer Needs to be Applied	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Loan2

Attribute	Description
Name	Loan2
Datatype	
Description	Indicates Loan Main Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANCCY

Attribute	Description
Name	LOANCCY
Datatype	String
Description	Indicates Loan Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	Indicates Loan Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAX

Attribute	Description
Name	TAX
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFINST

Attribute	Description
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates Income Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M,B,W

TOP

SPREAD

Attribute	Description	
Name	SPREAD	
Datatype	String	
Description	Indicates Interest Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EFFRATE

Attribute	Description	
Name	EFFRATE	
Datatype	String	
Description	Indicates Effective Interest Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLACCNO

Attribute	Description	
Name	CLACCNO	
Datatype	String	
Description	Indicates Loan Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

INSSTDT

Attribute	Description
Name	INSSTDT
Datatype	Date
Description	Indicates Installment Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loan3

Attribute	Description
Name	Loan3
Datatype	
Description	Indicates Loan Component Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NO1

Attribute	Description
Name	NO1
Datatype	Number
Description	Indicates Schedule No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Frequency Unit

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHTYP

Attribute	Description
Name	SCHTYP
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / P,D,R

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loan4

Attribute	Description
Name	Loan4
Datatype	
Description	Indicates Loan Schedule Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCHNO

Attribute	Description
Name	SCHNO
Datatype	Number
Description	Indicates Schedule Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EMI_AMOUNT

Attribute	Description
Name	EMI_AMOUNT
Datatype	Number
Description	Indicate EMI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMORPRI

Attribute	Description
Name	AMORPRI
Datatype	Number
Description	Indicates Amortized Principal Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTEREST_AMOUNT

Attribute	Description
Name	INTEREST_AMOUNT
Datatype	Number
Description	Indicates Interest Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPI

Attribute	Description
Name	CAPI
Datatype	String
Description	Indicates Capitalized Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WAIVE

Attribute	Description
Name	WAIVE
Datatype	String
Description	Indicates whether Amount is Waived
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Crdratout

Attribute	Description
Name	Crdratout
Datatype	
Description	Indicates External Credit Rating Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTAGEN

Attribute	Description
Name	EXTAGEN
Datatype	String
Description	Indicates External Credit Rating Agency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RECOMM

Attribute	Description
Name	RECOMM
Datatype	String
Description	Indicates External Credit Rating Agency Final Recommendation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

Crdratin

Attribute	Description
Name	Crdratin
Datatype	
Description	Indicates Internal Credit Rating Details of Loan Application
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description

Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

GRD

Attribute	**Description**
Name	GRD
Datatype	String
Description	Indicates Final Internal Credit Rating Grade
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SCR

Attribute	**Description**
Name	SCR
Datatype	Number
Description	Indicates Internal Credit Rating Score
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	Indicates Internal Credit Rating Rule Id used
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Crratin2

Attribute	Description
Name	Crratin2
Datatype	
Description	Indicates Internal Credit Rating Details by Customer
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 35

TOP

QUES

Attribute	Description
Name	QUES
Datatype	String
Description	Indicates Credit Rating Question
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 105

TOP

ANS

Attribute	Description
Name	ANS
Datatype	String
Description	Indicates Answer to Credit Rating Question
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

CAT

Attribute	Description
Name	CAT
Datatype	String
Description	Indicates Credit Rating Question Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Bureau

Attribute	Description
Name	Bureau
Datatype	
Description	Indicates Credit Bureau Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Number for which Credit Bureau Information is obtained
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUREAU

Attribute	Description
Name	BUREAU

Datatype	String
Description	Indicates Credit Bureau
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RPTTYP

Attribute	**Description**
Name	RPTTYP
Datatype	String
Description	Indicates Bureau Report Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / NEWAPP,VFYAPP,UNDERW,UNAPPR,CHKDOC,FIVERI,FUNDED

TOP

Chgs

Attribute	**Description**
Name	Chgs
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	**Description**
Name	EVENTCD
Datatype	String
Description	Indicates Charge Collection Event
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTSETT

Attribute	Description
Name	AMTSETT
Datatype	Number
Description	Indicates Charge Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDUEDT

Attribute	Description
Name	SCHDUEDT
Datatype	Date
Description	Indicates Charge Due Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

WAIV

Attribute	Description
Name	WAIV
Datatype	String
Description	Indicates whether Charge is Waived

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNM

Attribute	**Description**	
Name	COMPNM	
Datatype	String	
Description	Indicates Component Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Loandedupe

Attribute	**Description**	
Name	Loandedupe	
Datatype		
Description	Indicates Other Loan Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	Indicates Loan Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	Indicates Outstanding Loan Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Riskfactor

Attribute	Description
Name	Riskfactor
Datatype	
Description	Indicates Risk Factor Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

RISKFACT

Attribute	Description
Name	RISKFACT
Datatype	String
Description	Indicates Risk Factor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Chgs1

Attribute	Description

ORACLE

Name	Chgs1
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Promotions

Attribute	**Description**
Name	Promotions
Datatype	
Description	Indicates Promotions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

2.31.2.OR-CreateSaveRLAppEntry-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Applicationhead-IO*
    - *APPNO*
    - *DATE*
    - *PRDCD*
    - *CHNL*
    - *INTERCD*
    - *INTNAME*
    - *CUSTTYPE1*
    - *CCY*
    - *LEAD*
    - *CONT*
    - *PUR*
    - *USERREFNO*
    - *APPCAT*
    - *OFFAPPLNUM*
    - *Customer1*
      - *CUSTNO*
      - *SALUT*
      - *FSTNM*

MIDNM
LSTNM
NATID
DOB
MOTHERNM
LANG
DEPEND
EMAIL
MARSTAT
EXISTING
PASSNO
PASSISSDT
PASSEXPDT
MOBNO
LANDNO
OFFNO
FAX
CUSTTYPE
FINCCY
ACCLS
ACCNUM
GENDER
SNAME
CNTY
NLTY
CUST_CATEG
Customer2
- *APPNO*
- *CUSTNO*
- *ADDTYPE*
- *MAILING*
- *CONNO*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ZIP*
- *CNTY*

Customer3
- *APPNO*
- *CUSTNO*
- *EMPTYPE*
- *EMP*
- *CUSTOCC*
- *DESIG*

ADDLN1
ADDLN2
ADDLN3
ZIP
CNTY
PHONE
EXTN
CONTACT
CONPHN
CONPHNEXTN
COMMENT
DEPT
EMPID
EMPYR
EMPMNTH
INCCCY
INCAMT
FREQ
CONTACT_NAME

Financials1

ASSETTYP
ASSETSUB
MAKE
MODEL
MANYR
BODY
HOUSENO
ASSETVL
ADDLN1
ADDLN2
OCCUPANCY
REGNO

Financials2

APPNO
CUSTNO
LIABTYP
LIABSUB
LIABFREQ
LAIBAMT
BAL
REM
LIABSTDT
LIABENDDT

Finsummary

MONACTINC
MONACTDEBT
GRADE
WHTPMT
Finsummary2
Investi1
CUSTNO
VERTYPE
AGENCY
Custdedupe
CTYPE
FSTNM
LSTNM
SNAME
NATID
CNT
NAT
CCAT
DOB
LANG
EMAIL
EXISTING
PASSNO
MOBNO
LANDNO
Financials3
INCTYPE
CCY
AMT
FREQ
Cusudf
NAME
VALUE
Cust-Acct
CUSTNO
ACCLS
ACCCY
ACMASK
CCYTYPE
ACODE
UDFDETAILS
FLDNAM
FLDVAL
Collat1

APPNO
CUSTNO
COLLCD
COLLDESC
COLLCCY
COLLVL
COLLSTDT
COLLENDDT
COLLCAT
COLLHAIR
COLLTYPE
COLLREVDT
COLLCHGDT
COLLREVLDT
COLLREVCHK
SECUID
NOMUNITVL
CAPAMT
GUAID
RATIN
Collat2
DUEDT
STMON
REM
COVNM
DESC
REVDT
MANDT
GRCDAY
NOTDAY
FREQ
Veh-Details
VEH_IDNUM
VEH_YEAR
VEH_MAKE
VEH_MODEL
VEH_BDYSTYLE
VEH_USAGE
Requested1
APPNO
PRDCD
REQAMT
TENORM
INTEREST_RATE_TYPE

- *DPMNTAMT*
- *CCY*
- *Requested2*
  - *APPNO*
  - *CUSTNO*
  - *ITEMIZATION*
  - *REQAMT*

Comments

- *APPNO*
- *PRDCD*
- *SEQUENCENUMBER*
- *COMMENT*
- *COMMBY*
- *COMMDT*

Udf

- *B1*
- *B2*
- *B3*
- *B4*
- *B5*
- *B6*

Chklst1

- *CHKLSTID*
- *CHKLSTDESC*
- *VERIFY*

Custudf

- *NAME*

Tradein

- *ASSETTYP*
- *ASSETWHVL*
- *ASSETBSVL*
- *PAYAMT*
- *ASSETADDON1*
- *TOTVAL*
- *CURR*

Loanoffers

- *OFFID*
- *RATE*
- *NOOFINST*
- *FREQUNIT*
- *FREQ*
- *RATECD*
- *SPREAD*
- *EFFRATE*

- *CHECK*

Loan2

- *LOANCCY*
- *LOANAMT*
- *RATE*
- *DPMNTAMT*
- *VALDT*
- *MATDT*
- *NOOFINST*
- *FREQUNIT*
- *FREQ*
- *SPREAD*
- *EFFRATE*
- *CLACCNO*
- *INSSTDT*

Loan3

- *NO1*
- *FREQ*
- *UNIT*
- *FRSTDUEDT*
- *AMT*
- *SCHTYP*
- *COMPNM*

Loan4

- *SCHNO*
- *DUEDT*
- *AMTDUE*
- *EMI_AMOUNT*
- *AMORPRI*
- *INTEREST_AMOUNT*
- *CAPI*
- *WAIVE*
- *COMPNM*

Crdratout

- *EXTAGEN*
- *RECOMM*

Crdratin

- *CUSTNO*
- *APPNO*
- *RULEID*
- *Crratin2*
  - *APPNO*
  - *CUSTNO*
  - *QUES*

ANS

CAT

Bureau

CUSTID

BUREAU

RPTTYP

STAT

Chgs

EVENTCD

CHGCCY

AMT

AMTSETT

SCHDUEDT

WAIV

COMPNM

Loandedupe

CCY

VALDT

MATDT

CUSTNO

LOAN_ACCNO

AMT

OUTSTAMT

RATE

Riskfactor

RISKFACT

DESC

Chgs1

Promotions

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Applicationhead-IO

Attribute	Description
Name	Applicationhead-IO
Datatype	
Description	

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DATE

Attribute	Description
Name	DATE

Datatype	Date
Description	Indicates Incorporation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHNL

Attribute	**Description**
Name	CHNL
Datatype	String
Description	Indicates Originating Channel of Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INTERCD

Attribute	**Description**
Name	INTERCD
Datatype	String
Description	Indicates Intermediary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTNAME

Attribute	**Description**
Name	INTNAME
Datatype	String
Description	Indicates Intermediary Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTTYPE1

Attribute	Description
Name	CUSTTYPE1
Datatype	String
Description	Indicates Customer Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LEAD

Attribute	Description
Name	LEAD
Datatype	String
Description	Indicates Lead Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CONT

Attribute	Description
Name	CONT
Datatype	String
Description	Indicates Contact Person
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PUR

Attribute	Description
Name	PUR
Datatype	String
Description	Indicates Loan Purpose
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

APPCAT

Attribute	Description
Name	APPCAT
Datatype	String
Description	Indicates Application Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OFFAPPLNUM

Attribute	Description
Name	OFFAPPLNUM
Datatype	String
Description	Indicates Offline Application Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Customer1

Attribute	Description
Name	Customer1
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SALUT

Attribute	Description
Name	SALUT
Datatype	String
Description	Indicates Salutation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Mr,Mrs,Miss,Dr

TOP

FSTNM

Attribute	Description
Name	FSTNM
Datatype	String
Description	Indicates First Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MIDNM

Attribute	Description
Name	MIDNM
Datatype	String

Description	Indicates Middle Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LSTNM

Attribute	**Description**
Name	LSTNM
Datatype	String
Description	Indicates Last Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NATID

Attribute	**Description**
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DOB

Attribute	**Description**
Name	DOB
Datatype	Date
Description	Indicates Date of Birth
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MOTHERNM

Attribute	**Description**
Name	MOTHERNM
Datatype	String
Description	Indicates Mothers Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEPEND

Attribute	Description
Name	DEPEND
Datatype	Number
Description	Indicates No of Dependencies
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	Indicates Customer Email
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

MARSTAT

Attribute	Description
Name	MARSTAT
Datatype	String
Description	Indicates Marital Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,U,D

TOP

EXISTING

Attribute	Description
Name	EXISTING

Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PASSNO

Attribute	Description
Name	PASSNO
Datatype	String
Description	Indicates Passport Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PASSISSDT

Attribute	Description
Name	PASSISSDT
Datatype	Date
Description	Indicates Passport Issue Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PASSEXPDT

Attribute	Description
Name	PASSEXPDT
Datatype	Date
Description	Indicates Passport Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Landline Number
Attributes	Attribute: minOccurs, Description: 0

TOP

OFFNO

Attribute	Description
Name	OFFNO
Datatype	Number
Description	Indicates Office Number
Attributes	Attribute: minOccurs, Description: 0

TOP

FAX

Attribute	Description
Name	FAX
Datatype	Number
Description	Indicates Customer Fax
Attributes	Attribute: minOccurs, Description: 0

TOP

CUSTTYPE

Attribute	Description
Name	CUSTTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: P,C

TOP

FINCCY

Attribute	Description
Name	FINCCY
Datatype	String
Description	Indicates Financial Details Currency
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Settlement Account Class
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ACCNUM

Attribute	Description
Name	ACCNUM
Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

GENDER

Attribute	Description
Name	GENDER
Datatype	String
Description	Indicates Customer Gender
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CUST_CATEG

Attribute	Description
Name	CUST_CATEG
Datatype	String
Description	Indicates Customer Category
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Customer2

Attribute	Description
Name	Customer2
Datatype	
Description	Indicates Customer Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String

Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDTYPE

Attribute	**Description**
Name	ADDTYPE
Datatype	String
Description	Indicates Address Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H,W,T,O

TOP

MAILING

Attribute	**Description**
Name	MAILING
Datatype	String
Description	Indicates whether Mailing Address
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONNO

Attribute	**Description**
Name	CONNO
Datatype	Number
Description	Indicates Contact Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY

Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customer3

Attribute	**Description**
Name	Customer3
Datatype	
Description	Indicates Director Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EMPTYPE

Attribute	**Description**
Name	EMPTYPE
Datatype	String
Description	Indicates Employment Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	PART,FULL,CONT

TOP

EMP

Attribute	Description
Name	EMP
Datatype	String
Description	Indicates Employer
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTOCC

Attribute	Description
Name	CUSTOCC
Datatype	String
Description	Indicates Customer Occupation
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

DESIG

Attribute	Description
Name	DESIG
Datatype	String
Description	Indicates Designation
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PHONE

Attribute	Description
Name	PHONE

Datatype	Number
Description	Indicates Phone Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXTN

Attribute	**Description**
Name	EXTN
Datatype	Number
Description	Indicates Customer Extension
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTACT

Attribute	**Description**
Name	CONTACT
Datatype	Number
Description	Indicates Customer Contact
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONPHN

Attribute	**Description**
Name	CONPHN
Datatype	Number
Description	Indicates Contact Phone Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONPHNEXTN

Attribute	**Description**
Name	CONPHNEXTN
Datatype	Number
Description	Indicates Contact Phone Extension
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMMENT

Attribute	**Description**
Name	COMMENT
Datatype	String
Description	Indicates Comments

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DEPT

Attribute	**Description**
Name	DEPT
Datatype	String
Description	Indicates Customer Department
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EMPID

Attribute	**Description**
Name	EMPID
Datatype	String
Description	Indicates Employee Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EMPYR

Attribute	**Description**
Name	EMPYR
Datatype	Number
Description	Indicates Employed Year
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EMPMNTH

Attribute	**Description**
Name	EMPMNTH
Datatype	Number
Description	Indicates Employed Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INCCCY

Attribute	Description
Name	INCCCY
Datatype	String
Description	Indicates Income Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INCAMT

Attribute	Description
Name	INCAMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,B,W

TOP

CONTACT_NAME

Attribute	Description
Name	CONTACT_NAME
Datatype	String
Description	Indicates Customer Contact Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Financials1

Attribute	Description
Name	Financials1
Datatype	
Description	Indicates Customer Financial Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ASSETTYP

Attribute	Description	
Name	ASSETTYP	
Datatype	String	
Description	Indicates Asset Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	V,H,O

TOP

ASSETSUB

Attribute	Description	
Name	ASSETSUB	
Datatype	String	
Description	Indicates Asset Sub Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKE

Attribute	Description	
Name	MAKE	
Datatype	Number	
Description	Indicates Vehicle Make	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MODEL

Attribute	Description	
Name	MODEL	
Datatype	String	
Description	Indicates Model Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MANYR

Attribute	Description
Name	MANYR
Datatype	Number
Description	Indicates Manufacture Year
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BODY

Attribute	Description
Name	BODY
Datatype	String
Description	Indicates Vehicle Body Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOUSENO

Attribute	Description
Name	HOUSENO
Datatype	String
Description	Indicates House Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETVL

Attribute	Description
Name	ASSETVL
Datatype	Number
Description	Indicates Asset Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN2

Attribute	**Description**
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OCCUPANCY

Attribute	**Description**
Name	OCCUPANCY
Datatype	Number
Description	Indicates Occupancy
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REGNO

Attribute	**Description**
Name	REGNO
Datatype	Number
Description	Indicates Registration Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Financials2

Attribute	**Description**
Name	Financials2
Datatype	
Description	Indicates Customer Liability Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**

Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABTYP

Attribute	**Description**
Name	LIABTYP
Datatype	String
Description	Indicates Liability Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LO,LE,RE,OT

TOP

LIABSUB

Attribute	**Description**
Name	LIABSUB
Datatype	String
Description	Indicates Liability Sub Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABFREQ

Attribute	**Description**
Name	LIABFREQ
Datatype	String
Description	Indicates Liability Frequency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y

TOP

LAIBAMT

Attribute	Description	
Name	LAIBAMT	
Datatype	Number	
Description	Indicates Liability Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BAL

Attribute	Description	
Name	BAL	
Datatype	Number	
Description	Indicates Liability Outstanding Balance	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LIABSTDT

Attribute	Description	
Name	LIABSTDT	
Datatype	Date	
Description	Indicates Liability Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIABENDDT

Attribute	Description
Name	LIABENDDT

Datatype	Date
Description	Indicates Liability End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Finsummary

Attribute	**Description**
Name	Finsummary
Datatype	
Description	Indicates Asset Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTINC

Attribute	**Description**
Name	MONACTINC
Datatype	Number
Description	Indicates Monthly Actual Income
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTDEBT

Attribute	**Description**
Name	MONACTDEBT
Datatype	Number
Description	Indicates Monthly Actual Debt
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRADE

Attribute	**Description**
Name	GRADE
Datatype	String
Description	Indicates Internal Final Grade
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

WHTPMT

Attribute	**Description**
Name	WHTPMT

Datatype	Number
Description	Indicates What if Payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Finsummary2

Attribute	Description
Name	Finsummary2
Datatype	
Description	Indicates Consolidated Financial Summary Information
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Investi1

Attribute	Description
Name	Investi1
Datatype	
Description	Indicates Investigation Summary
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERTYPE

Attribute	Description
Name	VERTYPE
Datatype	String
Description	Indicates Verification Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGENCY

Attribute	Description
Name	AGENCY
Datatype	String
Description	Indicates Investigating Agency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custdedupe

Attribute	Description
Name	Custdedupe
Datatype	
Description	Indicates Possible Duplicate Customer Names
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FSTNM

Attribute	Description
Name	FSTNM
Datatype	String
Description	Indicates First Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LSTNM

Attribute	Description

Name	LSTNM
Datatype	String
Description	Indicates Last Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNAME

Attribute	**Description**
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NATID

Attribute	**Description**
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CNT

Attribute	**Description**
Name	CNT
Datatype	String
Description	Indicates Counter Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

NAT

Attribute	**Description**
Name	NAT
Datatype	String
Description	Indicates Nationality

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CCAT

Attribute	Description	
Name	CCAT	
Datatype	String	
Description	Indicates Customer Category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DOB

Attribute	Description	
Name	DOB	
Datatype	Date	
Description	Indicates Date of Birth	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description	Indicates Customer Language	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description	Indicates Customer Email	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

EXISTING

Attribute	Description
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASSNO

Attribute	Description
Name	PASSNO
Datatype	String
Description	Indicates Passport Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Landline Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Financials3

Attribute	Description
Name	Financials3
Datatype	
Description	Indicates Customer Income Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

INCTYPE

Attribute	Description	
Name	INCTYPE	
Datatype	String	
Description	Indicates Income Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S,R,B,O

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates Currency Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Income Amount	
Attributes	Attribute	Description
	minOccurs	0

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates Income Frequency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,M,B,W

TOP

Cusudf

Attribute	Description
Name	Cusudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

Cust-Acct

Attribute	Description
Name	Cust-Acct
Datatype	
Description	Indicates Customer Account Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Settlement Account Class
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates Customer Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACMASK

Attribute	Description
Name	ACMASK
Datatype	String
Description	Indicates Customer Account Mask
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CCYTYPE

Attribute	Description
Name	CCYTYPE
Datatype	String
Description	Indicates Currency Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACODE

Attribute	Description
Name	ACODE

Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Collat1

Attribute	**Description**
Name	Collat1
Datatype	
Description	Indicates Collateral Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLCD

Attribute	Description
Name	COLLCD
Datatype	String
Description	Indicates Collateral Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	Indicates Collateral Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	Indicates Collateral Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLSTDT

Attribute	Description
Name	COLLSTDT
Datatype	Date
Description	Indicates Collateral Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLENDDT

Attribute	Description
Name	COLLENDDT
Datatype	Date
Description	Indicates Collateral End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	Indicates Collateral Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	Indicates Collateral Haircut Margin
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,M,G

TOP

COLLREVDT

Attribute	Description
Name	COLLREVDT
Datatype	Date
Description	Indicates Collateral Revision Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCHGDT

Attribute	Description
Name	COLLCHGDT
Datatype	String
Description	Indicates Collateral
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,L,P,H,A

TOP

COLLREVLDT

Attribute	Description
Name	COLLREVLDT
Datatype	Date
Description	Indicates Collateral Revaluation Date

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLREVCHK

Attribute	Description
Name	COLLREVCHK
Datatype	String
Description	Indicates whether Collateral Revaluation is Required
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

NOMUNITVL

Attribute	Description
Name	NOMUNITVL
Datatype	Number
Description	Indicates Nominal Unit Value
Attributes	Attribute: minOccurs; Description: 0

TOP

CAPAMT

Attribute	Description
Name	CAPAMT
Datatype	Number
Description	Indicates Collateral Cap Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

GUAID

Attribute	Description
Name	GUAID

Datatype	String
Description	Indicates Guarantor Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RATIN

Attribute	Description
Name	RATIN
Datatype	String
Description	Indicates Rating
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Collat2

Attribute	Description
Name	Collat2
Datatype	
Description	Indicates Collateral Covenant Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STMON

Attribute	Description
Name	STMON
Datatype	String
Description	Indicates Start Month
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVNM

Attribute	Description
Name	COVNM
Datatype	String
Description	Indicates Covenant Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	Indicates Revision Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MANDT

Attribute	Description
Name	MANDT

Datatype	Date
Description	Indicates whether Covenant is Mandatory
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAY

Attribute	Description
Name	GRCDAY
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

Veh-Details

Attribute	Description
Name	Veh-Details
Datatype	
Description	Indicates Vehicle Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VEH_IDNUM

Attribute	Description
Name	VEH_IDNUM

Datatype	String
Description	Indicates Vehicle Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_YEAR

Attribute	Description
Name	VEH_YEAR
Datatype	Number
Description	Indicates Vehicle Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_MAKE

Attribute	Description
Name	VEH_MAKE
Datatype	String
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_MODEL

Attribute	Description
Name	VEH_MODEL
Datatype	String
Description	Indicates Vehicle Model
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_BDYSTYLE

Attribute	Description
Name	VEH_BDYSTYLE
Datatype	String
Description	Indicates Vehicle Body Style
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VEH_USAGE

Attribute	Description
Name	VEH_USAGE
Datatype	String
Description	Indicates Vehicle Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Requested1

Attribute	Description
Name	Requested1
Datatype	
Description	Indicates Overall Loan Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

REQAMT

Attribute	Description
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TENORM

Attribute	Description
Name	TENORM
Datatype	Number
Description	Indicates Loan Tenor
Attributes	Attribute: minOccurs, Description: 0

TOP

INTEREST_RATE_TYPE

Attribute	Description
Name	INTEREST_RATE_TYPE
Datatype	Number
Description	Indicates Interest Rate Type
Attributes	Attribute: minOccurs, Description: 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

Requested2

Attribute	Description
Name	Requested2
Datatype	
Description	Indicates Individual Request Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITEMIZATION

Attribute	Description
Name	ITEMIZATION
Datatype	String
Description	Indicates Itemization Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REQAMT

Attribute	Description
Name	REQAMT

Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Comments

Attribute	**Description**
Name	Comments
Datatype	
Description	Indicates Comment Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SEQUENCENUMBER

Attribute	**Description**
Name	SEQUENCENUMBER
Datatype	String
Description	Indicates Comment Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMBY

Attribute	Description
Name	COMMBY
Datatype	String
Description	Indicates User who input Comment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMDT

Attribute	Description
Name	COMMDT
Datatype	Date
Description	Indicates Comment Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Udf

Attribute	Description
Name	Udf
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

B1

Attribute	Description
Name	B1
Datatype	String
Description	Indicates User Defined Field

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B2

Attribute	**Description**
Name	B2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B3

Attribute	**Description**
Name	B3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B4

Attribute	**Description**
Name	B4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B5

Attribute	**Description**
Name	B5
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B6

Attribute	**Description**
Name	B6
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Chklst1

Attribute	**Description**
Name	Chklst1
Datatype	
Description	Indicates Checklist Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHKLSTID

Attribute	**Description**
Name	CHKLSTID
Datatype	String
Description	Indicates Checklist Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKLSTDESC

Attribute	**Description**
Name	CHKLSTDESC
Datatype	String
Description	Indicates Checklist Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

VERIFY

Attribute	Description
Name	VERIFY
Datatype	String
Description	Indicates Verified By
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Custudf

Attribute	Description
Name	Custudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

Tradein

Attribute	Description
Name	Tradein
Datatype	
Description	Indicates Trade In Asset Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ASSETTYP

Attribute	Description
Name	ASSETTYP
Datatype	String
Description	Indicates Asset Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / V,H,O

TOP

ASSETWHVL

Attribute	Description
Name	ASSETWHVL
Datatype	Number
Description	Indicates Wholesale Value
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETBSVL

Attribute	Description
Name	ASSETBSVL
Datatype	Number
Description	Indicates Asset Base Value
Attributes	Attribute: minOccurs, Description: 0

TOP

PAYAMT

Attribute	Description
Name	PAYAMT
Datatype	Number
Description	Indicates Asset Payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETADDON1

Attribute	Description
Name	ASSETADDON1
Datatype	Number
Description	Indicates Asset Add-on Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TOTVAL

Attribute	Description
Name	TOTVAL
Datatype	Number
Description	Indicates Asset Total Value
Attributes	Attribute: minOccurs, Description: 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

Loanoffers

Attribute	Description
Name	Loanoffers
Datatype	
Description	Indicates Loan Offer Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

OFFID

Attribute	Description
Name	OFFID
Datatype	String
Description	Indicates Offer Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFINST

Attribute	Description
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREQUNIT

Attribute	**Description**	
Name	FREQUNIT	
Datatype	String	
Description	Indicates Schedule Frequency Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Q,H,Y

TOP

FREQ

Attribute	**Description**	
Name	FREQ	
Datatype	String	
Description	Indicates Income Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M,B,W

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Interest Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SPREAD

Attribute	**Description**	
Name	SPREAD	
Datatype	String	
Description	Indicates Interest Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECK

Attribute	Description
Name	CHECK
Datatype	String
Description	Indicates whether Offer Needs to be Applied
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Loan2

Attribute	Description
Name	Loan2
Datatype	
Description	Indicates Loan Main Details
Attributes	Attribute: minOccurs — Description: 0

TOP

LOANCCY

Attribute	Description
Name	LOANCCY
Datatype	String
Description	Indicates Loan Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	Indicates Loan Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs, Description: 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	Attribute: minOccurs, Description: 0

TOP

NOOFINST

Attribute	Description

Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREQUNIT

Attribute	**Description**
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,B,W

TOP

SPREAD

Attribute	**Description**
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EFFRATE

Attribute	**Description**
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	Indicates Loan Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

INSSTDT

Attribute	Description
Name	INSSTDT
Datatype	Date
Description	Indicates Installment Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Loan3

Attribute	Description
Name	Loan3
Datatype	
Description	Indicates Loan Component Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NO1

Attribute	Description
Name	NO1
Datatype	Number
Description	Indicates Schedule No
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	Description

Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,B,W

TOP

UNIT

Attribute	**Description**
Name	UNIT
Datatype	String
Description	Indicates Frequency Unit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FRSTDUEDT

Attribute	**Description**
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHTYP

Attribute	**Description**
Name	SCHTYP
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,D,R

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loan4

Attribute	Description
Name	Loan4
Datatype	
Description	Indicates Loan Schedule Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SCHNO

Attribute	Description
Name	SCHNO
Datatype	Number
Description	Indicates Schedule Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due

Attributes	Attribute	Description
	minOccurs	0

TOP

EMI_AMOUNT

Attribute	Description
Name	EMI_AMOUNT
Datatype	Number
Description	Indicate EMI Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

AMORPRI

Attribute	Description
Name	AMORPRI
Datatype	Number
Description	Indicates Amortized Principal Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

INTEREST_AMOUNT

Attribute	Description
Name	INTEREST_AMOUNT
Datatype	Number
Description	Indicates Interest Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CAPI

Attribute	Description
Name	CAPI
Datatype	String
Description	Indicates Capitalized Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

WAIVE

Attribute	Description
Name	WAIVE
Datatype	String
Description	Indicates whether Amount is Waived

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Crdratout

Attribute	Description
Name	Crdratout
Datatype	
Description	Indicates External Credit Rating Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EXTAGEN

Attribute	Description
Name	EXTAGEN
Datatype	String
Description	Indicates External Credit Rating Agency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RECOMM

Attribute	Description
Name	RECOMM
Datatype	String
Description	Indicates External Credit Rating Agency Final Recommendation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

Crdratin

Attribute	Description
Name	Crdratin
Datatype	
Description	Indicates Internal Credit Rating Details of Loan Application
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	Indicates Internal Credit Rating Rule Id used
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Crratin2

Attribute	Description
Name	Crratin2

Datatype	
Description	Indicates Internal Credit Rating Details by Customer
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QUES

Attribute	**Description**
Name	QUES
Datatype	String
Description	Indicates Credit Rating Question
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ANS

Attribute	**Description**
Name	ANS
Datatype	String
Description	Indicates Answer to Credit Rating Question
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

CAT

Attribute	**Description**
Name	CAT
Datatype	String
Description	Indicates Credit Rating Question Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Bureau

Attribute	**Description**
Name	Bureau
Datatype	
Description	Indicates Credit Bureau Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTID

Attribute	**Description**
Name	CUSTID
Datatype	String
Description	Indicates Customer Number for which Credit Bureau Information is obtained
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUREAU

Attribute	**Description**
Name	BUREAU
Datatype	String
Description	Indicates Credit Bureau
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RPTTYP

Attribute	Description
Name	RPTTYP
Datatype	String
Description	Indicates Bureau Report Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Bureau Information Retrieval Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

Chgs

Attribute	Description
Name	Chgs
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Charge Collection Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCCY

Attribute	Description
Name	CHGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTSETT

Attribute	Description
Name	AMTSETT
Datatype	Number
Description	Indicates Charge Amount Settled
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHDUEDT

Attribute	Description
Name	SCHDUEDT
Datatype	Date
Description	Indicates Charge Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIV

Attribute	Description
Name	WAIV
Datatype	String
Description	Indicates whether Charge is Waived
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Loandedupe

Attribute	Description
Name	Loandedupe
Datatype	
Description	Indicates Other Loan Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	Indicates Loan Account Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	Indicates Outstanding Loan Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

RATE

Attribute	Description
Name	RATE

Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Riskfactor

Attribute	Description
Name	Riskfactor
Datatype	
Description	Indicates Risk Factor Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RISKFACT

Attribute	Description
Name	RISKFACT
Datatype	String
Description	Indicates Risk Factor
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Chgs1

Attribute	Description
Name	Chgs1
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Promotions

Attribute	Description
Name	Promotions
Datatype	
Description	Indicates Promotions details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.31.3.OR-CreateSaveRLAppEntry-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Applicationhead-Full*
    - *APPNO*
    - *DATE*
    - *PRDCD*
    - *CHNL*
    - *BRN*
    - *STAT*
    - *INTERCD*
    - *INTNAME*
    - *CUSTTYPE1*
    - *CCY*
    - *LEAD*
    - *CONT*
    - *PUR*
    - *USERREFNO*
    - *APPCAT*
    - *ENQUIRY_ID*
    - *OFFAPPLNUM*
    - *Customer1*

CUSTNO
SALUT
FSTNM
MIDNM
LSTNM
NATID
DOB
MOTHERNM
LANG
DEPEND
EMAIL
MARSTAT
EXISTING
PASSNO
PASSISSDT
PASSEXPDT
MOBNO
LANDNO
OFFNO
FAX
CUSTTYPE
FINCCY
ACCLS
ACCNUM
GENDER
SNAME
CNTY
NLTY
CUST_CATEG
Customer2
- *APPNO*
- *CUSTNO*
- *ADDTYPE*
- *MAILING*
- *CONNO*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ZIP*
- *CNTY*

Customer3
- *APPNO*
- *CUSTNO*
- *EMPTYPE*

EMP
CUSTOCC
DESIG
ADDLN1
ADDLN2
ADDLN3
ZIP
CNTY
PHONE
EXTN
CONTACT
CONPHN
CONPHNEXTN
COMMENT
DEPT
EMPID
EMPYR
EMPMNTH
INCCCY
INCAMT
FREQ
CONTACT_NAME

Financials1

APPNO
CUSTNO
ASSETTYP
ASSETSUB
MAKE
MODEL
MANYR
BODY
HOUSENO
ASSETDESC
ASSETVL
ADDLN1
ADDLN2
ADDLN3
WIDTH
LENGTH
OCCUPANCY
REGNO

Financials2

LIABTYP
LIABSUB

LIABFREQ
LAIBAMT
BAL
REM
LIABSTDT
LIABENDDT
Finsummary
MONSTATINC
MONACTINC
MONSTATDEBT
MONACTDEBT
GRADE
SCORE
ASSETWORTH
LIABWORTH
TOTWOR
WHTPMT
Finsummary2
RATNM
STATBF
STATAF
ACTBF
ACTAF
Investi1
CUSTNO
VERTYPE
AGENCY
Investi2
SPOKE
ATTEMPTS
CALLDT
RESULT
VERMAT
REM
Custdedupe
CTYPE
FSTNM
LSTNM
SNAME
NATID
CNT
NAT
CCAT
DOB

- *LANG*
- *EMAIL*
- *EXISTING*
- *PASSNO*
- *MOBNO*
- *LANDNO*

Financials3

- *APPNO*
- *CUSTNO*
- *INCTYPE*
- *CCY*
- *AMT*
- *FREQ*

Cusudf

- *NAME*
- *VALUE*

Cust-Acct

- *CUSTNO*
- *ACCLS*
- *ACCCY*
- *ACMASK*
- *CCYTYPE*
- *ACODE*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

Collat1

- *APPNO*
- *CUSTNO*
- *COLLCD*
- *COLLDESC*
- *COLLCCY*
- *COLLVL*
- *COLLSTDT*
- *COLLENDDT*
- *COLLCAT*
- *COLLHAIR*
- *COLLTYPE*
- *COLLREVDT*
- *COLLCHGDT*
- *COLLREVLDT*
- *COLLREVCHK*
- *SECUID*
- *NOMUNITVL*

- *CAPAMT*
- *GUAID*
- *RATIN*
- *Collat2*
  - *DUEDT*
  - *STMON*
  - *REM*
  - *COVNM*
  - *DESC*
  - *REVDT*
  - *MANDT*
  - *GRCDAY*
  - *NOTDAY*
  - *FREQ*
- *Veh-Details*
  - *VEH_IDNUM*
  - *VEH_YEAR*
  - *VEH_MAKE*
  - *VEH_MODEL*
  - *VEH_BDYSTYLE*
  - *VEH_USAGE*

Requested1

- *APPNO*
- *PRDCD*
- *REQAMT*
- *TENORM*
- *INTEREST_RATE_TYPE*
- *DPMNTAMT*
- *PROMO*
- *CCY*
- *Requested2*
  - *ITEMIZATION*
  - *REQAMT*
  - *COMMENT*

Comments

- *APPNO*
- *PRDCD*
- *SEQUENCENUMBER*
- *COMMENT*
- *COMMBY*
- *COMMDT*

Udf

- *L1*
- *L2*

L3
L4
L5
L6
L7
L8
L9
L10
L11
L12
L13
L14
L15
L16
L17
L18
L19
L20
F1
F2
F3
F4
F5
F6
F7
F8
F9
F10
F11
F12
F13
F14
F15
F16
F17
F18
F19
F20
B1
B2
B3
B4
B5
B6

Chklst1

- *CHKLSTID*
- *CHKLSTDESC*
- *VERIFY*
- *COMMENT*

Custudf

- *NAME*
- *DESC*

Tradein

- *ASSETTYP*
- *ASSETSUBTYP*
- *MAKE*
- *MODEL*
- *MANYR*
- *BODY*
- *ASSETIDNO*
- *ASSETDESC*
- *ASSETWHVL*
- *ASSETBSVL*
- *PAYAMT*
- *ASSETADDON1*
- *TOTVAL*
- *ASSETVLDT*
- *ASSETSOURCE*
- *ASSETSUPP*
- *ASSETEDI*
- *CURR*

Loanoffers

- *OFFID*
- *RATE*
- *NOOFINST*
- *FREQUNIT*
- *FREQ*
- *RATECD*
- *SPREAD*
- *EFFRATE*
- *CHECK*

Loan2

- *LOANCCY*
- *LOANAMT*
- *RATE*
- *DPMNTAMT*
- *TAX*
- *VALDT*

MATDT
NOOFINST
FREQUNIT
FREQ
SPREAD
EFFRATE
CLACCNO
INSSTDT
Loan3
NO1
FREQ
UNIT
FRSTDUEDT
AMT
SCHTYP
COMPNM
Loan4
SCHNO
DUEDT
AMTDUE
EMI_AMOUNT
AMORPRI
INTEREST_AMOUNT
CAPI
WAIVE
COMPNM
Crdratout
EXTAGEN
RECOMM
Crdratin
CUSTNO
APPNO
GRD
SCR
RULEID
Crratin2
APPNO
CUSTNO
QUES
ANS
CAT
Bureau
CUSTID
BUREAU

RPTTYP

STAT

Chgs

EVENTCD

CHGCCY

AMT

AMTSETT

SCHDUEDT

WAIV

COMPNM

Loandedupe

CCY

VALDT

MATDT

CUSTNO

LOAN_ACCNO

AMT

OUTSTAMT

RATE

Riskfactor

RISKFACT

DESC

Chgs1

Promotions

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Applicationhead-Full

Attribute	Description
Name	Applicationhead-Full
Datatype	
Description	

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DATE

Attribute	Description
Name	DATE

Datatype	Date
Description	Indicates Incorporation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHNL

Attribute	Description
Name	CHNL
Datatype	String
Description	Indicates Originating Channel of Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / NEWAPP,VFYAPP,UNDERW,UNAPPR,CHKDOC,FIVERI,FUNDED

TOP

INTERCD

Attribute	Description
Name	INTERCD
Datatype	String
Description	Indicates Intermediary Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTNAME

Attribute	Description
Name	INTNAME
Datatype	String
Description	Indicates Intermediary Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTTYPE1

Attribute	Description
Name	CUSTTYPE1
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LEAD

Attribute	Description
Name	LEAD
Datatype	String
Description	Indicates Lead Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONT

Attribute	Description
Name	CONT
Datatype	String
Description	Indicates Contact Person
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PUR

Attribute	Description
Name	PUR
Datatype	String
Description	Indicates Loan Purpose
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

APPCAT

Attribute	Description
Name	APPCAT
Datatype	String
Description	Indicates Application Category
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

ENQUIRY_ID

Attribute	Description
Name	ENQUIRY_ID
Datatype	String
Description	Indicates Enquiry Id
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

OFFAPPLNUM

Attribute	Description
Name	OFFAPPLNUM
Datatype	String
Description	Indicates Offline Application Number
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

Customer1

Attribute	Description
Name	Customer1
Datatype	
Description	Indicates Customer Details
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String

Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SALUT

Attribute	**Description**
Name	SALUT
Datatype	String
Description	Indicates Salutation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Mr,Mrs,Miss,Dr

TOP

FSTNM

Attribute	**Description**
Name	FSTNM
Datatype	String
Description	Indicates First Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MIDNM

Attribute	**Description**
Name	MIDNM
Datatype	String
Description	Indicates Middle Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LSTNM

Attribute	**Description**
Name	LSTNM
Datatype	String
Description	Indicates Last Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NATID

Attribute	Description
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	Indicates Date of Birth
Attributes	Attribute: minOccurs — Description: 0

TOP

MOTHERNM

Attribute	Description
Name	MOTHERNM
Datatype	String
Description	Indicates Mothers Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

DEPEND

Attribute	Description
Name	DEPEND
Datatype	Number
Description	Indicates No of Dependencies
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	Indicates Customer Email
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

MARSTAT

Attribute	Description
Name	MARSTAT
Datatype	String
Description	Indicates Marital Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,U,D

TOP

EXISTING

Attribute	Description
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASSNO

Attribute	Description
Name	PASSNO
Datatype	String
Description	Indicates Passport Number

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PASSISSDT

Attribute	Description
Name	PASSISSDT
Datatype	Date
Description	Indicates Passport Issue Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASSEXPDT

Attribute	Description
Name	PASSEXPDT
Datatype	Date
Description	Indicates Passport Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Landline Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFNO

Attribute	Description
Name	OFFNO
Datatype	Number
Description	Indicates Office Number

Attributes	Attribute	Description
	minOccurs	0

TOP

FAX

Attribute	Description
Name	FAX
Datatype	Number
Description	Indicates Customer Fax
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTTYPE

Attribute	Description
Name	CUSTTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,C

TOP

FINCCY

Attribute	Description
Name	FINCCY
Datatype	String
Description	Indicates Financial Details Currency
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Settlement Account Class
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ACCNUM

Attribute	Description
Name	ACCNUM
Datatype	String
Description	Indicates Account Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 22

TOP

GENDER

Attribute	Description
Name	GENDER
Datatype	String
Description	Indicates Customer Gender
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,F

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

NLTY

Attribute	Description
Name	NLTY

Datatype	String
Description	Indicates Customer Nationality
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CUST_CATEG

Attribute	**Description**
Name	CUST_CATEG
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Customer2

Attribute	**Description**
Name	Customer2
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDTYPE

Attribute	Description
Name	ADDTYPE
Datatype	String
Description	Indicates Address Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / P,H,W,T,O

TOP

MAILING

Attribute	Description
Name	MAILING
Datatype	String
Description	Indicates whether Mailing Address
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONNO

Attribute	Description
Name	CONNO
Datatype	Number
Description	Indicates Contact Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

Customer3

Attribute	Description
Name	Customer3
Datatype	
Description	Indicates Director Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

EMPTYPE

Attribute	Description
Name	EMPTYPE
Datatype	String
Description	Indicates Employment Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: PART,FULL,CONT

TOP

EMP

Attribute	Description
Name	EMP
Datatype	String
Description	Indicates Employer
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTOCC

Attribute	Description
Name	CUSTOCC
Datatype	String
Description	Indicates Customer Occupation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DESIG

Attribute	Description
Name	DESIG
Datatype	String
Description	Indicates Designation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

PHONE

Attribute	Description
Name	PHONE
Datatype	Number
Description	Indicates Phone Number
Attributes	Attribute: minOccurs — Description: 0

TOP

EXTN

Attribute	Description
Name	EXTN
Datatype	Number
Description	Indicates Customer Extension
Attributes	Attribute: minOccurs — Description: 0

TOP

CONTACT

Attribute	Description
Name	CONTACT
Datatype	Number
Description	Indicates Customer Contact
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONPHN

Attribute	Description
Name	CONPHN
Datatype	Number
Description	Indicates Contact Phone Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONPHNEXTN

Attribute	Description
Name	CONPHNEXTN
Datatype	Number
Description	Indicates Contact Phone Extension
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comments
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DEPT

Attribute	Description
Name	DEPT
Datatype	String
Description	Indicates Customer Department
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EMPID

Attribute	Description	
Name	EMPID	
Datatype	String	
Description	Indicates Employee Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

EMPYR

Attribute	Description	
Name	EMPYR	
Datatype	Number	
Description	Indicates Employed Year	
Attributes	Attribute	Description
	minOccurs	0

TOP

EMPMNTH

Attribute	Description	
Name	EMPMNTH	
Datatype	Number	
Description	Indicates Employed Months	
Attributes	Attribute	Description
	minOccurs	0

TOP

INCCCY

Attribute	Description	
Name	INCCCY	
Datatype	String	
Description	Indicates Income Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

INCAMT

Attribute	Description
Name	INCAMT

Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

CONTACT_NAME

Attribute	Description
Name	CONTACT_NAME
Datatype	String
Description	Indicates Customer Contact Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Financials1

Attribute	Description
Name	Financials1
Datatype	
Description	Indicates Customer Financial Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ASSETTYP

Attribute	Description
Name	ASSETTYP
Datatype	String
Description	Indicates Asset Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,H,O

TOP

ASSETSUB

Attribute	Description
Name	ASSETSUB
Datatype	String
Description	Indicates Asset Sub Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKE

Attribute	Description
Name	MAKE
Datatype	Number
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODEL

Attribute	Description
Name	MODEL

Datatype	String
Description	Indicates Model Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MANYR

Attribute	**Description**
Name	MANYR
Datatype	Number
Description	Indicates Manufacture Year
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BODY

Attribute	**Description**
Name	BODY
Datatype	String
Description	Indicates Vehicle Body Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

HOUSENO

Attribute	**Description**
Name	HOUSENO
Datatype	String
Description	Indicates House Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETDESC

Attribute	**Description**
Name	ASSETDESC
Datatype	String
Description	Indicates Asset Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ASSETVL

Attribute	Description	
Name	ASSETVL	
Datatype	Number	
Description	Indicates Asset Value	
Attributes	Attribute	Description
	minOccurs	0

TOP

ADDLN1

Attribute	Description	
Name	ADDLN1	
Datatype	String	
Description	Indicates Address Line 1	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLN2

Attribute	Description	
Name	ADDLN2	
Datatype	String	
Description	Indicates Address Line 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLN3

Attribute	Description	
Name	ADDLN3	
Datatype	String	
Description	Indicates Address Line 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

WIDTH

Attribute	Description
Name	WIDTH
Datatype	Number
Description	Indicates Width
Attributes	Attribute: minOccurs, Description: 0

TOP

LENGTH

Attribute	Description
Name	LENGTH
Datatype	Number
Description	Indicates Length
Attributes	Attribute: minOccurs, Description: 0

TOP

OCCUPANCY

Attribute	Description
Name	OCCUPANCY
Datatype	Number
Description	Indicates Occupancy
Attributes	Attribute: minOccurs, Description: 0

TOP

REGNO

Attribute	Description
Name	REGNO
Datatype	Number
Description	Indicates Registration Number
Attributes	Attribute: minOccurs, Description: 0

TOP

Financials2

Attribute	Description
Name	Financials2
Datatype	
Description	Indicates Customer Liability Details
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

LIABTYP

Attribute	Description
Name	LIABTYP
Datatype	String
Description	Indicates Liability Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / LO,LE,RE,OT

TOP

LIABSUB

Attribute	Description
Name	LIABSUB
Datatype	String
Description	Indicates Liability Sub Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABFREQ

Attribute	Description
Name	LIABFREQ
Datatype	String
Description	Indicates Liability Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y

TOP

LAIBAMT

Attribute	Description
Name	LAIBAMT
Datatype	Number
Description	Indicates Liability Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAL

Attribute	Description
Name	BAL
Datatype	Number
Description	Indicates Liability Outstanding Balance

Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LIABSTDT

Attribute	Description
Name	LIABSTDT
Datatype	Date
Description	Indicates Liability Start Date
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABENDDT

Attribute	Description
Name	LIABENDDT
Datatype	Date
Description	Indicates Liability End Date
Attributes	Attribute: minOccurs — Description: 0

TOP

Finsummary

Attribute	Description
Name	Finsummary
Datatype	
Description	Indicates Asset Details
Attributes	Attribute: minOccurs — Description: 0

TOP

MONSTATINC

Attribute	Description
Name	MONSTATINC
Datatype	Number
Description	Indicates Monthly Stated Income

Attributes	Attribute	Description
	minOccurs	0

TOP

MONACTINC

Attribute	Description
Name	MONACTINC
Datatype	Number
Description	Indicates Monthly Actual Income
Attributes	Attribute: minOccurs — Description: 0

TOP

MONSTATDEBT

Attribute	Description
Name	MONSTATDEBT
Datatype	Number
Description	Indicates Monthly Stated Debt
Attributes	Attribute: minOccurs — Description: 0

TOP

MONACTDEBT

Attribute	Description
Name	MONACTDEBT
Datatype	Number
Description	Indicates Monthly Actual Debt
Attributes	Attribute: minOccurs — Description: 0

TOP

GRADE

Attribute	Description
Name	GRADE
Datatype	String
Description	Indicates Internal Final Grade
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SCORE

Attribute	Description
Name	SCORE
Datatype	Number
Description	Indicates Internal Credit Score

Attributes	Attribute	Description
	minOccurs	0

TOP

ASSETWORTH

Attribute	Description
Name	ASSETWORTH
Datatype	Number
Description	Indicates Asset Value
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABWORTH

Attribute	Description
Name	LIABWORTH
Datatype	Number
Description	Indicates Total Liabilities
Attributes	Attribute: minOccurs — Description: 0

TOP

TOTWOR

Attribute	Description
Name	TOTWOR
Datatype	Number
Description	Indicates Total Net worth
Attributes	Attribute: minOccurs — Description: 0

TOP

WHTPMT

Attribute	Description
Name	WHTPMT
Datatype	Number
Description	Indicates What if Payment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Finsummary2

Attribute	Description
Name	Finsummary2
Datatype	
Description	Indicates Consolidated Financial Summary Information

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

RATNM

Attribute	Description
Name	RATNM
Datatype	String
Description	Indicates Ratio Name
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 35

TOP

STATBF

Attribute	Description
Name	STATBF
Datatype	String
Description	Indicates Ratio based on Stated Financials After Accounting for Payment Amount
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

STATAF

Attribute	Description
Name	STATAF
Datatype	String
Description	Indicates Ratio based on Stated Financials After Accounting for Payment Amount
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ACTBF

Attribute	Description
Name	ACTBF
Datatype	String
Description	Indicates Ratio based on Actual Financials Before Accounting for Payment Amount
Attributes	Attribute: minOccurs; Description: 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

ACTAF

Attribute	Description
Name	ACTAF
Datatype	String
Description	Indicates Ratio based on Actual Financials After Accounting for Payment Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Investi1

Attribute	Description
Name	Investi1
Datatype	
Description	Indicates Investigation Summary
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

VERTYPE

Attribute	Description
Name	VERTYPE
Datatype	String
Description	Indicates Verification Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

AGENCY

Attribute	Description
Name	AGENCY
Datatype	String
Description	Indicates Investigating Agency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Investi2

Attribute	Description
Name	Investi2
Datatype	
Description	Indicates Investigation Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOKE

Attribute	Description
Name	SPOKE
Datatype	String
Description	Indicates who the Agency Contacted
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ATTEMPTS

Attribute	Description
Name	ATTEMPTS
Datatype	Number
Description	Indicates No of Attempts
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CALLDT

Attribute	Description
Name	CALLDT
Datatype	Date
Description	Indicates Called Date

Attributes	Attribute	Description
	minOccurs	0

TOP

RESULT

Attribute	Description	
Name	RESULT	
Datatype	String	
Description	Indicates Investigation Result	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

VERMAT

Attribute	Description	
Name	VERMAT	
Datatype	String	
Description	Indicates whether Verification Matched	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Custdedupe

Attribute	Description	
Name	Custdedupe	
Datatype		
Description	Indicates Possible Duplicate Customer Names	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FSTNM

Attribute	Description
Name	FSTNM
Datatype	String
Description	Indicates First Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LSTNM

Attribute	Description
Name	LSTNM
Datatype	String
Description	Indicates Last Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NATID

Attribute	Description

Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CNT

Attribute	Description
Name	CNT
Datatype	String
Description	Indicates Counter Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

NAT

Attribute	Description
Name	NAT
Datatype	String
Description	Indicates Nationality
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCAT

Attribute	Description
Name	CCAT
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	Indicates Date of Birth

Attributes	Attribute	Description
	minOccurs	0

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description	Indicates Customer Language	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description	Indicates Customer Email	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

TOP

EXISTING

Attribute	Description	
Name	EXISTING	
Datatype	String	
Description	Indicates whether Existing Customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PASSNO

Attribute	Description	
Name	PASSNO	
Datatype	String	
Description	Indicates Passport Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Landline Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Financials3

Attribute	Description
Name	Financials3
Datatype	
Description	Indicates Customer Income Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INCTYPE

Attribute	**Description**	
Name	INCTYPE	
Datatype	String	
Description	Indicates Income Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,R,B,O

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Income Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREQ

Attribute	**Description**	
Name	FREQ	
Datatype	String	
Description	Indicates Income Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M,B,W

TOP

Cusudf

Attribute	Description
Name	Cusudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

Cust-Acct

Attribute	Description
Name	Cust-Acct
Datatype	
Description	Indicates Customer Account Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Settlement Account Class
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates Customer Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACMASK

Attribute	Description
Name	ACMASK
Datatype	String
Description	Indicates Customer Account Mask
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CCYTYPE

Attribute	Description
Name	CCYTYPE
Datatype	String
Description	Indicates Currency Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACODE

Attribute	Description

Name	ACODE
Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

Collat1

Attribute	Description
Name	Collat1
Datatype	
Description	Indicates Collateral Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

COLLCD

Attribute	Description
Name	COLLCD
Datatype	String
Description	Indicates Collateral Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	Indicates Collateral Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	Indicates Collateral Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLSTDT

Attribute	Description
Name	COLLSTDT
Datatype	Date
Description	Indicates Collateral Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLENDDT

Attribute	Description
Name	COLLENDDT
Datatype	Date
Description	Indicates Collateral End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	Indicates Collateral Category
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	Indicates Collateral Haircut Margin
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,M,G

TOP

COLLREVDT

Attribute	Description
Name	COLLREVDT
Datatype	Date
Description	Indicates Collateral Revision Date
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLCHGDT

Attribute	Description
Name	COLLCHGDT
Datatype	String
Description	Indicates Collateral
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,L,P,H,A

TOP

COLLREVLDT

Attribute	Description
Name	COLLREVLDT

Datatype	Date
Description	Indicates Collateral Revaluation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLREVCHK

Attribute	**Description**
Name	COLLREVCHK
Datatype	String
Description	Indicates whether Collateral Revaluation is Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SECUID

Attribute	**Description**
Name	SECUID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NOMUNITVL

Attribute	**Description**
Name	NOMUNITVL
Datatype	Number
Description	Indicates Nominal Unit Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPAMT

Attribute	**Description**
Name	CAPAMT
Datatype	Number
Description	Indicates Collateral Cap Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUAID

Attribute	Description
Name	GUAID
Datatype	String
Description	Indicates Guarantor Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RATIN

Attribute	Description
Name	RATIN
Datatype	String
Description	Indicates Rating
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Collat2

Attribute	Description
Name	Collat2
Datatype	
Description	Indicates Collateral Covenant Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMON

Attribute	Description
Name	STMON
Datatype	String
Description	Indicates Start Month

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REM

Attribute	**Description**	
Name	REM	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVNM

Attribute	**Description**	
Name	COVNM	
Datatype	String	
Description	Indicates Covenant Name	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Covenant Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REVDT

Attribute	**Description**	
Name	REVDT	
Datatype	Date	
Description	Indicates Revision Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANDT

Attribute	Description
Name	MANDT
Datatype	Date
Description	Indicates whether Covenant is Mandatory
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAY

Attribute	Description
Name	GRCDAY
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	Indicates Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

Veh-Details

Attribute	Description
Name	Veh-Details
Datatype	
Description	Indicates Vehicle Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VEH_IDNUM

Attribute	Description
Name	VEH_IDNUM
Datatype	String
Description	Indicates Vehicle Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_YEAR

Attribute	Description
Name	VEH_YEAR
Datatype	Number
Description	Indicates Vehicle Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_MAKE

Attribute	Description
Name	VEH_MAKE
Datatype	String
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_MODEL

Attribute	Description
Name	VEH_MODEL
Datatype	String
Description	Indicates Vehicle Model
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_BDYSTYLE

Attribute	Description
Name	VEH_BDYSTYLE

Datatype	String
Description	Indicates Vehicle Body Style
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VEH_USAGE

Attribute	**Description**
Name	VEH_USAGE
Datatype	String
Description	Indicates Vehicle Usage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Requested1

Attribute	**Description**
Name	Requested1
Datatype	
Description	Indicates Overall Loan Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	4

TOP

REQAMT

Attribute	Description
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	Attribute: minOccurs, Description: 1

TOP

TENORM

Attribute	Description
Name	TENORM
Datatype	Number
Description	Indicates Loan Tenor
Attributes	Attribute: minOccurs, Description: 0

TOP

INTEREST_RATE_TYPE

Attribute	Description
Name	INTEREST_RATE_TYPE
Datatype	Number
Description	Indicates Interest Rate Type
Attributes	Attribute: minOccurs, Description: 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

PROMO

Attribute	Description
Name	PROMO
Datatype	String
Description	Indicates Promotion Id
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Requested2

Attribute	**Description**
Name	Requested2
Datatype	
Description	Indicates Individual Request Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ITEMIZATION

Attribute	**Description**
Name	ITEMIZATION
Datatype	String
Description	Indicates Itemization Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REQAMT

Attribute	**Description**
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMMENT

Attribute	**Description**

Name	COMMENT
Datatype	String
Description	Indicates Comments
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Comments

Attribute	**Description**
Name	Comments
Datatype	
Description	Indicates Comment Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SEQUENCENUMBER

Attribute	**Description**
Name	SEQUENCENUMBER
Datatype	String
Description	Indicates Comment Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	35

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMBY

Attribute	Description
Name	COMMBY
Datatype	String
Description	Indicates User who input Comment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMDT

Attribute	Description
Name	COMMDT
Datatype	Date
Description	Indicates Comment Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Udf

Attribute	Description
Name	Udf
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

L1

Attribute	Description
Name	L1

Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L2

Attribute	Description
Name	L2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L3

Attribute	Description
Name	L3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L4

Attribute	Description
Name	L4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L5

Attribute	Description
Name	L5
Datatype	String
Description	Indicates User Defined Field

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L6

Attribute	**Description**
Name	L6
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L7

Attribute	**Description**
Name	L7
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L8

Attribute	**Description**
Name	L8
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

L9

Attribute	**Description**
Name	L9
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

L10

Attribute	Description
Name	L10
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L11

Attribute	Description
Name	L11
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L12

Attribute	Description
Name	L12
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L13

Attribute	Description
Name	L13
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L14

Attribute	Description
Name	L14
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

L15

Attribute	Description
Name	L15
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

L16

Attribute	Description
Name	L16
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

L17

Attribute	Description
Name	L17
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

L18

Attribute	Description
Name	L18
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L19

Attribute	Description
Name	L19
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

L20

Attribute	Description
Name	L20
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F1

Attribute	Description
Name	F1
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

F2

Attribute	Description
Name	F2

Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F3

Attribute	Description
Name	F3
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F4

Attribute	Description
Name	F4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F5

Attribute	Description
Name	F5
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

F6

Attribute	Description
Name	F6
Datatype	String
Description	Indicates User Defined Field

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F7

Attribute	Description	
Name	F7	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F8

Attribute	Description	
Name	F8	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F9

Attribute	Description	
Name	F9	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

F10

Attribute	Description	
Name	F10	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

F11

Attribute	Description	
Name	F11	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

F12

Attribute	Description	
Name	F12	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

F13

Attribute	Description	
Name	F13	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

F14

Attribute	Description	
Name	F14	
Datatype	String	
Description	Indicates User Defined Field	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

F15

Attribute	Description
Name	F15
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F16

Attribute	Description
Name	F16
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F17

Attribute	Description
Name	F17
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F18

Attribute	Description
Name	F18
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F19

Attribute	Description
Name	F19
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

F20

Attribute	Description
Name	F20
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B1

Attribute	Description
Name	B1
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B2

Attribute	Description
Name	B2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

B3

Attribute	Description
Name	B3

Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B4

Attribute	Description
Name	B4
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B5

Attribute	Description
Name	B5
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B6

Attribute	Description
Name	B6
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Chklst1

Attribute	Description
Name	Chklst1
Datatype	
Description	Indicates Checklist Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CHKLSTID

Attribute	Description	
Name	CHKLSTID	
Datatype	String	
Description	Indicates Checklist Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHKLSTDESC

Attribute	Description	
Name	CHKLSTDESC	
Datatype	String	
Description	Indicates Checklist Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

VERIFY

Attribute	Description	
Name	VERIFY	
Datatype	String	
Description	Indicates Verified By	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

COMMENT

Attribute	Description	
Name	COMMENT	
Datatype	String	
Description	Indicates Comments	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

Custudf

Attribute	Description
Name	Custudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tradein

Attribute	Description
Name	Tradein
Datatype	
Description	Indicates Trade In Asset Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ASSETTYP

Attribute	Description
Name	ASSETTYP
Datatype	String
Description	Indicates Asset Type
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	enumeration	V,H,O

TOP

ASSETSUBTYP

Attribute	Description
Name	ASSETSUBTYP
Datatype	String
Description	Indicates Asset Sub Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MAKE

Attribute	Description
Name	MAKE
Datatype	Number
Description	Indicates Vehicle Make
Attributes	Attribute: minOccurs — Description: 0

TOP

MODEL

Attribute	Description
Name	MODEL
Datatype	String
Description	Indicates Model Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MANYR

Attribute	Description
Name	MANYR
Datatype	Number
Description	Indicates Manufacture Year
Attributes	Attribute: minOccurs — Description: 0

TOP

BODY

Attribute	Description
Name	BODY

Datatype	String
Description	Indicates Vehicle Body Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ASSETIDNO

Attribute	**Description**
Name	ASSETIDNO
Datatype	String
Description	Indicates Asset Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ASSETDESC

Attribute	**Description**
Name	ASSETDESC
Datatype	String
Description	Indicates Asset Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASSETWHVL

Attribute	**Description**
Name	ASSETWHVL
Datatype	Number
Description	Indicates Wholesale Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ASSETBSVL

Attribute	**Description**
Name	ASSETBSVL
Datatype	Number
Description	Indicates Asset Base Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYAMT

Attribute	Description
Name	PAYAMT
Datatype	Number
Description	Indicates Asset Payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ASSETADDON1

Attribute	Description
Name	ASSETADDON1
Datatype	Number
Description	Indicates Asset Add-on Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTVAL

Attribute	Description
Name	TOTVAL
Datatype	Number
Description	Indicates Asset Total Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ASSETVLDT

Attribute	Description
Name	ASSETVLDT
Datatype	Date
Description	Indicates Asset Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ASSETSOURCE

Attribute	Description
Name	ASSETSOURCE
Datatype	String
Description	Indicates Asset Source
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ASSETSUPP

Attribute	Description
Name	ASSETSUPP
Datatype	String
Description	Indicates Asset Supplier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ASSETEDI

Attribute	Description
Name	ASSETEDI
Datatype	String
Description	Indicates Asset Edition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Loanoffers

Attribute	Description
Name	Loanoffers
Datatype	
Description	Indicates Loan Offer Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

OFFID

Attribute	Description

Name	OFFID
Datatype	String
Description	Indicates Offer Id
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFINST

Attribute	**Description**
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREQUNIT

Attribute	**Description**
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Interest Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECK

Attribute	Description
Name	CHECK
Datatype	String
Description	Indicates whether Offer Needs to be Applied
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Loan2

Attribute	Description
Name	Loan2
Datatype	
Description	Indicates Loan Main Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANCCY

Attribute	Description
Name	LOANCCY
Datatype	String
Description	Indicates Loan Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	Indicates Loan Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAX

Attribute	Description
Name	TAX
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFINST

Attribute	Description
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	String	
Description	Indicates Income Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M,B,W

TOP

SPREAD

Attribute	Description	
Name	SPREAD	
Datatype	String	
Description	Indicates Interest Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EFFRATE

Attribute	Description	
Name	EFFRATE	
Datatype	String	
Description	Indicates Effective Interest Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLACCNO

Attribute	Description	
Name	CLACCNO	
Datatype	String	
Description	Indicates Loan Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

INSSTDT

Attribute	Description
Name	INSSTDT
Datatype	Date
Description	Indicates Installment Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loan3

Attribute	Description
Name	Loan3
Datatype	
Description	Indicates Loan Component Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NO1

Attribute	Description
Name	NO1
Datatype	Number
Description	Indicates Schedule No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Frequency Unit

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

SCHTYP

Attribute	Description
Name	SCHTYP
Datatype	String
Description	Indicates Schedule Type
Attributes	**Attribute** / **Description**
	minOccurs / 1
Restrictions	**Restrictions** / **Description**
	enumeration / P,D,R

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 35

TOP

Loan4

Attribute	Description
Name	Loan4
Datatype	
Description	Indicates Loan Schedule Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCHNO

Attribute	Description
Name	SCHNO
Datatype	Number
Description	Indicates Schedule Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EMI_AMOUNT

Attribute	Description
Name	EMI_AMOUNT
Datatype	Number
Description	Indicate EMI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMORPRI

Attribute	Description
Name	AMORPRI
Datatype	Number
Description	Indicates Amortized Principal Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTEREST_AMOUNT

Attribute	Description
Name	INTEREST_AMOUNT
Datatype	Number
Description	Indicates Interest Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPI

Attribute	Description
Name	CAPI
Datatype	String
Description	Indicates Capitalized Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WAIVE

Attribute	Description
Name	WAIVE
Datatype	String
Description	Indicates whether Amount is Waived
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Crdratout

Attribute	Description	
Name	Crdratout	
Datatype		
Description	Indicates External Credit Rating Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

EXTAGEN

Attribute	Description	
Name	EXTAGEN	
Datatype	String	
Description	Indicates External Credit Rating Agency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

RECOMM

Attribute	Description	
Name	RECOMM	
Datatype	String	
Description	Indicates External Credit Rating Agency Final Recommendation	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	R,N

TOP

Crdratin

Attribute	Description	
Name	Crdratin	
Datatype		
Description	Indicates Internal Credit Rating Details of Loan Application	
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description

Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

GRD

Attribute	**Description**
Name	GRD
Datatype	String
Description	Indicates Final Internal Credit Rating Grade
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SCR

Attribute	**Description**
Name	SCR
Datatype	Number
Description	Indicates Internal Credit Rating Score
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	Indicates Internal Credit Rating Rule Id used
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Crratin2

Attribute	Description
Name	Crratin2
Datatype	
Description	Indicates Internal Credit Rating Details by Customer
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 35

TOP

QUES

Attribute	Description
Name	QUES
Datatype	String
Description	Indicates Credit Rating Question
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 105

TOP

ANS

Attribute	Description
Name	ANS
Datatype	String
Description	Indicates Answer to Credit Rating Question
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

CAT

Attribute	Description
Name	CAT
Datatype	String
Description	Indicates Credit Rating Question Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Bureau

Attribute	Description
Name	Bureau
Datatype	
Description	Indicates Credit Bureau Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Number for which Credit Bureau Information is obtained
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUREAU

Attribute	Description
Name	BUREAU

Datatype	String
Description	Indicates Credit Bureau
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RPTTYP

Attribute	**Description**
Name	RPTTYP
Datatype	String
Description	Indicates Bureau Report Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / NEWAPP,VFYAPP,UNDERW,UNAPPR,CHKDOC,FIVERI,FUNDED

TOP

Chgs

Attribute	**Description**
Name	Chgs
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	**Description**
Name	EVENTCD
Datatype	String
Description	Indicates Charge Collection Event
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTSETT

Attribute	Description
Name	AMTSETT
Datatype	Number
Description	Indicates Charge Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDUEDT

Attribute	Description
Name	SCHDUEDT
Datatype	Date
Description	Indicates Charge Due Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

WAIV

Attribute	Description
Name	WAIV
Datatype	String
Description	Indicates whether Charge is Waived

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNM

Attribute	**Description**	
Name	COMPNM	
Datatype	String	
Description	Indicates Component Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Loandedupe

Attribute	**Description**	
Name	Loandedupe	
Datatype		
Description	Indicates Other Loan Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Currency Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	Indicates Loan Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	Indicates Outstanding Loan Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

Riskfactor

Attribute	Description
Name	Riskfactor
Datatype	
Description	Indicates Risk Factor Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

RISKFACT

Attribute	Description
Name	RISKFACT
Datatype	String
Description	Indicates Risk Factor
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

Chgs1

Attribute	Description

ORACLE

Name	Chgs1
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Promotions

Attribute	**Description**
Name	Promotions
Datatype	
Description	Indicates Promotions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.4.OR-CreateSaveRLAppEntry-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Applicationhead-PK*
      - *APPNO*
    - *Applicationhead-IO*
      - *APPNO*
      - *DATE*
      - *PRDCD*
      - *CHNL*
      - *INTERCD*
      - *INTNAME*
      - *CUSTTYPE1*
      - *CCY*
      - *LEAD*
      - *CONT*
      - *PUR*
      - *USERREFNO*
      - *APPCAT*
      - *OFFAPPLNUM*
      - *Customer1*

CUSTNO
SALUT
FSTNM
MIDNM
LSTNM
NATID
DOB
MOTHERNM
LANG
DEPEND
EMAIL
MARSTAT
EXISTING
PASSNO
PASSISSDT
PASSEXPDT
MOBNO
LANDNO
OFFNO
FAX
CUSTTYPE
FINCCY
ACCLS
ACCNUM
GENDER
SNAME
CNTY
NLTY
CUST_CATEG
Customer2
- *APPNO*
- *CUSTNO*
- *ADDTYPE*
- *MAILING*
- *CONNO*
- *ADDLN1*
- *ADDLN2*
- *ADDLN3*
- *ZIP*
- *CNTY*

Customer3
- *APPNO*
- *CUSTNO*
- *EMPTYPE*

EMP
CUSTOCC
DESIG
ADDLN1
ADDLN2
ADDLN3
ZIP
CNTY
PHONE
EXTN
CONTACT
CONPHN
CONPHNEXTN
COMMENT
DEPT
EMPID
EMPYR
EMPMNTH
INCCCY
INCAMT
FREQ
CONTACT_NAME

Financials1

ASSETTYP
ASSETSUB
MAKE
MODEL
MANYR
BODY
HOUSENO
ASSETVL
ADDLN1
ADDLN2
OCCUPANCY
REGNO

Financials2

APPNO
CUSTNO
LIABTYP
LIABSUB
LIABFREQ
LAIBAMT
BAL
REM

LIABSTDT

LIABENDDT

Finsummary

MONACTINC

MONACTDEBT

GRADE

WHTPMT

Finsummary2

Investi1

CUSTNO

VERTYPE

AGENCY

Custdedupe

CTYPE

FSTNM

LSTNM

SNAME

NATID

CNT

NAT

CCAT

DOB

LANG

EMAIL

EXISTING

PASSNO

MOBNO

LANDNO

Financials3

INCTYPE

CCY

AMT

FREQ

Cusudf

NAME

VALUE

Cust-Acct

CUSTNO

ACCLS

ACCCY

ACMASK

CCYTYPE

ACODE

UDFDETAILS

FLDNAM

FLDVAL

Collat1

APPNO

CUSTNO

COLLCD

COLLDESC

COLLCCY

COLLVL

COLLSTDT

COLLENDDT

COLLCAT

COLLHAIR

COLLTYPE

COLLREVDT

COLLCHGDT

COLLREVLDT

COLLREVCHK

SECUID

NOMUNITVL

CAPAMT

GUAID

RATIN

Collat2

DUEDT

STMON

REM

COVNM

DESC

REVDT

MANDT

GRCDAY

NOTDAY

FREQ

Veh-Details

VEH_IDNUM

VEH_YEAR

VEH_MAKE

VEH_MODEL

VEH_BDYSTYLE

VEH_USAGE

Requested1

APPNO

PRDCD

- *REQAMT*
- *TENORM*
- *INTEREST_RATE_TYPE*
- *DPMNTAMT*
- *CCY*
- *Requested2*
  - *APPNO*
  - *CUSTNO*
  - *ITEMIZATION*
  - *REQAMT*

Comments

- *APPNO*
- *PRDCD*
- *SEQUENCENUMBER*
- *COMMENT*
- *COMMBY*
- *COMMDT*

Udf

- *B1*
- *B2*
- *B3*
- *B4*
- *B5*
- *B6*

Chklst1

- *CHKLSTID*
- *CHKLSTDESC*
- *VERIFY*

Custudf

- *NAME*

Tradein

- *ASSETTYP*
- *ASSETWHVL*
- *ASSETBSVL*
- *PAYAMT*
- *ASSETADDON1*
- *TOTVAL*
- *CURR*

Loanoffers

- *OFFID*
- *RATE*
- *NOOFINST*
- *FREQUNIT*
- *FREQ*

- *RATECD*
- *SPREAD*
- *EFFRATE*
- *CHECK*

Loan2

- *LOANCCY*
- *LOANAMT*
- *RATE*
- *DPMNTAMT*
- *VALDT*
- *MATDT*
- *NOOFINST*
- *FREQUNIT*
- *FREQ*
- *SPREAD*
- *EFFRATE*
- *CLACCNO*
- *INSSTDT*

Loan3

- *NO1*
- *FREQ*
- *UNIT*
- *FRSTDUEDT*
- *AMT*
- *SCHTYP*
- *COMPNM*

Loan4

- *SCHNO*
- *DUEDT*
- *AMTDUE*
- *EMI_AMOUNT*
- *AMORPRI*
- *INTEREST_AMOUNT*
- *CAPI*
- *WAIVE*
- *COMPNM*

Crdratout

- *EXTAGEN*
- *RECOMM*

Crdratin

- *CUSTNO*
- *APPNO*
- *RULEID*
- *Crratin2*

APPNO
CUSTNO
QUES
ANS
CAT
Bureau
CUSTID
BUREAU
RPTTYP
STAT
Chgs
EVENTCD
CHGCCY
AMT
AMTSETT
SCHDUEDT
WAIV
COMPNM
Loandedupe
CCY
VALDT
MATDT
CUSTNO
LOAN_ACCNO
AMT
OUTSTAMT
RATE
Riskfactor
RISKFACT
DESC
Chgs1
Promotions

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Applicationhead-PK

Attribute	Description
Name	Applicationhead-PK
Datatype	
Description	

TOP

APPNO

Attribute	Description	
Name	APPNO	
Datatype	String	
Description	Indicates Application Number	
Attributes	Attribute	Description
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Applicationhead-IO

Attribute	Description
Name	Applicationhead-IO
Datatype	
Description	

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	Indicates Incorporation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHNL

Attribute	Description
Name	CHNL
Datatype	String
Description	Indicates Originating Channel of Application

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INTERCD

Attribute	Description
Name	INTERCD
Datatype	String
Description	Indicates Intermediary Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTNAME

Attribute	Description
Name	INTNAME
Datatype	String
Description	Indicates Intermediary Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTTYPE1

Attribute	Description
Name	CUSTTYPE1
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LEAD

Attribute	**Description**
Name	LEAD
Datatype	String
Description	Indicates Lead Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONT

Attribute	**Description**
Name	CONT
Datatype	String
Description	Indicates Contact Person
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PUR

Attribute	**Description**
Name	PUR
Datatype	String
Description	Indicates Loan Purpose
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

USERREFNO

Attribute	**Description**
Name	USERREFNO
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

APPCAT

Attribute	Description
Name	APPCAT
Datatype	String
Description	Indicates Application Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OFFAPPLNUM

Attribute	Description
Name	OFFAPPLNUM
Datatype	String
Description	Indicates Offline Application Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Customer1

Attribute	Description
Name	Customer1
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SALUT

Attribute	Description

Name	SALUT
Datatype	String
Description	Indicates Salutation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Mr,Mrs,Miss,Dr

TOP

FSTNM

Attribute	**Description**
Name	FSTNM
Datatype	String
Description	Indicates First Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MIDNM

Attribute	**Description**
Name	MIDNM
Datatype	String
Description	Indicates Middle Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LSTNM

Attribute	**Description**
Name	LSTNM
Datatype	String
Description	Indicates Last Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NATID

Attribute	**Description**
Name	NATID
Datatype	String
Description	Indicates National Id

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	Indicates Date of Birth
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOTHERNM

Attribute	Description
Name	MOTHERNM
Datatype	String
Description	Indicates Mothers Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEPEND

Attribute	Description
Name	DEPEND
Datatype	Number
Description	Indicates No of Dependencies
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	Indicates Customer Email
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

MARSTAT

Attribute	Description
Name	MARSTAT
Datatype	String
Description	Indicates Marital Status
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,U,D

TOP

EXISTING

Attribute	Description
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PASSNO

Attribute	Description
Name	PASSNO
Datatype	String
Description	Indicates Passport Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PASSISSDT

Attribute	Description
Name	PASSISSDT

Datatype	Date
Description	Indicates Passport Issue Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASSEXPDT

Attribute	Description
Name	PASSEXPDT
Datatype	Date
Description	Indicates Passport Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	Indicates Mobile Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANDNO

Attribute	Description
Name	LANDNO
Datatype	Number
Description	Indicates Landline Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFNO

Attribute	Description
Name	OFFNO
Datatype	Number
Description	Indicates Office Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FAX

Attribute	Description
Name	FAX
Datatype	Number
Description	Indicates Customer Fax

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTTYPE

Attribute	Description
Name	CUSTTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,C

TOP

FINCCY

Attribute	Description
Name	FINCCY
Datatype	String
Description	Indicates Financial Details Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Settlement Account Class
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ACCNUM

Attribute	Description
Name	ACCNUM
Datatype	String
Description	Indicates Account Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 22

TOP

GENDER

Attribute	Description
Name	GENDER
Datatype	String
Description	Indicates Customer Gender
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	Indicates Customer Nationality
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUST_CATEG

Attribute	Description
Name	CUST_CATEG
Datatype	String
Description	Indicates Customer Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Customer2

Attribute	Description
Name	Customer2
Datatype	
Description	Indicates Customer Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDTYPE

Attribute	Description
Name	ADDTYPE
Datatype	String

Description	Indicates Address Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H,W,T,O

TOP

MAILING

Attribute	**Description**
Name	MAILING
Datatype	String
Description	Indicates whether Mailing Address
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONNO

Attribute	**Description**
Name	CONNO
Datatype	Number
Description	Indicates Contact Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLN1

Attribute	**Description**
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN2

Attribute	**Description**
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Customer3

Attribute	Description
Name	Customer3
Datatype	
Description	Indicates Director Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String

Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EMPTYPE

Attribute	**Description**
Name	EMPTYPE
Datatype	String
Description	Indicates Employment Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PART,FULL,CONT

TOP

EMP

Attribute	**Description**
Name	EMP
Datatype	String
Description	Indicates Employer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTOCC

Attribute	**Description**
Name	CUSTOCC
Datatype	String
Description	Indicates Customer Occupation
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DESIG

Attribute	Description
Name	DESIG
Datatype	String
Description	Indicates Designation
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLN1

Attribute	Description
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLN2

Attribute	Description
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLN3

Attribute	Description
Name	ADDLN3
Datatype	String
Description	Indicates Address Line 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ZIP

Attribute	Description
Name	ZIP
Datatype	Number
Description	Indicates Zip Code
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	Indicates Customer Country
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PHONE

Attribute	Description
Name	PHONE
Datatype	Number
Description	Indicates Phone Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXTN

Attribute	Description
Name	EXTN
Datatype	Number
Description	Indicates Customer Extension
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTACT

Attribute	Description
Name	CONTACT
Datatype	Number
Description	Indicates Customer Contact
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPHN

Attribute	Description
Name	CONPHN
Datatype	Number
Description	Indicates Contact Phone Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPHNEXTN

Attribute	Description
Name	CONPHNEXTN
Datatype	Number
Description	Indicates Contact Phone Extension
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMMENT

Attribute	Description
Name	COMMENT
Datatype	String
Description	Indicates Comments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DEPT

Attribute	Description
Name	DEPT
Datatype	String
Description	Indicates Customer Department
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EMPID

Attribute	Description
Name	EMPID
Datatype	String
Description	Indicates Employee Id

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EMPYR

Attribute	Description
Name	EMPYR
Datatype	Number
Description	Indicates Employed Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPMNTH

Attribute	Description
Name	EMPMNTH
Datatype	Number
Description	Indicates Employed Months
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCCCY

Attribute	Description
Name	INCCCY
Datatype	String
Description	Indicates Income Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INCAMT

Attribute	Description
Name	INCAMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ

Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

CONTACT_NAME

Attribute	**Description**
Name	CONTACT_NAME
Datatype	String
Description	Indicates Customer Contact Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Financials1

Attribute	**Description**
Name	Financials1
Datatype	
Description	Indicates Customer Financial Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ASSETTYP

Attribute	**Description**
Name	ASSETTYP
Datatype	String
Description	Indicates Asset Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / V,H,O

TOP

ASSETSUB

Attribute	**Description**
Name	ASSETSUB
Datatype	String
Description	Indicates Asset Sub Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

MAKE

Attribute	Description
Name	MAKE
Datatype	Number
Description	Indicates Vehicle Make
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODEL

Attribute	Description
Name	MODEL
Datatype	String
Description	Indicates Model Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MANYR

Attribute	Description
Name	MANYR
Datatype	Number
Description	Indicates Manufacture Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BODY

Attribute	Description
Name	BODY
Datatype	String
Description	Indicates Vehicle Body Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

HOUSENO

Attribute	Description
Name	HOUSENO

Datatype	String
Description	Indicates House Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ASSETVL

Attribute	**Description**
Name	ASSETVL
Datatype	Number
Description	Indicates Asset Value
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDLN1

Attribute	**Description**
Name	ADDLN1
Datatype	String
Description	Indicates Address Line 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLN2

Attribute	**Description**
Name	ADDLN2
Datatype	String
Description	Indicates Address Line 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OCCUPANCY

Attribute	**Description**
Name	OCCUPANCY
Datatype	Number
Description	Indicates Occupancy
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REGNO

Attribute	Description
Name	REGNO
Datatype	Number
Description	Indicates Registration Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Financials2

Attribute	Description
Name	Financials2
Datatype	
Description	Indicates Customer Liability Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LIABTYP

Attribute	Description
Name	LIABTYP
Datatype	String

Description	Indicates Liability Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / LO,LE,RE,OT

TOP

LIABSUB

Attribute	**Description**
Name	LIABSUB
Datatype	String
Description	Indicates Liability Sub Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LIABFREQ

Attribute	**Description**
Name	LIABFREQ
Datatype	String
Description	Indicates Liability Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y

TOP

LAIBAMT

Attribute	**Description**
Name	LAIBAMT
Datatype	Number
Description	Indicates Liability Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAL

Attribute	**Description**
Name	BAL
Datatype	Number
Description	Indicates Liability Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LIABSTDT

Attribute	Description
Name	LIABSTDT
Datatype	Date
Description	Indicates Liability Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIABENDDT

Attribute	Description
Name	LIABENDDT
Datatype	Date
Description	Indicates Liability End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Finsummary

Attribute	Description
Name	Finsummary
Datatype	
Description	Indicates Asset Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTINC

Attribute	Description
Name	MONACTINC
Datatype	Number
Description	Indicates Monthly Actual Income
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MONACTDEBT

Attribute	Description
Name	MONACTDEBT
Datatype	Number
Description	Indicates Monthly Actual Debt
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRADE

Attribute	Description
Name	GRADE
Datatype	String
Description	Indicates Internal Final Grade
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

WHTPMT

Attribute	Description
Name	WHTPMT
Datatype	Number
Description	Indicates What if Payment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Finsummary2

Attribute	Description
Name	Finsummary2
Datatype	
Description	Indicates Consolidated Financial Summary Information
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Investi1

Attribute	Description
Name	Investi1
Datatype	
Description	Indicates Investigation Summary

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

VERTYPE

Attribute	Description
Name	VERTYPE
Datatype	String
Description	Indicates Verification Type
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

AGENCY

Attribute	Description
Name	AGENCY
Datatype	String
Description	Indicates Investigating Agency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Custdedupe

Attribute	Description
Name	Custdedupe
Datatype	
Description	Indicates Possible Duplicate Customer Names
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	Indicates Customer Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FSTNM

Attribute	Description
Name	FSTNM
Datatype	String
Description	Indicates First Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LSTNM

Attribute	Description
Name	LSTNM
Datatype	String
Description	Indicates Last Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates Customer Short Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NATID

Attribute	Description
Name	NATID
Datatype	String
Description	Indicates National Id
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

CNT

Attribute	Description
Name	CNT
Datatype	String
Description	Indicates Counter Number
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

NAT

Attribute	Description
Name	NAT
Datatype	String
Description	Indicates Nationality
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

CCAT

Attribute	Description
Name	CCAT
Datatype	String
Description	Indicates Customer Category
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

DOB

Attribute	Description
Name	DOB

Datatype	Date
Description	Indicates Date of Birth
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANG

Attribute	**Description**
Name	LANG
Datatype	String
Description	Indicates Customer Language
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	Indicates Customer Email
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

EXISTING

Attribute	**Description**
Name	EXISTING
Datatype	String
Description	Indicates whether Existing Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PASSNO

Attribute	**Description**
Name	PASSNO
Datatype	String
Description	Indicates Passport Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

MOBNO

Attribute	Description	
Name	MOBNO	
Datatype	Number	
Description	Indicates Mobile Number	
Attributes	Attribute	Description
	minOccurs	0

TOP

LANDNO

Attribute	Description	
Name	LANDNO	
Datatype	Number	
Description	Indicates Landline Number	
Attributes	Attribute	Description
	minOccurs	0

TOP

Financials3

Attribute	Description	
Name	Financials3	
Datatype		
Description	Indicates Customer Income Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

INCTYPE

Attribute	Description	
Name	INCTYPE	
Datatype	String	
Description	Indicates Income Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S,R,B,O

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String

Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

Cusudf

Attribute	**Description**
Name	Cusudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE

Datatype	String
Description	

TOP

Cust-Acct

Attribute	Description
Name	Cust-Acct
Datatype	
Description	Indicates Customer Account Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACCLS

Attribute	Description
Name	ACCLS
Datatype	String
Description	Indicates Settlement Account Class
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	Indicates Customer Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACMASK

Attribute	Description
Name	ACMASK
Datatype	String
Description	Indicates Customer Account Mask
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CCYTYPE

Attribute	Description
Name	CCYTYPE
Datatype	String
Description	Indicates Currency Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACODE

Attribute	Description
Name	ACODE
Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM

Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Collat1

Attribute	**Description**
Name	Collat1
Datatype	
Description	Indicates Collateral Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

COLLCD

Attribute	Description
Name	COLLCD
Datatype	String
Description	Indicates Collateral Code
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	Indicates Collateral Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

COLLVL

Attribute	Description
Name	COLLVL
Datatype	Number
Description	Indicates Collateral Value
Attributes	Attribute: minOccurs; Description: 0

TOP

COLLSTDT

Attribute	Description
Name	COLLSTDT
Datatype	Date
Description	Indicates Collateral Start Date
Attributes	Attribute: minOccurs, Description: 0

TOP

COLLENDDT

Attribute	Description
Name	COLLENDDT
Datatype	Date
Description	Indicates Collateral End Date
Attributes	Attribute: minOccurs, Description: 0

TOP

COLLCAT

Attribute	Description
Name	COLLCAT
Datatype	String
Description	Indicates Collateral Category
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

COLLHAIR

Attribute	Description
Name	COLLHAIR
Datatype	Number
Description	Indicates Collateral Haircut Margin
Attributes	Attribute: minOccurs, Description: 0

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: N,M,G

TOP

COLLREVDT

Attribute	Description
Name	COLLREVDT
Datatype	Date
Description	Indicates Collateral Revision Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCHGDT

Attribute	Description
Name	COLLCHGDT
Datatype	String
Description	Indicates Collateral
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,P,H,A

TOP

COLLREVLDT

Attribute	Description
Name	COLLREVLDT
Datatype	Date
Description	Indicates Collateral Revaluation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLREVCHK

Attribute	Description
Name	COLLREVCHK
Datatype	String
Description	Indicates whether Collateral Revaluation is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NOMUNITVL

Attribute	**Description**	
Name	NOMUNITVL	
Datatype	Number	
Description	Indicates Nominal Unit Value	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CAPAMT

Attribute	**Description**	
Name	CAPAMT	
Datatype	Number	
Description	Indicates Collateral Cap Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GUAID

Attribute	**Description**	
Name	GUAID	
Datatype	String	
Description	Indicates Guarantor Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RATIN

Attribute	**Description**	
Name	RATIN	
Datatype	String	
Description	Indicates Rating	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Collat2

Attribute	Description
Name	Collat2
Datatype	
Description	Indicates Collateral Covenant Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMON

Attribute	Description
Name	STMON
Datatype	String
Description	Indicates Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVNM

Attribute	Description
Name	COVNM
Datatype	String
Description	Indicates Covenant Name

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	Indicates Revision Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MANDT

Attribute	Description
Name	MANDT
Datatype	Date
Description	Indicates whether Covenant is Mandatory
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GRCDAY

Attribute	Description
Name	GRCDAY
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTDAY

Attribute	Description
Name	NOTDAY

Datatype	Number
Description	Indicates Notice Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,B,W

TOP

Veh-Details

Attribute	Description
Name	Veh-Details
Datatype	
Description	Indicates Vehicle Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_IDNUM

Attribute	Description
Name	VEH_IDNUM
Datatype	String
Description	Indicates Vehicle Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VEH_YEAR

Attribute	Description
Name	VEH_YEAR
Datatype	Number
Description	Indicates Vehicle Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VEH_MAKE

Attribute	Description
Name	VEH_MAKE
Datatype	String
Description	Indicates Vehicle Make
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

VEH_MODEL

Attribute	Description
Name	VEH_MODEL
Datatype	String
Description	Indicates Vehicle Model
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

VEH_BDYSTYLE

Attribute	Description
Name	VEH_BDYSTYLE
Datatype	String
Description	Indicates Vehicle Body Style
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

VEH_USAGE

Attribute	Description
Name	VEH_USAGE
Datatype	String
Description	Indicates Vehicle Usage
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Requested1

Attribute	Description
Name	Requested1

Datatype	
Description	Indicates Overall Loan Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

REQAMT

Attribute	**Description**
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TENORM

Attribute	**Description**
Name	TENORM
Datatype	Number
Description	Indicates Loan Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTEREST_RATE_TYPE

Attribute	Description
Name	INTEREST_RATE_TYPE
Datatype	Number
Description	Indicates Interest Rate Type
Attributes	Attribute: minOccurs, Description: 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

Requested2

Attribute	Description
Name	Requested2
Datatype	
Description	Indicates Individual Request Details
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

APPNO

Attribute	Description
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	Attribute: minOccurs, Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITEMIZATION

Attribute	**Description**
Name	ITEMIZATION
Datatype	String
Description	Indicates Itemization Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REQAMT

Attribute	**Description**
Name	REQAMT
Datatype	Number
Description	Indicates Overall Requested Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Comments

Attribute	**Description**
Name	Comments
Datatype	
Description	Indicates Comment Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

APPNO

Attribute	**Description**

Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SEQUENCENUMBER

Attribute	**Description**
Name	SEQUENCENUMBER
Datatype	String
Description	Indicates Comment Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMENT

Attribute	**Description**
Name	COMMENT
Datatype	String
Description	Indicates Comments
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COMMBY

Attribute	**Description**
Name	COMMBY
Datatype	String
Description	Indicates User who input Comment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COMMDT

Attribute	**Description**
Name	COMMDT
Datatype	Date
Description	Indicates Comment Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Udf

Attribute	**Description**
Name	Udf
Datatype	
Description	Indicates UDF Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

B1

Attribute	**Description**
Name	B1
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B2

Attribute	**Description**
Name	B2
Datatype	String
Description	Indicates User Defined Field
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

B3

Attribute	Description
Name	B3
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

B4

Attribute	Description
Name	B4
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

B5

Attribute	Description
Name	B5
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

B6

Attribute	Description
Name	B6
Datatype	String
Description	Indicates User Defined Field
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Chklst1

Attribute	Description
Name	Chklst1

Datatype	
Description	Indicates Checklist Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHKLSTID

Attribute	**Description**
Name	CHKLSTID
Datatype	String
Description	Indicates Checklist Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKLSTDESC

Attribute	**Description**
Name	CHKLSTDESC
Datatype	String
Description	Indicates Checklist Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

VERIFY

Attribute	**Description**
Name	VERIFY
Datatype	String
Description	Indicates Verified By
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Custudf

Attribute	**Description**
Name	Custudf
Datatype	
Description	Indicates Customer UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

Tradein

Attribute	Description	
Name	Tradein	
Datatype		
Description	Indicates Trade In Asset Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ASSETTYP

Attribute	Description	
Name	ASSETTYP	
Datatype	String	
Description	Indicates Asset Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	V,H,O

TOP

ASSETWHVL

Attribute	Description	
Name	ASSETWHVL	
Datatype	Number	
Description	Indicates Wholesale Value	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ASSETBSVL

Attribute	Description	
Name	ASSETBSVL	
Datatype	Number	
Description	Indicates Asset Base Value	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYAMT

Attribute	Description
Name	PAYAMT
Datatype	Number
Description	Indicates Asset Payment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

ASSETADDON1

Attribute	Description
Name	ASSETADDON1
Datatype	Number
Description	Indicates Asset Add-on Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TOTVAL

Attribute	Description
Name	TOTVAL
Datatype	Number
Description	Indicates Asset Total Value
Attributes	Attribute: minOccurs, Description: 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

Loanoffers

Attribute	Description
Name	Loanoffers
Datatype	
Description	Indicates Loan Offer Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

OFFID

Attribute	Description	
Name	OFFID	
Datatype	String	
Description	Indicates Offer Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

RATE

Attribute	Description	
Name	RATE	
Datatype	Number	
Description	Indicates Interest Rate	
Attributes	Attribute	Description
	minOccurs	0

TOP

NOOFINST

Attribute	Description	
Name	NOOFINST	
Datatype	String	
Description	Indicates No of Installments	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

FREQUNIT

Attribute	Description	
Name	FREQUNIT	
Datatype	String	
Description	Indicates Schedule Frequency Unit	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Interest Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EFFRATE

Attribute	Description
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECK

Attribute	Description

Name	CHECK
Datatype	String
Description	Indicates whether Offer Needs to be Applied
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Loan2

Attribute	Description
Name	Loan2
Datatype	
Description	Indicates Loan Main Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANCCY

Attribute	Description
Name	LOANCCY
Datatype	String
Description	Indicates Loan Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	Indicates Loan Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DPMNTAMT

Attribute	Description
Name	DPMNTAMT
Datatype	Number
Description	Indicates Down payment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFINST

Attribute	Description
Name	NOOFINST
Datatype	String
Description	Indicates No of Installments
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREQUNIT

Attribute	Description
Name	FREQUNIT
Datatype	String
Description	Indicates Schedule Frequency Unit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

SPREAD

Attribute	**Description**
Name	SPREAD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EFFRATE

Attribute	**Description**
Name	EFFRATE
Datatype	String
Description	Indicates Effective Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CLACCNO

Attribute	**Description**
Name	CLACCNO
Datatype	String
Description	Indicates Loan Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

INSSTDT

Attribute	Description
Name	INSSTDT
Datatype	Date
Description	Indicates Installment Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loan3

Attribute	Description
Name	Loan3
Datatype	
Description	Indicates Loan Component Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NO1

Attribute	Description
Name	NO1
Datatype	Number
Description	Indicates Schedule No
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	String
Description	Indicates Income Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,B,W

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Frequency Unit

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FRSTDUEDT

Attribute	**Description**	
Name	FRSTDUEDT	
Datatype	Date	
Description	Indicates First Due Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMT

Attribute	**Description**	
Name	AMT	
Datatype	Number	
Description	Indicates Income Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SCHTYP

Attribute	**Description**	
Name	SCHTYP	
Datatype	String	
Description	Indicates Schedule Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,D,R

TOP

COMPNM

Attribute	**Description**	
Name	COMPNM	
Datatype	String	
Description	Indicates Component Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Loan4

Attribute	Description
Name	Loan4
Datatype	
Description	Indicates Loan Schedule Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCHNO

Attribute	Description
Name	SCHNO
Datatype	Number
Description	Indicates Schedule Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DUEDT

Attribute	Description
Name	DUEDT
Datatype	Date
Description	Indicates Due Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EMI_AMOUNT

Attribute	Description
Name	EMI_AMOUNT
Datatype	Number
Description	Indicate EMI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMORPRI

Attribute	Description
Name	AMORPRI
Datatype	Number
Description	Indicates Amortized Principal Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTEREST_AMOUNT

Attribute	Description
Name	INTEREST_AMOUNT
Datatype	Number
Description	Indicates Interest Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPI

Attribute	Description
Name	CAPI
Datatype	String
Description	Indicates Capitalized Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WAIVE

Attribute	Description
Name	WAIVE
Datatype	String
Description	Indicates whether Amount is Waived
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Crdratout

Attribute	Description	
Name	Crdratout	
Datatype		
Description	Indicates External Credit Rating Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

EXTAGEN

Attribute	Description	
Name	EXTAGEN	
Datatype	String	
Description	Indicates External Credit Rating Agency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

RECOMM

Attribute	Description	
Name	RECOMM	
Datatype	String	
Description	Indicates External Credit Rating Agency Final Recommendation	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	R,N

TOP

Crdratin

Attribute	Description	
Name	Crdratin	
Datatype		
Description	Indicates Internal Credit Rating Details of Loan Application	
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description

Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	Indicates Internal Credit Rating Rule Id used
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Crratin2

Attribute	**Description**
Name	Crratin2
Datatype	
Description	Indicates Internal Credit Rating Details by Customer
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

APPNO

Attribute	**Description**
Name	APPNO
Datatype	String
Description	Indicates Application Number
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates Customer Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

QUES

Attribute	Description
Name	QUES
Datatype	String
Description	Indicates Credit Rating Question
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ANS

Attribute	Description
Name	ANS
Datatype	String
Description	Indicates Answer to Credit Rating Question
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

CAT

Attribute	Description
Name	CAT
Datatype	String
Description	Indicates Credit Rating Question Category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Bureau

Attribute	Description
Name	Bureau
Datatype	
Description	Indicates Credit Bureau Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Number for which Credit Bureau Information is obtained
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUREAU

Attribute	Description
Name	BUREAU
Datatype	String
Description	Indicates Credit Bureau
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RPTTYP

Attribute	Description
Name	RPTTYP
Datatype	String
Description	Indicates Bureau Report Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

STAT

Attribute	Description

Name	STAT
Datatype	String
Description	Indicates Bureau Information Retrieval Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

Chgs

Attribute	**Description**
Name	Chgs
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	**Description**
Name	EVENTCD
Datatype	String
Description	Indicates Charge Collection Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCCY

Attribute	**Description**
Name	CHGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTSETT

Attribute	Description
Name	AMTSETT
Datatype	Number
Description	Indicates Charge Amount Settled
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHDUEDT

Attribute	Description
Name	SCHDUEDT
Datatype	Date
Description	Indicates Charge Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIV

Attribute	Description
Name	WAIV
Datatype	String
Description	Indicates whether Charge is Waived
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNM

Attribute	Description
Name	COMPNM
Datatype	String
Description	Indicates Component Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Loandedupe

Attribute	Description
Name	Loandedupe
Datatype	
Description	Indicates Other Loan Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates Currency Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	Attribute	Description
	minOccurs	0

TOP

MATDT

Attribute	Description	
Name	MATDT	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description	Indicates Customer Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

LOAN_ACCNO

Attribute	Description

Name	LOAN_ACCNO
Datatype	String
Description	Indicates Loan Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Income Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUTSTAMT

Attribute	**Description**
Name	OUTSTAMT
Datatype	Number
Description	Indicates Outstanding Loan Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Riskfactor

Attribute	**Description**
Name	Riskfactor
Datatype	
Description	Indicates Risk Factor Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RISKFACT

Attribute	Description
Name	RISKFACT
Datatype	String
Description	Indicates Risk Factor
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Covenant Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Chgs1

Attribute	Description
Name	Chgs1
Datatype	
Description	Indicates Charge Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Promotions

Attribute	Description
Name	Promotions
Datatype	
Description	Indicates Promotions details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

2.32.AuthCustCatMaint

Authorisation of Customer Ctaegory

2.32.1.ST-AuthCustCatMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Customer-Cat-Full*
    - *CUSTCAT*
    - *CUSTCATDESC*
    - *POPULATECHANGESLOG*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Customer-Cat-Full

Attribute	Description

Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Authorization details

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the populate Changes Log. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

2.32.2.ST-AuthCustCatMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Customer-Cat-IO*
    - *CUSTCAT*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Authorization-IO details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

2.32.3.ST-AuthCustCatMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Customer-Cat-IO*
      - *CUSTCAT*
      - *MODNO*
    - *Sttm-Customer-Cat-Full*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Authorization-IO details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Sttm-Customer-Cat-Full

Attribute	Description
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Authorization details

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the populate Changes Log. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.4.ST-AuthCustCatMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Customer-Cat-PK*
      - *CUSTCAT*
    - *Sttm-Customer-Cat-IO*
      - *CUSTCAT*
      - *MODNO*
    - *Sttm-Customer-Cat-Full*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Customer-Cat-PK

Attribute	Description
Name	Sttm-Customer-Cat-PK
Datatype	
Description	Includes Customer Category Maintenance Authorization-Primary key details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Authorization-IO details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

Sttm-Customer-Cat-Full

Attribute	Description
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Authorization details

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG

Datatype	String
Description	Indicates the populate Changes Log. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.AuthLocMaint

Authorisation of Location Maintenance

2.33.1.ST-AuthLocMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Location-Full*
    - *LOCCODE*
    - *DESCRIPTION*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Authorization details

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the document Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the document description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

2.33.2.ST-AuthLocMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Location-IO*
    - *LOCCODE*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Authorization-IO details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the Location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number.

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

2.33.3.ST-AuthLocMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Location-IO*
      - *LOCCODE*
      - *MODNO*
    - *Sttm-Location-Full*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Authorization-IO details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the Location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Authorization details

TOP

LOCCODE

Attribute	Description

Name	LOCCODE
Datatype	String
Description	Indicates the Location Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the document description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.4.ST-AuthLocMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Location-PK*
      - *LOCCODE*
    - *Sttm-Location-IO*
      - *LOCCODE*
      - *MODNO*
    - *Sttm-Location-Full*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Location-PK

Attribute	Description
Name	Sttm-Location-PK
Datatype	
Description	Includes Location Maintenance Authorization-Primary key details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Authorization-IO details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Authorization details

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the location Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the document description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.34.AuthManStatChangInp

Authorize Staus Change

2.34.1.ST-AuthManStatChangInp-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Ac-Stat-Change-Full*
    - *CUSTACNO*
    - *ACCSTATUS*
    - *BRANCHCODE*
    - *BRANCHNAME*
    - *STATUSCHANGEDATE*
    - *SEQNO*
    - *STATUS*
    - *ACSTATNODR*
    - *ACSTATNOCR*
    - *ACSTATFROZEN*
    - *ACSTATDEPOST*
    - *ACSTATCHGAUTO*
    - *DORMANT*
    - *MAKERID*
    - *MAKERDTSTAMP*

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Authorization Full type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCSTATUS

Attribute	Description	
Name	ACCSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATNOCR

Attribute	**Description**	
Name	ACSTATNOCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATFROZEN

Attribute	**Description**	
Name	ACSTATFROZEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATDEPOST

Attribute	**Description**	
Name	ACSTATDEPOST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATCHGAUTO

Attribute	**Description**	
Name	ACSTATCHGAUTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Ac-Stat-Change-IO
CUSTACNO
BRANCHCODE
STATUSCHANGEDATE
SEQNO
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.34.3.ST-AuthManStatChangInp-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Ac-Stat-Change-IO*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *MODNO*
    - *Sttm-Ac-Stat-Change-Full*
      - *CUSTACNO*
      - *ACCSTATUS*
      - *BRANCHCODE*
      - *BRANCHNAME*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *STATUS*
      - *ACSTATNODR*
      - *ACSTATNOCR*
      - *ACSTATFROZEN*
      - *ACSTATDEPOST*

ACSTATCHGAUTO

DORMANT

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Authorization Input Only type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Authorization Full type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ACCSTATUS

Attribute	Description
Name	ACCSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATNOCR

Attribute	Description
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.34.4.ST-AuthManStatChangInp-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Ac-Stat-Change-PK*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
    - *Sttm-Ac-Stat-Change-IO*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *MODNO*
    - *Sttm-Ac-Stat-Change-Full*
      - *CUSTACNO*
      - *ACCSTATUS*
      - *BRANCHCODE*
      - *BRANCHNAME*
      - *STATUSCHANGEDATE*
      - *SEQNO*

STATUS
ACSTATNODR
ACSTATNOCR
ACSTATFROZEN
ACSTATDEPOST
ACSTATCHGAUTO
DORMANT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-PK

Attribute	Description
Name	Sttm-Ac-Stat-Change-PK
Datatype	
Description	Includes Manual Status Change Input Authorization Primary Key type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Authorization Input Only type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: totalDigits — Description: 22

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Authorization Full type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACCSTATUS

Attribute	**Description**
Name	ACCSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCHNAME

Attribute	**Description**
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	**Description**
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACSTATNODR

Attribute	Description	
Name	ACSTATNODR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATNOCR

Attribute	Description	
Name	ACSTATNOCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: totalDigits — Description: 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.AuthNoticePRD

Authorization of Notice Period Maintenance

2.35.1.ST-AuthNoticePRD-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Notice-Period-Full*
    - *BRANCHCODE*
    - *CUSTACNO*
    - *INITIATIONDATE*
    - *ACTIVATIONDATE*
    - *VALIDITYPERIOD*
    - *ENDDATE*
    - *NOTICEAMT*
    - *NOTICEID*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Notice-Period-Full

Attribute	Description
Name	Notice-Period-Full
Datatype	
Description	It indicates Full Details of the Notice Period Maintenance.

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicates Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INITIATIONDATE

Attribute	Description	
Name	INITIATIONDATE	
Datatype	Date	
Description	Indicates Initiation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACTIVATIONDATE

Attribute	Description	
Name	ACTIVATIONDATE	
Datatype	Date	
Description	Indicates Activation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALIDITYPERIOD

Attribute	Description
Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE
Datatype	Date
Description	Indicates End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>Name</td><td>VAL_TYPE</td></tr>
<tr><td>Datatype</td><td>String</td></tr>
<tr><td>Description</td><td>Indicates Value type.</td></tr>
<tr><td>Attributes</td><td>
<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table>
</td></tr>
<tr><td>Restrictions</td><td>
<table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>maxLength</td><td>2</td></tr>
<tr><td>minLength</td><td>0</td></tr>
</table>
</td></tr>
</table>

TOP

2.35.2.ST-AuthNoticePRD-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Notice-Period-IO*
    - *NOTICEID*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Notice Period Maintenance.

TOP

NOTICEID

Attribute	Description	
Name	NOTICEID	
Datatype	String	
Description	Indicates Notice Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

2.35.3.ST-AuthNoticePRD-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Notice-Period-IO*
      - *NOTICEID*
      - *MODNO*
    - *Notice-Period-Full*
      - *BRANCHCODE*
      - *CUSTACNO*
      - *INITIATIONDATE*
      - *ACTIVATIONDATE*
      - *VALIDITYPERIOD*
      - *ENDDATE*
      - *NOTICEAMT*
      - *NOTICEID*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Notice Period Maintenance.

TOP

NOTICEID

Attribute	Description	
Name	NOTICEID	
Datatype	String	
Description	Indicates Notice Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Notice-Period-Full

Attribute	Description
Name	Notice-Period-Full
Datatype	
Description	It indicates Full Details of the Notice Period Maintenance.

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicates Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INITIATIONDATE

Attribute	Description	
Name	INITIATIONDATE	
Datatype	Date	
Description	Indicates Initiation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACTIVATIONDATE

Attribute	Description	
Name	ACTIVATIONDATE	
Datatype	Date	
Description	Indicates Activation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALIDITYPERIOD

Attribute	Description
Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE
Datatype	Date
Description	Indicates End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Notice-Period-PK*
      - *NOTICEID*
    - *Notice-Period-IO*
      - *NOTICEID*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Notice-Period-PK

Attribute	Description
Name	Notice-Period-PK
Datatype	
Description	It indicates the PK Details of the Notice Period Maintenance.

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Notice Period Maintenance.

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.36.CreateCustTrfr

CreateCustTrfr

2.36.1.ST-CreateCustTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cust-Brn-Transfer-Full

Attribute	Description
Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description	
Name	TRANSFER_MORTGAGES_MODULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFER_CASA

Attribute	Description	
Name	TRANSFER_CASA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	**Description**
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	**Description**
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	**Description**
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	**Description**
Name	CURRENT_BRANCH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.36.2.ST-CreateCustTrfr-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cust-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Cust-Brn-Transfer-IO*
      - *TRANSFER_MORTGAGES_MODULE*
      - *TRANSFER_CASA*
      - *CURRENT_BRANCH_CODE*
      - *TARGET_BRANCH_CODESS*
      - *TRANSFER_DATE*
      - *TRANSFER_ID*
      - *TRANSFER_LENDING_MODULE*
      - *TRANSFER_ISLAMIC_FINANCING_MODULE*
      - *CUSTOMER_ID*
      - *TRANSFER_TERM_DEPOSITS*
      - *TXT_CUSTNAME*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Cust-Brn-Transfer-PK

Attribute	Description
Name	Cust-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description	
Name	TRANSFER_MORTGAGES_MODULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFER_CASA

Attribute	Description	
Name	TRANSFER_CASA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

2.36.3.ST-CreateCustTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cust-Brn-Transfer-Full

Attribute	Description

Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description
Name	TRANSFER_MORTGAGES_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_CASA

Attribute	Description
Name	TRANSFER_CASA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	**Description**
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	**Description**
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	**Description**
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	**Description**
Name	TXT_CUSTNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-IO*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TXT_CUSTNAME*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description
Name	TRANSFER_MORTGAGES_MODULE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFER_CASA

Attribute	**Description**
Name	TRANSFER_CASA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	**Description**
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	**Description**
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRANSFER_DATE

Attribute	**Description**
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

2.37.CreateExtDeal

Create External Deal

2.37.1.ST-CreateExtDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ext-Deal-Link-Full*
    - *DL_BOOK_DT1*
    - *DL_EXP_DT1*
    - *ACCCCY*
    - *EQ_AMT1*
    - *ACCOUNT_NUMBER*
    - *FCREFERENCE*
    - *EXTDLREF1*
    - *REKEYOFDEALAMOUNT*
    - *EXCHANGERATE*
    - *REKEYOFDEALCURRENCY*
    - *PRDREMRKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Ext-Deal-Link-Full

Attribute	Description

Name	Ext-Deal-Link-Full
Datatype	
Description	

TOP

DL_BOOK_DT1

Attribute	Description
Name	DL_BOOK_DT1
Datatype	Date
Description	Indicates the Deal Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DL_EXP_DT1

Attribute	Description
Name	DL_EXP_DT1
Datatype	Date
Description	Indicates the Deal Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates the Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EQ_AMT1

Attribute	Description
Name	EQ_AMT1
Datatype	Number
Description	Indicates the Equivalent Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	Indicates the Account Number

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTDLREF1

Attribute	Description
Name	EXTDLREF1
Datatype	String
Description	Indicates the External Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REKEYOFDEALAMOUNT

Attribute	Description
Name	REKEYOFDEALAMOUNT
Datatype	Number
Description	Indicates the Deal Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	Indicates the Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REKEYOFDEALCURRENCY

Attribute	Description
Name	REKEYOFDEALCURRENCY
Datatype	String
Description	Indicates the Deal Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PRDREMRKS

Attribute	Description
Name	PRDREMRKS
Datatype	String
Description	Indicates the Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker Identification
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	Indicates the Checker Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number i.e. the number of times the record has been modified
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	Indicates the Record Status Open :O Closed :C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status Authorized :A UnAuthorized :U
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Ext-Deal-Link-IO
DL_BOOK_DT1
DL_EXP_DT1
ACCOUNT_NUMBER
FCREFERENCE
EXTDLREF1
REKEYOFDEALAMOUNT
EXCHANGERATE
REKEYOFDEALCURRENCY
PRDREMRKS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ext-Deal-Link-IO

Attribute	Description
Name	Ext-Deal-Link-IO
Datatype	
Description	

TOP

DL_BOOK_DT1

Attribute	Description
Name	DL_BOOK_DT1
Datatype	Date
Description	Indicates the Deal Booking Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DL_EXP_DT1

Attribute	Description
Name	DL_EXP_DT1
Datatype	Date
Description	Indicates the Deal Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	Indicates the Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTDLREF1

Attribute	Description
Name	EXTDLREF1
Datatype	String
Description	Indicates the External Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REKEYOFDEALAMOUNT

Attribute	Description
Name	REKEYOFDEALAMOUNT

Datatype	Number
Description	Indicates the External Deal Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number
Description	Indicates the Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYOFDEALCURRENCY

Attribute	Description
Name	REKEYOFDEALCURRENCY
Datatype	String
Description	Indicates the Deal Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDREMRKS

Attribute	Description
Name	PRDREMRKS
Datatype	String
Description	Indicates the Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.37.3.ST-CreateExtDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ext-Deal-Link-Full*
    - *DL_BOOK_DT1*
    - *DL_EXP_DT1*
    - *ACCCCY*
    - *EQ_AMT1*
    - *ACCOUNT_NUMBER*
    - *FCREFERENCE*
    - *EXTDLREF1*
    - *REKEYOFDEALAMOUNT*
    - *EXCHANGERATE*
    - *REKEYOFDEALCURRENCY*
    - *PRDREMRKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Ext-Deal-Link-Full

Attribute	Description
Name	Ext-Deal-Link-Full
Datatype	
Description	

TOP

DL_BOOK_DT1

Attribute	Description	
Name	DL_BOOK_DT1	
Datatype	Date	
Description	Indicates the Deal Booking Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DL_EXP_DT1

Attribute	Description	
Name	DL_EXP_DT1	
Datatype	Date	
Description	Indicates the Deal Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates the Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EQ_AMT1

Attribute	Description	
Name	EQ_AMT1	
Datatype	Number	
Description	Indicates the Equivalent Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	Indicates the Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTDLREF1

Attribute	Description
Name	EXTDLREF1
Datatype	String
Description	Indicates the External Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REKEYOFDEALAMOUNT

Attribute	Description
Name	REKEYOFDEALAMOUNT
Datatype	Number
Description	Indicates the Deal Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE
Datatype	Number

Description	Indicates the Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYOFDEALCURRENCY

Attribute	Description
Name	REKEYOFDEALCURRENCY
Datatype	String
Description	Indicates the Deal Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDREMRKS

Attribute	Description
Name	PRDREMRKS
Datatype	String
Description	Indicates the Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number i.e. the number of times the record has been modified
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Record Status Open :O Closed :C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status Authorized :A UnAuthorized :U
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

2.37.4.ST-CreateExtDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ext-Deal-Link-PK*
      - *FCREFERENCE*
    - *Ext-Deal-Link-IO*
      - *DL_BOOK_DT1*
      - *DL_EXP_DT1*
      - *ACCOUNT_NUMBER*
      - *FCREFERENCE*
      - *EXTDLREF1*
      - *REKEYOFDEALAMOUNT*
      - *EXCHANGERATE*
      - *REKEYOFDEALCURRENCY*
      - *PRDREMRKS*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Ext-Deal-Link-PK

Attribute	Description
Name	Ext-Deal-Link-PK
Datatype	
Description	

TOP

FCREFERENCE

Attribute	Description	
Name	FCREFERENCE	
Datatype	String	
Description	Indicates the Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Ext-Deal-Link-IO

Attribute	Description
Name	Ext-Deal-Link-IO
Datatype	
Description	

TOP

DL_BOOK_DT1

Attribute	Description	
Name	DL_BOOK_DT1	
Datatype	Date	
Description	Indicates the Deal Booking Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DL_EXP_DT1

Attribute	Description	
Name	DL_EXP_DT1	
Datatype	Date	
Description	Indicates the Deal Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	Indicates the Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTDLREF1

Attribute	Description
Name	EXTDLREF1
Datatype	String
Description	Indicates the External Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REKEYOFDEALAMOUNT

Attribute	Description
Name	REKEYOFDEALAMOUNT
Datatype	Number
Description	Indicates the External Deal Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXCHANGERATE

Attribute	Description
Name	EXCHANGERATE

Datatype	Number
Description	Indicates the Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYOFDEALCURRENCY

Attribute	**Description**
Name	REKEYOFDEALCURRENCY
Datatype	String
Description	Indicates the Deal Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDREMRKS

Attribute	**Description**
Name	PRDREMRKS
Datatype	String
Description	Indicates the Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.38.CreateLocMaint

Input of Location Maintenance

2.38.1.ST-CreateLocMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Location-Full*
    - *LOCCODE*
    - *DESCRIPTION*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Creation Full type details

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the document Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the document description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the authorisation Status.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Location-IO*
    - *LOCCODE*
    - *DESCRIPTION*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Creation Input Only type details

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the Location Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates th Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.38.3.ST-CreateLocMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Location-IO*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Sttm-Location-Full*

LOCCODE

DESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Creation Input Only type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the Location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates th Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Creation Full type details

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the Location Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates th Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.38.4.ST-CreateLocMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Location-PK*
      - *LOCCODE*
    - *Sttm-Location-IO*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*

VAL_TYPE
Sttm-Location-Full
LOCCODE
DESCRIPTION
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Location-PK

Attribute	Description
Name	Sttm-Location-PK
Datatype	
Description	Includes Location Maintenance Creation Primary Key type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Creation Input Only type details

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the location Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates th Record Status.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME

Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Creation Full type details

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the location Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates th Record Status.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.39.CreateManStatChangInp

Input of Manual Status Change

2.39.1.ST-CreateManStatChangInp-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Ac-Stat-Change-Full*
    - *CUSTACNO*
    - *ACCSTATUS*
    - *BRANCHCODE*
    - *BRANCHNAME*
    - *STATUSCHANGEDATE*
    - *SEQNO*
    - *STATUS*
    - *ACSTATNODR*
    - *ACSTATNOCR*
    - *ACSTATFROZEN*
    - *ACSTATDEPOST*
    - *ACSTATCHGAUTO*
    - *DORMANT*
    - *MAKERID*
    - *MAKERDTSTAMP*

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Creation Full type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCSTATUS

Attribute	Description	
Name	ACCSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATNOCR

Attribute	Description
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	N,Y

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,Y

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

2.39.2.ST-CreateManStatChangInp-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Ac-Stat-Change-IO*
    - *CUSTACNO*
    - *BRANCHCODE*
    - *STATUSCHANGEDATE*
    - *SEQNO*
    - *STATUS*
    - *ACSTATNODR*
    - *ACSTATNOCR*
    - *ACSTATFROZEN*
    - *ACSTATDEPOST*
    - *ACSTATCHGAUTO*
    - *DORMANT*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*

ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Creation Input Only type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STATUSCHANGEDATE

Attribute	Description	
Name	STATUSCHANGEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SEQNO

Attribute	Description	
Name	SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATNOCR

Attribute	Description
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.39.3.ST-CreateManStatChangInp-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Ac-Stat-Change-IO*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *STATUS*
      - *ACSTATNODR*
      - *ACSTATNOCR*
      - *ACSTATFROZEN*
      - *ACSTATDEPOST*
      - *ACSTATCHGAUTO*
      - *DORMANT*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sttm-Ac-Stat-Change-Full
CUSTACNO
ACCSTATUS
BRANCHCODE
BRANCHNAME
STATUSCHANGEDATE
SEQNO
STATUS
ACSTATNODR
ACSTATNOCR
ACSTATFROZEN
ACSTATDEPOST
ACSTATCHGAUTO
DORMANT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Creation Input Only type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STATUSCHANGEDATE

Attribute	Description	
Name	STATUSCHANGEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SEQNO

Attribute	Description	
Name	SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATNOCR

Attribute	Description
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Creation Full type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCSTATUS

Attribute	Description
Name	ACCSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATNOCR

Attribute	Description
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.39.4.ST-CreateManStatChangInp-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Ac-Stat-Change-PK*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
    - *Sttm-Ac-Stat-Change-IO*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *STATUS*
      - *ACSTATNODR*
      - *ACSTATNOCR*
      - *ACSTATFROZEN*
      - *ACSTATDEPOST*
      - *ACSTATCHGAUTO*
      - *DORMANT*
      - *MAKERID*

MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sttm-Ac-Stat-Change-Full
CUSTACNO
ACCSTATUS
BRANCHCODE
BRANCHNAME
STATUSCHANGEDATE
SEQNO
STATUS
ACSTATNODR
ACSTATNOCR
ACSTATFROZEN
ACSTATDEPOST
ACSTATCHGAUTO
DORMANT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-PK

Attribute	Description
Name	Sttm-Ac-Stat-Change-PK
Datatype	
Description	Includes Manual Status Change Input Creation Primary Key type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Creation Input Only type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

STATUS

Attribute	Description

Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	**Description**
Name	ACSTATNODR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATNOCR

Attribute	**Description**
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATFROZEN

Attribute	**Description**
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACSTATDEPOST

Attribute	**Description**
Name	ACSTATDEPOST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME

Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Creation Full type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACCSTATUS

Attribute	Description
Name	ACCSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACSTATNODR

Attribute	Description	
Name	ACSTATNODR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATNOCR

Attribute	Description	
Name	ACSTATNOCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.40.CreateManStatChange

CreateManStatChange

2.40.1.ST-CreateManStatChange-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-Full*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *NEWSTAT*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *BRNNAME*
    - *FROM_STATUS*
    - *NO_DR*
    - *ACSTATNCR*

ACSTATFRZN

ACSTATDEPST

STATCHNGAUTMATIC

DORM

AC_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Ac-Stat-Change-Full

Attribute	Description
Name	Sttms-Ac-Stat-Change-Full
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description	
Name	SINCE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWSTAT

Attribute	Description
Name	NEWSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_DE_POST

Attribute	Description	
Name	AC_STAT_DE_POST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description	
Name	AC_STAT_CHG_AUTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

FROM_STATUS

Attribute	Description
Name	FROM_STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATNCR

Attribute	Description
Name	ACSTATNCR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATFRZN

Attribute	Description
Name	ACSTATFRZN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM

Attribute	Description
Name	DORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-IO*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *NEWSTAT*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *FROM_STATUS*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description	
Name	SINCE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SEQ_NO

Attribute	Description	
Name	SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEWSTAT

Attribute	Description	
Name	NEWSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACSTATNDR1

Attribute	Description

Name	ACSTATNDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_DE_POST

Attribute	Description
Name	AC_STAT_DE_POST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description
Name	AC_STAT_CHG_AUTO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROM_STATUS

Attribute	Description
Name	FROM_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

2.40.3.ST-CreateManStatChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-Full*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *NEWSTAT*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *BRNNAME*
    - *FROM_STATUS*
    - *NO_DR*
    - *ACSTATNCR*
    - *ACSTATFRZN*
    - *ACSTATDEPST*
    - *STATCHNGAUTMATIC*

DORM

AC_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Ac-Stat-Change-Full

Attribute	Description
Name	Sttms-Ac-Stat-Change-Full
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	1

TOP

SEQ_NO

Attribute	Description	
Name	SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEWSTAT

Attribute	Description	
Name	NEWSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACSTATNDR1

Attribute	Description	
Name	ACSTATNDR1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_NO_CR

Attribute	Description	
Name	AC_STAT_NO_CR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_DE_POST

Attribute	Description
Name	AC_STAT_DE_POST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description
Name	AC_STAT_CHG_AUTO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FROM_STATUS

Attribute	**Description**
Name	FROM_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NO_DR

Attribute	**Description**
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACSTATNCR

Attribute	**Description**
Name	ACSTATNCR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACSTATFRZN

Attribute	**Description**
Name	ACSTATFRZN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM

Attribute	Description
Name	DORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.40.4.ST-CreateManStatChange-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Ac-Stat-Change-PK*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
    - *Sttms-Ac-Stat-Change-IO*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
      - *NEWSTAT*
      - *ACSTATNDR1*
      - *AC_STAT_NO_CR*
      - *AC_STAT_FROZEN*
      - *AC_STAT_DE_POST*
      - *AC_STAT_CHG_AUTO*
      - *DORMANT*
      - *FROM_STATUS*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Ac-Stat-Change-PK

Attribute	Description
Name	Sttms-Ac-Stat-Change-PK
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO

Datatype	Number
Description	

TOP

NEWSTAT

Attribute	Description
Name	NEWSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_DE_POST

Attribute	Description
Name	AC_STAT_DE_POST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description
Name	AC_STAT_CHG_AUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROM_STATUS

Attribute	Description
Name	FROM_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.41.CreateNoticePRD

Input of Notice Period Maintenance

2.41.1.ST-CreateNoticePRD-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Notice-Period-Full*
    - *BRANCHCODE*
    - *CUSTACNO*
    - *INITIATIONDATE*
    - *ACTIVATIONDATE*
    - *VALIDITYPERIOD*
    - *ENDDATE*
    - *NOTICEAMT*
    - *NOTICEID*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Notice-Period-Full

Attribute	Description
Name	Notice-Period-Full
Datatype	
Description	It indicates Full Details of the Notice Period Maintenance.

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicates Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INITIATIONDATE

Attribute	Description	
Name	INITIATIONDATE	
Datatype	Date	
Description	Indicates Initiation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACTIVATIONDATE

Attribute	Description	
Name	ACTIVATIONDATE	
Datatype	Date	
Description	Indicates Activation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALIDITYPERIOD

Attribute	Description
Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE
Datatype	Date
Description	Indicates End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>Name</td><td>VAL_TYPE</td></tr>
<tr><td>Datatype</td><td>String</td></tr>
<tr><td>Description</td><td>Indicates Value type.</td></tr>
<tr><td>Attributes</td><td>
<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table>
</td></tr>
<tr><td>Restrictions</td><td>
<table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>maxLength</td><td>2</td></tr>
<tr><td>minLength</td><td>0</td></tr>
</table>
</td></tr>
</table>

TOP

2.41.2.ST-CreateNoticePRD-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Notice-Period-IO*
    - *BRANCHCODE*
    - *CUSTACNO*
    - *INITIATIONDATE*
    - *ACTIVATIONDATE*
    - *VALIDITYPERIOD*
    - *ENDDATE*
    - *NOTICEAMT*
    - *NOTICEID*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Notice-Period-IO

Attribute	Description

Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Notice Period Maintenance.

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INITIATIONDATE

Attribute	Description
Name	INITIATIONDATE
Datatype	Date
Description	Indicate Initiation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTIVATIONDATE

Attribute	Description
Name	ACTIVATIONDATE
Datatype	Date
Description	Indicates Activation date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALIDITYPERIOD

Attribute	Description

Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE
Datatype	Date
Description	Indicates End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

TOP

2.41.3.ST-CreateNoticePRD-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Notice-Period-IO*
      - *BRANCHCODE*
      - *CUSTACNO*
      - *INITIATIONDATE*
      - *ACTIVATIONDATE*
      - *VALIDITYPERIOD*
      - *ENDDATE*
      - *NOTICEAMT*
      - *NOTICEID*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Notice-Period-Full
BRANCHCODE
CUSTACNO
INITIATIONDATE
ACTIVATIONDATE
VALIDITYPERIOD
ENDDATE
NOTICEAMT
NOTICEID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Notice Period Maintenance.

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INITIATIONDATE

Attribute	Description
Name	INITIATIONDATE
Datatype	Date
Description	Indicate Initiation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATIONDATE

Attribute	Description
Name	ACTIVATIONDATE
Datatype	Date
Description	Indicates Activation date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALIDITYPERIOD

Attribute	Description
Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period

Attributes	Attribute	Description
	minOccurs	0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE
Datatype	Date
Description	Indicates End Date
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

Notice-Period-Full

Attribute	Description
Name	Notice-Period-Full
Datatype	
Description	It indicates Full Details of the Notice Period Maintenance.

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicates Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INITIATIONDATE

Attribute	Description	
Name	INITIATIONDATE	
Datatype	Date	
Description	Indicate Initiation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACTIVATIONDATE

Attribute	Description	
Name	ACTIVATIONDATE	
Datatype	Date	
Description	Indicates Activation date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALIDITYPERIOD

Attribute	Description
Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE
Datatype	Date
Description	Indicates End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 2 Restrictions: minLength, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.41.4.ST-CreateNoticePRD-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Notice-Period-PK*
      - *NOTICEID*
    - *Notice-Period-IO*
      - *BRANCHCODE*
      - *CUSTACNO*
      - *INITIATIONDATE*
      - *ACTIVATIONDATE*
      - *VALIDITYPERIOD*
      - *ENDDATE*
      - *NOTICEAMT*
      - *NOTICEID*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Notice-Period-PK

Attribute	Description
Name	Notice-Period-PK
Datatype	
Description	It indicates the PK Details of the Notice Period

TOP

NOTICEID

Attribute	Description	
Name	NOTICEID	
Datatype	String	
Description	Indicates Notice Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Notice Period

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Indicates Branch Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INITIATIONDATE

Attribute	Description
Name	INITIATIONDATE
Datatype	Date
Description	Indicate Initiation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATIONDATE

Attribute	Description
Name	ACTIVATIONDATE
Datatype	Date
Description	Indicates Activation date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALIDITYPERIOD

Attribute	Description
Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE

Datatype	Date
Description	Indicates End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.42.CreateOnlineCharge

CreateOnlineCharge

2.42.1.ST-CreateOnlineCharge-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Onlinecharge-Master-Full

Attribute	Description
Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHARGE_EVENT

Attribute	Description
Name	CHARGE_EVENT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	**Description**
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Onlinecharge-Master-IO
SOURCE
Onlinecharge-Detail
CHARGE_EVENT
CHARGE_PRODUCT
ACTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CHARGE_EVENT

Attribute	Description
Name	CHARGE_EVENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 8

TOP

CHARGE_PRODUCT

Attribute	Description
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

2.42.3.ST-CreateOnlineCharge-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Onlinecharge-Master-Full

Attribute	Description

Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHARGE_EVENT

Attribute	**Description**	
Name	CHARGE_EVENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CHARGE_PRODUCT

Attribute	**Description**	
Name	CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
Onlinecharge-Master-PK
SOURCE
Onlinecharge-Master-IO
SOURCE
Onlinecharge-Detail
CHARGE_EVENT
CHARGE_PRODUCT
ACTION
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Onlinecharge-Master-PK

Attribute	Description
Name	Onlinecharge-Master-PK
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

Onlinecharge-Detail

Attribute	Description	
Name	Onlinecharge-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHARGE_EVENT

Attribute	Description
Name	CHARGE_EVENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CHARGE_PRODUCT

Attribute	Description
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.43.CreateSTDSTCDM

CreateSTDSTCDM

2.43.1.ST-CreateSTDSTCDM-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Crdrstat-Full

Attribute	Description
Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description	
Name	CUST_AC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NODEBIT

Attribute	Description	
Name	NODEBIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOCREDIT

Attribute	Description	
Name	NOCREDIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Crdrstat-IO
BRANCH_CODE
CUST_AC
NODEBIT
NOCREDIT
POSTALLOWED
REMARKS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NODEBIT

Attribute	Description
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCREDIT

Attribute	Description
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String

<table>
<tr><td>Description</td><td>Indicates Remarks</td></tr>
<tr><td>Attributes</td><td><table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table></td></tr>
<tr><td>Restrictions</td><td><table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>maxLength</td><td>255</td></tr>
</table></td></tr>
</table>

TOP

2.43.3.ST-CreateSTDSTCDM-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Crdrstat-Full

Attribute	Description

Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NODEBIT

Attribute	Description
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOCREDIT

Attribute	Description
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

2.43.4.ST-CreateSTDSTCDM-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Crdrstat-PK*
      - *BRANCH_CODE*
      - *CUST_AC*
    - *Crdrstat-IO*
      - *BRANCH_CODE*
      - *CUST_AC*
      - *NODEBIT*
      - *NOCREDIT*
      - *POSTALLOWED*
      - *REMARKS*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Crdrstat-PK

Attribute	Description
Name	Crdrstat-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description	
Name	CUST_AC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NODEBIT

Attribute	Description
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCREDIT

Attribute	Description
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.44.CreateSTDSTDOR

CreateSTDSTDOR

2.44.1.ST-CreateSTDSTDOR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Status-Full

Attribute	Description

Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NO_DR

Attribute	Description	
Name	NO_DR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NO_CR

Attribute	Description	
Name	NO_CR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROZEN

Attribute	Description	
Name	FROZEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-IO*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description

Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	**Description**
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	**Description**
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

2.44.3.ST-CreateSTDSTDOR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Status-Full

Attribute	Description
Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Status-PK*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
    - *Status-IO*
      - *REVERSE_MOVEMENT_PARAM*
      - *REMARKS*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
      - *NO_DR*
      - *NO_CR*
      - *FROZEN*
      - *DORMANT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Status-PK

Attribute	Description
Name	Status-PK
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AC_NO

Attribute	Description	
Name	AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description	
Name	REVERSE_MOVEMENT_PARAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.45.CreateSTTypeMnt

Input of Card Type Maintenance

2.45.1.ST-CreateSTTypeMnt-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *St-Debit-Card-Type-Full*
    - *CARDTYPE*
    - *DESCRIPTION*
    - *CARDBIN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *St-Debit-Card-Type-Detail*
      - *CARDTYPE*
      - *CARDBIN1*
    - *UDFDETAILS*

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

St-Debit-Card-Type-Full

Attribute	Description

Name	St-Debit-Card-Type-Full
Datatype	
Description	Include full details about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Cardtype
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CARDBIN

Attribute	Description
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Cardtype
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME

Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.45.2.ST-CreateSTTypeMnt-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *St-Debit-Card-Type-IO*
    - *CARDTYPE*
    - *DESCRIPTION*
    - *CARDBIN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *St-Debit-Card-Type-Detail*
      - *CARDTYPE*
      - *CARDBIN1*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

St-Debit-Card-Type-IO

Attribute	Description

Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CARDBIN

Attribute	Description
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME

Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.45.3.ST-CreateSTTypeMnt-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *St-Debit-Card-Type-IO*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *CARDBIN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *St-Debit-Card-Type-Detail*
        - *CARDTYPE*
        - *CARDBIN1*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*

DATATYPE

FIELD_VALUE

VAL_TYPE

St-Debit-Card-Type-Full

CARDTYPE

DESCRIPTION

CARDBIN

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

St-Debit-Card-Type-Detail

CARDTYPE

CARDBIN1

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CARDBIN

Attribute	**Description**
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CARDBIN1

Attribute	Description

Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

St-Debit-Card-Type-Full

Attribute	Description
Name	St-Debit-Card-Type-Full
Datatype	
Description	Include full details about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CARDBIN

Attribute	Description
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Card Bin 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 8
	pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.45.4.ST-CreateSTTypeMnt-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *St-Debit-Card-Type-PK*
      - *CARDTYPE*
    - *St-Debit-Card-Type-IO*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *CARDBIN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *St-Debit-Card-Type-Detail*
        - *CARDTYPE*
        - *CARDBIN1*
      - *UDFDETAILS*

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
St-Debit-Card-Type-Full
CARDTYPE
DESCRIPTION
CARDBIN
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
St-Debit-Card-Type-Detail
CARDTYPE
CARDBIN1
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

St-Debit-Card-Type-PK

Attribute	Description
Name	St-Debit-Card-Type-PK
Datatype	
Description	Includes primary detials about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

St-Debit-Card-Type-IO

Attribute	**Description**
Name	St-Debit-Card-Type-IO
Datatype	
Description	Includes information about debit card type.

TOP

CARDTYPE

Attribute	**Description**	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CARDBIN

Attribute	**Description**	
Name	CARDBIN	
Datatype	String	
Description	Indicates Card Bin	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail

Datatype	
Description	Debit Card Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	**Description**
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CARDBIN1

Attribute	**Description**
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

St-Debit-Card-Type-Full

Attribute	Description
Name	St-Debit-Card-Type-Full
Datatype	
Description	Includes full detials about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CARDBIN

Attribute	Description	
Name	CARDBIN	
Datatype	String	
Description	Indicates Card Bin	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.46.CreateServiceRequest

2.46.1.ST-CreateServiceRequest-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Service-Request-Details-Full*
    - *SUBJECT*
    - *ACTDATE*
    - *PRIORITY*
    - *STATUS*
    - *REQUESTER_TYPE*
    - *NATURE*
    - *CRITERIA*
    - *SNAME*
    - *TEL*
    - *EMAIL*
    - *MOBILE_NUMBER*
    - *FNAME*
    - *SERVICE_NUM*
    - *CUST_AC_NO*
    - *CUSTOMER_NO*
    - *SERV_REQ_TYPE*

BRANCH_CODE

CONTACT_DATE

TARGET_DATE

DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Service-Request-Details-Full

Attribute	Description
Name	Service-Request-Details-Full
Datatype	
Description	

TOP

SUBJECT

Attribute	Description	
Name	SUBJECT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACTDATE

Attribute	Description	
Name	ACTDATE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	String	
Description	Indicates Priority High : 1 Normal : 2 Low : 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	High,Medium,Low

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,P,C,X

TOP

REQUESTER_TYPE

Attribute	Description
Name	REQUESTER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,W

TOP

NATURE

Attribute	Description
Name	NATURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Sales,Service

TOP

CRITERIA

Attribute	Description
Name	CRITERIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Enquiry,Channel,Product,Application ,Maintenance

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates the Short Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	This gives the Customer email address
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MOBILE_NUMBER

Attribute	Description
Name	MOBILE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FNAME

Attribute	Description
Name	FNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SERVICE_NUM

Attribute	**Description**
Name	SERVICE_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTOMER_NO

Attribute	**Description**
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SERV_REQ_TYPE

Attribute	**Description**
Name	SERV_REQ_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / TXN,NTX,CMP

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONTACT_DATE

Attribute	**Description**
Name	CONTACT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TARGET_DATE

Attribute	**Description**
Name	TARGET_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER

Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number

Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Service-Request-Details-IO*
    - *SUBJECT*
    - *ACTDATE*
    - *PRIORITY*
    - *STATUS*
    - *REQUESTER_TYPE*
    - *NATURE*
    - *CRITERIA*
    - *SERVICE_NUM*
    - *CUST_AC_NO*
    - *CUSTOMER_NO*
    - *SERV_REQ_TYPE*
    - *CONTACT_DATE*
    - *TARGET_DATE*
    - *DESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Service-Request-Details-IO

Attribute	Description
Name	Service-Request-Details-IO
Datatype	
Description	

TOP

SUBJECT

Attribute	Description
Name	SUBJECT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / High,Medium,Low

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,P,C,X

TOP

REQUESTER_TYPE

Attribute	Description
Name	REQUESTER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	C,W

TOP

NATURE

Attribute	Description	
Name	NATURE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,Sales,Service

TOP

CRITERIA

Attribute	Description	
Name	CRITERIA	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,Enquiry,Channel,Product,Application ,Maintenance

TOP

SERVICE_NUM

Attribute	Description	
Name	SERVICE_NUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description	Indicates the Customer Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SERV_REQ_TYPE

Attribute	Description
Name	SERV_REQ_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / TXN,NTX,CMP

TOP

CONTACT_DATE

Attribute	Description
Name	CONTACT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TARGET_DATE

Attribute	Description
Name	TARGET_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.46.3.ST-CreateServiceRequest-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Service-Request-Details-Full*
    - *SUBJECT*
    - *ACTDATE*
    - *PRIORITY*
    - *STATUS*
    - *REQUESTER_TYPE*
    - *NATURE*
    - *CRITERIA*
    - *SNAME*
    - *TEL*
    - *EMAIL*
    - *MOBILE_NUMBER*
    - *FNAME*
    - *SERVICE_NUM*
    - *CUST_AC_NO*
    - *CUSTOMER_NO*
    - *SERV_REQ_TYPE*
    - *BRANCH_CODE*
    - *CONTACT_DATE*

TARGET_DATE
DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Service-Request-Details-Full

Attribute	Description
Name	Service-Request-Details-Full
Datatype	
Description	

TOP

SUBJECT

Attribute	Description	
Name	SUBJECT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACTDATE

Attribute	Description	
Name	ACTDATE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority High : 1 Normal : 2 Low : 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	High,Medium,Low

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,P,C,X

TOP

REQUESTER_TYPE

Attribute	Description
Name	REQUESTER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,W

TOP

NATURE

Attribute	Description
Name	NATURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Sales,Service

TOP

CRITERIA

Attribute	Description
Name	CRITERIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,Enquiry,Channel,Product,Application ,Maintenance

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates the Short Name.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	This gives the Customer email address
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MOBILE_NUMBER

Attribute	Description
Name	MOBILE_NUMBER
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FNAME

Attribute	Description
Name	FNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SERVICE_NUM

Attribute	Description
Name	SERVICE_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SERV_REQ_TYPE

Attribute	Description

Name	SERV_REQ_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / TXN,NTX,CMP

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONTACT_DATE

Attribute	**Description**
Name	CONTACT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TARGET_DATE

Attribute	**Description**
Name	TARGET_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR

Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.46.4.ST-CreateServiceRequest-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Service-Request-Details-PK*
      - *SERVICE_NUM*
    - *Service-Request-Details-IO*
      - *SUBJECT*
      - *ACTDATE*
      - *PRIORITY*
      - *STATUS*
      - *REQUESTER_TYPE*
      - *NATURE*
      - *CRITERIA*
      - *SERVICE_NUM*
      - *CUST_AC_NO*
      - *CUSTOMER_NO*
      - *SERV_REQ_TYPE*
      - *CONTACT_DATE*
      - *TARGET_DATE*
      - *DESC*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Service-Request-Details-PK

Attribute	Description
Name	Service-Request-Details-PK
Datatype	
Description	

TOP

SERVICE_NUM

Attribute	Description	
Name	SERVICE_NUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Service-Request-Details-IO

Attribute	Description
Name	Service-Request-Details-IO
Datatype	
Description	

TOP

SUBJECT

Attribute	Description	
Name	SUBJECT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACTDATE

Attribute	Description
Name	ACTDATE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	String
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / High,Medium,Low

TOP

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,P,C,X

TOP

REQUESTER_TYPE

Attribute	**Description**
Name	REQUESTER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W

TOP

NATURE

Attribute	**Description**
Name	NATURE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Sales,Service

TOP

CRITERIA

Attribute	Description	
Name	CRITERIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Enquiry,Channel,Product,Application ,Maintenance

TOP

SERVICE_NUM

Attribute	Description	
Name	SERVICE_NUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description	Indicates the Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SERV_REQ_TYPE

Attribute	**Description**
Name	SERV_REQ_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / TXN,NTX,CMP

TOP

CONTACT_DATE

Attribute	**Description**
Name	CONTACT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TARGET_DATE

Attribute	**Description**
Name	TARGET_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.47.AuthorizeManStatChange

AuthorizeManStatChange

2.47.1.ST-AuthorizeManStatChange-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-Full*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *NEWSTAT*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *BRNNAME*
    - *FROM_STATUS*
    - *NO_DR*
    - *ACSTATNCR*

ACSTATFRZN

ACSTATDEPST

STATCHNGAUTMATIC

DORM

AC_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Ac-Stat-Change-Full

Attribute	Description
Name	Sttms-Ac-Stat-Change-Full
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description	
Name	SINCE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWSTAT

Attribute	Description
Name	NEWSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_DE_POST

Attribute	Description	
Name	AC_STAT_DE_POST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description	
Name	AC_STAT_CHG_AUTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

FROM_STATUS

Attribute	Description
Name	FROM_STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATNCR

Attribute	Description
Name	ACSTATNCR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATFRZN

Attribute	Description
Name	ACSTATFRZN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM

Attribute	Description
Name	DORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Ac-Stat-Change-IO
CUST_AC_NO
BRANCH
SINCE
SEQ_NO
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.47.3.ST-AuthorizeManStatChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-Full*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *NEWSTAT*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *BRNNAME*
    - *FROM_STATUS*
    - *NO_DR*
    - *ACSTATNCR*
    - *ACSTATFRZN*
    - *ACSTATDEPST*
    - *STATCHNGAUTMATIC*

DORM

AC_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Ac-Stat-Change-Full

Attribute	Description
Name	Sttms-Ac-Stat-Change-Full
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWSTAT

Attribute	Description
Name	NEWSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_DE_POST

Attribute	Description
Name	AC_STAT_DE_POST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description
Name	AC_STAT_CHG_AUTO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FROM_STATUS

Attribute	**Description**
Name	FROM_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

NO_DR

Attribute	**Description**
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATNCR

Attribute	**Description**
Name	ACSTATNCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATFRZN

Attribute	**Description**
Name	ACSTATFRZN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM

Attribute	Description
Name	DORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.47.4.ST-AuthorizeManStatChange-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Ac-Stat-Change-PK*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
    - *Sttms-Ac-Stat-Change-IO*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttms-Ac-Stat-Change-PK

Attribute	Description
Name	Sttms-Ac-Stat-Change-PK
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.48.AuthorizeOnlineCharge

AuthorizeOnlineCharge

2.48.1.ST-AuthorizeOnlineCharge-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Onlinecharge-Master-Full

Attribute	Description
Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHARGE_EVENT

Attribute	Description
Name	CHARGE_EVENT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	**Description**
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Onlinecharge-Master-IO
SOURCE
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.48.3.ST-AuthorizeOnlineCharge-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Onlinecharge-Master-Full

Attribute	Description

Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHARGE_EVENT

Attribute	**Description**	
Name	CHARGE_EVENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CHARGE_PRODUCT

Attribute	**Description**	
Name	CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Onlinecharge-Master-PK*
      - *SOURCE*
    - *Onlinecharge-Master-IO*
      - *SOURCE*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Onlinecharge-Master-PK

Attribute	Description
Name	Onlinecharge-Master-PK
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.49.AuthorizeSTDSTCDM

AuthorizeSTDSTCDM

2.49.1.ST-AuthorizeSTDSTCDM-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Crdrstat-Full

Attribute	Description
Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUST_AC

Attribute	**Description**
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NODEBIT

Attribute	**Description**
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOCREDIT

Attribute	**Description**
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

POSTALLOWED

Attribute	**Description**
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

2.49.2.ST-AuthorizeSTDSTCDM-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-IO*
    - *BRANCH_CODE*
    - *CUST_AC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

2.49.3.ST-AuthorizeSTDSTCDM-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Crdrstat-Full

Attribute	Description

Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NODEBIT

Attribute	Description
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOCREDIT

Attribute	Description
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Crdrstat-PK*
      - *BRANCH_CODE*
      - *CUST_AC*
    - *Crdrstat-IO*
      - *BRANCH_CODE*
      - *CUST_AC*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Crdrstat-PK

Attribute	Description
Name	Crdrstat-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.50.AuthorizeSTDSTDOR

AuthorizeSTDSTDOR

2.50.1.ST-AuthorizeSTDSTDOR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Status-Full

Attribute	Description

Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Status-IO
ACCOUNT_BRANCH
AC_NO
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

AC_NO

Attribute	Description
Name	AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.50.3.ST-AuthorizeSTDSTDOR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Status-Full

Attribute	Description
Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Status-PK*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
    - *Status-IO*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Status-PK

Attribute	Description
Name	Status-PK
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.51.CloseACRSMaint

CloseACRSMaint

2.51.1.ST-CloseACRSMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description

Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCD

Attribute	Description
Name	BRANCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREEQUENCY

Attribute	Description
Name	FREEQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,S,A

TOP

STARTMON

Attribute	Description
Name	STARTMON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LASTEXEDATE

Attribute	Description
Name	LASTEXEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	**Description**	
Name	CHARGEBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	**Description**	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

2.51.2.ST-CloseACRSMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-IO*
    - *REFERENCENO*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

2.51.3.ST-CloseACRSMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description
Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCD

Attribute	Description	
Name	BRANCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date

Attributes	Attribute	Description
	minOccurs	0

TOP

FREEQUENCY

Attribute	Description	
Name	FREEQUENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,S,A

TOP

STARTMON

Attribute	Description	
Name	STARTMON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description	
Name	STARTON	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

LASTEXEDATE

Attribute	Description	
Name	LASTEXEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

E-STATEMENT

Attribute	Description

Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Auto-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Auto-Crs-Master-IO*
      - *REFERENCENO*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Auto-Crs-Master-PK

Attribute	Description
Name	Sttm-Auto-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.52.DeleteCustCatMaint

Deletion of Customer Category Maintenance

2.52.1.ST-DeleteCustCatMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Customer-Cat-IO*
      - *CUSTCAT*
    - *Sttm-Customer-Cat-Full*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Deletion Input Only type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Customer-Cat-Full

Attribute	Description
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Deletion Full type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	16

TOP

CUSTCATDESC

Attribute	Description	
Name	CUSTCATDESC	
Datatype	String	
Description	Indicates the Customer Category Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

POPULATECHANGESLOG

Attribute	Description	
Name	POPULATECHANGESLOG	
Datatype	String	
Description	Indicates the populate Changes Log. Y - Yes, N - No.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,Y

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: Description
	minOccurs: 0
Restrictions	Restrictions: Description
	maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: Description
	minOccurs: 0
Restrictions	Restrictions: Description
	maxLength: 255
	minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: Description
	minOccurs: 0
Restrictions	Restrictions: Description
	maxLength: 2
	minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	Attribute: Description
	maxOccurs: unbounded
	minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.52.2.ST-DeleteCustCatMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Customer-Cat-IO*
      - *CUSTCAT*
    - *Sttm-Customer-Cat-PK*
      - *CUSTCAT*
    - *Sttm-Customer-Cat-Full*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Deletion Input Only type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Customer-Cat-PK

Attribute	Description
Name	Sttm-Customer-Cat-PK
Datatype	
Description	Includes Customer Category Maintenance Deletion Primary Key type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Customer-Cat-Full

Attribute	Description
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Deletion Full type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTCATDESC

Attribute	Description	
Name	CUSTCATDESC	
Datatype	String	
Description	Indicates the Customer Category Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POPULATECHANGESLOG

Attribute	Description	
Name	POPULATECHANGESLOG	
Datatype	String	
Description	Indicates the populate Changes Log. Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Customer-Cat-Full*
    - *CUSTCAT*
    - *CUSTCATDESC*
    - *POPULATECHANGESLOG*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Customer-Cat-Full

Attribute	Description
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Deletion Full type details

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the populate Changes Log. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Customer-Cat-IO
CUSTCAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Deletion Input Only type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.53.DeleteCustTrfr

DeleteCustTrfr

2.53.1.ST-DeleteCustTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cust-Brn-Transfer-Full

Attribute	Description

Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description
Name	TRANSFER_MORTGAGES_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_CASA

Attribute	Description
Name	TRANSFER_CASA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	**Description**
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	**Description**
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	**Description**
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	**Description**
Name	TXT_CUSTNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-IO*
    - *TRANSFER_ID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

2.53.3.ST-DeleteCustTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cust-Brn-Transfer-Full

Attribute	Description
Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description	
Name	TRANSFER_MORTGAGES_MODULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFER_CASA

Attribute	Description	
Name	TRANSFER_CASA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	Description
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	Description
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cust-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Cust-Brn-Transfer-IO*
      - *TRANSFER_ID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cust-Brn-Transfer-PK

Attribute	Description
Name	Cust-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.54.DeleteJointHolderMaint

Delete Joint Holder Maintenance

2.54.1.ST-DeleteJointHolderMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Acc-Joint-Full*
    - *ACCOUNT_BRANCH*
    - *ACCOUNT_NUMBER*
    - *CUST_NO*
    - *ACCTYPE*
    - *OPMODE*
    - *ACCOUNT_CURRENCY*
    - *AC_DESC*
    - *CUSTNAME1*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

Acc-Joint-Holder

CUSTOMER_NUMBER

CUSTOMER_NAME

JNTHLDTYP

START_DATE

END_DATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Acc-Joint-Full

Attribute	Description
Name	Acc-Joint-Full
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,J

TOP

OPMODE

Attribute	**Description**	
Name	OPMODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,J,E,F,M,

TOP

ACCOUNT_CURRENCY

Attribute	**Description**	
Name	ACCOUNT_CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

AC_DESC

Attribute	**Description**	
Name	AC_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTNAME1

Attribute	**Description**	
Name	CUSTNAME1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Acc-Joint-Holder

Attribute	Description
Name	Acc-Joint-Holder
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER_NUMBER

Attribute	Description
Name	CUSTOMER_NUMBER
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTOMER_NAME

Attribute	**Description**
Name	CUSTOMER_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

JNTHLDTYP

Attribute	**Description**
Name	JNTHLDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / AUS,CON,GUR,CUS,DEV,GUA,JAF,JAO,JOF,JOO,NOM,REL,SOL,SOW,THR,TRU,VAL,POA

TOP

START_DATE

Attribute	**Description**
Name	START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

END_DATE

Attribute	**Description**
Name	END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.54.2.ST-DeleteJointHolderMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Acc-Joint-IO*
    - *ACCOUNT_BRANCH*
    - *ACCOUNT_NUMBER*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Acc-Joint-IO

Attribute	Description
Name	Acc-Joint-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

2.54.3.ST-DeleteJointHolderMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Acc-Joint-Full*
    - *ACCOUNT_BRANCH*
    - *ACCOUNT_NUMBER*
    - *CUST_NO*
    - *ACCTYPE*
    - *OPMODE*
    - *ACCOUNT_CURRENCY*
    - *AC_DESC*
    - *CUSTNAME1*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Acc-Joint-Holder*
      - *CUSTOMER_NUMBER*
      - *CUSTOMER_NAME*

JNTHLDTYP

START_DATE

END_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Acc-Joint-Full

Attribute	Description
Name	Acc-Joint-Full
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCOUNT_NUMBER

Attribute	Description	
Name	ACCOUNT_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,J

TOP

OPMODE

Attribute	Description
Name	OPMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,J,E,F,M,

TOP

ACCOUNT_CURRENCY

Attribute	Description
Name	ACCOUNT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTNAME1

Attribute	Description

Name	CUSTNAME1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Acc-Joint-Holder

Attribute	Description
Name	Acc-Joint-Holder
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER_NUMBER

Attribute	Description
Name	CUSTOMER_NUMBER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTOMER_NAME

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

JNTHLDTYP

Attribute	Description
Name	JNTHLDTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: AUS,CON,GUR,CUS,DEV,GUA,JAF,JAO,JOF,JOO,NOM,REL,SOL,SOW,THR,TRU,VAL,POA

TOP

START_DATE

Attribute	Description
Name	START_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

END_DATE

Attribute	Description
Name	END_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Acc-Joint-PK*
      - *ACCOUNT_BRANCH*
      - *ACCOUNT_NUMBER*
    - *Acc-Joint-IO*
      - *ACCOUNT_BRANCH*
      - *ACCOUNT_NUMBER*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Acc-Joint-PK

Attribute	Description
Name	Acc-Joint-PK
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Acc-Joint-IO

Attribute	Description
Name	Acc-Joint-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.55.DeleteLocMaint

Deletion of Location Maintenance

2.55.1.ST-DeleteLocMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Location-Full*
    - *LOCCODE*
    - *DESCRIPTION*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Deletion Full type details

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the document Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the document description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Location-IO
LOCCODE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Deletion Input Only type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.55.3.ST-DeleteLocMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Location-IO*
      - *LOCCODE*
    - *Sttm-Location-Full*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Deletion Input Only type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Deletion Full type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DESCRIPTION

Attribute	Description

Name	DESCRIPTION
Datatype	String
Description	Indicates the document description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.55.4.ST-DeleteLocMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Location-IO*
      - *LOCCODE*
    - *Sttm-Location-PK*
      - *LOCCODE*
    - *Sttm-Location-Full*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Deletion Input Only type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Location-PK

Attribute	Description
Name	Sttm-Location-PK
Datatype	
Description	Includes Location Maintenance Deletion Primary Key type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Deletion Full type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the document description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.56.DeleteManStatChangInp

Deletion of Manual Status Change

2.56.1.ST-DeleteManStatChangInp-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Ac-Stat-Change-Full*
    - *CUSTACNO*
    - *ACCSTATUS*
    - *BRANCHCODE*
    - *BRANCHNAME*
    - *STATUSCHANGEDATE*
    - *SEQNO*
    - *STATUS*
    - *ACSTATNODR*
    - *ACSTATNOCR*
    - *ACSTATFROZEN*
    - *ACSTATDEPOST*
    - *ACSTATCHGAUTO*
    - *DORMANT*
    - *MAKERID*
    - *MAKERDTSTAMP*

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Deletion Full type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCSTATUS

Attribute	Description	
Name	ACCSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATNOCR

Attribute	Description	
Name	ACSTATNOCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATFROZEN

Attribute	Description	
Name	ACSTATFROZEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATDEPOST

Attribute	Description	
Name	ACSTATDEPOST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATCHGAUTO

Attribute	Description	
Name	ACSTATCHGAUTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	N,Y

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,Y

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Ac-Stat-Change-IO
CUSTACNO
BRANCHCODE
STATUSCHANGEDATE
SEQNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Deletion Input Only type details

TOP

CUSTACNO

Attribute	**Description**
Name	CUSTACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

2.56.3.ST-DeleteManStatChangInp-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Ac-Stat-Change-IO*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
    - *Sttm-Ac-Stat-Change-Full*
      - *CUSTACNO*
      - *ACCSTATUS*
      - *BRANCHCODE*
      - *BRANCHNAME*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *STATUS*
      - *ACSTATNODR*
      - *ACSTATNOCR*
      - *ACSTATFROZEN*
      - *ACSTATDEPOST*
      - *ACSTATCHGAUTO*

DORMANT

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Deletion Input Only type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Deletion Full type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ACCSTATUS

Attribute	Description	
Name	ACCSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATNOCR

Attribute	Description
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.56.4.ST-DeleteManStatChangInp-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Ac-Stat-Change-IO*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
    - *Sttm-Ac-Stat-Change-PK*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
    - *Sttm-Ac-Stat-Change-Full*
      - *CUSTACNO*
      - *ACCSTATUS*
      - *BRANCHCODE*
      - *BRANCHNAME*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *STATUS*

ACSTATNODR
ACSTATNOCR
ACSTATFROZEN
ACSTATDEPOST
ACSTATCHGAUTO
DORMANT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Deletion Input Only type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

Sttm-Ac-Stat-Change-PK

Attribute	Description
Name	Sttm-Ac-Stat-Change-PK
Datatype	
Description	Includes Manual Status Change Input Deletion Primary Key type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCHCODE

Attribute	Description

Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Deletion Full type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACCSTATUS

Attribute	Description
Name	ACCSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	4

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACSTATNODR

Attribute	**Description**
Name	ACSTATNODR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACSTATNOCR

Attribute	**Description**
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACSTATFROZEN

Attribute	**Description**
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACSTATDEPOST

Attribute	**Description**
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.57.DeleteManStatChange

DeleteManStatChange

2.57.1.ST-DeleteManStatChange-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-Full*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *NEWSTAT*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *BRNNAME*
    - *FROM_STATUS*
    - *NO_DR*
    - *ACSTATNCR*

ACSTATFRZN

ACSTATDEPST

STATCHNGAUTMATIC

DORM

AC_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Ac-Stat-Change-Full

Attribute	Description
Name	Sttms-Ac-Stat-Change-Full
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description	
Name	SINCE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWSTAT

Attribute	Description
Name	NEWSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_DE_POST

Attribute	Description	
Name	AC_STAT_DE_POST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description	
Name	AC_STAT_CHG_AUTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

FROM_STATUS

Attribute	Description
Name	FROM_STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATNCR

Attribute	Description
Name	ACSTATNCR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATFRZN

Attribute	Description
Name	ACSTATFRZN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM

Attribute	Description
Name	DORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Ac-Stat-Change-IO
CUST_AC_NO
BRANCH
SINCE
SEQ_NO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.57.3.ST-DeleteManStatChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-Full*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *NEWSTAT*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *BRNNAME*
    - *FROM_STATUS*
    - *NO_DR*
    - *ACSTATNCR*
    - *ACSTATFRZN*
    - *ACSTATDEPST*
    - *STATCHNGAUTMATIC*

DORM

AC_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Ac-Stat-Change-Full

Attribute	Description
Name	Sttms-Ac-Stat-Change-Full
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWSTAT

Attribute	Description
Name	NEWSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_DE_POST

Attribute	Description
Name	AC_STAT_DE_POST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description
Name	AC_STAT_CHG_AUTO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FROM_STATUS

Attribute	**Description**
Name	FROM_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

NO_DR

Attribute	**Description**
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATNCR

Attribute	**Description**
Name	ACSTATNCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATFRZN

Attribute	**Description**
Name	ACSTATFRZN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM

Attribute	Description
Name	DORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.57.4.ST-DeleteManStatChange-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Ac-Stat-Change-PK*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
    - *Sttms-Ac-Stat-Change-IO*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Ac-Stat-Change-PK

Attribute	Description
Name	Sttms-Ac-Stat-Change-PK
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO

Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.58.DeleteNoticePRD

Deletion of Notice Period Maintenance

2.58.1.ST-DeleteNoticePRD-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Notice-Period-Full*
    - *BRANCHCODE*
    - *CUSTACNO*
    - *INITIATIONDATE*
    - *ACTIVATIONDATE*
    - *VALIDITYPERIOD*
    - *ENDDATE*
    - *NOTICEAMT*
    - *NOTICEID*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Notice-Period-Full

Attribute	Description
Name	Notice-Period-Full
Datatype	
Description	It indicates the Full details of the Notice Period.

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicates Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INITIATIONDATE

Attribute	Description	
Name	INITIATIONDATE	
Datatype	Date	
Description	Indicates Initiation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACTIVATIONDATE

Attribute	Description	
Name	ACTIVATIONDATE	
Datatype	Date	
Description	Indicates Activation Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALIDITYPERIOD

Attribute	Description
Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE
Datatype	Date
Description	Indicates End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>Name</td><td>VAL_TYPE</td></tr>
<tr><td>Datatype</td><td>String</td></tr>
<tr><td>Description</td><td>Indicates Value type.</td></tr>
<tr><td>Attributes</td><td>
<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table>
</td></tr>
<tr><td>Restrictions</td><td>
<table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>maxLength</td><td>2</td></tr>
<tr><td>minLength</td><td>0</td></tr>
</table>
</td></tr>
</table>

TOP

2.58.2.ST-DeleteNoticePRD-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Notice-Period-IO*
    - *NOTICEID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Notice Period

TOP

NOTICEID

Attribute	Description	
Name	NOTICEID	
Datatype	String	
Description	Indicates Notice Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.58.3.ST-DeleteNoticePRD-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Notice-Period-IO*
      - *NOTICEID*
    - *Notice-Period-Full*
      - *BRANCHCODE*
      - *CUSTACNO*
      - *INITIATIONDATE*
      - *ACTIVATIONDATE*
      - *VALIDITYPERIOD*
      - *ENDDATE*
      - *NOTICEAMT*
      - *NOTICEID*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates PK Details of the Notice Period Maintenance.

TOP

NOTICEID

Attribute	Description	
Name	NOTICEID	
Datatype	String	
Description	Indicates Notice Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Notice-Period-Full

Attribute	Description
Name	Notice-Period-Full
Datatype	
Description	It indicates Full Details of the Notice Period Maintenance.

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Indicates Branch Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INITIATIONDATE

Attribute	Description
Name	INITIATIONDATE
Datatype	Date
Description	Indicates Initiation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATIONDATE

Attribute	Description
Name	ACTIVATIONDATE
Datatype	Date
Description	Indicates Activation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALIDITYPERIOD

Attribute	Description
Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE

Datatype	Date
Description	Indicates End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Notice-Period-IO*
      - *NOTICEID*
    - *Notice-Period-PK*
      - *NOTICEID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Notice Period Maintenance.

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Notice-Period-PK

Attribute	Description
Name	Notice-Period-PK
Datatype	
Description	It indicates PK Details of the Notice Period Maintenance.

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.59.DeleteOnlineCharge

DeleteOnlineCharge

2.59.1.ST-DeleteOnlineCharge-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Onlinecharge-Master-Full

Attribute	Description
Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHARGE_EVENT

Attribute	Description
Name	CHARGE_EVENT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	**Description**
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

2.59.2.ST-DeleteOnlineCharge-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-IO*
    - *SOURCE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

2.59.3.ST-DeleteOnlineCharge-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Onlinecharge-Master-Full

Attribute	Description

Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHARGE_EVENT

Attribute	**Description**	
Name	CHARGE_EVENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CHARGE_PRODUCT

Attribute	**Description**	
Name	CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Onlinecharge-Master-PK*
      - *SOURCE*
    - *Onlinecharge-Master-IO*
      - *SOURCE*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Onlinecharge-Master-PK

Attribute	Description
Name	Onlinecharge-Master-PK
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.60.DeleteSTDSTCDM

DeleteSTDSTCDM

2.60.1.ST-DeleteSTDSTCDM-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Crdrstat-Full

Attribute	Description
Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	**Description**	
Name	CUST_AC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NODEBIT

Attribute	**Description**	
Name	NODEBIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOCREDIT

Attribute	**Description**	
Name	NOCREDIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POSTALLOWED

Attribute	**Description**
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

2.60.2.ST-DeleteSTDSTCDM-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Crdrstat-IO
BRANCH_CODE
CUST_AC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	

Attributes		
	Attribute	**Description**
	minOccurs	1
Restrictions		
	Restrictions	**Description**
	maxLength	20

TOP

2.60.3.ST-DeleteSTDSTCDM-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Crdrstat-Full

Attribute	Description

Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NODEBIT

Attribute	Description
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOCREDIT

Attribute	Description
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Crdrstat-PK*
      - *BRANCH_CODE*
      - *CUST_AC*
    - *Crdrstat-IO*
      - *BRANCH_CODE*
      - *CUST_AC*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Crdrstat-PK

Attribute	Description
Name	Crdrstat-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.61.DeleteSTDSTDOR

DeleteSTDSTDOR

2.61.1.ST-DeleteSTDSTDOR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Status-Full

Attribute	Description

Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

2.61.2.ST-DeleteSTDSTDOR-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Status-IO
ACCOUNT_BRANCH
AC_NO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

2.61.3.ST-DeleteSTDSTDOR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Status-Full

Attribute	Description
Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NO_DR

Attribute	Description	
Name	NO_DR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NO_CR

Attribute	Description	
Name	NO_CR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROZEN

Attribute	Description	
Name	FROZEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Status-PK*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
    - *Status-IO*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Status-PK

Attribute	Description
Name	Status-PK
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.62.DeleteSTTypeMnt

Deletion of Card Type Maintenance

2.62.1.ST-DeleteSTTypeMnt-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *St-Debit-Card-Type-Full*
    - *CARDTYPE*
    - *DESCRIPTION*
    - *CARDBIN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *St-Debit-Card-Type-Detail*
      - *CARDTYPE*
      - *CARDBIN1*
    - *UDFDETAILS*

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

St-Debit-Card-Type-Full

Attribute	Description

Name	St-Debit-Card-Type-Full
Datatype	
Description	Include full details about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Cardtype
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CARDBIN

Attribute	Description
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Cardtype
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME

Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.62.2.ST-DeleteSTTypeMnt-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *St-Debit-Card-Type-IO*
    - *CARDTYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Includes the details about the debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

2.62.3.ST-DeleteSTTypeMnt-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *St-Debit-Card-Type-IO*
      - *CARDTYPE*
    - *St-Debit-Card-Type-Full*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *CARDBIN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *St-Debit-Card-Type-Detail*
        - *CARDTYPE*
        - *CARDBIN1*
      - *UDFDETAILS*

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

St-Debit-Card-Type-Full

Attribute	Description
Name	St-Debit-Card-Type-Full
Datatype	
Description	Include full details about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CARDBIN

Attribute	**Description**
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CARDBIN1

Attribute	Description

Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.62.4.ST-DeleteSTTypeMnt-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *St-Debit-Card-Type-IO*
      - *CARDTYPE*
    - *St-Debit-Card-Type-PK*
      - *CARDTYPE*
    - *St-Debit-Card-Type-Full*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *CARDBIN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *St-Debit-Card-Type-Detail*
        - *CARDTYPE*

CARDBIN1
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

St-Debit-Card-Type-PK

Attribute	Description
Name	St-Debit-Card-Type-PK
Datatype	
Description	Include ptrimary key details about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

St-Debit-Card-Type-Full

Attribute	Description
Name	St-Debit-Card-Type-Full
Datatype	
Description	Include full details about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CARDBIN

Attribute	Description	
Name	CARDBIN	
Datatype	String	
Description	Indicates Card Bin	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail

Datatype	
Description	Debit Card Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	**Description**
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CARDBIN1

Attribute	**Description**
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.63.CreateBranchTrfr

CreateBranchTrfr

2.63.1.ST-CreateBranchTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Brn-Transfer-Full

Attribute	Description

Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TD_REQ

Attribute	Description

Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	**Description**
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	**Description**
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-IO*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASA_REQ

Attribute	**Description**
Name	CASA_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TD_REQ

Attribute	**Description**
Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.63.3.ST-CreateBranchTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Brn-Transfer-Full

Attribute	Description
Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description	
Name	TARGET_BRANCH_CODESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	**Description**
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CI_REQ

Attribute	**Description**
Name	CI_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MO_REQ

Attribute	**Description**
Name	MO_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CASA_REQ

Attribute	**Description**
Name	CASA_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TD_REQ

Attribute	Description
Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	Description
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	Description
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.63.4.ST-CreateBranchTrfr-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Sttms-Brn-Transfer-IO*
      - *TARGET_BRANCH_CODESS*
      - *TRANSFER_DATE*
      - *TRANSFER_ID*
      - *TRANSFER_LENDING_MODULE*
      - *CI_REQ*
      - *MO_REQ*
      - *CASA_REQ*
      - *TD_REQ*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Brn-Transfer-PK

Attribute	Description
Name	Sttms-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TARGET_BRANCH_CODESS

Attribute	Description	
Name	TARGET_BRANCH_CODESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CASA_REQ

Attribute	Description

Name	CASA_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TD_REQ

Attribute	**Description**
Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.64.CreateCRSRequest

Creation of Adhoc Consolidated Statement Request

2.64.1.ST-CreateCRSRequest-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Crs-Master-Full

Attribute	Description

Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description
Name	TO_DATE
Datatype	Date
Description	Specifies the To Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Specifies The Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS_DETAILS

Attribute	Description
Name	PROCESS_STATUS_DETAILS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

E-STATEMENT

Attribute	**Description**
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Crs-Master-IO
TO_DATE
REFERENCENO
CUSTOMER_NO
REQUESTTYPE
FROMDATE
REQUESTDATE
E-STATEMENT
CHARGEACCOUNT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

TO_DATE

Attribute	Description
Name	TO_DATE
Datatype	Date
Description	Specifies the To Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	**Description**
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQUESTTYPE

Attribute	**Description**
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,L

TOP

FROMDATE

Attribute	**Description**
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REQUESTDATE

Attribute	**Description**
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEACCOUNT

Attribute	Description
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

2.64.3.ST-CreateCRSRequest-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Crs-Master-Full

Attribute	Description
Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description	
Name	TO_DATE	
Datatype	Date	
Description	Specifies the To Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	Attribute: minOccurs — Description: 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PROCESS_STATUS_DETAILS

Attribute	Description
Name	PROCESS_STATUS_DETAILS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	Description
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	Description
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.64.4.ST-CreateCRSRequest-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Crs-Master-IO*
      - *TO_DATE*
      - *REFERENCENO*
      - *CUSTOMER_NO*
      - *REQUESTTYPE*
      - *FROMDATE*
      - *REQUESTDATE*
      - *E-STATEMENT*
      - *CHARGEACCOUNT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Crs-Master-PK

Attribute	Description
Name	Sttm-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

TO_DATE

Attribute	Description	
Name	TO_DATE	
Datatype	Date	
Description	Specifies the To Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEACCOUNT

Attribute	Description
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.65.CreateCardAccount

Input of Card Accounts Detail

2.65.1.ST-CreateCardAccount-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CardAccount-Full*
    - *BRNCODE*
    - *CUSTACNO*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the detail abount card account.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255 Restrictions: minLength; Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 2 Restrictions: minLength; Description: 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CardAccount-IO*
    - *BRNCODE*
    - *CUSTACNO*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates the card account information.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String

Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

2.65.3.ST-CreateCardAccount-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CardAccount-IO*
      - *BRNCODE*
      - *CUSTACNO*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *CardAccount-Full*

BRNCODE

CUSTACNO

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates the card account information

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicate Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs, Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the detail card account information

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String

Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.65.4.ST-CreateCardAccount-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CardAccount-PK*
      - *BRNCODE*
      - *CUSTACNO*
    - *CardAccount-IO*
      - *BRNCODE*
      - *CUSTACNO*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*

FIELD_VALUE

VAL_TYPE

CardAccount-Full

BRNCODE

CUSTACNO

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CardAccount-PK

Attribute	Description
Name	CardAccount-PK
Datatype	
Description	it indicates the primary key of card account.

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates card account information.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Time when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User Id who has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the detail about card account.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.66.CreateCardMaster

CreateCardMaster

2.66.1.ST-CreateCardMaster-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*

CREDIT_CARD_LIMIT
PRIMARY_CARD
CARD_APPL_DATE
CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OWNER_ID_NO1

Attribute	Description
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADD_HOLDER_IDNO

Attribute	Description
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

OWNER_ID_TYPE

Attribute	Description
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CARD_APPL_DATE

Attribute	Description
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	Description
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

CARD_STATUS

Attribute	Description

Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	**Description**
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OPERATION

Attribute	**Description**
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BILL_CYCLE

Attribute	**Description**
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	Description	
Name	RENEWAL_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	Description	
Name	RENEWAL_CYCLE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_LIMIT_UNIT

Attribute	Description	
Name	ATM_LIMIT_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description	
Name	ATM_COUNT_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 19

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DEL_CHNL_PIN

Attribute	**Description**
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ADDL_HOLDER_DOB

Attribute	**Description**
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDL_HOLDER_RELATION

Attribute	**Description**
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DR_CR_INDICATOR

Attribute	**Description**
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.66.2.ST-CreateCardMaster-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-IO*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*
    - *CREDIT_CARD_LIMIT*
    - *PRIMARY_CARD*
    - *CARD_APPL_DATE*

CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CARD_PRODUCT

Attribute	**Description**
Name	CARD_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CARD_BIN

Attribute	**Description**
Name	CARD_BIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	**Description**
Name	REQ_REF_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OWNER_ID_NO1

Attribute	Description
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	150

TOP

ADD_HOLDER_IDNO

Attribute	Description	
Name	ADD_HOLDER_IDNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

OWNER_ID_TYPE

Attribute	Description	
Name	OWNER_ID_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description	
Name	ADDL_HOLDER_ID_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CARD_APPL_DATE

Attribute	Description
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CARD_RENEWAL_DT

Attribute	Description
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DISPATCH_STATUS

Attribute	Description	
Name	DISPATCH_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description	
Name	PIN_MAILED_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N,

TOP

CARD_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LAST_STATUS_UPDATED

Attribute	Description	
Name	LAST_STATUS_UPDATED	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LAST_OPERATION

Attribute	Description
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BILL_CYCLE

Attribute	Description
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	Description
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	Description
Name	RENEWAL_CYCLE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	Description
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

ADDL_HOLDER_DOB

Attribute	Description
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDL_HOLDER_RELATION

Attribute	Description
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.66.3.ST-CreateCardMaster-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*
    - *CREDIT_CARD_LIMIT*
    - *PRIMARY_CARD*
    - *CARD_APPL_DATE*

CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

OWNER_ID_NO1

Attribute	Description
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

ADD_HOLDER_IDNO

Attribute	Description
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

OWNER_ID_TYPE

Attribute	Description
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CARD_APPL_DATE

Attribute	**Description**
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	**Description**
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	**Description**
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N,

TOP

CARD_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

LAST_STATUS_UPDATED

Attribute	Description	
Name	LAST_STATUS_UPDATED	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

LAST_OPERATION

Attribute	Description	
Name	LAST_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

BILL_CYCLE

Attribute	Description	
Name	BILL_CYCLE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	**Description**
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	**Description**
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	**Description**
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	**Description**
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	19

TOP

DEL_CHNL_CARD

Attribute	Description	
Name	DEL_CHNL_CARD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

DEL_CHNL_PIN

Attribute	Description	
Name	DEL_CHNL_PIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

ADDL_HOLDER_DOB

Attribute	Description	
Name	ADDL_HOLDER_DOB	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

ADDL_HOLDER_RELATION

Attribute	Description	
Name	ADDL_HOLDER_RELATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DR_CR_INDICATOR

Attribute	Description
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.66.4.ST-CreateCardMaster-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Debit-Card-Master-PK*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *CUST_NO*
      - *CUST_AC_NO*
    - *Sttms-Debit-Card-Master-IO*
      - *CUST_NO*
      - *CUST_AC_NO*
      - *CARD_PRODUCT*
      - *CARD_BIN*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *HOLD_BILL_INDICATOR*
      - *RECOVERY_ACCOUNT*
      - *NAME_ON_CARD*
      - *OWNER_ID_NO1*
      - *ADD_HOLDER_IDNO*
      - *OWNER_ID_TYPE*

ADDL_HOLDER_ID_TYPE
ISSUER
PLASTIC_TYPE
CREDIT_CARD_LIMIT
PRIMARY_CARD
CARD_APPL_DATE
CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttms-Debit-Card-Master-PK

Attribute	Description
Name	Sttms-Debit-Card-Master-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description	
Name	REQ_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description

Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

OWNER_ID_NO1

Attribute	Description
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

ADD_HOLDER_IDNO

Attribute	Description
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

OWNER_ID_TYPE

Attribute	Description
Name	OWNER_ID_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	**Description**
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ISSUER

Attribute	**Description**
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PLASTIC_TYPE

Attribute	**Description**
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	**Description**
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CARD_APPL_DATE

Attribute	Description
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CARD_RENEWAL_DT

Attribute	Description
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	Description
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OPERATION

Attribute	Description
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BILL_CYCLE

Attribute	Description
Name	BILL_CYCLE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RENEWAL_UNIT

Attribute	Description	
Name	RENEWAL_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	Description	
Name	RENEWAL_CYCLE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_LIMIT_UNIT

Attribute	Description	
Name	ATM_LIMIT_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

ADDL_HOLDER_DOB

Attribute	Description
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDL_HOLDER_RELATION

Attribute	Description
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.67.CreateCustCatMaint

Input of Customer Category Maintenance

2.67.1.ST-CreateCustCatMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Customer-Cat-Full*
    - *CUSTCAT*
    - *CUSTCATDESC*
    - *POPULATECHANGESLOG*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Customer-Cat-Full

Attribute	Description

Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Creation Full type details

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the populate Changes Log. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Customer-Cat-IO*
    - *CUSTCAT*
    - *CUSTCATDESC*
    - *POPULATECHANGESLOG*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Creation Input Only type details

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer category.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the Populate Changes Log. Y - Yes,N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.67.3.ST-CreateCustCatMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Customer-Cat-IO*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*

Sttm-Customer-Cat-Full

CUSTCAT

CUSTCATDESC

POPULATECHANGESLOG

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Creation Input Only type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the Populate Changes Log. Y - Yes,N - No.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Sttm-Customer-Cat-Full

Attribute	Description
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Creation Full type details

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer category.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the Populate Changes Log. Y - Yes,N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the modification Number.
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME

Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.67.4.ST-CreateCustCatMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Customer-Cat-PK*
      - *CUSTCAT*
    - *Sttm-Customer-Cat-IO*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*

FIELD_VALUE

VAL_TYPE

Sttm-Customer-Cat-Full

CUSTCAT

CUSTCATDESC

POPULATECHANGESLOG

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Customer-Cat-PK

Attribute	Description
Name	Sttm-Customer-Cat-PK
Datatype	
Description	Includes Customer Category Maintenance Creation Primary Key type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Creation Input Only type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTCATDESC

Attribute	Description	
Name	CUSTCATDESC	
Datatype	String	
Description	Indicates the Customer Category Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POPULATECHANGESLOG

Attribute	Description	
Name	POPULATECHANGESLOG	
Datatype	String	
Description	Indicates the Populate Changes Log. Y - Yes,N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Sttm-Customer-Cat-Full

Attribute	Description
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Creation Full type details

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the Populate Changes Log. Y - Yes,N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description

Name	MODNO
Datatype	Number
Description	Indicates the modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.68.ModifyCardMaster

ModifyCardMaster

2.68.1.ST-ModifyCardMaster-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*

CREDIT_CARD_LIMIT
PRIMARY_CARD
CARD_APPL_DATE
CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CARD_PRODUCT

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NAME_ON_CARD

Attribute	**Description**
Name	NAME_ON_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OWNER_ID_NO1

Attribute	**Description**
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

ADD_HOLDER_IDNO

Attribute	**Description**
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

OWNER_ID_TYPE

Attribute	**Description**
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CARD_APPL_DATE

Attribute	**Description**
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	**Description**
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	**Description**
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_NO

Attribute	**Description**
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CARD_SEQ_NO

Attribute	**Description**
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DISPATCH_STATUS

Attribute	**Description**
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	**Description**
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N,

TOP

CARD_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

LAST_STATUS_UPDATED

Attribute	Description	
Name	LAST_STATUS_UPDATED	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

LAST_OPERATION

Attribute	Description	
Name	LAST_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

BILL_CYCLE

Attribute	Description	
Name	BILL_CYCLE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RENEWAL_UNIT

Attribute	**Description**
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	**Description**
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	**Description**
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	**Description**
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	19

TOP

DEL_CHNL_CARD

Attribute	Description	
Name	DEL_CHNL_CARD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

DEL_CHNL_PIN

Attribute	Description	
Name	DEL_CHNL_PIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

ADDL_HOLDER_DOB

Attribute	Description	
Name	ADDL_HOLDER_DOB	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

ADDL_HOLDER_RELATION

Attribute	Description	
Name	ADDL_HOLDER_RELATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DR_CR_INDICATOR

Attribute	Description
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,C

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.68.2.ST-ModifyCardMaster-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Debit-Card-Master-PK*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *CUST_NO*
      - *CUST_AC_NO*
    - *Sttms-Debit-Card-Master-IO*
      - *CUST_NO*
      - *CUST_AC_NO*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *ADD_HOLDER_IDNO*
      - *PRIMARY_CARD*
      - *CARD_RENEWAL_DT*
      - *CARD_EXPIRY_DT*
      - *DISPATCH_STATUS*
      - *PIN_MAILED_STATUS*
      - *CARD_STATUS*
      - *LAST_STATUS_UPDATED*

LAST_OPERATION
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
MAKER
MAKERSTAMP
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Debit-Card-Master-PK

Attribute	Description
Name	Sttms-Debit-Card-Master-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	**Description**
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADD_HOLDER_IDNO

Attribute	**Description**
Name	ADD_HOLDER_IDNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

PRIMARY_CARD

Attribute	**Description**
Name	PRIMARY_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CARD_RENEWAL_DT

Attribute	**Description**
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	**Description**
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPATCH_STATUS

Attribute	**Description**
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	Description
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OPERATION

Attribute	Description
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RENEWAL_UNIT

Attribute	**Description**	
Name	RENEWAL_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	**Description**	
Name	RENEWAL_CYCLE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_LIMIT_UNIT

Attribute	**Description**	
Name	ATM_LIMIT_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	**Description**	
Name	ATM_COUNT_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

DEL_CHNL_PIN

Attribute	Description
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

ADDL_HOLDER_DOB

Attribute	Description
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADDL_HOLDER_RELATION

Attribute	Description
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.68.3.ST-ModifyCardMaster-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*
    - *CREDIT_CARD_LIMIT*
    - *PRIMARY_CARD*
    - *CARD_APPL_DATE*

CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	**Description**
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLD_BILL_INDICATOR

Attribute	**Description**
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECOVERY_ACCOUNT

Attribute	**Description**
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NAME_ON_CARD

Attribute	**Description**
Name	NAME_ON_CARD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO1

Attribute	Description
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADD_HOLDER_IDNO

Attribute	Description
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

OWNER_ID_TYPE

Attribute	Description
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CARD_APPL_DATE

Attribute	Description
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CARD_RENEWAL_DT

Attribute	Description
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CARD_NO

Attribute	Description

Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LAST_STATUS_UPDATED

Attribute	Description
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OPERATION

Attribute	Description
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BILL_CYCLE

Attribute	Description
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	Description
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	Description
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	Description
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DEL_CHNL_PIN

Attribute	Description
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ADDL_HOLDER_DOB

Attribute	Description
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDL_HOLDER_RELATION

Attribute	Description
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DR_CR_INDICATOR

Attribute	Description
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

2.68.4.ST-ModifyCardMaster-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-IO*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *ADD_HOLDER_IDNO*
    - *PRIMARY_CARD*
    - *CARD_RENEWAL_DT*
    - *CARD_EXPIRY_DT*
    - *DISPATCH_STATUS*
    - *PIN_MAILED_STATUS*
    - *CARD_STATUS*
    - *LAST_STATUS_UPDATED*
    - *LAST_OPERATION*
    - *REMARKS*
    - *RENEWAL_UNIT*
    - *RENEWAL_CYCLE*
    - *ATM_LIMIT_UNIT*
    - *ATM_COUNT_LIMIT*

ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
MAKER
MAKERSTAMP
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQ_REF_NO

Attribute	**Description**
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ADD_HOLDER_IDNO

Attribute	**Description**
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

PRIMARY_CARD

Attribute	**Description**
Name	PRIMARY_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CARD_RENEWAL_DT

Attribute	**Description**
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	Description
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LAST_OPERATION

Attribute	Description
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

RENEWAL_UNIT

Attribute	Description
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	Description
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ATM_LIMIT_UNIT

Attribute	Description
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

DEL_CHNL_PIN

Attribute	Description
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

ADDL_HOLDER_DOB

Attribute	Description
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADDL_HOLDER_RELATION

Attribute	Description
Name	ADDL_HOLDER_RELATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.69.ModifyCustCatMaint

Modification of Customer Category Maintenance

2.69.1.ST-ModifyCustCatMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Customer-Cat-Full*
    - *CUSTCAT*
    - *CUSTCATDESC*
    - *POPULATECHANGESLOG*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Customer-Cat-Full

Attribute	Description

Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes the Full details about customer based on customer catagory

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CUSTCATDESC

Attribute	Description	
Name	CUSTCATDESC	
Datatype	String	
Description	Indicates the Customer Category Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POPULATECHANGESLOG

Attribute	Description	
Name	POPULATECHANGESLOG	
Datatype	String	
Description	Indicates the populate Changes Log. Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Customer-Cat-IO*
    - *CUSTCAT*
    - *CUSTCATDESC*
    - *POPULATECHANGESLOG*
    - *MODNO*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes information about customer category.

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CUSTCATDESC

Attribute	**Description**	
Name	CUSTCATDESC	
Datatype	String	
Description	Indicates the Customer Category description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POPULATECHANGESLOG

Attribute	**Description**	
Name	POPULATECHANGESLOG	
Datatype	String	
Description	Indicates the Populate Changes Log.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.69.3.ST-ModifyCustCatMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Customer-Cat-IO*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Sttm-Customer-Cat-Full*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes information related customer category.

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CUSTCATDESC

Attribute	Description	
Name	CUSTCATDESC	
Datatype	String	
Description	Indicates the Customer Category description.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the Populate Changes Log.Y - Yes, N - No.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: N,Y

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: totalDigits, Description: 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 8 Restrictions: pattern, Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sttm-Customer-Cat-Full

Attribute	Description
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes full details related customer category.

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the Populate Changes Log.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 2 Restrictions: minLength, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.69.4.ST-ModifyCustCatMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Customer-Cat-PK*
      - *CUSTCAT*
    - *Sttm-Customer-Cat-IO*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Sttm-Customer-Cat-Full*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MAKERID*

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Customer-Cat-PK

Attribute	Description
Name	Sttm-Customer-Cat-PK
Datatype	
Description	Includes primary key details related customer category.

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes information related customer category.

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTCATDESC

Attribute	Description
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the Populate Changes Log.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sttm-Customer-Cat-Full

Attribute	**Description**
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes full details related customer category.

TOP

CUSTCAT

Attribute	**Description**
Name	CUSTCAT
Datatype	String
Description	Indicates the Customer Category.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTCATDESC

Attribute	**Description**
Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	Description
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the Populate Changes Log.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: totalDigits — Description: 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.70.ModifyCustTrfr

ModifyCustTrfr

2.70.1.ST-ModifyCustTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cust-Brn-Transfer-Full

Attribute	Description

Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description
Name	TRANSFER_MORTGAGES_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_CASA

Attribute	Description
Name	TRANSFER_CASA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	**Description**
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	**Description**
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	**Description**
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	**Description**
Name	TXT_CUSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-IO*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *MAKER*
    - *MAKERSTAMP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description
Name	TRANSFER_MORTGAGES_MODULE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFER_CASA

Attribute	Description	
Name	TRANSFER_CASA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description	
Name	TARGET_BRANCH_CODESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

2.70.3.ST-ModifyCustTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cust-Brn-Transfer-Full

Attribute	Description
Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description	
Name	TRANSFER_MORTGAGES_MODULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFER_CASA

Attribute	Description	
Name	TRANSFER_CASA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	Description
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	Description
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.70.4.ST-ModifyCustTrfr-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cust-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Cust-Brn-Transfer-IO*
      - *TRANSFER_MORTGAGES_MODULE*
      - *TRANSFER_CASA*
      - *CURRENT_BRANCH_CODE*
      - *TARGET_BRANCH_CODESS*
      - *TRANSFER_DATE*
      - *TRANSFER_ID*
      - *TRANSFER_LENDING_MODULE*
      - *TRANSFER_ISLAMIC_FINANCING_MODULE*
      - *CUSTOMER_ID*
      - *TRANSFER_TERM_DEPOSITS*
      - *MAKER*
      - *MAKERSTAMP*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Cust-Brn-Transfer-PK

Attribute	Description
Name	Cust-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description	
Name	TRANSFER_MORTGAGES_MODULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFER_CASA

Attribute	Description	
Name	TRANSFER_CASA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.71.ModifyJointHolderMaint

Modify Joint Holder Maintenance

2.71.1.ST-ModifyJointHolderMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Acc-Joint-Full*
    - *ACCOUNT_BRANCH*
    - *ACCOUNT_NUMBER*
    - *CUST_NO*
    - *ACCTYPE*
    - *OPMODE*
    - *ACCOUNT_CURRENCY*
    - *AC_DESC*
    - *CUSTNAME1*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

Acc-Joint-Holder

CUSTOMER_NUMBER

CUSTOMER_NAME

JNTHLDTYP

START_DATE

END_DATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Acc-Joint-Full

Attribute	Description
Name	Acc-Joint-Full
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,J

TOP

OPMODE

Attribute	Description
Name	OPMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,J,E,F,M,

TOP

ACCOUNT_CURRENCY

Attribute	Description
Name	ACCOUNT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTNAME1

Attribute	Description
Name	CUSTNAME1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Acc-Joint-Holder

Attribute	Description
Name	Acc-Joint-Holder
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NUMBER

Attribute	Description
Name	CUSTOMER_NUMBER
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTOMER_NAME

Attribute	**Description**
Name	CUSTOMER_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

JNTHLDTYP

Attribute	**Description**
Name	JNTHLDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / AUS,CON,GUR,CUS,DEV,GUA,JAF,JAO,JOF,JOO,NOM,REL,SOL,SOW,THR,TRU,VAL,POA

TOP

START_DATE

Attribute	**Description**
Name	START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

END_DATE

Attribute	**Description**
Name	END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.71.2.ST-ModifyJointHolderMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Acc-Joint-IO*
    - *ACCOUNT_BRANCH*
    - *ACCOUNT_NUMBER*
    - *ACCTYPE*
    - *OPMODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *Acc-Joint-Holder*
      - *CUSTOMER_NUMBER*
      - *CUSTOMER_NAME*
      - *JNTHLDTYP*
      - *START_DATE*
      - *END_DATE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Acc-Joint-IO

Attribute	Description
Name	Acc-Joint-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCOUNT_NUMBER

Attribute	Description	
Name	ACCOUNT_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,J

TOP

OPMODE

Attribute	Description	
Name	OPMODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,J,E,F,M,

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Acc-Joint-Holder

Attribute	Description
Name	Acc-Joint-Holder
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

CUSTOMER_NUMBER

Attribute	Description
Name	CUSTOMER_NUMBER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTOMER_NAME

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

JNTHLDTYP

Attribute	Description
Name	JNTHLDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUS,CON,GUR,CUS,DEV,GUA,JAF,JAO,JOF,JOO,NOM,REL,SOL,SOW,THR,TRU,VAL,POA

TOP

START_DATE

Attribute	Description
Name	START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

END_DATE

Attribute	Description
Name	END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.71.3.ST-ModifyJointHolderMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Acc-Joint-Full*
    - *ACCOUNT_BRANCH*
    - *ACCOUNT_NUMBER*
    - *CUST_NO*
    - *ACCTYPE*
    - *OPMODE*
    - *ACCOUNT_CURRENCY*
    - *AC_DESC*
    - *CUSTNAME1*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Acc-Joint-Holder*
      - *CUSTOMER_NUMBER*
      - *CUSTOMER_NAME*

JNTHLDTYP

START_DATE

END_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Acc-Joint-Full

Attribute	Description
Name	Acc-Joint-Full
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCOUNT_NUMBER

Attribute	Description	
Name	ACCOUNT_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,J

TOP

OPMODE

Attribute	Description
Name	OPMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,J,E,F,M,

TOP

ACCOUNT_CURRENCY

Attribute	Description
Name	ACCOUNT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTNAME1

Attribute	Description

Name	CUSTNAME1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Acc-Joint-Holder

Attribute	**Description**
Name	Acc-Joint-Holder
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NUMBER

Attribute	Description
Name	CUSTOMER_NUMBER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTOMER_NAME

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

JNTHLDTYP

Attribute	Description
Name	JNTHLDTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: AUS,CON,GUR,CUS,DEV,GUA,JAF,JAO,JOF,JOO,NOM,REL,SOL,SOW,THR,TRU,VAL,POA

TOP

START_DATE

Attribute	Description
Name	START_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

END_DATE

Attribute	Description
Name	END_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.71.4.ST-ModifyJointHolderMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Acc-Joint-PK*
      - *ACCOUNT_BRANCH*
      - *ACCOUNT_NUMBER*
    - *Acc-Joint-IO*
      - *ACCOUNT_BRANCH*
      - *ACCOUNT_NUMBER*
      - *ACCTYPE*
      - *OPMODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *Acc-Joint-Holder*
        - *CUSTOMER_NUMBER*
        - *CUSTOMER_NAME*
        - *JNTHLDTYP*
        - *START_DATE*
        - *END_DATE*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Acc-Joint-PK

Attribute	Description
Name	Acc-Joint-PK
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCOUNT_NUMBER

Attribute	Description	
Name	ACCOUNT_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Acc-Joint-IO

Attribute	Description
Name	Acc-Joint-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	**Description**
Name	ACCOUNT_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCTYPE

Attribute	**Description**
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,J

TOP

OPMODE

Attribute	**Description**
Name	OPMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,J,E,F,M,

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Acc-Joint-Holder

Attribute	Description	
Name	Acc-Joint-Holder	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTOMER_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

JNTHLDTYP

Attribute	Description
Name	JNTHLDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUS,CON,GUR,CUS,DEV,GUA,JAF,JAO,JOF,JOO,NOM,REL,SOL,SOW,THR,TRU,VAL,POA

TOP

START_DATE

Attribute	Description
Name	START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

END_DATE

Attribute	Description
Name	END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.72.ModifyLocMaint

Modification of Location Maintenance

2.72.1.ST-ModifyLocMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Location-Full*
    - *LOCCODE*
    - *DESCRIPTION*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	It indicates full details of the Document Maintenance.

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the document Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the document description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the authorisation Status.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

- FCUBS_HEADER
  - SOURCE
  - UBSCOMP
  - MSGID
  - CORRELID
  - USERID
  - BRANCH
  - MODULEID
  - SERVICE
  - OPERATION
  - SOURCE_OPERATION
  - SOURCE_USERID
  - DESTINATION
  - MULTITRIPID
  - FUNCTIONID
  - ACTION
  - MSGSTAT
  - PASSWORD
  - ADDL
    - PARAM
      - NAME
      - VALUE
- FCUBS_BODY
  - Sttm-Location-IO
    - LOCCODE
    - DESCRIPTION
    - MODNO
    - UDFDETAILS
      - FUNCTIONID
      - FIELD_NAME
      - DATATYPE
      - FIELD_VALUE
      - VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	It indicates IO type of the Document Maintenance.

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the Location Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Location Description.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: totalDigits — Description: 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.72.3.ST-ModifyLocMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Location-IO*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Sttm-Location-Full*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	It indicates IO type of the Document Maintenance.

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the Location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the Location Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String

Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sttm-Location-Full

Attribute	**Description**
Name	Sttm-Location-Full
Datatype	
Description	It indicates full details of the Document Maintenance.

TOP

LOCCODE

Attribute	**Description**
Name	LOCCODE
Datatype	String
Description	Indicates the Location Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Location Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.72.4.ST-ModifyLocMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Location-PK*
      - *LOCCODE*
    - *Sttm-Location-IO*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Sttm-Location-Full*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*

CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Location-PK

Attribute	Description
Name	Sttm-Location-PK
Datatype	
Description	It indicates PK Details of the Document Maintenance.

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	It indicates IO type of the Document Maintenance.

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the location Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Location Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	It indicates full details of the Document Maintenance.

TOP

LOCCODE

Attribute	Description
Name	LOCCODE
Datatype	String
Description	Indicates the location Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Location Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

ORACLE

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	Indicates the authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.73.ModifyManStatChangInp

Modification of Manual Status Change

2.73.1.ST-ModifyManStatChangInp-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Ac-Stat-Change-Full*
    - *CUSTACNO*
    - *ACCSTATUS*
    - *BRANCHCODE*
    - *BRANCHNAME*
    - *STATUSCHANGEDATE*
    - *SEQNO*
    - *STATUS*
    - *ACSTATNODR*
    - *ACSTATNOCR*
    - *ACSTATFROZEN*
    - *ACSTATDEPOST*
    - *ACSTATCHGAUTO*
    - *DORMANT*
    - *MAKERID*
    - *MAKERDTSTAMP*

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Modification Full type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCSTATUS

Attribute	Description	
Name	ACCSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATNOCR

Attribute	Description	
Name	ACSTATNOCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATFROZEN

Attribute	Description	
Name	ACSTATFROZEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATDEPOST

Attribute	Description	
Name	ACSTATDEPOST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATCHGAUTO

Attribute	Description	
Name	ACSTATCHGAUTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	N,Y

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	N,Y

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Ac-Stat-Change-IO
CUSTACNO
BRANCHCODE
STATUSCHANGEDATE
SEQNO
MODNO
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Modification Input Only type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 2
	minLength / 0

TOP

2.73.3.ST-ModifyManStatChangInp-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Ac-Stat-Change-IO*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Sttm-Ac-Stat-Change-Full*
      - *CUSTACNO*
      - *ACCSTATUS*
      - *BRANCHCODE*
      - *BRANCHNAME*
      - *STATUSCHANGEDATE*

SEQNO
STATUS
ACSTATNODR
ACSTATNOCR
ACSTATFROZEN
ACSTATDEPOST
ACSTATCHGAUTO
DORMANT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Modification Input Only type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	20

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: totalDigits — Description: 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sttm-Ac-Stat-Change-Full

Attribute	**Description**
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Modification Full type details

TOP

CUSTACNO

Attribute	**Description**
Name	CUSTACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCSTATUS

Attribute	**Description**
Name	ACCSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	4

TOP

ACSTATNODR

Attribute	Description	
Name	ACSTATNODR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATNOCR

Attribute	Description	
Name	ACSTATNOCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATFROZEN

Attribute	Description	
Name	ACSTATFROZEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATDEPOST

Attribute	Description	
Name	ACSTATDEPOST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: totalDigits — Description: 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: Description
	minOccurs: 0
Restrictions	Restrictions: Description
	maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: Description
	minOccurs: 0
Restrictions	Restrictions: Description
	maxLength: 255
	minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: Description
	minOccurs: 0
Restrictions	Restrictions: Description
	maxLength: 2
	minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	Attribute: Description
	maxOccurs: unbounded
	minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.73.4.ST-ModifyManStatChangInp-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Ac-Stat-Change-PK*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
    - *Sttm-Ac-Stat-Change-IO*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Sttm-Ac-Stat-Change-Full*

CUSTACNO
ACCSTATUS
BRANCHCODE
BRANCHNAME
STATUSCHANGEDATE
SEQNO
STATUS
ACSTATNODR
ACSTATNOCR
ACSTATFROZEN
ACSTATDEPOST
ACSTATCHGAUTO
DORMANT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-PK

Attribute	Description
Name	Sttm-Ac-Stat-Change-PK
Datatype	
Description	Includes Manual Status Change Input Modification Primary Key type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Modification Input Only type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

STATUSCHANGEDATE

Attribute	**Description**
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	**Description**
Name	SEQNO
Datatype	Number
Description	

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Modification Full type details

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

ACCSTATUS

Attribute	Description
Name	ACCSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATNOCR

Attribute	Description
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

ACSTATCHGAUTO

Attribute	Description

Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

DORMANT

Attribute	**Description**
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.74.ModifyManStatChange

ModifyManStatChange

2.74.1.ST-ModifyManStatChange-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-Full*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *NEWSTAT*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *BRNNAME*
    - *FROM_STATUS*
    - *NO_DR*
    - *ACSTATNCR*

ACSTATFRZN

ACSTATDEPST

STATCHNGAUTMATIC

DORM

AC_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Ac-Stat-Change-Full

Attribute	Description
Name	Sttms-Ac-Stat-Change-Full
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description	
Name	SINCE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWSTAT

Attribute	Description
Name	NEWSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_DE_POST

Attribute	Description	
Name	AC_STAT_DE_POST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description	
Name	AC_STAT_CHG_AUTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

FROM_STATUS

Attribute	Description
Name	FROM_STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATNCR

Attribute	Description
Name	ACSTATNCR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATFRZN

Attribute	Description
Name	ACSTATFRZN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM

Attribute	Description
Name	DORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-IO*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *MAKER*
    - *MAKERSTAMP*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description	
Name	SINCE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SEQ_NO

Attribute	Description	
Name	SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACSTATNDR1

Attribute	Description	
Name	ACSTATNDR1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_STAT_NO_CR

Attribute	Description

Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_FROZEN

Attribute	**Description**
Name	AC_STAT_FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_DE_POST

Attribute	**Description**
Name	AC_STAT_DE_POST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	**Description**
Name	AC_STAT_CHG_AUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	**Description**
Name	DORMANT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.74.3.ST-ModifyManStatChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-Full*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*
    - *NEWSTAT*
    - *ACSTATNDR1*
    - *AC_STAT_NO_CR*
    - *AC_STAT_FROZEN*
    - *AC_STAT_DE_POST*
    - *AC_STAT_CHG_AUTO*
    - *DORMANT*
    - *BRNNAME*
    - *FROM_STATUS*
    - *NO_DR*
    - *ACSTATNCR*
    - *ACSTATFRZN*
    - *ACSTATDEPST*
    - *STATCHNGAUTMATIC*

DORM

AC_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Ac-Stat-Change-Full

Attribute	Description
Name	Sttms-Ac-Stat-Change-Full
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWSTAT

Attribute	Description
Name	NEWSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_DE_POST

Attribute	Description
Name	AC_STAT_DE_POST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description
Name	AC_STAT_CHG_AUTO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FROM_STATUS

Attribute	**Description**
Name	FROM_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

NO_DR

Attribute	**Description**
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATNCR

Attribute	**Description**
Name	ACSTATNCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATFRZN

Attribute	**Description**
Name	ACSTATFRZN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACSTATDEPST

Attribute	**Description**	
Name	ACSTATDEPST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATCHNGAUTMATIC

Attribute	**Description**	
Name	STATCHNGAUTMATIC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORM

Attribute	**Description**	
Name	DORM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_DESC

Attribute	**Description**	
Name	AC_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.74.4.ST-ModifyManStatChange-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Ac-Stat-Change-PK*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
    - *Sttms-Ac-Stat-Change-IO*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
      - *ACSTATNDR1*
      - *AC_STAT_NO_CR*
      - *AC_STAT_FROZEN*
      - *AC_STAT_DE_POST*
      - *AC_STAT_CHG_AUTO*
      - *DORMANT*
      - *MAKER*
      - *MAKERSTAMP*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Ac-Stat-Change-PK

Attribute	Description
Name	Sttms-Ac-Stat-Change-PK
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO

Datatype	Number
Description	

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_DE_POST

Attribute	Description
Name	AC_STAT_DE_POST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description
Name	AC_STAT_CHG_AUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.75.ModifyOnlineCharge

ModifyOnlineCharge

2.75.1.ST-ModifyOnlineCharge-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Onlinecharge-Master-Full

Attribute	Description
Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHARGE_EVENT

Attribute	Description
Name	CHARGE_EVENT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	**Description**
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Onlinecharge-Master-IO
SOURCE
MAKER
MAKERSTAMP
Onlinecharge-Detail
SOURCE
CHARGE_EVENT
CHARGE_PRODUCT
ACTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Onlinecharge-Detail

Attribute	**Description**
Name	Onlinecharge-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

SOURCE

Attribute	**Description**
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHARGE_EVENT

Attribute	**Description**
Name	CHARGE_EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	Description
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

2.75.3.ST-ModifyOnlineCharge-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Onlinecharge-Master-Full

Attribute	Description

Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHARGE_EVENT

Attribute	**Description**	
Name	CHARGE_EVENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CHARGE_PRODUCT

Attribute	**Description**	
Name	CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.75.4.ST-ModifyOnlineCharge-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Onlinecharge-Master-PK*
      - *SOURCE*
    - *Onlinecharge-Master-IO*
      - *SOURCE*
      - *MAKER*
      - *MAKERSTAMP*
      - *Onlinecharge-Detail*
        - *SOURCE*
        - *CHARGE_EVENT*
        - *CHARGE_PRODUCT*
        - *ACTION*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Onlinecharge-Master-PK

Attribute	Description
Name	Onlinecharge-Master-PK
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description

ORACLE

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Onlinecharge-Detail

Attribute	**Description**
Name	Onlinecharge-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

SOURCE

Attribute	**Description**
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHARGE_EVENT

Attribute	**Description**
Name	CHARGE_EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	**Description**
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.76.ModifySTDSTCDM

ModifySTDSTCDM

2.76.1.ST-ModifySTDSTCDM-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Crdrstat-Full

Attribute	Description
Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description	
Name	CUST_AC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NODEBIT

Attribute	Description	
Name	NODEBIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOCREDIT

Attribute	Description	
Name	NOCREDIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-IO*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NODEBIT

Attribute	Description
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCREDIT

Attribute	Description
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String

Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.76.3.ST-ModifySTDSTCDM-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Crdrstat-Full

Attribute	Description

Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NODEBIT

Attribute	Description
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCREDIT

Attribute	Description
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.76.4.ST-ModifySTDSTCDM-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Crdrstat-PK*
      - *BRANCH_CODE*
      - *CUST_AC*
    - *Crdrstat-IO*
      - *BRANCH_CODE*
      - *CUST_AC*
      - *NODEBIT*
      - *NOCREDIT*
      - *POSTALLOWED*
      - *REMARKS*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Crdrstat-PK

Attribute	Description
Name	Crdrstat-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description	
Name	CUST_AC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NODEBIT

Attribute	Description
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCREDIT

Attribute	Description
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.77.ModifySTDSTDOR

ModifySTDSTDOR

2.77.1.ST-ModifySTDSTDOR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Status-Full

Attribute	Description

Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NO_DR

Attribute	Description	
Name	NO_DR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NO_CR

Attribute	Description	
Name	NO_CR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROZEN

Attribute	Description	
Name	FROZEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORMANT

Attribute	Description	
Name	DORMANT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-IO*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *MAKER*
    - *MAKERSTAMP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

2.77.3.ST-ModifySTDSTDOR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Status-Full

Attribute	Description
Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

2.77.4.ST-ModifySTDSTDOR-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Status-PK*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
    - *Status-IO*
      - *REVERSE_MOVEMENT_PARAM*
      - *REMARKS*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
      - *NO_DR*
      - *NO_CR*
      - *FROZEN*
      - *DORMANT*
      - *MAKER*
      - *MAKERSTAMP*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Status-PK

Attribute	Description
Name	Status-PK
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AC_NO

Attribute	Description	
Name	AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description	
Name	REVERSE_MOVEMENT_PARAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.78.ModifySTTypeMnt

Modification of Card Type Maintenance

2.78.1.ST-ModifySTTypeMnt-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *St-Debit-Card-Type-Full*
    - *CARDTYPE*
    - *DESCRIPTION*
    - *CARDBIN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *St-Debit-Card-Type-Detail*
      - *CARDTYPE*
      - *CARDBIN1*
    - *UDFDETAILS*

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

St-Debit-Card-Type-Full

Attribute	Description

Name	St-Debit-Card-Type-Full
Datatype	
Description	Include full details about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Cardtype
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CARDBIN

Attribute	Description
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Cardtype
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME

Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.78.2.ST-ModifySTTypeMnt-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *St-Debit-Card-Type-IO*
    - *CARDTYPE*
    - *DESCRIPTION*
    - *MODNO*
    - *St-Debit-Card-Type-Detail*
      - *CARDTYPE*
      - *CARDBIN1*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

St-Debit-Card-Type-Detail

Attribute	**Description**
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	**Description**
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Indicates Card Bin1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

2.78.3.ST-ModifySTTypeMnt-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *St-Debit-Card-Type-IO*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *MODNO*
      - *St-Debit-Card-Type-Detail*
        - *CARDTYPE*
        - *CARDBIN1*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *St-Debit-Card-Type-Full*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *CARDBIN*
      - *MAKERID*

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

St-Debit-Card-Type-Detail

CARDTYPE

CARDBIN1

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Indicates Card Bin1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

St-Debit-Card-Type-Full

Attribute	Description
Name	St-Debit-Card-Type-Full
Datatype	
Description	Include full details about debit card type.

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CARDBIN

Attribute	**Description**
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type Details
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Indicates Card Bin1
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String

Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.78.4.ST-ModifySTTypeMnt-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *St-Debit-Card-Type-PK*
      - *CARDTYPE*
    - *St-Debit-Card-Type-IO*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *MODNO*
      - *St-Debit-Card-Type-Detail*
        - *CARDTYPE*
        - *CARDBIN1*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *St-Debit-Card-Type-Full*
      - *CARDTYPE*
      - *DESCRIPTION*

CARDBIN
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
St-Debit-Card-Type-Detail
CARDTYPE
CARDBIN1
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

St-Debit-Card-Type-PK

Attribute	Description
Name	St-Debit-Card-Type-PK
Datatype	
Description	Include primary key details about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Indicates Card Bin1
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs / Description: unbounded Attribute: minOccurs / Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 8 Restrictions: pattern / Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

St-Debit-Card-Type-Full

Attribute	Description
Name	St-Debit-Card-Type-Full
Datatype	
Description	Include full details about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CARDBIN

Attribute	Description	
Name	CARDBIN	
Datatype	String	
Description	Indicates Card Bin	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	**Description**
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 15

TOP

CARDBIN1

Attribute	Description
Name	CARDBIN1
Datatype	String
Description	Indicates Card Bin1
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 11

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs / Description: unbounded Attribute: minOccurs / Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 8 Restrictions: pattern / Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.79.DeleteAccClasMaint

Deletion of Account Class maintenance

2.79.1.ST-DeleteAccClasMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-Full*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *ACCTYPE*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*

ACCSTMNTTYPT
ACCSTMNTCYCL3
OFFLNLMT
AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS

DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS
MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE

BALRPTTYP
STARTDT
STMNTPARAM1
STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT

INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN
ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*

- *DR_CB*
- *DR_LINE*
- *DR_HO*
- *RBKPROVSN*
- *STAT*
- *TXTSTATDESC*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation

- *ACCCLS*
- *SEQNO*
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint

- *BLCKNGORDR*
- *PRDCD*
- *PRDDESC*

Products

- *PRDCD*
- *PRDDESC*
- *DRTXN*
- *CRTXN*

Transaction-Codes

- *TXNCD*
- *TRNDESC*
- *DRTXN*
- *CRTXN*

Branch-Restriction

- *BRNCD*

Ccy-Restriction

- *CCYCD*

Ccy-Preferences

- *CCYCD*
- *MINBAL*

ATMCSHLMT
ATMTRNSLMT
TRUSTACCASHLIMIT
MINIMUM_OPENING_BALANCE
ACCOUNT_OPENING_CHARGES
THRESHOLD_AMOUNT

Cat-Restriction
CUSTCAT

Cust-Restriction
CUSTNO
ALLWD

Interim-Dramt
CCY
AMT

Interim-Cramt
CCY
AMT

Msg-Gentime
GENTIM

Msg-Gentime1
GENTIM

Notice-Pref
ADVINTREQD
MNTHLYFREEAMT
NOTCPRD
VALDITYPRD

Aclass-Doctype
CUSTOMER_TYPE
DOCUMENT_TYPE
MANDATORY

Sttms-Accls-Minmax-Amt-Ccy
CCY
MIN_AMOUNT
MAX_AMOUNT
TOPUP_UNITS

Dep-Accls-Rest
AC_CLASS
ADESC

Denom-Deposit
DENOMINATION_ID
DENOMINATION_DESC
DENOMINATION_VALUE
CURRENCY

Deposit-Ccy-Pref

- *ACCCCY*
- *Deposit-Ccy-Pref-Dtl*
  - *CURRENCY*
  - *PAYIN*
  - *INT_PAYOUT_C*
  - *PRI_PAYOUT_C*
- *Exrate-Pref*
  - *PAYINOUT_C*
  - *MODE_TYPE_C*
  - *RATETYPE_C*
  - *RATECODE_C*
  - *VARIANCE_C*
- *Chan-Rest-C*
  - *CHANLID*
  - *CHANNDESC*
- *Minmax-Ccy-C*
  - *CURR*
  - *CHANLID*
  - *MIN_AMOUNT*
  - *MAX_AMOUNT*
  - *TOPUP_UNITS*
- *Dorm-Param*
  - *ACCOUNT_CLASS*
  - *LCY_BALANCE*
  - *FREQUENCY*
  - *DORM_PREP_SEL_METH*
  - *DORM_PREP_DATE*
  - *DORM_PREP_NTH*
  - *DORM_PREP_DAY*
  - *DORM_PREP_MONTH*
  - *DORM_PREP_ACTION*
  - *DORM_PROC_SEL_METH*
  - *DORM_PROC_DATE*
  - *DORM_PROC_NTH*
  - *DORM_PROC_DAY*
  - *DORM_PROC_MONTH*
  - *DORM_GL*
  - *DORM_TRN_CODE*
  - *DORM_ADV_GEN*
  - *DORM_STOP_IC*
- *UDFDETAILS*
  - *FLDNAM*
  - *FLDVAL*
- *Misaccdflt*

MISCODE2
MISCODE3
MISCODE4
MISCODE5
MISCODE6
MISCODE7
MISCODE8
MISCODE9
MISCODE10
COSTCODE1
COSTCODE2
COSTCODE3
COSTCODE4
COSTCODE5
ACCLASS
MISGROUP
POOLCODE
MISCODE1
MISCLASS1
MISCLASS2
MISCLASS3
MISCLASS4
MISCLASS5
MISCLASS6
MISCLASS7
MISCLASS8
MISCLASS9
MISCLASS10
LINKTOGROUP
Status-Control

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Account-Class-Master-Full

Attribute	Description
Name	Account-Class-Master-Full
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DESC

Attribute	Description
Name	DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCCD

Attribute	Description
Name	ACCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,C

TOP

DRMNTPRM

Attribute	Description
Name	DRMNTPRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description
Name	ACCSTMNTCYCL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	**Description**
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	**Description**
Name	ACCSTMNTCYCL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	**Description**
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTPROVREQD

Attribute	**Description**
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PROVSNGFREQ

Attribute	Description	
Name	PROVSNGFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,D

TOP

PROVCCYTYP

Attribute	Description	
Name	PROVCCYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,A

TOP

EXPSRCAT

Attribute	Description	
Name	EXPSRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EVNTCLSCD

Attribute	Description	
Name	EVNTCLSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

DRINTUSNGRECV

Attribute	Description
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	Description
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	Description
Name	DRINTNOTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTLIQDAY

Attribute	Description
Name	DRINTLIQDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,A

TOP

CHGSTRTADV

Attribute	**Description**
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCDAYS

Attribute	**Description**
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREBNKNGDAYS

Attribute	**Description**
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDLST

Attribute	**Description**
Name	PRDLST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

CUSATLST

Attribute	Description
Name	CUSATLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	Description
Name	DEF_AUTODEP_AC_CLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

AUTDEPTRNCD

Attribute	Description
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AUTDEPCCY

Attribute	Description
Name	AUTDEPCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBALREQD

Attribute	**Description**
Name	MINBALREQD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPMLTPLOF

Attribute	**Description**
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKDEPOSITFRST

Attribute	**Description**
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDEPDERRATCD

Attribute	**Description**
Name	AUTDEPDERRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOROLL

Attribute	Description
Name	AUTOROLL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSONMATURTY

Attribute	Description
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRTLLIQDTN

Attribute	Description
Name	PRTLLIQDTN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	**Description**
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRACEPRD

Attribute	**Description**
Name	GRACEPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRDAYS

Attribute	**Description**
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRMNTHS

Attribute	**Description**
Name	MINTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXTNRMNTHS

Attribute	Description

Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNRYRS

Attribute	**Description**
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDFLG

Attribute	**Description**
Name	RDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RDMVMATTOUNCLMD

Attribute	**Description**
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MOVEFUNDOVD

Attribute	**Description**
Name	MOVEFUNDOVD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LMTCHKREQD

Attribute	Description	
Name	LMTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OVRDRFTFACLTY

Attribute	Description	
Name	OVRDRFTFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASBKFACLTY

Attribute	Description	
Name	PASBKFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRCKRECBLE

Attribute	Description	
Name	TRCKRECBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCSTATS

Attribute	Description
Name	ACCSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description
Name	EXCLSAMDYRVRTRNSFMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description
Name	ALLWBCKPRDENTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CONSOLDTNREQD

Attribute	Description
Name	CONSOLDTNREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ICINCLSN

Attribute	Description
Name	ICINCLSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRCKACCREDIC

Attribute	Description
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

HASDRCRADV

Attribute	Description
Name	HASDRCRADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ILMAPPLICBL

Attribute	Description
Name	ILMAPPLICBL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATMFACLTY

Attribute	Description
Name	ATMFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENINTRIMSTMNT

Attribute	Description
Name	GENINTRIMSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

GENBALRPT

Attribute	Description	
Name	GENBALRPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTRIMRPTSNCE

Attribute	Description	
Name	INTRIMRPTSNCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	942,941,940,

TOP

INTRIMRPTTYP

Attribute	Description	
Name	INTRIMRPTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,S,T,

TOP

BALRPTSINCE

Attribute	Description	
Name	BALRPTSINCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	941,940,950,

TOP

BALRPTTYP

Attribute	Description
Name	BALRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STMNTPARAM1

Attribute	Description
Name	STMNTPARAM1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM2

Attribute	Description
Name	STMNTPARAM2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM3

Attribute	Description
Name	STMNTPARAM3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

ESCROWPROCESS

Attribute	Description
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNCODE

Attribute	Description
Name	TRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNREVCODE

Attribute	Description
Name	TRNREVCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINOR_MAJOR

Attribute	Description
Name	MINOR_MAJOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description	
Name	REPL_CUST_SIG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description	
Name	MAX_NO_CHEQUE_REJECTIONS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SAL_BLK_DAYS

Attribute	Description	
Name	SAL_BLK_DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description	
Name	DAYSUNAUTHNOACTIVITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description
Name	SETTLE_BRIDGE_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PCTXNCODE

Attribute	Description
Name	PCTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TDRATECHARTALLOW

Attribute	Description
Name	TDRATECHARTALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLUSTER_ID

Attribute	Description
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

PROJECTACCNT

Attribute	Description
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	Description
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

LRGDRBALFLG

Attribute	**Description**	
Name	LRGDRBALFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DAYLIGHTLIMIT

Attribute	**Description**	
Name	DAYLIGHTLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNOVR_CODE

Attribute	**Description**	
Name	TRNOVR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FREQUENCY

Attribute	**Description**	
Name	FREQUENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	D,W,M,Q,H,Y,

TOP

DAYS

Attribute	Description	
Name	DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SEND_NOTIFICATION

Attribute	Description	
Name	SEND_NOTIFICATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	Description	
Name	RT_CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SPDANLSYS

Attribute	Description	
Name	SPDANLSYS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description

Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	**Description**
Name	COMP_WISE_TRACKING_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENABLE_SWEEP_IN

Attribute	**Description**
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	**Description**
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEPACCCLS

Attribute	**Description**
Name	DEPACCCLS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

RATECHARTTENOR

Attribute	Description	
Name	RATECHARTTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

HOLIDAYCALENDAR

Attribute	Description	
Name	HOLIDAYCALENDAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	Description	
Name	HOLIDAYMOVEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	Description	
Name	MOVEACROSSMONTHS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	A,S,N,

TOP

ADHOCHOL

Attribute	Description	
Name	ADHOCHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description	
Name	APPLICABLEDEPTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description	
Name	MONTHENDDEPOSIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DENM_DEPOSIT

Attribute	Description	
Name	DENM_DEPOSIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description
Name	REPCKUPACCLSTNRONROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFERREDBALUPD

Attribute	Description
Name	DEFERREDBALUPD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MULTICURRENCY

Attribute	Description
Name	MULTICURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MONTHS_C

Attribute	Description
Name	MONTHS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

INSTBASIS

Attribute	Description
Name	INSTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NOTICE_DEPOSIT

Attribute	Description
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	Description
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTICE_DAYS

Attribute	Description
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BONUS_INTEREST_C

Attribute	Description
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TRANSACTION_CODE

Attribute	Description
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	Description
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UNCLAIMED_DAYS

Attribute	Description
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NC_DEPOSIT_C

Attribute	Description
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Status-Master

Attribute	Description	
Name	Status-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CR_CB

Attribute	Description	
Name	CR_CB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CR_LINE

Attribute	Description	
Name	CR_LINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CR_HO

Attribute	Description	
Name	CR_HO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DR_CB

Attribute	Description
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DR_LINE

Attribute	Description
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DR_HO

Attribute	Description
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TXTSTATDESC

Attribute	Description
Name	TXTSTATDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Status-Detail

Attribute	Description
Name	Status-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	**Description**
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	**Description**
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Status-Derivation

Attribute	**Description**
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCCLS

Attribute	**Description**
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	6

TOP

SEQNO

Attribute	Description	
Name	SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

STATRUL1

Attribute	Description	
Name	STATRUL1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

STATRUL2

Attribute	Description	
Name	STATRUL2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

STATRUL3

Attribute	Description
Name	STATRUL3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

STATRUL4

Attribute	Description
Name	STATRUL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

STATRUL5

Attribute	Description
Name	STATRUL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

COMPONENT_PRIORITY1

Attribute	Description
Name	COMPONENT_PRIORITY1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	**Description**
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	**Description**
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BLCKNGORDR

Attribute	**Description**
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRTXN

Attribute	Description

Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Transaction-Codes

Attribute	**Description**
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TXNCD

Attribute	**Description**
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNDESC

Attribute	**Description**
Name	TRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRTXN

Attribute	**Description**
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Branch-Restriction

Attribute	**Description**
Name	Branch-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Restriction

Attribute	Description
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Interim-Cramt

Attribute	Description
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	Description
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MANDATORY

Attribute	**Description**
Name	MANDATORY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	**Description**
Name	Sttms-Accls-Minmax-Amt-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MIN_AMOUNT

Attribute	**Description**
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Denom-Deposit

Attribute	Description	
Name	Denom-Deposit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DENOMINATION_ID

Attribute	Description	
Name	DENOMINATION_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

DENOMINATION_DESC

Attribute	Description	
Name	DENOMINATION_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

DENOMINATION_VALUE

Attribute	Description	
Name	DENOMINATION_VALUE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	Description
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	Description
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYIN

Attribute	**Description**
Name	PAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_PAYOUT_C

Attribute	**Description**
Name	INT_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRI_PAYOUT_C

Attribute	**Description**
Name	PRI_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Exrate-Pref

Attribute	**Description**
Name	Exrate-Pref
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PAYINOUT_C

Attribute	Description	
Name	PAYINOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,O

TOP

MODE_TYPE_C

Attribute	Description	
Name	MODE_TYPE_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,S

TOP

RATETYPE_C

Attribute	Description	
Name	RATETYPE_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

TOP

RATECODE_C

Attribute	Description	
Name	RATECODE_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

TOP

VARIANCE_C

Attribute	Description
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	Description
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHANNDESC

Attribute	Description
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	**Description**
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	**Description**
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	**Description**
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_DAY

Attribute	**Description**
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_MONTH

Attribute	**Description**
Name	DORM_PREP_MONTH
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

Misaccdflt

Attribute	Description

Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	**Description**
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	**Description**
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	**Description**
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	**Description**
Name	MISCODE5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCODE6

Attribute	Description
Name	MISCODE6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE7

Attribute	Description
Name	MISCODE7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE8

Attribute	Description
Name	MISCODE8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE9

Attribute	Description
Name	MISCODE9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE3

Attribute	Description
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE4

Attribute	Description
Name	COSTCODE4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE5

Attribute	Description
Name	COSTCODE5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ACCLASS

Attribute	Description
Name	ACCLASS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

MISGROUP

Attribute	Description
Name	MISGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS4

Attribute	**Description**
Name	MISCLASS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS5

Attribute	**Description**
Name	MISCLASS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS6

Attribute	**Description**
Name	MISCLASS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS7

Attribute	**Description**
Name	MISCLASS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Status-Control

Attribute	Description
Name	Status-Control
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.79.2.ST-DeleteAccClasMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-IO*
    - *ACCCLS*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Account-Class-Master-IO

Attribute	Description
Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

2.79.3.ST-DeleteAccClasMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-Full*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *ACCTYPE*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*
    - *ACCSTMNTTYPT*
    - *ACCSTMNTCYCL3*
    - *OFFLNLMT*

AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS
DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS

MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE
BALRPTTYP
STARTDT
STMNTPARAM1

STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT
INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN

ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*
- *DR_CB*
- *DR_LINE*
- *DR_HO*

- *RBKPROVSN*
- *STAT*
- *TXTSTATDESC*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation
- *ACCCLS*
- *SEQNO*
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint
- *BLCKNGORDR*
- *PRDCD*
- *PRDDESC*

Products
- *PRDCD*
- *PRDDESC*
- *DRTXN*
- *CRTXN*

Transaction-Codes
- *TXNCD*
- *TRNDESC*
- *DRTXN*
- *CRTXN*

Branch-Restriction
- *BRNCD*

Ccy-Restriction
- *CCYCD*

Ccy-Preferences
- *CCYCD*
- *MINBAL*
- *ATMCSHLMT*
- *ATMTRNSLMT*
- *TRUSTACCASHLIMIT*

MINIMUM_OPENING_BALANCE
ACCOUNT_OPENING_CHARGES
THRESHOLD_AMOUNT
Cat-Restriction
CUSTCAT
Cust-Restriction
CUSTNO
ALLWD
Interim-Dramt
CCY
AMT
Interim-Cramt
CCY
AMT
Msg-Gentime
GENTIM
Msg-Gentime1
GENTIM
Notice-Pref
ADVINTREQD
MNTHLYFREEAMT
NOTCPRD
VALDITYPRD
Aclass-Doctype
CUSTOMER_TYPE
DOCUMENT_TYPE
MANDATORY
Sttms-Accls-Minmax-Amt-Ccy
CCY
MIN_AMOUNT
MAX_AMOUNT
TOPUP_UNITS
Dep-Accls-Rest
AC_CLASS
ADESC
Denom-Deposit
DENOMINATION_ID
DENOMINATION_DESC
DENOMINATION_VALUE
CURRENCY
Deposit-Ccy-Pref
ACCCCY
Deposit-Ccy-Pref-Dtl
CURRENCY

PAYIN

INT_PAYOUT_C

PRI_PAYOUT_C

Exrate-Pref

PAYINOUT_C

MODE_TYPE_C

RATETYPE_C

RATECODE_C

VARIANCE_C

Chan-Rest-C

CHANLID

CHANNDESC

Minmax-Ccy-C

CURR

CHANLID

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dorm-Param

ACCOUNT_CLASS

LCY_BALANCE

FREQUENCY

DORM_PREP_SEL_METH

DORM_PREP_DATE

DORM_PREP_NTH

DORM_PREP_DAY

DORM_PREP_MONTH

DORM_PREP_ACTION

DORM_PROC_SEL_METH

DORM_PROC_DATE

DORM_PROC_NTH

DORM_PROC_DAY

DORM_PROC_MONTH

DORM_GL

DORM_TRN_CODE

DORM_ADV_GEN

DORM_STOP_IC

UDFDETAILS

FLDNAM

FLDVAL

Misaccdflt

MISCODE2

MISCODE3

MISCODE4

MISCODE5
MISCODE6
MISCODE7
MISCODE8
MISCODE9
MISCODE10
COSTCODE1
COSTCODE2
COSTCODE3
COSTCODE4
COSTCODE5
ACCLASS
MISGROUP
POOLCODE
MISCODE1
MISCLASS1
MISCLASS2
MISCLASS3
MISCLASS4
MISCLASS5
MISCLASS6
MISCLASS7
MISCLASS8
MISCLASS9
MISCLASS10
LINKTOGROUP
Status-Control
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Account-Class-Master-Full

Attribute	Description
Name	Account-Class-Master-Full
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCCD

Attribute	**Description**
Name	ACCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ENDDT

Attribute	**Description**
Name	ENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRMNCY

Attribute	**Description**
Name	DRMNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACSTFORMT

Attribute	**Description**
Name	ACSTFORMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

DRMNTPRM

Attribute	Description
Name	DRMNTPRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description
Name	ACCSTMNTCYCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	Description
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	Description
Name	ACCSTMNTCYCL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	Description
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,D

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,A

TOP

EXPSRCAT

Attribute	Description
Name	EXPSRCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

EVNTCLSCD

Attribute	Description
Name	EVNTCLSCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

DRINTUSNGRECV

Attribute	**Description**
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	**Description**
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	**Description**
Name	DRINTNOTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTLIQDAY

Attribute	**Description**
Name	DRINTLIQDAY
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DRINTLIQDMODE

Attribute	Description	
Name	DRINTLIQDMODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,A

TOP

CHGSTRTADV

Attribute	Description	
Name	CHGSTRTADV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCDAYS

Attribute	Description	
Name	ADVCDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREBNKNGDAYS

Attribute	Description	
Name	FREBNKNGDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDLST

Attribute	Description
Name	PRDLST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

CUSATLST

Attribute	**Description**	
Name	CUSATLST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	**Description**	
Name	DEF_AUTODEP_AC_CLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

AUTDEPTRNCD

Attribute	**Description**	
Name	AUTDEPTRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AUTDEPCCY

Attribute	Description
Name	AUTDEPCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBALREQD

Attribute	Description
Name	MINBALREQD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEPMLTPLOF

Attribute	Description
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKDEPOSITFRST

Attribute	Description
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTDEPDERRATCD

Attribute	Description
Name	AUTDEPDERRATCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOROLL

Attribute	**Description**	
Name	AUTOROLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLSONMATURTY

Attribute	**Description**	
Name	CLSONMATURTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRTLLIQDTN

Attribute	**Description**	
Name	PRTLLIQDTN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	**Description**	
Name	ALLWPRTLIQAMTBLK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	Description
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GRACEPRD

Attribute	Description
Name	GRACEPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNRDAYS

Attribute	Description
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNRMNTHS

Attribute	Description
Name	MINTNRMNTHS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXTNRMNTHS

Attribute	Description
Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRYRS

Attribute	Description
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDFLG

Attribute	Description
Name	RDFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RDMVMATTOUNCLMD

Attribute	Description
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MOVEFUNDOVD

Attribute	Description
Name	MOVEFUNDOVD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCHKREQD

Attribute	Description
Name	LMTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVRDRFTFACLTY

Attribute	Description
Name	OVRDRFTFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASBKFACLTY

Attribute	Description
Name	PASBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECBLE

Attribute	Description
Name	TRCKRECBLE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCSTATS

Attribute	Description
Name	ACCSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description
Name	EXCLSAMDYRVRTRNSFMSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description
Name	ALLWBCKPRDENTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONSOLDTNREQD

Attribute	Description
Name	CONSOLDTNREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ICINCLSN

Attribute	Description	
Name	ICINCLSN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRCKACCREDIC

Attribute	Description	
Name	TRCKACCREDIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

HASDRCRADV

Attribute	Description	
Name	HASDRCRADV	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ACSTATDEPST

Attribute	Description	
Name	ACSTATDEPST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ILMAPPLICBL

Attribute	Description
Name	ILMAPPLICBL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ATMFACLTY

Attribute	Description
Name	ATMFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNT

Attribute	Description
Name	GENINTRIMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENBALRPT

Attribute	**Description**
Name	GENBALRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRIMRPTSNCE

Attribute	**Description**
Name	INTRIMRPTSNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	**Description**
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	**Description**
Name	BALRPTSINCE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	941,940,950,

TOP

BALRPTTYP

Attribute	Description	
Name	BALRPTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,S,T,

TOP

STARTDT

Attribute	Description	
Name	STARTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STMNTPARAM1

Attribute	Description	
Name	STMNTPARAM1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM2

Attribute	Description	
Name	STMNTPARAM2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM3

Attribute	Description
Name	STMNTPARAM3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

ESCROWPROCESS

Attribute	Description
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNCODE

Attribute	Description
Name	TRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNREVCODE

Attribute	Description
Name	TRNREVCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINOR_MAJOR

Attribute	Description
Name	MINOR_MAJOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description
Name	REPL_CUST_SIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description
Name	MAX_NO_CHEQUE_REJECTIONS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SAL_BLK_DAYS

Attribute	Description
Name	SAL_BLK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description
Name	DAYSUNAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description	
Name	SETTLE_BRIDGE_GL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRDCAT

Attribute	Description	
Name	PRDCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PCTXNCODE

Attribute	Description	
Name	PCTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TDRATECHARTALLOW

Attribute	Description	
Name	TDRATECHARTALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLUSTER_ID

Attribute	**Description**
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PROJECTACCNT

Attribute	**Description**
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	**Description**
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	**Description**
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

LRGDRBALFLG

Attribute	Description
Name	LRGDRBALFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description
Name	DAYLIGHTLIMIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRNOVR_CODE

Attribute	Description
Name	TRNOVR_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DAYS

Attribute	**Description**
Name	DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEND_NOTIFICATION

Attribute	**Description**
Name	SEND_NOTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	**Description**
Name	RT_CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SPDANLSYS

Attribute	**Description**
Name	SPDANLSYS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description
Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	Description
Name	COMP_WISE_TRACKING_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_SWEEP_IN

Attribute	Description
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	Description
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEPACCCLS

Attribute	Description
Name	DEPACCCLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

RATECHARTTENOR

Attribute	Description
Name	RATECHARTTENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

HOLIDAYCALENDAR

Attribute	Description
Name	HOLIDAYCALENDAR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	Description
Name	HOLIDAYMOVEMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	Description
Name	MOVEACROSSMONTHS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,N,

TOP

ADHOCHOL

Attribute	**Description**
Name	ADHOCHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	**Description**
Name	APPLICABLEDEPTENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,D,

TOP

MONTHENDDEPOSIT

Attribute	**Description**
Name	MONTHENDDEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENM_DEPOSIT

Attribute	**Description**
Name	DENM_DEPOSIT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description	
Name	REPCKUPACCLSTNRONROLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFERREDBALUPD

Attribute	Description	
Name	DEFERREDBALUPD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MULTICURRENCY

Attribute	Description	
Name	MULTICURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MONTHS_C

Attribute	Description	
Name	MONTHS_C	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: A,D

TOP

INSTBASIS

Attribute	Description
Name	INSTBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: A,L

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_DEPOSIT

Attribute	**Description**
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	**Description**
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICE_DAYS

Attribute	**Description**
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BONUS_INTEREST_C

Attribute	**Description**
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRANSACTION_CODE

Attribute	Description
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	Description
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UNCLAIMED_DAYS

Attribute	**Description**
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NC_DEPOSIT_C

Attribute	**Description**
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Status-Master

Attribute	Description
Name	Status-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CR_CB

Attribute	Description
Name	CR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CR_LINE

Attribute	Description
Name	CR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CR_HO

Attribute	Description
Name	CR_HO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_CB

Attribute	**Description**
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_LINE

Attribute	**Description**
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DR_HO

Attribute	**Description**
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RBKPROVSN

Attribute	**Description**
Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TXTSTATDESC

Attribute	Description
Name	TXTSTATDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Status-Detail

Attribute	Description
Name	Status-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Status-Derivation

Attribute	Description
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCLS

Attribute	Description
Name	ACCCLS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SEQNO

Attribute	**Description**
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATRUL1

Attribute	**Description**
Name	STATRUL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL2

Attribute	**Description**
Name	STATRUL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL3

Attribute	Description	
Name	STATRUL3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL4

Attribute	Description	
Name	STATRUL4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL5

Attribute	Description	
Name	STATRUL5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

COMPONENT_PRIORITY1

Attribute	Description	
Name	COMPONENT_PRIORITY1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	Description
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	Description
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BLCKNGORDR

Attribute	Description
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRTXN

Attribute	**Description**
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Transaction-Codes

Attribute	**Description**
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNCD

Attribute	**Description**
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRNDESC

Attribute	Description
Name	TRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRTXN

Attribute	Description
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	Description
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Restriction

Attribute	Description
Name	Branch-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Restriction

Attribute	**Description**
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	**Description**
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interim-Cramt

Attribute	**Description**
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	**Description**
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	Description	
Name	Sttms-Accls-Minmax-Amt-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Denom-Deposit

Attribute	Description
Name	Denom-Deposit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DENOMINATION_ID

Attribute	Description
Name	DENOMINATION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

DENOMINATION_DESC

Attribute	Description
Name	DENOMINATION_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

DENOMINATION_VALUE

Attribute	Description

Name	DENOMINATION_VALUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	**Description**
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	**Description**
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PAYIN

Attribute	Description	
Name	PAYIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INT_PAYOUT_C

Attribute	Description	
Name	INT_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRI_PAYOUT_C

Attribute	Description	
Name	PRI_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Exrate-Pref

Attribute	Description
Name	Exrate-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAYINOUT_C

Attribute	Description
Name	PAYINOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O

TOP

MODE_TYPE_C

Attribute	Description
Name	MODE_TYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S

TOP

RATETYPE_C

Attribute	Description
Name	RATETYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RATECODE_C

Attribute	Description

Name	RATECODE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

VARIANCE_C

Attribute	**Description**
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	**Description**
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHANLID

Attribute	**Description**
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHANNDESC

Attribute	**Description**
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	Description
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	Description
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_DAY

Attribute	Description
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

Misaccdflt

Attribute	Description
Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	Description
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	Description
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	Description
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	Description
Name	MISCODE5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE6

Attribute	**Description**
Name	MISCODE6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE7

Attribute	**Description**
Name	MISCODE7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE8

Attribute	**Description**
Name	MISCODE8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE9

Attribute	**Description**
Name	MISCODE9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE3

Attribute	Description
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE4

Attribute	Description	
Name	COSTCODE4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE5

Attribute	Description	
Name	COSTCODE5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCLASS

Attribute	Description	
Name	ACCLASS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

TOP

MISGROUP

Attribute	Description	
Name	MISGROUP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS4

Attribute	Description
Name	MISCLASS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Status-Control

Attribute	Description	
Name	Status-Control	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Account-Class-Master-PK*
      - *ACCCLS*
    - *Account-Class-Master-IO*
      - *ACCCLS*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Account-Class-Master-PK

Attribute	Description
Name	Account-Class-Master-PK
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

Account-Class-Master-IO

Attribute	Description
Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.80.DeleteBranch

DeleteBranch

2.80.1.ST-DeleteBranch-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*

BRNADDR
BRNADDR2
BRNADDR3
SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC

EXTVAL
BRNAVALSTAT
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH

CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description	
Name	PRNTBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REGNLOFC

Attribute	**Description**
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TIMLVL

Attribute	**Description**
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CNTRYCD

Attribute	**Description**
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

FUNDBRNCH

Attribute	Description
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODATMBRN

Attribute	Description
Name	CODATMBRN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CODINSTID

Attribute	Description
Name	CODINSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNADDR3

Attribute	Description
Name	BRNADDR3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SWFTADDR

Attribute	Description
Name	SWFTADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

OFFSTHRS

Attribute	**Description**
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OFFSTMIN

Attribute	**Description**
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDOFINP

Attribute	**Description**
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PCCLRGBRN

Attribute	**Description**
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CONVGL

Attribute	Description
Name	CONVGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONVTXNCD

Attribute	Description
Name	CONVTXNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CURRCYCLE

Attribute	Description
Name	CURRCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLGBRNCD

Attribute	Description
Name	CLGBRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRBRN

Attribute	Description
Name	CLRBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTRYCDDESC

Attribute	**Description**
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SUSPGLSLDESC

Attribute	**Description**
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CONTSUSPGLSLDESC

Attribute	**Description**
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SUSPGLFCYDESC

Attribute	**Description**
Name	SUSPGLFCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CONTSUSPGLFCYDESC

Attribute	Description
Name	CONTSUSPGLFCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ATMSUSPGLDESC

Attribute	Description
Name	ATMSUSPGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVGLDESC

Attribute	Description
Name	CONVGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVTXNCDDESC

Attribute	Description
Name	CONVTXNCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EXTVAL

Attribute	Description
Name	EXTVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNAVALSTAT

Attribute	Description
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CLRACC

Attribute	**Description**
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OFFSTCLRACC

Attribute	**Description**
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

WEEKHOL1

Attribute	**Description**
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	**Description**
Name	WEELHOL2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description	
Name	CLRBNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MISCCYMISMATCHGRP

Attribute	Description	
Name	MISCCYMISMATCHGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

INTERDICTCHKREQD

Attribute	Description	
Name	INTERDICTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTERDICTTIMOUT

Attribute	Description	
Name	INTERDICTTIMOUT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENTGL

Attribute	Description
Name	ENTGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	Description
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALDAYS

Attribute	Description
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	Description
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 500

TOP

DRPRDDESC

Attribute	Description
Name	DRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CRPRDDESC

Attribute	Description
Name	CRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRTAXCYCLE

Attribute	Description
Name	CURRTAXCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONSOLTXCERTREQD

Attribute	Description
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	Description
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SUSENTRYREQ

Attribute	Description
Name	SUSENTRYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUSBATCHNO

Attribute	Description
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SUSTXNCODE

Attribute	Description
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVSUSENTRYDAYS

Attribute	Description
Name	REVSUSENTRYDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CASAAMTBLKTRNCODE

Attribute	**Description**
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOFFREQ

Attribute	**Description**
Name	HOFFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWCORPACS

Attribute	**Description**
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFER_TYPE

Attribute	**Description**
Name	TRANSFER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R,

TOP

POSITION_ASSET_GL

Attribute	Description
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	Description
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GL_CLASSS

Attribute	Description
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	Description
Name	CHEQUESTALEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FILECONSTXNCODE

Attribute	Description	
Name	FILECONSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CNTRY_CKSUM_MASK

Attribute	Description	
Name	CNTRY_CKSUM_MASK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Branch-Swift-Address

Attribute	Description
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SWFTADRS

Attribute	Description
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYDESC

Attribute	**Description**
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Message-Type

Attribute	**Description**
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE

Attribute	**Description**
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

LCYMSGTYP

Attribute	**Description**
Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	S,M,P,

TOP

Dup-Chk

Attribute	Description
Name	Dup-Chk
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MODULE1

Attribute	Description
Name	MODULE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

DUP_FLG

Attribute	Description
Name	DUP_FLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DUP_DAY

Attribute	Description
Name	DUP_DAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Account-Params

Attribute	Description

Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACCMSK

Attribute	**Description**
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHKSUMALGO

Attribute	**Description**
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	**Description**
Name	STRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTACCALG

Attribute	Description	
Name	CUSTACCALG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTNOALG

Attribute	Description	
Name	CUSTNOALG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FNDSTACNO

Attribute	Description	
Name	FNDSTACNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FNDEDACNO

Attribute	Description	
Name	FNDEDACNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Branch-Details-IO
BRNCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

2.80.3.ST-DeleteBranch-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*
    - *BRNADDR*
    - *BRNADDR2*
    - *BRNADDR3*

SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC
EXTVAL
BRNAVALSTAT
NETSUSPGL

WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS

TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
- *BRNCD*
- *CUSTACCMSK*

CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description

Name	PRNTBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGNLOFC

Attribute	**Description**
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TIMLVL

Attribute	**Description**
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRYCD

Attribute	**Description**
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

FUNDBRNCH

Attribute	Description	
Name	FUNDBRNCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNLCY

Attribute	Description	
Name	BRNLCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CODATMBRN

Attribute	Description	
Name	CODATMBRN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CODINSTID

Attribute	Description	
Name	CODINSTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR2

Attribute	Description	
Name	BRNADDR2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR3

Attribute	Description	
Name	BRNADDR3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SWFTADDR

Attribute	Description	
Name	SWFTADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

TELEXADDR

Attribute	Description	
Name	TELEXADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	Description
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	Description
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	Description
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SUSPGLSL

Attribute	**Description**	
Name	SUSPGLSL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONTSUSPGLSL

Attribute	**Description**	
Name	CONTSUSPGLSL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SUSPGLFCY

Attribute	**Description**	
Name	SUSPGLFCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONTSUSPGLFCY

Attribute	**Description**	
Name	CONTSUSPGLFCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ATMSUSPGL

Attribute	Description	
Name	ATMSUSPGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONVGL

Attribute	Description	
Name	CONVGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONVTXNCD

Attribute	Description	
Name	CONVTXNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CURRCYCLE

Attribute	Description	
Name	CURRCYCLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFSTMNTSTAT

Attribute	**Description**	
Name	DEFSTMNTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

GEN

Attribute	**Description**	
Name	GEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,

TOP

GEN103P

Attribute	**Description**	
Name	GEN103P	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFBNKOPCD

Attribute	**Description**	
Name	DEFBNKOPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	4

TOP

PROCWITHOUTFLOAT

Attribute	Description	
Name	PROCWITHOUTFLOAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLGBRNCD

Attribute	Description	
Name	CLGBRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECTORCD

Attribute	Description	
Name	SECTORCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CLRBRN

Attribute	Description	
Name	CLRBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNTRYCDDESC

Attribute	Description
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLSLDESC

Attribute	Description
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONTSUSPGLSLDESC

Attribute	Description
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLFCYDESC

Attribute	Description
Name	SUSPGLFCYDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONTSUSPGLFCYDESC

Attribute	**Description**	
Name	CONTSUSPGLFCYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ATMSUSPGLDESC

Attribute	**Description**	
Name	ATMSUSPGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVGLDESC

Attribute	**Description**	
Name	CONVGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVTXNCDDESC

Attribute	**Description**	
Name	CONVTXNCDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

EXTVAL

Attribute	Description	
Name	EXTVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNAVALSTAT

Attribute	Description	
Name	BRNAVALSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NETSUSPGL

Attribute	Description	
Name	NETSUSPGL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

WALKINCUST

Attribute	Description	
Name	WALKINCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description
Name	CLRBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

MISCCYMISMATCHGRP

Attribute	Description
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

INTERDICTCHKREQD

Attribute	Description
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTERDICTTIMOUT

Attribute	Description
Name	INTERDICTTIMOUT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ENTGL

Attribute	Description	
Name	ENTGL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

BCKVALCHKREQD

Attribute	Description	
Name	BCKVALCHKREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

BCKVALDAYS

Attribute	Description	
Name	BCKVALDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TRCKPREVYRPRLS

Attribute	Description	
Name	TRCKPREVYRPRLS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LDAPTEMP

Attribute	**Description**
Name	LDAPTEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

DRPRDDESC

Attribute	**Description**
Name	DRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CRPRDDESC

Attribute	**Description**
Name	CRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRTAXCYCLE

Attribute	**Description**
Name	CURRTAXCYCLE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONSOLTXCERTREQD

Attribute	Description	
Name	CONSOLTXCERTREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description	
Name	INDIVTAXVERTREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TAXCERTFREQ

Attribute	Description	
Name	TAXCERTFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,Y,

TOP

FREQVAL

Attribute	Description	
Name	FREQVAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SUSENTRYREQ

Attribute	Description	
Name	SUSENTRYREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SUSBATCHNO

Attribute	Description	
Name	SUSBATCHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SUSTXNCODE

Attribute	Description	
Name	SUSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVSUSENTRYDAYS

Attribute	Description	
Name	REVSUSENTRYDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_TYPE

Attribute	Description
Name	TRANSFER_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,

TOP

POSITION_ASSET_GL

Attribute	**Description**
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	**Description**
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GL_CLASSS

Attribute	**Description**
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	**Description**
Name	CHEQUESTALEDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRY_CKSUM_MASK

Attribute	Description
Name	CNTRY_CKSUM_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Branch-Swift-Address

Attribute	**Description**
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Message-Type

Attribute	Description
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

LCYMSGTYP

Attribute	Description

Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,M,P,

TOP

Dup-Chk

Attribute	**Description**
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MODULE1

Attribute	**Description**
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

DUP_FLG

Attribute	**Description**
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUP_DAY

Attribute	**Description**
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	Description
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	Description
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	Description
Name	STRTACCNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDACCNO

Attribute	**Description**
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	**Description**
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDAUTOACCFLG

Attribute	**Description**
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOSTRTACCNO

Attribute	**Description**
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Branch-Details-PK*
      - *BRNCD*
    - *Branch-Details-IO*
      - *BRNCD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Branch-Details-PK

Attribute	Description
Name	Branch-Details-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.81.DeleteBranchTrfr

DeleteBranchTrfr

2.81.1.ST-DeleteBranchTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Brn-Transfer-Full

Attribute	Description

Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TD_REQ

Attribute	Description

Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	**Description**
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	**Description**
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>Name</td><td>AUTHSTAT</td></tr>
<tr><td>Datatype</td><td>String</td></tr>
<tr><td>Description</td><td></td></tr>
<tr><td>Attributes</td><td>
<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table>
</td></tr>
<tr><td>Restrictions</td><td>
<table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>maxLength</td><td>1</td></tr>
</table>
</td></tr>
</table>

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Brn-Transfer-IO
TRANSFER_ID

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

2.81.3.ST-DeleteBranchTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Brn-Transfer-Full

Attribute	Description
Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description	
Name	TARGET_BRANCH_CODESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TD_REQ

Attribute	Description
Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	Description
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	Description
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Sttms-Brn-Transfer-IO*
      - *TRANSFER_ID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Brn-Transfer-PK

Attribute	Description
Name	Sttms-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.82.DeleteCardAccount

Deletion of Card Accounts Detail

2.82.1.ST-DeleteCardAccount-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CardAccount-Full*
    - *BRNCODE*
    - *CUSTACNO*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the detail about card account.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.82.2.ST-DeleteCardAccount-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CardAccount-IO*
    - *BRNCODE*
    - *CUSTACNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates the information about card account

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

2.82.3.ST-DeleteCardAccount-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CardAccount-IO*
      - *BRNCODE*
      - *CUSTACNO*
    - *CardAccount-Full*
      - *BRNCODE*
      - *CUSTACNO*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates the information about card account

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicate Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the detail abount the card information

TOP

BRNCODE

Attribute	Description

Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String

Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Contract Authorize details is atleast Authorized Once .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	UDF Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.82.4.ST-DeleteCardAccount-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CardAccount-IO*
      - *BRNCODE*
      - *CUSTACNO*
    - *CardAccount-PK*
      - *BRNCODE*
      - *CUSTACNO*
    - *CardAccount-Full*
      - *BRNCODE*
      - *CUSTACNO*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates card account information.

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicate Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CardAccount-PK

Attribute	Description
Name	CardAccount-PK

Datatype	
Description	it indicates the primary key of card account.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the detail about card account.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO

Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String

Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 8
	pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.83.DeleteCardMaster

DeleteCardMaster

2.83.1.ST-DeleteCardMaster-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*

CREDIT_CARD_LIMIT
PRIMARY_CARD
CARD_APPL_DATE
CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CARD_PRODUCT

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CARD_BIN

Attribute	Description	
Name	CARD_BIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OWNER_ID_NO1

Attribute	Description
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADD_HOLDER_IDNO

Attribute	Description
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

OWNER_ID_TYPE

Attribute	Description
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ISSUER

Attribute	Description	
Name	ISSUER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PLASTIC_TYPE

Attribute	Description	
Name	PLASTIC_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CREDIT_CARD_LIMIT

Attribute	Description	
Name	CREDIT_CARD_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CARD_APPL_DATE

Attribute	Description
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	Description
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

CARD_STATUS

Attribute	Description

Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	**Description**
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OPERATION

Attribute	**Description**
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BILL_CYCLE

Attribute	**Description**
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	Description
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	Description
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	Description
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 19

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DEL_CHNL_PIN

Attribute	**Description**
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ADDL_HOLDER_DOB

Attribute	**Description**
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDL_HOLDER_RELATION

Attribute	**Description**
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DR_CR_INDICATOR

Attribute	**Description**
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	D,C

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Debit-Card-Master-IO
CUST_NO
CUST_AC_NO
BRANCH_CODE
REQ_REF_NO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	**Description**
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.83.3.ST-DeleteCardMaster-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*
    - *CREDIT_CARD_LIMIT*
    - *PRIMARY_CARD*
    - *CARD_APPL_DATE*

CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR

ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NAME_ON_CARD

Attribute	**Description**
Name	NAME_ON_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OWNER_ID_NO1

Attribute	**Description**
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

ADD_HOLDER_IDNO

Attribute	**Description**
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

OWNER_ID_TYPE

Attribute	**Description**
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CARD_APPL_DATE

Attribute	**Description**
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	**Description**
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	**Description**
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

CARD_STATUS

Attribute	**Description**
Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	**Description**
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LAST_OPERATION

Attribute	**Description**
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BILL_CYCLE

Attribute	**Description**
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	**Description**
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	**Description**
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	**Description**
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	**Description**
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	19

TOP

DEL_CHNL_CARD

Attribute	Description	
Name	DEL_CHNL_CARD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

DEL_CHNL_PIN

Attribute	Description	
Name	DEL_CHNL_PIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

ADDL_HOLDER_DOB

Attribute	Description	
Name	ADDL_HOLDER_DOB	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

ADDL_HOLDER_RELATION

Attribute	Description	
Name	ADDL_HOLDER_RELATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DR_CR_INDICATOR

Attribute	Description
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,C

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.83.4.ST-DeleteCardMaster-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Debit-Card-Master-PK*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *CUST_NO*
      - *CUST_AC_NO*
    - *Sttms-Debit-Card-Master-IO*
      - *CUST_NO*
      - *CUST_AC_NO*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Debit-Card-Master-PK

Attribute	Description
Name	Sttms-Debit-Card-Master-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description	
Name	REQ_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.84.QueryCustTrfr

QueryCustTrfr

2.84.1.ST-QueryCustTrfr-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-IO*
    - *TRANSFER_ID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

2.84.2.ST-QueryCustTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cust-Brn-Transfer-IO*
      - *TRANSFER_ID*
    - *Cust-Brn-Transfer-Full*
      - *TRANSFER_MORTGAGES_MODULE*
      - *TRANSFER_CASA*
      - *CURRENT_BRANCH_CODE*
      - *TARGET_BRANCH_CODESS*
      - *TRANSFER_DATE*
      - *TRANSFER_ID*
      - *TRANSFER_LENDING_MODULE*
      - *TRANSFER_ISLAMIC_FINANCING_MODULE*
      - *CUSTOMER_ID*
      - *TRANSFER_TERM_DEPOSITS*
      - *TARGET_BRANCH*
      - *CURRENT_BRANCH*
      - *TXT_CUSTNAME*
      - *MAKER*
      - *MAKERSTAMP*

CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Cust-Brn-Transfer-Full

Attribute	Description
Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description	
Name	TRANSFER_MORTGAGES_MODULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFER_CASA

Attribute	**Description**
Name	TRANSFER_CASA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	**Description**
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	**Description**
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRANSFER_DATE

Attribute	**Description**
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	**Description**
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	**Description**
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	**Description**
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.85.QueryDealer

Query of Dealer

2.85.1.ST-QueryDealer-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Dealer-IO*
    - *DEALER_ID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttms-Dealer-IO

Attribute	Description
Name	Sttms-Dealer-IO
Datatype	
Description	It indicates the IO type of the Dealer Maintenance.

TOP

DEALER_ID

Attribute	Description	
Name	DEALER_ID	
Datatype	String	
Description	Indicates Dealer Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.85.2.ST-QueryDealer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Dealer-IO*
      - *DEALER_ID*
    - *Sttms-Dealer-Full*
      - *DEALER_ID*
      - *DEALER_NAME*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Dealer-IO

Attribute	Description
Name	Sttms-Dealer-IO
Datatype	
Description	It indicates IO type of the Query Dealer.

TOP

DEALER_ID

Attribute	Description	
Name	DEALER_ID	
Datatype	String	
Description	Indicates Dealer Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttms-Dealer-Full

Attribute	Description
Name	Sttms-Dealer-Full
Datatype	
Description	It indicates full details of the Query Dealer.

TOP

DEALER_ID

Attribute	Description	
Name	DEALER_ID	
Datatype	String	
Description	Indicates Dealer Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DEALER_NAME

Attribute	Description

Name	DEALER_NAME
Datatype	String
Description	Indicates Dealer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String

Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 8
	pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.86.QueryExtDeal

Query External Deal

2.86.1.ST-QueryExtDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ext-Deal-Link-IO*
    - *FCREFERENCE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ext-Deal-Link-IO

Attribute	Description
Name	Ext-Deal-Link-IO
Datatype	
Description	

TOP

FCREFERENCE

Attribute	Description	
Name	FCREFERENCE	
Datatype	String	
Description	Indicates the Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

2.86.2.ST-QueryExtDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ext-Deal-Link-IO*
      - *FCREFERENCE*
    - *Ext-Deal-Link-Full*
      - *DL_BOOK_DT1*
      - *DL_EXP_DT1*
      - *ACCCCY*
      - *EQ_AMT1*
      - *ACCOUNT_NUMBER*
      - *FCREFERENCE*
      - *EXTDLREF1*
      - *REKEYOFDEALAMOUNT*
      - *EXCHANGERATE*
      - *REKEYOFDEALCURRENCY*
      - *PRDREMRKS*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ext-Deal-Link-IO

Attribute	Description
Name	Ext-Deal-Link-IO
Datatype	
Description	

TOP

FCREFERENCE

Attribute	Description	
Name	FCREFERENCE	
Datatype	String	
Description	Indicates the Flexcube Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Ext-Deal-Link-Full

Attribute	Description
Name	Ext-Deal-Link-Full
Datatype	
Description	

TOP

DL_BOOK_DT1

Attribute	Description	
Name	DL_BOOK_DT1	
Datatype	Date	
Description	Indicates the Deal Booking Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DL_EXP_DT1

Attribute	Description
Name	DL_EXP_DT1
Datatype	Date
Description	Indicates the Deal Expiry Date
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates the Account Currency
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

EQ_AMT1

Attribute	Description
Name	EQ_AMT1
Datatype	Number
Description	Indicates the Equivalent Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	Indicates the Account Number
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 20

TOP

FCREFERENCE

Attribute	Description
Name	FCREFERENCE
Datatype	String
Description	Indicates the Flexcube Reference Number

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EXTDLREF1

Attribute	**Description**
Name	EXTDLREF1
Datatype	String
Description	Indicates the External Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REKEYOFDEALAMOUNT

Attribute	**Description**
Name	REKEYOFDEALAMOUNT
Datatype	Number
Description	Indicates the Deal Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXCHANGERATE

Attribute	**Description**
Name	EXCHANGERATE
Datatype	Number
Description	Indicates the Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYOFDEALCURRENCY

Attribute	**Description**
Name	REKEYOFDEALCURRENCY
Datatype	String
Description	Indicates the Deal Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDREMRKS

Attribute	Description
Name	PRDREMRKS
Datatype	String
Description	Indicates the Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker Identification
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker Identification
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	Indicates the Checker Date Stamp
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number i.e. the number of times the record has been modified
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Record Status Open :O Closed :C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status Authorized :A UnAuthorized :U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.87.QueryJointHolderMaint

Query Joint Holder Maintenance

2.87.1.ST-QueryJointHolderMaint-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Acc-Joint-IO
ACCOUNT_BRANCH
ACCOUNT_NUMBER

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Acc-Joint-IO

Attribute	Description
Name	Acc-Joint-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

2.87.2.ST-QueryJointHolderMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Acc-Joint-IO*
      - *ACCOUNT_BRANCH*
      - *ACCOUNT_NUMBER*
    - *Acc-Joint-Full*
      - *ACCOUNT_BRANCH*
      - *ACCOUNT_NUMBER*
      - *CUST_NO*
      - *ACCTYPE*
      - *OPMODE*
      - *ACCOUNT_CURRENCY*
      - *AC_DESC*
      - *CUSTNAME1*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*

AUTHSTAT

Acc-Joint-Holder

CUSTOMER_NUMBER

CUSTOMER_NAME

JNTHLDTYP

START_DATE

END_DATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Acc-Joint-IO

Attribute	Description
Name	Acc-Joint-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCOUNT_NUMBER

Attribute	Description	
Name	ACCOUNT_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Acc-Joint-Full

Attribute	Description

Name	Acc-Joint-Full
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCOUNT_NUMBER

Attribute	Description
Name	ACCOUNT_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,J

TOP

OPMODE

Attribute	Description
Name	OPMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,J,E,F,M,

TOP

ACCOUNT_CURRENCY

Attribute	Description
Name	ACCOUNT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTNAME1

Attribute	Description
Name	CUSTNAME1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Acc-Joint-Holder

Attribute	Description
Name	Acc-Joint-Holder
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NUMBER

Attribute	Description
Name	CUSTOMER_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTOMER_NAME

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

JNTHLDTYP

Attribute	Description
Name	JNTHLDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUS,CON,GUR,CUS,DEV,GUA,JAF,JAO,JOF,JOO,NOM,REL,SOL,SOW,THR,TRU,VAL,POA

TOP

START_DATE

Attribute	Description
Name	START_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

END_DATE

Attribute	Description
Name	END_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.88.QueryLocMaint

Query of Location Maintenance

2.88.1.ST-QueryLocMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Location-IO*
    - *LOCCODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Querying Input Only type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.88.2.ST-QueryLocMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Location-IO*
      - *LOCCODE*
    - *Sttm-Location-Full*
      - *LOCCODE*
      - *DESCRIPTION*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Location-IO

Attribute	Description
Name	Sttm-Location-IO
Datatype	
Description	Includes Location Maintenance Querying Input Only type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Location-Full

Attribute	Description
Name	Sttm-Location-Full
Datatype	
Description	Includes Location Maintenance Querying Full type details

TOP

LOCCODE

Attribute	Description	
Name	LOCCODE	
Datatype	String	
Description	Indicates the location Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DESCRIPTION

Attribute	Description

Name	DESCRIPTION
Datatype	String
Description	Indicates the document description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.89.QueryManStatChangInp

Query of Manual Status Change

2.89.1.ST-QueryManStatChangInp-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Ac-Stat-Change-IO*
    - *CUSTACNO*
    - *BRANCHCODE*
    - *STATUSCHANGEDATE*
    - *SEQNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Querying Input Only type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

2.89.2.ST-QueryManStatChangInp-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Ac-Stat-Change-IO*
      - *CUSTACNO*
      - *BRANCHCODE*
      - *STATUSCHANGEDATE*
      - *SEQNO*
    - *Sttm-Ac-Stat-Change-Full*
      - *CUSTACNO*
      - *ACCSTATUS*
      - *BRANCHCODE*
      - *BRANCHNAME*
      - *STATUSCHANGEDATE*
      - *SEQNO*
      - *STATUS*
      - *ACSTATNODR*
      - *ACSTATNOCR*
      - *ACSTATFROZEN*
      - *ACSTATDEPOST*
      - *ACSTATCHGAUTO*

DORMANT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Ac-Stat-Change-IO

Attribute	Description
Name	Sttm-Ac-Stat-Change-IO
Datatype	
Description	Includes Manual Status Change Input Querying Input Only type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

Sttm-Ac-Stat-Change-Full

Attribute	Description
Name	Sttm-Ac-Stat-Change-Full
Datatype	
Description	Includes Manual Status Change Input Querying Full type details

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ACCSTATUS

Attribute	Description	
Name	ACCSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCHNAME

Attribute	Description
Name	BRANCHNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

STATUSCHANGEDATE

Attribute	Description
Name	STATUSCHANGEDATE
Datatype	Date
Description	

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ORACLE

TOP

ACSTATNODR

Attribute	Description
Name	ACSTATNODR
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: N,Y

TOP

ACSTATNOCR

Attribute	Description
Name	ACSTATNOCR
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: N,Y

TOP

ACSTATFROZEN

Attribute	Description
Name	ACSTATFROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: N,Y

TOP

ACSTATDEPOST

Attribute	Description
Name	ACSTATDEPOST
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: N,Y

TOP

ACSTATCHGAUTO

Attribute	Description
Name	ACSTATCHGAUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.90.QueryManStatChange

QueryManStatChange

2.90.1.ST-QueryManStatChange-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Ac-Stat-Change-IO*
    - *CUST_AC_NO*
    - *BRANCH*
    - *SINCE*
    - *SEQ_NO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.90.2.ST-QueryManStatChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Ac-Stat-Change-IO*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
    - *Sttms-Ac-Stat-Change-Full*
      - *CUST_AC_NO*
      - *BRANCH*
      - *SINCE*
      - *SEQ_NO*
      - *NEWSTAT*
      - *ACSTATNDR1*
      - *AC_STAT_NO_CR*
      - *AC_STAT_FROZEN*
      - *AC_STAT_DE_POST*
      - *AC_STAT_CHG_AUTO*
      - *DORMANT*
      - *BRNNAME*

FROM_STATUS
NO_DR
ACSTATNCR
ACSTATFRZN
ACSTATDEPST
STATCHNGAUTMATIC
DORM
AC_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Ac-Stat-Change-IO

Attribute	Description
Name	Sttms-Ac-Stat-Change-IO
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Sttms-Ac-Stat-Change-Full

Attribute	Description
Name	Sttms-Ac-Stat-Change-Full
Datatype	
Description	

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

SINCE

Attribute	Description
Name	SINCE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SEQ_NO

Attribute	Description
Name	SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWSTAT

Attribute	Description
Name	NEWSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACSTATNDR1

Attribute	Description
Name	ACSTATNDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AC_STAT_NO_CR

Attribute	Description
Name	AC_STAT_NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AC_STAT_FROZEN

Attribute	Description
Name	AC_STAT_FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AC_STAT_DE_POST

Attribute	Description
Name	AC_STAT_DE_POST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AC_STAT_CHG_AUTO

Attribute	Description
Name	AC_STAT_CHG_AUTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FROM_STATUS

Attribute	Description
Name	FROM_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATNCR

Attribute	Description
Name	ACSTATNCR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATFRZN

Attribute	Description
Name	ACSTATFRZN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DORM

Attribute	Description
Name	DORM

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AC_DESC

Attribute	**Description**
Name	AC_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.91.QueryNoticePRD

Query of Notice Period Maintenance

2.91.1.ST-QueryNoticePRD-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Notice-Period-IO*
    - *NOTICEID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Query Notice Period.

TOP

NOTICEID

Attribute	Description	
Name	NOTICEID	
Datatype	String	
Description	Indicates Notice Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.91.2.ST-QueryNoticePRD-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Notice-Period-IO*
      - *NOTICEID*
    - *Notice-Period-Full*
      - *BRANCHCODE*
      - *CUSTACNO*
      - *INITIATIONDATE*
      - *ACTIVATIONDATE*
      - *VALIDITYPERIOD*
      - *ENDDATE*
      - *NOTICEAMT*
      - *NOTICEID*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Notice-Period-IO

Attribute	Description
Name	Notice-Period-IO
Datatype	
Description	It indicates the IO type of the Notice Period Maintenance.

TOP

NOTICEID

Attribute	Description	
Name	NOTICEID	
Datatype	String	
Description	Indicates Notice Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Notice-Period-Full

Attribute	Description
Name	Notice-Period-Full
Datatype	
Description	It indicates Full Details of the Notice Period Maintenance.

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Indicates Branch Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicates Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INITIATIONDATE

Attribute	Description
Name	INITIATIONDATE
Datatype	Date
Description	Indicates Initiation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATIONDATE

Attribute	Description
Name	ACTIVATIONDATE
Datatype	Date
Description	Indicates Activation Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALIDITYPERIOD

Attribute	Description
Name	VALIDITYPERIOD
Datatype	Number
Description	Indicates Validity Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDATE

Attribute	Description
Name	ENDDATE

Datatype	Date
Description	Indicates End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEAMT

Attribute	Description
Name	NOTICEAMT
Datatype	Number
Description	Indicates Notice Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICEID

Attribute	Description
Name	NOTICEID
Datatype	String
Description	Indicates Notice Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.92.QueryOnlineCharge

QueryOnlineCharge

2.92.1.ST-QueryOnlineCharge-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-IO*
    - *SOURCE*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHARGE_EVENT

Attribute	**Description**
Name	CHARGE_EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	**Description**
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

2.92.2.ST-QueryOnlineCharge-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Onlinecharge-Master-IO*
      - *SOURCE*
      - *Onlinecharge-Detail*
        - *CHARGE_EVENT*
        - *CHARGE_PRODUCT*
        - *ACTION*
    - *Onlinecharge-Master-Full*
      - *SOURCE*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *Onlinecharge-Detail*
        - *CHARGE_EVENT*
        - *CHARGE_PRODUCT*

ACTION

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

Onlinecharge-Detail

Attribute	Description	
Name	Onlinecharge-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHARGE_EVENT

Attribute	Description	
Name	CHARGE_EVENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CHARGE_PRODUCT

Attribute	Description
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

Onlinecharge-Master-Full

Attribute	Description
Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Onlinecharge-Detail

Attribute	**Description**
Name	Onlinecharge-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHARGE_EVENT

Attribute	**Description**
Name	CHARGE_EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	**Description**
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	4

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.93.QuerySTDSTCDM

QuerySTDSTCDM

2.93.1.ST-QuerySTDSTCDM-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-IO*
    - *BRANCH_CODE*
    - *CUST_AC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

2.93.2.ST-QuerySTDSTCDM-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Crdrstat-IO*
      - *BRANCH_CODE*
      - *CUST_AC*
    - *Crdrstat-Full*
      - *BRANCH_CODE*
      - *CUST_AC*
      - *NODEBIT*
      - *NOCREDIT*
      - *POSTALLOWED*
      - *REMARKS*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description	
Name	CUST_AC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Crdrstat-Full

Attribute	Description
Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE

Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUST_AC

Attribute	**Description**
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NODEBIT

Attribute	**Description**
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOCREDIT

Attribute	**Description**
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

POSTALLOWED

Attribute	**Description**
Name	POSTALLOWED
Datatype	String

Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String

Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.94.QuerySTDSTDOR

QuerySTDSTDOR

2.94.1.ST-QuerySTDSTDOR-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-IO*
    - *ACCOUNT_BRANCH*
    - *AC_NO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

AC_NO

Attribute	Description
Name	AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

2.94.2.ST-QuerySTDSTDOR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Status-IO*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
    - *Status-Full*
      - *REVERSE_MOVEMENT_PARAM*
      - *REMARKS*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
      - *NO_DR*
      - *NO_CR*
      - *FROZEN*
      - *DORMANT*
      - *AC_DESC*
      - *ACCOUNT_CCY*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AC_NO

Attribute	Description	
Name	AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Status-Full

Attribute	Description
Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCOUNT_CCY

Attribute	**Description**
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.95.QuerySTTypeMnt

Query of Card Type Maintenance

2.95.1.ST-QuerySTTypeMnt-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *St-Debit-Card-Type-IO*
    - *CARDTYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Include information about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

2.95.2.ST-QuerySTTypeMnt-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *St-Debit-Card-Type-IO*
      - *CARDTYPE*
    - *St-Debit-Card-Type-Full*
      - *CARDTYPE*
      - *DESCRIPTION*
      - *CARDBIN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *St-Debit-Card-Type-Detail*
        - *CARDTYPE*
        - *CARDBIN1*
      - *UDFDETAILS*

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

St-Debit-Card-Type-IO

Attribute	Description
Name	St-Debit-Card-Type-IO
Datatype	
Description	Includes information about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

St-Debit-Card-Type-Full

Attribute	Description
Name	St-Debit-Card-Type-Full
Datatype	
Description	Includes Full deatails about debit card type.

TOP

CARDTYPE

Attribute	Description	
Name	CARDTYPE	
Datatype	String	
Description	Indicates Card Type	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CARDBIN

Attribute	**Description**
Name	CARDBIN
Datatype	String
Description	Indicates Card Bin
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

St-Debit-Card-Type-Detail

Attribute	Description
Name	St-Debit-Card-Type-Detail
Datatype	
Description	Debit Card Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CARDTYPE

Attribute	Description
Name	CARDTYPE
Datatype	String
Description	Indicates Card Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CARDBIN1

Attribute	Description

Name	CARDBIN1
Datatype	String
Description	Card Bin 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.96.QueryServiceRequest

2.96.1.ST-QueryServiceRequest-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Service-Request-Details-IO*
    - *SERVICE_NUM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Service-Request-Details-IO

Attribute	Description
Name	Service-Request-Details-IO
Datatype	
Description	

TOP

SERVICE_NUM

Attribute	Description	
Name	SERVICE_NUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.96.2.ST-QueryServiceRequest-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Service-Request-Details-IO*
      - *SERVICE_NUM*
    - *Service-Request-Details-Full*
      - *SUBJECT*
      - *ACTDATE*
      - *PRIORITY*
      - *STATUS*
      - *REQUESTER_TYPE*
      - *NATURE*
      - *CRITERIA*
      - *SNAME*
      - *TEL*
      - *EMAIL*
      - *MOBILE_NUMBER*
      - *FNAME*
      - *SERVICE_NUM*
      - *CUST_AC_NO*
      - *CUSTOMER_NO*

SERV_REQ_TYPE

BRANCH_CODE

CONTACT_DATE

TARGET_DATE

DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Service-Request-Details-IO

Attribute	Description
Name	Service-Request-Details-IO
Datatype	
Description	

TOP

SERVICE_NUM

Attribute	Description	
Name	SERVICE_NUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Service-Request-Details-Full

Attribute	Description
Name	Service-Request-Details-Full
Datatype	
Description	

TOP

SUBJECT

Attribute	Description
Name	SUBJECT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / High,Medium,Low

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,P,C,X

TOP

REQUESTER_TYPE

Attribute	Description
Name	REQUESTER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,W

TOP

NATURE

Attribute	Description
Name	NATURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Sales,Service

TOP

CRITERIA

Attribute	Description
Name	CRITERIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Enquiry,Channel,Product,Application ,Maintenance

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates the Short Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TEL

Attribute	Description

Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	This gives the Customer email address
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MOBILE_NUMBER

Attribute	**Description**
Name	MOBILE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FNAME

Attribute	**Description**
Name	FNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SERVICE_NUM

Attribute	**Description**
Name	SERVICE_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description	Indicates the Customer Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

SERV_REQ_TYPE

Attribute	Description	
Name	SERV_REQ_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	TXN,NTX,CMP

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CONTACT_DATE

Attribute	Description
Name	CONTACT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TARGET_DATE

Attribute	Description
Name	TARGET_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.97.QueryTransactionCodes

Static Maintenance

2.97.1.ST-QueryTransactionCodes-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Code-IO*
    - *TRN_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Transaction-Code-IO

Attribute	Description
Name	Transaction-Code-IO
Datatype	
Description	Includes Transaction Code Maintenance Querying Input Only type details

TOP

TRN_CODE

Attribute	Description
Name	TRN_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs / Description: 1
Restrictions	Restrictions: maxLength / Description: 3

TOP

2.97.2.ST-QueryTransactionCodes-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transaction-Code-IO*
      - *TRN_CODE*
    - *Transaction-Code-Full*
      - *TRN_CODE*
      - *TRN_DESC*
      - *SWFTCD*
      - *MIS_HEAD*
      - *AVL_INFO*
      - *INTRADAY_RELEASE*
      - *CHEQUE_MANDATORY*
      - *IC_TXN_COUNT*
      - *IC_TOVER_INCLUSION*
      - *CONSIDER_FOR_ACTIVITY*
      - *AVALBALREQD*
      - *IC_PENALTY*
      - *IC_BAL_INCLUSION*
      - *INTERBRANCH_IN_LCY*
      - *STMT_DT_BASIS*

ACUMEN_TRN_CODE

ANTI_MONEY_LAUND_REQD

PRDCAT

DAYS_SS

EXEMPT_ADV_INTEREST

TRNOVER_LMT_INCLUSION

ESCROW_PROCESSING

SALARY_CREDIT

BAL_UPDATE_THRU_PPC

CONSIDER_COVER_ACC

EXTERNAL_CODE

COMPON_TYPE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transaction-Code-IO

Attribute	Description
Name	Transaction-Code-IO
Datatype	
Description	Includes Transaction Code Maintenance Querying Input Only type details

TOP

TRN_CODE

Attribute	Description
Name	TRN_CODE
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

TOP

Transaction-Code-Full

Attribute	Description
Name	Transaction-Code-Full
Datatype	
Description	Includes Transaction Code Maintenance Querying Full type details

TOP

TRN_CODE

Attribute	Description	
Name	TRN_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRN_DESC

Attribute	Description	
Name	TRN_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SWFTCD

Attribute	Description	
Name	SWFTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MIS_HEAD

Attribute	Description
Name	MIS_HEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AVL_INFO

Attribute	**Description**
Name	AVL_INFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,V,N,A

TOP

INTRADAY_RELEASE

Attribute	**Description**
Name	INTRADAY_RELEASE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHEQUE_MANDATORY

Attribute	**Description**
Name	CHEQUE_MANDATORY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

IC_TXN_COUNT

Attribute	**Description**
Name	IC_TXN_COUNT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IC_TOVER_INCLUSION

Attribute	**Description**
Name	IC_TOVER_INCLUSION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONSIDER_FOR_ACTIVITY

Attribute	**Description**
Name	CONSIDER_FOR_ACTIVITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AVALBALREQD

Attribute	**Description**
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IC_PENALTY

Attribute	**Description**
Name	IC_PENALTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

IC_BAL_INCLUSION

Attribute	**Description**
Name	IC_BAL_INCLUSION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTERBRANCH_IN_LCY

Attribute	**Description**
Name	INTERBRANCH_IN_LCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMT_DT_BASIS

Attribute	**Description**
Name	STMT_DT_BASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,P

TOP

ACUMEN_TRN_CODE

Attribute	**Description**
Name	ACUMEN_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ANTI_MONEY_LAUND_REQD

Attribute	Description
Name	ANTI_MONEY_LAUND_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DAYS_SS

Attribute	Description
Name	DAYS_SS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXEMPT_ADV_INTEREST

Attribute	Description
Name	EXEMPT_ADV_INTEREST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNOVER_LMT_INCLUSION

Attribute	Description
Name	TRNOVER_LMT_INCLUSION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ESCROW_PROCESSING

Attribute	**Description**
Name	ESCROW_PROCESSING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SALARY_CREDIT

Attribute	**Description**
Name	SALARY_CREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y,B

TOP

BAL_UPDATE_THRU_PPC

Attribute	**Description**
Name	BAL_UPDATE_THRU_PPC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONSIDER_COVER_ACC

Attribute	**Description**
Name	CONSIDER_COVER_ACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTERNAL_CODE

Attribute	Description	
Name	EXTERNAL_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COMPON_TYPE

Attribute	Description	
Name	COMPON_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,I,C

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	Restrictions: maxLength, Description: 105 Restrictions: minLength, Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 150 Restrictions: minLength, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.98.ReopenACRSMaint

ReopenACRSMaint

2.98.1.ST-ReopenACRSMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description

Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCD

Attribute	Description
Name	BRANCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREEQUENCY

Attribute	Description
Name	FREEQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,S,A

TOP

STARTMON

Attribute	Description
Name	STARTMON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LASTEXEDATE

Attribute	Description
Name	LASTEXEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	**Description**	
Name	CHARGEBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	**Description**	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

2.98.2.ST-ReopenACRSMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-IO*
    - *REFERENCENO*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

2.98.3.ST-ReopenACRSMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description
Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCD

Attribute	Description	
Name	BRANCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date

Attributes	Attribute	Description
	minOccurs	0

TOP

FREEQUENCY

Attribute	Description	
Name	FREEQUENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,S,A

TOP

STARTMON

Attribute	Description	
Name	STARTMON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description	
Name	STARTON	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

LASTEXEDATE

Attribute	Description	
Name	LASTEXEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

E-STATEMENT

Attribute	Description

Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the Transaction Status O - Open C - Close	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Auto-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Auto-Crs-Master-IO*
      - *REFERENCENO*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Auto-Crs-Master-PK

Attribute	Description
Name	Sttm-Auto-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.99.ReopenBranch

ReopenBranch

2.99.1.ST-ReopenBranch-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*

BRNADDR
BRNADDR2
BRNADDR3
SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC

EXTVAL
BRNAVALSTAT
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH

CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
  SWFTADRS
  DESC
Branch-Customer-Params
  STRTCUSTNO
  ENDCUSTNO
  STRTDUMMYCUSTNO
  ENDDUMMYCUSTNO
  START_PID_NO
  END_PID_NO
Branch-Functions
  FUNCID
Branch-Ccy
  CCYCD
  CCYDESC
Branch-Message-Type
  MODULE
  LCYMSGTYP
Dup-Chk
  MODULE1
  DUP_FLG
  DUP_DAY

Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description	
Name	PRNTBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

REGNLOFC

Attribute	Description
Name	REGNLOFC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TIMLVL

Attribute	Description
Name	TIMLVL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTRYCD

Attribute	Description
Name	CNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CIDIF

Attribute	Description
Name	CIDIF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

FUNDBRNCH

Attribute	Description
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODATMBRN

Attribute	Description
Name	CODATMBRN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CODINSTID

Attribute	Description
Name	CODINSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNADDR3

Attribute	Description
Name	BRNADDR3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SWFTADDR

Attribute	Description
Name	SWFTADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	**Description**
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	**Description**
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	**Description**
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	**Description**
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CONVGL

Attribute	Description
Name	CONVGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONVTXNCD

Attribute	Description
Name	CONVTXNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CURRCYCLE

Attribute	Description
Name	CURRCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLGBRNCD

Attribute	Description
Name	CLGBRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CLRBRN

Attribute	Description
Name	CLRBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNTRYCDDESC

Attribute	**Description**
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SUSPGLSLDESC

Attribute	**Description**
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CONTSUSPGLSLDESC

Attribute	**Description**
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SUSPGLFCYDESC

Attribute	**Description**
Name	SUSPGLFCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CONTSUSPGLFCYDESC

Attribute	Description
Name	CONTSUSPGLFCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ATMSUSPGLDESC

Attribute	Description
Name	ATMSUSPGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVGLDESC

Attribute	Description
Name	CONVGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVTXNCDDESC

Attribute	Description
Name	CONVTXNCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EXTVAL

Attribute	Description
Name	EXTVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNAVALSTAT

Attribute	Description
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRACC

Attribute	**Description**
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	**Description**
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	**Description**
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	**Description**
Name	WEELHOL2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description	
Name	CLRBNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MISCCYMISMATCHGRP

Attribute	Description	
Name	MISCCYMISMATCHGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

INTERDICTCHKREQD

Attribute	Description	
Name	INTERDICTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTERDICTTIMOUT

Attribute	Description	
Name	INTERDICTTIMOUT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENTGL

Attribute	Description
Name	ENTGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BCKVALCHKREQD

Attribute	Description
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BCKVALDAYS

Attribute	Description
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRCKPREVYRPRLS

Attribute	Description
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRPRD

Attribute	**Description**
Name	DRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CRPRD

Attribute	**Description**
Name	CRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

IBANMSKBNKCD

Attribute	**Description**
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

IBANMSKACCNO

Attribute	**Description**
Name	IBANMSKACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 500

TOP

DRPRDDESC

Attribute	Description
Name	DRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CRPRDDESC

Attribute	Description
Name	CRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRTAXCYCLE

Attribute	Description
Name	CURRTAXCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONSOLTXCERTREQD

Attribute	Description
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	Description
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SUSENTRYREQ

Attribute	Description
Name	SUSENTRYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUSBATCHNO

Attribute	Description
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SUSTXNCODE

Attribute	Description
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVSUSENTRYDAYS

Attribute	Description
Name	REVSUSENTRYDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CASAAMTBLKTRNCODE

Attribute	**Description**
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOFFREQ

Attribute	**Description**
Name	HOFFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWCORPACS

Attribute	**Description**
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFER_TYPE

Attribute	**Description**
Name	TRANSFER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	P,R,

TOP

POSITION_ASSET_GL

Attribute	Description	
Name	POSITION_ASSET_GL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

POSITION_LIABILITY_GL

Attribute	Description	
Name	POSITION_LIABILITY_GL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

GL_CLASSS

Attribute	Description	
Name	GL_CLASSS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CHEQUESTALEDAYS

Attribute	Description	
Name	CHEQUESTALEDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FILECONSTXNCODE

Attribute	Description	
Name	FILECONSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CNTRY_CKSUM_MASK

Attribute	Description	
Name	CNTRY_CKSUM_MASK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Branch-Swift-Address

Attribute	Description
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SWFTADRS

Attribute	Description
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYDESC

Attribute	**Description**
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Message-Type

Attribute	**Description**
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MODULE

Attribute	**Description**
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

LCYMSGTYP

Attribute	**Description**
Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	S,M,P,

TOP

Dup-Chk

Attribute	Description	
Name	Dup-Chk	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MODULE1

Attribute	Description	
Name	MODULE1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

TOP

DUP_FLG

Attribute	Description	
Name	DUP_FLG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DUP_DAY

Attribute	Description	
Name	DUP_DAY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Account-Params

Attribute	Description

Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACCMSK

Attribute	**Description**
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHKSUMALGO

Attribute	**Description**
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	**Description**
Name	STRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTACCALG

Attribute	Description	
Name	CUSTACCALG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTNOALG

Attribute	Description	
Name	CUSTNOALG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FNDSTACNO

Attribute	Description	
Name	FNDSTACNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FNDEDACNO

Attribute	Description	
Name	FNDEDACNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-IO*
    - *BRNCD*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.99.3.ST-ReopenBranch-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*
    - *BRNADDR*
    - *BRNADDR2*
    - *BRNADDR3*

SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC
EXTVAL
BRNAVALSTAT
NETSUSPGL

WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS

TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
- *BRNCD*
- *CUSTACCMSK*

CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description

Name	PRNTBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGNLOFC

Attribute	**Description**
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TIMLVL

Attribute	**Description**
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRYCD

Attribute	**Description**
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

FUNDBRNCH

Attribute	**Description**
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNLCY

Attribute	**Description**
Name	BRNLCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CODATMBRN

Attribute	**Description**
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CODINSTID

Attribute	**Description**
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR2

Attribute	Description	
Name	BRNADDR2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR3

Attribute	Description	
Name	BRNADDR3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SWFTADDR

Attribute	Description	
Name	SWFTADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

TELEXADDR

Attribute	Description	
Name	TELEXADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	Description
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	Description
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	Description
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SUSPGLSL

Attribute	**Description**	
Name	SUSPGLSL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONTSUSPGLSL

Attribute	**Description**	
Name	CONTSUSPGLSL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SUSPGLFCY

Attribute	**Description**	
Name	SUSPGLFCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONTSUSPGLFCY

Attribute	**Description**	
Name	CONTSUSPGLFCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ATMSUSPGL

Attribute	Description	
Name	ATMSUSPGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONVGL

Attribute	Description	
Name	CONVGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONVTXNCD

Attribute	Description	
Name	CONVTXNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CURRCYCLE

Attribute	Description	
Name	CURRCYCLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFSTMNTSTAT

Attribute	Description	
Name	DEFSTMNTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

GEN

Attribute	Description	
Name	GEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,

TOP

GEN103P

Attribute	Description	
Name	GEN103P	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFBNKOPCD

Attribute	Description	
Name	DEFBNKOPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	4

TOP

PROCWITHOUTFLOAT

Attribute	Description	
Name	PROCWITHOUTFLOAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CLGBRNCD

Attribute	Description	
Name	CLGBRNCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

SECTORCD

Attribute	Description	
Name	SECTORCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CLRBRN

Attribute	Description	
Name	CLRBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNTRYCDDESC

Attribute	Description
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLSLDESC

Attribute	Description
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONTSUSPGLSLDESC

Attribute	Description
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLFCYDESC

Attribute	Description
Name	SUSPGLFCYDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONTSUSPGLFCYDESC

Attribute	Description	
Name	CONTSUSPGLFCYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ATMSUSPGLDESC

Attribute	Description	
Name	ATMSUSPGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVGLDESC

Attribute	Description	
Name	CONVGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVTXNCDDESC

Attribute	Description	
Name	CONVTXNCDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

EXTVAL

Attribute	Description
Name	EXTVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNAVALSTAT

Attribute	Description
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description
Name	CLRBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

MISCCYMISMATCHGRP

Attribute	Description
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

INTERDICTCHKREQD

Attribute	Description
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTERDICTTIMOUT

Attribute	Description
Name	INTERDICTTIMOUT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ENTGL

Attribute	Description	
Name	ENTGL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

BCKVALCHKREQD

Attribute	Description	
Name	BCKVALCHKREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

BCKVALDAYS

Attribute	Description	
Name	BCKVALDAYS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TRCKPREVYRPRLS

Attribute	Description	
Name	TRCKPREVYRPRLS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LDAPTEMP

Attribute	**Description**
Name	LDAPTEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

DRPRDDESC

Attribute	**Description**
Name	DRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CRPRDDESC

Attribute	**Description**
Name	CRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRTAXCYCLE

Attribute	**Description**
Name	CURRTAXCYCLE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CONSOLTXCERTREQD

Attribute	**Description**
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	**Description**
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	**Description**
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	**Description**
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SUSENTRYREQ

Attribute	Description	
Name	SUSENTRYREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SUSBATCHNO

Attribute	Description	
Name	SUSBATCHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SUSTXNCODE

Attribute	Description	
Name	SUSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVSUSENTRYDAYS

Attribute	Description	
Name	REVSUSENTRYDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRANSFER_TYPE

Attribute	Description
Name	TRANSFER_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,

TOP

POSITION_ASSET_GL

Attribute	**Description**
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	**Description**
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GL_CLASSS

Attribute	**Description**
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	**Description**
Name	CHEQUESTALEDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRY_CKSUM_MASK

Attribute	Description
Name	CNTRY_CKSUM_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Branch-Swift-Address

Attribute	Description
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SWFTADRS

Attribute	Description
Name	SWFTADRS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Message-Type

Attribute	Description
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

LCYMSGTYP

Attribute	Description

Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,P,

TOP

Dup-Chk

Attribute	**Description**
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE1

Attribute	**Description**
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

DUP_FLG

Attribute	**Description**
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DUP_DAY

Attribute	**Description**
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	Description
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	Description
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	Description
Name	STRTACCNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Branch-Details-PK*
      - *BRNCD*
    - *Branch-Details-IO*
      - *BRNCD*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Branch-Details-PK

Attribute	Description
Name	Branch-Details-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.100.ReopenBranchTrfr

ReopenBranchTrfr

2.100.1.ST-ReopenBranchTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Brn-Transfer-Full

Attribute	Description

Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TD_REQ

Attribute	Description

Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	**Description**
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	**Description**
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Brn-Transfer-IO
TRANSFER_ID
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.100.3.ST-ReopenBranchTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Brn-Transfer-Full

Attribute	Description
Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description	
Name	TARGET_BRANCH_CODESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TD_REQ

Attribute	Description
Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	Description
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	Description
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Sttms-Brn-Transfer-IO*
      - *TRANSFER_ID*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Brn-Transfer-PK

Attribute	Description
Name	Sttms-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.101.ReopenCRSRequest

ReopenCRSRequest

2.101.1.ST-ReopenCRSRequest-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Crs-Master-Full

Attribute	Description

Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description
Name	TO_DATE
Datatype	Date
Description	Specifies the To Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Specifies The Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS_DETAILS

Attribute	Description
Name	PROCESS_STATUS_DETAILS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

E-STATEMENT

Attribute	**Description**	
Name	E-STATEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	**Description**	
Name	CHARGEBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	**Description**	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Crs-Master-IO
REFERENCENO
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	totalDigits	22

TOP

2.101.3.ST-ReopenCRSRequest-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Crs-Master-Full

Attribute	Description
Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description	
Name	TO_DATE	
Datatype	Date	
Description	Specifies the To Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	Attribute: minOccurs — Description: 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PROCESS_STATUS_DETAILS

Attribute	Description
Name	PROCESS_STATUS_DETAILS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	Description
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	Description
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the Transaction Status O - Open C - Close	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Crs-Master-IO*
      - *REFERENCENO*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Crs-Master-PK

Attribute	Description
Name	Sttm-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.102.ModifyACRSMaint

Modification of Automatic Consolidated Statement Request

2.102.1.ST-ModifyACRSMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description

Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCD

Attribute	Description
Name	BRANCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREEQUENCY

Attribute	Description
Name	FREEQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,S,A

TOP

STARTMON

Attribute	Description
Name	STARTMON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

LASTEXEDATE

Attribute	Description
Name	LASTEXEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	**Description**	
Name	CHARGEBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	**Description**	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Auto-Crs-Master-IO
REFERENCENO
EFFDATE
FREEQUENCY
STARTMON
STARTON
E-STATEMENT
CHARGEBRANCH
CHARGEACCOUNT
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	Attribute: minOccurs — Description: 0

TOP

FREEQUENCY

Attribute	Description
Name	FREEQUENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,Q,S,A

TOP

STARTMON

Attribute	Description
Name	STARTMON
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

E-STATEMENT

Attribute	Description

Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

2.102.3.ST-ModifyACRSMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-Full*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCD*
    - *EFFDATE*
    - *FREEQUENCY*
    - *STARTMON*
    - *STARTON*
    - *LASTEXEDATE*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description
Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCD

Attribute	Description	
Name	BRANCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date

Attributes	Attribute	Description
	minOccurs	0

TOP

FREEQUENCY

Attribute	Description
Name	FREEQUENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,Q,S,A

TOP

STARTMON

Attribute	Description
Name	STARTMON
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: enumeration — Description: JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

LASTEXEDATE

Attribute	Description
Name	LASTEXEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

E-STATEMENT

Attribute	Description

Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.102.4.ST-ModifyACRSMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Auto-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Auto-Crs-Master-IO*
      - *REFERENCENO*
      - *EFFDATE*
      - *FREEQUENCY*
      - *STARTMON*
      - *STARTON*
      - *E-STATEMENT*
      - *CHARGEBRANCH*
      - *CHARGEACCOUNT*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttm-Auto-Crs-Master-PK

Attribute	Description
Name	Sttm-Auto-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EFFDATE

Attribute	Description	
Name	EFFDATE	
Datatype	Date	
Description	Indicates the Effective Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREEQUENCY

Attribute	Description	
Name	FREEQUENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,S,A

TOP

STARTMON

Attribute	Description	
Name	STARTMON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description	
Name	STARTON	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

E-STATEMENT

Attribute	Description	
Name	E-STATEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	Description

Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.103.ModifyAccClasMaint

Modification of Account Class maintenance

2.103.1.ST-ModifyAccClasMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-Full*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *ACCTYPE*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*

ACCSTMNTTYPT
ACCSTMNTCYCL3
OFFLNLMT
AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS

DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS
MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE

BALRPTTYP
STARTDT
STMNTPARAM1
STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT

INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN
ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*

- *DR_CB*
- *DR_LINE*
- *DR_HO*
- *RBKPROVSN*
- *STAT*
- *TXTSTATDESC*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation

- *ACCCLS*
- *SEQNO*
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint

- *BLCKNGORDR*
- *PRDCD*
- *PRDDESC*

Products

- *PRDCD*
- *PRDDESC*
- *DRTXN*
- *CRTXN*

Transaction-Codes

- *TXNCD*
- *TRNDESC*
- *DRTXN*
- *CRTXN*

Branch-Restriction

- *BRNCD*

Ccy-Restriction

- *CCYCD*

Ccy-Preferences

- *CCYCD*
- *MINBAL*

ATMCSHLMT

ATMTRNSLMT

TRUSTACCASHLIMIT

MINIMUM_OPENING_BALANCE

ACCOUNT_OPENING_CHARGES

THRESHOLD_AMOUNT

Cat-Restriction

CUSTCAT

Cust-Restriction

CUSTNO

ALLWD

Interim-Dramt

CCY

AMT

Interim-Cramt

CCY

AMT

Msg-Gentime

GENTIM

Msg-Gentime1

GENTIM

Notice-Pref

ADVINTREQD

MNTHLYFREEAMT

NOTCPRD

VALDITYPRD

Aclass-Doctype

CUSTOMER_TYPE

DOCUMENT_TYPE

MANDATORY

Sttms-Accls-Minmax-Amt-Ccy

CCY

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dep-Accls-Rest

AC_CLASS

ADESC

Denom-Deposit

DENOMINATION_ID

DENOMINATION_DESC

DENOMINATION_VALUE

CURRENCY

Deposit-Ccy-Pref

- *ACCCCY*
- *Deposit-Ccy-Pref-Dtl*
  - *CURRENCY*
  - *PAYIN*
  - *INT_PAYOUT_C*
  - *PRI_PAYOUT_C*
- *Exrate-Pref*
  - *PAYINOUT_C*
  - *MODE_TYPE_C*
  - *RATETYPE_C*
  - *RATECODE_C*
  - *VARIANCE_C*
- *Chan-Rest-C*
  - *CHANLID*
  - *CHANNDESC*
- *Minmax-Ccy-C*
  - *CURR*
  - *CHANLID*
  - *MIN_AMOUNT*
  - *MAX_AMOUNT*
  - *TOPUP_UNITS*
- *Dorm-Param*
  - *ACCOUNT_CLASS*
  - *LCY_BALANCE*
  - *FREQUENCY*
  - *DORM_PREP_SEL_METH*
  - *DORM_PREP_DATE*
  - *DORM_PREP_NTH*
  - *DORM_PREP_DAY*
  - *DORM_PREP_MONTH*
  - *DORM_PREP_ACTION*
  - *DORM_PROC_SEL_METH*
  - *DORM_PROC_DATE*
  - *DORM_PROC_NTH*
  - *DORM_PROC_DAY*
  - *DORM_PROC_MONTH*
  - *DORM_GL*
  - *DORM_TRN_CODE*
  - *DORM_ADV_GEN*
  - *DORM_STOP_IC*
- *UDFDETAILS*
  - *FLDNAM*
  - *FLDVAL*
- *Misaccdflt*

MISCODE2
MISCODE3
MISCODE4
MISCODE5
MISCODE6
MISCODE7
MISCODE8
MISCODE9
MISCODE10
COSTCODE1
COSTCODE2
COSTCODE3
COSTCODE4
COSTCODE5
ACCLASS
MISGROUP
POOLCODE
MISCODE1
MISCLASS1
MISCLASS2
MISCLASS3
MISCLASS4
MISCLASS5
MISCLASS6
MISCLASS7
MISCLASS8
MISCLASS9
MISCLASS10
LINKTOGROUP
Status-Control

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Account-Class-Master-Full

Attribute	Description
Name	Account-Class-Master-Full
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DESC

Attribute	Description
Name	DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCCD

Attribute	Description
Name	ACCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

DRMNTPRM

Attribute	Description
Name	DRMNTPRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description
Name	ACCSTMNTCYCL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	**Description**
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	**Description**
Name	ACCSTMNTCYCL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	**Description**
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTPROVREQD

Attribute	**Description**
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PROVSNGFREQ

Attribute	Description	
Name	PROVSNGFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,D

TOP

PROVCCYTYP

Attribute	Description	
Name	PROVCCYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,A

TOP

EXPSRCAT

Attribute	Description	
Name	EXPSRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EVNTCLSCD

Attribute	Description	
Name	EVNTCLSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

DRINTUSNGRECV

Attribute	Description
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	Description
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	Description
Name	DRINTNOTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTLIQDAY

Attribute	Description
Name	DRINTLIQDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,A

TOP

CHGSTRTADV

Attribute	**Description**
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVCDAYS

Attribute	**Description**
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREBNKNGDAYS

Attribute	**Description**
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDLST

Attribute	**Description**
Name	PRDLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

CUSATLST

Attribute	Description
Name	CUSATLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	Description
Name	DEF_AUTODEP_AC_CLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

AUTDEPTRNCD

Attribute	Description
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AUTDEPCCY

Attribute	Description
Name	AUTDEPCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBALREQD

Attribute	**Description**
Name	MINBALREQD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPMLTPLOF

Attribute	**Description**
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKDEPOSITFRST

Attribute	**Description**
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDEPDERRATCD

Attribute	**Description**
Name	AUTDEPDERRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOROLL

Attribute	Description
Name	AUTOROLL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSONMATURTY

Attribute	Description
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRTLLIQDTN

Attribute	Description
Name	PRTLLIQDTN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	**Description**
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRACEPRD

Attribute	**Description**
Name	GRACEPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRDAYS

Attribute	**Description**
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRMNTHS

Attribute	**Description**
Name	MINTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXTNRMNTHS

Attribute	Description

Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNRYRS

Attribute	**Description**
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDFLG

Attribute	**Description**
Name	RDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RDMVMATTOUNCLMD

Attribute	**Description**
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MOVEFUNDOVD

Attribute	**Description**
Name	MOVEFUNDOVD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LMTCHKREQD

Attribute	Description	
Name	LMTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OVRDRFTFACLTY

Attribute	Description	
Name	OVRDRFTFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASBKFACLTY

Attribute	Description	
Name	PASBKFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRCKRECBLE

Attribute	Description	
Name	TRCKRECBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCSTATS

Attribute	Description
Name	ACCSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description
Name	EXCLSAMDYRVRTRNSFMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description
Name	ALLWBCKPRDENTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CONSOLDTNREQD

Attribute	Description
Name	CONSOLDTNREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ICINCLSN

Attribute	Description
Name	ICINCLSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRCKACCREDIC

Attribute	Description
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

HASDRCRADV

Attribute	Description
Name	HASDRCRADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	**Description**
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	**Description**
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	**Description**
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	**Description**
Name	STATCHNGAUTMATIC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ILMAPPLICBL

Attribute	Description	
Name	ILMAPPLICBL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ATMFACLTY

Attribute	Description	
Name	ATMFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNT

Attribute	Description	
Name	GENINTRIMSTMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description	
Name	GENINTRIMSTMNTONMVMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

GENBALRPT

Attribute	Description	
Name	GENBALRPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTRIMRPTSNCE

Attribute	Description	
Name	INTRIMRPTSNCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	942,941,940,

TOP

INTRIMRPTTYP

Attribute	Description	
Name	INTRIMRPTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,S,T,

TOP

BALRPTSINCE

Attribute	Description	
Name	BALRPTSINCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	941,940,950,

TOP

BALRPTTYP

Attribute	Description
Name	BALRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STMNTPARAM1

Attribute	Description
Name	STMNTPARAM1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM2

Attribute	Description
Name	STMNTPARAM2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STMNTPARAM3

Attribute	Description
Name	STMNTPARAM3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

ESCROWPROCESS

Attribute	**Description**
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNCODE

Attribute	**Description**
Name	TRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNREVCODE

Attribute	**Description**
Name	TRNREVCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINOR_MAJOR

Attribute	**Description**
Name	MINOR_MAJOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description	
Name	REPL_CUST_SIG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description	
Name	MAX_NO_CHEQUE_REJECTIONS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SAL_BLK_DAYS

Attribute	Description	
Name	SAL_BLK_DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description	
Name	DAYSUNAUTHNOACTIVITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description
Name	SETTLE_BRIDGE_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PCTXNCODE

Attribute	Description
Name	PCTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TDRATECHARTALLOW

Attribute	Description
Name	TDRATECHARTALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLUSTER_ID

Attribute	Description
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PROJECTACCNT

Attribute	Description
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	Description
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

LRGDRBALFLG

Attribute	Description
Name	LRGDRBALFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description
Name	DAYLIGHTLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNOVR_CODE

Attribute	Description
Name	TRNOVR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DAYS

Attribute	**Description**
Name	DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEND_NOTIFICATION

Attribute	**Description**
Name	SEND_NOTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	**Description**
Name	RT_CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SPDANLSYS

Attribute	**Description**
Name	SPDANLSYS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description

Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	**Description**
Name	COMP_WISE_TRACKING_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENABLE_SWEEP_IN

Attribute	**Description**
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	**Description**
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEPACCCLS

Attribute	**Description**
Name	DEPACCCLS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

RATECHARTTENOR

Attribute	**Description**	
Name	RATECHARTTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

HOLIDAYCALENDAR

Attribute	**Description**	
Name	HOLIDAYCALENDAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	**Description**	
Name	HOLIDAYMOVEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	**Description**	
Name	MOVEACROSSMONTHS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	A,S,N,

TOP

ADHOCHOL

Attribute	Description	
Name	ADHOCHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description	
Name	APPLICABLEDEPTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description	
Name	MONTHENDDEPOSIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DENM_DEPOSIT

Attribute	Description	
Name	DENM_DEPOSIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description
Name	REPCKUPACCLSTNRONROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFERREDBALUPD

Attribute	Description
Name	DEFERREDBALUPD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MULTICURRENCY

Attribute	Description
Name	MULTICURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MONTHS_C

Attribute	Description
Name	MONTHS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

INSTBASIS

Attribute	Description
Name	INSTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NOTICE_DEPOSIT

Attribute	Description
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	Description
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTICE_DAYS

Attribute	Description
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BONUS_INTEREST_C

Attribute	Description
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRANSACTION_CODE

Attribute	Description
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	Description
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UNCLAIMED_DAYS

Attribute	Description
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NC_DEPOSIT_C

Attribute	Description
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Status-Master

Attribute	Description	
Name	Status-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CR_CB

Attribute	Description	
Name	CR_CB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CR_LINE

Attribute	Description	
Name	CR_LINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CR_HO

Attribute	Description	
Name	CR_HO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DR_CB

Attribute	Description
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DR_LINE

Attribute	Description
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DR_HO

Attribute	Description
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RBKPROVSN

Attribute	Description
Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TXTSTATDESC

Attribute	Description
Name	TXTSTATDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Status-Detail

Attribute	Description
Name	Status-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCHD

Attribute	**Description**
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	**Description**
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Status-Derivation

Attribute	**Description**
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCCLS

Attribute	**Description**
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	6

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

STATRUL1

Attribute	Description
Name	STATRUL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

STATRUL2

Attribute	Description
Name	STATRUL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

STATRUL3

Attribute	Description
Name	STATRUL3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

STATRUL4

Attribute	Description
Name	STATRUL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

STATRUL5

Attribute	Description
Name	STATRUL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

COMPONENT_PRIORITY1

Attribute	Description
Name	COMPONENT_PRIORITY1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	**Description**
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	**Description**
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BLCKNGORDR

Attribute	**Description**
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRTXN

Attribute	Description

Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Transaction-Codes

Attribute	**Description**
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TXNCD

Attribute	**Description**
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNDESC

Attribute	**Description**
Name	TRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DRTXN

Attribute	Description	
Name	DRTXN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CRTXN

Attribute	Description	
Name	CRTXN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Branch-Restriction

Attribute	Description	
Name	Branch-Restriction	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

Ccy-Restriction

Attribute	Description
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Interim-Cramt

Attribute	Description
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	Description
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MANDATORY

Attribute	**Description**
Name	MANDATORY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	**Description**
Name	Sttms-Accls-Minmax-Amt-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MIN_AMOUNT

Attribute	**Description**
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Denom-Deposit

Attribute	Description	
Name	Denom-Deposit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DENOMINATION_ID

Attribute	Description	
Name	DENOMINATION_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

DENOMINATION_DESC

Attribute	Description	
Name	DENOMINATION_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

DENOMINATION_VALUE

Attribute	Description	
Name	DENOMINATION_VALUE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	Description
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	Description
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CURRENCY

Attribute	Description
Name	CURRENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYIN

Attribute	**Description**
Name	PAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_PAYOUT_C

Attribute	**Description**
Name	INT_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRI_PAYOUT_C

Attribute	**Description**
Name	PRI_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Exrate-Pref

Attribute	**Description**
Name	Exrate-Pref
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PAYINOUT_C

Attribute	Description	
Name	PAYINOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,O

TOP

MODE_TYPE_C

Attribute	Description	
Name	MODE_TYPE_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,S

TOP

RATETYPE_C

Attribute	Description	
Name	RATETYPE_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

TOP

RATECODE_C

Attribute	Description	
Name	RATECODE_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

TOP

VARIANCE_C

Attribute	Description
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	Description
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHANNDESC

Attribute	Description
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 6

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	**Description**
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	**Description**
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	**Description**
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_DAY

Attribute	**Description**
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_MONTH

Attribute	**Description**
Name	DORM_PREP_MONTH
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150 Restrictions: minLength — Description: 0

TOP

Misaccdflt

Attribute	Description

Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	**Description**
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	**Description**
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	**Description**
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	**Description**
Name	MISCODE5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCODE6

Attribute	Description
Name	MISCODE6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE7

Attribute	Description
Name	MISCODE7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE8

Attribute	Description
Name	MISCODE8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE9

Attribute	Description
Name	MISCODE9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE3

Attribute	Description
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE4

Attribute	Description
Name	COSTCODE4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE5

Attribute	Description
Name	COSTCODE5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ACCLASS

Attribute	Description
Name	ACCLASS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

MISGROUP

Attribute	Description
Name	MISGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS4

Attribute	Description	
Name	MISCLASS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS5

Attribute	Description	
Name	MISCLASS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS6

Attribute	Description	
Name	MISCLASS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS7

Attribute	Description	
Name	MISCLASS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Status-Control

Attribute	Description
Name	Status-Control
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.103.2.ST-ModifyAccClasMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-IO*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *STMNTDAY*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*
    - *STMNTDAY2*
    - *ACCSTMNTTYPT*
    - *ACCSTMNTCYCL3*

STMNTDAY3
OFFLNLMT
AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
MINAMT
MAXAMT
GRACEPRD
MINTNRDAYS
MINTNRMNTHS

MINTNRYRS
DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS
MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE

BALRPTTYP
STMNTPARAM1
STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT
INTRATE_CUMAMT_REQD
ENABLE_SWEEP_IN

ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
MONTHEND_INST
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*
- *DR_CB*
- *DR_LINE*
- *DR_HO*
- *STAT*
- *Status-Detail*

Status-Derivation
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*

COMPONENT_PRIORITY3

Product-Maint

BLCKNGORDR

PRDCD

Products

PRDCD

Transaction-Codes

Branch-Restriction

BRNCD

Ccy-Restriction

CCYCD

Ccy-Preferences

CCYCD

MINBAL

ATMCSHLMT

ATMTRNSLMT

TRUSTACCASHLIMIT

MINIMUM_OPENING_BALANCE

ACCOUNT_OPENING_CHARGES

THRESHOLD_AMOUNT

Cat-Restriction

CUSTCAT

Cust-Restriction

CUSTNO

ALLWD

Interim-Dramt

CCY

AMT

Interim-Cramt

CCY

AMT

Msg-Gentime

GENTIM

MSGTYP

SRLNO

Msg-Gentime1

GENTIM

MSGTYP

SRLNO

Notice-Pref

ADVINTREQD

MNTHLYFREEAMT

NOTCPRD

VALDITYPRD

Aclass-Doctype

CUSTOMER_TYPE

DOCUMENT_TYPE

MANDATORY

Sttms-Accls-Minmax-Amt-Ccy

CCY

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dep-Accls-Rest

AC_CLASS

ADESC

Denom-Deposit

ACCOUNT_CLASS

DENOMINATION_ID

DENOMINATION_DESC

DENOMINATION_VALUE

CURRENCY

Deposit-Ccy-Pref

ACCCCY

Deposit-Ccy-Pref-Dtl

CURRENCY

PAYIN

INT_PAYOUT_C

PRI_PAYOUT_C

Exrate-Pref

PAYINOUT_C

MODE_TYPE_C

RATETYPE_C

RATECODE_C

VARIANCE_C

Chan-Rest-C

CHANLID

Minmax-Ccy-C

CURR

CHANLID

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dorm-Param

LCY_BALANCE

FREQUENCY

DORM_PREP_SEL_METH

DORM_PREP_DATE

- *DORM_PREP_NTH*
- *DORM_PREP_DAY*
- *DORM_PREP_MONTH*
- *DORM_PREP_ACTION*
- *DORM_PROC_SEL_METH*
- *DORM_PROC_DATE*
- *DORM_PROC_NTH*
- *DORM_PROC_DAY*
- *DORM_PROC_MONTH*
- *DORM_GL*
- *DORM_TRN_CODE*
- *DORM_ADV_GEN*
- *DORM_STOP_IC*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

Misaccdflt

- *MISCODE2*
- *MISCODE3*
- *MISCODE4*
- *MISCODE5*
- *MISCODE6*
- *MISCODE7*
- *MISCODE8*
- *MISCODE9*
- *MISCODE10*
- *COSTCODE1*
- *COSTCODE2*
- *COSTCODE3*
- *COSTCODE4*
- *COSTCODE5*
- *ACCLASS*
- *MISGROUP*
- *POOLCODE*
- *MISCODE1*
- *MISCLASS1*
- *MISCLASS2*
- *MISCLASS3*
- *MISCLASS4*
- *MISCLASS5*
- *MISCLASS6*
- *MISCLASS7*
- *MISCLASS8*
- *MISCLASS9*

MISCLASS10

LINKTOGROUP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Account-Class-Master-IO

Attribute	Description

Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCCD

Attribute	Description
Name	ACCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

DRMNTPRM

Attribute	**Description**
Name	DRMNTPRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	**Description**
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL

Attribute	**Description**
Name	ACCSTMNTCYCL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

STMNTDAY

Attribute	**Description**
Name	STMNTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

STMNTDAY2

Attribute	Description
Name	STMNTDAY2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCSTMNTTYPT

Attribute	Description
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	Description
Name	ACCSTMNTCYCL3

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

STMNTDAY3

Attribute	Description
Name	STMNTDAY3
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OFFLNLMT

Attribute	Description
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,D

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A

TOP

EXPSRCAT

Attribute	Description
Name	EXPSRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EVNTCLSCD

Attribute	Description
Name	EVNTCLSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

DRINTUSNGRECV

Attribute	Description
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	Description
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	Description
Name	DRINTNOTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTLIQDAY

Attribute	Description
Name	DRINTLIQDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,A

TOP

CHGSTRTADV

Attribute	Description
Name	CHGSTRTADV
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCDAYS

Attribute	Description
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREBNKNGDAYS

Attribute	Description
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDLST

Attribute	Description
Name	PRDLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

CUSATLST

Attribute	Description
Name	CUSATLST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	Description
Name	DEF_AUTODEP_AC_CLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

AUTDEPTRNCD

Attribute	Description
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AUTDEPCCY

Attribute	Description
Name	AUTDEPCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBALREQD

Attribute	Description
Name	MINBALREQD
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DEPMLTPLOF

Attribute	Description
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKDEPOSITFRST

Attribute	Description
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTDEPDERRATCD

Attribute	Description
Name	AUTDEPDERRATCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOROLL

Attribute	Description
Name	AUTOROLL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSONMATURTY

Attribute	Description
Name	CLSONMATURTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTLLIQDTN

Attribute	Description
Name	PRTLLIQDTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	Description
Name	MVPRICTOUNCLMD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MINAMT

Attribute	**Description**
Name	MINAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXAMT

Attribute	**Description**
Name	MAXAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEPRD

Attribute	**Description**
Name	GRACEPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNRDAYS

Attribute	**Description**
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNRMNTHS

Attribute	**Description**
Name	MINTNRMNTHS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRMNTHS

Attribute	Description
Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRYRS

Attribute	Description
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDFLG

Attribute	Description
Name	RDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RDMVMATTOUNCLMD

Attribute	Description
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MOVEFUNDOVD

Attribute	Description
Name	MOVEFUNDOVD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCHKREQD

Attribute	**Description**
Name	LMTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVRDRFTFACLTY

Attribute	**Description**
Name	OVRDRFTFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASBKFACLTY

Attribute	**Description**
Name	PASBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECBLE

Attribute	**Description**
Name	TRCKRECBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ACCSTATS

Attribute	Description	
Name	ACCSTATS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description	
Name	EXCLSAMDYRVRTRNSFMSTMNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description	
Name	ALLWBCKPRDENTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CONSOLDTNREQD

Attribute	Description	
Name	CONSOLDTNREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ICINCLSN

Attribute	Description
Name	ICINCLSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKACCREDIC

Attribute	Description
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASDRCRADV

Attribute	Description
Name	HASDRCRADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATMFACLTY

Attribute	Description
Name	ATMFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENINTRIMSTMNT

Attribute	Description
Name	GENINTRIMSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENBALRPT

Attribute	Description
Name	GENBALRPT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTRIMRPTSNCE

Attribute	Description
Name	INTRIMRPTSNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	Description
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	Description
Name	BALRPTSINCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 941,940,950,

TOP

BALRPTTYP

Attribute	Description
Name	BALRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,S,T,

TOP

STMNTPARAM1

Attribute	**Description**
Name	STMNTPARAM1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

STMNTPARAM2

Attribute	**Description**
Name	STMNTPARAM2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

STMNTPARAM3

Attribute	**Description**
Name	STMNTPARAM3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

ESCROWPROCESS

Attribute	**Description**
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRNCODE

Attribute	Description	
Name	TRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRNREVCODE

Attribute	Description	
Name	TRNREVCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MINOR_MAJOR

Attribute	Description	
Name	MINOR_MAJOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description	
Name	REPL_CUST_SIG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description
Name	MAX_NO_CHEQUE_REJECTIONS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SAL_BLK_DAYS

Attribute	Description
Name	SAL_BLK_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description
Name	DAYSUNAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description
Name	SETTLE_BRIDGE_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PCTXNCODE

Attribute	**Description**
Name	PCTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CLUSTER_ID

Attribute	**Description**
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PROJECTACCNT

Attribute	**Description**
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	**Description**
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	Description
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

LRGDRBALFLG

Attribute	Description
Name	LRGDRBALFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description
Name	DAYLIGHTLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNOVR_CODE

Attribute	Description
Name	TRNOVR_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,W,M,Q,H,Y,

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SEND_NOTIFICATION

Attribute	Description
Name	SEND_NOTIFICATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	Description
Name	RT_CHARGE_PRODUCT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SPDANLSYS

Attribute	Description
Name	SPDANLSYS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description
Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_SWEEP_IN

Attribute	Description
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	Description
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEPACCCLS

Attribute	Description
Name	DEPACCCLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

RATECHARTTENOR

Attribute	Description
Name	RATECHARTTENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

HOLIDAYCALENDAR

Attribute	Description
Name	HOLIDAYCALENDAR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	Description
Name	HOLIDAYMOVEMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	Description
Name	MOVEACROSSMONTHS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,S,N,

TOP

ADHOCHOL

Attribute	Description
Name	ADHOCHOL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description
Name	APPLICABLEDEPTENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description
Name	MONTHENDDEPOSIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DENM_DEPOSIT

Attribute	Description
Name	DENM_DEPOSIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	**Description**
Name	REPCKUPACCLSTNRONROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MONTHS_C

Attribute	**Description**
Name	MONTHS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_C

Attribute	**Description**
Name	DAYS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	**Description**
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BONUS_INTEREST_C

Attribute	Description
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRANSACTION_CODE

Attribute	**Description**
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	**Description**
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	**Description**
Name	PREMAT_REDM_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UNCLAIMED_DAYS

Attribute	**Description**
Name	UNCLAIMED_DAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NC_DEPOSIT_C

Attribute	Description
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Status-Master

Attribute	Description
Name	Status-Master
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CR_CB

Attribute	Description
Name	CR_CB
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

CR_LINE

Attribute	Description
Name	CR_LINE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

CR_HO

Attribute	Description
Name	CR_HO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

DR_CB

Attribute	Description
Name	DR_CB
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

DR_LINE

Attribute	Description

Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DR_HO

Attribute	**Description**
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Status-Detail

Attribute	**Description**
Name	Status-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

Status-Derivation

Attribute	**Description**
Name	Status-Derivation
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

STATRUL1

Attribute	Description	
Name	STATRUL1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL2

Attribute	Description	
Name	STATRUL2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL3

Attribute	Description	
Name	STATRUL3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL4

Attribute	Description
Name	STATRUL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL5

Attribute	Description
Name	STATRUL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

COMPONENT_PRIORITY1

Attribute	Description
Name	COMPONENT_PRIORITY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	Description
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	Description
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

BLCKNGORDR

Attribute	Description
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

PRDCD

Attribute	**Description**	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Transaction-Codes

Attribute	**Description**	
Name	Transaction-Codes	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Branch-Restriction

Attribute	**Description**	
Name	Branch-Restriction	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

BRNCD

Attribute	**Description**	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-Restriction

Attribute	Description
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Interim-Cramt

Attribute	Description
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	Description
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SRLNO

Attribute	Description
Name	SRLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SRLNO

Attribute	Description
Name	SRLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MANDATORY

Attribute	Description
Name	MANDATORY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	Description
Name	Sttms-Accls-Minmax-Amt-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 255

TOP

Denom-Deposit

Attribute	Description

Name	Denom-Deposit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

ACCOUNT_CLASS

Attribute	**Description**
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DENOMINATION_ID

Attribute	**Description**
Name	DENOMINATION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DENOMINATION_DESC

Attribute	**Description**
Name	DENOMINATION_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

DENOMINATION_VALUE

Attribute	**Description**
Name	DENOMINATION_VALUE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

Deposit-Ccy-Pref

Attribute	Description	
Name	Deposit-Ccy-Pref	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	Description	
Name	Deposit-Ccy-Pref-Dtl	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PAYIN

Attribute	Description
Name	PAYIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INT_PAYOUT_C

Attribute	Description
Name	INT_PAYOUT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRI_PAYOUT_C

Attribute	Description
Name	PRI_PAYOUT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Exrate-Pref

Attribute	Description
Name	Exrate-Pref

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAYINOUT_C

Attribute	**Description**
Name	PAYINOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O

TOP

MODE_TYPE_C

Attribute	**Description**
Name	MODE_TYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S

TOP

RATETYPE_C

Attribute	**Description**
Name	RATETYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RATECODE_C

Attribute	**Description**
Name	RATECODE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

VARIANCE_C

Attribute	Description
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Chan-Rest-C

Attribute	Description
Name	Chan-Rest-C
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CURR

Attribute	Description
Name	CURR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHANLID

Attribute	**Description**
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MIN_AMOUNT

Attribute	**Description**
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAX_AMOUNT

Attribute	**Description**
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOPUP_UNITS

Attribute	**Description**
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	Description
Name	DORM_PREP_DATE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DORM_PREP_NTH

Attribute	Description
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PREP_DAY

Attribute	Description
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W

TOP

DORM_PROC_DATE

Attribute	Description	
Name	DORM_PROC_DATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DORM_PROC_NTH

Attribute	Description	
Name	DORM_PROC_NTH	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DORM_PROC_DAY

Attribute	Description	
Name	DORM_PROC_DAY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DORM_PROC_MONTH

Attribute	Description	
Name	DORM_PROC_MONTH	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DORM_TRN_CODE

Attribute	Description	
Name	DORM_TRN_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DORM_ADV_GEN

Attribute	Description	
Name	DORM_ADV_GEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORM_STOP_IC

Attribute	Description	
Name	DORM_STOP_IC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Misaccdflt

Attribute	Description
Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISCODE2

Attribute	Description
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE3

Attribute	Description
Name	MISCODE3

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE4

Attribute	**Description**
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE5

Attribute	**Description**
Name	MISCODE5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE6

Attribute	**Description**
Name	MISCODE6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE7

Attribute	**Description**
Name	MISCODE7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCODE8

Attribute	Description
Name	MISCODE8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE9

Attribute	Description
Name	MISCODE9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE3

Attribute	Description
Name	COSTCODE3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE4

Attribute	Description
Name	COSTCODE4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCODE5

Attribute	Description
Name	COSTCODE5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ACCLASS

Attribute	Description
Name	ACCLASS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

MISGROUP

Attribute	Description
Name	MISGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS4

Attribute	Description
Name	MISCLASS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCLASS10

Attribute	**Description**	
Name	MISCLASS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTOGROUP

Attribute	**Description**	
Name	LINKTOGROUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

2.103.3.ST-ModifyAccClasMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Account-Class-Master-Full*
    - *ACCCLS*
    - *DESC*
    - *ACCCD*
    - *ENDDT*
    - *DRMNCY*
    - *ACSTFORMT*
    - *DSPLYIBANINADV*
    - *INTRPY*
    - *ACCTYPE*
    - *NATRLGLSGN*
    - *DRMNTPRM*
    - *ACCSTMNTTYPP*
    - *ACCSTMNTCYCL*
    - *ACCSTMNTTYPS*
    - *ACCSTMNTCYCL2*
    - *ACCSTMNTTYPT*
    - *ACCSTMNTCYCL3*
    - *OFFLNLMT*

AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS
DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS

MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE
BALRPTTYP
STARTDT
STMNTPARAM1

STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT
INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN

ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*
- *DR_CB*
- *DR_LINE*
- *DR_HO*

- *RBKPROVSN*
- *STAT*
- *TXTSTATDESC*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation

- *ACCCLS*
- *SEQNO*
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint

- *BLCKNGORDR*
- *PRDCD*
- *PRDDESC*

Products

- *PRDCD*
- *PRDDESC*
- *DRTXN*
- *CRTXN*

Transaction-Codes

- *TXNCD*
- *TRNDESC*
- *DRTXN*
- *CRTXN*

Branch-Restriction

- *BRNCD*

Ccy-Restriction

- *CCYCD*

Ccy-Preferences

- *CCYCD*
- *MINBAL*
- *ATMCSHLMT*
- *ATMTRNSLMT*
- *TRUSTACCASHLIMIT*

- *MINIMUM_OPENING_BALANCE*
- *ACCOUNT_OPENING_CHARGES*
- *THRESHOLD_AMOUNT*

Cat-Restriction

- *CUSTCAT*

Cust-Restriction

- *CUSTNO*
- *ALLWD*

Interim-Dramt

- *CCY*
- *AMT*

Interim-Cramt

- *CCY*
- *AMT*

Msg-Gentime

- *GENTIM*

Msg-Gentime1

- *GENTIM*

Notice-Pref

- *ADVINTREQD*
- *MNTHLYFREEAMT*
- *NOTCPRD*
- *VALDITYPRD*

Aclass-Doctype

- *CUSTOMER_TYPE*
- *DOCUMENT_TYPE*
- *MANDATORY*

Sttms-Accls-Minmax-Amt-Ccy

- *CCY*
- *MIN_AMOUNT*
- *MAX_AMOUNT*
- *TOPUP_UNITS*

Dep-Accls-Rest

- *AC_CLASS*
- *ADESC*

Denom-Deposit

- *DENOMINATION_ID*
- *DENOMINATION_DESC*
- *DENOMINATION_VALUE*
- *CURRENCY*

Deposit-Ccy-Pref

- *ACCCCY*
- *Deposit-Ccy-Pref-Dtl*
  - *CURRENCY*

PAYIN

INT_PAYOUT_C

PRI_PAYOUT_C

Exrate-Pref

PAYINOUT_C

MODE_TYPE_C

RATETYPE_C

RATECODE_C

VARIANCE_C

Chan-Rest-C

CHANLID

CHANNDESC

Minmax-Ccy-C

CURR

CHANLID

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dorm-Param

ACCOUNT_CLASS

LCY_BALANCE

FREQUENCY

DORM_PREP_SEL_METH

DORM_PREP_DATE

DORM_PREP_NTH

DORM_PREP_DAY

DORM_PREP_MONTH

DORM_PREP_ACTION

DORM_PROC_SEL_METH

DORM_PROC_DATE

DORM_PROC_NTH

DORM_PROC_DAY

DORM_PROC_MONTH

DORM_GL

DORM_TRN_CODE

DORM_ADV_GEN

DORM_STOP_IC

UDFDETAILS

FLDNAM

FLDVAL

Misaccdflt

MISCODE2

MISCODE3

MISCODE4

MISCODE5
MISCODE6
MISCODE7
MISCODE8
MISCODE9
MISCODE10
COSTCODE1
COSTCODE2
COSTCODE3
COSTCODE4
COSTCODE5
ACCLASS
MISGROUP
POOLCODE
MISCODE1
MISCLASS1
MISCLASS2
MISCLASS3
MISCLASS4
MISCLASS5
MISCLASS6
MISCLASS7
MISCLASS8
MISCLASS9
MISCLASS10
LINKTOGROUP
Status-Control
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Account-Class-Master-Full

Attribute	Description
Name	Account-Class-Master-Full
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCCD

Attribute	Description
Name	ACCCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

DRMNTPRM

Attribute	Description
Name	DRMNTPRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description
Name	ACCSTMNTCYCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	Description
Name	ACCSTMNTTYPS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	Description
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	Description
Name	ACCSTMNTCYCL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	Description
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,D

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,A

TOP

EXPSRCAT

Attribute	Description
Name	EXPSRCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

EVNTCLSCD

Attribute	Description
Name	EVNTCLSCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

DRINTUSNGRECV

Attribute	**Description**
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	**Description**
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	**Description**
Name	DRINTNOTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTLIQDAY

Attribute	**Description**
Name	DRINTLIQDAY
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,A

TOP

CHGSTRTADV

Attribute	Description
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVCDAYS

Attribute	Description
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FREBNKNGDAYS

Attribute	Description
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRDLST

Attribute	Description
Name	PRDLST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

CUSATLST

Attribute	Description
Name	CUSATLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	Description
Name	DEF_AUTODEP_AC_CLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

AUTDEPTRNCD

Attribute	Description
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

AUTDEPCCY

Attribute	Description	
Name	AUTDEPCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MINBALREQD

Attribute	Description	
Name	MINBALREQD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEPMLTPLOF

Attribute	Description	
Name	DEPMLTPLOF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKDEPOSITFRST

Attribute	Description	
Name	BRKDEPOSITFRST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDEPDERRATCD

Attribute	Description
Name	AUTDEPDERRATCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOROLL

Attribute	**Description**	
Name	AUTOROLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLSONMATURTY

Attribute	**Description**	
Name	CLSONMATURTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRTLLIQDTN

Attribute	**Description**	
Name	PRTLLIQDTN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	**Description**	
Name	ALLWPRTLIQAMTBLK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MVPRICTOUNCLMD

Attribute	Description
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GRACEPRD

Attribute	Description
Name	GRACEPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINTNRDAYS

Attribute	Description
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINTNRMNTHS

Attribute	Description
Name	MINTNRMNTHS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXTNRMNTHS

Attribute	Description
Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTNRYRS

Attribute	Description
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDFLG

Attribute	Description
Name	RDFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RDMVMATTOUNCLMD

Attribute	Description
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MOVEFUNDOVD

Attribute	Description
Name	MOVEFUNDOVD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RDMINSCHDLDAYS

Attribute	**Description**
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	**Description**
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	**Description**
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	**Description**
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDSCHDLYRS

Attribute	**Description**
Name	RDSCHDLYRS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCHKREQD

Attribute	Description
Name	LMTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVRDRFTFACLTY

Attribute	Description
Name	OVRDRFTFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASBKFACLTY

Attribute	Description
Name	PASBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECBLE

Attribute	Description
Name	TRCKRECBLE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCSTATS

Attribute	Description
Name	ACCSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description
Name	EXCLSAMDYRVRTRNSFMSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description
Name	ALLWBCKPRDENTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONSOLDTNREQD

Attribute	Description
Name	CONSOLDTNREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ICINCLSN

Attribute	Description	
Name	ICINCLSN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRCKACCREDIC

Attribute	Description	
Name	TRCKACCREDIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

HASDRCRADV

Attribute	Description	
Name	HASDRCRADV	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ACSTATDEPST

Attribute	Description	
Name	ACSTATDEPST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ILMAPPLICBL

Attribute	Description
Name	ILMAPPLICBL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ATMFACLTY

Attribute	Description
Name	ATMFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNT

Attribute	Description
Name	GENINTRIMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENBALRPT

Attribute	**Description**
Name	GENBALRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRIMRPTSNCE

Attribute	**Description**
Name	INTRIMRPTSNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	**Description**
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	**Description**
Name	BALRPTSINCE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	941,940,950,

TOP

BALRPTTYP

Attribute	Description	
Name	BALRPTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,S,T,

TOP

STARTDT

Attribute	Description	
Name	STARTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STMNTPARAM1

Attribute	Description	
Name	STMNTPARAM1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM2

Attribute	Description	
Name	STMNTPARAM2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM3

Attribute	Description
Name	STMNTPARAM3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

ESCROWPROCESS

Attribute	Description
Name	ESCROWPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNCODE

Attribute	Description
Name	TRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRNREVCODE

Attribute	Description
Name	TRNREVCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINOR_MAJOR

Attribute	Description
Name	MINOR_MAJOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	Description
Name	REPL_CUST_SIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	Description
Name	MAX_NO_CHEQUE_REJECTIONS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SAL_BLK_DAYS

Attribute	Description
Name	SAL_BLK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description
Name	DAYSUNAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description	
Name	SETTLE_BRIDGE_GL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRDCAT

Attribute	Description	
Name	PRDCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PCTXNCODE

Attribute	Description	
Name	PCTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TDRATECHARTALLOW

Attribute	Description	
Name	TDRATECHARTALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CLUSTER_ID

Attribute	Description
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

PROJECTACCNT

Attribute	Description
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	Description
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TURNOVER_RTOH_CODE

Attribute	Description
Name	TURNOVER_RTOH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

LRGDRBALFLG

Attribute	Description
Name	LRGDRBALFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description
Name	DAYLIGHTLIMIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRNOVR_CODE

Attribute	Description
Name	TRNOVR_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DAYS

Attribute	**Description**
Name	DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEND_NOTIFICATION

Attribute	**Description**
Name	SEND_NOTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	**Description**
Name	RT_CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SPDANLSYS

Attribute	**Description**
Name	SPDANLSYS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SPL_RATE

Attribute	Description
Name	SPL_RATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

BLK_OPEN_DAYS

Attribute	Description
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_OPEN_MONTHS

Attribute	Description
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_DAYS

Attribute	Description
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description
Name	INTRATE_CUMAMT_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	Description
Name	COMP_WISE_TRACKING_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_SWEEP_IN

Attribute	Description
Name	ENABLE_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	Description
Name	ENABLE_REV_SWEEP_IN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEPACCCLS

Attribute	Description
Name	DEPACCCLS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

RATECHARTTENOR

Attribute	Description
Name	RATECHARTTENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

HOLIDAYCALENDAR

Attribute	Description
Name	HOLIDAYCALENDAR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	Description
Name	HOLIDAYMOVEMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	Description
Name	MOVEACROSSMONTHS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,N,

TOP

ADHOCHOL

Attribute	**Description**
Name	ADHOCHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	**Description**
Name	APPLICABLEDEPTENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,D,

TOP

MONTHENDDEPOSIT

Attribute	**Description**
Name	MONTHENDDEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENM_DEPOSIT

Attribute	**Description**
Name	DENM_DEPOSIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	**Description**	
Name	REPCKUPACCLSTNRONROLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFERREDBALUPD

Attribute	**Description**	
Name	DEFERREDBALUPD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MULTICURRENCY

Attribute	**Description**	
Name	MULTICURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MONTHS_C

Attribute	**Description**	
Name	MONTHS_C	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

INSTBASIS

Attribute	Description
Name	INSTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_DEPOSIT

Attribute	**Description**
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	**Description**
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICE_DAYS

Attribute	**Description**
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BONUS_INTEREST_C

Attribute	**Description**
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BONUS_FACTOR_C

Attribute	Description
Name	BONUS_FACTOR_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	Description
Name	INT_EXPENSE_GL_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRANSACTION_CODE

Attribute	Description
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	Description
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UNCLAIMED_DAYS

Attribute	**Description**
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NC_DEPOSIT_C

Attribute	**Description**
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Status-Master

Attribute	Description
Name	Status-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CR_CB

Attribute	Description
Name	CR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CR_LINE

Attribute	Description
Name	CR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CR_HO

Attribute	Description
Name	CR_HO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_CB

Attribute	**Description**
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DR_LINE

Attribute	**Description**
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DR_HO

Attribute	**Description**
Name	DR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RBKPROVSN

Attribute	**Description**
Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TXTSTATDESC

Attribute	Description
Name	TXTSTATDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Status-Detail

Attribute	Description
Name	Status-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ACCROL

Attribute	Description
Name	ACCROL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCHD

Attribute	Description
Name	ACCHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Status-Derivation

Attribute	Description
Name	Status-Derivation
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCLS

Attribute	Description
Name	ACCCLS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SEQNO

Attribute	**Description**
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATRUL1

Attribute	**Description**
Name	STATRUL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL2

Attribute	**Description**
Name	STATRUL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL3

Attribute	Description	
Name	STATRUL3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL4

Attribute	Description	
Name	STATRUL4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL5

Attribute	Description	
Name	STATRUL5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

COMPONENT_PRIORITY1

Attribute	Description	
Name	COMPONENT_PRIORITY1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	Description
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,I,C

TOP

Product-Maint

Attribute	Description
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BLCKNGORDR

Attribute	Description
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRTXN

Attribute	**Description**
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Transaction-Codes

Attribute	**Description**
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNCD

Attribute	**Description**
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRNDESC

Attribute	Description
Name	TRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRTXN

Attribute	Description
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRTXN

Attribute	Description
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Restriction

Attribute	Description
Name	Branch-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Restriction

Attribute	**Description**
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	**Description**
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interim-Cramt

Attribute	**Description**
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	**Description**
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	Description	
Name	Sttms-Accls-Minmax-Amt-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Denom-Deposit

Attribute	Description
Name	Denom-Deposit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DENOMINATION_ID

Attribute	Description
Name	DENOMINATION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

DENOMINATION_DESC

Attribute	Description
Name	DENOMINATION_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

DENOMINATION_VALUE

Attribute	Description

Name	DENOMINATION_VALUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	**Description**
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	**Description**
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PAYIN

Attribute	Description	
Name	PAYIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INT_PAYOUT_C

Attribute	Description	
Name	INT_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRI_PAYOUT_C

Attribute	Description	
Name	PRI_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Exrate-Pref

Attribute	Description
Name	Exrate-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAYINOUT_C

Attribute	Description
Name	PAYINOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O

TOP

MODE_TYPE_C

Attribute	Description
Name	MODE_TYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S

TOP

RATETYPE_C

Attribute	Description
Name	RATETYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RATECODE_C

Attribute	Description

Name	RATECODE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

VARIANCE_C

Attribute	**Description**
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	**Description**
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHANLID

Attribute	**Description**
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHANNDESC

Attribute	**Description**
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	**Description**
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dorm-Param

Attribute	**Description**
Name	Dorm-Param
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCOUNT_CLASS

Attribute	**Description**
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

LCY_BALANCE

Attribute	**Description**
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQUENCY

Attribute	**Description**
Name	FREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	Description
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	Description
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_DAY

Attribute	Description
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORM_STOP_IC

Attribute	**Description**	
Name	DORM_STOP_IC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	**Description**	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

Misaccdflt

Attribute	Description
Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	Description
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	Description
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	Description
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	Description
Name	MISCODE5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE6

Attribute	**Description**
Name	MISCODE6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE7

Attribute	**Description**
Name	MISCODE7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE8

Attribute	**Description**
Name	MISCODE8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE9

Attribute	**Description**
Name	MISCODE9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE3

Attribute	Description
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE4

Attribute	Description	
Name	COSTCODE4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE5

Attribute	Description	
Name	COSTCODE5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCLASS

Attribute	Description	
Name	ACCLASS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

TOP

MISGROUP

Attribute	Description	
Name	MISGROUP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS4

Attribute	Description
Name	MISCLASS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Status-Control

Attribute	Description	
Name	Status-Control	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.103.4.ST-ModifyAccClasMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Account-Class-Master-PK*
      - *ACCCLS*
    - *Account-Class-Master-IO*
      - *ACCCLS*
      - *DESC*
      - *ACCCD*
      - *ENDDT*
      - *DRMNCY*
      - *ACSTFORMT*
      - *DSPLYIBANINADV*
      - *INTRPY*
      - *NATRLGLSGN*
      - *DRMNTPRM*
      - *ACCSTMNTTYPP*
      - *ACCSTMNTCYCL*
      - *STMNTDAY*
      - *ACCSTMNTTYPS*
      - *ACCSTMNTCYCL2*

STMNTDAY2
ACCSTMNTTYPT
ACCSTMNTCYCL3
STMNTDAY3
OFFLNLMT
AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
MINAMT
MAXAMT

GRACEPRD
MINTNRDAYS
MINTNRMNTHS
MINTNRYRS
DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS
MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT

INTRIMRPTSNCE
INTRIMRPTTYP
BALRPTSINCE
BALRPTTYP
STMNTPARAM1
STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP
INT_RATE_OPTION_REDAMT

INT_RATE_OPTION_REMAMT
INTRATE_CUMAMT_REQD
ENABLE_SWEEP_IN
ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
MONTHEND_INST
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
Status-Master
- *CR_CB*
- *CR_LINE*
- *CR_HO*
- *DR_CB*
- *DR_LINE*
- *DR_HO*
- *STAT*
- *Status-Detail*

Status-Derivation
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*

STATRUL5
COMPONENT_PRIORITY1
COMPONENT_PRIORITY2
COMPONENT_PRIORITY3
Product-Maint
BLCKNGORDR
PRDCD
Products
PRDCD
Transaction-Codes
Branch-Restriction
BRNCD
Ccy-Restriction
CCYCD
Ccy-Preferences
CCYCD
MINBAL
ATMCSHLMT
ATMTRNSLMT
TRUSTACCASHLIMIT
MINIMUM_OPENING_BALANCE
ACCOUNT_OPENING_CHARGES
THRESHOLD_AMOUNT
Cat-Restriction
CUSTCAT
Cust-Restriction
CUSTNO
ALLWD
Interim-Dramt
CCY
AMT
Interim-Cramt
CCY
AMT
Msg-Gentime
GENTIM
MSGTYP
SRLNO
Msg-Gentime1
GENTIM
MSGTYP
SRLNO
Notice-Pref
ADVINTREQD

- *MNTHLYFREEAMT*
- *NOTCPRD*
- *VALDITYPRD*

Aclass-Doctype

- *CUSTOMER_TYPE*
- *DOCUMENT_TYPE*
- *MANDATORY*

Sttms-Accls-Minmax-Amt-Ccy

- *CCY*
- *MIN_AMOUNT*
- *MAX_AMOUNT*
- *TOPUP_UNITS*

Dep-Accls-Rest

- *AC_CLASS*
- *ADESC*

Denom-Deposit

- *ACCOUNT_CLASS*
- *DENOMINATION_ID*
- *DENOMINATION_DESC*
- *DENOMINATION_VALUE*
- *CURRENCY*

Deposit-Ccy-Pref

- *ACCCCY*
- *Deposit-Ccy-Pref-Dtl*
  - *CURRENCY*
  - *PAYIN*
  - *INT_PAYOUT_C*
  - *PRI_PAYOUT_C*

Exrate-Pref

- *PAYINOUT_C*
- *MODE_TYPE_C*
- *RATETYPE_C*
- *RATECODE_C*
- *VARIANCE_C*

Chan-Rest-C

- *CHANLID*

Minmax-Ccy-C

- *CURR*
- *CHANLID*
- *MIN_AMOUNT*
- *MAX_AMOUNT*
- *TOPUP_UNITS*

Dorm-Param

- *LCY_BALANCE*

- *FREQUENCY*
- *DORM_PREP_SEL_METH*
- *DORM_PREP_DATE*
- *DORM_PREP_NTH*
- *DORM_PREP_DAY*
- *DORM_PREP_MONTH*
- *DORM_PREP_ACTION*
- *DORM_PROC_SEL_METH*
- *DORM_PROC_DATE*
- *DORM_PROC_NTH*
- *DORM_PROC_DAY*
- *DORM_PROC_MONTH*
- *DORM_GL*
- *DORM_TRN_CODE*
- *DORM_ADV_GEN*
- *DORM_STOP_IC*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

Misaccdflt

- *MISCODE2*
- *MISCODE3*
- *MISCODE4*
- *MISCODE5*
- *MISCODE6*
- *MISCODE7*
- *MISCODE8*
- *MISCODE9*
- *MISCODE10*
- *COSTCODE1*
- *COSTCODE2*
- *COSTCODE3*
- *COSTCODE4*
- *COSTCODE5*
- *ACCLASS*
- *MISGROUP*
- *POOLCODE*
- *MISCODE1*
- *MISCLASS1*
- *MISCLASS2*
- *MISCLASS3*
- *MISCLASS4*
- *MISCLASS5*
- *MISCLASS6*

MISCLASS7

MISCLASS8

MISCLASS9

MISCLASS10

LINKTOGROUP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Account-Class-Master-PK

Attribute	Description
Name	Account-Class-Master-PK
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Account-Class-Master-IO

Attribute	Description
Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCCD

Attribute	Description
Name	ACCCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

DRMNTPRM

Attribute	Description
Name	DRMNTPRM
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	Description	
Name	ACCSTMNTTYPP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,S,D

TOP

ACCSTMNTCYCL

Attribute	Description	
Name	ACCSTMNTCYCL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,Q,M,F,W,D,A

TOP

STMNTDAY

Attribute	Description	
Name	STMNTDAY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCSTMNTTYPS

Attribute	Description	
Name	ACCSTMNTTYPS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description
Name	ACCSTMNTCYCL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

STMNTDAY2

Attribute	Description
Name	STMNTDAY2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCSTMNTTYPT

Attribute	Description
Name	ACCSTMNTTYPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL3

Attribute	Description
Name	ACCSTMNTCYCL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

STMNTDAY3

Attribute	Description
Name	STMNTDAY3

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFLNLMT

Attribute	**Description**
Name	OFFLNLMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTPROVREQD

Attribute	**Description**
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PROVSNGFREQ

Attribute	**Description**
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

PROVCCYTYP

Attribute	**Description**
Name	PROVCCYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A

TOP

EXPSRCAT

Attribute	Description
Name	EXPSRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EVNTCLSCD

Attribute	Description
Name	EVNTCLSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

DRINTUSNGRECV

Attribute	Description
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VRFYFNDSFORDRINT

Attribute	Description
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRINTNOTC

Attribute	Description
Name	DRINTNOTC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRINTLIQDAY

Attribute	Description
Name	DRINTLIQDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRINTLIQDMODE

Attribute	Description
Name	DRINTLIQDMODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,A

TOP

CHGSTRTADV

Attribute	Description
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVCDAYS

Attribute	Description
Name	ADVCDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

FREBNKNGDAYS

Attribute	Description
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRDLST

Attribute	Description
Name	PRDLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

CUSATLST

Attribute	Description
Name	CUSATLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	Description
Name	DEF_AUTODEP_AC_CLS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

AUTDEPTRNCD

Attribute	**Description**
Name	AUTDEPTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AUTDEPCCY

Attribute	**Description**
Name	AUTDEPCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBALREQD

Attribute	**Description**
Name	MINBALREQD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPMLTPLOF

Attribute	**Description**
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKDEPOSITFRST

Attribute	Description
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDEPDERRATCD

Attribute	Description
Name	AUTDEPDERRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOROLL

Attribute	Description
Name	AUTOROLL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSONMATURTY

Attribute	Description
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRTLLIQDTN

Attribute	Description
Name	PRTLLIQDTN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	Description
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVINTTOUNCLMD

Attribute	Description
Name	MVINTTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MVPRICTOUNCLMD

Attribute	Description
Name	MVPRICTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MINAMT

Attribute	Description
Name	MINAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXAMT

Attribute	Description
Name	MAXAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GRACEPRD

Attribute	Description
Name	GRACEPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINTNRDAYS

Attribute	Description
Name	MINTNRDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINTNRMNTHS

Attribute	Description
Name	MINTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRDAYS

Attribute	Description
Name	MAXTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRMNTHS

Attribute	Description
Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNRYRS

Attribute	Description
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDFLG

Attribute	Description
Name	RDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RDMVMATTOUNCLMD

Attribute	Description
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MOVEFUNDOVD

Attribute	Description
Name	MOVEFUNDOVD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LMTCHKREQD

Attribute	Description
Name	LMTCHKREQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVRDRFTFACLTY

Attribute	**Description**
Name	OVRDRFTFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASBKFACLTY

Attribute	**Description**
Name	PASBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKRECBLE

Attribute	**Description**
Name	TRCKRECBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCSTATS

Attribute	**Description**
Name	ACCSTATS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description	
Name	EXCLSAMDYRVRTRNSFMSTMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description	
Name	ALLWBCKPRDENTRY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONSOLDTNREQD

Attribute	Description	
Name	CONSOLDTNREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ICINCLSN

Attribute	Description	
Name	ICINCLSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRCKACCREDIC

Attribute	**Description**
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HASDRCRADV

Attribute	**Description**
Name	HASDRCRADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACSTATDEPST

Attribute	**Description**
Name	ACSTATDEPST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LODGEMNTBK

Attribute	**Description**
Name	LODGEMNTBK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description
Name	STATCHNGAUTMATIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATMFACLTY

Attribute	Description
Name	ATMFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNT

Attribute	Description
Name	GENINTRIMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GENBALRPT

Attribute	Description
Name	GENBALRPT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTRIMRPTSNCE

Attribute	Description
Name	INTRIMRPTSNCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	Description
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	Description
Name	BALRPTSINCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 941,940,950,

TOP

BALRPTTYP

Attribute	Description
Name	BALRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

STMNTPARAM1

Attribute	Description
Name	STMNTPARAM1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM2

Attribute	Description	
Name	STMNTPARAM2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM3

Attribute	Description	
Name	STMNTPARAM3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

ESCROWPROCESS

Attribute	Description	
Name	ESCROWPROCESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNCODE

Attribute	Description	
Name	TRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRNREVCODE

Attribute	**Description**
Name	TRNREVCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINOR_MAJOR

Attribute	**Description**
Name	MINOR_MAJOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	**Description**
Name	REPL_CUST_SIG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	**Description**
Name	MAX_NO_CHEQUE_REJECTIONS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SAL_BLK_DAYS

Attribute	Description
Name	SAL_BLK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	Description
Name	DAYSUNAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description
Name	SETTLE_BRIDGE_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PCTXNCODE

Attribute	Description
Name	PCTXNCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLUSTER_ID

Attribute	**Description**
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PROJECTACCNT

Attribute	**Description**
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	**Description**
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	**Description**
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TURNOVER_RTOH_CODE

Attribute	Description	
Name	TURNOVER_RTOH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

LRGDRBALFLG

Attribute	Description	
Name	LRGDRBALFLG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRNOVR_CODE

Attribute	Description	
Name	TRNOVR_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEND_NOTIFICATION

Attribute	Description
Name	SEND_NOTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	Description
Name	RT_CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SPDANLSYS

Attribute	Description
Name	SPDANLSYS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPL_RATE

Attribute	**Description**
Name	SPL_RATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BLK_OPEN_DAYS

Attribute	**Description**
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_OPEN_MONTHS

Attribute	**Description**
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_MAT_DAYS

Attribute	**Description**
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description	
Name	INTRATE_CUMAMT_REQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENABLE_SWEEP_IN

Attribute	Description	
Name	ENABLE_SWEEP_IN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	Description	
Name	ENABLE_REV_SWEEP_IN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEPACCCLS

Attribute	Description	
Name	DEPACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	A,D

TOP

RATECHARTTENOR

Attribute	Description	
Name	RATECHARTTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

HOLIDAYCALENDAR

Attribute	Description	
Name	HOLIDAYCALENDAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	Description	
Name	HOLIDAYMOVEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	Description	
Name	MOVEACROSSMONTHS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,N,

TOP

ADHOCHOL

Attribute	Description
Name	ADHOCHOL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description
Name	APPLICABLEDEPTENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description
Name	MONTHENDDEPOSIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DENM_DEPOSIT

Attribute	Description
Name	DENM_DEPOSIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description
Name	REPCKUPACCLSTNRONROLL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MONTHS_C

Attribute	Description
Name	MONTHS_C
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

MONTHEND_INST

Attribute	**Description**
Name	MONTHEND_INST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BONUS_INTEREST_C

Attribute	**Description**
Name	BONUS_INTEREST_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BONUS_FACTOR_C

Attribute	**Description**
Name	BONUS_FACTOR_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT_EXPENSE_GL_C

Attribute	**Description**
Name	INT_EXPENSE_GL_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TRANSACTION_CODE

Attribute	Description
Name	TRANSACTION_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCCCY_CHANGE_C

Attribute	Description
Name	ACCCCY_CHANGE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UNCLAIMED_DAYS

Attribute	Description
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NC_DEPOSIT_C

Attribute	Description
Name	NC_DEPOSIT_C
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Status-Master

Attribute	Description
Name	Status-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CR_CB

Attribute	Description
Name	CR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CR_LINE

Attribute	Description
Name	CR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CR_HO

Attribute	Description
Name	CR_HO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DR_CB

Attribute	Description
Name	DR_CB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DR_LINE

Attribute	Description
Name	DR_LINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DR_HO

Attribute	Description
Name	DR_HO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

Status-Detail

Attribute	Description
Name	Status-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

Status-Derivation

Attribute	Description
Name	Status-Derivation
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

STATRUL1

Attribute	Description
Name	STATRUL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL2

Attribute	Description
Name	STATRUL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL3

Attribute	Description
Name	STATRUL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL4

Attribute	Description
Name	STATRUL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

STATRUL5

Attribute	Description	
Name	STATRUL5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

COMPONENT_PRIORITY1

Attribute	Description	
Name	COMPONENT_PRIORITY1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description	
Name	COMPONENT_PRIORITY2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	Description	
Name	COMPONENT_PRIORITY3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,P,I,C

TOP

Product-Maint

Attribute	Description
Name	Product-Maint
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BLCKNGORDR

Attribute	Description
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Products

Attribute	Description
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Transaction-Codes

Attribute	Description	
Name	Transaction-Codes	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Branch-Restriction

Attribute	Description	
Name	Branch-Restriction	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-Restriction

Attribute	Description	
Name	Ccy-Restriction	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALLWD

Attribute	Description
Name	ALLWD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	**Description**
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Interim-Cramt

Attribute	**Description**
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Msg-Gentime

Attribute	Description
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SRLNO

Attribute	Description
Name	SRLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SRLNO

Attribute	Description

Name	SRLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Notice-Pref

Attribute	**Description**
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVINTREQD

Attribute	**Description**
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	**Description**
Name	MNTHLYFREEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTCPRD

Attribute	**Description**
Name	NOTCPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDITYPRD

Attribute	**Description**

Name	VALDITYPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Aclass-Doctype

Attribute	**Description**
Name	Aclass-Doctype
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_TYPE

Attribute	**Description**
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,C,B

TOP

DOCUMENT_TYPE

Attribute	**Description**
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MANDATORY

Attribute	**Description**
Name	MANDATORY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	Description
Name	Sttms-Accls-Minmax-Amt-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Dep-Accls-Rest

Attribute	Description	
Name	Dep-Accls-Rest	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AC_CLASS

Attribute	Description	
Name	AC_CLASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ADESC

Attribute	Description	
Name	ADESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Denom-Deposit

Attribute	Description	
Name	Denom-Deposit	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DENOMINATION_ID

Attribute	Description
Name	DENOMINATION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

DENOMINATION_DESC

Attribute	Description
Name	DENOMINATION_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

DENOMINATION_VALUE

Attribute	Description
Name	DENOMINATION_VALUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CURRENCY

Attribute	Description
Name	CURRENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	**Description**
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	**Description**
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYIN

Attribute	Description
Name	PAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_PAYOUT_C

Attribute	Description
Name	INT_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRI_PAYOUT_C

Attribute	Description
Name	PRI_PAYOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Exrate-Pref

Attribute	Description
Name	Exrate-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PAYINOUT_C

Attribute	Description

Name	PAYINOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O

TOP

MODE_TYPE_C

Attribute	**Description**
Name	MODE_TYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S

TOP

RATETYPE_C

Attribute	**Description**
Name	RATETYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RATECODE_C

Attribute	**Description**
Name	RATECODE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

VARIANCE_C

Attribute	**Description**
Name	VARIANCE_C
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Chan-Rest-C

Attribute	Description	
Name	Chan-Rest-C	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CHANLID

Attribute	Description	
Name	CHANLID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Minmax-Ccy-C

Attribute	Description	
Name	Minmax-Ccy-C	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CURR

Attribute	Description	
Name	CURR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	Description
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	Description
Name	DORM_PREP_NTH
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DORM_PREP_DAY

Attribute	Description
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DORM_ADV_GEN

Attribute	**Description**
Name	DORM_ADV_GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DORM_STOP_IC

Attribute	**Description**
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

Misaccdflt

Attribute	Description
Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	Description
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	Description
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	Description

Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	**Description**
Name	MISCODE5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE6

Attribute	**Description**
Name	MISCODE6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE7

Attribute	**Description**
Name	MISCODE7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE8

Attribute	**Description**
Name	MISCODE8
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCODE9

Attribute	Description
Name	MISCODE9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE10

Attribute	Description
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE1

Attribute	Description
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCODE2

Attribute	Description
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE3

Attribute	Description	
Name	COSTCODE3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE4

Attribute	Description	
Name	COSTCODE4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE5

Attribute	Description	
Name	COSTCODE5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCLASS

Attribute	Description	
Name	ACCLASS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

TOP

MISGROUP

Attribute	Description
Name	MISGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS4

Attribute	Description
Name	MISCLASS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.104.ModifyBranch

ModifyBranch

2.104.1.ST-ModifyBranch-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*

BRNADDR
BRNADDR2
BRNADDR3
SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC

EXTVAL
BRNAVALSTAT
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH

CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description	
Name	PRNTBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

REGNLOFC

Attribute	Description
Name	REGNLOFC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TIMLVL

Attribute	Description
Name	TIMLVL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTRYCD

Attribute	Description
Name	CNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CIDIF

Attribute	Description
Name	CIDIF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

FUNDBRNCH

Attribute	Description
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODATMBRN

Attribute	Description
Name	CODATMBRN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CODINSTID

Attribute	Description
Name	CODINSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNADDR3

Attribute	Description
Name	BRNADDR3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SWFTADDR

Attribute	Description
Name	SWFTADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	**Description**
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	**Description**
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	**Description**
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	**Description**
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CONVGL

Attribute	Description
Name	CONVGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONVTXNCD

Attribute	Description
Name	CONVTXNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CURRCYCLE

Attribute	Description
Name	CURRCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFHR

Attribute	**Description**
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFMIN

Attribute	**Description**
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

JOBSTAT

Attribute	**Description**
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOAUTH

Attribute	**Description**
Name	AUTOAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLGBRNCD

Attribute	Description
Name	CLGBRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CLRBRN

Attribute	Description
Name	CLRBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

CNTRYCDDESC

Attribute	Description	
Name	CNTRYCDDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SUSPGLSLDESC

Attribute	Description	
Name	SUSPGLSLDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CONTSUSPGLSLDESC

Attribute	Description	
Name	CONTSUSPGLSLDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SUSPGLFCYDESC

Attribute	Description	
Name	SUSPGLFCYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CONTSUSPGLFCYDESC

Attribute	Description
Name	CONTSUSPGLFCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ATMSUSPGLDESC

Attribute	Description
Name	ATMSUSPGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVGLDESC

Attribute	Description
Name	CONVGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONVTXNCDDESC

Attribute	Description
Name	CONVTXNCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EXTVAL

Attribute	Description
Name	EXTVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BRNAVALSTAT

Attribute	Description
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description	
Name	CLRBNKCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MISCCYMISMATCHGRP

Attribute	Description	
Name	MISCCYMISMATCHGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

INTERDICTCHKREQD

Attribute	Description	
Name	INTERDICTCHKREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INTERDICTTIMOUT

Attribute	Description	
Name	INTERDICTTIMOUT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENTGL

Attribute	Description
Name	ENTGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	Description
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALDAYS

Attribute	Description
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	Description
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRPRD

Attribute	**Description**
Name	DRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CRPRD

Attribute	**Description**
Name	CRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

IBANMSKBNKCD

Attribute	**Description**
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

IBANMSKACCNO

Attribute	**Description**
Name	IBANMSKACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 500

TOP

DRPRDDESC

Attribute	Description
Name	DRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CRPRDDESC

Attribute	Description
Name	CRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRTAXCYCLE

Attribute	Description
Name	CURRTAXCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONSOLTXCERTREQD

Attribute	Description
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	Description
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SUSENTRYREQ

Attribute	Description
Name	SUSENTRYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SUSBATCHNO

Attribute	Description
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SUSTXNCODE

Attribute	Description
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVSUSENTRYDAYS

Attribute	Description
Name	REVSUSENTRYDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CASAAMTBLKTRNCODE

Attribute	**Description**
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOFFREQ

Attribute	**Description**
Name	HOFFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWCORPACS

Attribute	**Description**
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFER_TYPE

Attribute	**Description**
Name	TRANSFER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	P,R,

TOP

POSITION_ASSET_GL

Attribute	Description
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

POSITION_LIABILITY_GL

Attribute	Description
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

GL_CLASSS

Attribute	Description
Name	GL_CLASSS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CHEQUESTALEDAYS

Attribute	Description
Name	CHEQUESTALEDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FILECONSTXNCODE

Attribute	Description	
Name	FILECONSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CNTRY_CKSUM_MASK

Attribute	Description	
Name	CNTRY_CKSUM_MASK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Branch-Swift-Address

Attribute	Description
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SWFTADRS

Attribute	Description
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Message-Type

Attribute	Description
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

LCYMSGTYP

Attribute	Description
Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	S,M,P,

TOP

Dup-Chk

Attribute	Description
Name	Dup-Chk
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MODULE1

Attribute	Description
Name	MODULE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

DUP_FLG

Attribute	Description
Name	DUP_FLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DUP_DAY

Attribute	Description
Name	DUP_DAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Account-Params

Attribute	Description

Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	**Description**
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	**Description**
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	**Description**
Name	STRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTACCALG

Attribute	Description	
Name	CUSTACCALG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTNOALG

Attribute	Description	
Name	CUSTNOALG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FNDSTACNO

Attribute	Description	
Name	FNDSTACNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FNDEDACNO

Attribute	Description	
Name	FNDEDACNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.104.2.ST-ModifyBranch-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-IO*
    - *BRNCD*
    - *BRNNAME*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*
    - *BRNADDR*
    - *BRNADDR2*
    - *BRNADDR3*
    - *SWFTADDR*
    - *TELEXADDR*
    - *HOSTNAM*

OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS

TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
CHAR_FIELD78
MAKER
MAKERSTAMP
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*

ENDDUMMYCUSTNO
START_PID_NO
END_PID_NO
Branch-Functions
Branch-Ccy
BRNCD
CCYCD
CCYDESC
Branch-Message-Type
LCYMSGTYP
Dup-Chk
BRN_D
MODULE1
DUP_FLG
DUP_DAY
Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMLVL

Attribute	Description

Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CNTRYCD

Attribute	**Description**
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

FUNDBRNCH

Attribute	**Description**
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CODATMBRN

Attribute	**Description**
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CODINSTID

Attribute	Description
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR3

Attribute	Description
Name	BRNADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWFTADDR

Attribute	Description
Name	SWFTADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

HOSTNAM

Attribute	**Description**
Name	HOSTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

OFFSTHRS

Attribute	**Description**
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OFFSTMIN

Attribute	**Description**
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDOFINP

Attribute	**Description**
Name	ENDOFINP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	**Description**
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUSPGLSL

Attribute	**Description**
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	**Description**
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SUSPGLFCY

Attribute	**Description**
Name	SUSPGLFCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONTSUSPGLFCY

Attribute	**Description**	
Name	CONTSUSPGLFCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ATMSUSPGL

Attribute	**Description**	
Name	ATMSUSPGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONVGL

Attribute	**Description**	
Name	CONVGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONVTXNCD

Attribute	**Description**	
Name	CONVTXNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

REFHR

Attribute	Description	
Name	REFHR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFMIN

Attribute	Description	
Name	REFMIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

JOBSTAT

Attribute	Description	
Name	JOBSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOAUTH

Attribute	Description	
Name	AUTOAUTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,

TOP

GEN103

Attribute	Description
Name	GEN103
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROCWITHOUTFLOAT

Attribute	Description	
Name	PROCWITHOUTFLOAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLGBRNCD

Attribute	Description	
Name	CLGBRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECTORCD

Attribute	Description	
Name	SECTORCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CLRBRN

Attribute	Description	
Name	CLRBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	**Description**
Name	CLRBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MISCCYMISMATCHGRP

Attribute	**Description**
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INTERDICTCHKREQD

Attribute	**Description**
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTERDICTTIMOUT

Attribute	**Description**
Name	INTERDICTTIMOUT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENTGL

Attribute	Description
Name	ENTGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	Description
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALDAYS

Attribute	Description
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	Description
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LDAPTEMP

Attribute	**Description**
Name	LDAPTEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

CONSOLTXCERTREQD

Attribute	**Description**
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	**Description**
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	**Description**
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SUSENTRYREQ

Attribute	Description	
Name	SUSENTRYREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SUSBATCHNO

Attribute	Description	
Name	SUSBATCHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SUSTXNCODE

Attribute	Description	
Name	SUSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVSUSENTRYDAYS

Attribute	Description	
Name	REVSUSENTRYDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_TYPE

Attribute	Description
Name	TRANSFER_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R,

TOP

POSITION_ASSET_GL

Attribute	**Description**
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	**Description**
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GL_CLASSS

Attribute	**Description**
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	**Description**
Name	CHEQUESTALEDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRY_CKSUM_MASK

Attribute	Description
Name	CNTRY_CKSUM_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CHAR_FIELD78

Attribute	Description
Name	CHAR_FIELD78
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Branch-Swift-Address

Attribute	**Description**
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Branch-Customer-Params

Attribute	**Description**
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYDESC

Attribute	**Description**
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Message-Type

Attribute	**Description**
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

LCYMSGTYP

Attribute	**Description**
Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,M,P,

TOP

Dup-Chk

Attribute	**Description**
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRN_D

Attribute	Description
Name	BRN_D
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

MODULE1

Attribute	Description
Name	MODULE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

DUP_FLG

Attribute	Description
Name	DUP_FLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DUP_DAY

Attribute	Description
Name	DUP_DAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCMSK

Attribute	Description	
Name	CUSTACCMSK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CHKSUMALGO

Attribute	Description	
Name	CHKSUMALGO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	mod11,mod97,mod11WW,mod10,U,

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.104.3.ST-ModifyBranch-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Details-Full*
    - *BRNCD*
    - *BRNNAME*
    - *PRNTBRN*
    - *REGNLOFC*
    - *TIMLVL*
    - *CNTRYCD*
    - *CIDIF*
    - *FUNDBRNCH*
    - *BRNLCY*
    - *CODATMBRN*
    - *CODINSTID*
    - *CODIBTRNCD*
    - *CODCUSTTRNS*
    - *OFFSTHOURS*
    - *OFFSTMINS*
    - *BRNADDR*
    - *BRNADDR2*
    - *BRNADDR3*

SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC
CONVTXNCDDESC
EXTVAL
BRNAVALSTAT
NETSUSPGL

WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS

TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*
- *DUP_DAY*

Account-Params
- *BRNCD*
- *CUSTACCMSK*

CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRNTBRN

Attribute	Description

Name	PRNTBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGNLOFC

Attribute	**Description**
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TIMLVL

Attribute	**Description**
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRYCD

Attribute	**Description**
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

FUNDBRNCH

Attribute	Description	
Name	FUNDBRNCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRNLCY

Attribute	Description	
Name	BRNLCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CODATMBRN

Attribute	Description	
Name	CODATMBRN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CODINSTID

Attribute	Description	
Name	CODINSTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR2

Attribute	Description	
Name	BRNADDR2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNADDR3

Attribute	Description	
Name	BRNADDR3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

SWFTADDR

Attribute	Description	
Name	SWFTADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

TELEXADDR

Attribute	Description	
Name	TELEXADDR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OFFSTHRS

Attribute	Description
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	Description
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	Description
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ATMSUSPGL

Attribute	Description	
Name	ATMSUSPGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONVGL

Attribute	Description	
Name	CONVGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONVTXNCD

Attribute	Description	
Name	CONVTXNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CURRCYCLE

Attribute	Description	
Name	CURRCYCLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CURRPERIOD

Attribute	Description
Name	CURRPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFSTMNTSTAT

Attribute	**Description**	
Name	DEFSTMNTSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

GEN

Attribute	**Description**	
Name	GEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,

TOP

GEN103P

Attribute	**Description**	
Name	GEN103P	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEFBNKOPCD

Attribute	**Description**	
Name	DEFBNKOPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	4

TOP

PROCWITHOUTFLOAT

Attribute	Description	
Name	PROCWITHOUTFLOAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLGBRNCD

Attribute	Description	
Name	CLGBRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECTORCD

Attribute	Description	
Name	SECTORCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CLRBRN

Attribute	Description	
Name	CLRBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRNLCYDESC

Attribute	Description
Name	BRNLCYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PRNTBRNDESC

Attribute	Description
Name	PRNTBRNDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGNLOFCDESC

Attribute	Description
Name	REGNLOFCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNTRYCDDESC

Attribute	Description
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLSLDESC

Attribute	Description
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONTSUSPGLSLDESC

Attribute	Description
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLFCYDESC

Attribute	Description
Name	SUSPGLFCYDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONTSUSPGLFCYDESC

Attribute	Description	
Name	CONTSUSPGLFCYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ATMSUSPGLDESC

Attribute	Description	
Name	ATMSUSPGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVGLDESC

Attribute	Description	
Name	CONVGLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CONVTXNCDDESC

Attribute	Description	
Name	CONVTXNCDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

EXTVAL

Attribute	Description	
Name	EXTVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BRNAVALSTAT

Attribute	Description	
Name	BRNAVALSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NETSUSPGL

Attribute	Description	
Name	NETSUSPGL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

WALKINCUST

Attribute	Description	
Name	WALKINCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description
Name	CLRBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

MISCCYMISMATCHGRP

Attribute	Description
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

INTERDICTCHKREQD

Attribute	Description
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTERDICTTIMOUT

Attribute	Description
Name	INTERDICTTIMOUT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ENTGL

Attribute	**Description**
Name	ENTGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	**Description**
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BCKVALDAYS

Attribute	**Description**
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	**Description**
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LDAPTEMP

Attribute	**Description**
Name	LDAPTEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

DRPRDDESC

Attribute	**Description**
Name	DRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CRPRDDESC

Attribute	**Description**
Name	CRPRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRTAXCYCLE

Attribute	**Description**
Name	CURRTAXCYCLE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CONSOLTXCERTREQD

Attribute	**Description**
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	**Description**
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	**Description**
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	**Description**
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SUSENTRYREQ

Attribute	Description	
Name	SUSENTRYREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SUSBATCHNO

Attribute	Description	
Name	SUSBATCHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SUSTXNCODE

Attribute	Description	
Name	SUSTXNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVSUSENTRYDAYS

Attribute	Description	
Name	REVSUSENTRYDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRANSFER_TYPE

Attribute	Description
Name	TRANSFER_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R,

TOP

POSITION_ASSET_GL

Attribute	**Description**
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	**Description**
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GL_CLASSS

Attribute	**Description**
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	**Description**
Name	CHEQUESTALEDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ELCM_REPLICATION

Attribute	Description
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRY_CKSUM_MASK

Attribute	Description
Name	CNTRY_CKSUM_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Branch-Swift-Address

Attribute	**Description**
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Branch-Customer-Params

Attribute	Description
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Message-Type

Attribute	Description
Name	Branch-Message-Type
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

LCYMSGTYP

Attribute	Description

Name	LCYMSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,M,P,

TOP

Dup-Chk

Attribute	**Description**
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MODULE1

Attribute	**Description**
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

DUP_FLG

Attribute	**Description**
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUP_DAY

Attribute	**Description**
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCMSK

Attribute	Description
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	Description
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	Description
Name	STRTACCNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDACCNO

Attribute	**Description**
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	**Description**
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDAUTOACCFLG

Attribute	**Description**
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOSTRTACCNO

Attribute	**Description**
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.104.4.ST-ModifyBranch-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Branch-Details-PK*
      - *BRNCD*
    - *Branch-Details-IO*
      - *BRNCD*
      - *BRNNAME*
      - *TIMLVL*
      - *CNTRYCD*
      - *CIDIF*
      - *FUNDBRNCH*
      - *CODATMBRN*
      - *CODINSTID*
      - *CODIBTRNCD*
      - *CODCUSTTRNS*
      - *OFFSTHOURS*
      - *OFFSTMINS*
      - *BRNADDR*
      - *BRNADDR2*
      - *BRNADDR3*

SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT

ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS
TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
CHAR_FIELD78
MAKER
MAKERSTAMP
Branch-Swift-Address
  SWFTADRS
  DESC
Branch-Customer-Params

STRTCUSTNO
ENDCUSTNO
STRTDUMMYCUSTNO
ENDDUMMYCUSTNO
START_PID_NO
END_PID_NO
Branch-Functions
Branch-Ccy
BRNCD
CCYCD
CCYDESC
Branch-Message-Type
LCYMSGTYP
Dup-Chk
BRN_D
MODULE1
DUP_FLG
DUP_DAY
Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Branch-Details-PK

Attribute	Description
Name	Branch-Details-PK
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMLVL

Attribute	Description	
Name	TIMLVL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CNTRYCD

Attribute	Description
Name	CNTRYCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CIDIF

Attribute	**Description**
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

FUNDBRNCH

Attribute	**Description**
Name	FUNDBRNCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CODATMBRN

Attribute	**Description**
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CODINSTID

Attribute	**Description**
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CODIBTRNCD

Attribute	Description
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CODCUSTTRNS

Attribute	Description
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OFFSTHOURS

Attribute	Description
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMINS

Attribute	Description
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNADDR

Attribute	Description
Name	BRNADDR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BRNADDR2

Attribute	Description
Name	BRNADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR3

Attribute	Description
Name	BRNADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWFTADDR

Attribute	Description
Name	SWFTADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	14

TOP

HOSTNAM

Attribute	Description
Name	HOSTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

OFFSTHRS

Attribute	Description
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OFFSTMIN

Attribute	Description
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ENDOFINP

Attribute	Description
Name	ENDOFINP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SUSPGLSL

Attribute	**Description**
Name	SUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CONTSUSPGLSL

Attribute	**Description**
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SUSPGLFCY

Attribute	**Description**
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CONTSUSPGLFCY

Attribute	**Description**
Name	CONTSUSPGLFCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ATMSUSPGL

Attribute	**Description**	
Name	ATMSUSPGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONVGL

Attribute	**Description**	
Name	CONVGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CONVTXNCD

Attribute	**Description**	
Name	CONVTXNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFHR

Attribute	**Description**	
Name	REFHR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

GEN

Attribute	Description
Name	GEN

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,

TOP

GEN103

Attribute	Description
Name	GEN103
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLGBRNCD

Attribute	Description
Name	CLGBRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRBRN

Attribute	Description
Name	CLRBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ROUTNO

Attribute	Description
Name	ROUTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

MSGGENDAY

Attribute	Description
Name	MSGGENDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETSUSPGL

Attribute	Description
Name	NETSUSPGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

WALKINCUST

Attribute	Description
Name	WALKINCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTSWAPCUST

Attribute	Description
Name	INTSWAPCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	Description
Name	CLRBNKCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MISCCYMISMATCHGRP

Attribute	Description
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INTERDICTCHKREQD

Attribute	Description
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTERDICTTIMOUT

Attribute	Description
Name	INTERDICTTIMOUT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	G,C,

TOP

PROVSNGFREQ

Attribute	Description	
Name	PROVSNGFREQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description	
Name	UNCOLLFNDSBASIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	U,A,

TOP

DEFSTMNT

Attribute	Description	
Name	DEFSTMNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ENTGL

Attribute	Description	
Name	ENTGL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

BCKVALCHKREQD

Attribute	Description
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCKVALDAYS

Attribute	Description
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	Description
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PLSPLITREQD

Attribute	Description
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DRPRD

Attribute	Description
Name	DRPRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CRPRD

Attribute	Description
Name	CRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

IBANMSKBNKCD

Attribute	Description
Name	IBANMSKBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

IBANMSKACCNO

Attribute	Description
Name	IBANMSKACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

CONSOLTXCERTREQD

Attribute	**Description**
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INDIVTAXVERTREQD

Attribute	**Description**
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXCERTFREQ

Attribute	**Description**
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,Y,

TOP

FREQVAL

Attribute	**Description**
Name	FREQVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2

TOP

MINORAGE

Attribute	Description
Name	MINORAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOTIFICATIONPERIOD

Attribute	Description
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXREALSUSAMT

Attribute	Description
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTSUSAMT

Attribute	Description
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SUSENTRYREQ

Attribute	Description
Name	SUSENTRYREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SUSBATCHNO

Attribute	Description
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

SUSTXNCODE

Attribute	Description
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REVSUSENTRYDAYS

Attribute	Description
Name	REVSUSENTRYDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRANSFER_BRANCH

Attribute	Description
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CASAAMTBLKTRNCODE

Attribute	Description
Name	CASAAMTBLKTRNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

HOFFREQ

Attribute	Description
Name	HOFFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWCORPACS

Attribute	Description
Name	ALLWCORPACS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRANSFER_TYPE

Attribute	Description
Name	TRANSFER_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,R,

TOP

POSITION_ASSET_GL

Attribute	Description
Name	POSITION_ASSET_GL

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	**Description**
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GL_CLASSS

Attribute	**Description**
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	**Description**
Name	CHEQUESTALEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSACTION_CODE1

Attribute	**Description**
Name	TRANSACTION_CODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

LMTEXP_NOTIFY_DAYS

Attribute	Description
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REPORT_DSN

Attribute	Description
Name	REPORT_DSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHQNO_MASK

Attribute	Description
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRY_CKSUM_MASK

Attribute	Description
Name	CNTRY_CKSUM_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CHAR_FIELD78

Attribute	Description
Name	CHAR_FIELD78
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Branch-Swift-Address

Attribute	Description
Name	Branch-Swift-Address

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Branch-Customer-Params

Attribute	**Description**
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTCUSTNO

Attribute	**Description**
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Branch-Message-Type

Attribute	Description	
Name	Branch-Message-Type	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

LCYMSGTYP

Attribute	Description	
Name	LCYMSGTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,M,P,

TOP

Dup-Chk

Attribute	Description	
Name	Dup-Chk	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRN_D

Attribute	Description	
Name	BRN_D	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MODULE1

Attribute	Description
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

DUP_FLG

Attribute	Description
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DUP_DAY

Attribute	Description
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCMSK

Attribute	Description
Name	CUSTACCMSK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHKSUMALGO

Attribute	Description
Name	CHKSUMALGO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / mod11,mod97,mod11WW,mod10,U,

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.105.ModifyBranchTrfr

ModifyBranchTrfr

2.105.1.ST-ModifyBranchTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Brn-Transfer-Full

Attribute	Description

Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

TD_REQ

Attribute	Description

Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	**Description**
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	**Description**
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>Name</td><td>AUTHSTAT</td></tr>
<tr><td>Datatype</td><td>String</td></tr>
<tr><td>Description</td><td></td></tr>
<tr><td>Attributes</td><td>
<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table>
</td></tr>
<tr><td>Restrictions</td><td>
<table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>maxLength</td><td>1</td></tr>
</table>
</td></tr>
</table>

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Brn-Transfer-IO
TRANSFER_DATE
TRANSFER_ID
TRANSFER_LENDING_MODULE
CI_REQ
MO_REQ
CASA_REQ
TD_REQ
MAKER
MAKERSTAMP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 128 Restrictions: pattern; Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TD_REQ

Attribute	Description
Name	TD_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

2.105.3.ST-ModifyBranchTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-Full*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *CI_REQ*
    - *MO_REQ*
    - *CASA_REQ*
    - *TD_REQ*
    - *CURRENT_BRANCH_NAME*
    - *TARGET_BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Brn-Transfer-Full

Attribute	Description
Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description	
Name	TARGET_BRANCH_CODESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

TD_REQ

Attribute	Description
Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	Description
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TARGET_BRANCH_NAME

Attribute	Description
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.105.4.ST-ModifyBranchTrfr-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Sttms-Brn-Transfer-IO*
      - *TRANSFER_DATE*
      - *TRANSFER_ID*
      - *TRANSFER_LENDING_MODULE*
      - *CI_REQ*
      - *MO_REQ*
      - *CASA_REQ*
      - *TD_REQ*
      - *MAKER*
      - *MAKERSTAMP*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttms-Brn-Transfer-PK

Attribute	Description
Name	Sttms-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TD_REQ

Attribute	Description
Name	TD_REQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.106.ModifyCRSRequest

Modification of Adhoc Consolidated Statement Request

2.106.1.ST-ModifyCRSRequest-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttm-Crs-Master-Full

Attribute	Description

Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description
Name	TO_DATE
Datatype	Date
Description	Specifies the To Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Specifies The Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_STATUS_DETAILS

Attribute	Description
Name	PROCESS_STATUS_DETAILS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

E-STATEMENT

Attribute	Description	
Name	E-STATEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	Description	
Name	CHARGEBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	Description	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Crs-Master-IO
TO_DATE
REFERENCENO
REQUESTTYPE
FROMDATE
REQUESTDATE
E-STATEMENT
CHARGEBRANCH
CHARGEACCOUNT
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

TO_DATE

Attribute	Description
Name	TO_DATE
Datatype	Date
Description	Specifies the To Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHARGEBRANCH

Attribute	Description	
Name	CHARGEBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	Description	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

2.106.3.ST-ModifyCRSRequest-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-Full*
    - *TO_DATE*
    - *REFERENCENO*
    - *CUSTOMER_NO*
    - *BRANCHCODE*
    - *REQUESTTYPE*
    - *FROMDATE*
    - *PROCESSSTAT*
    - *REQUESTDATE*
    - *PROCESS_STATUS_DETAILS*
    - *E-STATEMENT*
    - *CHARGEBRANCH*
    - *CHARGEACCOUNT*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttm-Crs-Master-Full

Attribute	Description
Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description	
Name	TO_DATE	
Datatype	Date	
Description	Specifies the To Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUESTTYPE

Attribute	**Description**
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,L

TOP

FROMDATE

Attribute	**Description**
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESSSTAT

Attribute	**Description**
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REQUESTDATE

Attribute	**Description**
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESS_STATUS_DETAILS

Attribute	**Description**
Name	PROCESS_STATUS_DETAILS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	Description
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHARGEACCOUNT

Attribute	Description
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	Attribute	Description
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the Transaction Status O - Open C - Close	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.106.4.ST-ModifyCRSRequest-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Crs-Master-PK*
      - *REFERENCENO*
    - *Sttm-Crs-Master-IO*
      - *TO_DATE*
      - *REFERENCENO*
      - *REQUESTTYPE*
      - *FROMDATE*
      - *REQUESTDATE*
      - *E-STATEMENT*
      - *CHARGEBRANCH*
      - *CHARGEACCOUNT*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttm-Crs-Master-PK

Attribute	Description
Name	Sttm-Crs-Master-PK
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

TO_DATE

Attribute	Description	
Name	TO_DATE	
Datatype	Date	
Description	Specifies the To Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	Description
Name	CHARGEBRANCH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CHARGEACCOUNT

Attribute	Description	
Name	CHARGEACCOUNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.107.ReopenCardMaster

ReopenCardMaster

2.107.1.ST-ReopenCardMaster-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*

CREDIT_CARD_LIMIT
PRIMARY_CARD
CARD_APPL_DATE
CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CARD_PRODUCT

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CARD_BIN

Attribute	Description	
Name	CARD_BIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OWNER_ID_NO1

Attribute	Description
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADD_HOLDER_IDNO

Attribute	Description
Name	ADD_HOLDER_IDNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

OWNER_ID_TYPE

Attribute	Description
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CARD_APPL_DATE

Attribute	Description
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	Description
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

CARD_STATUS

Attribute	Description

Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	**Description**
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OPERATION

Attribute	**Description**
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BILL_CYCLE

Attribute	**Description**
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	Description	
Name	RENEWAL_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	Description	
Name	RENEWAL_CYCLE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_LIMIT_UNIT

Attribute	Description	
Name	ATM_LIMIT_UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description	
Name	ATM_COUNT_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 19

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DEL_CHNL_PIN

Attribute	**Description**
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ADDL_HOLDER_DOB

Attribute	**Description**
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDL_HOLDER_RELATION

Attribute	**Description**
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DR_CR_INDICATOR

Attribute	**Description**
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	D,C

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Debit-Card-Master-IO
CUST_NO
CUST_AC_NO
BRANCH_CODE
REQ_REF_NO
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQ_REF_NO

Attribute	**Description**
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.107.3.ST-ReopenCardMaster-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-Full*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *CARD_PRODUCT*
    - *CARD_BIN*
    - *BRANCH_CODE*
    - *REQ_REF_NO*
    - *HOLD_BILL_INDICATOR*
    - *RECOVERY_ACCOUNT*
    - *NAME_ON_CARD*
    - *OWNER_ID_NO1*
    - *ADD_HOLDER_IDNO*
    - *OWNER_ID_TYPE*
    - *ADDL_HOLDER_ID_TYPE*
    - *ISSUER*
    - *PLASTIC_TYPE*
    - *CREDIT_CARD_LIMIT*
    - *PRIMARY_CARD*
    - *CARD_APPL_DATE*

CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECOVERY_ACCOUNT

Attribute	Description
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

OWNER_ID_NO1

Attribute	Description	
Name	OWNER_ID_NO1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

ADD_HOLDER_IDNO

Attribute	Description	
Name	ADD_HOLDER_IDNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

OWNER_ID_TYPE

Attribute	Description	
Name	OWNER_ID_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CREDIT_CARD_LIMIT

Attribute	Description
Name	CREDIT_CARD_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CARD_APPL_DATE

Attribute	**Description**
Name	CARD_APPL_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_RENEWAL_DT

Attribute	**Description**
Name	CARD_RENEWAL_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	**Description**
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	Description
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N,

TOP

CARD_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

LAST_STATUS_UPDATED

Attribute	Description	
Name	LAST_STATUS_UPDATED	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

LAST_OPERATION

Attribute	Description	
Name	LAST_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

BILL_CYCLE

Attribute	Description	
Name	BILL_CYCLE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RENEWAL_UNIT

Attribute	**Description**
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	**Description**
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	**Description**
Name	ATM_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	**Description**
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	19

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

DEL_CHNL_PIN

Attribute	Description
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

ADDL_HOLDER_DOB

Attribute	Description
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADDL_HOLDER_RELATION

Attribute	Description
Name	ADDL_HOLDER_RELATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DR_CR_INDICATOR

Attribute	Description
Name	DR_CR_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.107.4.ST-ReopenCardMaster-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Debit-Card-Master-PK*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *CUST_NO*
      - *CUST_AC_NO*
    - *Sttms-Debit-Card-Master-IO*
      - *CUST_NO*
      - *CUST_AC_NO*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttms-Debit-Card-Master-PK

Attribute	Description
Name	Sttms-Debit-Card-Master-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description	
Name	REQ_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description

Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Debit-Card-Master-IO

Attribute	**Description**
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.108.ReopenCustTrfr

ReopenCustTrfr

2.108.1.ST-ReopenCustTrfr-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cust-Brn-Transfer-Full

Attribute	Description

Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description
Name	TRANSFER_MORTGAGES_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_CASA

Attribute	Description
Name	TRANSFER_CASA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description
Name	CURRENT_BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	**Description**
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	**Description**
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	**Description**
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	**Description**
Name	TXT_CUSTNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cust-Brn-Transfer-IO
TRANSFER_ID
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.108.3.ST-ReopenCustTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cust-Brn-Transfer-Full*
    - *TRANSFER_MORTGAGES_MODULE*
    - *TRANSFER_CASA*
    - *CURRENT_BRANCH_CODE*
    - *TARGET_BRANCH_CODESS*
    - *TRANSFER_DATE*
    - *TRANSFER_ID*
    - *TRANSFER_LENDING_MODULE*
    - *TRANSFER_ISLAMIC_FINANCING_MODULE*
    - *CUSTOMER_ID*
    - *TRANSFER_TERM_DEPOSITS*
    - *TARGET_BRANCH*
    - *CURRENT_BRANCH*
    - *TXT_CUSTNAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cust-Brn-Transfer-Full

Attribute	Description
Name	Cust-Brn-Transfer-Full
Datatype	
Description	

TOP

TRANSFER_MORTGAGES_MODULE

Attribute	Description	
Name	TRANSFER_MORTGAGES_MODULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFER_CASA

Attribute	Description	
Name	TRANSFER_CASA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFER_ISLAMIC_FINANCING_MODULE

Attribute	Description
Name	TRANSFER_ISLAMIC_FINANCING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_TERM_DEPOSITS

Attribute	Description
Name	TRANSFER_TERM_DEPOSITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARGET_BRANCH

Attribute	Description
Name	TARGET_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CURRENT_BRANCH

Attribute	Description
Name	CURRENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cust-Brn-Transfer-PK*
      - *TRANSFER_ID*
    - *Cust-Brn-Transfer-IO*
      - *TRANSFER_ID*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cust-Brn-Transfer-PK

Attribute	Description
Name	Cust-Brn-Transfer-PK
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Cust-Brn-Transfer-IO

Attribute	Description
Name	Cust-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.109.ReopenOnlineCharge

ReopenOnlineCharge

2.109.1.ST-ReopenOnlineCharge-Req-Full-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Onlinecharge-Master-Full
SOURCE
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Onlinecharge-Detail
CHARGE_EVENT
CHARGE_PRODUCT
ACTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Onlinecharge-Master-Full

Attribute	Description
Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHARGE_EVENT

Attribute	Description
Name	CHARGE_EVENT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CHARGE_PRODUCT

Attribute	**Description**
Name	CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Onlinecharge-Master-IO
SOURCE
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

2.109.3.ST-ReopenOnlineCharge-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Onlinecharge-Master-Full*
    - *SOURCE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Onlinecharge-Detail*
      - *CHARGE_EVENT*
      - *CHARGE_PRODUCT*
      - *ACTION*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Onlinecharge-Master-Full

Attribute	Description

Name	Onlinecharge-Master-Full
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Onlinecharge-Detail

Attribute	Description
Name	Onlinecharge-Detail
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHARGE_EVENT

Attribute	**Description**	
Name	CHARGE_EVENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CHARGE_PRODUCT

Attribute	**Description**	
Name	CHARGE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Onlinecharge-Master-PK*
      - *SOURCE*
    - *Onlinecharge-Master-IO*
      - *SOURCE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Onlinecharge-Master-PK

Attribute	Description
Name	Onlinecharge-Master-PK
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

Onlinecharge-Master-IO

Attribute	Description
Name	Onlinecharge-Master-IO
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.110.ReopenSTDSTCDM

ReopenSTDSTCDM

2.110.1.ST-ReopenSTDSTCDM-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Crdrstat-Full

Attribute	Description
Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description	
Name	CUST_AC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NODEBIT

Attribute	Description	
Name	NODEBIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOCREDIT

Attribute	Description	
Name	NOCREDIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Crdrstat-IO
BRANCH_CODE
CUST_AC
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.110.3.ST-ReopenSTDSTCDM-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Crdrstat-Full*
    - *BRANCH_CODE*
    - *CUST_AC*
    - *NODEBIT*
    - *NOCREDIT*
    - *POSTALLOWED*
    - *REMARKS*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Crdrstat-Full

Attribute	Description

Name	Crdrstat-Full
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

NODEBIT

Attribute	Description
Name	NODEBIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOCREDIT

Attribute	Description
Name	NOCREDIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

POSTALLOWED

Attribute	Description
Name	POSTALLOWED
Datatype	String
Description	This indicates whether the customer account can be accessible to the FLEXCUBE UBS product processors to transact. Valid values are: Y - Yes N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Crdrstat-PK*
      - *BRANCH_CODE*
      - *CUST_AC*
    - *Crdrstat-IO*
      - *BRANCH_CODE*
      - *CUST_AC*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Crdrstat-PK

Attribute	Description
Name	Crdrstat-PK
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Crdrstat-IO

Attribute	Description
Name	Crdrstat-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_AC

Attribute	Description
Name	CUST_AC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.111.ReopenSTDSTDOR

ReopenSTDSTDOR

2.111.1.ST-ReopenSTDSTDOR-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

TXNSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Status-Full

Attribute	Description

Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Status-IO
ACCOUNT_BRANCH
AC_NO
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.111.3.ST-ReopenSTDSTDOR-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Status-Full*
    - *REVERSE_MOVEMENT_PARAM*
    - *REMARKS*
    - *ACCOUNT_BRANCH*
    - *AC_NO*
    - *NO_DR*
    - *NO_CR*
    - *FROZEN*
    - *DORMANT*
    - *AC_DESC*
    - *ACCOUNT_CCY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Status-Full

Attribute	Description
Name	Status-Full
Datatype	
Description	

TOP

REVERSE_MOVEMENT_PARAM

Attribute	Description
Name	REVERSE_MOVEMENT_PARAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D,M,B

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

NO_DR

Attribute	Description
Name	NO_DR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NO_CR

Attribute	Description
Name	NO_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DORMANT

Attribute	Description
Name	DORMANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

AC_DESC

Attribute	Description
Name	AC_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCOUNT_CCY

Attribute	Description
Name	ACCOUNT_CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Status-PK*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
    - *Status-IO*
      - *ACCOUNT_BRANCH*
      - *AC_NO*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Status-PK

Attribute	Description
Name	Status-PK
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

Status-IO

Attribute	Description
Name	Status-IO
Datatype	
Description	

TOP

ACCOUNT_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

AC_NO

Attribute	Description
Name	AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.112.ModifyServiceRequest

2.112.1.ST-ModifyServiceRequest-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Service-Request-Details-Full*
    - *SUBJECT*
    - *ACTDATE*
    - *PRIORITY*
    - *STATUS*
    - *REQUESTER_TYPE*
    - *NATURE*
    - *CRITERIA*
    - *SNAME*
    - *TEL*
    - *EMAIL*
    - *MOBILE_NUMBER*
    - *FNAME*
    - *SERVICE_NUM*
    - *CUST_AC_NO*
    - *CUSTOMER_NO*
    - *SERV_REQ_TYPE*

BRANCH_CODE
CONTACT_DATE
TARGET_DATE
DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Service-Request-Details-Full

Attribute	Description
Name	Service-Request-Details-Full
Datatype	
Description	

TOP

SUBJECT

Attribute	Description	
Name	SUBJECT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACTDATE

Attribute	Description	
Name	ACTDATE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	String	
Description	Indicates Priority High : 1 Normal : 2 Low : 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	High,Medium,Low

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,P,C,X

TOP

REQUESTER_TYPE

Attribute	Description
Name	REQUESTER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,W

TOP

NATURE

Attribute	Description
Name	NATURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Sales,Service

TOP

CRITERIA

Attribute	Description
Name	CRITERIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Enquiry,Channel,Product,Application ,Maintenance

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates the Short Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	This gives the Customer email address
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MOBILE_NUMBER

Attribute	Description
Name	MOBILE_NUMBER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FNAME

Attribute	Description
Name	FNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SERVICE_NUM

Attribute	**Description**
Name	SERVICE_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTOMER_NO

Attribute	**Description**
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SERV_REQ_TYPE

Attribute	**Description**
Name	SERV_REQ_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / TXN,NTX,CMP

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONTACT_DATE

Attribute	**Description**
Name	CONTACT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TARGET_DATE

Attribute	**Description**
Name	TARGET_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER

Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number

Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Service-Request-Details-IO*
    - *BRANCH*
    - *SUBJECT*
    - *DESCRIPTION*
    - *CONTACTDATE*
    - *TARGETDATE*
    - *ACTDATE*
    - *PRIORITY*
    - *STATUS*
    - *SERVICE_NUM*
    - *CUST_AC_NO*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Service-Request-Details-IO

Attribute	Description
Name	Service-Request-Details-IO
Datatype	
Description	

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SUBJECT

Attribute	Description	
Name	SUBJECT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

TOP

CONTACTDATE

Attribute	Description	
Name	CONTACTDATE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

TOP

TARGETDATE

Attribute	Description	
Name	TARGETDATE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / High,Medium,Low

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,P,C,X

TOP

SERVICE_NUM

Attribute	Description
Name	SERVICE_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

2.112.3.ST-ModifyServiceRequest-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Service-Request-Details-Full*
    - *SUBJECT*
    - *ACTDATE*
    - *PRIORITY*
    - *STATUS*
    - *REQUESTER_TYPE*
    - *NATURE*
    - *CRITERIA*
    - *SNAME*
    - *TEL*
    - *EMAIL*
    - *MOBILE_NUMBER*
    - *FNAME*
    - *SERVICE_NUM*
    - *CUST_AC_NO*
    - *CUSTOMER_NO*
    - *SERV_REQ_TYPE*
    - *BRANCH_CODE*
    - *CONTACT_DATE*

TARGET_DATE
DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Service-Request-Details-Full

Attribute	Description
Name	Service-Request-Details-Full
Datatype	
Description	

TOP

SUBJECT

Attribute	Description	
Name	SUBJECT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACTDATE

Attribute	Description	
Name	ACTDATE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority High : 1 Normal : 2 Low : 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	High,Medium,Low

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,P,C,X

TOP

REQUESTER_TYPE

Attribute	Description
Name	REQUESTER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,W

TOP

NATURE

Attribute	Description
Name	NATURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Sales,Service

TOP

CRITERIA

Attribute	Description
Name	CRITERIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,Enquiry,Channel,Product,Application ,Maintenance

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	Indicates the Short Name.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	This gives the Customer email address
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MOBILE_NUMBER

Attribute	Description
Name	MOBILE_NUMBER
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FNAME

Attribute	Description
Name	FNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SERVICE_NUM

Attribute	Description
Name	SERVICE_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SERV_REQ_TYPE

Attribute	Description

Name	SERV_REQ_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / TXN,NTX,CMP

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONTACT_DATE

Attribute	**Description**
Name	CONTACT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TARGET_DATE

Attribute	**Description**
Name	TARGET_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.112.4.ST-ModifyServiceRequest-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Service-Request-Details-PK*
      - *SERVICE_NUM*
    - *Service-Request-Details-IO*
      - *BRANCH*
      - *SUBJECT*
      - *DESCRIPTION*
      - *CONTACTDATE*
      - *TARGETDATE*
      - *ACTDATE*
      - *PRIORITY*
      - *STATUS*
      - *SERVICE_NUM*
      - *CUST_AC_NO*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Service-Request-Details-PK

Attribute	Description
Name	Service-Request-Details-PK
Datatype	
Description	

TOP

SERVICE_NUM

Attribute	Description	
Name	SERVICE_NUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Service-Request-Details-IO

Attribute	Description
Name	Service-Request-Details-IO
Datatype	
Description	

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

SUBJECT

Attribute	Description	
Name	SUBJECT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 50

TOP

CONTACTDATE

Attribute	Description
Name	CONTACTDATE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 50

TOP

TARGETDATE

Attribute	Description
Name	TARGETDATE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 50

TOP

ACTDATE

Attribute	Description
Name	ACTDATE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 50

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / High,Medium,Low

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,P,C,X

TOP

SERVICE_NUM

Attribute	Description
Name	SERVICE_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.113.QueryACRSMaint

Query Of Automatic Consolidated Statement Request

2.113.1.ST-QueryACRSMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Auto-Crs-Master-IO*
    - *REFERENCENO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.113.2.ST-QueryACRSMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Auto-Crs-Master-IO*
      - *REFERENCENO*
    - *Sttm-Auto-Crs-Master-Full*
      - *REFERENCENO*
      - *CUSTOMER_NO*
      - *BRANCD*
      - *EFFDATE*
      - *FREEQUENCY*
      - *STARTMON*
      - *STARTON*
      - *LASTEXEDATE*
      - *E-STATEMENT*
      - *CHARGEBRANCH*
      - *CHARGEACCOUNT*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Auto-Crs-Master-IO

Attribute	Description
Name	Sttm-Auto-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Auto-Crs-Master-Full

Attribute	Description
Name	Sttm-Auto-Crs-Master-Full
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCD

Attribute	Description
Name	BRANCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREEQUENCY

Attribute	Description
Name	FREEQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,S,A

TOP

STARTMON

Attribute	Description
Name	STARTMON

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

STARTON

Attribute	Description
Name	STARTON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

LASTEXEDATE

Attribute	Description
Name	LASTEXEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	Description
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHARGEACCOUNT

Attribute	Description
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.114.QueryAccClasMaint

Query of Account Class maintenance

2.114.1.ST-QueryAccClasMaint-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Account-Class-Master-IO
ACCCLS
LRGDRBALFLG
DEPACCCLS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Account-Class-Master-IO

Attribute	Description
Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description	
Name	ACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

LRGDRBALFLG

Attribute	Description
Name	LRGDRBALFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPACCCLS

Attribute	**Description**
Name	DEPACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

2.114.2.ST-QueryAccClasMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Account-Class-Master-IO*
      - *ACCCLS*
      - *LRGDRBALFLG*
      - *DEPACCCLS*
    - *Account-Class-Master-Full*
      - *ACCCLS*
      - *DESC*
      - *ACCCD*
      - *ENDDT*
      - *DRMNCY*
      - *ACSTFORMT*
      - *DSPLYIBANINADV*
      - *INTRPY*
      - *ACCTYPE*
      - *NATRLGLSGN*
      - *DRMNTPRM*
      - *ACCSTMNTTYPP*
      - *ACCSTMNTCYCL*

ACCSTMNTTYPS
ACCSTMNTCYCL2
ACCSTMNTTYPT
ACCSTMNTCYCL3
OFFLNLMT
AUTPROVREQD
PROVSNGFREQ
PROVCCYTYP
EXPSRCAT
EVNTCLSCD
DRINTUSNGRECV
VRFYFNDSFORDRINT
DRINTNOTC
DRINTLIQDAY
DRINTLIQDMODE
CHGSTRTADV
ADVCDAYS
FREBNKNGDAYS
PRDLST
TXNLST
REGDAPPLCBLE
REGDPRDICTY
CCYLST
BRNLST
CUSATLST
DEF_AUTODEP_AC_CLS
AUTDEPTRNCD
AUTDEPCCY
MINBALREQD
DEPMLTPLOF
BRKDEPOSITFRST
AUTDEPDERRATCD
AUTDEPDERRATTYP
SWPMD
AUTDEPBRKMETHD
PRVDINTONBRKNDEP
AUTOROLL
CLSONMATURTY
PRTLLIQDTN
ALLWPRTLIQAMTBLK
MVINTTOUNCLMD
MVPRICTOUNCLMD
GRACEPRD
MINTNRDAYS

MINTNRMNTHS
MINTNRYRS
DFLTTNRDAY
DFLTTNRMNTHS
DFLTTNRYRS
MAXTNRDAYS
MAXTNRMNTHS
MAXTNRYRS
RDFLG
RDMVMATTOUNCLMD
MOVEFUNDOVD
RDMINSCHDLDAYS
RDMININSTLMNTAMT
RDSCHDLDAYS
RDSCHDLMNTHS
RDSCHDLYRS
RDMAXSCHDLDAYS
CHQBKFACLTY
AUTOREORDRCHQREQD
AUTREORDRCHKLVLS
AUTOREORDRCHKLEAVES
LMTCHKREQD
OVRDRFTFACLTY
PASBKFACLTY
TRCKRECBLE
ACCSTATS
EXCLSAMDYRVRTRNSFMSTMNT
ALLWBCKPRDENTRY
CONSOLDTNREQD
ICINCLSN
TRCKACCREDIC
HASDRCRADV
ACSTATDEPST
LODGEMNTBK
HASIS
AVALBALREQD
REFREQD
STATCHNGAUTMATIC
ILMAPPLICBL
ATMFACLTY
GENINTRIMSTMNT
GENINTRIMSTMNTONMVMNT
GENBALRPT
INTRIMRPTSNCE

INTRIMRPTTYP
BALRPTSINCE
BALRPTTYP
STARTDT
STMNTPARAM1
STMNTPARAM2
STMNTPARAM3
ESCROWPROCESS
TRNCODE
TRNREVCODE
MINOR_MAJOR
REPL_CUST_SIG
MAX_NO_CHEQUE_REJECTIONS
SAL_BLK_DAYS
DAYSUNAUTHNOACTIVITY
DAYSAUTHNOACTIVITY
LINK_CCY
CCY_OPTION
FIX_DAY
DUALCCYDEP
SETTLE_BRIDGE_GL
PRDCAT
PCTXNCODE
TDRATECHARTALLOW
CLUSTER_ID
PROJECTACCNT
TRUSTACCASHLIMIT
TURNOVER_EVENT_CLASS_CODE
TURNOVER_RTOH_CODE
LRGDRBALFLG
DAYLIGHTLIMIT
TRNOVR_CODE
FREQUENCY
DAYS
SEND_NOTIFICATION
RT_CHARGE_PRODUCT
SPDANLSYS
SPL_RATE
BLK_OPEN_DAYS
BLK_OPEN_MONTHS
BLK_MAT_DAYS
BLK_MAT_MONTHS
ALLOW_TOPUP
INT_RATE_OPTION_TOPUP

INT_RATE_OPTION_REDAMT
INT_RATE_OPTION_REMAMT
INTRATE_CUMAMT_REQD
COMP_WISE_TRACKING_REQD
ENABLE_SWEEP_IN
ENABLE_REV_SWEEP_IN
DEPACCCLS
RATECHARTTENOR
HOLIDAYCALENDAR
HOLIDAYMOVEMENT
MOVEACROSSMONTHS
ADHOCHOL
APPLICABLEDEPTENOR
MONTHENDDEPOSIT
DENM_DEPOSIT
REPCKUPACCLSTNRONROLL
DEFERREDBALUPD
MULTICURRENCY
MONTHS_C
DAYS_C
HIGH_VAL_DEPOSIT_C
CHANLIST
INSTBASIS
MONTHEND_INST
NOTICE_DEPOSIT
NOTICE_LOCK_DAYS
NOTICE_DAYS
BONUS_INTEREST_C
BONUS_FACTOR_C
INT_EXPENSE_GL_C
TRANSACTION_CODE
ACCCCY_CHANGE_C
PREMAT_REDM_C
UNCLAIMED_DAYS
NC_DEPOSIT_C
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Status-Master
  CR_CB

- *CR_LINE*
- *CR_HO*
- *DR_CB*
- *DR_LINE*
- *DR_HO*
- *RBKPROVSN*
- *STAT*
- *TXTSTATDESC*
- *Status-Detail*
  - *ACCROL*
  - *ROLDESC*
  - *ACCHD*
  - *GLDESC*

Status-Derivation

- *ACCCLS*
- *SEQNO*
- *STAT*
- *STATRUL1*
- *STATRUL2*
- *STATRUL3*
- *STATRUL4*
- *STATRUL5*
- *COMPONENT_PRIORITY1*
- *COMPONENT_PRIORITY2*
- *COMPONENT_PRIORITY3*

Product-Maint

- *BLCKNGORDR*
- *PRDCD*
- *PRDDESC*

Products

- *PRDCD*
- *PRDDESC*
- *DRTXN*
- *CRTXN*

Transaction-Codes

- *TXNCD*
- *TRNDESC*
- *DRTXN*
- *CRTXN*

Branch-Restriction

- *BRNCD*

Ccy-Restriction

- *CCYCD*

Ccy-Preferences

CCYCD

MINBAL

ATMCSHLMT

ATMTRNSLMT

TRUSTACCASHLIMIT

MINIMUM_OPENING_BALANCE

ACCOUNT_OPENING_CHARGES

THRESHOLD_AMOUNT

Cat-Restriction

CUSTCAT

Cust-Restriction

CUSTNO

ALLWD

Interim-Dramt

CCY

AMT

Interim-Cramt

CCY

AMT

Msg-Gentime

GENTIM

Msg-Gentime1

GENTIM

Notice-Pref

ADVINTREQD

MNTHLYFREEAMT

NOTCPRD

VALDITYPRD

Aclass-Doctype

CUSTOMER_TYPE

DOCUMENT_TYPE

MANDATORY

Sttms-Accls-Minmax-Amt-Ccy

CCY

MIN_AMOUNT

MAX_AMOUNT

TOPUP_UNITS

Dep-Accls-Rest

AC_CLASS

ADESC

Denom-Deposit

DENOMINATION_ID

DENOMINATION_DESC

DENOMINATION_VALUE

- *CURRENCY*
- *Deposit-Ccy-Pref*
  - *ACCCCY*
  - *Deposit-Ccy-Pref-Dtl*
    - *CURRENCY*
    - *PAYIN*
    - *INT_PAYOUT_C*
    - *PRI_PAYOUT_C*
- *Exrate-Pref*
  - *PAYINOUT_C*
  - *MODE_TYPE_C*
  - *RATETYPE_C*
  - *RATECODE_C*
  - *VARIANCE_C*
- *Chan-Rest-C*
  - *CHANLID*
  - *CHANNDESC*
- *Minmax-Ccy-C*
  - *CURR*
  - *CHANLID*
  - *MIN_AMOUNT*
  - *MAX_AMOUNT*
  - *TOPUP_UNITS*
- *Dorm-Param*
  - *ACCOUNT_CLASS*
  - *LCY_BALANCE*
  - *FREQUENCY*
  - *DORM_PREP_SEL_METH*
  - *DORM_PREP_DATE*
  - *DORM_PREP_NTH*
  - *DORM_PREP_DAY*
  - *DORM_PREP_MONTH*
  - *DORM_PREP_ACTION*
  - *DORM_PROC_SEL_METH*
  - *DORM_PROC_DATE*
  - *DORM_PROC_NTH*
  - *DORM_PROC_DAY*
  - *DORM_PROC_MONTH*
  - *DORM_GL*
  - *DORM_TRN_CODE*
  - *DORM_ADV_GEN*
  - *DORM_STOP_IC*
- *UDFDETAILS*
  - *FLDNAM*

FLDVAL

Misaccdflt

MISCODE2

MISCODE3

MISCODE4

MISCODE5

MISCODE6

MISCODE7

MISCODE8

MISCODE9

MISCODE10

COSTCODE1

COSTCODE2

COSTCODE3

COSTCODE4

COSTCODE5

ACCLASS

MISGROUP

POOLCODE

MISCODE1

MISCLASS1

MISCLASS2

MISCLASS3

MISCLASS4

MISCLASS5

MISCLASS6

MISCLASS7

MISCLASS8

MISCLASS9

MISCLASS10

LINKTOGROUP

Status-Control

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Account-Class-Master-IO

Attribute	Description
Name	Account-Class-Master-IO
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

LRGDRBALFLG

Attribute	Description
Name	LRGDRBALFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEPACCCLS

Attribute	Description
Name	DEPACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Account-Class-Master-Full

Attribute	Description
Name	Account-Class-Master-Full
Datatype	
Description	

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCCD

Attribute	Description
Name	ACCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ENDDT

Attribute	Description
Name	ENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRMNCY

Attribute	Description
Name	DRMNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACSTFORMT

Attribute	Description
Name	ACSTFORMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

DSPLYIBANINADV

Attribute	Description
Name	DSPLYIBANINADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INTRPY

Attribute	Description
Name	INTRPY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACCTYPE

Attribute	Description
Name	ACCTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,D,C,S,U,Y,L

TOP

NATRLGLSGN

Attribute	Description
Name	NATRLGLSGN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

DRMNTPRM

Attribute	**Description**
Name	DRMNTPRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C,B,M

TOP

ACCSTMNTTYPP

Attribute	**Description**
Name	ACCSTMNTTYPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,S,D

TOP

ACCSTMNTCYCL

Attribute	**Description**
Name	ACCSTMNTCYCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPS

Attribute	**Description**
Name	ACCSTMNTTYPS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,S,D

TOP

ACCSTMNTCYCL2

Attribute	Description	
Name	ACCSTMNTCYCL2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,Q,M,F,W,D,A

TOP

ACCSTMNTTYPT

Attribute	Description	
Name	ACCSTMNTTYPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,S,D

TOP

ACCSTMNTCYCL3

Attribute	Description	
Name	ACCSTMNTCYCL3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,Q,M,F,W,D,A

TOP

OFFLNLMT

Attribute	Description	
Name	OFFLNLMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTPROVREQD

Attribute	Description
Name	AUTPROVREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

PROVCCYTYP

Attribute	Description
Name	PROVCCYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,A

TOP

EXPSRCAT

Attribute	Description
Name	EXPSRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EVNTCLSCD

Attribute	Description
Name	EVNTCLSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8

TOP

DRINTUSNGRECV

Attribute	Description
Name	DRINTUSNGRECV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

VRFYFNDSFORDRINT

Attribute	Description
Name	VRFYFNDSFORDRINT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRINTNOTC

Attribute	Description
Name	DRINTNOTC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DRINTLIQDAY

Attribute	Description
Name	DRINTLIQDAY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRINTLIQDMODE

Attribute	**Description**
Name	DRINTLIQDMODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,A

TOP

CHGSTRTADV

Attribute	**Description**
Name	CHGSTRTADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVCDAYS

Attribute	**Description**
Name	ADVCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREBNKNGDAYS

Attribute	**Description**
Name	FREBNKNGDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDLST

Attribute	Description
Name	PRDLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

TXNLST

Attribute	Description
Name	TXNLST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,D

TOP

REGDAPPLCBLE

Attribute	Description
Name	REGDAPPLCBLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REGDPRDICTY

Attribute	Description
Name	REGDPRDICTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,S,N

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

BRNLST

Attribute	**Description**
Name	BRNLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

CUSATLST

Attribute	**Description**
Name	CUSATLST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

DEF_AUTODEP_AC_CLS

Attribute	**Description**
Name	DEF_AUTODEP_AC_CLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

AUTDEPTRNCD

Attribute	**Description**
Name	AUTDEPTRNCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AUTDEPCCY

Attribute	Description
Name	AUTDEPCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINBALREQD

Attribute	Description
Name	MINBALREQD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPMLTPLOF

Attribute	Description
Name	DEPMLTPLOF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKDEPOSITFRST

Attribute	Description
Name	BRKDEPOSITFRST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDEPDERRATCD

Attribute	Description
Name	AUTDEPDERRATCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8

TOP

AUTDEPDERRATTYP

Attribute	Description
Name	AUTDEPDERRATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,B,S

TOP

SWPMD

Attribute	Description
Name	SWPMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: AUTO,MANU

TOP

AUTDEPBRKMETHD

Attribute	Description
Name	AUTDEPBRKMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: LIFO,FIFO,MAXB,MINB

TOP

PRVDINTONBRKNDEP

Attribute	Description
Name	PRVDINTONBRKNDEP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOROLL

Attribute	**Description**
Name	AUTOROLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSONMATURTY

Attribute	**Description**
Name	CLSONMATURTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTLLIQDTN

Attribute	**Description**
Name	PRTLLIQDTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWPRTLIQAMTBLK

Attribute	**Description**
Name	ALLWPRTLIQAMTBLK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MVINTTOUNCLMD

Attribute	Description	
Name	MVINTTOUNCLMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MVPRICTOUNCLMD

Attribute	Description	
Name	MVPRICTOUNCLMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GRACEPRD

Attribute	Description	
Name	GRACEPRD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINTNRDAYS

Attribute	Description	
Name	MINTNRDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINTNRMNTHS

Attribute	Description
Name	MINTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MINTNRYRS

Attribute	Description
Name	MINTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DFLTTNRDAY

Attribute	Description
Name	DFLTTNRDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DFLTTNRMNTHS

Attribute	Description
Name	DFLTTNRMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

DFLTTNRYRS

Attribute	Description
Name	DFLTTNRYRS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MAXTNRDAYS

Attribute	Description

Name	MAXTNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNRMNTHS

Attribute	**Description**
Name	MAXTNRMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNRYRS

Attribute	**Description**
Name	MAXTNRYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDFLG

Attribute	**Description**
Name	RDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RDMVMATTOUNCLMD

Attribute	**Description**
Name	RDMVMATTOUNCLMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MOVEFUNDOVD

Attribute	Description
Name	MOVEFUNDOVD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RDMINSCHDLDAYS

Attribute	Description
Name	RDMINSCHDLDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDMININSTLMNTAMT

Attribute	Description
Name	RDMININSTLMNTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDSCHDLDAYS

Attribute	Description
Name	RDSCHDLDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDSCHDLMNTHS

Attribute	Description
Name	RDSCHDLMNTHS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RDSCHDLYRS

Attribute	Description
Name	RDSCHDLYRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDMAXSCHDLDAYS

Attribute	Description
Name	RDMAXSCHDLDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQBKFACLTY

Attribute	Description
Name	CHQBKFACLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREORDRCHQREQD

Attribute	Description
Name	AUTOREORDRCHQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTREORDRCHKLVLS

Attribute	Description
Name	AUTREORDRCHKLVLS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AUTOREORDRCHKLEAVES

Attribute	Description
Name	AUTOREORDRCHKLEAVES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LMTCHKREQD

Attribute	Description
Name	LMTCHKREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

OVRDRFTFACLTY

Attribute	Description
Name	OVRDRFTFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PASBKFACLTY

Attribute	Description
Name	PASBKFACLTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRCKRECBLE

Attribute	Description
Name	TRCKRECBLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACCSTATS

Attribute	Description
Name	ACCSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCLSAMDYRVRTRNSFMSTMNT

Attribute	Description
Name	EXCLSAMDYRVRTRNSFMSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALLWBCKPRDENTRY

Attribute	Description
Name	ALLWBCKPRDENTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CONSOLDTNREQD

Attribute	Description
Name	CONSOLDTNREQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ICINCLSN

Attribute	Description
Name	ICINCLSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRCKACCREDIC

Attribute	Description
Name	TRCKACCREDIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASDRCRADV

Attribute	Description
Name	HASDRCRADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACSTATDEPST

Attribute	Description
Name	ACSTATDEPST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LODGEMNTBK

Attribute	Description
Name	LODGEMNTBK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HASIS

Attribute	Description
Name	HASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AVALBALREQD

Attribute	Description
Name	AVALBALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REFREQD

Attribute	Description
Name	REFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

STATCHNGAUTMATIC

Attribute	Description	
Name	STATCHNGAUTMATIC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ILMAPPLICBL

Attribute	Description	
Name	ILMAPPLICBL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ATMFACLTY

Attribute	Description	
Name	ATMFACLTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNT

Attribute	Description	
Name	GENINTRIMSTMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GENINTRIMSTMNTONMVMNT

Attribute	Description
Name	GENINTRIMSTMNTONMVMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GENBALRPT

Attribute	Description
Name	GENBALRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INTRIMRPTSNCE

Attribute	Description
Name	INTRIMRPTSNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 942,941,940,

TOP

INTRIMRPTTYP

Attribute	Description
Name	INTRIMRPTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,S,T,

TOP

BALRPTSINCE

Attribute	Description
Name	BALRPTSINCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 941,940,950,

TOP

BALRPTTYP

Attribute	Description
Name	BALRPTTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,S,T,

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STMNTPARAM1

Attribute	Description
Name	STMNTPARAM1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 22

TOP

STMNTPARAM2

Attribute	Description
Name	STMNTPARAM2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

STMNTPARAM3

Attribute	**Description**	
Name	STMNTPARAM3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

ESCROWPROCESS

Attribute	**Description**	
Name	ESCROWPROCESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNCODE

Attribute	**Description**	
Name	TRNCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TRNREVCODE

Attribute	**Description**	
Name	TRNREVCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINOR_MAJOR

Attribute	**Description**
Name	MINOR_MAJOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / MI,MJ,BT,NA

TOP

REPL_CUST_SIG

Attribute	**Description**
Name	REPL_CUST_SIG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAX_NO_CHEQUE_REJECTIONS

Attribute	**Description**
Name	MAX_NO_CHEQUE_REJECTIONS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SAL_BLK_DAYS

Attribute	**Description**
Name	SAL_BLK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYSUNAUTHNOACTIVITY

Attribute	**Description**
Name	DAYSUNAUTHNOACTIVITY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYSAUTHNOACTIVITY

Attribute	Description
Name	DAYSAUTHNOACTIVITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINK_CCY

Attribute	Description
Name	LINK_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCY_OPTION

Attribute	Description
Name	CCY_OPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FIX_DAY

Attribute	Description
Name	FIX_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUALCCYDEP

Attribute	Description
Name	DUALCCYDEP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

SETTLE_BRIDGE_GL

Attribute	Description
Name	SETTLE_BRIDGE_GL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PRDCAT

Attribute	Description
Name	PRDCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

PCTXNCODE

Attribute	Description
Name	PCTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TDRATECHARTALLOW

Attribute	Description
Name	TDRATECHARTALLOW

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLUSTER_ID

Attribute	**Description**
Name	CLUSTER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PROJECTACCNT

Attribute	**Description**
Name	PROJECTACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRUSTACCASHLIMIT

Attribute	**Description**
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TURNOVER_EVENT_CLASS_CODE

Attribute	**Description**
Name	TURNOVER_EVENT_CLASS_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TURNOVER_RTOH_CODE

Attribute	Description	
Name	TURNOVER_RTOH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

LRGDRBALFLG

Attribute	Description	
Name	LRGDRBALFLG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DAYLIGHTLIMIT

Attribute	Description	
Name	DAYLIGHTLIMIT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRNOVR_CODE

Attribute	Description	
Name	TRNOVR_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Q,H,Y,

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEND_NOTIFICATION

Attribute	Description
Name	SEND_NOTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RT_CHARGE_PRODUCT

Attribute	Description
Name	RT_CHARGE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SPDANLSYS

Attribute	Description
Name	SPDANLSYS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPL_RATE

Attribute	**Description**
Name	SPL_RATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BLK_OPEN_DAYS

Attribute	**Description**
Name	BLK_OPEN_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_OPEN_MONTHS

Attribute	**Description**
Name	BLK_OPEN_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_MAT_DAYS

Attribute	**Description**
Name	BLK_MAT_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLK_MAT_MONTHS

Attribute	Description
Name	BLK_MAT_MONTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOW_TOPUP

Attribute	Description
Name	ALLOW_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INT_RATE_OPTION_TOPUP

Attribute	Description
Name	INT_RATE_OPTION_TOPUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,T

TOP

INT_RATE_OPTION_REDAMT

Attribute	Description
Name	INT_RATE_OPTION_REDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,R,S,E

TOP

INT_RATE_OPTION_REMAMT

Attribute	Description
Name	INT_RATE_OPTION_REMAMT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,O,R,E

TOP

INTRATE_CUMAMT_REQD

Attribute	Description	
Name	INTRATE_CUMAMT_REQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMP_WISE_TRACKING_REQD

Attribute	Description	
Name	COMP_WISE_TRACKING_REQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENABLE_SWEEP_IN

Attribute	Description	
Name	ENABLE_SWEEP_IN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENABLE_REV_SWEEP_IN

Attribute	Description	
Name	ENABLE_REV_SWEEP_IN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DEPACCCLS

Attribute	Description	
Name	DEPACCCLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

RATECHARTTENOR

Attribute	Description	
Name	RATECHARTTENOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

HOLIDAYCALENDAR

Attribute	Description	
Name	HOLIDAYCALENDAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,L,C,B,

TOP

HOLIDAYMOVEMENT

Attribute	Description	
Name	HOLIDAYMOVEMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,P,N,

TOP

MOVEACROSSMONTHS

Attribute	Description
Name	MOVEACROSSMONTHS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,N,

TOP

ADHOCHOL

Attribute	Description
Name	ADHOCHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,A,N,

TOP

APPLICABLEDEPTENOR

Attribute	Description
Name	APPLICABLEDEPTENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,D,

TOP

MONTHENDDEPOSIT

Attribute	Description
Name	MONTHENDDEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENM_DEPOSIT

Attribute	Description
Name	DENM_DEPOSIT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REPCKUPACCLSTNRONROLL

Attribute	Description
Name	REPCKUPACCLSTNRONROLL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEFERREDBALUPD

Attribute	Description
Name	DEFERREDBALUPD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MULTICURRENCY

Attribute	Description
Name	MULTICURRENCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MONTHS_C

Attribute	Description
Name	MONTHS_C

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_C

Attribute	Description
Name	DAYS_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HIGH_VAL_DEPOSIT_C

Attribute	Description
Name	HIGH_VAL_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHANLIST

Attribute	Description
Name	CHANLIST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

INSTBASIS

Attribute	Description
Name	INSTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,L

TOP

MONTHEND_INST

Attribute	Description
Name	MONTHEND_INST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_DEPOSIT

Attribute	Description
Name	NOTICE_DEPOSIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOTICE_LOCK_DAYS

Attribute	Description
Name	NOTICE_LOCK_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTICE_DAYS

Attribute	Description
Name	NOTICE_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BONUS_INTEREST_C

Attribute	Description
Name	BONUS_INTEREST_C
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BONUS_FACTOR_C

Attribute	Description	
Name	BONUS_FACTOR_C	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INT_EXPENSE_GL_C

Attribute	Description	
Name	INT_EXPENSE_GL_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TRANSACTION_CODE

Attribute	Description	
Name	TRANSACTION_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCCCY_CHANGE_C

Attribute	Description	
Name	ACCCCY_CHANGE_C	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PREMAT_REDM_C

Attribute	Description
Name	PREMAT_REDM_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UNCLAIMED_DAYS

Attribute	Description
Name	UNCLAIMED_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NC_DEPOSIT_C

Attribute	Description
Name	NC_DEPOSIT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

Status-Master

Attribute	Description	
Name	Status-Master	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CR_CB

Attribute	Description	
Name	CR_CB	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

CR_LINE

Attribute	Description	
Name	CR_LINE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CR_HO

Attribute	Description
Name	CR_HO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

DR_CB

Attribute	Description
Name	DR_CB
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

DR_LINE

Attribute	Description
Name	DR_LINE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

DR_HO

Attribute	Description
Name	DR_HO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

RBKPROVSN

Attribute	Description

Name	RBKPROVSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TXTSTATDESC

Attribute	**Description**
Name	TXTSTATDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Status-Detail

Attribute	**Description**
Name	Status-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROL

Attribute	**Description**
Name	ACCROL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCHD

Attribute	Description	
Name	ACCHD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

Status-Derivation

Attribute	Description	
Name	Status-Derivation	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATRUL1

Attribute	Description
Name	STATRUL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

STATRUL2

Attribute	Description
Name	STATRUL2
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

STATRUL3

Attribute	**Description**
Name	STATRUL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

STATRUL4

Attribute	**Description**
Name	STATRUL4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

STATRUL5

Attribute	**Description**
Name	STATRUL5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

COMPONENT_PRIORITY1

Attribute	**Description**
Name	COMPONENT_PRIORITY1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,P,I,C

TOP

COMPONENT_PRIORITY2

Attribute	Description
Name	COMPONENT_PRIORITY2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,I,C

TOP

COMPONENT_PRIORITY3

Attribute	Description
Name	COMPONENT_PRIORITY3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,I,C

TOP

Product-Maint

Attribute	Description
Name	Product-Maint
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

BLCKNGORDR

Attribute	Description
Name	BLCKNGORDR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

PRDCD

Attribute	Description

Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	**Description**
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Products

Attribute	**Description**
Name	Products
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	**Description**
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRTXN

Attribute	**Description**
Name	DRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CRTXN

Attribute	**Description**
Name	CRTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Transaction-Codes

Attribute	**Description**
Name	Transaction-Codes
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNCD

Attribute	**Description**
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TRNDESC

Attribute	Description
Name	TRNDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DRTXN

Attribute	Description
Name	DRTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CRTXN

Attribute	Description
Name	CRTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Branch-Restriction

Attribute	Description
Name	Branch-Restriction
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

BRNCD

Attribute	Description
Name	BRNCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Restriction

Attribute	**Description**
Name	Ccy-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-Preferences

Attribute	**Description**
Name	Ccy-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	**Description**
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINBAL

Attribute	Description
Name	MINBAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMCSHLMT

Attribute	Description
Name	ATMCSHLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ATMTRNSLMT

Attribute	Description
Name	ATMTRNSLMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRUSTACCASHLIMIT

Attribute	Description
Name	TRUSTACCASHLIMIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MINIMUM_OPENING_BALANCE

Attribute	Description
Name	MINIMUM_OPENING_BALANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCOUNT_OPENING_CHARGES

Attribute	Description
Name	ACCOUNT_OPENING_CHARGES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

THRESHOLD_AMOUNT

Attribute	Description
Name	THRESHOLD_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Cat-Restriction

Attribute	Description
Name	Cat-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTCAT

Attribute	Description
Name	CUSTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Restriction

Attribute	Description
Name	Cust-Restriction
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ALLWD

Attribute	Description
Name	ALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Interim-Dramt

Attribute	Description
Name	Interim-Dramt
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interim-Cramt

Attribute	**Description**
Name	Interim-Cramt
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime

Attribute	**Description**
Name	Msg-Gentime
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msg-Gentime1

Attribute	Description
Name	Msg-Gentime1
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GENTIM

Attribute	Description
Name	GENTIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Notice-Pref

Attribute	Description
Name	Notice-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVINTREQD

Attribute	Description
Name	ADVINTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MNTHLYFREEAMT

Attribute	Description
Name	MNTHLYFREEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTCPRD

Attribute	Description
Name	NOTCPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDITYPRD

Attribute	Description
Name	VALDITYPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Aclass-Doctype

Attribute	Description
Name	Aclass-Doctype
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER_TYPE

Attribute	Description
Name	CUSTOMER_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	I,C,B

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MANDATORY

Attribute	Description	
Name	MANDATORY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Sttms-Accls-Minmax-Amt-Ccy

Attribute	Description	
Name	Sttms-Accls-Minmax-Amt-Ccy	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dep-Accls-Rest

Attribute	Description
Name	Dep-Accls-Rest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AC_CLASS

Attribute	Description
Name	AC_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ADESC

Attribute	Description
Name	ADESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Denom-Deposit

Attribute	Description
Name	Denom-Deposit
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DENOMINATION_ID

Attribute	Description
Name	DENOMINATION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

DENOMINATION_DESC

Attribute	Description
Name	DENOMINATION_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

DENOMINATION_VALUE

Attribute	Description

Name	DENOMINATION_VALUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref

Attribute	**Description**
Name	Deposit-Ccy-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Deposit-Ccy-Pref-Dtl

Attribute	**Description**
Name	Deposit-Ccy-Pref-Dtl
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PAYIN

Attribute	Description	
Name	PAYIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INT_PAYOUT_C

Attribute	Description	
Name	INT_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRI_PAYOUT_C

Attribute	Description	
Name	PRI_PAYOUT_C	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Exrate-Pref

Attribute	Description
Name	Exrate-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PAYINOUT_C

Attribute	Description
Name	PAYINOUT_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O

TOP

MODE_TYPE_C

Attribute	Description
Name	MODE_TYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S

TOP

RATETYPE_C

Attribute	Description
Name	RATETYPE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RATECODE_C

Attribute	Description

Name	RATECODE_C
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

VARIANCE_C

Attribute	**Description**
Name	VARIANCE_C
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Chan-Rest-C

Attribute	**Description**
Name	Chan-Rest-C
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHANLID

Attribute	**Description**
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHANNDESC

Attribute	**Description**
Name	CHANNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Minmax-Ccy-C

Attribute	Description
Name	Minmax-Ccy-C
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHANLID

Attribute	Description
Name	CHANLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MIN_AMOUNT

Attribute	Description
Name	MIN_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAX_AMOUNT

Attribute	Description
Name	MAX_AMOUNT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOPUP_UNITS

Attribute	Description
Name	TOPUP_UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dorm-Param

Attribute	Description
Name	Dorm-Param
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCOUNT_CLASS

Attribute	Description
Name	ACCOUNT_CLASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

LCY_BALANCE

Attribute	Description
Name	LCY_BALANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQUENCY

Attribute	Description
Name	FREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Q,H,Y,

TOP

DORM_PREP_SEL_METH

Attribute	Description
Name	DORM_PREP_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W

TOP

DORM_PREP_DATE

Attribute	Description
Name	DORM_PREP_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_NTH

Attribute	Description
Name	DORM_PREP_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_DAY

Attribute	Description
Name	DORM_PREP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DORM_PREP_MONTH

Attribute	Description
Name	DORM_PREP_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PREP_ACTION

Attribute	Description
Name	DORM_PREP_ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / DP,GA,

TOP

DORM_PROC_SEL_METH

Attribute	Description
Name	DORM_PROC_SEL_METH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W

TOP

DORM_PROC_DATE

Attribute	Description
Name	DORM_PROC_DATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_NTH

Attribute	Description
Name	DORM_PROC_NTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_DAY

Attribute	Description
Name	DORM_PROC_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_PROC_MONTH

Attribute	Description
Name	DORM_PROC_MONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DORM_GL

Attribute	Description
Name	DORM_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DORM_TRN_CODE

Attribute	Description
Name	DORM_TRN_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DORM_ADV_GEN

Attribute	Description
Name	DORM_ADV_GEN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DORM_STOP_IC

Attribute	Description
Name	DORM_STOP_IC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

Misaccdflt

Attribute	Description
Name	Misaccdflt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISCODE2

Attribute	Description
Name	MISCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE3

Attribute	Description
Name	MISCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE4

Attribute	Description
Name	MISCODE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE5

Attribute	Description
Name	MISCODE5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE6

Attribute	**Description**
Name	MISCODE6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE7

Attribute	**Description**
Name	MISCODE7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE8

Attribute	**Description**
Name	MISCODE8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE9

Attribute	**Description**
Name	MISCODE9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCODE10

Attribute	**Description**
Name	MISCODE10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE1

Attribute	**Description**
Name	COSTCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE2

Attribute	**Description**
Name	COSTCODE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCODE3

Attribute	**Description**
Name	COSTCODE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCODE4

Attribute	Description	
Name	COSTCODE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCODE5

Attribute	Description	
Name	COSTCODE5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ACCLASS

Attribute	Description	
Name	ACCLASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

MISGROUP

Attribute	Description	
Name	MISGROUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCODE

Attribute	Description
Name	POOLCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCODE1

Attribute	Description
Name	MISCODE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS1

Attribute	Description
Name	MISCLASS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS2

Attribute	Description
Name	MISCLASS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS3

Attribute	Description
Name	MISCLASS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS4

Attribute	Description
Name	MISCLASS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS5

Attribute	Description
Name	MISCLASS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS6

Attribute	Description
Name	MISCLASS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS7

Attribute	Description
Name	MISCLASS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS8

Attribute	Description
Name	MISCLASS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS9

Attribute	Description
Name	MISCLASS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLASS10

Attribute	Description
Name	MISCLASS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKTOGROUP

Attribute	Description
Name	LINKTOGROUP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Status-Control

Attribute	Description	
Name	Status-Control	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.115.QueryBranch

QueryBranch

2.115.1.ST-QueryBranch-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Branch-Details-IO
BRNCD
CHEQUESTALEDAYS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHEQUESTALEDAYS

Attribute	Description
Name	CHEQUESTALEDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.115.2.ST-QueryBranch-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Branch-Details-IO*
      - *BRNCD*
      - *CHEQUESTALEDAYS*
    - *Branch-Details-Full*
      - *BRNCD*
      - *BRNNAME*
      - *PRNTBRN*
      - *REGNLOFC*
      - *TIMLVL*
      - *CNTRYCD*
      - *CIDIF*
      - *FUNDBRNCH*
      - *BRNLCY*
      - *CODATMBRN*
      - *CODINSTID*
      - *CODIBTRNCD*
      - *CODCUSTTRNS*
      - *OFFSTHOURS*

OFFSTMINS
BRNADDR
BRNADDR2
BRNADDR3
SWFTADDR
TELEXADDR
HOSTNAM
OFFSTHRS
OFFSTMIN
ENDOFINP
PCCLRGBRN
SUSPGLSL
CONTSUSPGLSL
SUSPGLFCY
CONTSUSPGLFCY
ATMSUSPGL
CONVGL
CONVTXNCD
CURRCYCLE
CURRPERIOD
REFHR
REFMIN
JOBSTAT
AUTOAUTH
DEFSTMNTSTAT
GEN
GEN103P
DEFBNKOPCD
PROCWITHOUTFLOAT
CLGBRNCD
SECTORCD
CLRBRN
ROUTNO
MSGGENDAY
BRNLCYDESC
PRNTBRNDESC
REGNLOFCDESC
CNTRYCDDESC
SUSPGLSLDESC
CONTSUSPGLSLDESC
SUSPGLFCYDESC
CONTSUSPGLFCYDESC
ATMSUSPGLDESC
CONVGLDESC

CONVTXNCDDESC
EXTVAL
BRNAVALSTAT
NETSUSPGL
WALKINCUST
INTSWAPCUST
CLRACC
OFFSTCLRACC
WEEKHOL1
WEELHOL2
CLRBNKCD
MISCCYMISMATCHGRP
INTERDICTCHKREQD
INTERDICTTIMOUT
STATPROCBASIS
PROVSNGFREQ
UNCOLLFNDSBASIS
DEFSTMNT
ENTGL
BCKVALCHKREQD
BCKVALDAYS
TRCKPREVYRPRLS
PLSPLITREQD
DRPRD
CRPRD
IBANMSKBNKCD
IBANMSKACCNO
LDAPTEMP
DRPRDDESC
CRPRDDESC
CURRTAXCYCLE
CONSOLTXCERTREQD
INDIVTAXVERTREQD
TAXCERTFREQ
FREQVAL
CIDIFDESC
MINORAGE
NOTIFICATIONPERIOD
MAXREALSUSAMT
MAXCONTSUSAMT
SUSENTRYREQ
SUSBATCHNO
SUSTXNCODE
REVSUSENTRYDAYS

TRANSFER_BRANCH
CASAAMTBLKTRNCODE
HOFFREQ
ALLWCORPACS
TRANSFER_TYPE
POSITION_ASSET_GL
POSITION_LIABILITY_GL
GL_CLASSS
CHEQUESTALEDAYS
TRANSACTION_CODE1
ELCM_REPLICATION
LMTEXP_NOTIFY_DAYS
REPORT_DSN
CHQNO_MASK
FILECONSTXNCODE
CNTRY_CKSUM_MASK
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Branch-Swift-Address
- *SWFTADRS*
- *DESC*

Branch-Customer-Params
- *STRTCUSTNO*
- *ENDCUSTNO*
- *STRTDUMMYCUSTNO*
- *ENDDUMMYCUSTNO*
- *START_PID_NO*
- *END_PID_NO*

Branch-Functions
- *FUNCID*

Branch-Ccy
- *CCYCD*
- *CCYDESC*

Branch-Message-Type
- *MODULE*
- *LCYMSGTYP*

Dup-Chk
- *MODULE1*
- *DUP_FLG*

DUP_DAY
Account-Params
BRNCD
CUSTACCMSK
CHKSUMALGO
STRTACCNO
ENDACCNO
ACAUTOGENFLG
LDAUTOACCFLG
AUTOSTRTACCNO
AUTOENDACCNO
CUSTACCALG
CUSTNOALG
FNDSTACNO
FNDEDACNO
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Branch-Details-IO

Attribute	Description
Name	Branch-Details-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHEQUESTALEDAYS

Attribute	Description
Name	CHEQUESTALEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Branch-Details-Full

Attribute	Description
Name	Branch-Details-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRNTBRN

Attribute	Description
Name	PRNTBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGNLOFC

Attribute	Description
Name	REGNLOFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TIMLVL

Attribute	Description
Name	TIMLVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRYCD

Attribute	Description
Name	CNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIDIF

Attribute	Description
Name	CIDIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

FUNDBRNCH

Attribute	Description
Name	FUNDBRNCH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRNLCY

Attribute	**Description**
Name	BRNLCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CODATMBRN

Attribute	**Description**
Name	CODATMBRN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CODINSTID

Attribute	**Description**
Name	CODINSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CODIBTRNCD

Attribute	**Description**
Name	CODIBTRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CODCUSTTRNS

Attribute	**Description**
Name	CODCUSTTRNS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OFFSTHOURS

Attribute	**Description**
Name	OFFSTHOURS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OFFSTMINS

Attribute	**Description**
Name	OFFSTMINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRNADDR

Attribute	**Description**
Name	BRNADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRNADDR2

Attribute	**Description**
Name	BRNADDR2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNADDR3

Attribute	**Description**
Name	BRNADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWFTADDR

Attribute	**Description**
Name	SWFTADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

HOSTNAM

Attribute	**Description**
Name	HOSTNAM
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OFFSTHRS

Attribute	Description
Name	OFFSTHRS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OFFSTMIN

Attribute	Description
Name	OFFSTMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ENDOFINP

Attribute	Description
Name	ENDOFINP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PCCLRGBRN

Attribute	Description
Name	PCCLRGBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SUSPGLSL

Attribute	Description
Name	SUSPGLSL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONTSUSPGLSL

Attribute	Description
Name	CONTSUSPGLSL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SUSPGLFCY

Attribute	Description
Name	SUSPGLFCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONTSUSPGLFCY

Attribute	Description
Name	CONTSUSPGLFCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ATMSUSPGL

Attribute	Description
Name	ATMSUSPGL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONVGL

Attribute	**Description**
Name	CONVGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CONVTXNCD

Attribute	**Description**
Name	CONVTXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURRCYCLE

Attribute	**Description**
Name	CURRCYCLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CURRPERIOD

Attribute	**Description**
Name	CURRPERIOD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFHR

Attribute	Description
Name	REFHR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFMIN

Attribute	Description
Name	REFMIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JOBSTAT

Attribute	Description
Name	JOBSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEFSTMNTSTAT

Attribute	Description
Name	DEFSTMNTSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: 1,2,3,

TOP

GEN103P

Attribute	Description
Name	GEN103P
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DEFBNKOPCD

Attribute	Description
Name	DEFBNKOPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

PROCWITHOUTFLOAT

Attribute	Description
Name	PROCWITHOUTFLOAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLGBRNCD

Attribute	**Description**
Name	CLGBRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLRBRN

Attribute	**Description**
Name	CLRBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ROUTNO

Attribute	**Description**
Name	ROUTNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

MSGGENDAY

Attribute	**Description**	
Name	MSGGENDAY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRNLCYDESC

Attribute	**Description**	
Name	BRNLCYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRNTBRNDESC

Attribute	**Description**	
Name	PRNTBRNDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGNLOFCDESC

Attribute	**Description**	
Name	REGNLOFCDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CNTRYCDDESC

Attribute	Description
Name	CNTRYCDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLSLDESC

Attribute	Description
Name	SUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONTSUSPGLSLDESC

Attribute	Description
Name	CONTSUSPGLSLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SUSPGLFCYDESC

Attribute	Description
Name	SUSPGLFCYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CONTSUSPGLFCYDESC

Attribute	Description
Name	CONTSUSPGLFCYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ATMSUSPGLDESC

Attribute	Description
Name	ATMSUSPGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CONVGLDESC

Attribute	Description
Name	CONVGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CONVTXNCDDESC

Attribute	Description
Name	CONVTXNCDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EXTVAL

Attribute	Description
Name	EXTVAL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRNAVALSTAT

Attribute	**Description**
Name	BRNAVALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NETSUSPGL

Attribute	**Description**
Name	NETSUSPGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

WALKINCUST

Attribute	**Description**
Name	WALKINCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INTSWAPCUST

Attribute	**Description**
Name	INTSWAPCUST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CLRACC

Attribute	Description
Name	CLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OFFSTCLRACC

Attribute	Description
Name	OFFSTCLRACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

WEEKHOL1

Attribute	Description
Name	WEEKHOL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

WEELHOL2

Attribute	Description
Name	WEELHOL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

CLRBNKCD

Attribute	**Description**
Name	CLRBNKCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MISCCYMISMATCHGRP

Attribute	**Description**
Name	MISCCYMISMATCHGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INTERDICTCHKREQD

Attribute	**Description**
Name	INTERDICTCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INTERDICTTIMOUT

Attribute	**Description**
Name	INTERDICTTIMOUT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATPROCBASIS

Attribute	Description
Name	STATPROCBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: G,C,

TOP

PROVSNGFREQ

Attribute	Description
Name	PROVSNGFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,

TOP

UNCOLLFNDSBASIS

Attribute	Description
Name	UNCOLLFNDSBASIS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: U,A,

TOP

DEFSTMNT

Attribute	Description
Name	DEFSTMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ENTGL

Attribute	Description
Name	ENTGL

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BCKVALCHKREQD

Attribute	**Description**
Name	BCKVALCHKREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BCKVALDAYS

Attribute	**Description**
Name	BCKVALDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRCKPREVYRPRLS

Attribute	**Description**
Name	TRCKPREVYRPRLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PLSPLITREQD

Attribute	**Description**
Name	PLSPLITREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DRPRD

Attribute	Description	
Name	DRPRD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

CRPRD

Attribute	Description	
Name	CRPRD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

IBANMSKBNKCD

Attribute	Description	
Name	IBANMSKBNKCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

IBANMSKACCNO

Attribute	Description	
Name	IBANMSKACCNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

LDAPTEMP

Attribute	Description
Name	LDAPTEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 500

TOP

DRPRDDESC

Attribute	Description
Name	DRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CRPRDDESC

Attribute	Description
Name	CRPRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRTAXCYCLE

Attribute	Description
Name	CURRTAXCYCLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CONSOLTXCERTREQD

Attribute	Description
Name	CONSOLTXCERTREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INDIVTAXVERTREQD

Attribute	Description
Name	INDIVTAXVERTREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TAXCERTFREQ

Attribute	Description
Name	TAXCERTFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,Q,H,Y,

TOP

FREQVAL

Attribute	Description
Name	FREQVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

CIDIFDESC

Attribute	Description
Name	CIDIFDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MINORAGE

Attribute	**Description**
Name	MINORAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTIFICATIONPERIOD

Attribute	**Description**
Name	NOTIFICATIONPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXREALSUSAMT

Attribute	**Description**
Name	MAXREALSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTSUSAMT

Attribute	**Description**
Name	MAXCONTSUSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUSENTRYREQ

Attribute	**Description**
Name	SUSENTRYREQ

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SUSBATCHNO

Attribute	**Description**
Name	SUSBATCHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SUSTXNCODE

Attribute	**Description**
Name	SUSTXNCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REVSUSENTRYDAYS

Attribute	**Description**
Name	REVSUSENTRYDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSFER_BRANCH

Attribute	**Description**
Name	TRANSFER_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CASAAMTBLKTRNCODE

Attribute	Description	
Name	CASAAMTBLKTRNCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

HOFFREQ

Attribute	Description	
Name	HOFFREQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ALLWCORPACS

Attribute	Description	
Name	ALLWCORPACS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRANSFER_TYPE

Attribute	Description	
Name	TRANSFER_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,R,

TOP

POSITION_ASSET_GL

Attribute	Description
Name	POSITION_ASSET_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

POSITION_LIABILITY_GL

Attribute	Description
Name	POSITION_LIABILITY_GL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GL_CLASSS

Attribute	Description
Name	GL_CLASSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CHEQUESTALEDAYS

Attribute	Description
Name	CHEQUESTALEDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSACTION_CODE1

Attribute	Description
Name	TRANSACTION_CODE1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ELCM_REPLICATION

Attribute	**Description**
Name	ELCM_REPLICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LMTEXP_NOTIFY_DAYS

Attribute	**Description**
Name	LMTEXP_NOTIFY_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPORT_DSN

Attribute	**Description**
Name	REPORT_DSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHQNO_MASK

Attribute	**Description**
Name	CHQNO_MASK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

FILECONSTXNCODE

Attribute	Description
Name	FILECONSTXNCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTRY_CKSUM_MASK

Attribute	Description
Name	CNTRY_CKSUM_MASK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Branch-Swift-Address

Attribute	**Description**
Name	Branch-Swift-Address
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SWFTADRS

Attribute	**Description**
Name	SWFTADRS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Branch-Customer-Params

Attribute	**Description**
Name	Branch-Customer-Params
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTCUSTNO

Attribute	Description
Name	STRTCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ENDCUSTNO

Attribute	Description
Name	ENDCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STRTDUMMYCUSTNO

Attribute	Description
Name	STRTDUMMYCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ENDDUMMYCUSTNO

Attribute	Description
Name	ENDDUMMYCUSTNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

START_PID_NO

Attribute	Description
Name	START_PID_NO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

END_PID_NO

Attribute	Description
Name	END_PID_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Branch-Functions

Attribute	Description
Name	Branch-Functions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCID

Attribute	Description
Name	FUNCID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Branch-Ccy

Attribute	Description
Name	Branch-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCD

Attribute	Description
Name	CCYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	3

TOP

CCYDESC

Attribute	Description	
Name	CCYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

Branch-Message-Type

Attribute	Description	
Name	Branch-Message-Type	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	2

TOP

LCYMSGTYP

Attribute	Description	
Name	LCYMSGTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S,M,P,

TOP

Dup-Chk

Attribute	Description
Name	Dup-Chk
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MODULE1

Attribute	Description
Name	MODULE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

DUP_FLG

Attribute	Description
Name	DUP_FLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUP_DAY

Attribute	Description
Name	DUP_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Account-Params

Attribute	Description
Name	Account-Params
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCMSK

Attribute	Description	
Name	CUSTACCMSK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CHKSUMALGO

Attribute	Description	
Name	CHKSUMALGO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	mod11,mod97,mod11WW,mod10,U,

TOP

STRTACCNO

Attribute	Description	
Name	STRTACCNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ENDACCNO

Attribute	Description
Name	ENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACAUTOGENFLG

Attribute	Description
Name	ACAUTOGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDAUTOACCFLG

Attribute	Description
Name	LDAUTOACCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOSTRTACCNO

Attribute	Description
Name	AUTOSTRTACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOENDACCNO

Attribute	Description
Name	AUTOENDACCNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTACCALG

Attribute	Description
Name	CUSTACCALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTNOALG

Attribute	Description
Name	CUSTNOALG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FNDSTACNO

Attribute	Description
Name	FNDSTACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FNDEDACNO

Attribute	Description
Name	FNDEDACNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 150 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.116.QueryBranchSysDates

Query of Branch Date

2.116.1.ST-QueryBranchSysDates-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Branch-Date-IO*
    - *BRNCHCOD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Branch-Date-IO

Attribute	Description
Name	Branch-Date-IO
Datatype	
Description	Includes Branch Sysyem Dates Querying Input Only type details

TOP

BRNCHCOD

Attribute	Description	
Name	BRNCHCOD	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.116.2.ST-QueryBranchSysDates-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Branch-Date-IO*
      - *BRNCHCOD*
    - *Branch-Date-Full*
      - *BRNCHCOD*
      - *BranchName*
      - *TODAY*
      - *PREWRKDAY*
      - *NXTWRKDAY*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Branch-Date-IO

Attribute	Description
Name	Branch-Date-IO
Datatype	
Description	Includes Branch Sysyem Dates Querying Input Only type details

TOP

BRNCHCOD

Attribute	Description	
Name	BRNCHCOD	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Branch-Date-Full

Attribute	Description
Name	Branch-Date-Full
Datatype	
Description	Includes Branch Sysyem Dates Querying Full type details

TOP

BRNCHCOD

Attribute	Description	
Name	BRNCHCOD	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BranchName

Attribute	Description
Name	BranchName
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TODAY

Attribute	Description
Name	TODAY
Datatype	Date
Description	Indicates Todays Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREWRKDAY

Attribute	Description
Name	PREWRKDAY
Datatype	Date
Description	Indicates Previous Working Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTWRKDAY

Attribute	Description
Name	NXTWRKDAY
Datatype	Date
Description	Indicates Next Working Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

2.117.QueryBranchTrfr

QueryBranchTrfr

2.117.1.ST-QueryBranchTrfr-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Brn-Transfer-IO*
    - *TRANSFER_ID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

2.117.2.ST-QueryBranchTrfr-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Brn-Transfer-IO*
      - *TRANSFER_ID*
    - *Sttms-Brn-Transfer-Full*
      - *CURRENT_BRANCH_CODE*
      - *TARGET_BRANCH_CODESS*
      - *TRANSFER_DATE*
      - *TRANSFER_ID*
      - *TRANSFER_LENDING_MODULE*
      - *CI_REQ*
      - *MO_REQ*
      - *CASA_REQ*
      - *TD_REQ*
      - *CURRENT_BRANCH_NAME*
      - *TARGET_BRANCH_NAME*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Brn-Transfer-IO

Attribute	Description
Name	Sttms-Brn-Transfer-IO
Datatype	
Description	

TOP

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Sttms-Brn-Transfer-Full

Attribute	Description
Name	Sttms-Brn-Transfer-Full
Datatype	
Description	

TOP

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TARGET_BRANCH_CODESS

Attribute	Description
Name	TARGET_BRANCH_CODESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRANSFER_ID

Attribute	Description
Name	TRANSFER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRANSFER_LENDING_MODULE

Attribute	Description
Name	TRANSFER_LENDING_MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CI_REQ

Attribute	Description
Name	CI_REQ

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MO_REQ

Attribute	Description
Name	MO_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CASA_REQ

Attribute	Description
Name	CASA_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TD_REQ

Attribute	Description
Name	TD_REQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CURRENT_BRANCH_NAME

Attribute	Description
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

TARGET_BRANCH_NAME

Attribute	Description
Name	TARGET_BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.118.QueryCRSRequest

Query Of Adhoc Consolidated Statement Request

2.118.1.ST-QueryCRSRequest-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttm-Crs-Master-IO*
    - *REFERENCENO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.118.2.ST-QueryCRSRequest-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Crs-Master-IO*
      - *REFERENCENO*
    - *Sttm-Crs-Master-Full*
      - *TO_DATE*
      - *REFERENCENO*
      - *CUSTOMER_NO*
      - *BRANCHCODE*
      - *REQUESTTYPE*
      - *FROMDATE*
      - *PROCESSSTAT*
      - *REQUESTDATE*
      - *PROCESS_STATUS_DETAILS*
      - *E-STATEMENT*
      - *CHARGEBRANCH*
      - *CHARGEACCOUNT*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Crs-Master-IO

Attribute	Description
Name	Sttm-Crs-Master-IO
Datatype	
Description	

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description	Indicates Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Crs-Master-Full

Attribute	Description
Name	Sttm-Crs-Master-Full
Datatype	
Description	

TOP

TO_DATE

Attribute	Description	
Name	TO_DATE	
Datatype	Date	
Description	Specifies the To Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	Indicates Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	Specifies The Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUESTTYPE

Attribute	Description
Name	REQUESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,L

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	Specifies the From Date
Attributes	Attribute: minOccurs, Description: 0

TOP

PROCESSSTAT

Attribute	Description
Name	PROCESSSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

REQUESTDATE

Attribute	Description
Name	REQUESTDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

PROCESS_STATUS_DETAILS

Attribute	Description
Name	PROCESS_STATUS_DETAILS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

E-STATEMENT

Attribute	Description
Name	E-STATEMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHARGEBRANCH

Attribute	**Description**
Name	CHARGEBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHARGEACCOUNT

Attribute	**Description**
Name	CHARGEACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

2.119.QueryCardAccount

Query of Card Accounts Detail

2.119.1.ST-QueryCardAccount-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CardAccount-IO*
    - *BRNCODE*
    - *CUSTACNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates the card account information.

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO

<table>
<tr><td>Datatype</td><td>String</td></tr>
<tr><td>Description</td><td>Indicate Customer Account Number</td></tr>
<tr><td>Attributes</td><td><table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table></td></tr>
<tr><td>Restrictions</td><td><table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table></td></tr>
</table>

TOP

2.119.2.ST-QueryCardAccount-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CardAccount-IO*
      - *BRNCODE*
      - *CUSTACNO*
    - *CardAccount-Full*
      - *BRNCODE*
      - *CUSTACNO*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CardAccount-IO

Attribute	Description
Name	CardAccount-IO
Datatype	
Description	it indicates the card account information.

TOP

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicate Customer Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CardAccount-Full

Attribute	Description
Name	CardAccount-Full
Datatype	
Description	it indicates the detail about card account.

TOP

BRNCODE

Attribute	Description

Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACNO

Attribute	Description
Name	CUSTACNO
Datatype	String
Description	Indicate Customer Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String

Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status O - Open C - Close

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Contract Authorize details is atleast Authorized Once .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.120.QueryCardMaster

QueryCardMaster

2.120.1.ST-QueryCardMaster-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Debit-Card-Master-IO*
    - *CUST_NO*
    - *CUST_AC_NO*
    - *BRANCH_CODE*
    - *REQ_REF_NO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQ_REF_NO

Attribute	**Description**
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.120.2.ST-QueryCardMaster-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Debit-Card-Master-IO*
      - *CUST_NO*
      - *CUST_AC_NO*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
    - *Sttms-Debit-Card-Master-Full*
      - *CUST_NO*
      - *CUST_AC_NO*
      - *CARD_PRODUCT*
      - *CARD_BIN*
      - *BRANCH_CODE*
      - *REQ_REF_NO*
      - *HOLD_BILL_INDICATOR*
      - *RECOVERY_ACCOUNT*
      - *NAME_ON_CARD*
      - *OWNER_ID_NO1*
      - *ADD_HOLDER_IDNO*
      - *OWNER_ID_TYPE*

ADDL_HOLDER_ID_TYPE
ISSUER
PLASTIC_TYPE
CREDIT_CARD_LIMIT
PRIMARY_CARD
CARD_APPL_DATE
CARD_ISSUED_DT
CARD_RENEWAL_DT
CARD_EXPIRY_DT
ACTIVATION_DT
CARD_NO
CARD_SEQ_NO
DISPATCH_STATUS
PIN_MAILED_STATUS
CARD_STATUS
LAST_STATUS_UPDATED
LAST_OPERATION
BILL_CYCLE
REMARKS
RENEWAL_UNIT
RENEWAL_CYCLE
ATM_LIMIT_UNIT
ATM_COUNT_LIMIT
ATM_AMOUNT_LIMIT
REM_ATM_COUNT_UNIT
REM_ATM_AMOUNT_LIMIT
POS_LIMIT_UNIT
POS_COUNT_LIMIT
POS_AMOUNT_LIMIT
REM_POS_LIMIT_UNIT
REM_POS_COUNT_LIMIT
REM_POS_AMOUNT_LIMIT
PRIMARY_CARD_NO
DEL_CHNL_CARD
DEL_CHNL_PIN
ADDL_HOLDER_DOB
ADDL_HOLDER_RELATION
DR_CR_INDICATOR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Debit-Card-Master-IO

Attribute	Description
Name	Sttms-Debit-Card-Master-IO
Datatype	
Description	

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUST_AC_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sttms-Debit-Card-Master-Full

Attribute	Description
Name	Sttms-Debit-Card-Master-Full
Datatype	
Description	

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

REQ_REF_NO

Attribute	Description
Name	REQ_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

HOLD_BILL_INDICATOR

Attribute	Description
Name	HOLD_BILL_INDICATOR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECOVERY_ACCOUNT

Attribute	**Description**
Name	RECOVERY_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

NAME_ON_CARD

Attribute	**Description**
Name	NAME_ON_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OWNER_ID_NO1

Attribute	**Description**
Name	OWNER_ID_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADD_HOLDER_IDNO

Attribute	**Description**
Name	ADD_HOLDER_IDNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

OWNER_ID_TYPE

Attribute	Description
Name	OWNER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ADDL_HOLDER_ID_TYPE

Attribute	Description
Name	ADDL_HOLDER_ID_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ISSUER

Attribute	Description
Name	ISSUER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PLASTIC_TYPE

Attribute	Description
Name	PLASTIC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

CREDIT_CARD_LIMIT

Attribute	Description	
Name	CREDIT_CARD_LIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CARD_APPL_DATE

Attribute	Description	
Name	CARD_APPL_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_ISSUED_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_RENEWAL_DT

Attribute	Description
Name	CARD_RENEWAL_DT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CARD_NO

Attribute	Description
Name	CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 19

TOP

CARD_SEQ_NO

Attribute	Description
Name	CARD_SEQ_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DISPATCH_STATUS

Attribute	Description
Name	DISPATCH_STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

PIN_MAILED_STATUS

Attribute	**Description**
Name	PIN_MAILED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

CARD_STATUS

Attribute	**Description**
Name	CARD_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LAST_STATUS_UPDATED

Attribute	**Description**
Name	LAST_STATUS_UPDATED
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OPERATION

Attribute	**Description**
Name	LAST_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BILL_CYCLE

Attribute	**Description**
Name	BILL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RENEWAL_UNIT

Attribute	**Description**
Name	RENEWAL_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,M,W,D,

TOP

RENEWAL_CYCLE

Attribute	**Description**
Name	RENEWAL_CYCLE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ATM_LIMIT_UNIT

Attribute	**Description**
Name	ATM_LIMIT_UNIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,M,W,D

TOP

ATM_COUNT_LIMIT

Attribute	Description
Name	ATM_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ATM_AMOUNT_LIMIT

Attribute	Description
Name	ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_COUNT_UNIT

Attribute	Description
Name	REM_ATM_COUNT_UNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM_ATM_AMOUNT_LIMIT

Attribute	Description
Name	REM_ATM_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POS_LIMIT_UNIT

Attribute	Description
Name	POS_LIMIT_UNIT

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,M,W,D

TOP

POS_COUNT_LIMIT

Attribute	Description
Name	POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POS_AMOUNT_LIMIT

Attribute	Description
Name	POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM_POS_LIMIT_UNIT

Attribute	Description
Name	REM_POS_LIMIT_UNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,M,W,D

TOP

REM_POS_COUNT_LIMIT

Attribute	Description
Name	REM_POS_COUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM_POS_AMOUNT_LIMIT

Attribute	Description
Name	REM_POS_AMOUNT_LIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRIMARY_CARD_NO

Attribute	Description
Name	PRIMARY_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

DEL_CHNL_CARD

Attribute	Description
Name	DEL_CHNL_CARD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DEL_CHNL_PIN

Attribute	Description
Name	DEL_CHNL_PIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ADDL_HOLDER_DOB

Attribute	Description
Name	ADDL_HOLDER_DOB
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ADDL_HOLDER_RELATION

Attribute	Description	
Name	ADDL_HOLDER_RELATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DR_CR_INDICATOR

Attribute	Description	
Name	DR_CR_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.121.QueryCustCatMaint

Query of Customer Category Maintenance

2.121.1.ST-QueryCustCatMaint-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttm-Customer-Cat-IO
CUSTCAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Querying Input Only type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.121.2.ST-QueryCustCatMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttm-Customer-Cat-IO*
      - *CUSTCAT*
    - *Sttm-Customer-Cat-Full*
      - *CUSTCAT*
      - *CUSTCATDESC*
      - *POPULATECHANGESLOG*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttm-Customer-Cat-IO

Attribute	Description
Name	Sttm-Customer-Cat-IO
Datatype	
Description	Includes Customer Category Maintenance Querying Input Only type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sttm-Customer-Cat-Full

Attribute	Description
Name	Sttm-Customer-Cat-Full
Datatype	
Description	Includes Customer Category Maintenance Querying Full type details

TOP

CUSTCAT

Attribute	Description	
Name	CUSTCAT	
Datatype	String	
Description	Indicates the Customer Category.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTCATDESC

Attribute	Description

Name	CUSTCATDESC
Datatype	String
Description	Indicates the Customer Category Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POPULATECHANGESLOG

Attribute	**Description**
Name	POPULATECHANGESLOG
Datatype	String
Description	Indicates the populate Changes Log. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description

Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	Attribute: maxOccurs — unbounded; Attribute: minOccurs — 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs — unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

Static Maintenance
[August] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2014], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of
this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.