

Gateway Documentation - Switch Gateway Service  
Oracle FLEXCUBE Universal Banking  
Release FCUBS\_12.0.87.1.0  
[August] [2014]



# Table Of Contents

<b>1. BACKGROUND</b>	<b>1</b>
<b>2. FCUBSSwitchService</b>	<b>2</b>
<b>2.1. QueryNetworkDetails</b>	<b>2</b>
2.1.1. SW-QueryNetworkDetails-Req-IO-MSG.xsd	2
2.1.2. SW-QueryNetworkDetails-Res-Full-MSG.xsd	8
<b>2.2. QueryNetworkDetailss</b>	<b>21</b>
2.2.1. SW-QueryNetworkDetailss-Req-IO-MSG.xsd	21
2.2.2. SW-QueryNetworkDetailss-Res-Full-MSG.xsd	27
<b>2.3. QueryProcessCodeMapping</b>	<b>39</b>
2.3.1. SW-QueryProcessCodeMapping-Req-IO-MSG.xsd	39
2.3.2. SW-QueryProcessCodeMapping-Res-Full-MSG.xsd	46
<b>2.4. QueryTerminalDetails</b>	<b>58</b>
2.4.1. SW-QueryTerminalDetails-Req-IO-MSG.xsd	58
2.4.2. SW-QueryTerminalDetails-Res-Full-MSG.xsd	64
<b>2.5. QueryUtilityProvider</b>	<b>76</b>
2.5.1. SW-QueryUtilityProvider-Req-IO-MSG.xsd	76
2.5.2. SW-QueryUtilityProvider-Res-Full-MSG.xsd	82
<b>2.6. QueryUtilityProviderDet</b>	<b>93</b>
2.6.1. SW-QueryUtilityProviderDet-Req-IO-MSG.xsd	93
2.6.2. SW-QueryUtilityProviderDet-Res-Full-MSG.xsd	99
<b>2.7. ReopenCARDTOACCMAPPING</b>	<b>110</b>
2.7.1. SW-ReopenCARDTOACCMAPPING-Req-Full-MSG.xsd	110
2.7.2. SW-ReopenCARDTOACCMAPPING-Req-IO-MSG.xsd	121
2.7.3. SW-ReopenCARDTOACCMAPPING-Res-Full-MSG.xsd	128
2.7.4. SW-ReopenCARDTOACCMAPPING-Res-PK-MSG.xsd	140
<b>2.8. ReopenCardAccount</b>	<b>150</b>
2.8.1. SW-ReopenCardAccount-Req-Full-MSG.xsd	150
2.8.2. SW-ReopenCardAccount-Req-IO-MSG.xsd	165
2.8.3. SW-ReopenCardAccount-Res-Full-MSG.xsd	173
2.8.4. SW-ReopenCardAccount-Res-PK-MSG.xsd	189
<b>2.9. ReopenCardCustomer</b>	<b>199</b>
2.9.1. SW-ReopenCardCustomer-Req-Full-MSG.xsd	199
2.9.2. SW-ReopenCardCustomer-Req-IO-MSG.xsd	213
2.9.3. SW-ReopenCardCustomer-Res-Full-MSG.xsd	220
2.9.4. SW-ReopenCardCustomer-Res-PK-MSG.xsd	236
<b>2.10. ReopenForwaderDetails</b>	<b>246</b>
2.10.1. SW-ReopenForwaderDetails-Req-Full-MSG.xsd	246
2.10.2. SW-ReopenForwaderDetails-Req-IO-MSG.xsd	256
2.10.3. SW-ReopenForwaderDetails-Res-Full-MSG.xsd	263
2.10.4. SW-ReopenForwaderDetails-Res-PK-MSG.xsd	274
<b>2.11. ModifyCARDTOACCMAPPING</b>	<b>283</b>
2.11.1. SW-ModifyCARDTOACCMAPPING-Req-Full-MSG.xsd	283
2.11.2. SW-ModifyCARDTOACCMAPPING-Req-IO-MSG.xsd	294
2.11.3. SW-ModifyCARDTOACCMAPPING-Res-Full-MSG.xsd	302
2.11.4. SW-ModifyCARDTOACCMAPPING-Res-PK-MSG.xsd	314
<b>2.12. ModifyCardAccMapping</b>	<b>325</b>
2.12.1. SW-ModifyCardAccMapping-Req-Full-MSG.xsd	325
2.12.2. SW-ModifyCardAccMapping-Req-IO-MSG.xsd	334
2.12.3. SW-ModifyCardAccMapping-Res-Full-MSG.xsd	341
2.12.4. SW-ModifyCardAccMapping-Res-PK-MSG.xsd	353
<b>2.13. ModifyCardUpload</b>	<b>366</b>

2.13.1. SW-ModifyCardUpload-Req-Full-MSG.xsd	366
2.13.2. SW-ModifyCardUpload-Req-IO-MSG.xsd	375
2.13.3. SW-ModifyCardUpload-Res-Full-MSG.xsd	382
2.13.4. SW-ModifyCardUpload-Res-PK-MSG.xsd	394
<b>2.14. ModifyCashDeposit</b>	<b>407</b>
2.14.1. SW-ModifyCashDeposit-Req-Full-MSG.xsd	407
2.14.2. SW-ModifyCashDeposit-Req-IO-MSG.xsd	421
2.14.3. SW-ModifyCashDeposit-Res-Full-MSG.xsd	428
2.14.4. SW-ModifyCashDeposit-Res-PK-MSG.xsd	444
<b>2.15. ModifyForwaderDetails</b>	<b>460</b>
2.15.1. SW-ModifyForwaderDetails-Req-Full-MSG.xsd	460
2.15.2. SW-ModifyForwaderDetails-Req-IO-MSG.xsd	470
2.15.3. SW-ModifyForwaderDetails-Res-Full-MSG.xsd	478
2.15.4. SW-ModifyForwaderDetails-Res-PK-MSG.xsd	489
<b>2.16. ModifyMerchDetails</b>	<b>500</b>
2.16.1. SW-ModifyMerchDetails-Req-Full-MSG.xsd	500
2.16.2. SW-ModifyMerchDetails-Req-IO-MSG.xsd	509
2.16.3. SW-ModifyMerchDetails-Res-Full-MSG.xsd	516
2.16.4. SW-ModifyMerchDetails-Res-PK-MSG.xsd	528
<b>2.17. ModifyNetworkDetails</b>	<b>541</b>
2.17.1. SW-ModifyNetworkDetails-Req-Full-MSG.xsd	541
2.17.2. SW-ModifyNetworkDetails-Req-IO-MSG.xsd	552
2.17.3. SW-ModifyNetworkDetails-Res-Full-MSG.xsd	561
2.17.4. SW-ModifyNetworkDetails-Res-PK-MSG.xsd	577
<b>2.18. ModifyNetworkDetailss</b>	<b>594</b>
2.18.1. SW-ModifyNetworkDetailss-Req-Full-MSG.xsd	594
2.18.2. SW-ModifyNetworkDetailss-Req-IO-MSG.xsd	604
2.18.3. SW-ModifyNetworkDetailss-Res-Full-MSG.xsd	613
2.18.4. SW-ModifyNetworkDetailss-Res-PK-MSG.xsd	625
<b>2.19. ModifyProcessCodeMapping</b>	<b>636</b>
2.19.1. SW-ModifyProcessCodeMapping-Req-Full-MSG.xsd	636
2.19.2. SW-ModifyProcessCodeMapping-Req-IO-MSG.xsd	646
2.19.3. SW-ModifyProcessCodeMapping-Res-Full-MSG.xsd	654
2.19.4. SW-ModifyProcessCodeMapping-Res-PK-MSG.xsd	667
<b>2.20. ModifyTerminalDetails</b>	<b>681</b>
2.20.1. SW-ModifyTerminalDetails-Req-Full-MSG.xsd	681
2.20.2. SW-ModifyTerminalDetails-Req-IO-MSG.xsd	691
2.20.3. SW-ModifyTerminalDetails-Res-Full-MSG.xsd	698
2.20.4. SW-ModifyTerminalDetails-Res-PK-MSG.xsd	710
<b>2.21. ModifyUtilityProvider</b>	<b>723</b>
2.21.1. SW-ModifyUtilityProvider-Req-Full-MSG.xsd	723
2.21.2. SW-ModifyUtilityProvider-Req-IO-MSG.xsd	732
2.21.3. SW-ModifyUtilityProvider-Res-Full-MSG.xsd	740
2.21.4. SW-ModifyUtilityProvider-Res-PK-MSG.xsd	750
<b>2.22. ModifyUtilityProviderDet</b>	<b>760</b>
2.22.1. SW-ModifyUtilityProviderDet-Req-Full-MSG.xsd	760
2.22.2. SW-ModifyUtilityProviderDet-Req-IO-MSG.xsd	769
2.22.3. SW-ModifyUtilityProviderDet-Res-Full-MSG.xsd	776
2.22.4. SW-ModifyUtilityProviderDet-Res-PK-MSG.xsd	788
<b>2.23. QueryCARDTOACCMAPPING</b>	<b>800</b>
2.23.1. SW-QueryCARDTOACCMAPPING-Req-IO-MSG.xsd	800
2.23.2. SW-QueryCARDTOACCMAPPING-Res-Full-MSG.xsd	807
<b>2.24. QueryCardAccMapping</b>	<b>820</b>
2.24.1. SW-QueryCardAccMapping-Req-IO-MSG.xsd	820
2.24.2. SW-QueryCardAccMapping-Res-Full-MSG.xsd	827
<b>2.25. QueryCardAccount</b>	<b>839</b>
2.25.1. SW-QueryCardAccount-Req-IO-MSG.xsd	839
2.25.2. SW-QueryCardAccount-Res-Full-MSG.xsd	846

<b>2.26. QueryCardCustomer</b>	<b>863</b>
2.26.1. SW-QueryCardCustomer-Req-IO-MSG.xsd	863
2.26.2. SW-QueryCardCustomer-Res-Full-MSG.xsd	870
<b>2.27. QueryCardUpload</b>	<b>887</b>
2.27.1. SW-QueryCardUpload-Req-IO-MSG.xsd	887
2.27.2. SW-QueryCardUpload-Res-Full-MSG.xsd	894
<b>2.28. QueryCashDeposit</b>	<b>906</b>
2.28.1. SW-QueryCashDeposit-Req-IO-MSG.xsd	906
2.28.2. SW-QueryCashDeposit-Res-Full-MSG.xsd	912
<b>2.29. QueryForwaderDetails</b>	<b>928</b>
2.29.1. SW-QueryForwaderDetails-Req-IO-MSG.xsd	928
2.29.2. SW-QueryForwaderDetails-Res-Full-MSG.xsd	934
<b>2.30. QueryMerchDetails</b>	<b>946</b>
2.30.1. SW-QueryMerchDetails-Req-IO-MSG.xsd	946
2.30.2. SW-QueryMerchDetails-Res-Full-MSG.xsd	953
<b>2.31. CreateUtilityProvider</b>	<b>965</b>
2.31.1. SW-CreateUtilityProvider-Req-Full-MSG.xsd	965
2.31.2. SW-CreateUtilityProvider-Req-IO-MSG.xsd	974
2.31.3. SW-CreateUtilityProvider-Res-Full-MSG.xsd	981
2.31.4. SW-CreateUtilityProvider-Res-PK-MSG.xsd	991
<b>2.32. CreateUtilityProviderDet</b>	<b>1000</b>
2.32.1. SW-CreateUtilityProviderDet-Req-Full-MSG.xsd	1000
2.32.2. SW-CreateUtilityProviderDet-Req-IO-MSG.xsd	1009
2.32.3. SW-CreateUtilityProviderDet-Res-Full-MSG.xsd	1018
2.32.4. SW-CreateUtilityProviderDet-Res-PK-MSG.xsd	1032
<b>2.33. DeleteCARDTOACCMAPPING</b>	<b>1046</b>
2.33.1. SW-DeleteCARDTOACCMAPPING-Req-Full-MSG.xsd	1046
2.33.2. SW-DeleteCARDTOACCMAPPING-Req-IO-MSG.xsd	1057
2.33.3. SW-DeleteCARDTOACCMAPPING-Res-Full-MSG.xsd	1064
2.33.4. SW-DeleteCARDTOACCMAPPING-Res-PK-MSG.xsd	1076
<b>2.34. DeleteCardAccMapping</b>	<b>1085</b>
2.34.1. SW-DeleteCardAccMapping-Req-Full-MSG.xsd	1085
2.34.2. SW-DeleteCardAccMapping-Req-IO-MSG.xsd	1094
2.34.3. SW-DeleteCardAccMapping-Res-Full-MSG.xsd	1101
2.34.4. SW-DeleteCardAccMapping-Res-PK-MSG.xsd	1113
<b>2.35. DeleteCardAccount</b>	<b>1126</b>
2.35.1. SW-DeleteCardAccount-Req-Full-MSG.xsd	1126
2.35.2. SW-DeleteCardAccount-Req-IO-MSG.xsd	1141
2.35.3. SW-DeleteCardAccount-Res-Full-MSG.xsd	1148
2.35.4. SW-DeleteCardAccount-Res-PK-MSG.xsd	1164
<b>2.36. DeleteCardCustomer</b>	<b>1174</b>
2.36.1. SW-DeleteCardCustomer-Req-Full-MSG.xsd	1174
2.36.2. SW-DeleteCardCustomer-Req-IO-MSG.xsd	1188
2.36.3. SW-DeleteCardCustomer-Res-Full-MSG.xsd	1195
2.36.4. SW-DeleteCardCustomer-Res-PK-MSG.xsd	1211
<b>2.37. DeleteCardUpload</b>	<b>1220</b>
2.37.1. SW-DeleteCardUpload-Req-Full-MSG.xsd	1220
2.37.2. SW-DeleteCardUpload-Req-IO-MSG.xsd	1229
2.37.3. SW-DeleteCardUpload-Res-Full-MSG.xsd	1236
2.37.4. SW-DeleteCardUpload-Res-PK-MSG.xsd	1248
<b>2.38. DeleteCashDeposit</b>	<b>1260</b>
2.38.1. SW-DeleteCashDeposit-Req-Full-MSG.xsd	1260
2.38.2. SW-DeleteCashDeposit-Req-IO-MSG.xsd	1274
2.38.3. SW-DeleteCashDeposit-Res-Full-MSG.xsd	1280
2.38.4. SW-DeleteCashDeposit-Res-PK-MSG.xsd	1296
<b>2.39. DeleteForwaderDetails</b>	<b>1312</b>

2.39.1. SW-DeleteForwaderDetails-Req-Full-MSG.xsd	1312
2.39.2. SW-DeleteForwaderDetails-Req-IO-MSG.xsd	1322
2.39.3. SW-DeleteForwaderDetails-Res-Full-MSG.xsd	1328
2.39.4. SW-DeleteForwaderDetails-Res-PK-MSG.xsd	1339
<b>2.40. DeleteMerchDetails</b>	<b>1348</b>
2.40.1. SW-DeleteMerchDetails-Req-Full-MSG.xsd	1348
2.40.2. SW-DeleteMerchDetails-Req-IO-MSG.xsd	1357
2.40.3. SW-DeleteMerchDetails-Res-Full-MSG.xsd	1364
2.40.4. SW-DeleteMerchDetails-Res-PK-MSG.xsd	1376
<b>2.41. DeleteNetworkDetails</b>	<b>1388</b>
2.41.1. SW-DeleteNetworkDetails-Req-Full-MSG.xsd	1388
2.41.2. SW-DeleteNetworkDetails-Req-IO-MSG.xsd	1399
2.41.3. SW-DeleteNetworkDetails-Res-Full-MSG.xsd	1405
2.41.4. SW-DeleteNetworkDetails-Res-PK-MSG.xsd	1418
<b>2.42. DeleteNetworkDetailss</b>	<b>1432</b>
2.42.1. SW-DeleteNetworkDetailss-Req-Full-MSG.xsd	1432
2.42.2. SW-DeleteNetworkDetailss-Req-IO-MSG.xsd	1442
2.42.3. SW-DeleteNetworkDetailss-Res-Full-MSG.xsd	1448
2.42.4. SW-DeleteNetworkDetailss-Res-PK-MSG.xsd	1460
<b>2.43. DeleteProcessCodeMapping</b>	<b>1469</b>
2.43.1. SW-DeleteProcessCodeMapping-Req-Full-MSG.xsd	1469
2.43.2. SW-DeleteProcessCodeMapping-Req-IO-MSG.xsd	1479
2.43.3. SW-DeleteProcessCodeMapping-Res-Full-MSG.xsd	1486
2.43.4. SW-DeleteProcessCodeMapping-Res-PK-MSG.xsd	1498
<b>2.44. DeleteTerminalDetails</b>	<b>1511</b>
2.44.1. SW-DeleteTerminalDetails-Req-Full-MSG.xsd	1511
2.44.2. SW-DeleteTerminalDetails-Req-IO-MSG.xsd	1521
2.44.3. SW-DeleteTerminalDetails-Res-Full-MSG.xsd	1527
2.44.4. SW-DeleteTerminalDetails-Res-PK-MSG.xsd	1539
<b>2.45. DeleteUtilityProvider</b>	<b>1551</b>
2.45.1. SW-DeleteUtilityProvider-Req-Full-MSG.xsd	1551
2.45.2. SW-DeleteUtilityProvider-Req-IO-MSG.xsd	1560
2.45.3. SW-DeleteUtilityProvider-Res-Full-MSG.xsd	1566
2.45.4. SW-DeleteUtilityProvider-Res-PK-MSG.xsd	1576
<b>2.46. DeleteUtilityProviderDet</b>	<b>1585</b>
2.46.1. SW-DeleteUtilityProviderDet-Req-Full-MSG.xsd	1585
2.46.2. SW-DeleteUtilityProviderDet-Req-IO-MSG.xsd	1594
2.46.3. SW-DeleteUtilityProviderDet-Res-Full-MSG.xsd	1600
2.46.4. SW-DeleteUtilityProviderDet-Res-PK-MSG.xsd	1611
<b>2.47. CloseCARDTOACCMAPPING</b>	<b>1622</b>
2.47.1. SW-CloseCARDTOACCMAPPING-Req-Full-MSG.xsd	1622
2.47.2. SW-CloseCARDTOACCMAPPING-Req-IO-MSG.xsd	1633
2.47.3. SW-CloseCARDTOACCMAPPING-Res-Full-MSG.xsd	1640
2.47.4. SW-CloseCARDTOACCMAPPING-Res-PK-MSG.xsd	1652
<b>2.48. CloseCardAccount</b>	<b>1662</b>
2.48.1. SW-CloseCardAccount-Req-Full-MSG.xsd	1662
2.48.2. SW-CloseCardAccount-Req-IO-MSG.xsd	1677
2.48.3. SW-CloseCardAccount-Res-Full-MSG.xsd	1685
2.48.4. SW-CloseCardAccount-Res-PK-MSG.xsd	1701
<b>2.49. CloseCardCustomer</b>	<b>1711</b>
2.49.1. SW-CloseCardCustomer-Req-Full-MSG.xsd	1711
2.49.2. SW-CloseCardCustomer-Req-IO-MSG.xsd	1725
2.49.3. SW-CloseCardCustomer-Res-Full-MSG.xsd	1732
2.49.4. SW-CloseCardCustomer-Res-PK-MSG.xsd	1748
<b>2.50. CloseForwaderDetails</b>	<b>1758</b>
2.50.1. SW-CloseForwaderDetails-Req-Full-MSG.xsd	1758
2.50.2. SW-CloseForwaderDetails-Req-IO-MSG.xsd	1768
2.50.3. SW-CloseForwaderDetails-Res-Full-MSG.xsd	1775

2.50.4. SW-CloseForwaderDetails-Res-PK-MSG.xsd	1786
<b>2.51. CreateCARDTOACCMAPPING</b>	<b>1795</b>
2.51.1. SW-CreateCARDTOACCMAPPING-Req-Full-MSG.xsd	1795
2.51.2. SW-CreateCARDTOACCMAPPING-Req-IO-MSG.xsd	1806
2.51.3. SW-CreateCARDTOACCMAPPING-Res-Full-MSG.xsd	1815
2.51.4. SW-CreateCARDTOACCMAPPING-Res-PK-MSG.xsd	1827
<b>2.52. CreateCardAccMapping</b>	<b>1838</b>
2.52.1. SW-CreateCardAccMapping-Req-Full-MSG.xsd	1838
2.52.2. SW-CreateCardAccMapping-Req-IO-MSG.xsd	1847
2.52.3. SW-CreateCardAccMapping-Res-Full-MSG.xsd	1856
2.52.4. SW-CreateCardAccMapping-Res-PK-MSG.xsd	1871
<b>2.53. CreateCardAccount</b>	<b>1887</b>
2.53.1. SW-CreateCardAccount-Req-Full-MSG.xsd	1887
2.53.2. SW-CreateCardAccount-Req-IO-MSG.xsd	1902
2.53.3. SW-CreateCardAccount-Res-Full-MSG.xsd	1915
2.53.4. SW-CreateCardAccount-Res-PK-MSG.xsd	1931
<b>2.54. CreateCardCustomer</b>	<b>1947</b>
2.54.1. SW-CreateCardCustomer-Req-Full-MSG.xsd	1947
2.54.2. SW-CreateCardCustomer-Req-IO-MSG.xsd	1961
2.54.3. SW-CreateCardCustomer-Res-Full-MSG.xsd	1973
2.54.4. SW-CreateCardCustomer-Res-PK-MSG.xsd	1989
<b>2.55. CreateCardUpload</b>	<b>2003</b>
2.55.1. SW-CreateCardUpload-Req-Full-MSG.xsd	2003
2.55.2. SW-CreateCardUpload-Req-IO-MSG.xsd	2012
2.55.3. SW-CreateCardUpload-Res-Full-MSG.xsd	2021
2.55.4. SW-CreateCardUpload-Res-PK-MSG.xsd	2035
<b>2.56. CreateCashDeposit</b>	<b>2050</b>
2.56.1. SW-CreateCashDeposit-Req-Full-MSG.xsd	2050
2.56.2. SW-CreateCashDeposit-Req-IO-MSG.xsd	2064
2.56.3. SW-CreateCashDeposit-Res-Full-MSG.xsd	2077
2.56.4. SW-CreateCashDeposit-Res-PK-MSG.xsd	2100
<b>2.57. CreateForwaderDetails</b>	<b>2123</b>
2.57.1. SW-CreateForwaderDetails-Req-Full-MSG.xsd	2123
2.57.2. SW-CreateForwaderDetails-Req-IO-MSG.xsd	2133
2.57.3. SW-CreateForwaderDetails-Res-Full-MSG.xsd	2141
2.57.4. SW-CreateForwaderDetails-Res-PK-MSG.xsd	2152
<b>2.58. CreateMerchDetails</b>	<b>2162</b>
2.58.1. SW-CreateMerchDetails-Req-Full-MSG.xsd	2162
2.58.2. SW-CreateMerchDetails-Req-IO-MSG.xsd	2171
2.58.3. SW-CreateMerchDetails-Res-Full-MSG.xsd	2180
2.58.4. SW-CreateMerchDetails-Res-PK-MSG.xsd	2194
<b>2.59. CreateNetworkDetails</b>	<b>2209</b>
2.59.1. SW-CreateNetworkDetails-Req-Full-MSG.xsd	2209
2.59.2. SW-CreateNetworkDetails-Req-IO-MSG.xsd	2220
2.59.3. SW-CreateNetworkDetails-Res-Full-MSG.xsd	2231
2.59.4. SW-CreateNetworkDetails-Res-PK-MSG.xsd	2249
<b>2.60. CreateNetworkDetailss</b>	<b>2268</b>
2.60.1. SW-CreateNetworkDetailss-Req-Full-MSG.xsd	2268
2.60.2. SW-CreateNetworkDetailss-Req-IO-MSG.xsd	2278
2.60.3. SW-CreateNetworkDetailss-Res-Full-MSG.xsd	2286
2.60.4. SW-CreateNetworkDetailss-Res-PK-MSG.xsd	2298
<b>2.61. CreateProcessCodeMapping</b>	<b>2309</b>
2.61.1. SW-CreateProcessCodeMapping-Req-Full-MSG.xsd	2309
2.61.2. SW-CreateProcessCodeMapping-Req-IO-MSG.xsd	2319
2.61.3. SW-CreateProcessCodeMapping-Res-Full-MSG.xsd	2329
2.61.4. SW-CreateProcessCodeMapping-Res-PK-MSG.xsd	2344

<b>2.62. CreateTerminalDetails</b>	<b>2359</b>
2.62.1. SW-CreateTerminalDetails-Req-Full-MSG.xsd	2359
2.62.2. SW-CreateTerminalDetails-Req-IO-MSG.xsd	2369
2.62.3. SW-CreateTerminalDetails-Res-Full-MSG.xsd	2379
2.62.4. SW-CreateTerminalDetails-Res-PK-MSG.xsd	2395
<b>2.63. AuthCardAccMapping</b>	<b>2411</b>
2.63.1. SW-AuthCardAccMapping-Req-Full-MSG.xsd	2411
2.63.2. SW-AuthCardAccMapping-Req-IO-MSG.xsd	2420
2.63.3. SW-AuthCardAccMapping-Res-Full-MSG.xsd	2427
2.63.4. SW-AuthCardAccMapping-Res-PK-MSG.xsd	2439
<b>2.64. AuthCardUpload</b>	<b>2452</b>
2.64.1. SW-AuthCardUpload-Req-Full-MSG.xsd	2452
2.64.2. SW-AuthCardUpload-Req-IO-MSG.xsd	2461
2.64.3. SW-AuthCardUpload-Res-Full-MSG.xsd	2468
2.64.4. SW-AuthCardUpload-Res-PK-MSG.xsd	2480
<b>2.65. AuthCashDeposit</b>	<b>2493</b>
2.65.1. SW-AuthCashDeposit-Req-Full-MSG.xsd	2493
2.65.2. SW-AuthCashDeposit-Req-IO-MSG.xsd	2507
2.65.3. SW-AuthCashDeposit-Res-Full-MSG.xsd	2514
2.65.4. SW-AuthCashDeposit-Res-PK-MSG.xsd	2530
<b>2.66. AuthMerchDetails</b>	<b>2546</b>
2.66.1. SW-AuthMerchDetails-Req-Full-MSG.xsd	2546
2.66.2. SW-AuthMerchDetails-Req-IO-MSG.xsd	2555
2.66.3. SW-AuthMerchDetails-Res-Full-MSG.xsd	2562
2.66.4. SW-AuthMerchDetails-Res-PK-MSG.xsd	2574
<b>2.67. AuthNetworkDetails</b>	<b>2587</b>
2.67.1. SW-AuthNetworkDetails-Req-Full-MSG.xsd	2587
2.67.2. SW-AuthNetworkDetails-Req-IO-MSG.xsd	2598
2.67.3. SW-AuthNetworkDetails-Res-Full-MSG.xsd	2605
2.67.4. SW-AuthNetworkDetails-Res-PK-MSG.xsd	2619
<b>2.68. AuthProcessCodeMapping</b>	<b>2633</b>
2.68.1. SW-AuthProcessCodeMapping-Req-Full-MSG.xsd	2633
2.68.2. SW-AuthProcessCodeMapping-Req-IO-MSG.xsd	2643
2.68.3. SW-AuthProcessCodeMapping-Res-Full-MSG.xsd	2650
2.68.4. SW-AuthProcessCodeMapping-Res-PK-MSG.xsd	2662
<b>2.69. AuthTerminalDetails</b>	<b>2675</b>
2.69.1. SW-AuthTerminalDetails-Req-Full-MSG.xsd	2675
2.69.2. SW-AuthTerminalDetails-Req-IO-MSG.xsd	2685
2.69.3. SW-AuthTerminalDetails-Res-Full-MSG.xsd	2692
2.69.4. SW-AuthTerminalDetails-Res-PK-MSG.xsd	2704
<b>2.70. AuthUtilityProviderDet</b>	<b>2717</b>
2.70.1. SW-AuthUtilityProviderDet-Req-Full-MSG.xsd	2717
2.70.2. SW-AuthUtilityProviderDet-Req-IO-MSG.xsd	2726
2.70.3. SW-AuthUtilityProviderDet-Res-Full-MSG.xsd	2733
2.70.4. SW-AuthUtilityProviderDet-Res-PK-MSG.xsd	2744
<b>2.71. AuthorizeCARDTOACCMAPPING</b>	<b>2756</b>
2.71.1. SW-AuthorizeCARDTOACCMAPPING-Req-Full-MSG.xsd	2756
2.71.2. SW-AuthorizeCARDTOACCMAPPING-Req-IO-MSG.xsd	2767
2.71.3. SW-AuthorizeCARDTOACCMAPPING-Res-Full-MSG.xsd	2774
2.71.4. SW-AuthorizeCARDTOACCMAPPING-Res-PK-MSG.xsd	2786
<b>2.72. AuthorizeCardAccount</b>	<b>2796</b>
2.72.1. SW-AuthorizeCardAccount-Req-Full-MSG.xsd	2796
2.72.2. SW-AuthorizeCardAccount-Req-IO-MSG.xsd	2811
2.72.3. SW-AuthorizeCardAccount-Res-Full-MSG.xsd	2819
2.72.4. SW-AuthorizeCardAccount-Res-PK-MSG.xsd	2835

<b>2.73. AuthorizeCardCustomer</b>	<b>2845</b>
2.73.1. SW-AuthorizeCardCustomer-Req-Full-MSG.xsd	2845
2.73.2. SW-AuthorizeCardCustomer-Req-IO-MSG.xsd	2859
2.73.3. SW-AuthorizeCardCustomer-Res-Full-MSG.xsd	2866
2.73.4. SW-AuthorizeCardCustomer-Res-PK-MSG.xsd	2882
<b>2.74. AuthorizeForwaderDetails</b>	<b>2892</b>
2.74.1. SW-AuthorizeForwaderDetails-Req-Full-MSG.xsd	2892
2.74.2. SW-AuthorizeForwaderDetails-Req-IO-MSG.xsd	2902
2.74.3. SW-AuthorizeForwaderDetails-Res-Full-MSG.xsd	2909
2.74.4. SW-AuthorizeForwaderDetails-Res-PK-MSG.xsd	2920
<b>2.75. AuthorizeNetworkDetailss</b>	<b>2929</b>
2.75.1. SW-AuthorizeNetworkDetailss-Req-Full-MSG.xsd	2929
2.75.2. SW-AuthorizeNetworkDetailss-Req-IO-MSG.xsd	2939
2.75.3. SW-AuthorizeNetworkDetailss-Res-Full-MSG.xsd	2946
2.75.4. SW-AuthorizeNetworkDetailss-Res-PK-MSG.xsd	2958
<b>2.76. AuthorizeUtilityProvider</b>	<b>2967</b>
2.76.1. SW-AuthorizeUtilityProvider-Req-Full-MSG.xsd	2967
2.76.2. SW-AuthorizeUtilityProvider-Req-IO-MSG.xsd	2976
2.76.3. SW-AuthorizeUtilityProvider-Res-Full-MSG.xsd	2983
2.76.4. SW-AuthorizeUtilityProvider-Res-PK-MSG.xsd	2993



# 1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.

The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

**1. Inbound application integration** – used when any external system needs to add, modify or query information within FLEXCUBE UBS

**2. Outbound application integration**– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSSwitchService of SW-Module

## 2.FCUBSSwitchService

Switch Gateway ServiceSwitch Gateway Service

### 2.1.QueryNetworkDetails

QueryNetworkDetails

#### 2.1.1.SW-QueryNetworkDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Network-Details-IO*

*NETWORKID*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Network-Details-IO

<b>Attribute</b>	<b>Description</b>
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Query details

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## 2.1.2.SW-QueryNetworkDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Network-Details-IO*

*NETWORKID*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*



[NETWORK\\_ID](#)  
[Issuer-Details](#)  
[ISSBIN](#)  
[ISSDESC](#)  
[NETWORKID](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description
Name	SERVICE

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Network-Details-IO

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Query-IO details

[TOP](#)

## NETWORKID

Attribute	Description				
Name	NETWORKID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## Network-Details-Full

Attribute	Description
Name	Network-Details-Full
Datatype	
Description	Includes Switch -Network details Query-Full details

[TOP](#)

## NETWORKID

Attribute	Description				
Name	NETWORKID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECORDSTAT**



Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

Attribute	Description	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## ACQDESC

Attribute	Description	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Issuer-Details

Attribute	Description	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

Attribute	Description
Name	ISSBIN
Datatype	String

Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)**WARNING**

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.2.QueryNetworkDetailss

QueryNetworkDetailss

### 2.2.1.SW-QueryNetworkDetailss-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-IO*

*NETWORK\_ID*

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------



Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Swtms-Network-Details-IO

<b>Attribute</b>	<b>Description</b>
Name	Swtms-Network-Details-IO
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## 2.2.2.SW-QueryNetworkDetailss-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Swtms-Network-Details-IO*

*NETWORK\_ID*

*Swtms-Network-Details-Full*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Swtms-Acquirer-Details*

*ACQ\_BINN*

*ACQ\_DESC*

*Swtms-Issuer-Details*

[ISS\\_BINN](#)  
[ISS\\_DESC](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
maxLength	12						
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
length	3						
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	



[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Swtms-Network-Details-IO

Attribute	Description
Name	Swtms-Network-Details-IO
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## Swtms-Network-Details-Full

Attribute	Description
Name	Swtms-Network-Details-Full
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## ACCOUNT\_NO

Attribute	Description
-----------	-------------

Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Swtms-Acquirer-Details**

Attribute	Description	
Name	Swtms-Acquirer-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ACQ\_BINN**

Attribute	Description	
Name	ACQ_BINN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

**ACQ\_DESC**

Attribute	Description	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

**Swtms-Issuer-Details**

Attribute	Description
-----------	-------------

Name	Swtrms-Issuer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ISS_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.3.QueryProcessCodeMapping

QueryProcessCodeMapping

### 2.3.1.SW-QueryProcessCodeMapping-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Process-Code-Mapping-IO*

*PROCODTYP*

*FCLITERAL*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	



Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch -Process code mapping Query details

[TOP](#)

## PROCODTYP

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)

## FCLITERAL

Attribute	Description
Name	FCLITERAL

Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## 2.3.2.SW-QueryProcessCodeMapping-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Process-Code-Mapping-IO*

*PROCODTYP*

*FCLITERAL*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch -Process code mapping Query-IO details

[TOP](#)

## PROCODTYP

Attribute	Description				
Name	PROCODTYP				
Datatype	String				
Description	Indicates Process Code Type				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2</td></tr></tbody></table>	Restrictions	Description	maxLength	2
	Restrictions	Description			
maxLength	2				

[TOP](#)

## FCLITERAL

Attribute	Description				
Name	FCLITERAL				
Datatype	String				
Description	Indicates Flexcube Literal				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## Process-Code-Mapping-Full

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes Switch -Process code mapping Query-Full details

[TOP](#)

## FCLITERAL

Attribute	Description
Name	FCLITERAL

Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description
-----------	-------------



Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.4.QueryTerminalDetails

QueryTerminalDetails

### 2.4.1.SW-QueryTerminalDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Terminal-Details-IO*

*TERMINID*

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Terminal-Details-IO

<b>Attribute</b>	<b>Description</b>
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch -Terminal details Query-IO details

[TOP](#)

## TERMID

<b>Attribute</b>	<b>Description</b>	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## 2.4.2.SW-QueryTerminalDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Terminal-Details-IO*

*TERMIN*

*Terminal-Details-Full*

*TERMIN*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*



FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Terminal-Details-IO

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch -Terminal details Query-IO details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Terminal-Details-Full

Attribute	Description
Name	Terminal-Details-Full
Datatype	
Description	Includes Switch -Terminal details Query-Full details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ORGBRN

Attribute	Description
-----------	-------------

Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CASHGL

<b>Attribute</b>	<b>Description</b>	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MERCHID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TERMADDR

<b>Attribute</b>	<b>Description</b>	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## INTELDEP

<b>Attribute</b>	<b>Description</b>	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		

Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.5.QueryUtilityProvider

QueryUtilityProvider

### 2.5.1.SW-QueryUtilityProvider-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-IO*

*UTILITY\_PROVIDER\_ID*

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	

[TOP](#)

## UTILITY\_PROVIDER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## 2.5.2.SW-QueryUtilityProvider-Res-Full-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-IO*  
*UTILITY\_PROVIDER\_ID*  
*Main-Full*  
*ACCOUNT\_NO*  
*UTILITY\_PROVIDER\_ID*  
*ACCOUNT\_BRANCH*  
*DESCRIPTION*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------

Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## UTILITY\_PROVIDER\_ID

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## ACCOUNT\_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## UTILITY\_PROVIDER\_ID

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**TXNSTAT**

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**AUTHSTAT**

Attribute	Description
Name	AUTHSTAT

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.6.QueryUtilityProviderDet

QueryUtilityProviderDet

### 2.6.1.SW-QueryUtilityProviderDet-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*UtilityProvider-Details-IO*

*UTILITYPROVIDERID*

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------



Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## UtilityProvider-Details-IO

<b>Attribute</b>	<b>Description</b>
Name	UtilityProvider-Details-IO
Datatype	
Description	Includes Switch -Utility Provider details-Query-IO details

[TOP](#)

## UTILITYPROVIDERID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## 2.6.2.SW-QueryUtilityProviderDet-Res-Full-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*UtilityProvider-Details-IO*  
*UTILITYPROVIDERID*  
*UtilityProvider-Details-Full*  
*ACCOUNTNO*  
*MAKERID*  
*MAKRDSTMP*  
*CHECKERID*  
*CHEKRDSTMP*  
*MODNO*  
*xRECORDSTAT*  
*AUTHSTAT*  
*ONCEAUTH*  
*UTILITYPROVIDERID*  
*ACCOUNTBRN*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------



Name	CHOICE
Datatype	
Description	

[TOP](#)

## UtilityProvider-Detials-IO

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes Switch -Utility Provider details-Query-IO details

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## UtilityProvider-Detials-Full

Attribute	Description
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes Switch -Utility Provider details-Query-Full details

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**xRECORDSTAT**

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description
Name	ACCOUNTBRN

Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.7.ReopenCARDTOACCMAPPING

Reopen Card To Account Mapping

### 2.7.1.SW-ReopenCARDTOACCMAPPING-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sub*

[ATM\\_DLY\\_TXN\\_LIMIT](#)  
[POS\\_DLY\\_CNT\\_LIMIT](#)  
[ATM\\_DLY\\_CNT\\_LIMIT](#)  
[POS\\_DLY\\_TXN\\_LIMIT](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION



Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
-----------	-------------

Name	Main-Full
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ACCNUM

Attribute	Description	
Name	ACCNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**CCY\_CODE**

Attribute		Description
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CARD\_TYPE**

Attribute		Description
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	80

**LMT\_APPLICABILITY**

Attribute		Description
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,S

**MAKER**

Attribute		Description
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sub

<b>Attribute</b>	<b>Description</b>	
Name	Sub	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_CNT_LIMIT	

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)



*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*MAKER*

*MAKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description
Name	ATM_ACCOUNT_NO

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## 2.7.3.SW-ReopenCARDTOACCMAPPING-Res-Full-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

#### *Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

#### *Sub*

*ATM\_DLY\_TXN\_LIMIT*

*POS\_DLY\_CNT\_LIMIT*

*ATM\_DLY\_CNT\_LIMIT*



[POS\\_DLY\\_TXN\\_LIMIT](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

**ATM\_CARD\_N**

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

**ATM\_ACCOUNT\_NO**

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

**ACCBRN**

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**ACCNUM**

Attribute	Description
Name	ACCNUM
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CARD\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

[TOP](#)

## LMT\_APPLICABILITY

<b>Attribute</b>	<b>Description</b>	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,S

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT



Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sub

Attribute	Description	
Name	Sub	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

Attribute	Description	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

Attribute	Description	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ATM\_DLY\_CNT\_LIMIT**

Attribute		Description
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**POS\_DLY\_TXN\_LIMIT**

Attribute		Description
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.7.4.SW-ReopenCARDTOACCMAPPING-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL



Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description				
Name	ATM_CARD_N				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>19</td></tr></tbody></table>	Restrictions	Description	maxLength	19
	Restrictions	Description			
maxLength	19				

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description				
Name	ATM_ACCOUNT_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>28</td></tr></tbody></table>	Restrictions	Description	maxLength	28
	Restrictions	Description			
maxLength	28				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description				
Name	ATM_CARD_N				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>19</td></tr></tbody></table>	Restrictions	Description	maxLength	19
	Restrictions	Description			
maxLength	19				

**ATM\_ACCOUNT\_NO**

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	

Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.8.ReopenCardAccount

ReopenCardAccount

### 2.8.1.SW-ReopenCardAccount-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

BRANCH\_CODE

CUST\_NO

ACTNO

Sttms-Detail

BRANCH\_CODE

REQUEST\_REFERENCE\_NO

CARDNO

CUST\_NO

CARD\_PRODUCT

PRIMARY\_CARD

NAME\_ON\_CARD

OWNER\_ID\_NO

CARD\_ISSUED\_DT

CARD\_EXPIRY\_DT

CARD\_STATUS

RECORD\_STAT

AUTH\_STAT

CARD\_BIN

CUST\_AC\_NO

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

[TOP](#)

## CUST\_AC\_NO

Attribute	Description				
Name	CUST_AC_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## CUSTOMER\_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## DR\_CR\_INDI

<b>Attribute</b>	<b>Description</b>	
Name	DR_CR_INDI	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,C

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

**Sttms-Debit**

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3



**REQUEST\_REFERENCE\_NO**

Attribute	Description	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

**CUST\_AC\_NO**

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## 2.8.2.SW-ReopenCardAccount-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Main-IO*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*MAKER*

*MAKERSTAMP*

*MODNO*

## **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## **SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------



Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>
Name	CUST_AC_NO

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### 2.8.3.SW-ReopenCardAccount-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

BRANCH\_CODE  
REQUEST\_REFERENCE\_NO  
CARDNO  
CUST\_NO  
CARD\_PRODUCT  
PRIMARY\_CARD  
NAME\_ON\_CARD  
OWNER\_ID\_NO  
CARD\_ISSUED\_DT  
CARD\_EXPIRY\_DT  
CARD\_STATUS  
RECORD\_STAT  
AUTH\_STAT  
CARD\_BIN  
CUST\_AC\_NO

FCUBS\_ERROR\_RESP

ERROR  
ECODE  
EDESC

FCUBS\_WARNING\_RESP

WARNING  
WCODE  
WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

**UBSCOMP**

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME

Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## DR\_CR\_INDI

Attribute	Description				
Name	DR_CR_INDI				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>D,C</td></tr></tbody></table>	Restrictions	Description	enumeration	D,C
	Restrictions	Description			
enumeration	D,C				

[TOP](#)

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

[TOP](#)

## CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description
-----------	-------------

Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4



[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**OWNER\_ID\_NO**

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)**CARD\_ISSUED\_DT**

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CARD\_EXPIRY\_DT**

Attribute	Description
Name	CARD_EXPIRY_DT

Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.8.4.SW-ReopenCardAccount-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*CUST\_AC\_NO*  
*CUSTOMER\_ID*  
*BRANCH\_CODE*  
*Main-IO*  
*BRANCH\_CODE*  
*CUST\_AC\_NO*  
*CUSTOMER\_ID*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Main-PK**

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)**CUST\_AC\_NO**

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER\_ID**

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**Main-IO**

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)**BRANCH\_CODE**

Attribute		Description
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**CUST\_AC\_NO**

Attribute		Description
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER\_ID**

Attribute		Description
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**MAKER**

Attribute		Description
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.9.ReopenCardCustomer

ReopenCardCustomer

### 2.9.1.SW-ReopenCardCustomer-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

REQUEST\_REFERENCE\_NO  
 CARDNO  
 CUST\_NO  
 CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16



[TOP](#)**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

## 2.9.2.SW-ReopenCardCustomer-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Main-IO

CUSTOMER\_ID

CUSTOMER\_NAME

MAKER

MAKERSTAMP

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------



Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

<b>Attribute</b>	<b>Description</b>
Name	CUSTOMER_NAME

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.9.3.SW-ReopenCardCustomer-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

*REQUEST\_REFERENCE\_NO*

*CARDNO*

*CUST\_NO*

CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



## MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></tbody></table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
	Restrictions	Description			
enumeration	SUCCESS,WARNING,FAILURE				

[TOP](#)

## PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
	Restrictions	Description					
	maxLength	128					
pattern	[a-zA-Z_0-9=+/*]						

[TOP](#)

## ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sttms-Debit

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Sttms-Detail

Attribute	Description	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String

Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

<b>Attribute</b>	<b>Description</b>	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>
Name	CARD_STATUS

Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute		Description
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute		Description
Name	WCODE	

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.9.4.SW-ReopenCardCustomer-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*CUSTOMER\_ID*  
*Main-IO*  
*CUSTOMER\_ID*  
*CUSTOMER\_NAME*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL



Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description				
Name	CUSTOMER_NAME				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description
Name	ERROR
Datatype	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
-----------	-------------

Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.10.ReopenForwaderDetails

ReopenForwaderDetails

### 2.10.1.SW-ReopenForwaderDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Forwarder-C-Full

Attribute	Description
Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description				
Name	FWD_INS_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td></td></tr></tbody></table>	Restrictions	Description	enumeration	
	Restrictions	Description			
enumeration					

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description				
Name	INTERNATIONAL_FLAG				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description				
Name	TRANSACTION_RESTR				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>A,D</td></tr></tbody></table>	Restrictions	Description	enumeration	A,D
	Restrictions	Description			
enumeration	A,D				

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Forward-Literal-C

<b>Attribute</b>	<b>Description</b>	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

2.10.2.SW-ReopenForwaderDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-IO*

*FRWRD\_INST\_ID*

*MAKER*

*MAKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Forwarder-C-IO

<b>Attribute</b>	<b>Description</b>
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>
Name	MAKER

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.10.3.SW-ReopenForwaderDetails-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

##### *Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

##### *Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

#### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Forwarder-C-Full

Attribute	Description
-----------	-------------

Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description	
Name	FWD_INS_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Forward-Literal-C

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	



Description	
-------------	--

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.10.4.SW-ReopenForwaderDetails-Res-PK-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*CHOICE*

*Forwarder-C-PK*

*FRWRD\_INST\_ID*

*Forwarder-C-IO*

*FRWRD\_INST\_ID*

*MAKER*

*MAKERSTAMP*

*MODNO*

### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

### *FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Forwarder-C-PK

Attribute	Description
Name	Forwarder-C-PK
Datatype	
Description	

[TOP](#)**FRWRD\_INST\_ID**

Attribute		Description	
Name	FRWRD_INST_ID		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	1	
Restrictions	Restrictions		Description
	maxLength	11	

[TOP](#)**Forwarder-C-IO**

Attribute		Description	
Name	Forwarder-C-IO		
Datatype			
Description			

[TOP](#)**FRWRD\_INST\_ID**

Attribute		Description	
Name	FRWRD_INST_ID		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	1	
Restrictions	Restrictions		Description
	maxLength	11	

[TOP](#)**MAKER**

Attribute		Description	
Name	MAKER		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

[TOP](#)**MAKERSTAMP**

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attributes	Attribute		Description
	maxOccurs	unbounded	
	minOccurs	0	

[TOP](#)

## WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attributes	Attribute		Description
	maxOccurs	unbounded	

[TOP](#)

## WCODE

Attribute		Description	
Name	WCODE		
Datatype	String		
Description			

[TOP](#)

## WDESC

Attribute		Description	
Name	WDESC		
Datatype	String		
Description			

[TOP](#)

## 2.11.ModifyCARDTOACCMAPPING

Modify Card To Account Mapping

### 2.11.1.SW-ModifyCARDTOACCMAPPING-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sub*

[ATM\\_DLY\\_TXN\\_LIMIT](#)  
[POS\\_DLY\\_CNT\\_LIMIT](#)  
[ATM\\_DLY\\_CNT\\_LIMIT](#)  
[POS\\_DLY\\_TXN\\_LIMIT](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
-----------	-------------



Name	Main-Full
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ACCNUM

Attribute	Description	
Name	ACCNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**CCY\_CODE**

Attribute		Description
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CARD\_TYPE**

Attribute		Description
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	80

**LMT\_APPLICABILITY**

Attribute		Description
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,S

**MAKER**

Attribute		Description
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sub

<b>Attribute</b>	<b>Description</b>	
Name	Sub	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_CNT_LIMIT	

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## 2.11.2.SW-ModifyCARDTOACCMAPPING-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*Sub*

*ATM\_DLY\_TXN\_LIMIT*

*POS\_DLY\_CNT\_LIMIT*

*ATM\_DLY\_CNT\_LIMIT*

*POS\_DLY\_TXN\_LIMIT*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION



Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description
Name	ATM_CARD_N
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## LMT\_APPLICABILITY

<b>Attribute</b>	<b>Description</b>	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,S

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## Sub

Attribute	Description	
Name	Sub	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

Attribute	Description	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

Attribute	Description	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ATM\_DLY\_CNT\_LIMIT

Attribute	Description	
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## POS\_DLY\_TXN\_LIMIT

Attribute	Description	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### 2.11.3.SW-ModifyCARDTOACCMAPPING-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

##### *Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

##### *Sub*

*ATM\_DLY\_TXN\_LIMIT*

*POS\_DLY\_CNT\_LIMIT*

*ATM\_DLY\_CNT\_LIMIT*

POS\_DLY\_TXN\_LIMIT  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC  
**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

**ATM\_CARD\_N**

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

**ATM\_ACCOUNT\_NO**

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

**ACCBRN**

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**ACCNUM**

Attribute	Description
Name	ACCNUM
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CARD\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

[TOP](#)

## LMT\_APPLICABILITY

<b>Attribute</b>	<b>Description</b>	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,S

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sub

Attribute	Description	
Name	Sub	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

Attribute	Description	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

Attribute	Description	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ATM\_DLY\_CNT\_LIMIT**

Attribute		Description
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**POS\_DLY\_TXN\_LIMIT**

Attribute		Description
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**



Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.11.4.SW-ModifyCARDTOACCMAPPING-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*ATM\_CARD\_N*  
*ATM\_ACCOUNT\_NO*  
*Main-IO*  
*ATM\_CARD\_N*  
*ATM\_ACCOUNT\_NO*  
*LMT\_APPLICABILITY*  
*MAKER*  
*MAKERSTAMP*  
*Sub*  
*ATM\_DLY\_TXN\_LIMIT*  
*POS\_DLY\_CNT\_LIMIT*  
*ATM\_DLY\_CNT\_LIMIT*  
*POS\_DLY\_TXN\_LIMIT*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------

Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## LMT\_APPLICABILITY

<b>Attribute</b>	<b>Description</b>	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,S

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**Sub**

Attribute	Description	
Name	Sub	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**ATM\_DLY\_TXN\_LIMIT**

Attribute	Description	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**POS\_DLY\_CNT\_LIMIT**

Attribute	Description	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ATM\_DLY\_CNT\_LIMIT**

Attribute	Description	
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**POS\_DLY\_TXN\_LIMIT**

Attribute	Description	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.12.ModifyCardAccMapping

ModifyCardAccMapping

### 2.12.1.SW-ModifyCardAccMapping-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

**FCUBS\_HEADER**

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Card-Account-Mapping-Full

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Modification Full type details

[TOP](#)

## ATMCARDNO

Attribute	Description
Name	ATMCARDNO
Datatype	String
Description	Indicates ATM/Debit Card Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## FCCACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCBRN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCCACCNO**

Attribute	Description	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**FCCACCCY**

Attribute	Description	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

## 2.12.2.SW-ModifyCardAccMapping-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Card-Account-Mapping-IO*

ATMCARDNO

ATMACCNO

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)



## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Card-Account-Mapping-IO**

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Modification Input Only type details

[TOP](#)**ATMCARDNO**

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**ATMACCNO**

Attribute	Description
Name	ATMACCNO
Datatype	String
Description	Indicates Card Account Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.12.3.SW-ModifyCardAccMapping-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*MODNO*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID



Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

**Card-Account-Mapping-IO**

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Modification Input Only type details

**ATMCARDNO**

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

**ATMACCNO**

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	28

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Card-Account-Mapping-Full**

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Modification Full type details

**ATMCARDNO**

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

**ATMACCNO**

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	28

**FCCACCBRN**

Attribute	Description	
Name	FCCACCBRN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCCACCNO

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCCACCCY

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.12.4.SW-ModifyCardAccMapping-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Account-Mapping-PK*

*ATMCARDNO*

*ATMACCNO*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*MODNO*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

ONCEAUTH  
 FCCACCNO  
 FCCACCCCY  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute		Description
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+]*</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+]*
	Restrictions	Description					
	maxLength	128					
pattern	[a-zA-Z_0-9=+]*						

[TOP](#)

## ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Account-Mapping-PK

Attribute	Description
Name	Card-Account-Mapping-PK
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Modification Primary Key type details

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	18

[TOP](#)

## Card-Account-Mapping-IO

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	

Description	Includes Switch ATM/Debit Card FCC Account Mapping Modification Input Only type details
-------------	---

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	18

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## Card-Account-Mapping-Full

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Modification Full type details

[TOP](#)

## ATMCARDNO

Attribute	Description
Name	ATMCARDNO



Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

## FCCACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCBRN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCCACCNO

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCCACCCY

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.13.ModifyCardUpload

ModifyCardUpload

### 2.13.1.SW-ModifyCardUpload-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Card-Upload-Full

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Modification Full type details

[TOP](#)

## FILENAME

Attribute	Description
Name	FILENAME
Datatype	String
Description	Indicates File Name

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

<b>Attribute</b>	<b>Description</b>	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.13.2.SW-ModifyCardUpload-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*INTRADAYSEQNO*

*MODNO*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### **SOURCE**

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	



Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Modification Input Only type details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description
Name	FILEPATH

Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.13.3.SW-ModifyCardUpload-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*INTRADAYSEQNO*

*MODNO*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Modification Input Only type details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## INTRADAYSEQNO

Attribute	Description	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Card-Upload-Full**

Attribute	Description	
Name	Card-Upload-Full	
Datatype		
Description	Includes Switch Debit Card FCC Account Upload Modification Full type details	

**FILENAME**

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	255

**FILEPATH**

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		



[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.13.4.SW-ModifyCardUpload-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Card-Upload-PK*  
*FILENAME*  
*FILEPATH*  
*Card-Upload-IO*  
*FILENAME*  
*FILEPATH*  
*INTRADAYSEQNO*  
*MODNO*  
*Card-Upload-Full*  
*FILENAME*  
*FILEPATH*  
*STATUS*  
*INTRADAYSEQNO*  
*MAKERID*  
*MAKERDTSTAMP*  
*CHECKERID*  
*CHECKERDTSTAMP*  
*MODNO*

AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute		Description
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Upload-PK

Attribute	Description
Name	Card-Upload-PK
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Modification Primary Key type details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	



Description	Includes Switch Debit Card FCC Account Upload Modification Input Only type details
-------------	--

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## INTRADAYSEQNO

Attribute	Description	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Card-Upload-Full**

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Modification Full type details

**FILENAME**

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**FILEPATH**

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**INTRADAYSEQNO**

Attribute	Description
Name	INTRADAYSEQNO
Datatype	String
Description	Indicates Intraday Sequence Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.14.ModifyCashDeposit

ModifyCashDeposit

### 2.14.1.SW-ModifyCashDeposit-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

*ChargeCcy3*

[ChargeAmt3](#)  
[ChargeDesc3](#)  
[ChargeCcy4](#)  
[ChargeAmt4](#)  
[ChargeDesc4](#)  
[TransactionRefno](#)  
[ActualAmt](#)  
[MAKERID](#)  
[MAKERDTSTAMP](#)  
[CHECKERID](#)  
[CHECKERDTSTAMP](#)  
[MODNO](#)  
[AUTHSTAT](#)  
[RECSTAT](#)  
[ONCEAUTH](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

**Cash-Deposit-Full**

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes Switch ATM Cash Deposit Details Modification Full type details

**TransactionAccount**

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**TransactionCurrency**

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**TransactionAmount**

Attribute	Description	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	Attribute	Description
	minOccurs	0

## LocalccyAmt

Attribute	Description				
Name	LocalccyAmt				
Datatype	Number				
Description	Indicates Local Currency Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## TrnsactionDate

Attribute	Description				
Name	TrnsactionDate				
Datatype	Date				
Description	Indicates Transaction Date				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeCcy

Attribute	Description				
Name	ChargeCcy				
Datatype	String				
Description	Indicates Charge Currency				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt

Attribute	Description				
Name	ChargeAmt				
Datatype	Number				
Description	Indicates Charge Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc

Attribute	Description				
Name	ChargeDesc				
Datatype	String				
Description	Indicates Charge Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt2

Attribute	Description	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc2

Attribute	Description	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

### ChargeCcy3

Attribute	Description	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### ChargeAmt3

Attribute	Description	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc3

Attribute	Description	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	Attribute	Description
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt

Attribute	Description	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.14.2.SW-ModifyCashDeposit-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Cash-Deposit-IO

TransactionRefno

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Cash-Deposit-IO**

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch ATM Cash Deposit Details Modification Input Only type details

[TOP](#)**TransactionRefno**

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**MODNO**

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.14.3.SW-ModifyCashDeposit-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cash-Deposit-IO*

*TransactionRefno*

*MODNO*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

ChargeCcy3  
 ChargeAmt3  
 ChargeDesc3  
 ChargeCcy4  
 ChargeAmt4  
 ChargeDesc4  
 TransactionRefno  
 ActualAmt  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME

Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cash-Deposit-IO

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch ATM Cash Deposit Details Modification Input Only type details

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO
Datatype	Number

Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cash-Deposit-Full

<b>Attribute</b>	<b>Description</b>
Name	Cash-Deposit-Full
Datatype	
Description	Includes Switch ATM Cash Deposit Details Modification Full type details

[TOP](#)

## TransactionAccount

<b>Attribute</b>	<b>Description</b>	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## TransactionCurrency

<b>Attribute</b>	<b>Description</b>	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## TransactionAmount

<b>Attribute</b>	<b>Description</b>	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LocalccyAmt

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LocalccyAmt	
Datatype	Number	
Description	Indicates Local Currency Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TrnsactionDate

<b>Attribute</b>	<b>Description</b>	
Name	TrnsactionDate	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeCcy

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

Attribute	Description				
Name	ChgCcy1				
Datatype	String				
Description	Indicates Charge Currency 1				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt1

Attribute	Description				
Name	ChargeAmt1				
Datatype	Number				
Description	Indicates Charge Amount 1				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc1

Attribute	Description				
Name	ChargeDesc1				
Datatype	String				
Description	Indicates Charge Description 1				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## ChargeCcy2

Attribute	Description				
Name	ChargeCcy2				
Datatype	String				
Description	Indicates Charge Currency 2				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt2

Attribute	Description
Name	ChargeAmt2
Datatype	Number

Description	Indicates Charge Amount 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy4

Attribute	Description				
Name	ChargeCcy4				
Datatype	String				
Description	Indicates Charge Currency 4				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt4

Attribute	Description				
Name	ChargeAmt4				
Datatype	Number				
Description	Indicates Charge Amount 4				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc4

Attribute	Description				
Name	ChargeDesc4				
Datatype	String				
Description	Indicates Charge Description 4				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## TransactionRefno

Attribute	Description				
Name	TransactionRefno				
Datatype	String				
Description	Indicates Transaction Reference Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## ActualAmt

Attribute	Description
Name	ActualAmt
Datatype	Number

Description	Indicates Actual Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25



**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description
-----------	-------------

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.14.4.SW-ModifyCashDeposit-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cash-Deposit-PK*

*TransactionRefno*

*Cash-Deposit-IO*

*TransactionRefno*

*MODNO*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

ChargeAmt2  
 ChargeDesc2  
 ChargeCcy3  
 ChargeAmt3  
 ChargeDesc3  
 ChargeCcy4  
 ChargeAmt4  
 ChargeDesc4  
 TransactionRefno  
 ActualAmt  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description
Name	SOURCE_USERID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cash-Deposit-PK

Attribute	Description
Name	Cash-Deposit-PK
Datatype	
Description	Includes Switch ATM Cash Deposit Details Modification Primary Key type details

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Cash-Deposit-IO

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch ATM Cash Deposit Details Modification Input Only type details

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## Cash-Deposit-Full

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes Switch ATM Cash Deposit Details Modification Full type details

[TOP](#)

## TransactionAccount

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## TransactionCurrency

Attribute	Description				
Name	TransactionCurrency				
Datatype	String				
Description	Indicates Transaction Currency				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## TransactionAmount

Attribute	Description				
Name	TransactionAmount				
Datatype	Number				
Description	Indicates Transaction Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## LocalccyAmt

Attribute	Description				
Name	LocalccyAmt				
Datatype	Number				
Description	Indicates Local Currency Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## TrnsactionDate

Attribute	Description				
Name	TrnsactionDate				
Datatype	Date				
Description	Indicates Transaction Date				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeCcy

Attribute	Description				
Name	ChargeCcy				
Datatype	String				
Description	Indicates Charge Currency				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc1

<b>Attribute</b>	<b>Description</b>
Name	ChargeDesc1

Datatype	String	
Description	Indicates Charge Description 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc4

<b>Attribute</b>	<b>Description</b>
Name	ChargeDesc4

Datatype	String	
Description	Indicates Charge Description 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt

<b>Attribute</b>	<b>Description</b>	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
-----------	-------------

Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.15.ModifyForwaderDetails

ModifyForwaderDetails

### 2.15.1.SW-ModifyForwaderDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL



Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Forwarder-C-Full

Attribute	Description
Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description				
Name	FWD_INS_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td></td></tr></tbody></table>	Restrictions	Description	enumeration	
	Restrictions	Description			
enumeration					

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description				
Name	INTERNATIONAL_FLAG				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description				
Name	TRANSACTION_RESTR				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>A,D</td></tr></tbody></table>	Restrictions	Description	enumeration	A,D
	Restrictions	Description			
enumeration	A,D				

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Forward-Literal-C

<b>Attribute</b>	<b>Description</b>	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

2.15.2.SW-ModifyForwaderDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-IO*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)**VALUE**

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)**FCUBS\_BODY**

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request	

[TOP](#)**Forwarder-C-IO**

Attribute	Description	
Name	Forwarder-C-IO	
Datatype		
Description		

[TOP](#)**FRWRD\_INST\_ID**

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## FWD\_INS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	FWD_INS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

<b>Attribute</b>	<b>Description</b>	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

<b>Attribute</b>	<b>Description</b>	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**Forward-Literal-C**

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**DESCRIPTION**

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**FC\_LITERAL**

Attribute	Description	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

### 2.15.3.SW-ModifyForwaderDetails-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

#### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION



Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Forwarder-C-Full

Attribute	Description
-----------	-------------

Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description	
Name	FWD_INS_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Forward-Literal-C

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	

Description	
-------------	--

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.15.4.SW-ModifyForwarderDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Forwarder-C-PK*  
*FRWRD\_INST\_ID*  
*Forwarder-C-IO*  
*FRWRD\_INST\_ID*  
*FWD\_INS\_DESC*  
*INTERNATIONAL\_FLAG*  
*TRANSACTION\_RESTR*  
*MAKER*  
*MAKERSTAMP*  
*Forward-Literal-C*  
*DESCRIPTION*  
*FC\_LITERAL*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------

Name	CHOICE
Datatype	
Description	

[TOP](#)

### Forwarder-C-PK

Attribute	Description
Name	Forwarder-C-PK
Datatype	
Description	

[TOP](#)

### FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

### Forwarder-C-IO

Attribute	Description
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)

### FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

### FWD\_INS\_DESC

Attribute	Description	
Name	FWD_INS_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

<b>Attribute</b>	<b>Description</b>	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

<b>Attribute</b>	<b>Description</b>	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35



**Forward-Literal-C**

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**DESCRIPTION**

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**FC\_LITERAL**

Attribute	Description	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description
Name	ERROR

Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.16.ModifyMerchDetails

ModifyMerchDetails

### 2.16.1.SW-ModifyMerchDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Description
Attribute	Description
maxOccurs	unbounded
minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Merchant-Details-Full

Attribute	Description
Name	Merchant-Details-Full
Datatype	
Description	Includes Switch -Merchant details Modification details

[TOP](#)

## SUSPAC

Attribute	Description
Name	SUSPAC
Datatype	String
Description	Indicates Suspense Account

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

2.16.2.SW-ModifyMerchDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Merchant-Details-IO*

*SUSPAC*

*MERCHANTID*

*ACCBRN*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------



Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Modification-IO details

[TOP](#)

## SUSPAC

Attribute	Description	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

## MERCHANTID

Attribute	Description
Name	MERCHANTID

Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.16.3.SW-ModifyMerchDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Merchant-Details-IO*

*SUSPAC*

*MERCHANTID*

*ACCBRN*

*MODNO*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------



Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Merchant-Details-IO**

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Modification-IO details

[TOP](#)**SUSPAC**

Attribute	Description	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)**MERCHANTID**

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**ACCBRN**

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Merchant-Details-Full**

Attribute	Description	
Name	Merchant-Details-Full	
Datatype		
Description	Includes Switch -Merchant details Modification-Full details	

**SUSPAC**

Attribute	Description	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRTSTMP**

Attribute	Description	
Name	MAKRTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)**ACCNO**

Attribute		Description
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.16.4.SW-ModifyMerchDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Merchant-Details-PK*

*MERCHANTID*

*ACCBRN*

*Merchant-Details-IO*

*SUSPAC*

*MERCHANTID*

*ACCBRN*

*MODNO*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*



MERCHANTID  
 ACCBRN  
 ACCNO  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute		Description
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+]*</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+]*
	Restrictions	Description					
	maxLength	128					
pattern	[a-zA-Z_0-9=+]*						

[TOP](#)

## ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Merchant-Details-PK

Attribute	Description
Name	Merchant-Details-PK
Datatype	
Description	Includes Switch -Merchant details Modification-Primary key details

[TOP](#)

## MERCHANTID

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Modification-IO details

**SUSPAC**

Attribute	Description	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

**MERCHANTID**

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**ACCBRN**

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Merchant-Details-Full**

Attribute	Description
Name	Merchant-Details-Full
Datatype	
Description	Includes Switch -Merchant details Modification-Full details

[TOP](#)

## SUSPAC

Attribute	Description	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKRDSTMP

Attribute	Description	
Name	MAKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## CHEKRID

Attribute	Description	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
-----------	-------------	--

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.17.ModifyNetworkDetails

ModifyNetworkDetails

### 2.17.1.SW-ModifyNetworkDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

[NETWORK\\_ID](#)  
[Issuer-Details](#)  
[ISSBIN](#)  
[ISSDESC](#)  
[NETWORKID](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Network-Details-Full

Attribute	Description
-----------	-------------

Name	Network-Details-Full
Datatype	
Description	Includes Switch -Network details Modification details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description						
Name	Acquirer_Details						
Datatype							
Description	Includes Acquirer details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ACQBIN

Attribute	Description				
Name	ACQBIN				
Datatype	String				
Description	Indicates Acquirer BIN				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## ACQDESC

Attribute	Description				
Name	ACQDESC				
Datatype	String				
Description	Indicates Acquirer Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## Issuer-Details

Attribute	Description
Name	Issuer-Details

Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

2.17.2.SW-ModifyNetworkDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Network-Details-IO*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*MODNO*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

*NETWORK\_ID*

*Issuer-Details*

*ISSBIN*

*ISSDESC*

*NETWORKID*

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	



**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Network-Details-IO

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Modification-IO details

[TOP](#)

## NETWORKID

Attribute	Description
Name	NETWORKID
Datatype	String
Description	Indicates Network Id

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Acquirer\_Details

<b>Attribute</b>	<b>Description</b>	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

**ACQBIN**

Attribute	Description	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

**ACQDESC**

Attribute	Description	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

**NETWORK\_ID**

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**Issuer-Details**

Attribute	Description	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ISSBIN**

Attribute	Description
-----------	-------------

Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)



### 2.17.3.SW-ModifyNetworkDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Network-Details-IO*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*MODNO*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

*NETWORK\_ID*

*Issuer-Details*

*ISSBIN*

*ISSDESC*

*NETWORKID*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

MAKERID  
 MAKRDTSTMP  
 CHECKERID  
 CHEKRDSTMP  
 MODNO  
 RECORDSTAT  
 AUTHSTAT  
 ONCEAUTH  
*Acquirer\_Details*  
 ACQBIN  
 ACQDESC  
 NETWORK\_ID  
*Issuer-Details*  
 ISSBIN  
 ISSDESC  
 NETWORKID  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME

Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Network-Details-IO

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Modification-IO details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Acquirer\_Details

<b>Attribute</b>	<b>Description</b>	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

<b>Attribute</b>	<b>Description</b>	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11



**ACQDESC**

Attribute	Description	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

**NETWORK\_ID**

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**Issuer-Details**

Attribute	Description	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ISSBIN**

Attribute	Description	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

**ISSDESC**

Attribute	Description
-----------	-------------

Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Network-Details-Full

<b>Attribute</b>	<b>Description</b>	
Name	Network-Details-Full	
Datatype		
Description	Includes Switch -Network details Modification-Full details	

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

**ACCOUNTNO**

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**ACCOUNTBRN**

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDSTMP**

Attribute	Description	
Name	MAKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHEKRDSTMP

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

Attribute	Description	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## ACQDESC

Attribute	Description
Name	ACQDESC

Datatype	String	
Description	Indicates Acquirer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORK\_ID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.17.4.SW-ModifyNetworkDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Network-Details-PK*

*NETWORKID*

*Network-Details-IO*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*MODNO*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

*NETWORK\_ID*

*Issuer-Details*

*ISSBIN*

*ISSDESC*

*NETWORKID*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

ACCOUNTNO  
 ACCOUNTBRN  
 MAKERID  
 MAKRDTSTMP  
 CHECKERID  
 CHEKRDSTMP  
 MODNO  
 RECORDSTAT  
 AUTHSTAT  
 ONCEAUTH  
 Acquirer\_Details  
     ACQBIN  
     ACQDESC  
     NETWORK\_ID  
 Issuer-Details  
     ISSBIN  
     ISSDESC  
     NETWORKID  
 FCUBS\_ERROR\_RESP  
     ERROR  
         ECODE  
         EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
         WCODE  
         WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description
Name	SOURCE_USERID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Network-Details-PK

Attribute	Description
Name	Network-Details-PK
Datatype	
Description	Includes Switch -Network details Modification-Primary key details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Network-Details-IO

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Modification-IO details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Acquirer\_Details

<b>Attribute</b>	<b>Description</b>	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

<b>Attribute</b>	<b>Description</b>	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQDESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORK\_ID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Issuer-Details

Attribute	Description						
Name	Issuer-Details						
Datatype							
Description	Includes Issuer details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ISSBIN

Attribute	Description				
Name	ISSBIN				
Datatype	String				
Description	Indicates Issuer BIN				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

## ISSDESC

Attribute	Description				
Name	ISSDESC				
Datatype	String				
Description	Indicates Issuer Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## NETWORKID

Attribute	Description				
Name	NETWORKID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## Network-Details-Full

Attribute	Description
Name	Network-Details-Full

Datatype	
Description	Includes Switch -Network details Modification-Full details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description						
Name	Acquirer_Details						
Datatype							
Description	Includes Acquirer details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ACQBIN

Attribute	Description				
Name	ACQBIN				
Datatype	String				
Description	Indicates Acquirer BIN				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## ACQDESC

Attribute	Description				
Name	ACQDESC				
Datatype	String				
Description	Indicates Acquirer Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## Issuer-Detials

Attribute	Description
Name	Issuer-Detials

Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE



Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.18.ModifyNetworkDetailss

ModifyNetworkDetailss

### 2.18.1.SW-ModifyNetworkDetailss-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-Full*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Swtms-Acquirer-Details*

*ACQ\_BINN*

*ACQ\_DESC*

*Swtms-Issuer-Details*

[ISS\\_BINN](#)

[ISS\\_DESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Swtns-Network-Details-Full

Attribute	Description
-----------	-------------

Name	Swtms-Network-Details-Full
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## ACCOUNT\_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3



**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Swtms-Acquirer-Details

Attribute	Description	
Name	Swtms-Acquirer-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

Attribute	Description	
Name	ACQ_BINN	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtns-Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Issuer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ISS_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## 2.18.2.SW-ModifyNetworkDetailss-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Swtms-Network-Details-IO*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*Swtms-Acquirer-Details*

*ACQ\_DESC*

*Swtms-Issuer-Details*

*ISS\_DESC*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Swtns-Network-Details-IO

Attribute	Description
Name	Swtns-Network-Details-IO
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description
Name	NETWORK_ID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## ACCOUNT\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## Swtms-Acquirer-Details

Attribute	Description	
Name	Swtms-Acquirer-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_DESC

Attribute	Description	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## Swtms-Issuer-Details

Attribute	Description	
Name	Swtms-Issuer-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

### 2.18.3.SW-ModifyNetworkDetailss-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-Full*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Swtms-Acquirer-Details*

*ACQ\_BINN*

*ACQ\_DESC*

*Swtms-Issuer-Details*

*ISS\_BINN*

*ISS\_DESC*

*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

## Swtms-Network-Details-Full

Attribute	Description
Name	Swtms-Network-Details-Full
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## ACCOUNT\_NO

Attribute	Description				
Name	ACCOUNT_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>225</td></tr></tbody></table>	Restrictions	Description	maxLength	225
Restrictions	Description				
maxLength	225				

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Swtns-Acquirer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Acquirer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ACQ_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtns-Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Issuer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ISS_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.18.4.SW-ModifyNetworkDetailss-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Swtms-Network-Details-PK*  
*NETWORK\_ID*  
*Swtms-Network-Details-IO*  
*NETWORK\_ID*  
*ACCOUNT\_NO*  
*DESCRIPTION*  
*ACCOUNT\_BRANCH*  
*MAKER*  
*MAKERSTAMP*  
*Swtms-Acquirer-Details*  
*ACQ\_DESC*  
*Swtms-Issuer-Details*  
*ISS\_DESC*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*

WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------

Name	CHOICE
Datatype	
Description	

[TOP](#)

### Swtms-Network-Details-PK

Attribute	Description
Name	Swtms-Network-Details-PK
Datatype	
Description	

[TOP](#)

### NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

### Swtms-Network-Details-IO

Attribute	Description
Name	Swtms-Network-Details-IO
Datatype	
Description	

[TOP](#)

### NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

### ACCOUNT\_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35



**Swtms-Acquirer-Details**

Attribute	Description	
Name	Swtms-Acquirer-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ACQ\_DESC**

Attribute	Description	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

**Swtms-Issuer-Details**

Attribute	Description	
Name	Swtms-Issuer-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ISS\_DESC**

Attribute	Description	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

**FCUBS\_ERROR\_RESP**

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.19.ModifyProcessCodeMapping

ModifyProcessCodeMapping

### 2.19.1.SW-ModifyProcessCodeMapping-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

**FCUBS\_HEADER**

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Process-Code-Mapping-Full

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes Switch Process Code Mapping Modification Full type details

[TOP](#)

## FCLITERAL

Attribute	Description
Name	FCLITERAL
Datatype	String

Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN(ADJUSTMENT) : MRA MERCHANDISE RETURN(VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## 2.19.2.SW-ModifyProcessCodeMapping-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Process-Code-Mapping-IO*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MODNO*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Process-Code-Mapping-IO

<b>Attribute</b>	<b>Description</b>
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch Process Code Mapping Modification Input Only type details

[TOP](#)

## FCLITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN(ADJUSTMENT) : MRA MERCHANDISE RETURN(VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

**MODNO**

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

### 2.19.3.SW-ModifyProcessCodeMapping-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Process-Code-Mapping-IO*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MODNO*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch Process Code Mapping Modification Input Only type details

[TOP](#)

## FCLITERAL

Attribute	Description				
Name	FCLITERAL				
Datatype	String				
Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN(ADJUSTMENT) : MRA MERCHANDISE RETURN(VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>1</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP
Restrictions	Description				
enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP				

[TOP](#)

## CHANNEL

Attribute	Description				
Name	CHANNEL				
Datatype	String				
Description	Indicates Channel				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

**Process-Code-Mapping-Full**

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes Switch Process Code Mapping Modification Full type details

**FCLITERAL**

Attribute	Description	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN (ADJUSTMENT) : MRA MERCHANDISE RETURN (VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP

**CHANNEL**

Attribute	Description	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

**EXTTXNCODE**

Attribute	Description	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
	Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1



**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	

Description	
-------------	--

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
Attribute	Description						
maxOccurs	unbounded						
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.19.4.SW-ModifyProcessCodeMapping-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Process-Code-Mapping-PK*

*PROCODTYP*

*FCLITERAL*

*Process-Code-Mapping-IO*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MODNO*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description
Name	SERVICE

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)



## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Process-Code-Mapping-PK

Attribute	Description
Name	Process-Code-Mapping-PK
Datatype	
Description	Includes Switch Process Code Mapping Modification Primary Key type details

[TOP](#)

## PROCODTYP

Attribute	Description				
Name	PROCODTYP				
Datatype	String				
Description	Indicates Process Code Type				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2</td></tr></tbody></table>	Restrictions	Description	maxLength	2
	Restrictions	Description			
maxLength	2				

[TOP](#)

## FCLITERAL

Attribute	Description				
Name	FCLITERAL				
Datatype	String				
Description	Indicates Flexcube Literal				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO

Datatype	
Description	Includes Switch Process Code Mapping Modification Input Only type details

[TOP](#)

## FCLITERAL

Attribute	Description	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CHANNEL

Attribute	Description	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

Attribute	Description	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Process-Code-Mapping-Full**

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes Switch Process Code Mapping Modification Full type details

**FCLITERAL**

Attribute	Description	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**CHANNEL**

Attribute	Description
Name	CHANNEL
Datatype	String
Description	Indicates Channel

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.20.ModifyTerminalDetails

ModifyTerminalDetails

### 2.20.1.SW-ModifyTerminalDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Terminal-Details-Full*

*TERMIN*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)**Terminal-Details-Full**

Attribute	Description
Name	Terminal-Details-Full
Datatype	
Description	Includes Switch Terminal Identification Modification Full type details

**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

**ORGBRN**

Attribute	Description	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**CASHGL**

Attribute	Description	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**MERCHID**

Attribute	Description	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**TERMADDR**

Attribute	Description	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## CHANNEL

Attribute	Description	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,P

[TOP](#)

## INTELDEP

Attribute	Description	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP



Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## 2.20.2.SW-ModifyTerminalDetails-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Terminal-Details-IO*

TERMINID

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Terminal-Details-IO**

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch Terminal Identification Modification Input Only type details

[TOP](#)**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**MODNO**

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.20.3.SW-ModifyTerminalDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Terminal-Details-IO*

*TERMIN*

*MODNO*

*Terminal-Details-Full*

*TERMIN*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

[ONCEAUTH](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)  
**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Terminal-Details-IO

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch Terminal Identification Modification Input Only type details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## Terminal-Details-Full

Attribute	Description
Name	Terminal-Details-Full
Datatype	
Description	Includes Switch Terminal Identification Modification Full type details

[TOP](#)

## TERMID

Attribute	Description
-----------	-------------



Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ORGBRN

<b>Attribute</b>	<b>Description</b>	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CASHGL

<b>Attribute</b>	<b>Description</b>	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MERCHID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TERMADDR

<b>Attribute</b>	<b>Description</b>	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## INTELDEP

<b>Attribute</b>	<b>Description</b>	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	

Description	
-------------	--

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
Attribute	Description						
maxOccurs	unbounded						
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.20.4.SW-ModifyTerminalDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Terminal-Details-PK*

*TERMID*

*Terminal-Details-IO*

*TERMID*

*MODNO*

*Terminal-Details-Full*

*TERMID*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute		Description
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute		Description
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute		Description
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute		Description
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**SERVICE**

Attribute		Description
Name	SERVICE	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute		Description
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+]*</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+]*
	Restrictions	Description					
	maxLength	128					
pattern	[a-zA-Z_0-9=+]*						

[TOP](#)

## ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Terminal-Details-PK

Attribute	Description
Name	Terminal-Details-PK
Datatype	
Description	Includes Switch Terminal Identification Modification Primary Key type details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Terminal-Details-IO

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch Terminal Identification Modification Input Only type details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Terminal-Details-Full**

Attribute	Description	
Name	Terminal-Details-Full	
Datatype		
Description	Includes Switch Terminal Identification Modification Full type details	

**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**ORGBRN**

Attribute	Description	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**CASHGL**

Attribute	Description	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MERCHID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TERMADDR

<b>Attribute</b>	<b>Description</b>	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## INTELDEP

<b>Attribute</b>	<b>Description</b>	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCUBS\_ERROR\_RESP**



Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description	Includes FCUBS Error Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.21.ModifyUtilityProvider

ModifyUtilityProvider

### 2.21.1.SW-ModifyUtilityProvider-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ACCOUNT\_NO*

*UTILITY\_PROVIDER\_ID*

*ACCOUNT\_BRANCH*

*DESCRIPTION*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTIRIPID

Attribute	Description				
Name	MULTIRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## ACCOUNT\_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UTILITY\_PROVIDER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.21.2.SW-ModifyUtilityProvider-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Main-IO*

*ACCOUNT\_NO*

*UTILITY\_PROVIDER\_ID*

*ACCOUNT\_BRANCH*

*DESCRIPTION*

*MAKER*

*MAKERSTAMP*

## **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## **SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		



Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ACCOUNT\_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## UTILITY\_PROVIDER\_ID

Attribute	Description
Name	UTILITY_PROVIDER_ID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

### 2.21.3.SW-ModifyUtilityProvider-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-Full*

*ACCOUNT\_NO*

*UTILITY\_PROVIDER\_ID*

*ACCOUNT\_BRANCH*

*DESCRIPTION*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

#### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

#### *FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*



[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)**ACCOUNT\_NO**

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**UTILITY\_PROVIDER\_ID**

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)**ACCOUNT\_BRANCH**

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**DESCRIPTION**

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.21.4.SW-ModifyUtilityProvider-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*UTILITY\_PROVIDER\_ID*  
*Main-IO*  
*ACCOUNT\_NO*  
*UTILITY\_PROVIDER\_ID*  
*ACCOUNT\_BRANCH*  
*DESCRIPTION*  
*MAKER*  
*MAKERSTAMP*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## UTILITY\_PROVIDER\_ID

Attribute	Description				
Name	UTILITY_PROVIDER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ACCOUNT\_NO

Attribute	Description				
Name	ACCOUNT_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## UTILITY\_PROVIDER\_ID

Attribute	Description				
Name	UTILITY_PROVIDER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.22.ModifyUtilityProviderDet

ModifyUtilityProviderDet

### 2.22.1.SW-ModifyUtilityProviderDet-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	



Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## UtilityProvider-Detials-Full

Attribute	Description
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes Switch Utility Provider Modification Full type details

[TOP](#)

## ACCOUNTNO

Attribute	Description
Name	ACCOUNTNO
Datatype	String
Description	Indicates the Account Number.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**xRECORDSTAT**

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UTILITYPROVIDERID**

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)



## 2.22.2.SW-ModifyUtilityProviderDet-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*UtilityProvider-Details-IO*

ACCOUNTNO

UTILITYPROVIDERID

ACCOUNTBRN

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## UtilityProvider-Details-IO

Attribute	Description
Name	UtilityProvider-Details-IO
Datatype	
Description	Includes Switch Utility Provider Modification Input Only type details

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description
Name	UTILITYPROVIDERID
Datatype	String
Description	Indicates the Utility Provider ID.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.22.3.SW-ModifyUtilityProviderDet-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*UtilityProvider-Details-IO*

*ACCOUNTNO*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

*MODNO*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

*FCUBS\_ERROR\_RESP*



[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## UtilityProvider-Details-IO

Attribute	Description
Name	UtilityProvider-Details-IO
Datatype	
Description	Includes Switch Utility Provider Modification Input Only type details

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## UtilityProvider-Detials-Full

<b>Attribute</b>	<b>Description</b>
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes Switch Utility Provider Modification Full type details

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHEKRDSTMP

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## xRECORDSTAT

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description
Name	AUTHSTAT



Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.22.4.SW-ModifyUtilityProviderDet-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*UtilityProvider-Details-PK*

*UTILITYPROVIDERID*

*UtilityProvider-Details-IO*

*ACCOUNTNO*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

*MODNO*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDTSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

ACCOUNTBRN  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------



Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## UtilityProvider-Detials-PK

Attribute	Description
Name	UtilityProvider-Detials-PK
Datatype	
Description	Includes Switch Utility Provider Modification Primary Key type details

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## UtilityProvider-Detials-IO

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes Switch Utility Provider Modification Input Only type details

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description
Name	UTILITYPROVIDERID
Datatype	String

Description	Indicates the utility Provider ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## UtilityProvider-Detials-Full

<b>Attribute</b>	<b>Description</b>
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes Switch Utility Provider Modification Full type details

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDTSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## xRECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.23.QueryCARDTOACCMAPPING

Query Card To Account Mapping

### 2.23.1.SW-QueryCARDTOACCMAPPING-Req-IO-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<b>Restrictions</b>
	<b>Description</b>
	pattern
	[a-zA-Z_0-9]*



**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description
Name	ATM_ACCOUNT_NO

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## 2.23.2.SW-QueryCARDTOACCMAPPING-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

Sub

ATM\_DLY\_TXN\_LIMIT

POS\_DLY\_CNT\_LIMIT

ATM\_DLY\_CNT\_LIMIT

POS\_DLY\_TXN\_LIMIT

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				



Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description
Name	SERVICE

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description				
Name	ATM_CARD_N				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>19</td></tr></tbody></table>	Restrictions	Description	maxLength	19
Restrictions	Description				
maxLength	19				

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description				
Name	ATM_ACCOUNT_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>28</td></tr></tbody></table>	Restrictions	Description	maxLength	28
Restrictions	Description				
maxLength	28				

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full

Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ACCNUM

Attribute	Description	
Name	ACCNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**CCY\_CODE**

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CARD\_TYPE**

Attribute	Description	
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	80

**LMT\_APPLICABILITY**

Attribute	Description	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,S

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sub

<b>Attribute</b>	<b>Description</b>	
Name	Sub	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_CNT_LIMIT	

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.24.QueryCardAccMapping

QueryCardAccMapping

### 2.24.1.SW-QueryCardAccMapping-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		



Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Card-Account-Mapping-IO

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch -Card Account mapping Query-IO details

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description
Name	ATMACCNO

Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

## 2.24.2.SW-QueryCardAccMapping-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)



## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Account-Mapping-IO

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch -Card Account mapping Query-IO details

[TOP](#)

## ATMCARDNO

Attribute	Description				
Name	ATMCARDNO				
Datatype	String				
Description	Indicates ATM/Debit Card Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>19</td></tr></tbody></table>	Restrictions	Description	maxLength	19
	Restrictions	Description			
maxLength	19				

[TOP](#)

## ATMACCNO

Attribute	Description				
Name	ATMACCNO				
Datatype	String				
Description	Indicates Card Account Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>18</td></tr></tbody></table>	Restrictions	Description	maxLength	18
	Restrictions	Description			
maxLength	18				

[TOP](#)

## Card-Account-Mapping-Full

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes Switch -Card Account mapping Query-Full details

[TOP](#)

## ATMCARDNO

Attribute	Description
Name	ATMCARDNO

Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

## FCCACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCBRN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCCACCNO

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCCACCCY

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.25.QueryCardAccount

QueryCardAccount

### 2.25.1.SW-QueryCardAccount-Req-IO-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-IO*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>
Name	CUST_AC_NO

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## 2.25.2.SW-QueryCardAccount-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-IO*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

FLDVAL

Sttms-Debit

BRANCH\_CODE

CUST\_NO

ACTNO

Sttms-Detail

BRANCH\_CODE

REQUEST\_REFERENCE\_NO

CARDNO

CUST\_NO

CARD\_PRODUCT

PRIMARY\_CARD

NAME\_ON\_CARD

OWNER\_ID\_NO

CARD\_ISSUED\_DT

CARD\_EXPIRY\_DT

CARD\_STATUS

RECORD\_STAT

AUTH\_STAT

CARD\_BIN

CUST\_AC\_NO

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	



Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## Main-Full

<b>Attribute</b>	<b>Description</b>
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>
Name	CUST_AC_NO

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## DR\_CR\_INDI

<b>Attribute</b>	<b>Description</b>	
Name	DR_CR_INDI	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,C

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

**Sttms-Debit**

Attribute	Description
-----------	-------------



Name	Sttms-Debit	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**REQUEST\_REFERENCE\_NO**

Attribute	Description	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description
Name	CARD_ISSUED_DT

Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**CARD\_BIN**

Attribute	Description	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

**CUST\_AC\_NO**

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	

Description	
-------------	--

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
Attribute	Description						
maxOccurs	unbounded						
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.26.QueryCardCustomer

QueryCardCustomer

### 2.26.1.SW-QueryCardCustomer-Req-IO-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-IO*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	



Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

<b>Attribute</b>	<b>Description</b>
Name	CUSTOMER_NAME

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## 2.26.2.SW-QueryCardCustomer-Res-Full-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-IO*  
*CUSTOMER\_ID*  
*CUSTOMER\_NAME*  
*Main-Full*  
*CUSTOMER\_ID*  
*CUSTOMER\_NAME*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Sttms-Debit*  
*BRANCH\_CODE*  
*CUST\_NO*  
*ACTNO*  
*Sttms-Detail*

BRANCH\_CODE  
 REQUEST\_REFERENCE\_NO  
 CARDNO  
 CUST\_NO  
 CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}



**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description
Name	SOURCE_USERID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## Main-Full

Attribute	Description	
Name	Main-Full	
Datatype		
Description		

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16



**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description
Name	ERROR
Datatype	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
-----------	-------------

Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.27.QueryCardUpload

QueryCardUpload

### 2.27.1.SW-QueryCardUpload-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	



Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch -Card Upload Query-IO details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description
Name	FILEPATH

Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## 2.27.2.SW-QueryCardUpload-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*FCUBS\_ERROR\_RESP*

*ERROR*

[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)



## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch -Card Upload Query-IO details

[TOP](#)

## FILENAME

Attribute	Description				
Name	FILENAME				
Datatype	String				
Description	Indicates File Name				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

[TOP](#)

## FILEPATH

Attribute	Description				
Name	FILEPATH				
Datatype	String				
Description	Indicates File Path				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

[TOP](#)

## Card-Upload-Full

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes Switch -Card Upload Query-Full details

[TOP](#)

## FILENAME

Attribute	Description
Name	FILENAME

Datatype	String	
Description	Indicates File Name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

<b>Attribute</b>	<b>Description</b>	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	



[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.28.QueryCashDeposit

QueryCashDeposit

### 2.28.1.SW-QueryCashDeposit-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cash-Deposit-IO*

*TransactionRefno*

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cash-Deposit-IO

<b>Attribute</b>	<b>Description</b>
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch -Cash Deposit Query-IO details

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## 2.28.2.SW-QueryCashDeposit-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cash-Deposit-IO*

*TransactionRefno*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

*ChargeCcy3*



ChargeAmt3  
 ChargeDesc3  
 ChargeCcy4  
 ChargeAmt4  
 ChargeDesc4  
 TransactionRefno  
 ActualAmt  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME

Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cash-Deposit-IO

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch -Cash Deposit Query-IO details

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Cash-Deposit-Full

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes Switch -Cash Deposit Query-Full details

**TransactionAccount**

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**TransactionCurrency**

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**TransactionAmount**

Attribute	Description	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	Attribute	Description
	minOccurs	0

**LocalccyAmt**

Attribute	Description	
Name	LocalccyAmt	
Datatype	Number	
Description	Indicates Local Currency Amount	
Attributes	Attribute	Description
	minOccurs	0

**TrnsactionDate**

Attribute	Description	
Name	TrnsactionDate	
Datatype	Date	
Description	Indicates Transaction Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeCcy

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt1



Attribute	Description	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ChargeDesc1

Attribute	Description	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## ChargeCcy2

Attribute	Description	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ChargeAmt2

Attribute	Description	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ChargeDesc2

Attribute	Description	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt4

Attribute	Description	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ChargeDesc4

Attribute	Description	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ActualAmt

Attribute	Description	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.29.QueryForwaderDetails

QueryForwaderDetails

### 2.29.1.SW-QueryForwaderDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-IO*

*FRWRD\_INST\_ID*

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				



**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Forwarder-C-IO

<b>Attribute</b>	<b>Description</b>
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## 2.29.2.SW-QueryForwarderDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Forwarder-C-IO*  
*FRWRD\_INST\_ID*  
*Forwarder-C-Full*  
*FRWRD\_INST\_ID*  
*FWD\_INS\_DESC*  
*INTERNATIONAL\_FLAG*  
*TRANSACTION\_RESTR*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Forward-Literal-C*  
*DESCRIPTION*  
*FC\_LITERAL*  
*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Forwarder-C-IO

Attribute	Description
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
Restrictions	Description				
maxLength	11				

[TOP](#)

## Forwarder-C-Full

Attribute	Description
Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
Restrictions	Description				
maxLength	11				

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description
Name	FWD_INS_DESC

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

<b>Attribute</b>	<b>Description</b>	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

<b>Attribute</b>	<b>Description</b>	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Forward-Literal-C**

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**DESCRIPTION**

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**FC\_LITERAL**

Attribute	Description	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**FCUBS\_ERROR\_RESP**

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded



[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.30.QueryMerchDetails

QueryMerchDetails

### 2.30.1.SW-QueryMerchDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Merchant-Details-IO*

*MERCHANTID*

*ACCBRN*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Query

[TOP](#)

## MERCHANTID

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)



## 2.30.2.SW-QueryMerchDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Merchant-Details-IO*

*MERCHANTID*

*ACCBRN*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDTSTMP*

*CHEKRID*

*CHEKRDTSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Query-IO details

[TOP](#)

## MERCHANTID

Attribute	Description				
Name	MERCHANTID				
Datatype	String				
Description	Indicates Merchant ID				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description	Indicates Account Branch				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## Merchant-Details-Full

Attribute	Description
Name	Merchant-Details-Full
Datatype	
Description	Includes Switch -Merchant details Query-Full details

[TOP](#)

## SUSPAC

Attribute	Description
Name	SUSPAC

Datatype	String	
Description	Indicates Suspense Account	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRTDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRTDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.31.CreateUtilityProvider

CreateUtilityProvider

### 2.31.1.SW-CreateUtilityProvider-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ACCOUNT\_NO*

*UTILITY\_PROVIDER\_ID*

*ACCOUNT\_BRANCH*

*DESCRIPTION*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTIRIPID

Attribute	Description				
Name	MULTIRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## ACCOUNT\_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UTILITY\_PROVIDER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.31.2.SW-CreateUtilityProvider-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Main-IO

ACCOUNT\_NO

UTILITY\_PROVIDER\_ID

ACCOUNT\_BRANCH

DESCRIPTION

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ACCOUNT\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UTILITY\_PROVIDER\_ID

<b>Attribute</b>	<b>Description</b>
Name	UTILITY_PROVIDER_ID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

### 2.31.3.SW-CreateUtilityProvider-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ACCOUNT\_NO*

*UTILITY\_PROVIDER\_ID*

*ACCOUNT\_BRANCH*

*DESCRIPTION*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)**ACCOUNT\_NO**

Attribute		Description
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**UTILITY\_PROVIDER\_ID**

Attribute		Description
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)**ACCOUNT\_BRANCH**

Attribute		Description
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**DESCRIPTION**

Attribute		Description
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.31.4.SW-CreateUtilityProvider-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*UTILITY\_PROVIDER\_ID*  
*Main-IO*  
*ACCOUNT\_NO*  
*UTILITY\_PROVIDER\_ID*  
*ACCOUNT\_BRANCH*  
*DESCRIPTION*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	



Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

**UTILITY\_PROVIDER\_ID**

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

**Main-IO**

Attribute	Description
Name	Main-IO
Datatype	
Description	

**ACCOUNT\_NO**

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**UTILITY\_PROVIDER\_ID**

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

**ACCOUNT\_BRANCH**

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	

Description	
-------------	--

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.32.CreateUtilityProviderDet

CreateUtilityProviderDet

### 2.32.1.SW-CreateUtilityProviderDet-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	



Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTIRIPID

Attribute	Description				
Name	MULTIRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## UtilityProvider-Detials-Full

Attribute	Description
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes Switch Utility Provider Creation Full type details

[TOP](#)

## ACCOUNTNO

Attribute	Description
Name	ACCOUNTNO
Datatype	String
Description	Indicates the Account Number.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRTDSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRTDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**xRECORDSTAT**

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UTILITYPROVIDERID**

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)



## 2.32.2.SW-CreateUtilityProviderDet-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*UtilityProvider-Details-IO*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## UtilityProvider-Detials-IO

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes Switch Utility Provider Creation Input Only type details

[TOP](#)

## ACCOUNTNO

Attribute	Description
Name	ACCOUNTNO
Datatype	String
Description	Indicates the Account Number.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRTDSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRTDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECORDSTAT**

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UTILITYPROVIDERID**



Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### 2.32.3.SW-CreateUtilityProviderDet-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*UtilityProvider-Details-IO*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

MODNO  
 xRECORDSTAT  
 AUTHSTAT  
 ONCEAUTH  
 UTILITYPROVIDERID  
 ACCOUNTBRN  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description
Name	SERVICE

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## UtilityProvider-Detials-IO

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes Switch Utility Provider Creation Input Only type details

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDTSTMP

Attribute	Description
Name	MAKRDTSTMP
Datatype	String
Description	Indicates the Maker Date Stamp.



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## UtilityProvider-Details-Full

Attribute	Description
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes Switch Utility Provider Creation Full type details

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDTSTMP

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**xRECORDSTAT**

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

[TOP](#)

## 2.32.4.SW-CreateUtilityProviderDet-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*UtilityProvider-Details-PK*

*UTILITYPROVIDERID*

*UtilityProvider-Details-IO*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*



CHECKERID  
 CHEKRDSTMP  
 MODNO  
 xRECORDSTAT  
 AUTHSTAT  
 ONCEAUTH  
 UTILITYPROVIDERID  
 ACCOUNTBRN  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## UtilityProvider-Detials-PK

Attribute	Description
Name	UtilityProvider-Detials-PK
Datatype	
Description	Includes Switch Utility Provider Creation Primary Key type details

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## UtilityProvider-Detials-IO

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes Switch Utility Provider Creation Input Only type details

[TOP](#)

## ACCOUNTNO

Attribute	Description
Name	ACCOUNTNO
Datatype	String
Description	Indicates the Account Number.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRTSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRTSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRTSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECORDSTAT**

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UTILITYPROVIDERID**



Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## UtilityProvider-Detials-Full

Attribute	Description	
Name	UtilityProvider-Detials-Full	
Datatype		
Description	Includes Switch Utility Provider Creation Full type details	

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**xRECORDSTAT**

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description
Name	ACCOUNTBRN

Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.33.DeleteCARDTOACCMAPPING

Delete Card To Account Mapping

### 2.33.1.SW-DeleteCARDTOACCMAPPING-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sub*

[ATM\\_DLY\\_TXN\\_LIMIT](#)  
[POS\\_DLY\\_CNT\\_LIMIT](#)  
[ATM\\_DLY\\_CNT\\_LIMIT](#)  
[POS\\_DLY\\_TXN\\_LIMIT](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION



Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
-----------	-------------

Name	Main-Full
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ACCNUM

Attribute	Description	
Name	ACCNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**CCY\_CODE**

Attribute		Description
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CARD\_TYPE**

Attribute		Description
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	80

**LMT\_APPLICABILITY**

Attribute		Description
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,S

**MAKER**

Attribute		Description
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sub

<b>Attribute</b>	<b>Description</b>	
Name	Sub	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_CNT_LIMIT	

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)



## 2.33.2.SW-DeleteCARDTOACCMAPPING-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Main-IO

ATM\_CARD\_N

ATM\_ACCOUNT\_NO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)**Main-IO**

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)**ATM\_CARD\_N**

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**ATM\_ACCOUNT\_NO**

Attribute	Description
Name	ATM_ACCOUNT_NO
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

### 2.33.3.SW-DeleteCARDTOACCMAPPING-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

##### *Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

##### *Sub*

*ATM\_DLY\_TXN\_LIMIT*

*POS\_DLY\_CNT\_LIMIT*

*ATM\_DLY\_CNT\_LIMIT*



[POS\\_DLY\\_TXN\\_LIMIT](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

**ATM\_CARD\_N**

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

**ATM\_ACCOUNT\_NO**

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

**ACCBRN**

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**ACCNUM**

Attribute	Description
Name	ACCNUM
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CARD\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

[TOP](#)

## LMT\_APPLICABILITY

<b>Attribute</b>	<b>Description</b>	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,S

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT



Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sub

Attribute	Description	
Name	Sub	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

Attribute	Description	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

Attribute	Description	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ATM\_DLY\_CNT\_LIMIT**

Attribute		Description
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**POS\_DLY\_TXN\_LIMIT**

Attribute		Description
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.33.4.SW-DeleteCARDTOACCMAPPING-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*ATM\_CARD\_N*  
*ATM\_ACCOUNT\_NO*  
*Main-IO*  
*ATM\_CARD\_N*  
*ATM\_ACCOUNT\_NO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTIRIPID

Attribute	Description				
Name	MULTIRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)**ATM\_CARD\_N**

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**ATM\_ACCOUNT\_NO**

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)**Main-IO**

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)**ATM\_CARD\_N**

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**ATM\_ACCOUNT\_NO**

Attribute	Description
Name	ATM_ACCOUNT_NO
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.34.DeleteCardAccMapping

DeleteCardAccMapping

### 2.34.1.SW-DeleteCardAccMapping-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

**FCUBS\_HEADER**

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Card-Account-Mapping-Full

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Deletion Full type details

[TOP](#)

## ATMCARDNO

Attribute	Description
Name	ATMCARDNO
Datatype	String
Description	Indicates ATM/Debit Card Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## FCCACCB RN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCB RN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCCACCNO**

Attribute	Description	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**FCCACCCY**

Attribute	Description	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

## 2.34.2.SW-DeleteCardAccMapping-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Card-Account-Mapping-IO

ATMCARDNO

ATMACCNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)



## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Card-Account-Mapping-IO**

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Deletion Input Only type details

[TOP](#)**ATMCARDNO**

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**ATMACCNO**

Attribute	Description
Name	ATMACCNO
Datatype	String
Description	Indicates Card Account Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

### 2.34.3.SW-DeleteCardAccMapping-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Account-Mapping-IO

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Deletion Input Only type details

[TOP](#)

## ATMCARDNO

Attribute	Description				
Name	ATMCARDNO				
Datatype	String				
Description	Indicates ATM/Debit Card Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>19</td></tr></tbody></table>	Restrictions	Description	maxLength	19
	Restrictions	Description			
maxLength	19				

[TOP](#)

## ATMACCNO

Attribute	Description				
Name	ATMACCNO				
Datatype	String				
Description	Indicates Card Account Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>18</td></tr></tbody></table>	Restrictions	Description	maxLength	18
	Restrictions	Description			
maxLength	18				

[TOP](#)

## Card-Account-Mapping-Full

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Deletion Full type details

[TOP](#)

## ATMCARDNO

Attribute	Description
-----------	-------------

Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

## FCCACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCBRN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCCACCNO

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCCACCCY

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



#### 2.34.4.SW-DeleteCardAccMapping-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*Card-Account-Mapping-PK*

*ATMCARDNO*

*ATMACCNO*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

FCCACCNO  
 FCCACCCCY  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Account-Mapping-IO

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Deletion Input Only type details

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	18

[TOP](#)

## Card-Account-Mapping-PK

Attribute	Description
Name	Card-Account-Mapping-PK
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Deletion Primary Key type details

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	18

[TOP](#)

## Card-Account-Mapping-Full

Attribute	Description	
Name	Card-Account-Mapping-Full	
Datatype		
Description	Includes Switch ATM/Debit Card FCC Account Mapping Deletion Full type details	

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

## FCCACCB RN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCB RN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKR DATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKR DATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**CHEKRDATSTMP**

Attribute	Description	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECORDSTAT**

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
	Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCCACCNO**

Attribute	Description	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**FCCACCCY**

Attribute	Description	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.35.DeleteCardAccount

DeleteCardAccount

### 2.35.1.SW-DeleteCardAccount-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

BRANCH\_CODE

CUST\_NO

ACTNO

Sttms-Detail

BRANCH\_CODE

REQUEST\_REFERENCE\_NO

CARDNO

CUST\_NO

CARD\_PRODUCT

PRIMARY\_CARD

NAME\_ON\_CARD

OWNER\_ID\_NO

CARD\_ISSUED\_DT

CARD\_EXPIRY\_DT

CARD\_STATUS

RECORD\_STAT

AUTH\_STAT

CARD\_BIN

CUST\_AC\_NO

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

[TOP](#)

## CUST\_AC\_NO

Attribute	Description				
Name	CUST_AC_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## CUSTOMER\_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## DR\_CR\_INDI

<b>Attribute</b>	<b>Description</b>	
Name	DR_CR_INDI	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,C

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

**Sttms-Debit**

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3



[TOP](#)**REQUEST\_REFERENCE\_NO**

Attribute	Description	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

**CUST\_AC\_NO**

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

2.35.2.SW-DeleteCardAccount-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-IO*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)**Main-IO**

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**CUST\_AC\_NO**

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

### 2.35.3.SW-DeleteCardAccount-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

BRANCH\_CODE  
REQUEST\_REFERENCE\_NO  
CARDNO  
CUST\_NO  
CARD\_PRODUCT  
PRIMARY\_CARD  
NAME\_ON\_CARD  
OWNER\_ID\_NO  
CARD\_ISSUED\_DT  
CARD\_EXPIRY\_DT  
CARD\_STATUS  
RECORD\_STAT  
AUTH\_STAT  
CARD\_BIN  
CUST\_AC\_NO

FCUBS\_ERROR\_RESP

ERROR  
ECODE  
EDESC

FCUBS\_WARNING\_RESP

WARNING  
WCODE  
WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

**UBSCOMP**

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME

Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## DR\_CR\_INDI

Attribute	Description				
Name	DR_CR_INDI				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>D,C</td></tr></tbody></table>	Restrictions	Description	enumeration	D,C
	Restrictions	Description			
enumeration	D,C				

[TOP](#)

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

[TOP](#)

## CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description
-----------	-------------

Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**OWNER\_ID\_NO**

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)**CARD\_ISSUED\_DT**

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CARD\_EXPIRY\_DT**

Attribute	Description
Name	CARD_EXPIRY_DT



Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.35.4.SW-DeleteCardAccount-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*BRANCH\_CODE*

*Main-IO*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL



Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## CUST\_AC\_NO

Attribute	Description				
Name	CUST_AC_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.36.DeleteCardCustomer

DeleteCardCustomer

### 2.36.1.SW-DeleteCardCustomer-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

REQUEST\_REFERENCE\_NO  
 CARDNO  
 CUST\_NO  
 CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**NAME\_ON\_CARD**



Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

## 2.36.2.SW-DeleteCardCustomer-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Main-IO

CUSTOMER\_ID

CUSTOMER\_NAME

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0



[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)**Main-IO**

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)**CUSTOMER\_ID**

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CUSTOMER\_NAME**

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

### 2.36.3.SW-DeleteCardCustomer-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

*REQUEST\_REFERENCE\_NO*

*CARDNO*

*CUST\_NO*

CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	



[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)**CUSTOMER\_ID**

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CUSTOMER\_NAME**

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)**MAKER**

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sttms-Debit

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Sttms-Detail

Attribute	Description	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String

Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

<b>Attribute</b>	<b>Description</b>	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>
Name	CARD_STATUS

Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0



[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.36.4.SW-DeleteCardCustomer-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*CUSTOMER\_ID*  
*Main-IO*  
*CUSTOMER\_ID*  
*CUSTOMER\_NAME*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	



[TOP](#)**CUSTOMER\_ID**

Attribute		Description
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**Main-IO**

Attribute		Description
Name	Main-IO	
Datatype		
Description		

[TOP](#)**CUSTOMER\_ID**

Attribute		Description
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CUSTOMER\_NAME**

Attribute		Description
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.37.DeleteCardUpload

DeleteCardUpload

### 2.37.1.SW-DeleteCardUpload-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Card-Upload-Full

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Deletion Full type details

[TOP](#)

## FILENAME

Attribute	Description
Name	FILENAME
Datatype	String
Description	Indicates File Name

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

<b>Attribute</b>	<b>Description</b>	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.37.2.SW-DeleteCardUpload-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Card-Upload-IO

FILENAME

FILEPATH

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Card-Upload-IO**

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Deletion Input Only type details

[TOP](#)**FILENAME**

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**FILEPATH**

Attribute	Description
Name	FILEPATH
Datatype	String
Description	Indicates File Path

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

### 2.37.3.SW-DeleteCardUpload-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*FCUBS\_ERROR\_RESP*

*ERROR*

[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		



Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Deletion Input Only type details

[TOP](#)

## FILENAME

Attribute	Description				
Name	FILENAME				
Datatype	String				
Description	Indicates File Name				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

[TOP](#)

## FILEPATH

Attribute	Description				
Name	FILEPATH				
Datatype	String				
Description	Indicates File Path				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

[TOP](#)

## Card-Upload-Full

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Deletion Full type details

[TOP](#)

## FILENAME

Attribute	Description
Name	FILENAME

Datatype	String	
Description	Indicates File Name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

<b>Attribute</b>	<b>Description</b>	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.37.4.SW-DeleteCardUpload-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*Card-Upload-PK*

*FILENAME*

*FILEPATH*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*



[ONCEAUTH](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Deletion Input Only type details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## Card-Upload-PK

Attribute	Description
Name	Card-Upload-PK
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Deletion Primary Key type details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## Card-Upload-Full

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Deletion Full type details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25



[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.38.DeleteCashDeposit

DeleteCashDeposit

### 2.38.1.SW-DeleteCashDeposit-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

*ChargeCcy3*

[ChargeAmt3](#)  
[ChargeDesc3](#)  
[ChargeCcy4](#)  
[ChargeAmt4](#)  
[ChargeDesc4](#)  
[TransactionRefno](#)  
[ActualAmt](#)  
[MAKERID](#)  
[MAKERDTSTAMP](#)  
[CHECKERID](#)  
[CHECKERDTSTAMP](#)  
[MODNO](#)  
[AUTHSTAT](#)  
[RECSTAT](#)  
[ONCEAUTH](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cash-Deposit-Full

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes Switch ATM Cash Deposit Details Deletion Full type details

[TOP](#)

## TransactionAccount

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## TransactionCurrency

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## TransactionAmount

Attribute	Description	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## LocalccyAmt

Attribute	Description	
Name	LocalccyAmt	
Datatype	Number	
Description	Indicates Local Currency Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TrnsactionDate

Attribute	Description	
Name	TrnsactionDate	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeCcy

Attribute	Description	
Name	ChargeCcy	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

Attribute	Description	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

Attribute	Description	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt2

Attribute	Description	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc2

Attribute	Description	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

### ChargeCcy3

Attribute	Description	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### ChargeAmt3

Attribute	Description	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc3

Attribute	Description	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt

Attribute	Description	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.38.2.SW-DeleteCashDeposit-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Cash-Deposit-IO

TransactionRefno

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Cash-Deposit-IO**

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch ATM Cash Deposit Details Deletion Input Only type details

[TOP](#)**TransactionRefno**

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

### 2.38.3.SW-DeleteCashDeposit-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cash-Deposit-IO*

*TransactionRefno*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

*ChargeCcy3*



ChargeAmt3  
 ChargeDesc3  
 ChargeCcy4  
 ChargeAmt4  
 ChargeDesc4  
 TransactionRefno  
 ActualAmt  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME

Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cash-Deposit-IO

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch ATM Cash Deposit Details Deletion Input Only type details

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Cash-Deposit-Full

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes Switch ATM Cash Deposit Details Deletion Full type details

## TransactionAccount

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

## TransactionCurrency

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

## TransactionAmount

Attribute	Description	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	Attribute	Description
	minOccurs	0

## LocalccyAmt

Attribute	Description	
Name	LocalccyAmt	
Datatype	Number	
Description	Indicates Local Currency Amount	
Attributes	Attribute	Description
	minOccurs	0

## TrnsactionDate

Attribute	Description	
Name	TrnsactionDate	
Datatype	Date	
Description	Indicates Transaction Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeCcy

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt1



Attribute	Description	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ChargeDesc1

Attribute	Description	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## ChargeCcy2

Attribute	Description	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ChargeAmt2

Attribute	Description	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ChargeDesc2

Attribute	Description	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt4

Attribute	Description	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ChargeDesc4

Attribute	Description	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ActualAmt

Attribute	Description	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.38.4.SW-DeleteCashDeposit-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cash-Deposit-IO*

*TransactionRefno*

*Cash-Deposit-PK*

*TransactionRefno*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*



ChargeDesc2  
 ChargeCcy3  
 ChargeAmt3  
 ChargeDesc3  
 ChargeCcy4  
 ChargeAmt4  
 ChargeDesc4  
 TransactionRefno  
 ActualAmt  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cash-Deposit-IO

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch ATM Cash Deposit Details Deletion Input Only type details

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Cash-Deposit-PK

Attribute	Description
Name	Cash-Deposit-PK
Datatype	
Description	Includes Switch ATM Cash Deposit Details Deletion Primary Key type details

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Cash-Deposit-Full

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes Switch ATM Cash Deposit Details Deletion Full type details

[TOP](#)

## TransactionAccount

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## TransactionCurrency

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## TransactionAmount

Attribute	Description				
Name	TransactionAmount				
Datatype	Number				
Description	Indicates Transaction Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## LocalccyAmt

Attribute	Description				
Name	LocalccyAmt				
Datatype	Number				
Description	Indicates Local Currency Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## TrnsactionDate

Attribute	Description				
Name	TrnsactionDate				
Datatype	Date				
Description	Indicates Transaction Date				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeCcy

Attribute	Description				
Name	ChargeCcy				
Datatype	String				
Description	Indicates Charge Currency				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt

Attribute	Description				
Name	ChargeAmt				
Datatype	Number				
Description	Indicates Charge Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				



**ChargeDesc**

Attribute	Description	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

**ChgCcy1**

Attribute	Description	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**ChargeAmt1**

Attribute	Description	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	Attribute	Description
	minOccurs	0

**ChargeDesc1**

Attribute	Description	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

**ChargeCcy2**

Attribute	Description
Name	ChargeCcy2

Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

### ChargeDesc3

Attribute	Description	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

### ChargeCcy4

Attribute	Description	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

### ChargeAmt4

Attribute	Description	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	Attribute	Description
	minOccurs	0

### ChargeDesc4

Attribute	Description	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

### TransactionRefno

Attribute	Description
Name	TransactionRefno

Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt

<b>Attribute</b>	<b>Description</b>	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute		Description
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.39.DeleteForwaderDetails

DeleteForwaderDetails

### 2.39.1.SW-DeleteForwaderDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

**FCUBS\_HEADER**



Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Forwarder-C-Full

Attribute	Description
Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description				
Name	FWD_INS_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td></td></tr></tbody></table>	Restrictions	Description	enumeration	
	Restrictions	Description			
enumeration					

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description				
Name	INTERNATIONAL_FLAG				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description				
Name	TRANSACTION_RESTR				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>A,D</td></tr></tbody></table>	Restrictions	Description	enumeration	A,D
	Restrictions	Description			
enumeration	A,D				

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Forward-Literal-C

<b>Attribute</b>	<b>Description</b>	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)



## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## 2.39.2.SW-DeleteForwaderDetails-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Forwarder-C-IO

FRWRD\_INST\_ID

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)**Forwarder-C-IO**

Attribute	Description
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)**FRWRD\_INST\_ID**

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

### 2.39.3.SW-DeleteForwaderDetails-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

##### *Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

##### *Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

#### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*



FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Forwarder-C-Full

Attribute	Description
-----------	-------------

Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description	
Name	FWD_INS_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Forward-Literal-C

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	

Description	
-------------	--

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.39.4.SW-DeleteForwaderDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Forwarder-C-PK*  
*FRWRD\_INST\_ID*  
*Forwarder-C-IO*  
*FRWRD\_INST\_ID*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Forwarder-C-PK

Attribute	Description
Name	Forwarder-C-PK
Datatype	
Description	



[TOP](#)**FRWRD\_INST\_ID**

Attribute		Description
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)**Forwarder-C-IO**

Attribute		Description
Name	Forwarder-C-IO	
Datatype		
Description		

[TOP](#)**FRWRD\_INST\_ID**

Attribute		Description
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

[TOP](#)

## 2.40.DeleteMerchDetails

DeleteMerchDetails

### 2.40.1.SW-DeleteMerchDetails-Req-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Description
Attribute	Description
maxOccurs	unbounded
minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Merchant-Details-Full

Attribute	Description
Name	Merchant-Details-Full
Datatype	
Description	Includes Switch -Merchant details Deletion details

[TOP](#)

## SUSPAC

Attribute	Description
Name	SUSPAC
Datatype	String
Description	Indicates Suspense Account

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## 2.40.2.SW-DeleteMerchDetails-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Merchant-Details-IO

MERCHANTID

ACCBRN

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Merchant-Details-IO**

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Deletion-IO details

[TOP](#)**MERCHANTID**

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**ACCBRN**

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### 2.40.3.SW-DeleteMerchDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Merchant-Details-IO*

*MERCHANTID*

*ACCBRN*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDTSTMP*

*CHEKRID*

*CHEKRDTSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
	Attribute	Description			
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Deletion-IO details

[TOP](#)

## MERCHANTID

Attribute	Description				
Name	MERCHANTID				
Datatype	String				
Description	Indicates Merchant ID				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description	Indicates Account Branch				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## Merchant-Details-Full

Attribute	Description
Name	Merchant-Details-Full
Datatype	
Description	Includes Switch -Merchant details Deletion-full details

[TOP](#)

## SUSPAC

Attribute	Description
Name	SUSPAC

Datatype	String	
Description	Indicates Suspense Account	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRTDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRTDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description	
Name	WCODE	

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

#### 2.40.4.SW-DeleteMerchDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Merchant-Details-IO*

*MERCHANTID*

*ACCBRN*

*Merchant-Details-PK*

*MERCHANTID*

*ACCBRN*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDTSTMP*

*CHEKRID*

*CHEKRDTSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*



ACCNO  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Deletion-IO details

[TOP](#)

## MERCHANTID

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## Merchant-Details-PK

Attribute	Description
Name	Merchant-Details-PK
Datatype	
Description	Includes Switch -Merchant details Deletion-Primary key details

[TOP](#)

## MERCHANTID

Attribute	Description
-----------	-------------

Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Merchant-Details-Full

<b>Attribute</b>	<b>Description</b>	
Name	Merchant-Details-Full	
Datatype		
Description	Includes Switch -Merchant details Deletion-full details	

[TOP](#)

## SUSPAC

<b>Attribute</b>	<b>Description</b>	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHEKRID**

Attribute	Description	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECORDSTAT**



Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## MERCHANTID

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ACCNO

Attribute	Description	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)**WARNING**

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.41.DeleteNetworkDetails

DeleteNetworkDetails

### 2.41.1.SW-DeleteNetworkDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

[NETWORK\\_ID](#)  
[Issuer-Details](#)  
[ISSBIN](#)  
[ISSDESC](#)  
[NETWORKID](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Network-Details-Full

Attribute	Description
-----------	-------------

Name	Network-Details-Full
Datatype	
Description	Includes Switch -Network details Deletion details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description						
Name	Acquirer_Details						
Datatype							
Description	Includes Acquirer details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ACQBIN

Attribute	Description				
Name	ACQBIN				
Datatype	String				
Description	Indicates Acquirer BIN				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## ACQDESC

Attribute	Description				
Name	ACQDESC				
Datatype	String				
Description	Indicates Acquirer Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## Issuer-Details

Attribute	Description
Name	Issuer-Details

Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## 2.41.2.SW-DeleteNetworkDetails-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Network-Details-IO

NETWORKID

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		



Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Network-Details-IO**

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Deletion-IO details

[TOP](#)**NETWORKID**

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

### 2.41.3.SW-DeleteNetworkDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Network-Details-IO*

*NETWORKID*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

[NETWORK\\_ID](#)  
[Issuer-Details](#)  
[ISSBIN](#)  
[ISSDESC](#)  
[NETWORKID](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description
Name	SERVICE

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Network-Details-IO

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Deletion-IO details

[TOP](#)

## NETWORKID

Attribute	Description				
Name	NETWORKID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## Network-Details-Full

Attribute	Description
Name	Network-Details-Full
Datatype	
Description	Includes Switch -Network details Deletion-Full details

[TOP](#)

## NETWORKID

Attribute	Description				
Name	NETWORKID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECORDSTAT**

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

Attribute	Description	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## ACQDESC

Attribute	Description	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Issuer-Details

Attribute	Description	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

Attribute	Description
Name	ISSBIN
Datatype	String

Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded



[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)**WARNING**

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

#### 2.41.4.SW-DeleteNetworkDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Network-Details-IO*

*NETWORKID*

*Network-Details-PK*

*NETWORKID*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDTSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

ACQBIN  
 ACQDESC  
 NETWORK\_ID  
 Issuer-Details  
 ISSBIN  
 ISSDESC  
 NETWORKID  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Network-Details-IO

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Deletion-IO details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Network-Details-PK

Attribute	Description
Name	Network-Details-PK
Datatype	
Description	Includes Switch -Network details Deletion-Primary key details

[TOP](#)

## NETWORKID

Attribute	Description
Name	NETWORKID
Datatype	String
Description	Indicates Network Id



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Network-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Network-Details-Full
Datatype	
Description	Includes Switch -Network details Deletion-Full details

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKRDTSTMP

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHEKRDSTMP

Attribute	Description
Name	CHEKRDSTMP

Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	

Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Acquirer\_Details

<b>Attribute</b>	<b>Description</b>	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

<b>Attribute</b>	<b>Description</b>	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQDESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORK\_ID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description	Includes FCUBS Error Response details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.42.DeleteNetworkDetailss

DeleteNetworkDetailss

### 2.42.1.SW-DeleteNetworkDetailss-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-Full*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Swtms-Acquirer-Details*

*ACQ\_BINN*

*ACQ\_DESC*

*Swtms-Issuer-Details*



[ISS\\_BINN](#)  
[ISS\\_DESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Swtns-Network-Details-Full

Attribute	Description
-----------	-------------

Name	Swtms-Network-Details-Full
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## ACCOUNT\_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Swtms-Acquirer-Details

Attribute	Description	
Name	Swtms-Acquirer-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

Attribute	Description	
Name	ACQ_BINN	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtms-Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtms-Issuer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ISS_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## 2.42.2.SW-DeleteNetworkDetailss-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Swtms-Network-Details-IO

NETWORK\_ID

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)**Swtns-Network-Details-IO**

Attribute	Description
Name	Swtns-Network-Details-IO
Datatype	
Description	

[TOP](#)**NETWORK\_ID**

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

### 2.42.3.SW-DeleteNetworkDetailss-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-Full*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Swtms-Acquirer-Details*

*ACQ\_BINN*

*ACQ\_DESC*

*Swtms-Issuer-Details*

*ISS\_BINN*

*ISS\_DESC*

*FCUBS\_ERROR\_RESP*



[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

## Swtms-Network-Details-Full

Attribute	Description
Name	Swtms-Network-Details-Full
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## ACCOUNT\_NO

Attribute	Description				
Name	ACCOUNT_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>225</td></tr></tbody></table>	Restrictions	Description	maxLength	225
Restrictions	Description				
maxLength	225				

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Swtns-Acquirer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Acquirer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	ACQ_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtns-Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Issuer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ISS_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.42.4.SW-DeleteNetworkDetailss-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Swtms-Network-Details-PK*  
*NETWORK\_ID*  
*Swtms-Network-Details-IO*  
*NETWORK\_ID*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Swtms-Network-Details-PK

Attribute	Description
Name	Swtms-Network-Details-PK
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## Swtms-Network-Details-IO

Attribute	Description
Name	Swtms-Network-Details-IO
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

[TOP](#)

## 2.43.DeleteProcessCodeMapping

DeleteProcessCodeMapping

### 2.43.1.SW-DeleteProcessCodeMapping-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

**FCUBS\_HEADER**

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Process-Code-Mapping-Full

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes Switch Process Code Mapping Deletion Full type details

[TOP](#)

## FCLITERAL

Attribute	Description
Name	FCLITERAL
Datatype	String

Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN(ADJUSTMENT) : MRA MERCHANDISE RETURN(VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## 2.43.2.SW-DeleteProcessCodeMapping-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTIRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Process-Code-Mapping-IO

PROCODTYP

FCLITERAL

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		



Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Process-Code-Mapping-IO**

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch Process Code Mapping Deletion Input Only type details

[TOP](#)**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)**FCLITERAL**

Attribute	Description
Name	FCLITERAL
Datatype	String
Description	Indicates Flexcube Literal

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### 2.43.3.SW-DeleteProcessCodeMapping-Res-Full-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Process-Code-Mapping-IO*  
*PROCODTYP*  
*FCLITERAL*  
*Process-Code-Mapping-Full*  
*FCLITERAL*  
*CHANNEL*  
*EXTTXNCODE*  
*DESCRIPTION*  
*PROCODTYP*  
*MAKERID*  
*MAKERDTSTAMP*  
*CHECKERID*  
*CHECKERDTSTAMP*  
*MODNO*  
*AUTHSTAT*  
*RECSTAT*  
*ONCEAUTH*  
*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch Process Code Mapping Deletion Input Only type details

[TOP](#)

## PROCODTYP

Attribute	Description				
Name	PROCODTYP				
Datatype	String				
Description	Indicates Process Code Type				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2</td></tr></tbody></table>	Restrictions	Description	maxLength	2
	Restrictions	Description			
maxLength	2				

[TOP](#)

## FCLITERAL

Attribute	Description				
Name	FCLITERAL				
Datatype	String				
Description	Indicates Flexcube Literal				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## Process-Code-Mapping-Full

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes Switch Process Code Mapping Deletion Full type details

[TOP](#)

## FCLITERAL

Attribute	Description
Name	FCLITERAL

Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
-----------	-------------	--



Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.43.4.SW-DeleteProcessCodeMapping-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Process-Code-Mapping-IO*

*PROCODYTYP*

*FCLITERAL*

*Process-Code-Mapping-PK*

*PROCODYTYP*

*FCLITERAL*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODYTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

[RECSTAT](#)  
[ONCEAUTH](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch Process Code Mapping Deletion Input Only type details

[TOP](#)

## PROCODTYP

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)

## FCLITERAL

Attribute	Description	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## Process-Code-Mapping-PK

Attribute	Description
Name	Process-Code-Mapping-PK
Datatype	
Description	Includes Switch Process Code Mapping Deletion Primary Key type details

[TOP](#)

## PROCODTYP

Attribute	Description
-----------	-------------



Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## FCLITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Process-Code-Mapping-Full

<b>Attribute</b>	<b>Description</b>	
Name	Process-Code-Mapping-Full	
Datatype		
Description	Includes Switch Process Code Mapping Deletion Full type details	

[TOP](#)

## FCLITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

**EXTTXNCODE**

Attribute	Description	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

**DESCRIPTION**

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	

Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

[TOP](#)

## 2.44.DeleteTerminalDetails

DeleteTerminalDetails

### 2.44.1.SW-DeleteTerminalDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Terminal-Details-Full*

*TERMINID*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				



[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Terminal-Details-Full

Attribute	Description
Name	Terminal-Details-Full
Datatype	
Description	Includes Switch Terminal Identification Deletion Full type details

[TOP](#)**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**ORGBRN**

Attribute	Description	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**CASHGL**

Attribute	Description	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**MERCHID**

Attribute	Description	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**TERMADDR**

Attribute	Description	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## CHANNEL

Attribute	Description	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,P

[TOP](#)

## INTELDEP

Attribute	Description	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)



## 2.44.2.SW-DeleteTerminalDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Terminal-Details-IO*

*TERMINID*

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Terminal-Details-IO**

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch Terminal Identification Deletion Input Only type details

[TOP](#)**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

### 2.44.3.SW-DeleteTerminalDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Terminal-Details-IO*

*TERMIN*

*Terminal-Details-Full*

*TERMIN*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID



Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Terminal-Details-IO**

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch Terminal Identification Deletion Input Only type details

[TOP](#)**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**Terminal-Details-Full**

Attribute	Description
Name	Terminal-Details-Full
Datatype	
Description	Includes Switch Terminal Identification Deletion Full type details

[TOP](#)**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**ORGBRN**

Attribute	Description
-----------	-------------

Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CASHGL

<b>Attribute</b>	<b>Description</b>	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MERCHID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TERMADDR

<b>Attribute</b>	<b>Description</b>	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## INTELDEP

<b>Attribute</b>	<b>Description</b>	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH



Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		

Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

#### 2.44.4.SW-DeleteTerminalDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Terminal-Details-IO*

*TERMIN*

*Terminal-Details-PK*

*TERMIN*

*Terminal-Details-Full*

*TERMIN*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

[RECSTAT](#)  
[ONCEAUTH](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	



[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Terminal-Details-IO

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch Terminal Identification Deletion Input Only type details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Terminal-Details-PK

Attribute	Description
Name	Terminal-Details-PK
Datatype	
Description	Includes Switch Terminal Identification Deletion Primary Key type details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Terminal-Details-Full

Attribute	Description
-----------	-------------

Name	Terminal-Details-Full
Datatype	
Description	Includes Switch Terminal Identification Deletion Full type details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ORGBRN

Attribute	Description	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CASHGL

Attribute	Description	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## MERCHID

Attribute	Description	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**TERMADDR**

Attribute	Description	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

**CHANNEL**

Attribute	Description	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,P

**INTELDEP**

Attribute	Description	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.45.DeleteUtilityProvider

DeleteUtilityProvider

### 2.45.1.SW-DeleteUtilityProvider-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ACCOUNT\_NO*

*UTILITY\_PROVIDER\_ID*

*ACCOUNT\_BRANCH*

*DESCRIPTION*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	



Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTIRIPID

Attribute	Description				
Name	MULTIRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## ACCOUNT\_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UTILITY\_PROVIDER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.45.2.SW-DeleteUtilityProvider-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-IO*

*UTILITY\_PROVIDER\_ID*

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP



Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)**Main-IO**

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)**UTILITY\_PROVIDER\_ID**

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

### 2.45.3.SW-DeleteUtilityProvider-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ACCOUNT\_NO*

*UTILITY\_PROVIDER\_ID*

*ACCOUNT\_BRANCH*

*DESCRIPTION*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)**ACCOUNT\_NO**

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**UTILITY\_PROVIDER\_ID**

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)**ACCOUNT\_BRANCH**

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**DESCRIPTION**

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.45.4.SW-DeleteUtilityProvider-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*UTILITY\_PROVIDER\_ID*  
*Main-IO*  
*UTILITY\_PROVIDER\_ID*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	



**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)**UTILITY\_PROVIDER\_ID**

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)**Main-IO**

Attribute	Description	
Name	Main-IO	
Datatype		
Description		

[TOP](#)**UTILITY\_PROVIDER\_ID**

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

[TOP](#)



## 2.46.DeleteUtilityProviderDet

DeleteUtilityProviderDet

### 2.46.1.SW-DeleteUtilityProviderDet-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTIRIPID

Attribute	Description				
Name	MULTIRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## UtilityProvider-Detials-Full

Attribute	Description
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes Switch Utility Provider Details Deletion Full type details

[TOP](#)

## ACCOUNTNO

Attribute	Description
Name	ACCOUNTNO
Datatype	String
Description	Indicates the Account Number.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRTDSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRTDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**xRECORDSTAT**

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UTILITYPROVIDERID**



Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

2.46.2.SW-DeleteUtilityProviderDet-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*UtilityProvider-Details-IO*

*UTILITYPROVIDERID*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**UtilityProvider-Detials-IO**

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes Switch Utility Provider Details Deletion Input Only type details

[TOP](#)**UTILITYPROVIDERID**

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

### 2.46.3.SW-DeleteUtilityProviderDet-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*UtilityProvider-Details-IO*

*UTILITYPROVIDERID*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*



FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------

Name	CHOICE
Datatype	
Description	

[TOP](#)

## UtilityProvider-Detials-IO

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes Switch Utility Provider Details Deletion Input Only type details

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## UtilityProvider-Detials-Full

Attribute	Description
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes Switch Utility Provider Details Deletion Full type details

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**xRECORDSTAT**

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description
Name	ACCOUNTBRN



Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.46.4.SW-DeleteUtilityProviderDet-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*UtilityProvider-Details-IO*

*UTILITYPROVIDERID*

*UtilityProvider-Details-PK*

*UTILITYPROVIDERID*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDTSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

*FCUBS\_ERROR\_RESP*

*ERROR*

[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTIRIPID

Attribute	Description
Name	MULTIRIPID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)



## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## UtilityProvider-Detials-IO

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes Switch Utility Provider Details Deletion Input Only type details

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description				
Name	UTILITYPROVIDERID				
Datatype	String				
Description	Indicates the utility Provider ID.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)

## UtilityProvider-Detials-PK

Attribute	Description
Name	UtilityProvider-Detials-PK
Datatype	
Description	Includes Switch Utility Provider Details Deletion Primary Key type details

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description				
Name	UTILITYPROVIDERID				
Datatype	String				
Description	Indicates the utility Provider ID.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)

## UtilityProvider-Detials-Full

Attribute	Description
Name	UtilityProvider-Detials-Full

Datatype	
Description	Includes Switch Utility Provider Details Deletion Full type details

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKRDTSTMP

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHEKRDSTMP

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## xRECORDSTAT

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)**WARNING**

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.47.CloseCARDTOACCMAPPING

Close Card To Account Mapping

### 2.47.1.SW-CloseCARDTOACCMAPPING-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sub*

[ATM\\_DLY\\_TXN\\_LIMIT](#)  
[POS\\_DLY\\_CNT\\_LIMIT](#)  
[ATM\\_DLY\\_CNT\\_LIMIT](#)  
[POS\\_DLY\\_TXN\\_LIMIT](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION



Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
-----------	-------------

Name	Main-Full
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ACCNUM

Attribute	Description	
Name	ACCNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**CCY\_CODE**

Attribute		Description
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CARD\_TYPE**

Attribute		Description
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	80

**LMT\_APPLICABILITY**

Attribute		Description
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,S

**MAKER**

Attribute		Description
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sub

<b>Attribute</b>	<b>Description</b>	
Name	Sub	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_CNT_LIMIT	

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)



*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*MAKER*

*MAKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

<b>Attribute</b>	<b>Description</b>	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

<b>Attribute</b>	<b>Description</b>
Name	ATM_ACCOUNT_NO

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.47.3.SW-CloseCARDTOACCMAPPING-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sub*

*ATM\_DLY\_TXN\_LIMIT*

*POS\_DLY\_CNT\_LIMIT*

*ATM\_DLY\_CNT\_LIMIT*



[POS\\_DLY\\_TXN\\_LIMIT](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

**ATM\_CARD\_N**

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

**ATM\_ACCOUNT\_NO**

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

**ACCBRN**

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**ACCNUM**

Attribute	Description
Name	ACCNUM
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CARD\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

[TOP](#)

## LMT\_APPLICABILITY

<b>Attribute</b>	<b>Description</b>	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,S

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT



Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sub

Attribute	Description	
Name	Sub	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

Attribute	Description	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

Attribute	Description	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ATM\_DLY\_CNT\_LIMIT**

Attribute		Description
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**POS\_DLY\_TXN\_LIMIT**

Attribute		Description
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.47.4.SW-CloseCARDTOACCMAPPING-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL



Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description				
Name	ATM_CARD_N				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>19</td></tr></tbody></table>	Restrictions	Description	maxLength	19
	Restrictions	Description			
maxLength	19				

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description				
Name	ATM_ACCOUNT_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>28</td></tr></tbody></table>	Restrictions	Description	maxLength	28
	Restrictions	Description			
maxLength	28				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description				
Name	ATM_CARD_N				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>19</td></tr></tbody></table>	Restrictions	Description	maxLength	19
	Restrictions	Description			
maxLength	19				

**ATM\_ACCOUNT\_NO**

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	

Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.48.CloseCardAccount

CloseCardAccount

### 2.48.1.SW-CloseCardAccount-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

BRANCH\_CODE

CUST\_NO

ACTNO

Sttms-Detail

BRANCH\_CODE

REQUEST\_REFERENCE\_NO

CARDNO

CUST\_NO

CARD\_PRODUCT

PRIMARY\_CARD

NAME\_ON\_CARD

OWNER\_ID\_NO

CARD\_ISSUED\_DT

CARD\_EXPIRY\_DT

CARD\_STATUS

RECORD\_STAT

AUTH\_STAT

CARD\_BIN

CUST\_AC\_NO

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

[TOP](#)

## CUST\_AC\_NO

Attribute	Description				
Name	CUST_AC_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## CUSTOMER\_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## DR\_CR\_INDI

<b>Attribute</b>	<b>Description</b>	
Name	DR_CR_INDI	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,C

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

**Sttms-Debit**

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**BRANCH\_CODE**

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3



[TOP](#)**REQUEST\_REFERENCE\_NO**

Attribute	Description	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

**CUST\_AC\_NO**

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## 2.48.2.SW-CloseCardAccount-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Main-IO*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*MAKER*

*MAKERSTAMP*

*MODNO*

### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### **SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------



Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

Attribute	Description
Name	CUST_AC_NO

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### 2.48.3.SW-CloseCardAccount-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

BRANCH\_CODE  
REQUEST\_REFERENCE\_NO  
CARDNO  
CUST\_NO  
CARD\_PRODUCT  
PRIMARY\_CARD  
NAME\_ON\_CARD  
OWNER\_ID\_NO  
CARD\_ISSUED\_DT  
CARD\_EXPIRY\_DT  
CARD\_STATUS  
RECORD\_STAT  
AUTH\_STAT  
CARD\_BIN  
CUST\_AC\_NO

FCUBS\_ERROR\_RESP

ERROR  
ECODE  
EDESC

FCUBS\_WARNING\_RESP

WARNING  
WCODE  
WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

**UBSCOMP**

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME

Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## DR\_CR\_INDI

Attribute	Description	
Name	DR_CR_INDI	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description
-----------	-------------

Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4



[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**OWNER\_ID\_NO**

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)**CARD\_ISSUED\_DT**

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CARD\_EXPIRY\_DT**

Attribute	Description
Name	CARD_EXPIRY_DT

Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.48.4.SW-CloseCardAccount-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*CUST\_AC\_NO*  
*CUSTOMER\_ID*  
*BRANCH\_CODE*  
*Main-IO*  
*BRANCH\_CODE*  
*CUST\_AC\_NO*  
*CUSTOMER\_ID*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Main-PK**

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)**CUST\_AC\_NO**

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER\_ID**

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**Main-IO**

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)**BRANCH\_CODE**

Attribute		Description
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**CUST\_AC\_NO**

Attribute		Description
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER\_ID**

Attribute		Description
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**MAKER**

Attribute		Description
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.49.CloseCardCustomer

CloseCardCustomer

### 2.49.1.SW-CloseCardCustomer-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

REQUEST\_REFERENCE\_NO  
 CARDNO  
 CUST\_NO  
 CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16



**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.49.2.SW-CloseCardCustomer-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-IO*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------



Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description
Name	CUSTOMER_NAME

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.49.3.SW-CloseCardCustomer-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

*REQUEST\_REFERENCE\_NO*

*CARDNO*

*CUST\_NO*

CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sttms-Debit

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Sttms-Detail

Attribute	Description	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String

Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

<b>Attribute</b>	<b>Description</b>	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>
Name	CARD_STATUS

Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.49.4.SW-CloseCardCustomer-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*CUSTOMER\_ID*

*Main-IO*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL



Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description				
Name	CUSTOMER_NAME				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description
Name	ERROR
Datatype	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
-----------	-------------

Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.50.CloseForwaderDetails

CloseForwaderDetails

### 2.50.1.SW-CloseForwaderDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Forwarder-C-Full

Attribute	Description
Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description				
Name	FWD_INS_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td></td></tr></tbody></table>	Restrictions	Description	enumeration	
	Restrictions	Description			
enumeration					

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description				
Name	INTERNATIONAL_FLAG				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description				
Name	TRANSACTION_RESTR				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>A,D</td></tr></tbody></table>	Restrictions	Description	enumeration	A,D
	Restrictions	Description			
enumeration	A,D				

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Forward-Literal-C

<b>Attribute</b>	<b>Description</b>	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

2.50.2.SW-CloseForwaderDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-IO*

*FRWRD\_INST\_ID*

*MAKER*

*MAKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Forwarder-C-IO

<b>Attribute</b>	<b>Description</b>
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>
Name	MAKER

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.50.3.SW-CloseForwaderDetails-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

#### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Forwarder-C-Full

Attribute	Description
-----------	-------------

Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description	
Name	FWD_INS_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Forward-Literal-C

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	



Description	
-------------	--

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.50.4.SW-CloseForwaderDetails-Res-PK-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*CHOICE*

*Forwarder-C-PK*

*FRWRD\_INST\_ID*

*Forwarder-C-IO*

*FRWRD\_INST\_ID*

*MAKER*

*MAKERSTAMP*

*MODNO*

### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

### *FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Forwarder-C-PK

Attribute	Description
Name	Forwarder-C-PK
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## Forwarder-C-IO

Attribute	Description
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute		Description
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute		Description
Name	WCODE	
Datatype	String	
Description		

[TOP](#)**WDESC**

Attribute		Description
Name	WDESC	
Datatype	String	
Description		

[TOP](#)

## 2.51.CreateCARDTOACCMAPPING

Create Card To Account Mapping

### 2.51.1.SW-CreateCARDTOACCMAPPING-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sub*

[ATM\\_DLY\\_TXN\\_LIMIT](#)  
[POS\\_DLY\\_CNT\\_LIMIT](#)  
[ATM\\_DLY\\_CNT\\_LIMIT](#)  
[POS\\_DLY\\_TXN\\_LIMIT](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
-----------	-------------



Name	Main-Full
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ACCNUM

Attribute	Description	
Name	ACCNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CCY\_CODE**

Attribute		Description
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**CARD\_TYPE**

Attribute		Description
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	80

[TOP](#)**LMT\_APPLICABILITY**

Attribute		Description
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,S

[TOP](#)**MAKER**

Attribute		Description
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sub

<b>Attribute</b>	<b>Description</b>	
Name	Sub	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_CNT_LIMIT	

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## 2.51.2.SW-CreateCARDTOACCMAPPING-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*Sub*

*ATM\_DLY\_TXN\_LIMIT*

*POS\_DLY\_CNT\_LIMIT*

*ATM\_DLY\_CNT\_LIMIT*

*POS\_DLY\_TXN\_LIMIT*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION



Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description
Name	ATM_CARD_N
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNUM

<b>Attribute</b>	<b>Description</b>	
Name	ACCNUM	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CARD\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

[TOP](#)

## LMT\_APPLICABILITY

<b>Attribute</b>	<b>Description</b>	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,S

[TOP](#)

## Sub

<b>Attribute</b>	<b>Description</b>	
Name	Sub	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## POS\_DLY\_TXN\_LIMIT

Attribute	Description	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### 2.51.3.SW-CreateCARDTOACCMAPPING-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sub*

*ATM\_DLY\_TXN\_LIMIT*

*POS\_DLY\_CNT\_LIMIT*

*ATM\_DLY\_CNT\_LIMIT*

[POS\\_DLY\\_TXN\\_LIMIT](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)



## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

**ATM\_CARD\_N**

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

**ATM\_ACCOUNT\_NO**

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

**ACCBRN**

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**ACCNUM**

Attribute	Description
Name	ACCNUM
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CARD\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

[TOP](#)

## LMT\_APPLICABILITY

<b>Attribute</b>	<b>Description</b>	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,S

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sub

Attribute	Description	
Name	Sub	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

Attribute	Description	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

Attribute	Description	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0



[TOP](#)**ATM\_DLY\_CNT\_LIMIT**

Attribute		Description
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**POS\_DLY\_TXN\_LIMIT**

Attribute		Description
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.51.4.SW-CreateCARDTOACCMAPPING-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*Sub*

*ATM\_DLY\_TXN\_LIMIT*

*POS\_DLY\_CNT\_LIMIT*

*ATM\_DLY\_CNT\_LIMIT*

*POS\_DLY\_TXN\_LIMIT*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------



Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNUM

<b>Attribute</b>	<b>Description</b>	
Name	ACCNUM	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CARD\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

**LMT\_APPLICABILITY**

Attribute	Description	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,S

**Sub**

Attribute	Description	
Name	Sub	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**ATM\_DLY\_TXN\_LIMIT**

Attribute	Description	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**POS\_DLY\_CNT\_LIMIT**

Attribute	Description	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ATM\_DLY\_CNT\_LIMIT**

Attribute	Description	
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**POS\_DLY\_TXN\_LIMIT**

Attribute	Description	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	

Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.52.CreateCardAccMapping

CreateCardAccMapping

### 2.52.1.SW-CreateCardAccMapping-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

**FCUBS\_HEADER**

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Card-Account-Mapping-Full

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Creation Full type details

[TOP](#)

## ATMCARDNO

Attribute	Description
Name	ATMCARDNO
Datatype	String
Description	Indicates ATM/Debit Card Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## FCCACCB RN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCB RN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCCACCNO**

Attribute	Description	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**FCCACCCY**

Attribute	Description	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

## 2.52.2.SW-CreateCardAccMapping-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Card-Account-Mapping-IO

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Creation Input Only type details

[TOP](#)

## ATMCARDNO

Attribute	Description
Name	ATMCARDNO
Datatype	String
Description	Indicates ATM/Debit Card Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## FCCACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCBRN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCCACCNO**

Attribute	Description	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**FCCACCCY**

Attribute	Description	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

### 2.52.3.SW-CreateCardAccMapping-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*



MAKERID  
 MAKRDATSTMP  
 CHECKERID  
 CHEKRDATSTMP  
 MODNO  
 RECORDSTAT  
 AUTHSTAT  
 ONCEAUTH  
 FCCACCNO  
 FCCACCCY  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Account-Mapping-IO

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Creation Input Only type details

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## FCCACCBRN

Attribute	Description				
Name	FCCACCBRN				
Datatype	String				
Description	Indicates Flexcube Account Branch				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## MAKERID

Attribute	Description				
Name	MAKERID				
Datatype	String				
Description	Indicates Maker ID				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKRDATSTMP

Attribute	Description				
Name	MAKRDATSTMP				
Datatype	String				
Description	Indicates Maker Date Time:				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>7</td></tr></tbody></table>	Restrictions	Description	maxLength	7
	Restrictions	Description			
maxLength	7				

[TOP](#)

## CHECKERID

Attribute	Description				
Name	CHECKERID				
Datatype	String				
Description	Indicates Checker ID				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## CHEKRDATSTMP

Attribute	Description
-----------	-------------

Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>
Name	ONCEAUTH



Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCCACCNO

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCCACCCY

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Card-Account-Mapping-Full

<b>Attribute</b>	<b>Description</b>
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Creation Full type details

[TOP](#)

## ATMCARDNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

**ATMACCNO**

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	28

**FCCACCBRN**

Attribute	Description	
Name	FCCACCBRN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDATSTMP**

Attribute	Description	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

Attribute	Description	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCCACCNO

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCCACCCY

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		

Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.52.4.SW-CreateCardAccMapping-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Account-Mapping-PK*

*ATMCARDNO*

*ATMACCNO*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

*Card-Account-Mapping-Full*

ATMCARDNO  
 ATMACCNO  
 FCCACCBRN  
 MAKERID  
 MAKRDATSTMP  
 CHECKERID  
 CHEKRDATSTMP  
 MODNO  
 RECORDSTAT  
 AUTHSTAT  
 ONCEAUTH  
 FCCACCNO  
 FCCACCCY  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS



**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Account-Mapping-PK

Attribute	Description
Name	Card-Account-Mapping-PK
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Creation Primary Key type details

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description
Name	ATMACCNO
Datatype	String
Description	Indicates Card Account Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

## Card-Account-Mapping-IO

<b>Attribute</b>	<b>Description</b>
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Creation Input Only type details

[TOP](#)

## ATMCARDNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

## FCCACCB RN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCB RN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

Attribute	Description				
Name	MAKERID				
Datatype	String				
Description	Indicates Maker ID				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKRDATSTMP

Attribute	Description				
Name	MAKRDATSTMP				
Datatype	String				
Description	Indicates Maker Date Time:				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>7</td></tr></tbody></table>	Restrictions	Description	maxLength	7
	Restrictions	Description			
maxLength	7				

[TOP](#)

## CHECKERID

Attribute	Description				
Name	CHECKERID				
Datatype	String				
Description	Indicates Checker ID				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## CHEKRDATSTMP

Attribute	Description				
Name	CHEKRDATSTMP				
Datatype	String				
Description	Indicates Checker Date Time:				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>7</td></tr></tbody></table>	Restrictions	Description	maxLength	7
	Restrictions	Description			
maxLength	7				

[TOP](#)

## MODNO

Attribute	Description
-----------	-------------

Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCCACCNO

<b>Attribute</b>	<b>Description</b>
Name	FCCACCNO



Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCCACCCCY

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Card-Account-Mapping-Full

<b>Attribute</b>	<b>Description</b>
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes Switch ATM/Debit Card FCC Account Mapping Creation Full type details

[TOP](#)

## ATMCARDNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

**FCCACCBRN**

Attribute	Description	
Name	FCCACCBRN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDATSTMP**

Attribute	Description	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDATSTMP**

Attribute	Description	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status  Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCCACCNO

Attribute	Description	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCCACCCY

Attribute	Description	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description
Name	ERROR
Datatype	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
-----------	-------------

Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.53.CreateCardAccount

CreateCardAccount

### 2.53.1.SW-CreateCardAccount-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

BRANCH\_CODE

CUST\_NO

ACTNO

Sttms-Detail

BRANCH\_CODE

REQUEST\_REFERENCE\_NO

CARDNO

CUST\_NO

CARD\_PRODUCT

PRIMARY\_CARD

NAME\_ON\_CARD

OWNER\_ID\_NO

CARD\_ISSUED\_DT

CARD\_EXPIRY\_DT

CARD\_STATUS

RECORD\_STAT

AUTH\_STAT

CARD\_BIN

CUST\_AC\_NO

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID



Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

[TOP](#)

## CUST\_AC\_NO

Attribute	Description				
Name	CUST_AC_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## CUSTOMER\_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## DR\_CR\_INDI

<b>Attribute</b>	<b>Description</b>	
Name	DR_CR_INDI	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,C

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

**Sttms-Debit**

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)**REQUEST\_REFERENCE\_NO**

Attribute	Description	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

**CUST\_AC\_NO**

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## 2.53.2.SW-CreateCardAccount-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Main-IO*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

*REQUEST\_REFERENCE\_NO*

*CARDNO*

*CUST\_NO*

*CARD\_PRODUCT*

*PRIMARY\_CARD*

[NAME\\_ON\\_CARD](#)  
[OWNER\\_ID\\_NO](#)  
[CARD\\_ISSUED\\_DT](#)  
[CARD\\_EXPIRY\\_DT](#)  
[CARD\\_STATUS](#)  
[RECORD\\_STAT](#)  
[AUTH\\_STAT](#)  
[CARD\\_BIN](#)  
[CUST\\_AC\\_NO](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request	

**Main-IO**

Attribute	Description
Name	Main-IO
Datatype	
Description	

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**CUST\_AC\_NO**

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**CUSTOMER\_ID**

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

**DR\_CR\_INDI**

Attribute	Description
Name	DR_CR_INDI
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,C

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

[TOP](#)

## Sttms-Debit

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Sttms-Detail

Attribute	Description	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description
Name	BRANCH_CODE

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

<b>Attribute</b>	<b>Description</b>	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



[TOP](#)**CARD\_EXPIRY\_DT**

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CARD\_STATUS**

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**RECORD\_STAT**

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**AUTH\_STAT**

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**CARD\_BIN**

Attribute	Description
Name	CARD_BIN

Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

### 2.53.3.SW-CreateCardAccount-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

BRANCH\_CODE  
REQUEST\_REFERENCE\_NO  
CARDNO  
CUST\_NO  
CARD\_PRODUCT  
PRIMARY\_CARD  
NAME\_ON\_CARD  
OWNER\_ID\_NO  
CARD\_ISSUED\_DT  
CARD\_EXPIRY\_DT  
CARD\_STATUS  
RECORD\_STAT  
AUTH\_STAT  
CARD\_BIN  
CUST\_AC\_NO

FCUBS\_ERROR\_RESP

ERROR  
ECODE  
EDESC

FCUBS\_WARNING\_RESP

WARNING  
WCODE  
WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

**UBSCOMP**

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME



Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## DR\_CR\_INDI

Attribute	Description	
Name	DR_CR_INDI	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description
-----------	-------------

Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**OWNER\_ID\_NO**

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)**CARD\_ISSUED\_DT**

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CARD\_EXPIRY\_DT**

Attribute	Description
Name	CARD_EXPIRY_DT

Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.53.4.SW-CreateCardAccount-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*CUST\_AC\_NO*  
*CUSTOMER\_ID*  
*BRANCH\_CODE*  
*Main-IO*  
*BRANCH\_CODE*  
*CUST\_AC\_NO*  
*CUSTOMER\_ID*  
*DR\_CR\_INDI*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*  
*Sttms-Debit*  
*BRANCH\_CODE*  
*CUST\_NO*  
*ACTNO*  
*Sttms-Detail*  
*BRANCH\_CODE*

REQUEST\_REFERENCE\_NO  
 CARDNO  
 CUST\_NO  
 CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	



[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Main-PK**

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)**CUST\_AC\_NO**

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER\_ID**

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## DR\_CR\_INDI

Attribute	Description	
Name	DR_CR_INDI	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

[TOP](#)

## Sttms-Debit

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

**Sttms-Detail**

Attribute	Description	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**REQUEST\_REFERENCE\_NO**

Attribute	Description	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

**CUST\_NO**

Attribute	Description

Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

<b>Attribute</b>	<b>Description</b>	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## CARD\_BIN

Attribute	Description	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description
Name	ERROR
Datatype	



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
-----------	-------------

Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.54.CreateCardCustomer

CreateCardCustomer

### 2.54.1.SW-CreateCardCustomer-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

REQUEST\_REFERENCE\_NO  
 CARDNO  
 CUST\_NO  
 CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	



Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0



## 2.54.2.SW-CreateCardCustomer-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Main-IO*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

*REQUEST\_REFERENCE\_NO*

*CARDNO*

*CUST\_NO*

*CARD\_PRODUCT*

*PRIMARY\_CARD*

*NAME\_ON\_CARD*

*OWNER\_ID\_NO*

*CARD\_ISSUED\_DT*

*CARD\_EXPIRY\_DT*

*CARD\_STATUS*

[RECORD\\_STAT](#)  
[AUTH\\_STAT](#)  
[CARD\\_BIN](#)  
[CUST\\_AC\\_NO](#)  
[UDFDETAILS](#)  
[FLDNAM](#)  
[FLDVAL](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description				
Name	CUSTOMER_NAME				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## Sttms-Debit

Attribute	Description				
Name	Sttms-Debit				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description	Branch Code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)



## REQUEST\_REFERENCE\_NO

Attribute	Description	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## CARDNO

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

Attribute	Description
-----------	-------------

Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

<b>Attribute</b>	<b>Description</b>	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORD\_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTH\_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## CARD\_BIN

Attribute	Description	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

[TOP](#)

### 2.54.3.SW-CreateCardCustomer-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

##### *Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

##### *Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

##### *Sttms-Detail*

*BRANCH\_CODE*

*REQUEST\_REFERENCE\_NO*

*CARDNO*

*CUST\_NO*

CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sttms-Debit

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Sttms-Detail

Attribute	Description	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String

Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

<b>Attribute</b>	<b>Description</b>	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>
Name	CARD_STATUS



Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

#### 2.54.4.SW-CreateCardCustomer-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*CUSTOMER\_ID*

*Main-IO*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

*REQUEST\_REFERENCE\_NO*

*CARDNO*

*CUST\_NO*

*CARD\_PRODUCT*

*PRIMARY\_CARD*

*NAME\_ON\_CARD*

*OWNER\_ID\_NO*

CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>1</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## Sttms-Debit

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)**ACTNO**

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**Sttms-Detail**

Attribute	Description	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**REQUEST\_REFERENCE\_NO**

Attribute	Description	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**CARDNO**

Attribute	Description
-----------	-------------

Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

<b>Attribute</b>	<b>Description</b>	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTH\_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## CARD\_BIN

Attribute	Description	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## UDFDETAILS

Attribute	Description
Name	UDFDETAILS



Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.55.CreateCardUpload

CreateCardUpload

### 2.55.1.SW-CreateCardUpload-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Card-Upload-Full

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Creation Full type details

[TOP](#)

## FILENAME

Attribute	Description
Name	FILENAME
Datatype	String
Description	Indicates File Name



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

<b>Attribute</b>	<b>Description</b>	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.55.2.SW-CreateCardUpload-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Creation Input Only type details

[TOP](#)

## FILENAME

Attribute	Description
Name	FILENAME
Datatype	String
Description	Indicates File Name

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

<b>Attribute</b>	<b>Description</b>	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

### 2.55.3.SW-CreateCardUpload-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Creation Input Only type details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

Attribute	Description	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Card-Upload-Full

<b>Attribute</b>	<b>Description</b>
Name	Card-Upload-Full
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Creation Full type details

[TOP](#)

## FILENAME

<b>Attribute</b>	<b>Description</b>	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

<b>Attribute</b>	<b>Description</b>	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

Attribute	Description	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	

Description	
-------------	--

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.55.4.SW-CreateCardUpload-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Upload-PK*

*FILENAME*

*FILEPATH*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Card-Upload-Full*

*FILENAME*

FILEPATH  
 STATUS  
 INTRADAYSEQNO  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)



## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Upload-PK

Attribute	Description
Name	Card-Upload-PK
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Creation Primary Key type details

[TOP](#)

## FILENAME

Attribute	Description				
Name	FILENAME				
Datatype	String				
Description	Indicates File Name				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

[TOP](#)

## FILEPATH

Attribute	Description				
Name	FILEPATH				
Datatype	String				
Description	Indicates File Path				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Creation Input Only type details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

Attribute	Description
-----------	-------------

Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Card-Upload-Full

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes Switch Debit Card FCC Account Upload Creation Full type details

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

Attribute	Description
Name	INTRADAYSEQNO

Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)



## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.56.CreateCashDeposit

CreateCashDeposit

### 2.56.1.SW-CreateCashDeposit-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

*ChargeCcy3*

[ChargeAmt3](#)  
[ChargeDesc3](#)  
[ChargeCcy4](#)  
[ChargeAmt4](#)  
[ChargeDesc4](#)  
[TransactionRefno](#)  
[ActualAmt](#)  
[MAKERID](#)  
[MAKERDTSTAMP](#)  
[CHECKERID](#)  
[CHECKERDTSTAMP](#)  
[MODNO](#)  
[AUTHSTAT](#)  
[RECSTAT](#)  
[ONCEAUTH](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

**Cash-Deposit-Full**

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes Switch ATM Cash Deposit Details Creation Full type details

**TransactionAccount**

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**TransactionCurrency**

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**TransactionAmount**

Attribute	Description	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	Attribute	Description
	minOccurs	0



## LocalccyAmt

Attribute	Description				
Name	LocalccyAmt				
Datatype	Number				
Description	Indicates Local Currency Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## TrnsactionDate

Attribute	Description				
Name	TrnsactionDate				
Datatype	Date				
Description	Indicates Transaction Date				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeCcy

Attribute	Description				
Name	ChargeCcy				
Datatype	String				
Description	Indicates Charge Currency				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt

Attribute	Description				
Name	ChargeAmt				
Datatype	Number				
Description	Indicates Charge Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc

Attribute	Description				
Name	ChargeDesc				
Datatype	String				
Description	Indicates Charge Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt2

Attribute	Description	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc2

Attribute	Description	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

### ChargeCcy3

Attribute	Description	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### ChargeAmt3

Attribute	Description	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc3

Attribute	Description	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt

Attribute	Description	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.56.2.SW-CreateCashDeposit-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cash-Deposit-IO*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

*ChargeCcy3*

*ChargeAmt3*

*ChargeDesc3*

*ChargeCcy4*



[ChargeAmt4](#)  
[ChargeDesc4](#)  
[TransactionRefno](#)  
[ActualAmt](#)  
[MAKERID](#)  
[MAKERDTSTAMP](#)  
[CHECKERID](#)  
[CHECKERDTSTAMP](#)  
[MODNO](#)  
[AUTHSTAT](#)  
[RECSTAT](#)  
[ONCEAUTH](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute		Description
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cash-Deposit-IO

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch ATM Cash Deposit Details Creation Input Only type details

[TOP](#)

## TransactionAccount

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## TransactionCurrency

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## TransactionAmount

Attribute	Description	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## LocalccyAmt

Attribute	Description
-----------	-------------

Name	LocalccyAmt	
Datatype	Number	
Description	Indicates Local Currency Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TrnsactionDate

<b>Attribute</b>	<b>Description</b>	
Name	TrnsactionDate	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeCcy

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

Attribute	Description				
Name	ChgCcy1				
Datatype	String				
Description	Indicates Charge Currency 1				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt1

Attribute	Description				
Name	ChargeAmt1				
Datatype	Number				
Description	Indicates Charge Amount 1				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc1

Attribute	Description				
Name	ChargeDesc1				
Datatype	String				
Description	Indicates Charge Description 1				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## ChargeCcy2

Attribute	Description				
Name	ChargeCcy2				
Datatype	String				
Description	Indicates Charge Currency 2				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt2

Attribute	Description
Name	ChargeAmt2
Datatype	Number



Description	Indicates Charge Amount 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy4

Attribute	Description				
Name	ChargeCcy4				
Datatype	String				
Description	Indicates Charge Currency 4				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt4

Attribute	Description				
Name	ChargeAmt4				
Datatype	Number				
Description	Indicates Charge Amount 4				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc4

Attribute	Description				
Name	ChargeDesc4				
Datatype	String				
Description	Indicates Charge Description 4				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## TransactionRefno

Attribute	Description				
Name	TransactionRefno				
Datatype	String				
Description	Indicates Transaction Reference Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## ActualAmt

Attribute	Description
Name	ActualAmt
Datatype	Number

Description	Indicates Actual Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

### 2.56.3.SW-CreateCashDeposit-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cash-Deposit-IO*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

*ChargeCcy3*

*ChargeAmt3*

*ChargeDesc3*

ChargeCcy4  
ChargeAmt4  
ChargeDesc4  
TransactionRefno  
ActualAmt  
MAKERID  
MAKERDTSTAMP  
CHECKERID  
CHECKERDTSTAMP  
MODNO  
AUTHSTAT  
RECSTAT  
ONCEAUTH  
Cash-Deposit-Full  
TransactionAccount  
TransactionCurrency  
TransactionAmount  
LocalccyAmt  
TrnsactionDate  
ChargeCcy  
ChargeAmt  
ChargeDesc  
ChgCcy1  
ChargeAmt1  
ChargeDesc1  
ChargeCcy2  
ChargeAmt2  
ChargeDesc2  
ChargeCcy3  
ChargeAmt3  
ChargeDesc3  
ChargeCcy4  
ChargeAmt4  
ChargeDesc4  
TransactionRefno  
ActualAmt  
MAKERID  
MAKERDTSTAMP  
CHECKERID  
CHECKERDTSTAMP  
MODNO  
AUTHSTAT  
RECSTAT  
ONCEAUTH

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

**Cash-Deposit-IO**

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch ATM Cash Deposit Details Creation Input Only type details

**TransactionAccount**

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**TransactionCurrency**

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**TransactionAmount**

Attribute	Description	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	Attribute	Description
	minOccurs	0

## LocalccyAmt

Attribute	Description				
Name	LocalccyAmt				
Datatype	Number				
Description	Indicates Local Currency Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## TrnsactionDate

Attribute	Description				
Name	TrnsactionDate				
Datatype	Date				
Description	Indicates Transaction Date				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeCcy

Attribute	Description				
Name	ChargeCcy				
Datatype	String				
Description	Indicates Charge Currency				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt

Attribute	Description				
Name	ChargeAmt				
Datatype	Number				
Description	Indicates Charge Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc

Attribute	Description				
Name	ChargeDesc				
Datatype	String				
Description	Indicates Charge Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt2

Attribute	Description	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc2

Attribute	Description	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

### ChargeCcy3

Attribute	Description	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### ChargeAmt3

Attribute	Description	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc3

Attribute	Description	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt



Attribute	Description	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cash-Deposit-Full

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes Switch ATM Cash Deposit Details Creation Full type details

[TOP](#)

## TransactionAccount

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## TransactionCurrency

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## TransactionAmount

Attribute	Description	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LocalccyAmt

Attribute	Description
Name	LocalccyAmt
Datatype	Number
Description	Indicates Local Currency Amount

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TrnsactionDate

<b>Attribute</b>	<b>Description</b>	
Name	TrnsactionDate	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeCcy

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

<b>Attribute</b>	<b>Description</b>
Name	ChgCcy1

Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## ChargeDesc2

Attribute	Description	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

## ChargeCcy3

Attribute	Description	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

## ChargeAmt3

Attribute	Description	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	Attribute	Description
	minOccurs	0

## ChargeDesc3

Attribute	Description	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

## ChargeCcy4

Attribute	Description
Name	ChargeCcy4

Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt

<b>Attribute</b>	<b>Description</b>	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**



Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.56.4.SW-CreateCashDeposit-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cash-Deposit-PK*

*TransactionRefno*

*Cash-Deposit-IO*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

*ChargeCcy3*

ChargeAmt3  
ChargeDesc3  
ChargeCcy4  
ChargeAmt4  
ChargeDesc4  
TransactionRefno  
ActualAmt  
MAKERID  
MAKERDTSTAMP  
CHECKERID  
CHECKERDTSTAMP  
MODNO  
AUTHSTAT  
RECSTAT  
ONCEAUTH  
Cash-Deposit-Full  
TransactionAccount  
TransactionCurrency  
TransactionAmount  
LocalccyAmt  
TrnsactionDate  
ChargeCcy  
ChargeAmt  
ChargeDesc  
ChgCcy1  
ChargeAmt1  
ChargeDesc1  
ChargeCcy2  
ChargeAmt2  
ChargeDesc2  
ChargeCcy3  
ChargeAmt3  
ChargeDesc3  
ChargeCcy4  
ChargeAmt4  
ChargeDesc4  
TransactionRefno  
ActualAmt  
MAKERID  
MAKERDTSTAMP  
CHECKERID  
CHECKERDTSTAMP  
MODNO  
AUTHSTAT

[RECSTAT](#)  
[ONCEAUTH](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID



Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cash-Deposit-PK

Attribute	Description
Name	Cash-Deposit-PK
Datatype	
Description	Includes Switch ATM Cash Deposit Details Creation Primary Key type details

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Cash-Deposit-IO

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes Switch ATM Cash Deposit Details Creation Input Only type details

[TOP](#)

## TransactionAccount

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## TransactionCurrency

Attribute	Description
-----------	-------------

Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## TransactionAmount

<b>Attribute</b>	<b>Description</b>	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LocalccyAmt

<b>Attribute</b>	<b>Description</b>	
Name	LocalccyAmt	
Datatype	Number	
Description	Indicates Local Currency Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TrnsactionDate

<b>Attribute</b>	<b>Description</b>	
Name	TrnsactionDate	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeCcy

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

Attribute	Description				
Name	ChargeAmt				
Datatype	Number				
Description	Indicates Charge Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc

Attribute	Description				
Name	ChargeDesc				
Datatype	String				
Description	Indicates Charge Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## ChgCcy1

Attribute	Description				
Name	ChgCcy1				
Datatype	String				
Description	Indicates Charge Currency 1				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt1

Attribute	Description				
Name	ChargeAmt1				
Datatype	Number				
Description	Indicates Charge Amount 1				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc1

Attribute	Description
Name	ChargeDesc1
Datatype	String
Description	Indicates Charge Description 1

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### ChargeAmt3

Attribute	Description	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	Attribute	Description
	minOccurs	0

### ChargeDesc3

Attribute	Description	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

### ChargeCcy4

Attribute	Description	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

### ChargeAmt4

Attribute	Description	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	Attribute	Description
	minOccurs	0

### ChargeDesc4

Attribute	Description	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt

<b>Attribute</b>	<b>Description</b>	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25



**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cash-Deposit-Full

Attribute	Description	
Name	Cash-Deposit-Full	
Datatype		
Description	Includes Switch ATM Cash Deposit Details Creation Full type details	

[TOP](#)

## TransactionAccount

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## TransactionCurrency

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## TransactionAmount

<b>Attribute</b>	<b>Description</b>	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LocalccyAmt

<b>Attribute</b>	<b>Description</b>	
Name	LocalccyAmt	
Datatype	Number	
Description	Indicates Local Currency Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TrnsactionDate

<b>Attribute</b>	<b>Description</b>	
Name	TrnsactionDate	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeCcy

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy2

Attribute	Description	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ChargeAmt2

Attribute	Description	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ChargeDesc2

Attribute	Description	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## ChargeCcy3

Attribute	Description	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ChargeAmt3

Attribute	Description	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ActualAmt

Attribute	Description	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute		Description
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute		Description
Name	WCODE	
Datatype	String	
Description		

[TOP](#)

## WDESC

Attribute		Description
Name	WDESC	
Datatype	String	
Description		

[TOP](#)

## 2.57.CreateForwaderDetails

CreateForwaderDetails

### 2.57.1.SW-CreateForwaderDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Forwarder-C-Full

Attribute	Description
Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)



## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description				
Name	FWD_INS_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td></td></tr></tbody></table>	Restrictions	Description	enumeration	
	Restrictions	Description			
enumeration					

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description				
Name	INTERNATIONAL_FLAG				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description				
Name	TRANSACTION_RESTR				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>A,D</td></tr></tbody></table>	Restrictions	Description	enumeration	A,D
	Restrictions	Description			
enumeration	A,D				

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Forward-Literal-C

<b>Attribute</b>	<b>Description</b>	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## 2.57.2.SW-CreateForwaderDetails-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Forwarder-C-IO*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*Forward-Literal-C*

*FC\_LITERAL*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------



Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Forwarder-C-IO

Attribute	Description
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description
Name	FWD_INS_DESC

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

<b>Attribute</b>	<b>Description</b>	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

<b>Attribute</b>	<b>Description</b>	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,D

[TOP](#)

## Forward-Literal-C

<b>Attribute</b>	<b>Description</b>	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### 2.57.3.SW-CreateForwarderDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Forwarder-C-Full

Attribute	Description
-----------	-------------

Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description	
Name	FWD_INS_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Forward-Literal-C

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	

Description	
-------------	--

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.57.4.SW-CreateForwarderDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Forwarder-C-PK*

*FRWRD\_INST\_ID*

*Forwarder-C-IO*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*Forward-Literal-C*

*FC\_LITERAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**



Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Forwarder-C-PK

Attribute	Description
Name	Forwarder-C-PK
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## Forwarder-C-IO

Attribute	Description
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description				
Name	FWD_INS_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td></td></tr></tbody></table>	Restrictions	Description	enumeration	
	Restrictions	Description			
enumeration					

**INTERNATIONAL\_FLAG**

Attribute	Description	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

**TRANSACTION\_RESTR**

Attribute	Description	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

**Forward-Literal-C**

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FC\_LITERAL**

Attribute	Description	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**FCUBS\_ERROR\_RESP**

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded



[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.58.CreateMerchDetails

CreateMerchDetails

### 2.58.1.SW-CreateMerchDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Merchant-Details-Full

Attribute	Description
Name	Merchant-Details-Full
Datatype	
Description	Includes Switch -Merchant details Creation details

[TOP](#)

## SUSPAC

Attribute	Description
Name	SUSPAC
Datatype	String
Description	Indicates Suspense Account

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

2.58.2.SW-CreateMerchDetails-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Merchant-Details-IO*

*SUSPAC*

*MAKERID*

*MAKRDTSTMP*

*CHEKRID*

*CHEKRDTSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Description
Attribute	Description
maxOccurs	unbounded
minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Creation-IO details

[TOP](#)

## SUSPAC

Attribute	Description
Name	SUSPAC
Datatype	String
Description	Indicates Suspense Account



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDTSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

### 2.58.3.SW-CreateMerchDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Merchant-Details-IO*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

CHEKRDSTMP  
 MODNO  
 RECORDSTAT  
 AUTHSTAT  
 ONCEAUTH  
 MERCHANTID  
 ACCBRN  
 ACCNO  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Merchant-Details-IO**

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Creation-IO details

[TOP](#)**SUSPAC**

Attribute	Description	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

[TOP](#)**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**MAKRTSTMP**

Attribute	Description
-----------	-------------

Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	

Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Merchant-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Merchant-Details-Full
Datatype	
Description	Includes Switch -Merchant details Creation-Full details

[TOP](#)

## SUSPAC

<b>Attribute</b>	<b>Description</b>	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTSTMP

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## CHEKRID

Attribute	Description	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHEKRDSTMP

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description
Name	RECORDSTAT

Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	

Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	



Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.58.4.SW-CreateMerchDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Merchant-Details-PK*

*MERCHANTID*

*ACCBRN*

*Merchant-Details-IO*

*SUSPAC*

*MAKERID*

*MAKRDTSTMP*

*CHEKRID*

*CHEKRDTSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

*Merchant-Details-Full*

*SUSPAC*

MAKERID  
 MAKRDTSTMP  
 CHEKRID  
 CHEKRDTSTMP  
 MODNO  
 RECORDSTAT  
 AUTHSTAT  
 ONCEAUTH  
 MERCHANTID  
 ACCBRN  
 ACCNO  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Merchant-Details-PK

Attribute	Description
Name	Merchant-Details-PK
Datatype	
Description	Includes Switch -Merchant details Creation-Primary key details

[TOP](#)

## MERCHANTID

Attribute	Description				
Name	MERCHANTID				
Datatype	String				
Description	Indicates Merchant ID				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description	Indicates Account Branch				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes Switch -Merchant details Creation-IO details

[TOP](#)

## SUSPAC

Attribute	Description	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTSTMP

Attribute	Description	
Name	MAKRTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

Attribute	Description
Name	CHEKRID

Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	

Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Merchant-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Merchant-Details-Full
Datatype	
Description	Includes Switch -Merchant details Creation-full details

[TOP](#)

## SUSPAC

<b>Attribute</b>	<b>Description</b>	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

Attribute	Description	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHEKRDSTMP

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## MERCHANTID

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ACCNO

Attribute	Description	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		

Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.59.CreateNetworkDetails

CreateNetworkDetails

### 2.59.1.SW-CreateNetworkDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

[NETWORK\\_ID](#)  
[Issuer-Details](#)  
[ISSBIN](#)  
[ISSDESC](#)  
[NETWORKID](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Network-Details-Full

Attribute	Description
-----------	-------------

Name	Network-Details-Full
Datatype	
Description	Includes Switch -Network details Creation details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**



Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description						
Name	Acquirer_Details						
Datatype							
Description	Includes Acquirer details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ACQBIN

Attribute	Description				
Name	ACQBIN				
Datatype	String				
Description	Indicates Acquirer BIN				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## ACQDESC

Attribute	Description				
Name	ACQDESC				
Datatype	String				
Description	Indicates Acquirer Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## Issuer-Details

Attribute	Description
Name	Issuer-Details

Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## 2.59.2.SW-CreateNetworkDetails-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Network-Details-IO*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

*NETWORK\_ID*

*Issuer-Details*

*ISSBIN*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Network-Details-IO

Attribute	Description
-----------	-------------

Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Creation-IO details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description						
Name	Acquirer_Details						
Datatype							
Description	Includes Acquirer details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ACQBIN

Attribute	Description				
Name	ACQBIN				
Datatype	String				
Description	Indicates Acquirer BIN				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## ACQDESC

Attribute	Description				
Name	ACQDESC				
Datatype	String				
Description	Indicates Acquirer Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## Issuer-Details

Attribute	Description
Name	Issuer-Details

Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

### 2.59.3.SW-CreateNetworkDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Network-Details-IO*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDTSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

*NETWORK\_ID*

*Issuer-Details*

ISSBIN  
 ISSDESC  
 NETWORKID  
*Network-Details-Full*  
 NETWORKID  
 DESCRIPTION  
 ACCOUNTNO  
 ACCOUNTBRN  
 MAKERID  
 MAKRDTSTMP  
 CHECKERID  
 CHEKRDSTMP  
 MODNO  
 RECORDSTAT  
 AUTHSTAT  
 ONCEAUTH  
*Acquirer\_Details*  
 ACQBIN  
 ACQDESC  
 NETWORK\_ID  
*Issuer-Details*  
 ISSBIN  
 ISSDESC  
 NETWORKID  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Network-Details-IO

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Creation-IO details

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECORDSTAT**

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN



Attribute	Description	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## ACQDESC

Attribute	Description	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Issuer-Details

Attribute	Description	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

Attribute	Description
Name	ISSBIN
Datatype	String

Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Network-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Network-Details-Full
Datatype	
Description	Includes Switch -Network details Creation-full details

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	String				
Description	Indicates Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>225</td></tr></tbody></table>	Restrictions	Description	maxLength	225
	Restrictions	Description			
maxLength	225				

[TOP](#)

## ACCOUNTNO

Attribute	Description				
Name	ACCOUNTNO				
Datatype	String				
Description	Indicates Account Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## ACCOUNTBRN

Attribute	Description				
Name	ACCOUNTBRN				
Datatype	String				
Description	Indicates Account Branch				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## MAKERID

Attribute	Description				
Name	MAKERID				
Datatype	String				
Description	Indicates the User id who created the record				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKRTSTMP

Attribute	Description
-----------	-------------

Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	

Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Acquirer\_Details

<b>Attribute</b>	<b>Description</b>	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

<b>Attribute</b>	<b>Description</b>	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQDESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORK\_ID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

**ISSDESC**

Attribute	Description	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

**NETWORKID**

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	

Description	
-------------	--

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.59.4.SW-CreateNetworkDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Network-Details-PK*

*NETWORKID*

*Network-Details-IO*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

*NETWORK\_ID*

*Issuer-Details*

*ISSBIN*

*ISSDESC*

*NETWORKID*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDTSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

*NETWORK\_ID*

*Issuer-Details*

*ISSBIN*

*ISSDESC*

*NETWORKID*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
	Attribute	Description			
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
	Attribute	Description			
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Network-Details-PK

Attribute	Description
Name	Network-Details-PK
Datatype	
Description	Includes Switch -Network details Creation-Primary key details

[TOP](#)

## NETWORKID

Attribute	Description
Name	NETWORKID
Datatype	String
Description	Indicates Network Id

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Network-Details-IO

<b>Attribute</b>	<b>Description</b>
Name	Network-Details-IO
Datatype	
Description	Includes Switch -Network details Creation-IO details

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## ACCOUNTBRN



Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKRDTSTMP

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHEKRDSTMP

Attribute	Description
Name	CHEKRDSTMP

Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	

Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Acquirer\_Details

<b>Attribute</b>	<b>Description</b>	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

<b>Attribute</b>	<b>Description</b>	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQDESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORK\_ID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Network-Details-Full

Attribute	Description
Name	Network-Details-Full
Datatype	
Description	Includes Switch -Network details Creation-full details

[TOP](#)

## NETWORKID

Attribute	Description				
Name	NETWORKID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	String				
Description	Indicates Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>225</td></tr></tbody></table>	Restrictions	Description	maxLength	225
	Restrictions	Description			
maxLength	225				

[TOP](#)

## ACCOUNTNO

Attribute	Description				
Name	ACCOUNTNO				
Datatype	String				
Description	Indicates Account Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## ACCOUNTBRN

Attribute	Description
Name	ACCOUNTBRN
Datatype	String
Description	Indicates Account Branch

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRTSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Acquirer\_Details

<b>Attribute</b>	<b>Description</b>	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

<b>Attribute</b>	<b>Description</b>	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQDESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORK\_ID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)



## Issuer-Details

Attribute	Description						
Name	Issuer-Details						
Datatype							
Description	Includes Issuer details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ISSBIN

Attribute	Description				
Name	ISSBIN				
Datatype	String				
Description	Indicates Issuer BIN				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

## ISSDESC

Attribute	Description				
Name	ISSDESC				
Datatype	String				
Description	Indicates Issuer Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## NETWORKID

Attribute	Description				
Name	NETWORKID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.60.CreateNetworkDetailss

CreateNetworkDetailss

### 2.60.1.SW-CreateNetworkDetailss-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-Full*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Swtms-Acquirer-Details*

*ACQ\_BINN*

*ACQ\_DESC*

*Swtms-Issuer-Details*

ISS\_BINN

ISS\_DESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Swtns-Network-Details-Full

Attribute	Description
-----------	-------------

Name	Swtms-Network-Details-Full
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## ACCOUNT\_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Swtms-Acquirer-Details

Attribute	Description	
Name	Swtms-Acquirer-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

Attribute	Description	
Name	ACQ_BINN	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtms-Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtms-Issuer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ISS_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## 2.60.2.SW-CreateNetworkDetailss-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Swtms-Network-Details-IO*

NETWORK\_ID

ACCOUNT\_NO

DESCRIPTION

*Swtms-Acquirer-Details*

ACQ\_BINN

ACQ\_DESC

*Swtms-Issuer-Details*

ISS\_BINN

ISS\_DESC

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description
-----------	-------------

Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request	

[TOP](#)

## Swtms-Network-Details-IO

Attribute	Description	
Name	Swtms-Network-Details-IO	
Datatype		
Description		

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## ACCOUNT\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtms-Acquirer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtms-Acquirer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

Attribute	Description				
Name	ACQ_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>225</td></tr></tbody></table>	Restrictions	Description	maxLength	225
	Restrictions	Description			
maxLength	225				

[TOP](#)

## Swtns-Issuer-Details

Attribute	Description						
Name	Swtns-Issuer-Details						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ISS\_BINN

Attribute	Description				
Name	ISS_BINN				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

## ISS\_DESC

Attribute	Description				
Name	ISS_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>225</td></tr></tbody></table>	Restrictions	Description	maxLength	225
	Restrictions	Description			
maxLength	225				

[TOP](#)

### 2.60.3.SW-CreateNetworkDetailss-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-Full*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Swtms-Acquirer-Details*

*ACQ\_BINN*

*ACQ\_DESC*

*Swtms-Issuer-Details*

*ISS\_BINN*

*ISS\_DESC*

*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Swtms-Network-Details-Full

Attribute	Description
Name	Swtms-Network-Details-Full
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## ACCOUNT\_NO

Attribute	Description				
Name	ACCOUNT_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>225</td></tr></tbody></table>	Restrictions	Description	maxLength	225
Restrictions	Description				
maxLength	225				

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Swtns-Acquirer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Acquirer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ACQ_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtns-Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Issuer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ISS_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)



## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.60.4.SW-CreateNetworkDetailss-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Swtms-Network-Details-PK*  
*NETWORK\_ID*  
*Swtms-Network-Details-IO*  
*NETWORK\_ID*  
*ACCOUNT\_NO*  
*DESCRIPTION*  
*Swtms-Acquirer-Details*  
*ACQ\_BINN*  
*ACQ\_DESC*  
*Swtms-Issuer-Details*  
*ISS\_BINN*  
*ISS\_DESC*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------

Name	CHOICE
Datatype	
Description	

[TOP](#)

### Swtms-Network-Details-PK

Attribute	Description
Name	Swtms-Network-Details-PK
Datatype	
Description	

[TOP](#)

### NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

### Swtms-Network-Details-IO

Attribute	Description
Name	Swtms-Network-Details-IO
Datatype	
Description	

[TOP](#)

### NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

### ACCOUNT\_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtms-Acquirer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtms-Acquirer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtms-Issuer-Details

Attribute	Description						
Name	Swtms-Issuer-Details						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ISS\_BINN

Attribute	Description				
Name	ISS_BINN				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
	Restrictions	Description			
maxLength	6				

[TOP](#)

## ISS\_DESC

Attribute	Description				
Name	ISS_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>225</td></tr></tbody></table>	Restrictions	Description	maxLength	225
	Restrictions	Description			
maxLength	225				

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

[TOP](#)

## 2.61.CreateProcessCodeMapping

CreateProcessCodeMapping

### 2.61.1.SW-CreateProcessCodeMapping-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

**FCUBS\_HEADER**

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Process-Code-Mapping-Full

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes Switch Process Code Mapping Creation Full type details

[TOP](#)

## FCLITERAL

Attribute	Description
Name	FCLITERAL
Datatype	String

Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN(ADJUSTMENT) : MRA MERCHANDISE RETURN(VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## 2.61.2.SW-CreateProcessCodeMapping-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Process-Code-Mapping-IO*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch Process Code Mapping Creation Input Only type details

[TOP](#)

## FCLITERAL

Attribute	Description
Name	FCLITERAL
Datatype	String

Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN(ADJUSTMENT) : MRA MERCHANDISE RETURN(VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)



### 2.61.3.SW-CreateProcessCodeMapping-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Process-Code-Mapping-IO*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

DESCRIPTION  
 PROCODTYP  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch Process Code Mapping Creation Input Only type details

[TOP](#)

## FCLITERAL

Attribute	Description				
Name	FCLITERAL				
Datatype	String				
Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN(ADJUSTMENT) : MRA MERCHANDISE RETURN(VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>1</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP
Restrictions	Description				
enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP				

[TOP](#)

## CHANNEL

Attribute	Description
-----------	-------------

Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Process-Code-Mapping-Full**

Attribute	Description	
Name	Process-Code-Mapping-Full	
Datatype		
Description	Includes Switch Process Code Mapping Creation Full type details	

**FCLITERAL**

Attribute	Description	
Name	FCLITERAL	

Datatype	String	
Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN(ADJUSTMENT) : MRA MERCHANDISE RETURN(VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		

Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.61.4.SW-CreateProcessCodeMapping-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Process-Code-Mapping-PK*

*PROCODTYP*

*FCLITERAL*

*Process-Code-Mapping-IO*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Process-Code-Mapping-Full*



FCLITERAL  
 CHANNEL  
 EXTTXNCODE  
 DESCRIPTION  
 PROCODTYP  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Process-Code-Mapping-PK

Attribute	Description
Name	Process-Code-Mapping-PK
Datatype	
Description	Includes Switch Process Code Mapping Creation Primary Key type details

[TOP](#)

## PROCODTYP

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)

## FCLITERAL

Attribute	Description
Name	FCLITERAL
Datatype	String
Description	Indicates Flexcube Literal

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Process-Code-Mapping-IO

<b>Attribute</b>	<b>Description</b>
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Switch Process Code Mapping Creation Input Only type details

[TOP](#)

## FCLITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## PROCODTYP

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description
Name	CHECKERID



Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
	Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Process-Code-Mapping-Full

<b>Attribute</b>	<b>Description</b>
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes Switch Process Code Mapping Creation Full type details

[TOP](#)

## FCLITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

Attribute	Description	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## PROCODTYP

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description	Includes FCUBS Warning Response details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.62.CreateTerminalDetails

CreateTerminalDetails

### 2.62.1.SW-CreateTerminalDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Terminal-Details-Full*

*TERMID*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				



[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)**Terminal-Details-Full**

Attribute	Description
Name	Terminal-Details-Full
Datatype	
Description	Includes Switch Terminal Identification Creation Full type details

[TOP](#)**TERMID**

Attribute		Description
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**ORGBRN**

Attribute		Description
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**CASHGL**

Attribute		Description
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**MERCHID**

Attribute		Description
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**TERMADDR**

Attribute	Description	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## CHANNEL

Attribute	Description	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,P

[TOP](#)

## INTELDEP

Attribute	Description	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)



## 2.62.2.SW-CreateTerminalDetails-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Terminal-Details-IO*

*TERMID*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Terminal-Details-IO

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch Terminal Identification Creation Input Only type details

[TOP](#)

## TERMID

Attribute	Description
Name	TERMID
Datatype	String
Description	Indicates the Terminal ID.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ORGBRN

<b>Attribute</b>	<b>Description</b>	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CASHGL

<b>Attribute</b>	<b>Description</b>	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MERCHID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TERMADDR

<b>Attribute</b>	<b>Description</b>	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## INTELDEP

<b>Attribute</b>	<b>Description</b>	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25



**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description
Name	RECSTAT

Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## 2.62.3.SW-CreateTerminalDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Terminal-Details-IO*

*TERMID*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Terminal-Details-Full*

*TERMID*

ORGBRN  
 CASHGL  
 MERCHID  
 TERMADDR  
 CHANNEL  
 INTELDEP  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	



[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Terminal-Details-IO

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch Terminal Identification Creation Input Only type details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ORGBRN

Attribute	Description
Name	ORGBRN
Datatype	String
Description	Indicates the Originating Branch.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CASHGL

<b>Attribute</b>	<b>Description</b>	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MERCHID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TERMADDR

<b>Attribute</b>	<b>Description</b>	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## INTELDEP

<b>Attribute</b>	<b>Description</b>	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates the Once Auth.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Terminal-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Terminal-Details-Full
Datatype	
Description	Includes Switch Terminal Identification Creation Full type details

[TOP](#)

## TERMID

<b>Attribute</b>	<b>Description</b>	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ORGBRN

<b>Attribute</b>	<b>Description</b>	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CASHGL

<b>Attribute</b>	<b>Description</b>	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

**MERCHID**

Attribute		Description
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**TERMADDR**

Attribute		Description
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

**CHANNEL**

Attribute		Description
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,P

**INTELDEP**

Attribute		Description
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0



[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes FCUBS Warning Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.62.4.SW-CreateTerminalDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Terminal-Details-PK*

*TERMID*

*Terminal-Details-IO*

*TERMID*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Terminal-Details-Full*

*TERMID*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

**UBSCOMP**

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME



Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Terminal-Details-PK

Attribute	Description
Name	Terminal-Details-PK
Datatype	
Description	Includes Switch Terminal Identification Creation Primary Key type details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Terminal-Details-IO

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes Switch Terminal Identification Creation Input Only type details

[TOP](#)**TERMID**

Attribute		Description
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**ORGBRN**

Attribute		Description
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**CASHGL**

Attribute		Description
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**MERCHID**

Attribute		Description
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**TERMADDR**

Attribute	Description	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## CHANNEL

Attribute	Description	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,P

[TOP](#)

## INTELDEP

Attribute	Description	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Terminal-Details-Full

Attribute	Description
Name	Terminal-Details-Full
Datatype	
Description	Includes Switch Terminal Identification Creation Full type details

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ORGBRN

Attribute	Description
Name	ORGBRN

Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CASHGL

<b>Attribute</b>	<b>Description</b>	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MERCHID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TERMADDR

<b>Attribute</b>	<b>Description</b>	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## INTELDEP

<b>Attribute</b>	<b>Description</b>	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH



Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		

Description	Includes FCUBS Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.63.AuthCardAccMapping

Card Account Mapping

### 2.63.1.SW-AuthCardAccMapping-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

**FCUBS\_HEADER**

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Card-Account-Mapping-Full

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes the Card Account Mapping Full Details.

[TOP](#)

## ATMCARDNO

Attribute	Description
Name	ATMCARDNO
Datatype	String
Description	Indicates ATM/Debit Card Number



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## FCCACCB RN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCB RN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCCACCNO**

Attribute	Description	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**FCCACCCY**

Attribute	Description	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

## 2.63.2.SW-AuthCardAccMapping-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Card-Account-Mapping-IO*

ATMCARDNO

ATMACCNO

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0



[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Card-Account-Mapping-IO**

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes the Card Account Mapping IO Details.

[TOP](#)**ATMCARDNO**

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**ATMACCNO**

Attribute	Description
Name	ATMACCNO
Datatype	String
Description	Indicates Card Account Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.63.3.SW-AuthCardAccMapping-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*MODNO*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*FCCACCNO*

*FCCACCCY*

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	



[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Account-Mapping-IO

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes the Card Account Mapping IO details.

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	18

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

## Card-Account-Mapping-Full

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes the Card Account Mapping Full details.

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

## ATMACCNO

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	18

## FCCACCB RN

Attribute	Description	
Name	FCCACCB RN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

## MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCCACCNO

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCCACCCCY

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.63.4.SW-AuthCardAccMapping-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Account-Mapping-PK*

*ATMCARDNO*

*ATMACCNO*

*Card-Account-Mapping-IO*

*ATMCARDNO*

*ATMACCNO*

*MODNO*

*Card-Account-Mapping-Full*

*ATMCARDNO*

*ATMACCNO*

*FCCACCBRN*

*MAKERID*

*MAKRDATSTMP*

*CHECKERID*

*CHEKRDATSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

ONCEAUTH  
 FCCACCNO  
 FCCACCCCY  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



[TOP](#)**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Account-Mapping-PK

Attribute	Description
Name	Card-Account-Mapping-PK
Datatype	
Description	Includes the Card Account Mapping Primary Key details.

[TOP](#)

## ATMCARDNO

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATMACCNO

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	18

[TOP](#)

## Card-Account-Mapping-IO

Attribute	Description
Name	Card-Account-Mapping-IO
Datatype	
Description	Includes the Card Account Mapping IO details.

**ATMCARDNO**

Attribute	Description	
Name	ATMCARDNO	
Datatype	String	
Description	Indicates ATM/Debit Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

**ATMACCNO**

Attribute	Description	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	18

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Card-Account-Mapping-Full**

Attribute	Description
Name	Card-Account-Mapping-Full
Datatype	
Description	Includes the Card Account Mapping Full details.

**ATMCARDNO**

Attribute	Description
Name	ATMCARDNO
Datatype	String
Description	Indicates ATM/Debit Card Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## ATMACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ATMACCNO	
Datatype	String	
Description	Indicates Card Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	18

[TOP](#)

## FCCACCB RN

<b>Attribute</b>	<b>Description</b>	
Name	FCCACCB RN	
Datatype	String	
Description	Indicates Flexcube Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDATSTMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDATSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDATSTMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1



**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCCACCNO**

Attribute	Description	
Name	FCCACCNO	
Datatype	String	
Description	Indicates Flexcube Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**FCCACCCY**

Attribute	Description	
Name	FCCACCCY	
Datatype	String	
Description	Indicates Flexcube Account Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
-----------	-------------	--

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.64.AuthCardUpload

Authorize Card Upload

### 2.64.1.SW-AuthCardUpload-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Card-Upload-Full

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes the Card Upload Full Details.

[TOP](#)

## FILENAME

Attribute	Description
Name	FILENAME
Datatype	String
Description	Indicates File Name

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

<b>Attribute</b>	<b>Description</b>	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.64.2.SW-AuthCardUpload-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Card-Upload-IO

FILENAME

FILEPATH

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes the Card Upload IO details.

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description
Name	FILEPATH
Datatype	String
Description	Indicates File Path

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.64.3.SW-AuthCardUpload-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*MODNO*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes the Card Upload IO details.

[TOP](#)

## FILENAME

Attribute	Description				
Name	FILENAME				
Datatype	String				
Description	Indicates File Name				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

[TOP](#)

## FILEPATH

Attribute	Description				
Name	FILEPATH				
Datatype	String				
Description	Indicates File Path				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description	Indicates Modification Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				

**Card-Upload-Full**

Attribute	Description
Name	Card-Upload-Full
Datatype	
Description	Includes the Card Upload Full details.

**FILENAME**

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**FILEPATH**

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**INTRADAYSEQNO**

Attribute	Description
Name	INTRADAYSEQNO
Datatype	String
Description	Indicates Intraday Sequence Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.64.4.SW-AuthCardUpload-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Card-Upload-PK*

*FILENAME*

*FILEPATH*

*Card-Upload-IO*

*FILENAME*

*FILEPATH*

*MODNO*

*Card-Upload-Full*

*FILENAME*

*FILEPATH*

*STATUS*

*INTRADAYSEQNO*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*



[RECSTAT](#)  
[ONCEAUTH](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Card-Upload-PK

Attribute	Description
Name	Card-Upload-PK
Datatype	
Description	Includes the Card Upload Primary Key Details.

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## Card-Upload-IO

Attribute	Description
Name	Card-Upload-IO
Datatype	
Description	Includes the Card Upload IO Details.

[TOP](#)

## FILENAME

Attribute	Description
-----------	-------------

Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

<b>Attribute</b>	<b>Description</b>	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Card-Upload-Full

<b>Attribute</b>	<b>Description</b>	
Name	Card-Upload-Full	
Datatype		
Description	Includes the Card Upload Full Details.	

[TOP](#)

## FILENAME

<b>Attribute</b>	<b>Description</b>	
Name	FILENAME	
Datatype	String	
Description	Indicates File Name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FILEPATH

Attribute	Description	
Name	FILEPATH	
Datatype	String	
Description	Indicates File Path	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## INTRADAYSEQNO

Attribute	Description	
Name	INTRADAYSEQNO	
Datatype	String	
Description	Indicates Intraday Sequence Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP



Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

[TOP](#)

## 2.65.AuthCashDeposit

Authorize Cash Deposit

### 2.65.1.SW-AuthCashDeposit-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

*ChargeCcy3*

[ChargeAmt3](#)  
[ChargeDesc3](#)  
[ChargeCcy4](#)  
[ChargeAmt4](#)  
[ChargeDesc4](#)  
[TransactionRefno](#)  
[ActualAmt](#)  
[MAKERID](#)  
[MAKERDTSTAMP](#)  
[CHECKERID](#)  
[CHECKERDTSTAMP](#)  
[MODNO](#)  
[AUTHSTAT](#)  
[RECSTAT](#)  
[ONCEAUTH](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

**Cash-Deposit-Full**

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes the Cah Deposit Full Details.

**TransactionAccount**

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**TransactionCurrency**

Attribute	Description	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**TransactionAmount**

Attribute	Description	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	Attribute	Description
	minOccurs	0

## LocalccyAmt

Attribute	Description				
Name	LocalccyAmt				
Datatype	Number				
Description	Indicates Local Currency Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## TrnsactionDate

Attribute	Description				
Name	TrnsactionDate				
Datatype	Date				
Description	Indicates Transaction Date				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeCcy

Attribute	Description				
Name	ChargeCcy				
Datatype	String				
Description	Indicates Charge Currency				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ChargeAmt

Attribute	Description				
Name	ChargeAmt				
Datatype	Number				
Description	Indicates Charge Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeDesc

Attribute	Description				
Name	ChargeDesc				
Datatype	String				
Description	Indicates Charge Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt2

Attribute	Description	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc2

Attribute	Description	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

### ChargeCcy3

Attribute	Description	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### ChargeAmt3

Attribute	Description	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### ChargeDesc3

Attribute	Description	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt

Attribute	Description	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.65.2.SW-AuthCashDeposit-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Cash-Deposit-IO

TransactionRefno

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Cash-Deposit-IO**

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes the Cash Deposit IO details.

[TOP](#)**TransactionRefno**

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**MODNO**

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.65.3.SW-AuthCashDeposit-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cash-Deposit-IO*

*TransactionRefno*

*MODNO*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

*ChargeAmt2*

*ChargeDesc2*

ChargeCcy3  
 ChargeAmt3  
 ChargeDesc3  
 ChargeCcy4  
 ChargeAmt4  
 ChargeDesc4  
 TransactionRefno  
 ActualAmt  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME

Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cash-Deposit-IO

Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes the Cash Deposit IO details.

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cash-Deposit-Full

<b>Attribute</b>	<b>Description</b>
Name	Cash-Deposit-Full
Datatype	
Description	Includes the Cash Deposit Full details.

[TOP](#)

## TransactionAccount

<b>Attribute</b>	<b>Description</b>	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## TransactionCurrency

<b>Attribute</b>	<b>Description</b>	
Name	TransactionCurrency	
Datatype	String	
Description	Indicates Transaction Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## TransactionAmount

<b>Attribute</b>	<b>Description</b>	
Name	TransactionAmount	
Datatype	Number	
Description	Indicates Transaction Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LocalccyAmt

<b>Attribute</b>	<b>Description</b>
Name	LocalccyAmt

Datatype	Number	
Description	Indicates Local Currency Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TrnsactionDate

<b>Attribute</b>	<b>Description</b>	
Name	TrnsactionDate	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeCcy

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

Attribute	Description	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ChargeAmt1

Attribute	Description	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ChargeDesc1

Attribute	Description	
Name	ChargeDesc1	
Datatype	String	
Description	Indicates Charge Description 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## ChargeCcy2

Attribute	Description	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ChargeAmt2

Attribute	Description	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy4

Attribute	Description	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ChargeAmt4

Attribute	Description	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ChargeDesc4

Attribute	Description	
Name	ChargeDesc4	
Datatype	String	
Description	Indicates Charge Description 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ActualAmt

Attribute	Description	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description
-----------	-------------



Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.65.4.SW-AuthCashDeposit-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cash-Deposit-PK*

*TransactionRefno*

*Cash-Deposit-IO*

*TransactionRefno*

*MODNO*

*Cash-Deposit-Full*

*TransactionAccount*

*TransactionCurrency*

*TransactionAmount*

*LocalccyAmt*

*TrnsactionDate*

*ChargeCcy*

*ChargeAmt*

*ChargeDesc*

*ChgCcy1*

*ChargeAmt1*

*ChargeDesc1*

*ChargeCcy2*

ChargeAmt2  
 ChargeDesc2  
 ChargeCcy3  
 ChargeAmt3  
 ChargeDesc3  
 ChargeCcy4  
 ChargeAmt4  
 ChargeDesc4  
 TransactionRefno  
 ActualAmt  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cash-Deposit-PK

Attribute	Description
Name	Cash-Deposit-PK
Datatype	
Description	Includes the Cash Deposit Primary key Details.

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Cash-Deposit-IO



Attribute	Description
Name	Cash-Deposit-IO
Datatype	
Description	Includes the Cash Deposit IO Details.

[TOP](#)

## TransactionRefno

Attribute	Description	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## Cash-Deposit-Full

Attribute	Description
Name	Cash-Deposit-Full
Datatype	
Description	Includes the Cash Deposit Full Details.

[TOP](#)

## TransactionAccount

Attribute	Description	
Name	TransactionAccount	
Datatype	String	
Description	Indicates Transaction Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## TransactionCurrency

Attribute	Description				
Name	TransactionCurrency				
Datatype	String				
Description	Indicates Transaction Currency				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## TransactionAmount

Attribute	Description				
Name	TransactionAmount				
Datatype	Number				
Description	Indicates Transaction Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## LocalccyAmt

Attribute	Description				
Name	LocalccyAmt				
Datatype	Number				
Description	Indicates Local Currency Amount				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## TrnsactionDate

Attribute	Description				
Name	TrnsactionDate				
Datatype	Date				
Description	Indicates Transaction Date				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ChargeCcy

Attribute	Description				
Name	ChargeCcy				
Datatype	String				
Description	Indicates Charge Currency				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc	
Datatype	String	
Description	Indicates Charge Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChgCcy1

<b>Attribute</b>	<b>Description</b>	
Name	ChgCcy1	
Datatype	String	
Description	Indicates Charge Currency 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt1

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt1	
Datatype	Number	
Description	Indicates Charge Amount 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc1

<b>Attribute</b>	<b>Description</b>
Name	ChargeDesc1

Datatype	String	
Description	Indicates Charge Description 1	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy2	
Datatype	String	
Description	Indicates Charge Currency 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ChargeAmt2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt2	
Datatype	Number	
Description	Indicates Charge Amount 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ChargeDesc2

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc2	
Datatype	String	
Description	Indicates Charge Description 2	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## ChargeCcy3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy3	
Datatype	String	
Description	Indicates Charge Currency 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt3	
Datatype	Number	
Description	Indicates Charge Amount 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc3

<b>Attribute</b>	<b>Description</b>	
Name	ChargeDesc3	
Datatype	String	
Description	Indicates Charge Description 3	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

### ChargeCcy4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeCcy4	
Datatype	String	
Description	Indicates Charge Currency 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### ChargeAmt4

<b>Attribute</b>	<b>Description</b>	
Name	ChargeAmt4	
Datatype	Number	
Description	Indicates Charge Amount 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### ChargeDesc4

<b>Attribute</b>	<b>Description</b>
Name	ChargeDesc4

Datatype	String	
Description	Indicates Charge Description 4	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## TransactionRefno

<b>Attribute</b>	<b>Description</b>	
Name	TransactionRefno	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ActualAmt

<b>Attribute</b>	<b>Description</b>	
Name	ActualAmt	
Datatype	Number	
Description	Indicates Actual Amount	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
-----------	-------------



Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.66.AuthMerchDetails

AuthMerchDetails

### 2.66.1.SW-AuthMerchDetails-Req-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER

Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Description
Attribute	Description
maxOccurs	unbounded
minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Merchant-Details-Full

Attribute	Description
Name	Merchant-Details-Full
Datatype	
Description	Includes the Merchant Full Details.

[TOP](#)

## SUSPAC

Attribute	Description
Name	SUSPAC
Datatype	String
Description	Indicates Suspense Account

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDTSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHEKRID

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## 2.66.2.SW-AuthMerchDetails-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Merchant-Details-IO

MERCHANTID

ACCBRN

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Merchant-Details-IO**

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes the Merchant IO Details.

[TOP](#)**MERCHANTID**

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**ACCBRN**

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Account Branch



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.66.3.SW-AuthMerchDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Merchant-Details-IO*

*MERCHANTID*

*ACCBRN*

*MODNO*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

*ACCBRN*

*ACCNO*

*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes the Merchant IO details.

[TOP](#)

## MERCHANTID

Attribute	Description				
Name	MERCHANTID				
Datatype	String				
Description	Indicates Merchant ID				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description	Indicates Account Branch				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description	Indicates Modification Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				



**Merchant-Details-Full**

Attribute	Description
Name	Merchant-Details-Full
Datatype	
Description	Includes the Merchant Full details.

**SUSPAC**

Attribute	Description	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRTSTMP**

Attribute	Description	
Name	MAKRTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHEKRID**

Attribute	Description
Name	CHEKRID
Datatype	String
Description	Indicates the User id who authorized the record

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MERCHANTID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ACCNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.66.4.SW-AuthMerchDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Merchant-Details-PK*

*MERCHANTID*

*ACCBRN*

*Merchant-Details-IO*

*MERCHANTID*

*ACCBRN*

*MODNO*

*Merchant-Details-Full*

*SUSPAC*

*MAKERID*

*MAKRDSTMP*

*CHEKRID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*MERCHANTID*

[ACCBRN](#)  
[ACCNO](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
maxLength	12						
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
length	3						
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Merchant-Details-PK

Attribute	Description
Name	Merchant-Details-PK
Datatype	
Description	Includes the Merchant Primary Key Details.

[TOP](#)

## MERCHANTID

Attribute	Description	
Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## Merchant-Details-IO

Attribute	Description
Name	Merchant-Details-IO
Datatype	
Description	Includes the Merchant IO Details.

[TOP](#)

## MERCHANTID

Attribute	Description
-----------	-------------

Name	MERCHANTID	
Datatype	String	
Description	Indicates Merchant ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ACCBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Merchant-Details-Full

<b>Attribute</b>	<b>Description</b>	
Name	Merchant-Details-Full	
Datatype		
Description	Includes the Merchant Full Details.	

[TOP](#)

## SUSPAC

<b>Attribute</b>	<b>Description</b>	
Name	SUSPAC	
Datatype	String	
Description	Indicates Suspense Account	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4000

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHEKRID**

Attribute	Description	
Name	CHEKRID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDTSTMP**

Attribute	Description	
Name	CHEKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## MERCHANTID

Attribute	Description				
Name	MERCHANTID				
Datatype	String				
Description	Indicates Merchant ID				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description	Indicates Account Branch				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## ACCNO

Attribute	Description				
Name	ACCNO				
Datatype	String				
Description	Indicates Account Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description	Includes the FCUBS Error Response Details.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ERROR

Attribute	Description
Name	ERROR



Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.67.AuthNetworkDetails

AuthNetworkDetails

### 2.67.1.SW-AuthNetworkDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDTSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

[NETWORK\\_ID](#)  
[Issuer-Details](#)  
[ISSBIN](#)  
[ISSDESC](#)  
[NETWORKID](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Network-Details-Full

Attribute	Description
-----------	-------------



Name	Network-Details-Full
Datatype	
Description	Includes the Network Full Details.

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description						
Name	Acquirer_Details						
Datatype							
Description	Includes Acquirer details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ACQBIN

Attribute	Description				
Name	ACQBIN				
Datatype	String				
Description	Indicates Acquirer BIN				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## ACQDESC

Attribute	Description				
Name	ACQDESC				
Datatype	String				
Description	Indicates Acquirer Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## Issuer-Detials

Attribute	Description
Name	Issuer-Detials

Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## 2.67.2.SW-AuthNetworkDetails-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Network-Details-IO

NETWORKID

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)



## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Network-Details-IO**

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes the network IO details.

[TOP](#)**NETWORKID**

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**MODNO**

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.67.3.SW-AuthNetworkDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Network-Details-IO*

*NETWORKID*

*MODNO*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

ACQDESC  
 NETWORK\_ID  
 Issuer-Details  
 ISSBIN  
 ISSDESC  
 NETWORKID  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Network-Details-IO

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes the Network IO details.

[TOP](#)

## NETWORKID

Attribute	Description				
Name	NETWORKID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description	Indicates Modification Number				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

[TOP](#)

## Network-Details-Full

Attribute	Description
Name	Network-Details-Full

Datatype	
Description	Includes the Network Full details.

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Acquirer\_Details

Attribute	Description						
Name	Acquirer_Details						
Datatype							
Description	Includes Acquirer details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ACQBIN

Attribute	Description				
Name	ACQBIN				
Datatype	String				
Description	Indicates Acquirer BIN				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## ACQDESC

Attribute	Description				
Name	ACQDESC				
Datatype	String				
Description	Indicates Acquirer Description				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>40</td></tr></tbody></table>	Restrictions	Description	maxLength	40
	Restrictions	Description			
maxLength	40				

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description	Indicates Network Id				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## Issuer-Details

Attribute	Description
Name	Issuer-Details

Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0



[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.67.4.SW-AuthNetworkDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Network-Details-PK*

*NETWORKID*

*Network-Details-IO*

*NETWORKID*

*MODNO*

*Network-Details-Full*

*NETWORKID*

*DESCRIPTION*

*ACCOUNTNO*

*ACCOUNTBRN*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*RECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*Acquirer\_Details*

*ACQBIN*

*ACQDESC*

*NETWORK\_ID*

*Issuer-Details*

*ISSBIN*

*ISSDESC*

*NETWORKID*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		



[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Network-Details-PK

Attribute	Description
Name	Network-Details-PK
Datatype	
Description	Includes the Network primary Key details.

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Network-Details-IO

Attribute	Description
Name	Network-Details-IO
Datatype	
Description	Includes the Network IO details.

[TOP](#)

## NETWORKID

Attribute	Description
Name	NETWORKID
Datatype	String
Description	Indicates Network Id

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Network-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Network-Details-Full
Datatype	
Description	Includes the Network Full details.

[TOP](#)

## NETWORKID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates Account Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKRDTSTMP

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## RECORDSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	

Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Acquirer\_Details

<b>Attribute</b>	<b>Description</b>	
Name	Acquirer_Details	
Datatype		
Description	Includes Acquirer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQBIN

<b>Attribute</b>	<b>Description</b>	
Name	ACQBIN	
Datatype	String	
Description	Indicates Acquirer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQDESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQDESC	
Datatype	String	
Description	Indicates Acquirer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORK\_ID

<b>Attribute</b>	<b>Description</b>	
Name	NETWORK_ID	
Datatype	String	
Description	Indicates Network Id	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Issuer-Details	
Datatype		
Description	Includes Issuer details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISSBIN

<b>Attribute</b>	<b>Description</b>	
Name	ISSBIN	
Datatype	String	
Description	Indicates Issuer BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISSDESC

<b>Attribute</b>	<b>Description</b>	
Name	ISSDESC	
Datatype	String	
Description	Indicates Issuer Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	40

[TOP](#)

## NETWORKID

Attribute	Description	
Name	NETWORKID	
Datatype	String	
Description	Indicates Network Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.68.AuthProcessCodeMapping

AuthProcessCodeMapping

### 2.68.1.SW-AuthProcessCodeMapping-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

**FCUBS\_HEADER**

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Process-Code-Mapping-Full

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes the Process Code Mapping Full Details.

[TOP](#)

## FCLITERAL

Attribute	Description
Name	FCLITERAL
Datatype	String

Description	Indicates Flexcube Literal AD-HOC STATEMENT : ADS BALANCE ENQUIRY : BEQ CASH BACK : CAB CASH WITHDRAWAL CASH ADVANCE : CAW CASH DEPOSIT : CDP CHEQUE BOOK REQUEST : CHB FUND TRANSFER : FTR MERCHANDISE RETURN(ADJUSTMENT) : MRA MERCHANDISE RETURN(VOID) : MRE MINI STATEMENT : MST NORMAL PURCHASE : NPA PURCHASE ADJUSTMENT : PAD	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	ADS,BEQ,BIQ,CAB,CAW,CDP,CHB,FTR,MRA,MRE,MST,NPA,PAD,PAY,SUP

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**



Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## 2.68.2.SW-AuthProcessCodeMapping-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTIRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Process-Code-Mapping-IO*

PROCODTYP

FCLITERAL

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Process-Code-Mapping-IO**

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes the Process Code Mapping IO Details.

[TOP](#)**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)**FCLITERAL**

Attribute	Description
Name	FCLITERAL
Datatype	String
Description	Indicates Flexcube Literal



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.68.3.SW-AuthProcessCodeMapping-Res-Full-MSG.xsd

FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS\_BODY

CHOICE

*Process-Code-Mapping-IO*

PROCODTYP

FCLITERAL

MODNO

*Process-Code-Mapping-Full*

FCLITERAL

CHANNEL

EXTTXNCODE

DESCRIPTION

PROCODTYP

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes the Process Code Mapping IO details.

[TOP](#)

## PROCODTYP

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)

## FCLITERAL

Attribute	Description	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22



## Process-Code-Mapping-Full

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes the Process Code Mapping Full details.

## FCLITERAL

Attribute	Description	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

## CHANNEL

Attribute	Description	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,P

## EXTTXNCODE

Attribute	Description	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

## DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Description

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute		Description
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute		Description
Name	WCODE	
Datatype	String	
Description		

[TOP](#)

## WDESC

Attribute		Description
Name	WDESC	
Datatype	String	
Description		

[TOP](#)

## 2.68.4.SW-AuthProcessCodeMapping-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Process-Code-Mapping-PK*

*PROCODTYP*

*FCLITERAL*

*Process-Code-Mapping-IO*

*PROCODTYP*

*FCLITERAL*

*MODNO*

*Process-Code-Mapping-Full*

*FCLITERAL*

*CHANNEL*

*EXTTXNCODE*

*DESCRIPTION*

*PROCODTYP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute		Description
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute		Description
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute		Description
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute		Description
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**SERVICE**

Attribute		Description
Name	SERVICE	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Process-Code-Mapping-PK

Attribute	Description
Name	Process-Code-Mapping-PK
Datatype	
Description	Includes Process Code Mapping primary key details.

[TOP](#)

## PROCODTYP

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

[TOP](#)

## FCLITERAL

Attribute	Description	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## Process-Code-Mapping-IO

Attribute	Description
Name	Process-Code-Mapping-IO
Datatype	
Description	Includes Process Code Mapping IO details.

**PROCODTYP**

Attribute	Description	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

**FCLITERAL**

Attribute	Description	
Name	FCLITERAL	
Datatype	String	
Description	Indicates Flexcube Literal	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Process-Code-Mapping-Full**

Attribute	Description
Name	Process-Code-Mapping-Full
Datatype	
Description	Includes Process Code Mapping Full details.

**FCLITERAL**

Attribute	Description
Name	FCLITERAL
Datatype	String
Description	Indicates Flexcube Literal

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates Channel	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## EXTTXNCODE

<b>Attribute</b>	<b>Description</b>	
Name	EXTTXNCODE	
Datatype	String	
Description	Indicates External Transaction Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Description	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## PROCODTYP

<b>Attribute</b>	<b>Description</b>	
Name	PROCODTYP	
Datatype	String	
Description	Indicates Process Code Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1



[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description
-----------	-------------

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.69.AuthTerminalDetails

AuthTerminalDetails

### 2.69.1.SW-AuthTerminalDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Terminal-Details-Full*

*TERMID*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)**Terminal-Details-Full**

Attribute	Description
Name	Terminal-Details-Full
Datatype	
Description	Includes the Terminal Full details.



[TOP](#)**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**ORGBRN**

Attribute	Description	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**CASHGL**

Attribute	Description	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**MERCHID**

Attribute	Description	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**TERMADDR**

Attribute	Description	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## CHANNEL

Attribute	Description	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,P

[TOP](#)

## INTELDEP

Attribute	Description	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## 2.69.2.SW-AuthTerminalDetails-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Terminal-Details-IO*

TERMINID

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**Terminal-Details-IO**

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes the Terminal IO details.

[TOP](#)**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**MODNO**

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modifictaion number.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.69.3.SW-AuthTerminalDetails-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Terminal-Details-IO*

*TERMIN*

*MODNO*

*Terminal-Details-Full*

*TERMIN*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

[ONCEAUTH](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)  
**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------



Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Terminal-Details-IO

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes the Terminal IO Details.

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modifictaion number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## Terminal-Details-Full

Attribute	Description
Name	Terminal-Details-Full
Datatype	
Description	Includes the Terminal Full Details.

[TOP](#)

## TERMID

Attribute	Description
-----------	-------------

Name	TERMID	
Datatype	String	
Description	Indicates the terminal ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ORGBRN

<b>Attribute</b>	<b>Description</b>	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CASHGL

<b>Attribute</b>	<b>Description</b>	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MERCHID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TERMADDR

<b>Attribute</b>	<b>Description</b>	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## INTELDEP

<b>Attribute</b>	<b>Description</b>	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modifictaion number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	

Description	
-------------	--

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.69.4.SW-AuthTerminalDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Terminal-Details-PK*

*TERMID*

*Terminal-Details-IO*

*TERMID*

*MODNO*

*Terminal-Details-Full*

*TERMID*

*ORGBRN*

*CASHGL*

*MERCHID*

*TERMADDR*

*CHANNEL*

*INTELDEP*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*



AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Terminal-Details-PK

Attribute	Description
Name	Terminal-Details-PK
Datatype	
Description	Includes the Terminal Details Primary key details.

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Terminal-Details-IO

Attribute	Description
Name	Terminal-Details-IO
Datatype	
Description	Includes the Terminal Details IO details.

[TOP](#)

## TERMID

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modifictaion number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)**Terminal-Details-Full**

Attribute	Description	
Name	Terminal-Details-Full	
Datatype		
Description	Includes the Terminal Details Full details.	

[TOP](#)**TERMID**

Attribute	Description	
Name	TERMID	
Datatype	String	
Description	Indicates the Terminal ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**ORGBRN**

Attribute	Description	
Name	ORGBRN	
Datatype	String	
Description	Indicates the Originating Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**CASHGL**

Attribute	Description	
Name	CASHGL	
Datatype	String	
Description	Indicates the Cash GL.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MERCHID

<b>Attribute</b>	<b>Description</b>	
Name	MERCHID	
Datatype	String	
Description	Indicates the Merchant ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TERMADDR

<b>Attribute</b>	<b>Description</b>	
Name	TERMADDR	
Datatype	String	
Description	Indicates the Terminal Address.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## CHANNEL

<b>Attribute</b>	<b>Description</b>	
Name	CHANNEL	
Datatype	String	
Description	Indicates the Channel.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	A,P

[TOP](#)

## INTELDEP

<b>Attribute</b>	<b>Description</b>	
Name	INTELDEP	
Datatype	String	
Description	Indicates the Intelligent Deposits.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modifictaion number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.70.AuthUtilityProviderDet

AuthUtilityProviderDet

### 2.70.1.SW-AuthUtilityProviderDet-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	

Description	Includes the FCUBS Header Details.
-------------	------------------------------------

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTIRIPID

Attribute	Description				
Name	MULTIRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## UtilityProvider-Detials-Full

Attribute	Description
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes the Utility Provider Full Details.

[TOP](#)

## ACCOUNTNO

Attribute	Description
Name	ACCOUNTNO
Datatype	String
Description	Indicates the Account Number.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRTDSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHEKRTDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	CHEKRTDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**xRECORDSTAT**

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UTILITYPROVIDERID**

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNTBRN

Attribute	Description	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## 2.70.2.SW-AuthUtilityProviderDet-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*UtilityProvider-Details-IO*

UTILITYPROVIDERID

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)



## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)**UtilityProvider-Detials-IO**

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes the Utility Provider IO details.

[TOP](#)**UTILITYPROVIDERID**

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)**MODNO**

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## 2.70.3.SW-AuthUtilityProviderDet-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*UtilityProvider-Details-IO*

*UTILITYPROVIDERID*

*MODNO*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDTSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	CHOICE
Datatype	
Description	

[TOP](#)

## UtilityProvider-Detials-IO

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes the Utility Provider IO details.

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the Utility Provider ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## UtilityProvider-Detials-Full

Attribute	Description
Name	UtilityProvider-Detials-Full
Datatype	
Description	Includes the Utility Provider Full details.

[TOP](#)

## ACCOUNTNO

Attribute	Description	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	Restrictions	Description
	maxLength	20

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKRDTSTMP**

Attribute	Description	
Name	MAKRDTSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHEKRDSTMP**

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## xRECORDSTAT

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description
Name	UTILITYPROVIDERID

Datatype	String	
Description	Indicates the Utility Provider ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.70.4.SW-AuthUtilityProviderDet-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*UtilityProvider-Details-PK*

*UTILITYPROVIDERID*

*UtilityProvider-Details-IO*

*UTILITYPROVIDERID*

*MODNO*

*UtilityProvider-Details-Full*

*ACCOUNTNO*

*MAKERID*

*MAKRDSTMP*

*CHECKERID*

*CHEKRDSTMP*

*MODNO*

*xRECORDSTAT*

*AUTHSTAT*

*ONCEAUTH*

*UTILITYPROVIDERID*

*ACCOUNTBRN*

*FCUBS\_ERROR\_RESP*



[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## UtilityProvider-Detials-PK

Attribute	Description
Name	UtilityProvider-Detials-PK
Datatype	
Description	Includes the Utility Provider primary key Details.

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description				
Name	UTILITYPROVIDERID				
Datatype	String				
Description	Indicates the utility Provider ID.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)

## UtilityProvider-Detials-IO

Attribute	Description
Name	UtilityProvider-Detials-IO
Datatype	
Description	Includes the Utility Provider IO Details.

[TOP](#)

## UTILITYPROVIDERID

Attribute	Description				
Name	UTILITYPROVIDERID				
Datatype	String				
Description	Indicates the utility Provider ID.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## UtilityProvider-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	UtilityProvider-Details-Full
Datatype	
Description	Includes the Utility Provider Full Details.

[TOP](#)

## ACCOUNTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTNO	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKRDSTMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKRDSTMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	7

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHEKRDSTMP

Attribute	Description	
Name	CHEKRDSTMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## xRECORDSTAT

Attribute	Description	
Name	xRECORDSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description
Name	AUTHSTAT



Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UTILITYPROVIDERID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITYPROVIDERID	
Datatype	String	
Description	Indicates the utility Provider ID.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNTBRN

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNTBRN	
Datatype	String	
Description	Indicates the Account Branch.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response Details.	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes the FCUBS Warning Response Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.71.AuthorizeCARDTOACCMAPPING

Authorize Card To Account Mapping

### 2.71.1.SW-AuthorizeCARDTOACCMAPPING-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sub*

[ATM\\_DLY\\_TXN\\_LIMIT](#)  
[POS\\_DLY\\_CNT\\_LIMIT](#)  
[ATM\\_DLY\\_CNT\\_LIMIT](#)  
[POS\\_DLY\\_TXN\\_LIMIT](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
-----------	-------------

Name	Main-Full
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

[TOP](#)

## ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ACCNUM

Attribute	Description	
Name	ACCNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

**CCY\_CODE**

Attribute		Description
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CARD\_TYPE**

Attribute		Description
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	80

**LMT\_APPLICABILITY**

Attribute		Description
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,S

**MAKER**

Attribute		Description
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sub

<b>Attribute</b>	<b>Description</b>	
Name	Sub	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ATM\_DLY\_CNT\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	ATM_DLY_CNT_LIMIT	

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## POS\_DLY\_TXN\_LIMIT

<b>Attribute</b>	<b>Description</b>	
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	



Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description
Name	ATM_ACCOUNT_NO

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	28

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.71.3.SW-AuthorizeCARDTOACCMAPPING-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

##### *Main-Full*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*ACCBRN*

*ACCNUM*

*CCY\_CODE*

*CARD\_TYPE*

*LMT\_APPLICABILITY*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

##### *Sub*

*ATM\_DLY\_TXN\_LIMIT*

*POS\_DLY\_CNT\_LIMIT*

*ATM\_DLY\_CNT\_LIMIT*

[POS\\_DLY\\_TXN\\_LIMIT](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

**ATM\_CARD\_N**

Attribute	Description	
Name	ATM_CARD_N	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	19

**ATM\_ACCOUNT\_NO**

Attribute	Description	
Name	ATM_ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	28

**ACCBRN**

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**ACCNUM**

Attribute	Description
Name	ACCNUM
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CARD\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CARD_TYPE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	80

[TOP](#)

## LMT\_APPLICABILITY

<b>Attribute</b>	<b>Description</b>	
Name	LMT_APPLICABILITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,S

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sub

Attribute	Description	
Name	Sub	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ATM\_DLY\_TXN\_LIMIT

Attribute	Description	
Name	ATM_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## POS\_DLY\_CNT\_LIMIT

Attribute	Description	
Name	POS_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ATM\_DLY\_CNT\_LIMIT**

Attribute		Description
Name	ATM_DLY_CNT_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**POS\_DLY\_TXN\_LIMIT**

Attribute		Description
Name	POS_DLY_TXN_LIMIT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**



Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.71.4.SW-AuthorizeCARDTOACCMAPPING-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*Main-IO*

*ATM\_CARD\_N*

*ATM\_ACCOUNT\_NO*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description				
Name	ATM_CARD_N				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>19</td></tr></tbody></table>	Restrictions	Description	maxLength	19
Restrictions	Description				
maxLength	19				

[TOP](#)

## ATM\_ACCOUNT\_NO

Attribute	Description				
Name	ATM_ACCOUNT_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>28</td></tr></tbody></table>	Restrictions	Description	maxLength	28
Restrictions	Description				
maxLength	28				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## ATM\_CARD\_N

Attribute	Description				
Name	ATM_CARD_N				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>19</td></tr></tbody></table>	Restrictions	Description	maxLength	19
Restrictions	Description				
maxLength	19				



**ATM\_ACCOUNT\_NO**

Attribute		Description	
Name	ATM_ACCOUNT_NO		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	1	
Restrictions	Restrictions		Description
	maxLength	28	

**CHECKER**

Attribute		Description	
Name	CHECKER		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

**CHECKERSTAMP**

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attributes	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

**MODNO**

Attribute		Description	
Name	MODNO		
Datatype	Number		
Description			
Attributes	Attribute		Description
	minOccurs	0	

**FCUBS\_ERROR\_RESP**

Attribute		Description	
Name	FCUBS_ERROR_RESP		

Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.72.AuthorizeCardAccount

AuthorizeCardAccount

### 2.72.1.SW-AuthorizeCardAccount-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

BRANCH\_CODE

CUST\_NO

ACTNO

Sttms-Detail

BRANCH\_CODE

REQUEST\_REFERENCE\_NO

CARDNO

CUST\_NO

CARD\_PRODUCT

PRIMARY\_CARD

NAME\_ON\_CARD

OWNER\_ID\_NO

CARD\_ISSUED\_DT

CARD\_EXPIRY\_DT

CARD\_STATUS

RECORD\_STAT

AUTH\_STAT

CARD\_BIN

CUST\_AC\_NO

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------



Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

[TOP](#)

## CUST\_AC\_NO

Attribute	Description				
Name	CUST_AC_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## CUSTOMER\_ID

Attribute	Description
Name	CUSTOMER_ID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## DR\_CR\_INDI

<b>Attribute</b>	<b>Description</b>	
Name	DR_CR_INDI	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	D,C

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

**Sttms-Debit**

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**BRANCH\_CODE**

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

Attribute	Description	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## CARDNO

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

**CUST\_AC\_NO**

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## 2.72.2.SW-AuthorizeCardAccount-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Main-IO*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### **SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>
Name	CUST_AC_NO



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### 2.72.3.SW-AuthorizeCardAccount-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*DR\_CR\_INDI*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

BRANCH\_CODE  
REQUEST\_REFERENCE\_NO  
CARDNO  
CUST\_NO  
CARD\_PRODUCT  
PRIMARY\_CARD  
NAME\_ON\_CARD  
OWNER\_ID\_NO  
CARD\_ISSUED\_DT  
CARD\_EXPIRY\_DT  
CARD\_STATUS  
RECORD\_STAT  
AUTH\_STAT  
CARD\_BIN  
CUST\_AC\_NO

FCUBS\_ERROR\_RESP

ERROR  
ECODE  
EDESC

FCUBS\_WARNING\_RESP

WARNING  
WCODE  
WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

**UBSCOMP**

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME



Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## DR\_CR\_INDI

Attribute	Description				
Name	DR_CR_INDI				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>D,C</td></tr></tbody></table>	Restrictions	Description	enumeration	D,C
	Restrictions	Description			
enumeration	D,C				

[TOP](#)

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

[TOP](#)

## CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description
-----------	-------------

Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**OWNER\_ID\_NO**

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)**CARD\_ISSUED\_DT**

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**CARD\_EXPIRY\_DT**

Attribute	Description
Name	CARD_EXPIRY_DT

Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

Attribute	Description	
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.72.4.SW-AuthorizeCardAccount-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*BRANCH\_CODE*

*Main-IO*

*BRANCH\_CODE*

*CUST\_AC\_NO*

*CUSTOMER\_ID*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	



[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## CUST\_AC\_NO

Attribute	Description				
Name	CUST_AC_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)**BRANCH\_CODE**

Attribute		Description
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**CUST\_AC\_NO**

Attribute		Description
Name	CUST_AC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER\_ID**

Attribute		Description
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CHECKER**

Attribute		Description
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.73.AuthorizeCardCustomer

AuthorizeCardCustomer

### 2.73.1.SW-AuthorizeCardCustomer-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

REQUEST\_REFERENCE\_NO  
 CARDNO  
 CUST\_NO  
 CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Sttms-Debit

Attribute	Description	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## ACTNO

<b>Attribute</b>	<b>Description</b>	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## Sttms-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

<b>Attribute</b>	<b>Description</b>	
Name	REQUEST_REFERENCE_NO	
Datatype	String	
Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)**CARDNO**

Attribute	Description	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	19

[TOP](#)**CUST\_NO**

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CARD\_PRODUCT**

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)**PRIMARY\_CARD**

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)**NAME\_ON\_CARD**

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

Attribute	Description	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CARD\_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description	Card Status	
Attributes	Attribute	Description
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

## 2.73.2.SW-AuthorizeCardCustomer-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Main-IO

CUSTOMER\_ID

CUSTOMER\_NAME

CHECKER

CHECKERSTAMP

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description
Name	CUSTOMER_NAME



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.73.3.SW-AuthorizeCardCustomer-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-Full*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Sttms-Debit*

*BRANCH\_CODE*

*CUST\_NO*

*ACTNO*

*Sttms-Detail*

*BRANCH\_CODE*

*REQUEST\_REFERENCE\_NO*

*CARDNO*

*CUST\_NO*

CARD\_PRODUCT  
 PRIMARY\_CARD  
 NAME\_ON\_CARD  
 OWNER\_ID\_NO  
 CARD\_ISSUED\_DT  
 CARD\_EXPIRY\_DT  
 CARD\_STATUS  
 RECORD\_STAT  
 AUTH\_STAT  
 CARD\_BIN  
 CUST\_AC\_NO  
 UDFDETAILS  
 FLDNAM  
 FLDVAL  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></tbody></table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
	Restrictions	Description			
enumeration	SUCCESS,WARNING,FAILURE				

[TOP](#)

## PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
	Restrictions	Description					
	maxLength	128					
pattern	[a-zA-Z_0-9=+/*]						

[TOP](#)

## ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)**CUSTOMER\_ID**

Attribute	Description	
Name	CUSTOMER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)**CUSTOMER\_NAME**

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)**MAKER**

Attribute	Description
-----------	-------------



Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Sttms-Debit

<b>Attribute</b>	<b>Description</b>	
Name	Sttms-Debit	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CUST\_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description	Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## Sttms-Detail

Attribute	Description	
Name	Sttms-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## REQUEST\_REFERENCE\_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String

Description	Request Reference Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## CARDNO

<b>Attribute</b>	<b>Description</b>	
Name	CARDNO	
Datatype	String	
Description	Card Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	19

[TOP](#)

## CUST\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_NO	
Datatype	String	
Description	Customer No	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## CARD\_PRODUCT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_PRODUCT	
Datatype	String	
Description	Card products	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## PRIMARY\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	PRIMARY_CARD	
Datatype	String	
Description	Primary Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## NAME\_ON\_CARD

<b>Attribute</b>	<b>Description</b>	
Name	NAME_ON_CARD	
Datatype	String	
Description	Name On Card	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## OWNER\_ID\_NO

<b>Attribute</b>	<b>Description</b>	
Name	OWNER_ID_NO	
Datatype	String	
Description	Owner Id number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150

[TOP](#)

## CARD\_ISSUED\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Card Issued Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_EXPIRY\_DT

<b>Attribute</b>	<b>Description</b>	
Name	CARD_EXPIRY_DT	
Datatype	Date	
Description	Card Expiry Date	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CARD\_STATUS

<b>Attribute</b>	<b>Description</b>
Name	CARD_STATUS

Datatype	String	
Description	Card Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECORD\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_STAT	
Datatype	String	
Description	Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTH\_STAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTH_STAT	
Datatype	String	
Description	Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## CARD\_BIN

<b>Attribute</b>	<b>Description</b>	
Name	CARD_BIN	
Datatype	String	
Description	Card BIN	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CUST\_AC\_NO

<b>Attribute</b>	<b>Description</b>	
Name	CUST_AC_NO	
Datatype	String	
Description	Account No	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	150
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE



Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.73.4.SW-AuthorizeCardCustomer-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*CUSTOMER\_ID*

*Main-IO*

*CUSTOMER\_ID*

*CUSTOMER\_NAME*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## CUSTOMER\_ID

Attribute	Description				
Name	CUSTOMER_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description				
Name	CUSTOMER_NAME				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				



**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description
Name	ERROR
Datatype	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
-----------	-------------

Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.74.AuthorizeForwaderDetails

AuthorizeForwaderDetails

### 2.74.1.SW-AuthorizeForwaderDetails-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL



Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Forwarder-C-Full

Attribute	Description
Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description				
Name	FRWRD_INST_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>11</td></tr></tbody></table>	Restrictions	Description	maxLength	11
	Restrictions	Description			
maxLength	11				

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description				
Name	FWD_INS_DESC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td></td></tr></tbody></table>	Restrictions	Description	enumeration	
	Restrictions	Description			
enumeration					

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description				
Name	INTERNATIONAL_FLAG				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description				
Name	TRANSACTION_RESTR				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>A,D</td></tr></tbody></table>	Restrictions	Description	enumeration	A,D
	Restrictions	Description			
enumeration	A,D				

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Forward-Literal-C

<b>Attribute</b>	<b>Description</b>	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## 2.74.2.SW-AuthorizeForwaderDetails-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Forwarder-C-IO

FRWRD\_INST\_ID

CHECKER

CHECKERSTAMP

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Forwarder-C-IO

<b>Attribute</b>	<b>Description</b>
Name	Forwarder-C-IO
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

<b>Attribute</b>	<b>Description</b>	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>
Name	CHECKER

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.74.3.SW-AuthorizeForwaderDetails-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

##### *Forwarder-C-Full*

*FRWRD\_INST\_ID*

*FWD\_INS\_DESC*

*INTERNATIONAL\_FLAG*

*TRANSACTION\_RESTR*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

##### *Forward-Literal-C*

*DESCRIPTION*

*FC\_LITERAL*

#### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Forwarder-C-Full

Attribute	Description
-----------	-------------

Name	Forwarder-C-Full
Datatype	
Description	

[TOP](#)

## FRWRD\_INST\_ID

Attribute	Description	
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)

## FWD\_INS\_DESC

Attribute	Description	
Name	FWD_INS_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	

[TOP](#)

## INTERNATIONAL\_FLAG

Attribute	Description	
Name	INTERNATIONAL_FLAG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

## TRANSACTION\_RESTR

Attribute	Description	
Name	TRANSACTION_RESTR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,D

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Forward-Literal-C

Attribute	Description	
Name	Forward-Literal-C	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## FC\_LITERAL

<b>Attribute</b>	<b>Description</b>	
Name	FC_LITERAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	

Description	
-------------	--

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.74.4.SW-AuthorizeForwaderDetails-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Forwarder-C-PK*  
*FRWRD\_INST\_ID*  
*Forwarder-C-IO*  
*FRWRD\_INST\_ID*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER



Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Forwarder-C-PK

Attribute	Description
Name	Forwarder-C-PK
Datatype	
Description	

[TOP](#)**FRWRD\_INST\_ID**

Attribute		Description
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)**Forwarder-C-IO**

Attribute		Description
Name	Forwarder-C-IO	
Datatype		
Description		

[TOP](#)**FRWRD\_INST\_ID**

Attribute		Description
Name	FRWRD_INST_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	11

[TOP](#)**CHECKER**

Attribute		Description
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**CHECKERSTAMP**

Attribute		Description
Name	CHECKERSTAMP	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attributes	Attribute		Description
	maxOccurs	unbounded	
	minOccurs	0	

[TOP](#)

## WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attributes	Attribute		Description
	maxOccurs	unbounded	

[TOP](#)

## WCODE

Attribute		Description	
Name	WCODE		
Datatype	String		
Description			

[TOP](#)

## WDESC

Attribute		Description	
Name	WDESC		
Datatype	String		
Description			

[TOP](#)



## 2.75.AuthorizeNetworkDetailss

AuthorizeNetworkDetailss

### 2.75.1.SW-AuthorizeNetworkDetailss-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-Full*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Swtms-Acquirer-Details*

*ACQ\_BINN*

*ACQ\_DESC*

*Swtms-Issuer-Details*

ISS\_BINN  
ISS\_DESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Swtns-Network-Details-Full

Attribute	Description
-----------	-------------

Name	Swtms-Network-Details-Full
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## ACCOUNT\_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MAKER**

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**CHECKER**

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERSTAMP**

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MODNO**



Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Swtms-Acquirer-Details

Attribute	Description	
Name	Swtms-Acquirer-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

Attribute	Description	
Name	ACQ_BINN	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtns-Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Issuer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ISS_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

2.75.2.SW-AuthorizeNetworkDetailss-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-IO*

*NETWORK\_ID*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Swtms-Network-Details-IO

Attribute	Description
Name	Swtms-Network-Details-IO
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CHECKER

Attribute	Description
Name	CHECKER



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.75.3.SW-AuthorizeNetworkDetailss-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Swtms-Network-Details-Full*

*NETWORK\_ID*

*ACCOUNT\_NO*

*DESCRIPTION*

*ACCOUNT\_BRANCH*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Swtms-Acquirer-Details*

*ACQ\_BINN*

*ACQ\_DESC*

*Swtms-Issuer-Details*

*ISS\_BINN*

*ISS\_DESC*

*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

## Swtms-Network-Details-Full

Attribute	Description
Name	Swtms-Network-Details-Full
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description				
Name	NETWORK_ID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## ACCOUNT\_NO

Attribute	Description				
Name	ACCOUNT_NO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## DESCRIPTION

Attribute	Description				
Name	DESCRIPTION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>225</td></tr></tbody></table>	Restrictions	Description	maxLength	225
Restrictions	Description				
maxLength	225				

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description
Name	ACCOUNT_BRANCH
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Swtns-Acquirer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Acquirer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACQ\_BINN

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ACQ_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	11

[TOP](#)

## ACQ\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ACQ_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	225

[TOP](#)

## Swtns-Issuer-Details

<b>Attribute</b>	<b>Description</b>	
Name	Swtns-Issuer-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ISS\_BINN

<b>Attribute</b>	<b>Description</b>	
Name	ISS_BINN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	6

[TOP](#)

## ISS\_DESC

<b>Attribute</b>	<b>Description</b>	
Name	ISS_DESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	225

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.75.4.SW-AuthorizeNetworkDetailss-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Swtms-Network-Details-PK*  
*NETWORK\_ID*  
*Swtms-Network-Details-IO*  
*NETWORK\_ID*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Swtms-Network-Details-PK

Attribute	Description
Name	Swtms-Network-Details-PK
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## Swtms-Network-Details-IO

Attribute	Description
Name	Swtms-Network-Details-IO
Datatype	
Description	

[TOP](#)

## NETWORK\_ID

Attribute	Description	
Name	NETWORK_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.76.AuthorizeUtilityProvider

AuthorizeUtilityProvider

### 2.76.1.SW-AuthorizeUtilityProvider-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*ACCOUNT\_NO*

*UTILITY\_PROVIDER\_ID*

*ACCOUNT\_BRANCH*

*DESCRIPTION*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	



Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTIRIPID

Attribute	Description				
Name	MULTIRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## ACCOUNT\_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## UTILITY\_PROVIDER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## ACCOUNT\_BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

2.76.2.SW-AuthorizeUtilityProvider-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-IO*

*UTILITY\_PROVIDER\_ID*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	

[TOP](#)

## UTILITY\_PROVIDER\_ID

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKER

Attribute	Description
Name	CHECKER

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

### 2.76.3.SW-AuthorizeUtilityProvider-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Main-Full*

*ACCOUNT\_NO*

*UTILITY\_PROVIDER\_ID*

*ACCOUNT\_BRANCH*

*DESCRIPTION*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

#### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

#### *FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	

[TOP](#)

## ACCOUNT\_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## UTILITY\_PROVIDER\_ID

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## ACCOUNT\_BRANCH

Attribute	Description	
Name	ACCOUNT_BRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.76.4.SW-AuthorizeUtilityProvider-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Main-PK*  
*UTILITY\_PROVIDER\_ID*  
*Main-IO*  
*UTILITY\_PROVIDER\_ID*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*  
**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	

[TOP](#)

## UTILITY\_PROVIDER\_ID

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## Main-IO

Attribute	Description	
Name	Main-IO	
Datatype		
Description		

[TOP](#)

## UTILITY\_PROVIDER\_ID

Attribute	Description	
Name	UTILITY_PROVIDER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		



[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



Switch Gateway Service  
[August] [2014]

Oracle Financial Services software Limited  
Oracle Park  
Off Western Express Highway  
Goregaon (East)  
Mumbai, Maharashtra 400 063  
India

Worldwide Inquiries:  
Phone: +91 22 6718 3000  
Fax: +91 22 6718 3001  
[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)

Copyright © [2007], [2014], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

**U.S. GOVERNMENT END USERS:** Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.