

OFS Governance, Risk, and Compliance

Cloning Reference Guide

Release 8.x

October 2019



OFS Cloning Reference Guide

Copyright © 2019 Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are “commercial computer software” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

For information on third party licenses, click [here](#).

Document Control

Version Number	Revision Date	Changes Log
1.0	Created: October 2015	Captured steps to setup an OFSAA instance "Clone" for the 8.0.x.0.0 release.

Table of Contents

1	Preface	5
1.1	Background	5
1.2	Assumptions	5
1.3	Audience	5
1.4	Conventions and Acronyms	5
2	Setting Up an OFSAA Instance “Clone” for 8.0.x Release	6
2.1	Prerequisites	6
2.1.1	<i>General</i>	6
2.1.2	<i>Source System</i>	6
2.1.3	<i>Target System</i>	6
2.2	Cloning Steps	7
2.2.1	<i>Export the complete Configuration and Atomic Schema from Source Environment</i>	7
2.2.2	<i>Restore the complete exported dumps into the Target Environment database</i>	7
2.2.3	<i>In case of restoring the complete exported dumps in to the Target Environment database with different database user names (schemas)</i>	8
2.2.4	<i>Provide select grants on sys.V_\$parameter view to Config and Atomic Schemas of Target Environment database</i>	8
2.2.5	<i>Login to Config Schema of Target Environment database</i>	9
2.2.6	<i>Copy and restore OFSAA file system</i>	9
2.2.7	<i>In case, you have imported into different schemas, additionally modify Files under \$FIC_HOME</i>	10
2.2.8	<i>Run Port Changer utility</i>	10
2.2.9	<i>Run EncryptC.jar utility to change the key and encryption strings</i>	11
2.2.10	<i>Perform Post Cloning Configurations</i>	12
2.2.11	<i>Create and deploy .ear/ .war</i>	12
2.2.12	<i>Access the UI</i>	13
3	Appendix A	14

1 Preface

The purpose of this document is to serve as a reference material to OFSAA administrators with detailed steps to setup an OFSAA instance “Clone” for the 8.0.x.0.0 release.

1.1 Background

There is a consistent need for a faster and effective approach of replicating an existing OFSAA instance for further project developments, that is, setting up OFSAA instances that are exact copies of the current OFSAA instance.

1.2 Assumptions

This document assumes a working Source OFSAA 8.0 instance is in place. It also assumes an appropriate Target system exists for the new OFSAA setup that is being created.

1.3 Audience

This reference guide is intended for administrators and implementation consultants who are responsible for cloning OFSAA instance.

1.4 Conventions and Acronyms

Conventions	Description
Source	A source OFSAA system
Target	A target OFSAA system
8.0	The OFSAA 8.0.0.0.0 release
Configuration Schema (Config Schema)	Database schema which contains setup related configurations and metadata.
Atomic Schema	Database schema where the application data model is uploaded.

2 Setting Up an OFSAA Instance "Clone" for 8.0.x Release

2.1 Prerequisites

The documented steps in the subsequent sections should be followed only after the following prerequisites are in place:

2.1.1 General

1. FTP/ SFTP service should be running on the OFSAA Target system. User credentials to be available prior to the subsequent activities.
2. If the OFS AAI (platform) version in use is 8.0.0.0.0, download and install patch 20422514 in Source.
3. If the OFS AAI (platform) version in use is 8.0.1.0.0, download and install patch 22329222 in Source.
4. If the OFS AAI (platform) version in use is 8.0.5.0.x or 8.0.5.1.x, upgrade the source to 8.0.5.2.0 by installing the OFS AAI 8.0.5.2.0 ML patch 27552096.

2.1.2 Source System

1. All OFSAA services are brought down.
2. Database connection details such as RAC/ NON-RAC URL, SID/ Service Name, and User credentials are available.

2.1.3 Target System

1. All basic software required for installation of OFSAA applications (including infrastructure) are installed and working on the machine identified as the Target OFSAA instance. You can use the "Environment Check" utility to verify the system readiness.

For details on Software and Hardware Requirements, refer the respective OFSAA Application Pack Installation and Configuration Guide available in [OHC Documentation Library](#).

For details on usage of Environment Check Utility, see [OFS Analytical Applications Environment Check Utility Guide](#).

2. Web Server and Web Application Server are configured. For details on how to configure, see Appendix A in the 8.0.0.0.0 and 8.0.2.0.0 [OFS AAI Application Pack Installation and Configuration Guide](#).
3. OFSAA installation folder is identified as \$FIC_HOME with permissions 750. For example, /scratch/ofsaanew/OFSAA
4. OFSAA staging/ metadata repository folder is identified as "ftpshare" with permissions 775. For example, /scratch/ofsaanew/ftpsharenew.
5. Database connection details such as RAC/ NON-RAC URL, SID/ Service Name, and User credentials are available.

NOTE Ensure a new database instance is created that is different from the database instance used in the Source OFSAA instance.

6. Web Server/ Web Application Server identified for the deployment of OFSAA applications is installed and configured on the machine identified as the Web Server/ Web Application Server.

NOTE If you intend to use the same Web Application Server, ensure you create a separate profile (WebSphere) or domain (WebLogic).

7. Details of WebSphere profile/WebLogic Domain/Tomcat context to be available.

NOTE Ensure the `RevLog4jConfig.xml` is configured with default log paths before executing the utility.

2.2 Cloning Steps

Login to source config schema and execute the following query to get the config and atomic schemas names. You can use schema names in SCHEMAS attribute of **expdp** and **impdp** Database utility.

```
select dbuserid from db_master;
```

Perform the instructions given in the following sections:

2.2.1 Export the complete Configuration and Atomic Schema from Source Environment

For example:

```
expdp SYSTEM/oracle@OFSAA12C2DB DIRECTORY=data_pump_dir
DUMPFILE=ofsaaconf_ofsaaatm_%U.dmp filesize=2G SCHEMAS=ofsaaconf,ofsaaatm
LOGFILE=ofsaaconf_ofsaaatm_exp.log
```

NOTE Using above command will create data dumps in files of 2GB each (multiples). Any other commands/ tools as appropriate may be used to archive the schemas.

2.2.2 Restore the complete exported dumps into the Target Environment database

For example:

```
impdp SYSTEM/oracle@OFSAA12nDB DIRECTORY=data_pump_dir
DUMPFILE=ofsaaconf_ofsaaatm_%U.dmp SCHEMAS=ofsaaconf,ofsaaatm
LOGFILE=ofsaaconf_ofsaaatm_imp.log
```

NOTE Restoring the exported dumps creates Config and Atomic Schema(s) with the same user credentials as that of the source, along with the existing grants.

2.2.3 In case of restoring the complete exported dumps in to the Target Environment database with different database user names (schemas)

For Example:

```
impdp SYSTEM/oracle@OFSAA12nDB DIRECTORY=data_pump_dir
DUMPFILE=ofsaaconf_ofsaaatm_%U.dmp REMAP_SCHEMA=
ofsaaconf:newofsaaconf,ofsaaatm:newofsaaatm
LOGFILE=new_ofsaaconf_ofsaaatm_imp.log
```

NOTE

- Restoring the exported dumps creates Config and Atomic Schema(s) with the users mentioned under *REMAP_SCHEMA* attribute replaced as of the source, along with the existing grants as in the Source environment.
- Ignore the **ORA-39082** object type create with compilation errors which will be rectified later in subsequent steps.

2.2.4 Provide select grants on `sys.v_$parameter` view to Config and Atomic Schemas of Target Environment database

For example:

Login as sys user:

```
SQL> GRANT SELECT ON SYS.V_$PARAMETER TO ofsaaconf;
```

Grant succeeded

```
SQL> GRANT SELECT ON SYS.V_$PARAMETER TO ofsaaatm;
```

Grant succeeded

NOTE In case you had imported into different schemas, you need to additionally set passwords for Config and Atomic schemas of target environment Database same as source.

For example:

Login as sys user

```
SQL> ALTER USER newofsaaconf IDENTIFIED BY welcome1;
```


User Altered

```
SQL> ALTER USER newofsaatm IDENTIFIED BY welcome1;
```

User Altered

2.2.5 Login to Config Schema of Target Environment database

Update the Config Schema Table values as mentioned in Table 1 of [Appendix A](#).

NOTE This step is required only in case you have imported into different schemas.

2.2.6 Copy and restore OFSAA file system

1. Navigate to `$FIC_HOME/utility/Clone/bin` on Source environment and give 750 permissions to all files present in the folder.
2. Execute `./OFSAA_Archive.sh`.
This step will create zipped files for `$FIC_HOME` and `FTPSHARE` folders in their respective locations on Source. For example, `<FIC_HOME>.zip` and `<FTPSHARE>.zip`.
3. Copy the `<FIC_HOME>` and `<FTPSHARE>` archive files from Source to Target in respective locations, that is, as per the folders created for `$FIC_HOME` and `FTPSHARE`. (Refer points 2, 3 in the [Target System](#) section.)

NOTE Ensure the archives are transferred in BINARY mode.

4. Copy the entries made by OFSAA installer in `.profile` of Source to the `.profile` of Target in respective location.
5. To unzip, navigate to the directory where the zipped folder is in *Target* and execute the following command:

```
unzip -a <<Zipped_file>>
```

For example,

```
unzip -a ftpshare.zip
```

Perform this step for both `<FIC_HOME>` and `<FTPSHARE>` zipped files. This will unzip both files in their respective locations in the *Target* environment.

6. Give 750 permissions recursively to `$FIC_HOME` and 775 to `FTPSHARE` folder that have been extracted in the Target environment.

For example:

```
chmod -R 750 $FIC_HOME
```

```
chmod -R 775 FTPSHARE
```

7. Modify the variables `FIC_HOME`, `JAVA_BIN`, `PATH`, `ORACLE_HOME`, `TNS_ADMIN`, `ORACLE_SID` and `OFSAA_LOG_HOME` in the entries made by installer in `.profile` of the *Target* environment according to the appropriate values of the *Target* Environment.

For example: Change the path to Java runtime in JAVA_BIN variable according to the java runtime installation on Target environment.

8. Execute the `.profile` file in the Target environment.
9. Edit the `tnsnames.ora` file under `$TNS_ADMIN` directory to add/edit the connection details to OFSAA schemas of Target environment.

2.2.7 In case, you have imported into different schemas, additionally modify Files under \$FIC_HOME

Navigate to `$FIC_HOME` of OFSAAI server, modify values in files as specified in step 2 of [Appendix A](#) and follow subsequent steps.

2.2.8 Run Port Changer utility

- Ensure `RevLog4jConfig.xml` is configured with default log paths before executing the utility.
- This utility will connect to config schema to collect all the configurations, hence mandatorily edit the file `DynamicServices.xml` of `$FIC_HOME/conf` directory for the attribute `DEFAULT_CONNECTION_URL`, The VALUE should be qualified jdbc url of Target Database.

NOTE

See [Run port changer utility for 8.0.2.2.0, 8.0.3.3.0, 8.0.4.2.0 to 8.0.4.5.0, and 8.0.5.2.0 to 8.0.5.4.0](#) for information on how to run the Port Changer Utility for the versions specified in the link.

1. Navigate to `$FIC_HOME` folder on Target.
2. Run the **PortC.jar** utility using the command:

```
java -jar PortC.jar DMP
```

A file with the name **DefaultPorts.properties** will be created under `$FIC_HOME` directory which will contain the ports, IPs and paths currently being used.

NOTE

It is mandatory to run the Port Changer utility using the DMP parameter every time before executing the utility using UPD command.

3. Make the necessary changes to those ports, IPs, and paths in the `DefaultPorts.properties` file as per the Target environment. Save the changes.
4. Run the **PortC.jar** utility using the command:

```
java -jar PortC.jar UPD
```

This will change the ports, IPs and paths in `.profile` (under home directory), all files under `$FIC_HOME` directory, and tables in the database according to the values mentioned in **DefaultPorts.properties** file.

NOTE

1. The table `batch_parameter` is not updated with the new IP after you run `portc.jar`. This table holds the batch execution details of batches that were executed earlier. The table `batch_parameter_master` holds the new IP after you run `portc.jar`.
2. Refer to logs for more information, and contact Oracle support if you encounter any errors.

2.2.8.1 Run Port Changer utility for 8.0.2.2.0, 8.0.3.3.0, 8.0.4.2.0 to 8.0.4.5.0, and 8.0.5.2.0 to 8.0.5.4.0

1. Navigate to `$FIC_HOME/utility/PortC/bin` folder on *Target*.
2. Run the **PortC.sh** utility using the command:

```
./PortC.sh DMP
```

A file with the name **DefaultPorts.properties** will be created under `$FIC_HOME` directory which will contain the ports, IPs and paths currently being used.

NOTE

It is mandatory to run the Port Changer utility using the DMP parameter every time before executing the utility using UPD command.

3. Make the necessary changes to those ports, IPs, and paths in the **DefaultPorts.properties** file as per the Target environment. Save the changes.
4. Run the **PortC.sh** utility using the command:

```
./PortC.sh UPD
```

This will change the ports, IPs and paths in `.profile` (under home directory), all files under `$FIC_HOME` directory, and tables in the database according to the values mentioned in **DefaultPorts.properties** file.

2.2.9 Run EncryptC.jar utility to change the key and encryption strings

NOTE

This section is applicable to OFSAAI 8.0.0.0.0 and later versions, except 8.0.2.2.0, 8.0.4.2.0 to 8.0.4.5.0, 8.0.5.2.0 to 8.0.5.4.0, 8.0.6.0.0 and later releases.

For more information on versions to which this section is not applicable, see subsections [Run EncryptC.sh utility to change the key and encryption strings for 8.0.2.2.0, 8.0.4.2.0 to 8.0.4.5.0, and 8.0.5.2.0 to 8.0.5.4.0](#) and [Run EncryptC.sh utility to change the key and encryption strings for 8.0.6.0.0 versions and above](#).

1. Navigate to `$FIC_HOME` folder on *Target*.

2. Execute the following command:

```
java -jar EncryptC.jar
```

3. See the `Encrypt_utility.log` file under `$FIC_HOME/utility/EncryptC/bin` folder for log information.

2.2.9.1 Run EncryptC.sh utility to change the key and encryption strings for 8.0.2.2.0, 8.0.4.2.0 to 8.0.4.5.0, and 8.0.5.2.0 to 8.0.5.4.0

1. Navigate to `$FIC_HOME/utility/EncryptC/bin` folder on *Target*.

2. Execute the following command:

```
./EncryptC.sh
```

3. See the `Encrypt_utility.log` file under `$FIC_HOME/utility/EncryptC/bin` folder for log information.

NOTE

`EncryptC.jar` is mainly to maintain new encrypt keys for a new environment, so there will not be an impact if you skip this step.

If you get the error message "Error: Could not find or load main class OFSAAI.AESCrypter" while you execute `./EncryptC.sh`, it is because the required jar file is missing in the lib folder. If you want to execute `EncryptC.jar` in 8.0.4.2.0, update `EncryptC.sh` with the following entry and proceed with execution:

Replace line

```
"JAR_FILELIST=`find ../lib \( -name "*.jar" \)`"
```

with

```
"JAR_FILELIST=`find $FIC_HOME \( -name "*.jar" \)`"
```

2.2.9.2 Run EncryptC.sh utility to change the key and encryption strings for version 8.0.6.0.0 and above

It is mandatory to change the key and encryption strings for version 8.0.6.0.0 and above. See *Generating new AESCryptKey.ext and updating the keystore* section under *Key management* section in [OFS Analytical Applications Infrastructure Administration Guide](#) for more information.

2.2.10 Perform Post Cloning Configurations

Perform the post cloning configurations as mentioned in the *Post Installation Configurations* section in the 8.0.0.0.0 and 8.0.2.0.0 [OFS AAI Application Pack Installation and Configuration Guide](#).

2.2.11 Create and deploy .ear/ .war

1. Navigate to `$FIC_WEB_HOME` on the *Target*.
2. Delete OFSAA application `*.war/*.ear` file present in this folder.
3. Execute the command:

```
./ant.sh
```

4. Copy the generated .ear/.war file on to the Web Application Server identified for this OFSAA instance.
5. Modify all the Database connection resources done on Web Application Server are mapped to new JDBC URL and Database User Credentials. Verify test connection to validate.
6. Deploy the .ear/.war file using the Web Application Server Admin Console.

2.2.12 Access the UI

Access the UI by using the new IP Address/ Host Name, new Port, and new Context Name.

For example:

```
http://<IP ADDRESS/ HOSTNAME>:<PORT>/<CONTEXT NAME>/login.jsp
```

3 Appendix A

Manually modify the occurrences of source database username with new target database username (see REMAP_SCHEMA attribute given in [Restore the complete exported dumps into the Target Environment database](#) of Cloning Steps).

1. Login to the newly imported Config Schema and update the Column values as mentioned in the following table (Ignore if there are no rows found):

Table 1

SI no	TABLE NAME	COLUMN NAME
1	DB_MASTER	DBUSERID
2	AAI_DB_AUTH_ALIAS	V_AUTH_USERNAME
3	AAI_DB_DETAIL	V_SCHEMA_NAME
4	AAI_ETL_SOURCE	V_TABLE_OWNER
5	ETLSOURCEDETAILS	V_SCHEMA

2. Manually modify the occurrences of source Config Database username with New Target Config Database username.

Table 2

SI no	Folder Path	File Name
1	\$FIC_HOME/conf/	Reveleus.SEC
2	\$FIC_HOME/utility/OFSAAGenerateRepository/conf/	Reveleus.SEC
3	\$FIC_HOME/conf/	DynamicServices.xml
4	\$FIC_HOME/MigrationUtilities/Migration_LDAP/conf/	DynamicServices.xml
5	\$FIC_HOME/utility/OFSAAGenerateRepository/conf/	DynamicServices.xml
6	\$FIC_HOME/ficweb/webroot/conf/	DynamicServices.xml
7	\$FIC_HOME/EXEWebService/Tomcat/ROOT/conf/	DynamicServices.xml
8	\$FIC_HOME/EXEWebService/WebSphere/ROOT/conf/	DynamicServices.xml
9	\$FIC_HOME/EXEWebService/weblogic/ROOT/conf/	DynamicServices.xml
10	\$FIC_HOME/commonscrips/	ofs_aai_create_atomic.ora

NOTE Based on the Web Application Server, choose the relevant folder path from number 7, 8 or 9 from above list.

3. Execute scripts on Atomic Schemas to update new target config database user name as mentioned in the following:
 - a. On the putty console, navigate to \$FIC_HOME/commonscripts/ on OFSAAI Server.
 - b. Create a copy of file ofs_aai_create_atomic.ora as ofs_aai_create_atomic_<INFODOM>.ora.
 - c. Now replace \$INFODOM place holder with actual infodom name in the file ofs_aai_create_atomic_<INFODOM>.ora.

NOTE Enclose the actual infodom name within single quote.

INFODOM is associated with each atomic schema, hence you have to create individual files for each atomic schema.

You can fetch the INFODOM value associated with each atomic schema by executing the following query logging into the newly modified config schema.

```
SQL> select h.dbuserid, g.dsnid from dsnmaster g, db_master h where
g.dbname = h.dbname and h.dbname <> 'CONFIG';
```

- d. Connect to Atomic Schemas using sqlplus utility of \$ORACLE_HOME/bin.
- e. Execute ofs_aai_create_atomic_<INFODOM>.ora file and ignore **ORA-00001** and **ORA-02292** errors in the log file. In case, there are other errors, contact Oracle Support Services.

```
SQL> spool aai_create_<INFODOM>.log
SQL> @ofs_aai_create_atomic_<INFODOM>.ora
SQL> spool off
SQL> exit;
```

NOTE Repeat this for all the atomic schemas. Once execution is complete, delete all files created as ofs_aai_create_atomic_<INFODOM>.ora.

- f. Login into the newly imported Atomic Schemas. Perform the following steps on each Atomic Schema to modify the interdependent object:

Run the following query in each Atomic schema for verification of invalid object status:

```
select object_type, object_name from user_objects
where object_type in ('FUNCTION', 'PACKAGE', 'PACKAGE
BODY', 'PROCEDURE', 'TRIGGER', 'VIEW') and status = 'INVALID'
order by object_type , object_name;
```

If the above query list out the objects,

- i. Run the following anonymous block to compile invalid objects:

```
BEGIN
```

```

FOR cur_rec IN ( select object_type, object_name from
user_objects
where object_type in ('FUNCTION','PACKAGE','PACKAGE
BODY','PROCEDURE','TRIGGER','VIEW') and status = 'INVALID'
order by object_type , object_name )
LOOP
BEGIN
IF cur_rec.object_type = 'PACKAGE BODY' THEN
EXECUTE IMMEDIATE 'ALTER PACKAGE ' || ' "' ||
cur_rec.object_name || '" COMPILE BODY';
COMMIT;
ELSE
EXECUTE IMMEDIATE 'ALTER ' || cur_rec.object_type || ' "' ||
cur_rec.object_name || '" COMPILE';
COMMIT;
END IF;
EXCEPTION
WHEN OTHERS THEN NULL;
END;
END LOOP;
END;

```

ii. Run the following scripts to enable object registration elements:

```

spool <Validpath>/restore_owner.log
alter table REV_TABLES_TL disable constraint FK_REV_TABLES_TL_1
/
alter table REV_TABLE_CLASS_ASSIGNMENT disable constraint
FK_V_TABLE_CLASS_ASSIGNMENT_2
/
alter table REV_TAB_COLUMNS disable constraint
FK_REV_TAB_COLUMNS_1
/
alter table REV_TABLE_LOG_CLASS_ASMNT disable constraint
FK_V_TABLE_CLASS_LOG_ASMNT_2
/
alter table REV_TAB_CONSTRAINTS disable constraint
FK_REV_TAB_CONSTRAINTS
/
alter table REV_TAB_CONSTRAINT_COLUMNS disable constraint
FK_REV_TAB_CONST_COLUMNS
/

```



```
alter table REV_TAB_INDEXES disable constraint
FK_REV_TAB_INDEXES
/
update FSI_DB_INFO set owner=USER
/
update REV_COLUMN_PROPERTIES set owner=USER
/
update REV_DESCRIPTION_TABLES set owner=USER ,
DESCRIPTION_TABLE_OWNER=USER
/
update REV_TABLES_B set owner=USER
/
update REV_TABLES_TL set owner=USER
/
update REV_TABLE_CLASS_ASSIGNMENT set owner=USER
/
update REV_TAB_COLUMNS set owner=USER
/
update REV_TAB_COLUMNS_MLS set owner=USER
/
update REV_VIRTUAL_TABLES set owner=USER
/
update REV_VIRTUAL_TABLES_MLS set owner=USER
/
update REV_VIRTUAL_TABLES_TL set owner=USER
/
update REV_TAB_CONSTRAINTS set owner=USER
/
update REV_SYNONYMS set table_owner=USER
/
update REV_TABLE_LOG_CLASS_ASMNT set owner=USER
/
update REV_TAB_CONSTRAINT_COLUMNS set owner=USER
/
update REV_TAB_INDEXES set owner=USER
/
update REV_TAB_REF_CONSTRAINTS set owner=USER
/
```

```
alter table REV_TABLE_LOG_CLASS_ASMNT enable constraint
FK_V_TABLE_CLASS_LOG_ASMNT_2
/

alter table REV_TAB_CONSTRAINTS enable constraint
FK_REV_TAB_CONSTRAINTS
/

alter table REV_TAB_CONSTRAINT_COLUMNS enable constraint
FK_REV_TAB_CONST_COLUMNS
/

alter table REV_TAB_INDEXES enable constraint FK_REV_TAB_INDEXES
/

alter table REV_TAB_COLUMNS enable constraint
FK_REV_TAB_COLUMNS_1
/

alter table REV_TABLE_CLASS_ASSIGNMENT enable constraint
FK_V_TABLE_CLASS_ASSIGNMENT_2
/

alter table REV_TABLES_TL enable constraint FK_REV_TABLES_TL_1
/

commit
/

spool off
exit;
```

Send Us Your Comments

Oracle welcomes your comments and suggestions on the quality and usefulness of this publication. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most about this manual?

If you find any errors or have any other suggestions for improvement, indicate the title and part number of the documentation along with the chapter/section/page number (if available) and contact the Oracle Support.

Before sending us your comments, you might like to ensure that you have the latest version of the document wherein any of your concerns have already been addressed. You can access My Oracle Support site which has all the revised/recently released documents.

