

Oracle® Business Intelligence Applications
Security Guide
11g Release 1 (11.1.1.10)
E53676-01

September 2015

Copyright © 2014, 2015, Oracle and/or its affiliates. All rights reserved.

Primary Author: Lalithashree Rajesh

Contributors: Oracle Business Intelligence Applications development, product management, and quality assurance teams.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in preproduction status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your beta trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Contents

Preface	v
Audience	v
Documentation Accessibility	v
Related Documentation	v
Conventions.....	vi
New Features for Oracle BI Applications Security Administrators.....	vii
1 Overview of Security Integration for Oracle BI Applications	
Terminology Used In Security	1-1
What Security Components Are Installed By Default?.....	1-2
High-Level Steps for Setting Up Security in Oracle BI Applications.....	1-2
What Tools Configure Security in Oracle Business Intelligence Applications?	1-3
Duty Roles for Access to Functional Setup Manager or Configuration Manager.....	1-4
Configuration Manager Permissions Reference.....	1-5
Functional Setup Manager Permissions Reference.....	1-6
About Managing Presentation Services Catalog Privileges in Oracle Business Intelligence	1-7
What Security Levels Do Oracle BI Applications Use?	1-7
About Object-Level Security	1-8
About Data-Level Security.....	1-8
Implementing Data-Level Security in the Oracle BI Repository	1-10
About User-Level Security.....	1-10
Related Documentation for Oracle BI Applications Security.....	1-10
2 Managing Duty Roles in Oracle BI Applications	
Viewing Duty Roles for Oracle BI Applications	2-2
Provisioning BI Users with Duty Roles.....	2-4
Creating Duty Roles for Oracle BI Applications	2-6
User Access Using Roles.....	2-7
3 Setting Up Security with Functional Setup Manager	

4 Extending Security in Oracle BI Applications

Index

Preface

Oracle Business Intelligence Applications is a comprehensive suite of prebuilt solutions that deliver pervasive intelligence across an organization, empowering users at all levels - from front line operational users to senior management - with the key information they need to maximize effectiveness. Intuitive and role-based, these solutions transform and integrate data from a range of enterprise sources and corporate data warehouses into actionable insight that enables more effective actions, decisions, and processes.

Oracle BI Applications is built on Oracle Business Intelligence Suite Enterprise Edition (Oracle BI EE), a comprehensive set of enterprise business intelligence tools and infrastructure, including a scalable and efficient query and analysis server, an ad-hoc query and analysis tool, interactive dashboards, proactive intelligence and alerts, and an enterprise reporting engine.

Audience

This document is intended for BI managers and implementors of Oracle BI Applications who are responsible for managing Oracle BI Applications security. It contains information describing Oracle BI Applications security and its preconfigured implementation.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documentation

The Oracle Business Intelligence Applications documentation library contains more documentation.

See http://docs.oracle.com/cd/E63231_01/index.htm for a list of related documents.

Conventions

The following text conventions are used in this document.

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

New Features for Oracle BI Applications Security Administrators

This release of Oracle BI Applications provides the following new feature related to security:

Oracle BI Applications Configuration Manager provides an option to set up data security for an Oracle Service Cloud source instance based on the Interfaces that are defined in Oracle Service Cloud.

Documentation Changes

The earlier versions of the Security Guide had an appendix titled Configuring Security, which contained Help topics that were displayed in Oracle BI Applications Functional Setup Manager (FSM) when a security administrator clicked a **Go to Task** icon next to a security task. In this release, that appendix has been moved to the *Oracle Business Intelligence Applications Functional Configuration Reference*.

Overview of Security Integration for Oracle BI Applications


This topic describes key concepts related to security in Oracle Business Intelligence Applications.

Security administrators can read this topic to understand Oracle BI Applications security and its preconfigured implementation.

- [About Terminology Used in Security](#)
- [What Security Components Are Installed By Default?](#)
- [High-Level Steps for Setting Up Security in Oracle BI Applications](#)
- [What Tools Configure Security in Oracle BI Applications?](#)
- [Duty Roles for Access to Functional Setup Manager or Configuration Manager](#)
- [Configuration Manager Permissions Reference](#)
- [Functional Setup Manager Permissions Reference](#)
- [About Managing Presentation Services Catalog Privileges in Oracle BI](#)
- [What Security Levels Does Oracle BI Applications Use?](#)
- [Related Documentation for Oracle BI Applications Security](#)

Terminology Used In Security

As you familiarize yourself with security concepts across different parts of the BI stack, there are differences in terminology that is used in the software and documentation.



- Enterprise Roles are also referred to as Groups, or Job Roles. For example:

- the term Enterprise Role is used in this guide, and in Fusion Applications.
- the term Group is used in Oracle WebLogic Server Administration Console and Oracle BI Administration Tool.


This guide uses the term Enterprise Role unless referring to tools that use the term Group or Job Role.

- Duty Roles are also referred to as Application Roles. For example:
 - the term Duty Role is used in this guide and in Fusion Applications.
 - the term Application Role is used in Oracle Enterprise Manager Fusion Middleware Control and Oracle WebLogic Server Administration Console.
- This guide uses the term Duty Role unless referring to tools that use the term Application Role.
- Lightweight Directory Access Protocol (LDAP) refers to the Authentication Provider. For example, Oracle WebLogic Server, Oracle Internet Directory (OID), or a proprietary LDAP server and tools.

What Security Components Are Installed By Default?

After installing Oracle BI Applications on the Oracle BI EE platform, you get the following ready-to-use security components.

- Oracle WebLogic Server LDAP, containing a set of default Enterprise Roles.
This LDAP also contains system Users that are required for BI components.
- A Policy Store that contains default Duty Roles for all of the Offerings, Functional Areas, and Modules that are available in Oracle BI Applications.



For illustrative purposes, it is assumed that you are using the default WebLogic Server LDAP and Policy Store to deploy Oracle BI Applications. For example, you might use the default security components for testing, and then migrate the Users and Enterprise Roles to a different LDAP (for example, Oracle Internet Directory) for production. If you want to deploy a different LDAP, such as Oracle Internet Directory, then you can migrate Users and Enterprise Roles from WebLogic Server LDAP to that LDAP.

High-Level Steps for Setting Up Security in Oracle BI Applications

Here are the high-level steps for setting up security in Oracle BI applications.

This content in this guide supplements *Oracle Business Intelligence Security Guide*, and contains additional security information that is specific to Oracle BI Applications running on Oracle Business Intelligence Enterprise Edition. In addition to the content

in this guide, *Oracle Business Intelligence Applications Functional Configuration Reference* contains the security-related help topics that are included in the product UI.

1. Familiarize yourself with the overview of security concepts, tools, and terminology, in particular, Duty Roles and how they control user privileges.
2. During Oracle BI Applications installation, the provisioning process creates a set of default Enterprise Roles in the Oracle WebLogic Server LDAP that is embedded by default, and a set of default Duty Roles in the Policy Store.
3. Create a user account in LDAP for each Oracle BI Applications Configuration Manager, Functional Setup Manager (FSM), and ODI User, and assign an appropriate Duty Role to each User.
 - A User for administration in FSM must be assigned to an Enterprise Role associated with the Duty Role 'BIA_ADMINISTRATOR_DUTY'.
 - A User for Load Plan administration in Oracle BI Applications Configuration Manager must be assigned to an Enterprise Role associated with the Duty Role 'BIA_LOAD_PLAN_DEVELOPER_DUTY'.
 - A User for Implementation Plan administration in FSM must be assigned to an Enterprise Role associated with the Duty Role 'BIA_IMPLEMENTATION_MANAGER_DUTY'.
4. Create a user account in LDAP for every BI dashboard and report user (BI Users).
5. Assign each BI User to the appropriate Enterprise Roles.

To provision BI Users for the Offerings that you are deploying, use Functional Setup Manager (FSM) Tasks to set up security for your Offerings and Functional Areas. For information about using FSM Tasks to configure security, see [Setting Up Security with Functional Setup Manager](#).

For each Offering and Functional Area, the FSM Tasks for security typically specify:

- Init Blocks that you need to enable.
- Duty Roles that BI Users require.
- Additional setup steps to perform (where required).

In addition to the information in the FSM Tasks for security, use *Content Guide for Oracle BI Applications* for a definitive list of default Duty Roles and Enterprise Roles required by BI Users (refer to Tech Note 1639479.1 on My Oracle Support). For more information about provisioning BI Users, see the topic titled "How to Define New Groups and Mappings for Users and BI Roles" in the *Oracle BI Applications Functional Configuration Reference*.

What Tools Configure Security in Oracle Business Intelligence Applications?

Use these tools to manage security settings in Oracle Business Intelligence Applications.

- Oracle BI Applications Functional Setup Manager (FSM)

Use Oracle BI Applications Functional Setup Manager informational tasks to set up security for Oracle BI Applications offerings and modules.

For a summary of how FSM Tasks are used to configure security, see [Setting Up Security with Functional Setup Manager](#).

- Oracle BI Administration Tool

Use Oracle BI Administration Tool to perform tasks such as setting permissions for business models, tables, columns, and subject areas; specifying filters to limit data accessibility; and setting authentication options. For detailed information, see *Oracle Fusion Middleware Metadata Repository Builder's Guide for Oracle Business Intelligence Enterprise Edition*.

- Oracle BI Presentation Services Administration

Use Oracle BI Presentation Services Administration to perform tasks such as setting permissions to Presentation Catalog objects, including dashboards and dashboard pages. For detailed information, see *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*.

- Oracle Enterprise Manager Fusion Middleware Control

Use Fusion Middleware Control to manage the policy store, Duty Roles, and permissions for determining functional access. For detailed information, see *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*.

- Oracle WebLogic Server Administration Console

Use the Administration Console to manage Users and Enterprise Roles/Groups in the Oracle WebLogic Server LDAP. You can also use the Administration Console to manage security realms, and to configure alternative authentication providers. For detailed information, see *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*.

Duty Roles for Access to Functional Setup Manager or Configuration Manager

Duty Roles define a set of permissions granted typically to an Enterprise Role.

To access Oracle BI Applications Configuration Manager or Functional Setup Manager (for Oracle BI Applications), a User must be assigned to an Enterprise Role that is associated with one of the following Duty Roles:

- BI Applications Administrator Duty (BIA_ADMINISTRATOR_DUTY)

Users with the BI Applications Administrator Duty Role have access to all Oracle BI Applications Configuration Manager User Interfaces and all Functional Setup Manager User Interfaces. For Oracle BI Applications Configuration Manager, only users with this Duty Role are able to perform system setup tasks.

- BI Applications Implementation Manager (BIA_IMPLEMENTATION_MANAGER_DUTY)

Users with the BI Applications Implementation Manager Duty Role have access to Oracle BI Applications Configuration Manager Overview page and the Export and Import of Setup Data. In Functional Setup Manager, these users have access to Configure Offerings and Manage Implementation Projects User Interfaces but cannot execute a setup task.

- BI Applications Functional Developer (BIA_FUNCTIONAL_DEVELOPER_DUTY)
Users with the BI Applications Functional Developer Duty Role have access to Oracle BI Applications Configuration Manager User Interfaces, except for the System Setup screens. In Functional Setup Manager, these users have access to the list of functional setup tasks assigned to them and have the ability to execute the setup tasks.
- BI Applications Load Plan Developer (BIA_LOAD_PLAN_DEVELOPER_DUTY)
Users with the BI Applications Load Plan Developer Duty Role have access to the Load Plans page, where they can create, edit, delete, generate, execute and monitor load plans. Users with this role can view and edit fact groups, data load parameters, domains mappings, and schedules associated with a load plan.
- BI Applications Load Plan Operator (BIA_LOAD_PLAN_OPERATORY_DUTY)
Users with the BI Applications Load Plan Operator Duty Role have limited access to the Load Plans page, where they can view the generation status and execution status details of load plans but are not able to modify them.

For information about granting users access to Oracle BI Applications components, see *Oracle Business Intelligence Applications Installation Guide*.

Configuration Manager Permissions Reference

The screens you can view in Configuration Manager depend on the duty roles to which you are assigned.

This table shows the list of Oracle BI Applications Configuration Manager screens visible to each of the Oracle BI Applications Roles.

Oracle BI Applications Duty Role	Oracle BI Applications Configuration Manager screen	Associated Privilege
BI Applications Administrator	Overview	BIA_OVERVIEW_PRIV
BI Applications Administrator	System Setups - Define Oracle BI Applications Instance	BIA_DEFINE_INSTANCE_PRIV
BI Applications Administrator	System Setups - Manage Oracle BI Applications	BIA_MANAGE_INSTANCE_PRIV
BI Applications Administrator	System Setups - Manage Preferred Currencies	BIA_MANAGE_INSTANCE_PRIV
BI Applications Administrator	Functional Configurations - 'Perform Functional Configurations' link to launch Functional Setup Manager	BIA_FUNCTIONAL_SETUPS_PRIV
BI Applications Administrator	Setup Data Maintenance and Administration - Manage Domains and Mappings	BIA_CONFIGURE_DOMAINS_PRIV
BI Applications Administrator	Setup Data Maintenance and Administration - Manage Data Load Parameters	BIA_CONFIGURE_DATA_LOAD_PARAMS_PRIV

Oracle BI Applications Duty Role	Oracle BI Applications Configuration Manager screen	Associated Privilege
BI Applications Administrator	Setup Data Maintenance and Administration - Manage Reporting Parameters	BIA_CONFIGURE_RPD_PARAMS_PRIV
BI Applications Administrator	Setup Data Export and Import - Export Setup Data	BIA_EXPORT_SETUPS_PRIV
BI Applications Administrator	Setup Data Export and Import - Import Setup Data	BIA_IMPORT_SETUPS_PRIV
BI Applications Functional Developer	Overview	BIA_OVERVIEW_PRIV
BI Applications Functional Developer	Functional Configurations - 'Perform Functional Configurations' link to launch Functional Setup Manager	BIA_FUNCTIONAL_SETUPS_PRIV
BI Applications Functional Developer	Setup Data Maintenance and Administration - Manage Domains and Mappings	BIA_CONFIGURE_DOMAINS_PRIV
BI Applications Functional Developer	Setup Data Maintenance and Administration - Manage Data Load Parameters	BIA_CONFIGURE_DATA_LOAD_PARAMS_PRIV
BI Applications Functional Developer	Setup Data Maintenance and Administration - Manage Reporting Parameters	BIA_CONFIGURE_RPD_PARAMS_PRIV
BI Applications Functional Developer	Setup Data Export and Import - Export Setup Data	BIA_EXPORT_SETUPS_PRIV
BI Applications Functional Developer	Setup Data Export and Import - Import Setup Data	BIA_IMPORT_SETUPS_PRIV
BI Applications Implementation Manager	Overview	BIA_OVERVIEW_PRIV
BI Applications Implementation Manager	Setup Data Export and Import - Export Setup Data	BIA_EXPORT_SETUPS_PRIV
BI Applications Implementation Manager	Setup Data Export and Import - Import Setup Data	BIA_IMPORT_SETUPS_PRIV

Functional Setup Manager Permissions Reference

Functional Setup Manager Roles are associated with Oracle BI Applications Roles.

- The BI Applications Administrator role (BIA_ADMINISTRATOR_DUTY) is associated to the following Functional Setup Manager Roles:
 - ASM_FUNCTIONAL_SETUPS_DUTY

- ASM_IMPLEMENTATION_MANAGER_DUTY
- ASM_APPLICATION_DEPLOYER_DUTY
- ASM_APPLICATION_REGISTRATION_DUTY
- ASM_LOGICAL_ENTITY_MODELING_DUTY
- ASM_SETUP_OBJECTS_PROVIDER_DUTY
- The BI Applications Implementation Manager role (BIA_IMPLEMENTATION_MANAGER_DUTY) is associated to the following Functional Setup Manager duty:
 - ASM_IMPLEMENTATION_MANAGER_DUTY
- The BI Applications Functional Developer role (BIA_FUNCTIONAL_DEVELOPER_DUTY) is associated to the following Functional Setup Manager duty:
 - ASM_FUNCTIONAL_SETUPS_DUTY

About Managing Presentation Services Catalog Privileges in Oracle Business Intelligence

When you add a new catalog privilege to a Duty Role in Oracle BI Presentation Services, the change is not immediately reflected in the Oracle Business Intelligence environment.

To register the catalog privilege, both the administrator and the user must perform the following tasks:

- The Oracle BI administrator must reload the Oracle BI Server metadata through Oracle BI Presentation Services. To reload the metadata, in Oracle Business Intelligence Answers, select **Administration**, and then click **Reload Files and Metadata**.

For more information on managing Presentation Services catalog privileges, see *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*.

- Users belonging to that Duty Role must log out from the Oracle BI application (or from Siebel or Oracle EBS operational application if the user is looking at Oracle BI dashboards using an embedded application) and then log in again.

What Security Levels Do Oracle BI Applications Use?

Security in Oracle BI Applications can be classified broadly into three levels.

- Object-level security. Object-level security controls the visibility to business logical objects based on a user's role. You can set up object-level security for metadata repository objects, such as business models and subject areas, and for Web objects, such as dashboards and dashboard pages, which are defined in the Presentation Catalog.
- Data-level security. Data-level security controls the visibility of data (content rendered in subject areas, dashboards, Oracle BI Answers, and so on) based on the user's association to data in the transactional system.

- User-level security (authentication of users). User-level security refers to authentication and confirmation of the identity of a user based on the credentials provided.

About Object-Level Security

Duty Roles control access to metadata objects, such as subject areas, tables and columns. For example, users in a particular department can view only the subject areas that belong to their department.

Metadata Object-Level Security in the RPD

Metadata object security is configured in the Oracle BI Repository, using the Oracle BI Administration Tool. The Everyone Duty Role is denied access to each of the subject areas. Each subject area is configured to give explicit read access to selected related responsibilities. This access can be extended to tables and columns. By default in Oracle BI Applications, only permissions at the subject area level have been configured.

Note:

The Siebel Communications and Financial Analytics industry applications have tables and columns that are industry-specific, and, therefore, hidden from other Duty Roles.

Oracle Business Intelligence supports hierarchies within Duty Roles. In the policy store, there are certain Duty Roles that are parent Duty Roles, which define the behavior of all the child Duty Roles. Inheritance is used to enable permissions to ripple through to child Duty Roles. For more information about parent Duty Roles and the pre-built Duty Role hierarchies, refer to the list of groups, Duty Roles, initialization blocks, and security policies published on My Oracle Support as a document named 'Oracle Business Intelligence Applications Roles and Security'.

Metadata Object-Level Security in Presentation Services

Access to Oracle BI Presentation Services objects, such as dashboards, pages, reports, and Web folders, is controlled using Duty Roles. For detailed information about managing object-level security in Presentation Services, see *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*.

About Data-Level Security

Data-level security defines what a user in an OLTP application can access inside a report. The same report, when run by two different users, can bring up different data. This is similar to how the My Opportunities view in an operational application displays different data for different users. However, the structure of the report is the same for all users, unless a user does not have access to the report subject area, in which case the report displays an error.

For information about the data security policies that are supported in Oracle BI Applications, refer to the list published on My Oracle Support as a document named 'Oracle Business Intelligence Applications Roles and Security'. During installation and configuration, you must make sure the correct Duty Roles and initialization blocks are set up for your environment.

Initialization Blocks Used for Data-Level Security in Oracle BI Applications

Initialization blocks are deployed as part of your configuration using guidance provided in Functional Setup Manager (FSM) tasks.

For a summary of how FSM Tasks are used, see [Setting Up Security with Functional Setup Manager](#). For detailed information about using FSM tasks, see *Oracle Business Intelligence Applications Configuration Guide*. For information about the initialization blocks prebuilt for Oracle BI Applications, refer to the list published on My Oracle Support as a document named 'Oracle Business Intelligence Applications Roles and Security'.

For more information about the use of initialization blocks in Oracle Business Intelligence, see *Oracle Fusion Middleware Metadata Repository Builder's Guide for Oracle Business Intelligence Enterprise Edition* and *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*.

About Data-Level Security Design in Oracle BI Applications

Oracle BI Applications maintains data-level security Duty Roles that are assigned dynamically to every user at the session level. Each Duty Role has a set of filters associated with it that determines the data that each user is allowed to see. A user is assigned a Duty Role through the Authorization initialization block.

The data security design has the following features:

- Drill down. The user can drill down on a particular position in the position hierarchy to slice the data by the next position level in the hierarchy. For example, if the initial report is defined as:

```
select Top Level Position, Revenue from RevenueStar
```

then by drilling down on a value of MyPosition in the TopLevelPosition hierarchy, the report will become:

```
Select Level8 Position, Revenue, where TopLevelPosition =
'MyPosition'
```

- Personalized reports. Users at different levels of the Position hierarchy can use the same Position-based reports but with each user seeing the data corresponding to his or her level. In such reports, Position is a dynamic column.

For example, if a report is defined as:

```
select Position, Revenue from RevenueStar
```

the logical query for the user at the top level of the hierarchy will be:

```
select Top Level Position, Revenue from RevenueStar
```

The logical query for the user at the next level of the hierarchy will be:

```
select Level8 Position, Revenue from RevenueStar
```

- CURRENT Position hierarchy columns. Position hierarchy columns with the prefix CURRENT contain the Current Position hierarchy at any point of time. This feature allows users to see the same data associated with the employee holding the Current Employee position at the time the report runs. This type of Analysis is called As Is.
- Additional Position hierarchy columns. The columns EMP_LOGIN and EMPLOYEE_FULL_NAME are used at every level of the Position hierarchy to store additional information about an employee holding a particular position. In the Logical layer, the Employee path and Position path are two drill down paths under

the Position hierarchy that allow the user to drill down on a position to see all positions under it. It also allows an employee to see all the employees reporting to him or her.

Implementing Data-Level Security in the Oracle BI Repository

Data-level security in Oracle BI Applications is implemented in three major steps.

1. Set up initialization blocks that obtain specific security-related information when a user logs in, for example, the user's hierarchy level in the organization hierarchy, or the user's responsibilities.

Initialization blocks obtain Dimension Ids for each user session in order to restrict row-level access to factual or dimensional data. See [About Data-Level Security](#) for a description of the preconfigured initialization blocks.

2. Set up the joins to the appropriate security tables in the metadata physical and logical layers.

For detailed information about this security feature, see *Oracle Fusion Middleware Metadata Repository Builder's Guide for Oracle Business Intelligence Enterprise Edition*.

3. Set up the data filters for each Duty Role on each logical table that needs to be secured.

For detailed information about this security feature, see *Oracle Fusion Middleware Metadata Repository Builder's Guide for Oracle Business Intelligence Enterprise Edition*.

About User-Level Security

User security concerns the authentication and confirmation of the identity of the user based on the credentials provided, such as user name and password. By default, user-level security is set up in the embedded Oracle WebLogic Server LDAP and Policy Store in Oracle Business Intelligence Enterprise Edition.

For more information, see *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*.

Related Documentation for Oracle BI Applications Security

Oracle offers additional documentation to help you configure security for Oracle BI applications.

When configuring security in Oracle BI Applications, in some circumstances you might need to refer to security in other areas:

- Oracle Fusion Applications security

For more information, see:

- *Oracle Fusion Applications Security Guide*
- *Oracle Fusion Applications Common Security Reference Manual*

- Oracle Business Intelligence Enterprise Edition security implementation

For more information, see:


- *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*

- *Oracle Fusion Middleware Metadata Repository Builder's Guide for Oracle Business Intelligence Enterprise Edition*

Managing Duty Roles in Oracle BI Applications

Object-level and data-level security are implemented in Oracle BI Applications using Duty Roles in the Policy Store. Duty Roles define a set of permissions granted typically to an Enterprise Role.

This figure illustrates how users are assigned to Enterprise Roles in the LDAP, which are associated with Duty Roles in the Policy Store.



Duty Roles are typically related to either data or object security. For example, the Oracle BI Applications repository (OracleBIAnalyticsApps.rpd) uses the following Duty Roles:

- The HR Org-based Security Duty Role is used to control access to human resources data at the data security level.
- The Human Resources Analyst Duty Role is used to control Presentation layer object visibility for the Human Resources Analyst role at the object security level.

The standard hierarchical structure of Duty Roles and users in Oracle BI Applications is typically the following: data security Duty Role, then object security Duty Role, then Enterprise Role (also called Group), then User. It is a best practice to use this structure when setting up security.

Security administrators can view, modify, and create Duty Roles in Oracle Enterprise Manager Fusion Middleware Control.

For example, BI User Fred has Enterprise Role 'Fixed Asset Accounting Manager EBS'. To provision Fred with security access for Fixed Assets Accounting reporting for EBS, you edit the BI Duty Role 'Fixed Asset Accounting Manager EBS' and add Enterprise Role 'Fixed Asset Accounting Manager EBS' as a Member.

Matching Pre-Configured Duty Roles with User Responsibilities

Pre-configured Duty Roles match responsibilities and roles in source operational applications, so that after authentication the correct roles can be applied. An administrator can check a user's responsibilities in the following ways:

- In the Siebel or Oracle EBS operational applications, go to the Responsibilities view.
- In PeopleSoft applications, go to the Roles view to check a user's roles.
- In JD Edwards EnterpriseOne applications, go to the User Profiles application (P0092) to check a user's roles.
- Individual users can view the list of Duty Roles to which they are assigned. In the Oracle BI application, select **Signed In As, *username***, then **My Account**. Then, click the Roles and Catalog Groups tab to view the Duty Roles. In Presentation Services, Duty Roles are used to control the ability to perform actions (privileges) within Presentation Services.

For more information, refer to the system administrator for your source system.

Tools to View Pre-configured Duty Roles

You can use a number of BI tools to view pre-configured Duty Roles, as follows:

- Oracle BI Administration Tool

To view pre-configured Duty Roles using Oracle BI Administration Tool, open the RPD, select **Manage**, then **Identity**. Duty Roles are visible in the Identity Manager dialog in online mode. In offline mode, only Duty Roles that have had permissions, filters, or query limits set for them appear. For this reason, it is recommended that when you work with data access security in the Oracle BI Applications repository, you use online mode.

- Oracle Enterprise Manager Fusion Middleware Control - for details, see [Viewing Duty Roles for Oracle BI Applications](#).
- Oracle Authorization Policy Manager - In Oracle APM, navigate to the 'obi' Application and use the Search options to locate Duty Roles prefixed with 'OBIA_'. Select a Duty Role, then click **Open** to display the <Application> | Application Role dialog. Display the External Role Mapping tab, and check that the role list contains the appropriate Enterprise Roles.

Viewing Duty Roles for Oracle BI Applications

You can view duty roles for Oracle BI applications using Oracle Enterprise Manager Fusion Middleware Control.

The screenshot shows an example of additional pre-defined Duty Roles that are created when Oracle BI Applications is installed. The list of Duty Roles depends on your installation.

Application Roles

Application roles are the roles used by security aware applications that are specific to the application. These roles are seeded by applications in single global policy store when the applications are registered. These are also application roles that are created in the context of end users accessing the application.

To manage users and groups in the WebLogic Domain, use the [Oracle WebLogic Server Security Provider](#).

Policy Store Provider

Search

Create... Create Like... Edit... Delete...

Role Name	Display Name	Description
OBIA_SPEND_PLANNING PROCUREMENT_AN	Spend Planning Procurement Analysis Duty	Spend Planning Procurement Analysis Duty
OBIA_COSTING_ORGANIZATION_DATA_SECL	Costing Organization Data Security	This role is used for Costing Organization Data Security
OBIA_DEPARTMENT_DATA_SECURITY	Department Data Security	This role is used for Department Data Security
OBIA_EMPLOYEE_EXPENSE_BUSINESS_UNIT_I	Employee Expense Business Unit Data Security	This role is used for Employee Expense Business Unit Data Security
OBIA_EMPLOYEE_EXPENSE_HIERARCHY_DAT	Employee Expense Hierarchy Data Security	This role is used for Employee Expense Hierarchy Data Security
OBIA_EXTENDED_INVENTORY_ORGANIZATION	Extended Inventory Organization and Shipmer	This role secures data access for Extended Inventory Organization and Shipmer
OBIA_EXTENDED_ORDER_FULFILLMENT_ORC	Extended Order Fulfillment Orchestratio	This role secures data access for Extended Order Fulfillment Orchestratio
OBIA_EXTENDED PROCUREMENT AND PAYA	Extended Procurement and Payable Business Unit	Extended Procurement and Payable Business Unit
OBIA_EXTENDED PROCUREMENT AND SPEND	Extended Procurement and Spend Business Unit	Extended Procurement and Spend Business Unit
OBIA_FIXED_ASSETS_BOOK_DATA_SECURITY	Fixed Assets Data Security	This role is used for Fixed Assets Data Security
OBIA_GENERAL_LEDGER_DATA_SECURITY	General Ledger Data Security	This role is used for General Ledger Data Security

Membership for OBIA_SPEND_PLANNING PROCUREMENT_ANALYSIS_DUTY

Principal	Display Name	Type	Description
Executive Manager		Group	
GL_GENERAL_ACCOUNTING_M		Group	

1. Log in to Oracle Enterprise Manager Fusion Middleware Control as an administrator.
2. Expand Business Intelligence, right-click **coreapplication**, and select **Security**, then **Application Roles**.

The available Duty Roles are listed. The Membership for <Duty Role name> area displays Enterprise Roles or other Duty Roles that are associated with the selected Duty Role.

ORACLE Enterprise Manager 11g Fusion Middleware Control

Farm Topology

Logged in as weblogic

Page Refreshed Feb 19, 2014 2:28:02 PM UTC

coreapplication Business Intelligence Instance

Application Roles

Application roles are the roles used by security aware applications that are specific to the application. These roles are seeded by applications in single global policy store when the applications are registered. These are also application roles that are created in the context of end users accessing the application.

To manage users and groups in the WebLogic Domain, use the [Oracle WebLogic Server Security Provider](#).

Policy Store Provider

Search

Enter search keyword for role name to query roles defined by this application. Use application stripe to search if application uses a stripe that is different from application name.

Application Stripe: obi

Role Name: Starts With:

Create... Create Like... Edit... Delete...

Membership for BISystem

Principal	Display Name	Type	Description
BISystemUser		User	

Provisioning BI Users with Duty Roles

To provision a BI User with a Duty Role, you first assign the User to an Enterprise Role/Group in LDAP, then make sure that the Enterprise Role/Group is associated with the appropriate Duty Role in the Policy Store.

BI Users are provisioned with BI Duty Roles using Enterprise Roles in the LDAP. To provision users, you typically use either Oracle Fusion Middleware, or RPD initialization blocks. If you are using the default embedded Enterprise Roles in Oracle WebLogic Server LDAP, then these Enterprise Roles are associated with the appropriate Duty Roles by default, and no further configuration is required.

If you are using a different LDAP with your own set of Enterprise Roles, then you need to make sure that these are associated with the appropriate Duty Roles, by following the steps below.

1. Log in to Oracle Enterprise Manager Fusion Middleware Control as an administrator.
2. Expand Business Intelligence, right-click **coreapplication**, and select **Security**, then **Application Roles**.


A list of available Duty Roles is displayed.

The screenshot shows the Oracle Enterprise Manager Fusion Middleware Control interface. The left sidebar shows a tree view of the farm structure, including Farm_fsmite_rel9_new, Application Deployments, WebLogic Domain, Business Intelligence, and coreapplication. The coreapplication node is selected. The main content area is titled 'coreapplication' and shows 'Business Intelligence Instance'. The 'Application Roles' section is displayed, with a sub-section for 'Policy Store Provider'. A search bar is present, and a table lists various application roles. The 'Membership for BISystem' section shows a table with one entry: BISystemUser.

Role Name	Display Name	Description
BISystem	BI System Role	
BIAdministrator	BI Administrator Role	
BAuthor	BI Author Role	
BIConsumer	BI Consumer Role	
BApplSystem	BI App System Role	
BIRepositoryManager	BI Platform Repository Manager	
BIImpersonator	BI Impersonator	
EssbaseCalcManager	Essbase Calculations Manager	
BIPublisherDataModelDeveloper	BI Publisher Data Model Developer	
FBI_ABSENCE_MANAGEMENT_TRANSACTION	Absence Management Transaction Analysis	Du Analyzes Workforce absences transactional info
FBI_AGREEMENT_TRANSACTION_ANALYSIS	Agreement Transaction Analysis	Du Analyzes Agreement transactional information


Principal	Display Name	Type	Description
BISystemUser		User	

3. Provision a BI User with a Duty Role.
 - a. Select the Duty Role that a BI User requires access to.
 - b. Click **Edit** to display the Edit Application Role dialog.



- c. In the Member list, click **Add** to display the Add Principal dialog.
- d. Use the Search area to locate and select the Enterprise Role/Group that the BI User has.

For example, User Fred has Enterprise Role 'Fixed Asset Accounting Manager EBS'. To provision Fred with security access for Fixed Assets Accounting reporting for EBS, you edit the BI Duty Role 'Fixed Asset Accounting Manager EBS' and add Enterprise Role 'Fixed Asset Accounting Manager EBS' as a Member.



- e. Click **OK**.

Creating Duty Roles for Oracle BI Applications

You can edit or create Duty Roles.

1. Log in to Oracle Enterprise Manager Fusion Middleware Control as an administrator.
2. Expand Business Intelligence, right-click **coreapplication**, and select **Security**, then **Application Roles**.

A list of available Duty Roles is displayed.

The screenshot shows the Oracle Enterprise Manager 11g Fusion Middleware Control interface. The left sidebar shows a tree structure with 'Farm_fsmlite_rel9_new' expanded, showing 'Application Deployments', 'WebLogic Domain', 'Business Intelligence', and 'coreapplication'. The 'coreapplication' node is selected. The main content area is titled 'coreapplication' and shows 'Business Intelligence Instance'. Below this, the 'Application Roles' section is displayed. A sub-section titled 'Policy Store Provider' contains a 'Search' field and a table of roles. The table has columns 'Role Name', 'Display Name', and 'Description'. The roles listed are: BISystem (Display Name: BI System Role), BIAdministrator (Display Name: BI Administrator Role), BIAuthor (Display Name: BI Author Role), BIConsumer (Display Name: BI Consumer Role), BIAppSystem (Display Name: BI Apps System Role), BIRepositoryManager (Display Name: BI Platform Repository Manager), BIImpersonator (Display Name: BI Impersonator), EssbaseCalcManager (Display Name: Essbase Calculations Manager), BIPublisherDataModelDeveloper (Display Name: BI Publisher Data Model Developer), FBI_ABSENCE_MANAGEMENT_TRANSACTION (Display Name: Absence Management Transaction Analysis), and FBI AGREEMENT TRANSACTION ANALYSIS (Display Name: Agreement Transaction Analysis). The 'BISystem' role is selected, and its membership is shown in a table with columns 'Principal', 'Display Name', 'Type', and 'Description'. The member listed is 'BISystemUser' (Type: User). The status bar at the bottom right indicates 'Page Refreshed Feb 19, 2014 2:28:02 PM UTC'.

3. Click **Create** to display the Create Application Role dialog.

Alternatively, select a Duty Role similar to the one that you want to create, and click **Create Like**. Using **Create Like** copies the default Members (that is, Enterprise Roles/Groups).

4. Use the General area to specify the details.
5. In the Member list, click **Add** to search for and select the Enterprise Roles/Groups that you want this Duty Role to be associated with.
6. Click **OK**.

User Access Using Roles

Authorization for Oracle BI Applications is controlled by security policies (Oracle BI Applications privileges) defined for users using a role-based model.

Every Oracle Applications user is hired by their company to perform a role in the organization, for example, Payroll Manager or Accounts Payable Manager. An Oracle Applications user is granted a role and thus inherits one or more associated privileges that were granted to the role.

It is possible to grant multiple Duty Roles to a User; however Oracle recommends that Enterprise Roles are defined so that a User is provisioned with a single Duty Role.

If you have Oracle Business Intelligence Enterprise Edition test servers configured against a test LDAP, and the production servers are configured against the corporate LDAP, but the test LDAP is not a fan-out copy of the corporate LDAP directory, then you must refresh the LDAP GUIDs. See "Refreshing User GUIDs" in *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition* for more information. Note that while LDAP is required for Fusion Applications environments, it is optional for other source applications.

Setting Up Security with Functional Setup Manager

To set up security for Offerings in Oracle BI Applications, you use Functional Setup Manager (FSM) to manage the security tasks. When you create an Implementation Plan in FSM for a particular Functional Area, FSM provides a list of tasks required to configure that Functional Area, including security setup tasks. Security setup tasks typically have the word 'Security' in the task name.

For detailed information about using FSM tasks, see *Oracle Business Intelligence Applications Configuration Guide*.

For example, the screenshot below shows a list of FSM Tasks for a Functional Area in Human Resources. A number of security-related tasks are highlighted, for example, 'How to Set Up Payroll Based Data Security'.

Implementation Project: IP3						Done
* How to Set Up Workforce Frozen Snapshots		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Assign Group Account Numbers to Natural Account		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Control Future Transaction Data Visibility		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Use Workforce Deployment Subject Area		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How To Grant GL Data Role to HR VP Users		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Set Up Payroll Based Data Security		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Set Up Payroll Legislative Data Group Based Data		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Set Up HR Supervisor Hierarchy Based Data Security		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Set Up HR Position Hierarchy Based Data Security		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Set Up Department Based Data Security		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* Review Table Partition for Human Resource Analytics		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Set Up Manager Hierarchy Base Security for People		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Configure New Country Code		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Set Up the C_STATE_PROV domain		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to Define New Groups and Mappings for Users and Entities		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0
* How to configure UOMs		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0

1. Log into Functional Setup Manager.
2. Navigate to the Implementation Project that has been created to configure a Functional Area.

If you log in as an Administrator, then you have access to all FSM Tasks. If you log in as a Functional Developer, then the Assigned Implementation Tasks tab provides a list of FSM Tasks that have been assigned to you by the Administrator.

For example, the screenshot below shows a list of FSM Tasks for a Human Resources module with the Task named 'How to Setup Up HR Supervisor Hierarchy Based Data Security' selected.

Implementation Project: IP3

- * How to Set Up Workforce Frozen Snapshots
- * How to Assign Group Account Numbers to Natural Account
- * How to Control Future Transaction Data Visibility
- * How to Use Workforce Deployment Subject Area
- * How To Grant GL Data Role to HR VP Users
- * How to Set Up Payroll Based Data Security
- * How to Set Up Payroll Legislative Data Group Based Data
- * How to Set Up HR Supervisor Hierarchy Based Data Secu
- * How to Set Up HR Position Hierarchy Based Data Security
- * How to Set Up Department Based Data Security
- * Review Table Partition for Human Resource Analytics
- * How to Set Up Manager Hierarchy Base Security for Peop
- * How to Configure New Country Code
- * How to Set Up the C_STATE_PROV domain
- * How to Define New Groups and Mappings for Users and E
- * How to configure UOMs

Rows Selected: 1 | Columns Hidden: 1 | Columns Frozen: 1

3. For each security task, do the following:


a. Click the **Go to Task** icon next to the security task.

Implementation Project: IP3

- * How to Set Up Workforce Frozen Snapshots
- * How to Assign Group Account Numbers to Natural Accour
- * How to Control Future Transaction Data Visibility
- * How to Use Workforce Deployment Subject Area
- * How To Grant GL Data Role to HR VP Users
- * How to Set Up Payroll Based Data Security
- * How to Set Up Payroll Legislative Data Group Based Data
- * How to Set Up HR Supervisor Hierarchy Based Data Secu
- * How to Set Up HR Position Hierarchy Based Data Security
- * How to Set Up Department Based Data Security
- * Review Table Partition for Human Resource Analytics
- * How to Set Up Manager Hierarchy Base Security for Peop
- * How to Configure New Country Code
- * How to Set Up the C_STATE_PROV domain
- * How to Define New Groups and Mappings for Users and E
- * How to configure UOMs

Rows Selected: 1 | Columns Hidden: 1 | Columns Frozen: 1

b. Click the **Help** icon next to the Task name.



The instructions are displayed in a Help topic.

• [HR Duty Role to Oracle BI Applications HR Presentation Catalog Mapping](#)

Introduction

Data can be secured via the HR Supervisor Hierarchy using list variable[s], with associated data roles and security filter[s] which are applied at the physical SQL level as IN (a, b, c,...) statement.

How to choose / assign the Duty Role

Each BI Apps Duty role grants access to one or more subject areas, and is a member of at least one data security role.

You need to map a source role/responsibility to one or more BI Apps Duty roles. For instructions on how this is done refer to the FSM task in [How to Define New Groups and Mappings for Users and BI Roles](#).

HR Data Role to Duty Role Mapping

Note: The following are applicable to HR Supervisor Hierarchy security.

- Follow the instructions in the Help topic.

To complete the task, you typically use one of the security tools such as Oracle Fusion Middleware Control, or Oracle BI Administration Tool. For example, the steps might involve logging into Oracle WebLogic Server Administration Console to provision a set of users.

- In FSM, click **Done**.
- Set the status of the task to **Completed**.

Extending Security in Oracle BI Applications

You can extend the preconfigured Oracle BI Applications security model to match your operational source system. When you extend Oracle BI Applications, you need to ensure that your customizations and any new objects are valid and functional.

You can also leverage the existing Oracle BI Applications security objects when extending data-level security. To do this, copy existing security objects for secured dimensions, such as initialization blocks and Duty Roles, and then modify them to apply to the additional dimensions.

For more information on working with security objects like Duty Roles and initialization blocks, see:

- *Creating and Managing Duty Roles and Application Policies Using Fusion Middleware Control in Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*
- *Working with Initialization Blocks in Oracle Fusion Middleware Metadata Repository Builder's Guide for Oracle Business Intelligence Enterprise Edition*

The general process for extending data-level security for repository objects is as follows:

1. Extend the physical table by adding the attribute by which the dimension or fact needs to be secured. (This step results in a change to the data model.)
2. Populate the relevant attribute value for each row in the fact or dimension table. (This step results in a change to the ETL mapping.)
3. Use the Oracle BI Administration Tool to create an initialization block to fetch the attribute values and populate them into a session variable when each user logs into Oracle BI Applications. You can create a target session variable for the initialization block if the initialization block is not a row-wise initialization block. (This step results in a change to the Oracle BI repository.) For instructions, see *Oracle Fusion Middleware Metadata Repository Builder's Guide for Oracle Business Intelligence Enterprise Edition*.
4. Use Fusion Middleware Control to create a Duty Role in the policy store. Then, restart the Oracle BI Server. For instructions, see *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*.
5. Use the Oracle BI Administration Tool in online mode to set up data filters based on the new role for each of the fact and dimension tables that need to be secured by the attribute you added in Step 1. (This step results in a change to the Oracle BI Repository.) For instructions, see *Oracle Fusion Middleware Metadata Repository Builder's Guide for Oracle Business Intelligence Enterprise Edition*.

- 6. Use the Oracle BI Administration Tool in online mode to restrict object access based on the Duty Role you created in Step 4. (This step results in a change to the Oracle BI Repository.) For instructions, see *Oracle Fusion Middleware Metadata Repository Builder's Guide for Oracle Business Intelligence Enterprise Edition*.
- 7. Use Presentation Services administration to set up Presentation Services catalog privileges based on the Duty Role you created in step 4. For instructions, see *Oracle Fusion Middleware Security Guide for Oracle Business Intelligence Enterprise Edition*.