#### Oracle® Hyperion Web Analysis Studio

User's Guide

Release 11.1.2.2.00



Web Analysis Studio User's Guide, 11.1.2.2.00

Copyright © 1996, 2012, Oracle and/or its affiliates. All rights reserved.

Authors: EPM Information Development Team

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

#### U.S. GOVERNMENT RIGHTS:

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

# Contents

Occumentation Accessibility	. 17
Chapter 1. Getting Started	. 19
About Web Analysis Studio	. 19
Starting Web Analysis Studio	. 19
Web Analysis Studio Interfaces	. 20
Analyze Interface	. 20
Documents and Data Objects	. 21
Filter Panel	. 22
Page Control Panel	. 22
Shortcut Menus	. 23
Exiting Web Analysis Studio	. 24
Chapter 2. Working with Web Analysis Studio Desktops	. 25
Desktop Folders	. 25
Accessing Desktops	. 25
Accessing the Current Specified Desktop	. 26
Accessing Desktops not Currently Specified	. 26
Managing Desktop Presentations	. 26
Opening Presentations from the Desktop	. 27
Editing Presentations from the Desktop	. 27
Deleting Presentation Icons from the Desktop	. 27
Editing Presentation-File Properties from the Desktop	. 28
Setting Desktop Wallpaper	. 28
Refreshing the Desktop	. 28
Chapter 3. Managing Documents	. 29
Documents	. 29
Open Dialog Box	. 29
Opening Documents	. 30
Saving Documents	. 31
Closing Documents	. 31
Modifying Document Properties	. 31

Chapter 4. Managing Presentations	. 33
About Presentations	33
Presentation Access and Document Permissions	33
User and Group Permissions	34
Document and Folder References	34
Presentation Benefits and Considerations	34
Presentation Reference Reconciliation	34
Opening Presentations	35
Closing Presentations	36
Creating Presentations	36
Editing Presentations	. 37
Chapter 5. Managing Files and Folder	. 39
Web Analysis Repository	39
Browser Tab	39
Accessing the Browser Tab	40
Setting the View	40
Filtering the Browser Tab	40
Resizing the Browser Tab	40
Folders	41
User and Group Folders	41
Files	42
Shortcuts and Links	42
Working with Files and Folders	42
Setting File Properties	43
General Properties Tab	43
Advanced Properties Tab	43
File and Folder Shortcut Menus	44
Opening Files	45
Editing Files	45
Adding Files to Favorites	45
Adding Files to the Desktop	46
Copying Files	46
Copying and Pasting Links	46
Moving Files	47
Renaming Files	47
Deleting Files	47
Chapter 6. Creating Documents	. 49
About Documents	49

Date and Text Cell Behavior 50
Creating Documents
Creating Documents from Existing Documents
Creating Auto-Populate Dimension Documents
Modifying Queries
Modifying Filter Dimensions
Data Layout Options
Relational Dimension Header Sort
Label Mode
Selecting Dimension Members
Advanced Member Selection
Advanced Member Selection by Data Source
Searching for Members
Searching For SAP BW Characteristic Values
Locating Dimension Members
Selecting Intervals
Previewing Member Selections
Selecting Members Using Essbase Subsets
Defining Member Subset Selections
Wildcard Characters
Expressions
UDAs
Selecting Financial Management User Defined Fields
Filtering by SAP BW Member Properties
SAP BW Select Top/Bottom
Selecting SAP BW Period to Date
Providing SAP BW Variables
Selecting Financial Management Member Lists
Selecting Substitution Variables
Multiple Substitution Variables
Tips on Syntax
Analysis Tools and Substitution Variables
Creating and Selecting Personal Variables
Creating and Applying Points of View
User POV
Defining Dynamic Time Series Selections
Defining Previous Member Selections
Selecting Attributes
Turning Off Key Figure Attributes

	Creating Calculated and Restricted Key Figures
Chapter 7. Navi	gating Documents
	Navigating Data Objects and Data Sources
	Navigation Methods
	Swapping and Moving Dimensions
	Paging
	Keep Only 84
	Remove Only
	Drilling
	Drill Linking
	Defining Drill Links
	Dragging
	Undo and Redo
Chapter 8. Forn	natting Documents
-	Formatting Options
	Other Kinds of Formatting
	Formatting Order of Precedence
	Data Display Options
	Setting the Label Mode
	Sorting Dimension Headers
	Relational Dimension Header Sort
	Formatting Dialog Box
	Creating Formatting Definitions
	Formatting Data
	Cell Formatting
	Sizing Columns
	Sizing Individual Columns
	Sizing All Columns to a Common Width
	Autosizing Column Width
	Changing and Locking Display Types
	Spreadsheet Options
	Charts and Chart Types
	Pie Charts
	Quadrant Charts         103
	Bubble Charts
	Chart Properties
	General Chart Properties
	Titles Chart Properties

	Axes Chart Properties	)5
	Series Effects Chart Properties	<b>)6</b>
	Series Chart Properties	<b>)7</b>
	Filling Chart Objects	<b>)7</b>
	Line Widths of Zero (0)	<b>)8</b>
	Pie Chart Properties	38
	Bubble Chart Properties	<b>3</b> 8
	Chart Preview	<b>)9</b>
	Selecting Color	10
	Font Properties	10
	Selecting Graphics	11
Chapter !	9. Managing Analysis Tools	13
	Analysis Tools	13
	Related Content	14
	Ordering Analysis Tools	14
	Default Analysis Tools	14
	Activating and Deactivating Analysis Tools	15
	Editing Definitions	15
	Show/Hide Only	15
	Asymmetrical Analysis	15
	Multiple Show/Hide Only Definitions	16
	Differences in Show/Hide Only Definitions	16
	Creating Show/Hide Only Definitions	17
	Traffic Lighting	18
	Financial Intelligence Variations	19
	Assign Limits Shortcut Menu	19
	Creating Traffic Lighting Definitions	20
	Setting Traffic Lighting Opacity	20
	Sorting	21
	Sorting Dialog Box	21
	Creating Sorting Definitions	21
	Restricting Data	22
	Restrict Data Controls	22
	Creating Restrict Data Definitions	22
	Retrieve Only Top/Bottom	24
	Behavior of multiple row dimension member selection	24
	Analysis Tools and Multiple Filter Axis Dimension Members	24
	Creating Retrieve Only Top/Bottom Definitions	25

Ι	Data Formatting	25
	Calculations	:6
	Absolute Value	:7
	Average	:7
	Cumulative	:7
	Difference from Average	27
	Divide	.8
	Linear Regression	.8
	Maximum	.8
	Maximum Value	28
	Minimum	29
	Minimum Value	29
	Multiply	29
	Percent	29
	Percent Difference from Average	0
	Percent of Difference	0
	Percent of Member	0
	Percent of Total	0
	Rank Ascending	1
	Rank Descending	1
	Subtract	1
	Sum	1
	Square Root	1
	Trend	2
	Variance	2
	Variance Percent	2
	Complex Calculations	2
	Creating Calculations	3
	Modifying Calculations	7
	Essbase Attribute Calculations	7
	Creating SAP BW Currency Conversion Definitions	8
(	Creating SAP BW Unit of Measure Conversion Definitions	8
Chantar 10 Evner	ting Decuments and Decembetions	11
	ting Documents and Presentations	
	Exporting Data Options	
	Exporting All Report Objects to Microsoft Office	
	Exporting a Screen to Microsoft Word or PowerPoint	
Е	Exporting to the Chipodata	:4

	Export Data Unformatted
	Export Options
	Exporting the Current Document
	Exporting Documents and Presentations
	Saving As HTML
	Emailing Document Links
Chapter	<b>11. Printing</b>
	Printing Options
	Print Dialog Page Tab
	Print Dialog Header/Footer Tab
	Dynamic Text Labels
	Creating Dynamic Text Labels
	Printing
	Printing all Open Reports
	Print Preview
Chapter	12. Managing Database Connections
	Database Connections
	Database Connections
	Database Connection Access and Document Permissions
	User and Group Permissions
	Creating OLAP and Oracle   Hyperion Database Connections
	Database Connection Properties
	Measures Formatting
	Integrating OLAP and Relational Data
	Defining Relational Drill-through
	Controlling Query Result Set Size
	Creating Relational Drill-Through
	Essbase Database Connections
	Restrict Data
	Retrieve Only Top/Bottom
	Edit Data
	Suppress Missing Rows, Zeroes, and Shared Members
	Label Mode and Alias Tables
	Essbase Drill Settings
	LROs
	Relational Drill-Through
	Integration Services Drill-through
	Essbase Advanced Member Selection

Attribute Dimensions and Attribute Calculations	168
Essbase Metadata Security and Web Analysis Document Design	169
Financial Management	169
Financial Management Related Content	169
Cell Text	169
Line Item Detail	170
Recalculating Financial Management	170
Org By Period	170
Financial Management Advanced Member Selection	170
User Defined Fields	171
Display Entity Currency	171
Financial Management Conventions	171
SAP BW	172
SAP BW Pre-requisites	172
SAP BW Conventions	172
SAP BW Advanced Member Selection	173
SAP BW Features Available in Web Analysis Studio	174
Creating SAP BW Database Connections	174
SQL Server Analysis Services	175
SSAS Prerequisites	175
SSAS Advanced Member Selections	175
SSAS Features Available in Web Analysis Studio	176
SQL Server Analysis Services Connectivity	176
Relational Access	177
SQL Spreadsheet	177
Freeform Grid	177
Relational Drill-through	177
Relational Database Connection	177
Integration Services Drill-through	177
Controlling Query Result Set Size	178
Relational Database Connections	178
Connection Page	178
Select Fact Table Page	179
Relational Cube Editor	180
Creating Relational Database Connections	181
Editing Database Connections	185
Changing Database Connections for Report Objects	185

Chapter 13. 0	Creating Pinboards
	Pinboards
	Pinboards Prerequisites
	Creating a Pinboard Series
	Creating Pins
	Traffic Lighting Control Panel
	Select Traffic Lighting Dimension Dialog Box
	Pinboard Designer
	Creating a Pinboard
	Modifying Pinboards
	Creating a Pinboard Series
	Creating Pins
	Selecting Pins
	Creating Pins
	Editing Pins
	Deleting Pins
	Creating Image Pins
	Creating Color Pins
Chapter 14	Properties COL Correspondences
Chapter 14. (	SQL Spreadsheets         195           SQL Spreadsheets         195
	Creating SQL Spreadsheets
	Creating SQL Spreadsheets
	Enter SQL Query Dialog Box
	SQL Query Builder Wizard
	Select Column Advanced Dialog Box
	Dynamic Text Labels
	Dynamic Text Labels for SQL Spreadsheets
	Creating a SQL Subscription Control
Chapter 15. (	Creating Freeform Grids
	Freeform Grids
	Creating Freeform Grids
	Formatting Freeform Grids
	Creating Formulas for Freeform Grids
	Controlling Freeform Grid Content with Data Objects
Ohantan 40 4	Durathy Ouston Decompute
Chapter 16. (	Creating Custom Documents
	Comparing Web Analysis Studio and EPM Workspace
	Differences between the Two Clients

Font List Differences Between Web Analysis Studio and EPM Workspace 214
Document Designer
Accessing Document Designer
Setting Document Designer Options
Design for HTML
Accessing the Palette Tab
Custom Document Components
Containers
Content Panels
Four Data Objects
Subscription Controls
SQL Spreadsheet and SQL Subscription
Creating Container Panels
Adding Custom Document Components
Undo and Redo
Selecting Components
Selecting Multiple Components
Sizing Components
Moving Components
Cutting, Copying, Pasting, and Deleting Components
Formatting Components
Default Object Properties
Setting the Background
Aligning Components
Creating Hotspots
Creating Split Panels
Nesting Split Panels
Retrieving Focus From Slack Space Split Panels
Linking Components by Query
Common Data Sources
Unlinking Components
Linking Selected Dimensions
Creating Subscription Controls
Subscription Control Dialog Sequence
Creating Subscription Controls
Ordering Dimension Member Controls
Indenting Dimension Member Controls
Saving Subscription Control Selections to User POVs
Enabling a Subscription Control to "Activate from Service Button"

Changing Data Sources	230
Creating Dynamic Dimension Member Controls	230
Creating Dependent Subscription Controls	231
Creating Selection Buttons	231
Ordering Dimension Member Controls	232
Creating Extended Mode Controls	232
Renaming Dimension Member Buttons	233
Creating Dynamic Text Labels	233
Dynamic Text Labels	233
Fixed References	234
Time Format Syntax	234
Examples	235
Custom Document Components	236
Panel Object	236
Using Panels for Object Placement	236
Split Panel Object	237
Label Object	237
Text Area Object	237
Image Objects	238
HTML Browser Object	238
Combo Box Subscription	238
Radio Button Group Subscription	238
Check Box Group Subscription	239
Tab Group Subscription	239
Slider Subscription	239
Selection Button Subscription	240
Multi-level Combo Box Subscription	240
Alias Controller Object	240
Services Button Object	241
SQL Spreadsheet Objects	243
SQL Subscription Objects	243
Minimizing Document Load Times	243
Chapter 17. Editing Data Values	245
Initiating Data Mode and Editing Data	245
Copying, Cutting, and Pasting To and From Microsoft Excel	246
Tips for Edit Data Mode	246
Integration Services Drill-Through	246
Accessing Related Content	247

	Related Content Definitions	:7
	Related Content Dialog Box	8
Chapter 1	.8. Accessing External Media	.9
	Importing Documents and Presentations	.9
	Integration Services Drill-Through	1
	Accessing Related Content	2
	Related Content Definitions	2
	Related Content Dialog Box	3
	Creating Related Content Definitions	3
	Specifying Related Content Dimension Members	3
	Defining Related Content	4
	LROs	5
	Creating LROs	5
	Accessing LROs	6
01	O. C. What Durfamous	_
Cnapter 1	9. Setting Preferences	
	Working with Preference Files	
	Setting Active Preferences	
	Preferences and Formatting Options	
	Creating Preference Files	
	Editing Shared Preference Files	
	Managing Shared Preference Files	
	Finding Preferences	
	General Preferences	
	Home Page Preferences	
	Startup Preferences	
	Folders Preferences	
	Look and Feel Preferences	
	Drilling Preferences	
	Default Formatting Preferences	
	OLAP Server Preferences	
	Database Preferences	
	Alias Tables	
	Setting Alias Tables and Default Logon Method	
	POV Definitions	
	Generic and Specific Documents	
	Replacing Member Selection Statements	
	Default Dimension Layout and Member Selections for New Documents	
	Session-based Points of View	8

Reloading Documents	268
POV Definitions and Personal Variables	268
Personal Variables	268
Generic and Specific Documents	268
POV Definitions and Personal Variables	269
Chapter 20. Web Analysis Administration	271
Defining the Behavior of Drill Link Reports When the Target Report is Closed	271
Web Analysis Utilities	271
Repository Password Encryption Utility	271
Web Analysis Configuration Test Servlet	272
Improving Web Analysis Studio Responsiveness	273
Improving Web Analysis Studio Performance	274
Importing ARU Files to Set User and Active Preferences	274
Processing Order	274
Importing ARU Files	275
ARU Import File Format Supported Tags	275
Creating Personal Variables	276
Removing Personal Variables	276
Creating POV Definitions	277
Removing POV Definitions	278
Adding Personal Database Connections	278
Setting User Preferences	279
Setting Active Preferences	280
Rename Utility	281
Rename Utility Important Considerations	281
Rename Utility Files	282
Rename Utility Installation	282
Rename Utility Map File	283
Using the Rename Utility	286
Renamer.properties	287
Glossary	289

# **Documentation Accessibility**

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <a href="http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc">http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc</a>.

## **Access to Oracle Support**

Oracle customers have access to electronic support through My Oracle Support. For information, visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info or visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs if you are hearing impaired.

1

# Getting Started

#### **In This Chapter**

About Web Analysis Studio	19
Starting Web Analysis Studio	19
Web Analysis Studio Interfaces	20
Analyze Interface	20
Documents and Data Objects	21
Exiting Web Analysis Studio	24

## **About Web Analysis Studio**

Oracle Hyperion Web Analysis Studio is an online analysis, presentation, and reporting interface for multidimensional and relational data.

## **Starting Web Analysis Studio**

The Sun Java plug-in is installed when Web Analysis Studio is first used.

- ➤ To start Web Analysis Studio:
- In your Web browser's Address bar, enter the Web Analysis Studio URL(http://hostname:port/WebAnalysis/WebAnalysis.jsp) and press Enter.

hostname:port is the name of the computer on which Web Analysis Studio is installed with the IP address and port number of the Web Analysis Studio server. The server name (WebAnalysis\_Server) is case sensitive.

The Logon page is displayed.

- 2 Enter a user name and password.
- 3 Click Logon.

The document or interface specified by Startup preferences is displayed. See "Startup Preferences" on page 261.

## **Web Analysis Studio Interfaces**

- Analyze For analyzing, presentations, and reporting; features navigation methods used for investigating information (see Chapter 7, "Navigating Documents").
- Desktop—For accessing presentation document playlists; contains icons that function like Windows desktop shortcuts (see Chapter 2, "Working with Web Analysis Studio Desktops").
- Document Designer—For creating custom documents; provides access to its components through a toolbar displayed below the menu bar (see Chapter 16, "Creating Custom Documents").
- Edit Data—For changing data values and sending changes back to Oracle Essbase; is accessed from the data object shortcut menu (see "Initiating Data Mode and Editing Data" on page 245).

## **Analyze Interface**

Analyze interface components:

- Title bar—Features minimize, maximize, and close buttons, and a shortcut menu.
- Masthead—Identifies the Oracle | Hyperion product, and enables companies to customize and co-brand the client.
- Menu bar—Provides access to commands and subcommands.
- Toolbar—Provides single-click access to tasks and modules.

To show or hide the toolbar, select View, then Toolbar.

Toolbar Button	Description
	Toggle View Pane
	New
	Open
F	Save
	Save As
<b>=</b>	Print
4)	Undo
C	Redo

Toolbar Button	Description
	Home Page
<b>(-</b>	Previous Document
$\Rightarrow$	Next Document
<b>F</b>	Data Layout
ď	Desktop
	Analyze
$ \boxtimes $	Design

- Process bar—Below the toolbar and above the content area. When you begin a complex task with multiple steps, the process bar indicates the number of steps, and the current step. The content area changes with each step, until the process is completed. When not in a process, it indicates the full path to the current document's repository location. The process bar also indicates the current module or interface.
- View pane—Extends down the left side of the interface. Buttons atop the View pane switch View pane tabs:
  - Browser —Presents the repository as a node tree. Only files and folders to which you are granted access are listed. This typically consists of your own folder and group folders to which you belong. When navigation panel items are selected, their contents are listed in the selection panel below.
  - Information Panel Composed of segments summarizing the content area. Each segment features controls and context-sensitive shortcut menus.
  - Palette—Lists the document components in the current document, and their component properties.

To show or hide the View pane, select View, then View Pane.

- Content area Indicates the current module, View pane panel, and document and, when multiple documents are open, displays a tab bar that identifies the open document.
- Status bar Provides applet processing information.

#### **Documents and Data Objects**

Documents display data values returned from the data source in a data object. Multiple data objects of multiple display types can occupy one document.

- Spreadsheet
- Chart
- Pinboard
- SQL spreadsheet
- Free-form grid

You can convert spreadsheets to charts or pinboards. SQL Spreadsheets and free-form grids must be created using the Document Designer. Prerequisites exist for all display types.

#### Topics related to documents and data objects:

- "Filter Panel" on page 22
- "Page Control Panel" on page 22
- "Shortcut Menus" on page 23


#### **Filter Panel**

The Filter panel displays member selections on the filter axis. If no members are selected, dimensions are represented by their first generation members. Filter selections focus the intersections, the data values, and, consequently, the data object analysis.

To show or hide the Filter panel, select View, then Filters.

#### **Page Control Panel**

The Page Control panel indicates members assigned to the Page axis of the spreadsheet. Spreadsheet row and column intersections are organized by Page–axis dimensions.



- To navigate Page dimensions, perform one or both actions:
- Click the Page Control scroll buttons.
- From the drop-down list, select a member name.

**Note:** Multiple-page, unlike single-page lists, which display only page combinations that contain data, multiple-page lists display all possible page combinations. Oracle | Hyperion recommends that, for sparse dimensions, single-page lists be used.

- To separate page dimensions into multiple lists, click the Page Control panel page icon.
- To combine multiple-page dimensions into one drop-down list, click the **Page** icon.

#### **Shortcut Menus**

Data object shortcut menus are context sensitive to headers, cells, dimensions, and data values. It provides immediate access to advanced formatting and function options:

Command	Description	Submenu
Browse	Displays the Dimension Browser dialog box, used for member selection	
Keep Only	Retains only the selected member	
Remove Only	Removes only the selected member.	
Drill	Increases or decreases the level of dimension detail	<ul> <li>Drill</li> <li>Down</li> <li>Up</li> <li>To Top</li> <li>Options</li> </ul>
Analysis Tools	Applies sorting, ranking, filtering, calculation, and conversion definitions to the current selection	<ul> <li>Analysis Tools Manager</li> <li>Traffic Lighting</li> <li>Sort</li> <li>Retrieve Only Top/Bottom</li> <li>Restrict Data</li> <li>Calculation</li> <li>Show/Hide Only</li> <li>Format</li> <li>Currency Conversion (On SAP BW data sources)</li> <li>Unit of Measure Conversion (On SAP BW data sources)</li> </ul>
Related Content	Accesses data from other Oracle   Hyperion sources	
Search	Searches for a member in the selected dimension	
Data display	Sets custom data display behavior	<ul> <li>Selected Member</li> <li>Selected Member First</li> <li>Default Label Mode</li> <li>Product-specific Label Mode</li> <li>Dimension Header Sort (Default, Ascending, Descending, Level, Generation)</li> <li>Show Linked Reporting Object Indicators</li> <li>Suppress (Missing Rows, Shared Members, Zero Rows)</li> </ul>

Command	Description	Submenu
Refresh data	Refreshes the data from the data source	
Export Data	Exports data values	You can export to Microsoft Office, to a tab-delimited text file, or to the operating system clipboard in these formats:
		Query-ready
		Formatted
		Image
		Export Entire Report
		Unformatted
Print	Displays the Print dialog box, used to print the current page of the data object	
Formatting	Displays the Formatting dialog box, used to set header and cell formatting options	
Edit data	Edits cell values and writes them back to Essbase	
Spreadsheet Options	Displays the Spreadsheet Options dialog box used to select options. For charts, opens Chart Properties	
Column Sizing	Sets the column width	Autosize
		Custom width
		Set all columns to this width

# **Exiting Web Analysis Studio**

➤ To exit Web Analysis Studio, select File, then Exit.

2

# Working with Web Analysis Studio Desktops

#### **In This Chapter**

Desktop Folders	25
Accessing Desktops	25
Managing Desktop Presentations	
Opening Presentations from the Desktop	
Editing Presentations from the Desktop	
Deleting Presentation Icons from the Desktop	
Editing Presentation-File Properties from the Desktop	
Setting Desktop Wallpaper	
Refreshing the Deskton	

## **Desktop Folders**

Presentations, playlists of documents, enable documents to be grouped, organized, ordered, distributed, and reviewed. Presentation icons are displayed on the desktop—like application shortcuts are displayed on the Windows desktop.

## **Accessing Desktops**

You can create multiple desktop folders. However, desktop interface can display only the desktop folder that is currently specified by the active preference file. See "Folders Preferences" on page 261.

#### Topics that discuss how to access desktops:

- "Accessing the Current Specified Desktop" on page 26
- "Accessing Desktops not Currently Specified" on page 26

#### **Accessing the Current Specified Desktop**

To access the currently specified desktop, select **Go**, then **Desktop**.

#### **Accessing Desktops not Currently Specified**

- To access desktops that are not currently specified:
- 1 Select File then, Preferences.

The User Preferences dialog box is displayed.

- 2 In Active Preferences, select one option:
  - Use My Preferences—To specify the folder identified in the preferences file of your user folder.
  - Use Shared Preferences—To specify a folder identified in the preferences file of a particular repository location.
- 3 Click Folders.

Desktop Folder specifies the location of the folder that you specified in the previous step.

- 4 Optional: To specify a different repository location for the desktop folder.
  - a. Click the Desktop Folder Browse button (...).
  - b. In Open, navigate to a repository location.
  - c. If there is no desktop folder at the location, click **New Folder**, and in **File name**, enter a name.
  - d. Click OK.

The repository location and folder name are displayed in Desktop Folder.

- 5 Click OK.
- 6 Click Switch to Desktop.

The selected desktop is displayed.

#### **Managing Desktop Presentations**

Only presentations, and links or shortcuts to presentations, display on the desktop. Other files and folders in the desktop folder do not display as icons.

You must be granted access, then locate a presentation, link, or shortcut in the desktop folder for a presentation icon to be displayed.

You cannot hide a presentation from the desktop. If you do not want to display a presentation on the desktop, place it outside the desktop folder.

#### Guidelines for managing presentations:

- Oracle | Hyperion discourages copying presentations to multiple individual desktops. It is difficult to track and synchronously maintain multiple copies in large repositories.
- Oracle | Hyperion recommends distributing shortcuts or links, rather than the original
  presentation. Maintaining only one presentation protects the repository from duplicate
  information and enables presentations to be centrally maintained and updated.

#### Recommended methods for managing presentations:

- 1. Create and maintain a presentation in your user desktop folder.
- 2. Create groups for each required distribution pattern.
- 3. Edit Security file properties to grant access to groups. This is done through Workspace.
- 4. Reference the original presentation by creating links or shortcuts in the group desktop.

#### **Opening Presentations from the Desktop**

To open presentations from the desktop, double-click a presentation icon.

You may be prompted with the Database Logon dialog box (if the selected presentation uses database connections that you do not own). To log on to the database connection, enter the database connection user name and password, and click OK.

All documents of the presentation playlist are loaded in the Analyze interface. Document names are listed in the tab bar. The first document is opened and its tab is highlighted.

**Note:** When you open a presentation from the desktop, all open documents close.

#### **Editing Presentations from the Desktop**

To edit presentations from the desktop, right-click a presentation icon, and select **Edit**.

The Presentation Wizard is displayed, enabling you to edit the presentation icon, contents, and order. See "Editing Presentations" on page 37.

## **Deleting Presentation Icons from the Desktop**

Deleted presentations are removed from your repository desktop folder, but the documents referenced by deleted presentations are not deleted. Deleting a shortcut or link does not remove the associated presentation from your desktop folders.

To delete presentations from the desktop, right-click a presentation icon, and select **Delete**.

See "File and Folder Shortcut Menus" on page 44.

## **Editing Presentation-File Properties from the Desktop**

Presentation-file properties enable you to rename presentations and enter file descriptions.

To edit presentation file properties, right-click a presentation icon, and select **Properties**.

The File Properties dialog box is displayed. The General tab enables you to rename the presentation and enter a description. The Advanced tab enables you to set document properties. See "Setting File Properties" on page 43.

## **Setting Desktop Wallpaper**

You can load an image as desktop wallpaper, and specify how the image covers the desktop.

- To set desktop wallpaper:
- 1 Right-click the desktop (not an icon), and select Wallpaper.

The Select Graphic dialog box is displayed.

- 2 Click Load to browse for a graphic file, then click Open to select the preferred file.
- 3 In **Style**, select an option:
  - Center—Centers the graphic on the desktop
  - Stretch—Stretches the graphic across the desktop
  - Tile—Repeats the graphic across the desktop
  - Top-Left—Displays the graphic in the top left corner of the desktop

You can set the desktop wallpaper for the current desktop using the preferences Look and Feel tab.

## **Refreshing the Desktop**

To refresh the desktop, right-click the desktop, and select **Refresh**.

3

# **Managing Documents**

#### **In This Chapter**

Documents	29
Open Dialog Box	29
Opening Documents	30
Saving Documents	31
Closing Documents	31
Modifying Document Properties	31

#### **Documents**

Documents format and display data values. When documents are saved, they become multipurpose files for presentation, analysis, and distribution in numerous formats.

#### Document tasks:

- "Opening Documents" on page 30
- "Saving Documents" on page 31
- "Closing Documents" on page 31
- "Modifying Document Properties" on page 31

#### Additional document procedures:

- Renaming documents—See "File and Folder Shortcut Menus" on page 44.
- Distributing documents—See "Exporting Documents and Presentations" on page 141, "Printing" on page 149, and "Setting File Properties" on page 43.

#### **Open Dialog Box**

The Open dialog box provides an interface for retrieving repository files.

To access the Open dialog box, select **File**, then **Open**.

Control	Description
Location	Indicates the current repository folder and provides a list of previously visited folders (stored as a series).

Control	Description
Back	Moves to the previous folder.
Forward	Moves to the next folder in the series.
Up	Moves up one folder level in the repository.
Favorites	Moves to the current Favorites folder.
Favorites List	Lists links to all available Favorites folders.
Home	Moves to the current Home folder.
New Folder	Creates a folder at the current location.
View	Changes between Detail, List and Icon views.
Favorites frame	Displays shortcuts to the contents of Favorites folders.
Selection frame	Lists the current folder's contents, and provides a menu that includes Copy, Cut, Rename, Delete, View, and Properties.
File Name	Indicates the name of the current folder.
Files of Type	Indicates the file-type filter (used to display the contents of the folder in the selection frame).

## **Opening Documents**

- ➤ To open documents:
- 1 Select File, then Open.

The Open dialog box is displayed.

- 2 From Files of Type, select Web Analysis Document.
- 3 Navigate to a document.
- 4 **Optional**: To sort large lists of documents and presentations:
  - a. Right-click the selection frame, and select View, then Detail.
    - The selection frame features three columns: Name, File Type, and Last Modified.
  - b. Click a column header once, to sort the contents of the selection frame in ascending order, or twice, to sort the contents of the selection frame in descending order.

#### 5 Perform an action:

- To select a document from the selection frame, click the document name or icon.
- To select multiple documents in a series, from the selection frame, click a document name and press and hold Shift while selecting another document name. The first selection, the last selection, and all documents between the first and last selection are selected.

- To select multiple documents, not necessarily in a series, press and hold the Ctrl key while clicking document names in the selection panel.
- To deselect items, click outside the Name column or on empty white space.
- To select an item and dismiss the **Open** dialog box, double-click the item.
- 6 Click OK.
- 7 If prompted, in Database Login, enter a user name and password for the database connection, click Save User ID and Password, and click OK.

The selected document is displayed in the content area.

## **Saving Documents**

Saving stores information, such as the query, the document properties, and the formatting. Saving does not send data value updates to the data source. See "Editing Data Values" on page 245. You can save documents only into folders that you can access.

**Note:** You can create hotspots that save the current document. See "Creating Hotspots" on page 225.

- To save documents:
- 1 Select an option:
  - To save previously saved documents, select File, then Save.
  - To save new documents, select File, then Save As.
- 2 In the Save As dialog box, define the properties of the saved document and click OK.

## **Closing Documents**

- To close the active document, select File, then Close.
- To close all open documents, select File, then Close All.

#### **Modifying Document Properties**

Document properties impact display and use. You set document properties in the Advanced tab of the File Properties dialog box.

- To modify document properties:
- 1 Right-click the Content tab for a document, and select **Properties**.
- 2 Select the Advanced tab.

The Advanced tab shows the document properties for the current document.

3 **Optional:** To prevent use of particular methods, select one or more **Document Usage** options.

You can prevent drilling up, drilling down, accessing shortcut menu, and changing display type.

4 Click OK.

4

# **Managing Presentations**

#### **In This Chapter**

About Presentations	33
Document and Folder References	34
Opening Presentations	35
Closing Presentations	36
Creating Presentations	36
Editing Presentations	37

#### **About Presentations**

Presentations are lists of references to documents in the repository.

#### Topics that discuss presentation permissions:

- "Presentation Access and Document Permissions" on page 33
- "User and Group Permissions" on page 34

#### **Related Topics**

"File and Folder Shortcut Menus" on page 44.

"Exporting Documents and Presentations" on page 141

#### **Presentation Access and Document Permissions**

Because document access is independent of presentation access, it is possible to distribute presentation that contain documents that users cannot access.

Documents in presentations are listed to all users with list permissions (to the presentations) but can be opened only by users with read permissions.

Document permissions that withhold access prevent all access to the document, directly or through a presentation. Presentation permissions that withhold access do not prevent access to a document.

<sup>&</sup>quot;Printing" on page 149

<sup>&</sup>quot;Setting File Properties" on page 43.

#### **User and Group Permissions**

Users can access presentations assigned directly to them or assigned to a group to which they belong.

When presentations are assigned to groups, the documents in the presentations must also be assigned to the groups. Otherwise, group members can access the presentation but cannot access its documents (unless they have individual user access).

To mitigate the risk of conflicting permissions, store presentations with the documents that they reference. Whenever possible, distribute documents and presentations to groups. It is easier to set permissions for all files in a folder and all users in a group than it is to manage permissions for individual files and users.

#### **Document and Folder References**

You can add two kinds of references to presentations:

- **Document**—When you add a document directly to a presentation, a reference to a unique document identifier is created in the presentation. The presentation can present the document from wherever it is located.
- Folders—When you add a folder to a presentation, the folder reference is added directly to the **Presentation Content**, but documents in the folder are dynamically referenced. Documents added or removed from the folder are automatically added to or removed from presentations that reference the folder.

**Note:** You cannot dynamically reference descendant folders or presentations.

#### **Presentation Benefits and Considerations**

Web Analysis Studio synchronizes presentation playlists with folder content. Therefore, you can modify folder content without editing the presentation that references the folder. You must limit write access to the folder to prevent other users from adding content to the folder, and thus, to the presentation.

For document references, presentation content is fixed.

#### **Presentation Reference Reconciliation**

When presentations are opened, Web Analysis Studio attempts to reconcile document references and then folder references.

If a file is copied and the original file is deleted, Web Analysis Studio cannot locate the unique file identifier. In this case, Web Analysis Studio searches for files of the correct name at the same location. If a reference cannot be found, the Presentation Wizard displays the reference in red.

#### **Opening Presentations**

- ➤ To open presentations:
- 1 From the menu bar, Select File, then Open.

The Open dialog box is displayed and lists the current folder contents, specified by location.

- 2 From Files of Type, select Web Analysis Presentation .
- 3 Navigate to a presentation.

As you navigate, the selection frame lists the files and folders indicated by Files of Type.

- 4 **Optional:** Sort large lists of documents and presentations using these options:
  - a. Right-click the selection frame and select View, then Detail.
     The selection frame features three columns Name, File Type, and Last Modified.
  - b. Click a column header to sort the selection frame contents in ascending order, by that column.
  - c. Click the column header again to sort the selection frame contents in descending order, by that column.
- 5 Select a presentation (or additional documents and presentations) using these options:
  - To select a presentation from the selection frame, click the presentation name or icon.
  - To select a series of document or presentations from the selection frame, click a file name and press and hold **Shift** while selecting another file name. The first selection, the last selection and all files in between are selected.
  - To select multiple files, not necessarily in a series, hold down **Ctrl** while clicking file names in the selection panel.
  - To deselect items, click outside the Name column or on empty white space.
  - Double-click to select and dismiss the Open dialog box.
- 6 Click OK.

If the first document in a presentation uses a Database Connection requiring log on, you are prompted by the Database Login dialog box.

7 If prompted by the **Database Login** dialog box, enter a User ID and password for the Database Connection. Select the **Save User ID and Password** option to store log on credentials for the Database Connection, and click **OK**.

The selected presentation (and other selections) are displayed as content tabs below the content area. The first document in the selected presentation is opened and displayed as the current document.

In the Open dialog box, you can select multiple documents and presentations. If you select multiple documents, documents are opened in the order in which they are listed in the Selection frame.

If you open multiple presentations containing the same document, only the first instance of the document is opened. It may appear that the document did not open or opened in the wrong order. Only one instance of a document can be opened (and modified).

## **Closing Presentations**

To close all opened presentations, select File, then Close All.

For previously saved changed files, a Save Changes prompt is displayed. For files not previously saved, the Save As dialog box is displayed. See "Saving Documents" on page 31.

#### **Creating Presentations**

- To create presentations:
- 1 Select File, then New, then Presentation.

The Process bar displays steps for creating presentations: Content, Order, and Image. The Presentation wizard displays the View Pane Browser tab, from which you select documents and folders from the repository.

- Navigate to a location that contains a document, folder, or link, and add one or more files to the presentation playlist by performing one or more actions:
  - Select a file on the Browser tab, and click the **right arrow** button.
  - To select consecutively listed documents, select a file name, press **Shift** and select another file name. The first selection, the last selection, and all files between the first and last selection selected. Click the **right arrow** button.
  - To randomly select documents, press and hold **Ctrl** while selecting multiple file names. The files you click are selected. Click the **right arrow** button.

Your selections are displayed in the Presentation Content list.

- 3 Optional: To remove content from the selected presentation content pane, on the Content page, perform one or more actions:
  - Select a file name, and click the **left arrow** button.
  - Select a file name, press **Shift**, select another file name, and lick the **left arrow** button.
  - To randomly select documents, press and hold Ctrl while clicking multiple file names.
     The files you click are selected. Click the left arrow button.
- 4 **Optional:** To reorder the selected content, on the Order page, perform one or more actions:
  - Select a file and click an **Up** or **Down** arrow button.
  - Select a file name, press **Shift**, select another file name, and click the **Up** or **Down** arrow.
  - Press and hold **Ctrl** while selecting multiple file names, and click the **Up** or **Down** arrow..
- **Optional:** To select an image for the presentation icon:

a. Click Select Graphic.

The Open dialog box is displayed.

- b. Navigate to a folder that contains a JPG or GIF image file, and select a file.
- c. Click Open.

Your image is displayed as the desktop button image on the Presentation wizard.

6 Click Finish.

The Save As dialog box is displayed that lists the current folder contents by location.

- 7 Navigate to the folder into which you want to save your presentation and, in Filename, enter a name.
- 8 Click OK.

The presentation is saved to the specified location, using the specified name.

# **Editing Presentations**

Options for modifying presentations:

- You can edit a presentation by changing the content, order, and presentation icon and saving these changes.
- You can also copy a presentation and paste it to another location, where it can be modified without impacting the original presentation. You can not save a presentation under another name or to another location (Save As).

See "Copying Files" on page 46.

- To modify presentations:
- 1 Right-click a presentation file name and select **Edit**.

The Presentation Wizard is displayed with the View Pane Browser tab.

- 2 **Optional:** In the View Pane **Browser** tab, navigate to a location containing a document, folder, or link that you would like to add to the presentation.
- 3 **Optional:** To add a file to the presentation playlist, perform one action:
  - Select a file on the Browser tab, and click the **right arrow** button.
  - To select a series of files in a folder, click a file name and press **Shift** and select another file name. The first selection, the last selection and all files in between are selected. Click the **right arrow** button.
  - To select multiple documents in a folder that are not necessarily in a series, hold down **Ctrl** while clicking multiple file names. The files you click are selected. Click the **right arrow** button.

Your selections display in the Presentation Content list.

- 4 Optional: To remove content from the selected presentation content panel, perform one action:
  - Click the file name on the Content page and click the **left arrow** button.

- Right-click a file on the Content page and select **Remove** from the shortcut menu.
- To deselect a series of files, click a file name and press Shift and select another file name.
   The first selection, the last selection and all files in between are selected. Click the left arrow button.
- To select multiple documents that are not necessarily in a series, hold down **Ctrl** while clicking multiple file names. The files you click are selected. Click the **left arrow** button.

### 5 Optional: Click Next.

### 6 Optional: To reorder the selected content, perform these actions:

- Select a file on the Order page and click **Up** or **Down** arrow button to reposition the file in the playlist.
- Right-click a file and select Move Up or Move Down from the shortcut menu.
- To select a series of files, click a file name and press **Shift** and select another file name. The first selection, the last selection and all files in between are selected. Click an **Up** or **Down** arrow button to reposition the files in the playlist.
- To select multiple documents in a folder that are not necessarily in a series, hold down Ctrl while clicking multiple file names. The files you click are selected. Click an Up or Down arrow button to reposition the files in the playlist.

### 7 **Optional:** To select an image for the presentation icon:

a. Click Select Graphic.

The Open dialog box is displayed.

- b. Navigate to a folder containing a JPG or GIF image file, and click to select the file.
- c. Click Open.

Your image is displayed as the **Desktop Button Image** on the Presentation wizard. Clicking **Clear**, restores the default desktop button image.

8 Click Finish.

# 5

# Managing Files and Folder

### **In This Chapter**

Web Analysis Repository	39
Folders	41
User and Group Folders	41
Files	42
Shortcuts and Links	
Working with Files and Folders	42
Setting File Properties	43
File and Folder Shortcut Menus	

# **Web Analysis Repository**

The repository stores system data in relational database tables—at a shared, local area network location. In the View Panel Browser tab, Web Analysis Studio presents the repository as a file management system.

# **Browser Tab**

The Browser tab is one of three View Pane tabs.

The navigation panel of the Browser tab displays the repository as a node tree. You see only the files and folders to which you are granted access, typically, your folder and folders of groups to which you belong.

You can expand, collapse, explore, and select from the repository in the course of your analysis, presentation, and reporting. The Selection frame of the Browser tab presents the contents of the folder currently selected in the Navigation frame.

# **Accessing the Browser Tab**

To display the View Pane Browser tab from the menu bar, Select View, then View Pane, then click.

# **Setting the View**

You can display repository contents in the Browser tab in three ways:

- Detail—Displays file names in a vertical list and provides file type and last modified information.
- Icon—Displays file icons horizontally and vertically
- List—Displays file names in a vertical listing
- To set the view, select View, and one of three options: Icon, List, or Detail.
- To refresh the interface, select View, then Refresh.

# **Filtering the Browser Tab**

You can restrict the objects displayed in the Browser tab and thus reduce the number and kinds of items displayed in the selected folder.

- To filter the Selection frame of the Browser tab:
- 1 Select View, then Display Items of Type.
- 2 Select one option:
  - All—displays all files, regardless of type
  - Document—displays only documents
  - Presentation—displays only presentations
  - Database Connection—displays only database connections

# **Resizing the Browser Tab**

You can resize the Navigation frame, the Selection frame and the View Pane Browser tab.

- To resize vertically the Navigation and Selection frames of the Browser tab, hover the cursor over the border between the frames, and when it changes to a double arrow, click and drag.
- To resize horizontally the Browser tab, hover the cursor over the border between the View Pane and the Content area, and, when it changes to a double arrow, click and drag left or right.
- To show or hide the View Pane, select View, then View Pane.

# **Folders**

By default, Web Analysis Studio installs three folders:

- The *root* folder, specified by a slash (/), contains all other files and folders.
- The *Groups* folder, directly below the root folder, is intended to contain all group folders. The Groups folder contains a default group folder, named *Everyone*, that enables users to be managed collectively.
- The *Users* folder, directly below the root folder, is intended to contain all user profile folders.

While administrators can see all folders and files, you can see only the files and folders to which you are granted access, typically your own folder and folders of groups to which you belong.

**Note:** As with all file systems, though the default directories, folders, and files were designed for a purpose there is nothing to prevent you from diverging from this original design. Consider this, when giving users and groups access and permissions to the repository. See "Setting File Properties" on page 43.

# **User and Group Folders**

User folders and group folders contain this standard set of folders:

Databases—Database connections.

Desktop—Presentations to be displayed on the desktop

Favorites—Most commonly sought content

Every user profile and group profile features a Favorites folder. Files in the Favorites folder are presented for quick access in the Open dialog box, the Save dialog box, and under the Go / Favorites menu, based on the active user specified by preferences.

Reports—Other repository files

Profiles—Preference files used to customize application look-and-feel and behavior

# **Files**

User folders, group folders, and their subfolders organize and manage files, shortcuts, and links. There are four kinds of files:

- Database Connection ——Define the terms, conditions and method for connecting to a
- Oracle Hyperion Web Analysis Documents —Synthesize formatting definitions and analysis tools definitions with the data values returned from the data source.
- Presentations ——Playlists of documents, enabling documents to be grouped, organized, ordered, distributed, and reviewed.
- Preferences—Customize application look and feel, and behavior.

Although multiple preference files can be defined, only one can be current. You can also change the active preference file to a preference file shared by users.

# **Shortcuts and Links**

Shortcuts, which are used for navigation, can link to folders, files, or links. Shortcuts do not grant access to their targets.

If you encounter a broken shortcut (the result of a target being renamed or moved or a location deleted), use caution. Another administrator may be updating a dynamic target. You restore a broken shortcut by creating an object with the specified name at the specified location.

A unique identifier is assigned to every element in the repository. Links use the identifiers to reference folders, files, shortcuts, and other links. Links are fixed, presenting their target in the current folder, regardless of where the targets are located or whether the targets are renamed.

Links simplify maintenance by enabling information stored at one location to be accessed from multiple locations.





If you encounter a broken link (the result of a deleted target), delete the link. You cannot restore a broken link. You must recreate it.

Links to broken links are displayed as broken links, even though they are operating correctly. You must identify and repair the broken link in the chain.

# **Working with Files and Folders**

The repository management system supports most standard operations.

- To expand a folder in the Navigation frame, click the plus sign (+) node next to the folder.
- To expand a folder and display its contents in the selection frame, double-click the folder icon or name.
- To collapse an open folder, click the minus sign (-) node.
- To select a file, select the file icon or its name.
- To select a series of files, select the first file in the series, press **Shift** and select the last file in the series.
- To select multiple files that are not in a series, press and hold **Ctrl** while selecting the files.

# **Setting File Properties**

All repository elements have general and users/groups properties.

To display file properties of repository files in the Browser tab, right-click a file name, and select **Properties**.

File properties can be set on the following tabs:

- "General Properties Tab" on page 43
- "Advanced Properties Tab" on page 43

# **General Properties Tab**

- Name—Artifact name
- Description—User-supplied description
- Type—Indicates whether the artifact is a folder, file, shortcut, or link (read-only)
- Owner—File creator, a user who can change permissions by default (read-only)
- Location—Repository location of the file (read-only)
- Created—The time that the artifact was created
- Modified—The time that the artifact was last modified

# **Advanced Properties Tab**

Advanced file properties apply to all users and groups:

 HTML Client Override Template—JavaServer Pages (JSP) template used to convert documents to HTML Web pages when opened in Oracle Hyperion Enterprise Performance Management Workspace

- HTML Export Override Template—JSP template used to convert Web Analysis to HTML Web pages using File, then Save As HTML; output location is specified in the Save dialog box
- HTML Batch Export Template—JSP template used to convertWeb Analysis to HTML Web pages when running batch export programs
- **Document Usage**—Restricts subsequent users from drilling up, drilling down, accessing shortcut menus, and changing the display type

### **Notes on JSP Templates**

- Web Analysis Studio converts Web Analysis to HTML Web pages using predefined JSP templates.
- All JSP templates must be located in your application server's Web Publishing template subdirectory (wp\_templates), and all templates must be specified by name (including the JSP file extension).
- When no JSP template is specified, Web Analysis Studio uses the report\_publish.jsp template in \webapps\WebAnalysis\templates.
- When you publish presentations, a directory named for the presentation is created in the application server's Web publishing output directory (wp\_output), if no other directory is specified. When you use the Batch Utility, the default output file location is the application server's Web publishing output directory (wp\_output), if no other directory is specified; however, you can enter a parameter that specifies an alternate output location.

### **Related Topics**

"Modifying Document Properties" on page 31

"Changing and Locking Display Types" on page 101

# **File and Folder Shortcut Menus**

Files and folders share a shortcut menu. Menu items are enabled and disabled based on user profile permissions, object type, and file state.

### Topics that discuss shortcuts:

- "Opening Files" on page 45
- "Editing Files" on page 45
- "Adding Files to Favorites" on page 45
- "Adding Files to the Desktop" on page 46
- "Copying Files" on page 46
- "Copying and Pasting Links" on page 46
- "Moving Files" on page 47
- "Renaming Files" on page 47

• "Deleting Files" on page 47

# **Opening Files**

Opening functionality differs by file type and access permissions.

To open a file, right-click the file name, and select **Open**.

File Type	Open Command Result
Document The document opens in the content area.	
Database Connection	Opens an auto-populate dimension document. The database connection is used. The highest aggregate members of the time and measures dimensions are used to populate the row and column axes of a spreadsheet.
Presentation	All documents in the presentation playlist open in the content area.
Shortcut or Link	Depending on the file type of the target file, a document, a spreadsheet, or all documents in a presentation open.

# **Editing Files**

Editing functionality differs by file type and permission access.

To edit files, right-click a file name, and select Edit.

File Type	Edit Command Result
Document	The document opens in Document Designer, enabling you to create a custom document.
Database Connection	The database connection wizard opens, enabling you to set data source parameters.
Presentation	The Presentation Wizard opens.
Shortcut or Link	Depending on the file type of the target file, a document or wizard opens.

# **Adding Files to Favorites**

All user and group profiles include a Favorites folder. Files in the Favorites folder are listed in the Open and Save dialog boxes, and under the Go / Favorites menu.

To create shortcuts to files in the Favorites folder, right-click a file name, and select **Add** To, then Favorites.

**Note:** Because shortcuts are location based, their target files must remain at their original locations. Links, however, reference files through unique identifiers that travel with the files. To create a file link in the Favorites folder, use the **Copy** / **Paste Link** shortcut menu option.

# **Adding Files to the Desktop**

All user and group profiles include a desktop folder. The desktop folder contains the presentation for which icons are displayed on the desktop. While all files can be saved to the desktop folder, only presentation icons are displayed on the desktop.

All users and groups have a desktop folder. The current desktop folder is the folder of the active user.

To create shortcuts to presentations in the desktop folder, right-click a file name, and select Add To, then Desktop.

# **Copying Files**

When you copy files, other than for links, to other locations, the files adopt the file permissions set for the new location (the new folder). Therefore, you need not coordinate file permissions of copied files with file permissions of target locations.

- To copy files and paste them as files or shortcuts:
- 1 Right-click a file name, and select Copy.
- 2 Navigate to the location where you want to create a copy of the original file.
- 3 Right-click the View Pane Browser tab selection frame and select an option:
  - Paste—Copies the original file
  - **Paste Shortcut**—Creates a reference to the location of the original file.

**Note:** Files copied to other locations adopt the file permissions set for the new location. To control access to copied files, consider copying links, not files. You van grant unlimited access to links, while restricting access to their target files.

# **Copying and Pasting Links**

When you paste copied files as a link, you must coordinate access between the links and the original files. You do not want to create links to files that cannot be accessed, or links with universal access permissions that override restricted access.

If no file permissions are set, the target files and the links are assigned Read access permissions.

- To copy files and paste them as links:
- 1 Right-click a file name and select Copy.
- 2 Navigate to the preferred location.
- 3 Right-click the Selection frame of the View Browser tab, and select Paste Link.

A link is created at the current location.

# **Moving Files**

When you cut and paste (or move) a file, the file retains its original file permissions without regard for the file permissions of its new folder location.

- ➤ To move files:
- Right-click a file name, and select Cut.
- Navigate to the preferred location.
- Right-click the Selection frame of the View pane Browser tab, and select Paste.

# **Renaming Files**

To rename files, right-click the file name, and select **Rename**.

# **Deleting Files**

To delete files, right-click the file name, and select **Delete**.

47

# 6

# **Creating Documents**

### **In This Chapter**

About Documents	49
Modifying Queries	56
Selecting Dimension Members	59
Searching for Members	63
Searching For SAP BW Characteristic Values	64
Locating Dimension Members	65
Selecting Members Using Essbase Subsets	66
Selecting Financial Management User Defined Fields	68
Filtering by SAP BW Member Properties	69
SAP BW Select Top/Bottom	70
Selecting SAP BW Period to Date	71
Providing SAP BW Variables	72
Selecting Financial Management Member Lists	72
Selecting Substitution Variables	72
Creating and Selecting Personal Variables	73
Creating and Applying Points of View	74
User POV	76
Defining Dynamic Time Series Selections	76
Defining Previous Member Selections	77
Selecting Attributes	77
Turning Off Key Figure Attributes	78
Creating Calculated and Restricted Kev Figures	78

# **About Documents**

Documents display data values returned from the data source in a data object. Multiple data objects can occupy a document, and each data object's display type can differ:

- Spreadsheet
- Chart
- Pinboard
- SQL Spreadsheet

• Free-form grid

Each display type has prerequisites.

- Pinboards are generated from spreadsheets and charts, and they require traffic lighting definitions. See "Creating Pinboards" on page 187.
- Because custom documents use component combinations that differ, there is no single process for creating custom documents. See "Creating Custom Documents" on page 213.
- SQL spreadsheets enable you to query a relational data source, and display the returned data values on a custom document. You must understand how to compose a SQL query to create a SQL spreadsheet. See "Creating SQL Spreadsheets" on page 195.
- Free-form grids enable you to combine data values from multiple data sources in one data object. Free-form grids leverage custom document database connections. See "Creating Freeform Grids" on page 205.
- You can change spreadsheets into a wide variety of charts. See "Changing and Locking Display Types" on page 101.
- Finally, each display type has formatting options. See "Formatting Options" on page 91.

To create a document you are required to specify:

- Data source—Provides data values, including date and text as data in cells. See "Date and Text Cell Behavior" on page 50
- Data object—Displays these values
- Query—Gets data values from the data source and returns them to the data object.

You can set properties that customize each element.

The database connection wizard specifies the type of data source, logon credentials, database applications, dimension formatting and drill-through properties.

Each data object can be set to a display types that features formatting options.

Queries can be explicit, requesting information on dimension members, or dynamic, requesting information about a dimension member that satisfies a set of criteria.

### Topics that discuss the three primary ways to create documents:

- "Creating Documents" on page 51
- "Creating Documents from Existing Documents" on page 54
- "Creating Auto-Populate Dimension Documents" on page 55

# **Date and Text Cell Behavior**

Data cells can store and display text and dates as data in specific Measure members that have been defined in the outline. Essbase Report Scripts allow for the query and display of these Measure types.

- If a Text or Date measure exists in a Filter, multiple selections are disabled.
- If a Text or Date measure is selected in a Page, Analysis Tools cannot be rendered or applied; only formatting can be applied (but not conditional formatting).
- Analysis Tools, where the context (selected member in row or column) is a Text or Date Measure, no Analysis Tools can be created except for Formatting.
- Analysis Tools, where the selected members are a Text or Date Measure (for example, column of Year dimensions is AT context, date measures in rows), Sort and Top/Bottom will render based on what Essbase returns. Other Analysis Tools will not be applied, except for Formatting.

# **Creating Documents**

A wizard guides you through creating Web Analysis Studio spreadsheets and charts. The wizard requires that you know where a database connection is located, and have permission to use it.

### To create a document:

### 1 Perform one:

- Select **File** then, New then, Document Wizard.
- Click , and select **Document Wizard**.
- Press Ctrl+Shift+N.

The Process bar displays steps for creating documents. Because the repository stores document definitions and not document data, you must identify a data source, and the parameters for connecting to it.

### 2 Perform one:

- In the text area, enter the path from the root directory (/) to a database connection, including the file name.
- Click Browse, select a database connection file from the Open dialog box, and click OK.
- Optional: Select Auto-Populate Dimensions to automatically populate and display a simple spreadsheet.

Selecting the Auto-Populate Dimension option and clicking Finish skips the remaining steps in the process. Auto-Populate Dimension uses the highest aggregate members of the time and measures dimensions to populate the rows and columns axes of a spreadsheet. This is the quickest method to display a simple spreadsheet using the wizard.

4 **Optional:** Select **Use Point of View** to populate the query from a predefined point of view (POV) definition.

Selecting Use Point of View and clicking Next inserts the dimensions and members that are of interest to you in documents. You can define multiple POV definitions, but Use Point of View only applies the current POV set in preferences.

Selecting Auto-Populate Dimension and Use Point of View and clicking Finish skips the remaining steps in the process and displays a simple spreadsheet using the active POV.

### 5 Click Next.

In Step 2: Select Row Dimension, you must select the dimensions to be used on the Rows axis. You must have at least one Row axis dimension and one Column axis dimension.

- 6 Move a dimension name from Filters to Rows:
  - Double-click a dimension name in Filters.
  - Select a dimension name in Filters and click the right arrow button.

The dimension name is displayed in the Rows frame. If no POV definition is applied in Step 1, the highest aggregate member in this dimension is used. If a POV definition is applied, its member selections are used.

7 Optional: To specify dimension member selections, double-click the dimension name hyperlink in Rows.

The Dimension Browser dialog box is displayed. The dimension is presented as a node tree in the Browse frame. You must select dimension members in Browse and move them to Selections:

- To expand or contract the dimension hierarchy:
  - o Double-click dimension member names
  - O Click the plus sign (+) or minus sign (-).
- To select dimension members, click the dimension member name.

A check mark is displayed in the check box of selected members, and the member name is displayed in the Selections list.

- To select dimension members dynamically, right-click a dimension member name and select an advanced member selection method.
- You can set the label mode for each dimension to the default label, an ID label, or the alias table description set in Database Preferences dialog box, through preferences.

See "Selecting Dimension Members" on page 59.

- Click **OK** to dismiss the Dimension Browser dialog box and return to the Wizard.
- 8 After indicating all Rows axis dimensions, and defining their member selections, click Next.
- 9 Using the same methods used to define Rows, move a dimension name from Filters to Columns.
- 10 Optional: Using the same Dimension Browser methods, double-click the dimension name hyperlink in Columns to specify member selections for the Column axis.
- 11 Click Next.

In Step 4: Select Page Dimensions, you can select dimensions to be used on the Page axis. While all intersections in the document are relative to all dimension member selections, you can organize these row and column intersections by page dimension members.

- 12 Optional: Using the same methods used to define Rows and Columns, move a dimension name from Filters to Pages.
- 13 Optional: Using the same Dimension Browser methods, double-click the dimension name hyperlink in Pages to specify member selections for the Page axis.

### 14 Click Next.

In Step 5: Customize Filters, you select dimension members to be used on the Filters axis.

All cube dimensions participate in every spreadsheet intersection, regardless of the axis to which dimensions are assigned. The arrangement of intersections is defined by the Rows, Columns and Pages axes. The data values displayed at each intersection are determined by the member selections.

all intersections in the data object are relative to Filter dimension member selections. Filter dimension member selections focus the intersections, the data values, and consequently the data object analysis.

Cube dimensions left in the Filter axis are by default represented by the highest aggregate dimension member defined in the data source outline. If a POV definition is applied, its member selections are used. If you make Filter member selections, all intersections are relative to these selections.

- 15 **Optional:** To display the Dimension Browser for Filter axis dimensions, perform one:
  - Select a Filter dimension and click Customize.
  - Double-click a dimension name hyperlink in Filters.
- 16 Optional: Using the same Dimension Browser methods, make Filter axis dimension member selections and click OK.
- 17 Click Next.

In Step 6: Set Options, you can set a variety of document options

18 Optional: In the Select Layout list, select one:

Chart—Displays the result set as a chart data object.

Spreadsheet—Displays the result set as a spreadsheet data object.

**Vertical Combination**—Displays the result set as a chart data object and a spreadsheet data object stacked vertically.

**Horizontal Combination**—Displays the result set as a chart data object and a spreadsheet data object arranged side-by-side.

Custom—Displays a blank palette

You can change the display type of the Vertical Combination and Horizontal Combination layouts; for example you can convert the spreadsheet to a chart type. The objects, however, are linked and maintain a coordinated context.

In case you select a layout, the Data Layout dialog box is displayed.

- Select dimensions and members and click OK to generate a Web Analysis document.
- 19 Optional: You can set the default Label mode to display dimension member IDs, or the alias table description set in database preferences.

This centrally sets all dimensions using the default Label mode to the same setting.

20 Optional: To suppress the display of one or more type of data, click the corresponding check box.

Missing Columns—Columns of data comprised of missing values.

Missing Rows—Rows of data comprised of missing values.

**Shared Members**—Dimension members that are used in multiple locations of one hierarchy.

Zero Rows—Rows of data comprised of zero (0) data values.

21 Optional: To suppress the display Linked Reporting Object Indicators, click the corresponding check box.

**Linked Reporting Object Indicators** are orange triangles indicating Related Content definitions in Essbase.

22 Optional: To augment the query with a server-based Retrieve Only Top/Bottom analysis, click the corresponding button.

See "Retrieve Only Top/Bottom" on page 124.

23 Optional: To augment the query with a server-based Restrict Data analysis, click the corresponding button.

See "Restricting Data" on page 122.

24 Click Finish to submit the query to the data source.

The data source is queried. The result set returned is displayed as a data object on a document.

# **Creating Documents from Existing Documents**

When you save a document with other names or to other locations, you use the data source, data object, and query defined by a document. This document creation option leverages existing documents to save time and effort. Before saving the document under a different name, or to another location, you can modify document properties and settings as needed.

- To create documents from existing documents:
- 1 Perform one:
  - Select File, then Open.
  - Click

The Open dialog box is displayed. It features a selection frame that lists the current folder contents specified by Location.

- 2 Select Web Analysis Document from Files of Type.
- 3 Navigate to the document you want to copy.
- 4 Select the document, and click **OK**.

If the document uses a Database Connection requiring you to log on, the Database Login dialog box prompts you.

If prompted by **Database Login**, enter a User ID and password for the Database Connection. Click **Save User ID and Password** to store log on credentials for the Database Connection, and click **OK**.

The selected document is displayed in the content area.

- 6 Modify the document.
- 7 Perform one:
  - Select File, then Save As.
  - Click .
  - From the Contents Tab bar, right-click the current content tab and select **Save As**.

    The Save As dialog box is displayed. It features a selection frame that lists the current folder contents specified by **Location**.
- 8 Navigate to the folder to save your modified document.
- 9 Optional: Enter a name for the document in Filename.
- 10 Click OK.

The modified document is saved to the specified location, using the specified name.

# **Creating Auto-Populate Dimension Documents**

This is the quickest method for creating a document. It specifies the database connection, and assumes use of the highest aggregate members of the time and measures dimensions to populate the rows and columns axes of a spreadsheet. You can modify document properties and settings as needed before eventually saving the document.

**Note:** You can set the Look and Feel preferences to display Data Layout, instead of assuming use of the highest aggregate members of the time and measures dimension.

- To create a Auto-Populate Dimension document:
- 1 Display the View Pane:
  - Select View, then View Pane.
  - Press F6.
- 2 Click the View Pane Browser tab.
- 3 In the repository, navigate to a database connection file, and double-click the file name.
  - If the Database Connection requires you to log on, you are prompted by the Database Login dialog box.
- 4 If prompted by the **Database Login** dialog box, enter a User ID and password for the Database Connection. Select **Save User ID and Password** to store log on credentials for the Database Connection, and click **OK**.

A Auto-Populate Dimension document is displayed in the content area.

# **Modifying Queries**

Data Layout is an interface used to edit queries. Data Layout displays the dimensions returned by the database connection, as they are arranged on four axes:

- Rows
- Columns
- Pages
- Filters

Three kinds of dimensions are differentiated by these icons:

lcon	Dimension
•	Dimensions
₫,	Attribute Dimensions
4	Attribute Calculations

Every query must have at least a dimension assigned to the Rows axis and the Columns axis, but you can also nest multiple dimensions on one axis. You can organize the Row and Column dimensions by assigning dimensions to the Page axis. Dimensions not assigned to Rows, Columns, and Pages, remain in the Filter axis.

All dimensions participate in every intersection displayed by a data object, regardless of the axis to which they are assigned. You use Data Layout to arrange dimensions, to specify their level of detail, and to specify query options.

**Note:** All data objects start as spreadsheets. Charts and Pinboards are graphical representations of the data in the spreadsheet.

- ➤ To redefine the current document's query and dimension layout:
- Click the Navigate Data Source toolbar button.
- Select View, then Data Layout.
- To move a dimension between axes, drag the dimension name from its current axis to another axis.

The cursor displays a box next to it when it is over the axis. When you release the mouse button, the Dimension Browser dialog box displays. Use Dimension Browser to make member selections as needed, and click **OK**.

- To make member selections without moving the dimension to another axis, double click the dimension name.
- To clear all dimension member assignments and start over, click **Reset All**.

### Topics that discuss query modification:

- "Modifying Filter Dimensions" on page 57
- "Data Layout Options" on page 58
- "Relational Dimension Header Sort" on page 58
- "Label Mode" on page 59

# **Modifying Filter Dimensions**

All data object intersections are relative to filter member selections, which focus intersections and data values, and consequently, analysis.

Filter-axis dimensions are by default represented by the highest aggregate member defined in the data source outline. To focus analysis on members other than the highest aggregate, you can select filter members.

Filter member selections do not rearrange dimensions or reorganize pages, but focus analysis on intersections.

**Note:** If the variableFilterRestrictToSingleMember= true is set, all users can select one member from the filter selections. In the Dim Browser, only one member can be selected, therefore the right click menu options are limited to Find in Tree and Search. Users can select one member in the left pane; additional selections overwrite the previous selection.

# **Behavior Using Multiple Filters**

The following describes how Web Analysis retrieves data from Essbase and processes it when using multiple filters:

- Web Analysis uses Essbase report scripts to query Essbase.
- To retrieve top/bottom functionality, Web Analysis uses the Essbase report script commands TOP and/or BOTTOM, so the top/bottom retrievals are passed directly to the Essbase server.
- Similar to Essbase Excel Add-In queries, Essbase report scripts do not support multiple dimension members in a filter. Therefore, for Web Analysis to achieve this, multiple Essbase report scripts are executed one for each member. The results are summed into one grid in Web Analysis.
- Therefore, when doing a top/bottom retrieval with multiple member filters, the top/bottom results are retrieved from Essbase, one for each filter member, then summed together in WA

# **Data Layout Options**

The bottom of the Data Layout dialog box enables you to specify server-based options in the query:

Option	Description
Default Label Mode	Sets all dimensions using the default label mode to:  • Descriptions—Current alias table specified by database preferences  • IDs—Unique ID label  • Both—When using Oracle Hyperion Financial Management, you can specify ID and Description simultaneously
Use Point of View	Enables and disables the active POV definition defined on the current database connection.
Retrieve Only Top/ Bottom	Displays the Retrieve Only Top/Bottom dialog box, used to limit and rank the query result set.
Restrict Data	Displays the Restrict Data dialog box, used to restrict the query result set based on criteria.
Show Linked Reporting Object Indicators	Shows/Hides the orange triangle symbols that indicate Related Content definitions in Essbase.
Suppress	Omits components, as selected, from the query result set:
	Missing Columns—Columns of data comprised of missing values
	Missing Rows—Rows of data comprised of missing values
	Shared Members—Dimension members that are used in multiple locations of one hierarchy
	Zero Rows—Rows of data comprised of zero data values
Display Entity Currency	When using an Financial Management data source with defined Entity dimension currency information, you can enable the Display Entity Currency option, to append the Entity dimension members with their currency value. This can be set before querying using Data Layout options, after querying using the Data Display shortcut menu, and for all subsequently created documents using OLAP Server preferences. See "Financial Management" on page 169.
Use User Point of View	Selecting it adds a member selection to the Dim Browser for every dimension in the ReportDataSrc. The selected members in the User POV are utilized in the spreadsheet.

# **Relational Dimension Header Sort**

You can also order the result set returned by the SQL query in a relational database connection. You can opt for Ascending, Descending, Selection Order and Default. Default is the natural order in which dimension members are returned, based on the data source outline. Selection Order is the order in which members were selected in Dimension Browser.

You must be aware that unlike OLAP servers, relational cubes are compiled and defined by Web Analysis Studio. The current label mode, alias tables, and selection orders from Dimension Browser are manually coordinated. Sort by alias may perform comparatively slow, as the default query result set is sorted by ID, and sorting by alias requires a complete client-side re-sort.

In addition, the source of the relational dimension header sort impacts performance. Defining a relational dimension header sort using Data Layout sorts all dimensions as part of the query result set being displayed.

You alternatively, can sort a relational dimension using the data object shortcut menu: Data Display / Dimension Header Sort. This method requires you to right-click a dimension header.

Lastly, you can apply dimension header sort definitions to relational generation defined in the Generation Editor. These definitions only impact the sort ordering displayed by the Dimension Browser however. Using the Order By Mode list, you can also specify to order members by ID or Alias.

### **Label Mode**

You can set the default label mode to ID or Description in Data Layout. This setting impacts only those dimensions set to display the Default label mode in Dimension Browser.

The Description label comes from the alias table setting, saved per database connection and per active user as a database user preference.

You can set the default label mode before querying using Data Layout options or the last step in the wizard, and after querying using the data object shortcut menu. You can specify which description label to use in dimensions, using Dimension Browser and the data object shortcut menu.

- To set the default label mode for the current database connection:
- 1 Click **Options** in the lower left corner of the Data Layout dialog box.
- 2 Select Default Label Mode from the menu.
- 3 Select the **IDs** or **Descriptions** option.

**Note:** Financial Management users have the additional label mode option of Both.

See "Setting the Label Mode" on page 94.

# **Selecting Dimension Members**

Dimension Browser, an interface for selecting members and refining database queries, is used with the document wizard, Data Layout dialog box, Information panel, or on its own.

The Dimension Browser presents dimensions as a node tree in the Browse frame. You must select dimension members from Browse and move them to Selections.

Members can be selected individually, by familial relationships, by data-source-specific options, or from predefined selection lists.

- To access the Dimension Browser:
- Right-click a dimension member label on a data object, and select Browse.

- In the View Pane Information Panel tab, right-click a dimension label and select Browse.
- Click the Navigate Data Source toolbar button, and double-click a dimension name.
- Click the **Navigate Data Source** toolbar button, and drag a dimension between axes. Relocating a dimension, prompts you to select members.
- To expand or collapse the dimension hierarchy:
- Double-click dimension member names
- Click the plus sign (+) or minus sign (-) nodes.
- To select a dimension member, click the member name in the **Browse** frame.

A check mark is displayed in the check boxes of selected members, and the member name is displayed in the Selections list. You cannot select the database connection name at the top of the node tree.

To select dimension members dynamically, right-click a dimension member name and select an advanced member selection method from the list.

See "Advanced Member Selection" on page 61.

- To remove members from the selection list:
- Select the member name in the Selection list and click Remove.
- Click the dimension member name in the Browse list again.
- To remove all members from the selection list, click **Remove All**.
- To set the label mode for the dimension, click a **Dimension Labels** option:
- Use Default—Preferences default label mode.
- Descriptions—Current alias table specified by database preferences.
- IDs—Unique ID label.
- Both—When using Financial Management, you can specify ID and Description simultaneously.

The label displayed by the Description label mode is drawn from the alias table specified by the active user's database preferences. You can set the alias table for each Active Preferences user ID or group ID.

You can specify label mode in dimensions, using Dimension Browser and the data object shortcut menu.

You can set a default label mode before querying the data source using Data Layout options or after querying using the data object shortcut menu.

See "Alias Tables" on page 265.

# **Advanced Member Selection**

In dimensions with large member sets, you can easily define selections using the Dimension Browser shortcut menu. Right-clicking dimension member names enables selection by familial relationship and data source-specific options:

Icon	Shortcut Menu Command	Selects:	
-	Also Select Children	Currently selected member and its children (one level below)	
	Also Select Descendants	Currently selected member and its descendants	
<b>=</b>	Select Parent	Direct parent of the selected member	
<b></b>	Also Select Ancestors	Currently selected member and its ancestors	
臣	Also Select Siblings	Currently selected member and members on one level with identical parent ancestor	
	Select Dim Bottom	All dimension members on the lowest level of the hierarchy	
<b>=</b>	Select Dim Top	Highest ancestor	
=	Also Select Level	Currently selected dimension member and all dimension members on one level	
-	Also Select Generation	Currently selected dimension member and all dimension members in one generation	
<b>≣</b> #	Also Select Previous	A number of previous members at one dimension level	
	Also Select Subset	An Essbase member subset	
	Substitution Variables	Sets a substitution variable as the dimension selection	
₫,	Select Attribute	A selection from a list of attribute dimensions	
	User Defined Fields	Financial Management—One of three predefined attribute values	
		. Select members featuring these attribute values and compose compound selection statements with AND and OR operators	
	Dynamic Time Series	Essbase Dynamic Time Series selection (for example: History To Date, Quarter To Date)	
	Search	Locates dimension members in large dimensions with search criteria, and adds found members to the Selection list	
	Find In Tree	Locates dimension members in large dimensions	
		Expands the dimension hierarchy, but does not add found members to the Selection list	

# **Advanced Member Selection by Data Source**

Data Source	Advanced Member Selection Method
Essbase	Also Select Children
	Also Select Descendants
	Select Parent
	Also Select Ancestors
	Also Select Siblings
	Select Dim Bottom
	Select Dim Top
	Also Select Level
	Also Select Generation
	Also Select Previous
	Select Subset
	Substitution Variables
	Select Attribute
	Dynamic Time Series
	Search
	Find in Tree
SAP BW	All Members
	Select Dim Top
	Select Dim Bottom
	<ul> <li>Also Select Descendants</li> </ul>
	Select Parent
	Also Select Ancestors
	Also Select Children
	Also Select Siblings
	Also Select Level
	Select At Level
	Also Select Previous
	Also Select Next
	Dynamic Time Series
	Select Top/Bottom
	Filter on Member Properties
	Find in Tree

Data Source	Advanced Member Selection Method
Financial Management	<ul> <li>All Members</li> <li>Select Dim Top</li> <li>Select Dim Bottom</li> <li>Also Select Descendants</li> <li>Member List</li> <li>Also Select Children</li> <li>User Defined Field</li> <li>Search</li> <li>Find in Tree</li> </ul>
	See "Financial Management" on page 169.
JDBC Relational Data Sources	<ul> <li>Also Select Children</li> <li>Also Select Descendants</li> <li>Select Parent</li> <li>Also Select Ancestors</li> <li>Also Select Siblings</li> <li>Select Dim Bottom</li> <li>Select Dim Top</li> <li>Also Select Generation</li> <li>Find in Tree</li> </ul>

Consider the implications of the relational hierarchy in advanced member selections on relational data sources. When the highest ancestor is selected, a default dimension member may be used instead of the aggregation. The relational hierarchy may also equate Also Select Children and Also Select Descendants for example.

Advanced member selection methods depend on your data source implementation.

# **Searching for Members**

Essbase users can locate members in large dimensions using search criteria. These searches can be conducted inside the Dimension Browser dialog box when composing a query, or from the data object shortcut menu when analyzing a document.

- To search for Essbase dimension members in Dimension Browser:
- Right-click a dimension member in the Dimension Browser, and select Search.
- Enter search criteria in the corresponding text boxes, and click **OK**.

Search Criteria	Control	Description
Member		The text string for the search function.

63

Search Criteria	Control	Description
Mode	ID	Searches by member name.
	Description	Searches by member alias (description).
	Both	Financial Management data source enables you to search by ID and Description, using this option.
	Expand Tree	When the Expand Tree option is selected, not only is the found member added to the Selections list, but the Browse node tree is expanded to display the found member in the dimension hierarchy. Only the first instance of the search criteria is selected.
		When the Expand Tree option is not selected, found members are added to the Selections list, without changing the Browse node tree.
Range		Specifies the search of the dimension (All Top Members), or down the hierarchy from the selected member.
Option	Whole	Searches on exact match with fully qualified member name or alias.
	Substring	Searches for the first, last, or middle part of the member, in the order entered in the member text box.
	Beginning	Searches for the start of the member string.
	Ending	Searches for the end of the member string.

- To search for Essbase dimension members in a document data object:
- Right-click a dimension member header and select Search.
- Enter search criteria in the corresponding text boxes, and click **OK**.

Note: Search performance is directly related to the size and complexity of the dimension hierarchy.

# **Searching For SAP BW Characteristic Values**

SAP BW users can locate characteristic values in large dimension hierarchies using search criteria. These searches can be conducted only inside the Dimension Browser dialog box when composing a query.

- To locate SAP BW dimension members in Dimension Browser:
- Right-click a dimension member, and select Search.
- Enter search criteria in the corresponding text boxes.

Search Criteria	Control	Description
Mode	ID	Searches by member technical name.
	Description	Searches by member alias (description).

Search Criteria	Control	Description
Search Criteria		A list enables selection from these operands:
		Equal To
		• >=
		• <=
		• >
		• <
		Between     Contains Pattern
		Contains Pattern
		Enter the text string for the search function in the text area.
		Supports the wildcard characters * and +.
Execute		Runs the search function.
Filtered Members		Displays the search result set.
	Add	Adds the currently selected member from the Filtered Members list to the Selected Members list.
	Remove	Removed the currently selected member from the Selected Members list back to the Filtered Members list.
Selected Members		Displays potential member selections made from the search result set.
	Add All	Adds all Filtered Members to the Selected Members list.
	Remove All	Removes all Selected Members back to the Filtered Members list.
OK		Adds the Search Selected Members list to the Dimension Browser Selections list.

3 Click Execute to run the search function using the criterion specified in the Mode and Search Criteria groups.

The search result set is displayed in the Filtered Members group.

4 Select members from **Filtered Members**, and click **Add** to add them to **Selected Members**.

Only the members added to the Selected Members list are added to the Dimension Browser Selections list when you click OK.

5 Click OK.

# **Locating Dimension Members**

In large or complex dimension hierarchies, you can locate known dimension members to select neighboring members. This is a useful alternative to composing a search string for unknown members.

To find a known dimension member, right-click a dimension member in the Dimension Browser **Selections** list, and select **Find In Tree**.

In the Browse frame, the dimension hierarchy expands and the first instance of the selected member is highlighted. You can now select other members based on their relationship to the selected member.

# **Selecting Intervals**

- To select an interval:
- 1 In Analyze, open Dimension Browser.
- 2 In Dimension Browser, right-click a characteristic and highlight Select Interval Between.
- 3 In the dialog box that is displayed, enter the interval **To** and **From** values.

For example, for a calendar year characteristic, you could enter 1990 to 1993 as the interval to analyze.

# **Previewing Member Selections**

You can preview the dimension members returned by advanced member selections, before you quit the Dimension Browser dialog box.

- To preview advanced member selections for the current dimension:
- 1 In Analyze, open Dimension Browser.
- 2 In Dimension Browser, click Preview Selections.

The data source is queried using the current Selections list. The result set is displayed in the Preview Selections dialog box.

3 Click Close to return to the Dimension Browser.

# **Selecting Members Using Essbase Subsets**

Essbase users can define rules that select dimension member subsets by rules composed of data source constructs:

- UDAs—Members with a specified user-defined attribute (UDA)
- Generation—Members belonging to a specified generation of the dimension hierarchy
- Level—Members belonging to a specified level of the dimensional hierarchy
- Expression—Members matching a pattern of wildcard characters
- Attribute dimensions—Members with a specified database-defined attribute
- Conditional logic—Members satisfying advanced subset member selection criteria

You can search all selected member descendants using a maximum of 50 subset conditions. Subset criteria are saved by individual document. Because the filter panel cannot accommodate lengthy selection lists, subset member selections made in Filters are summarized with a description.

### Topics that discuss Essbase subset selections:

- "Defining Member Subset Selections" on page 67
- "Wildcard Characters" on page 68
- "Expressions" on page 68
- "UDAs" on page 68

# **Defining Member Subset Selections**

- To define a member subset selection:
- 1 Right-click a dimension member in the Dimension Browser, and select Select Subset.
  - The Subset dialog box is displayed. At the top, it indicates dimension members against which the rule is applied. Use the Individual Selection Rule control to compose a rule by selecting components from drop-down lists.
- 2 Select a subset type: UDA, Generation, Level, Expression, or Attribute.
- 3 Select an operand for the subset rule: is (=) or is not (not equal).
- 4 Select a value for the subset rule from the last drop-down list.
- 5 Click Add to augment the Total Subset Definition.

You must add the individual rule to the Total Subset Definition for it to be used. You can define compound and conditional rules by adding multiple rules to the definition, and using Advanced options to connect them:

Advanced Subset Option	Sub menu	Description
Add		Add the current rule to the Total Subset Definition.
Update		Replace the selected rule with the current rule.
Validate		Verifies the parenthetical syntax of the Total Subset Definition.
Remove		Remove the current rule from the Total Subset Definition.
Remove All		Remove all rules from the Total Subset Definition.
Connect	And	Inserts the AND operand at the end of the currently selected rule. The AND operand is used by default when multiple rules are added to the Definition.
	Or	Inserts the OR operand at the end of the currently selected rule.
Move	Move Up	Moves up the currently selected rule in the Total Subset Definition.

Advanced Subset Option	Sub menu	Description
	Move Down	Move the currently selected rule down in the Total Subset Definition.
Parenthesis	Add (	Inserts an open parenthesis at the beginning of the currently selected rule.
	Add )	Inserts a close parenthesis at the end of the currently selected rule, but before an operand.
	Remove (	Deletes the open parenthesis from the beginning of the currently selected rule.
	Remove )	Deletes the close parenthesis from the end of the currently selected rule.
	Remove All ()	Removes all parentheses from the Total Subset Definition.
Substitution Variable		Presents the Substitution Variable dialog box, enabling you to select a predefined substitution variable for the subset rule value.

- Optional: To compose a compound subset definition, repeat steps 3 through 6, and click Add to augment the Total Subset Definition.
- 7 Click **OK** to finish your subset selection and return to Dimension Browser.

### **Wildcard Characters**

Supported expression wildcard characters include the question mark (?) and the asterisk (\*). The asterisk can be used only once in an expression and only at the end of a text string.

# **Expressions**

Subset queries defined by expressions are not dependent upon label mode, and return all strings satisfying the expressions regardless of the alias table. The user is responsible for distinguishing whether the source of the value is the ID, the Description, or from an alias table, and to refine the query if needed.

# **UDAs**

Essbase users can create user-defined attributes (UDAs) for dimension member subsets. A UDA is a word or phrase about the dimension member that is associated with it as a characteristic.

# **Selecting Financial Management User Defined Fields**

Financial Management users can select members with specified attribute criterion. A user defined field is used to define compound selection rules for attributes of a specified value.

- To define a user defined field selection:
- 1 Right-click a dimension member in the Dimension Browser, and select User Defined Field.

The User Defined Field Selection dialog box is displayed. The controls at the top prompt the user to compose a rule by selecting a user defined field and setting it to a value.

Select a field: UserDefined1, UserDefined2, or UserDefined3.

The equal sign is the sole operand for the rule.

- Enter a value for the user defined field.
- Click Add to augment the Selection Criteria.

To be used, the individual rule must be added to the Selection Criteria. Define compound and conditional rules by adding multiple rules to the frame, and use Advanced options to connect them.

Advanced Option	Sub menu	Description
Add		Add the current rule to the Total Subset Definition.
Update		Replace the selected rule with the current rule.
Remove		Remove the current rule from the Total Subset Definition.
Remove All		Remove all rules from the Total Subset Definition.
Connect	And	Inserts the AND operand at the end of the currently selected rule. The AND operand is used by default when multiple rules are added to the Definition.
	Or	Inserts the OR operand at the end of the currently selected rule.
Move	Move Up	Moves the currently selected rule up in the Total Subset Definition.
	Move Down	Move the currently selected rule down in the Total Subset Definition.
Parenthesis	Add (	Inserts an open parenthesis at the beginning of the currently selected rule.
	Add )	Inserts a close parenthesis at the end of the currently selected rule, but before an operand.
	Remove (	Deletes the open parenthesis from the beginning of the currently selected rule.
	Remove )	Deletes the close parenthesis from the end of the currently selected rule.

- Optional: To compose compound subset definitions, repeat steps 3 through 5, and click Add to augment the Selection Criteria.
- Click **OK** to finish your user defined field selection and return to Dimension Browser.

# **Filtering by SAP BW Member Properties**

SAP uses the term member properties to indicate member attributes. You can select SAP BW members and filter them by their member properties. This requires you to first make a conventional member selection, or advanced member selection, and further define a filtering definition on the selection.

- To select SAP BW members by their member properties:
- 1 In **Dimension Browser**, make a member selection or advanced member selection.

Your member selection is displayed in the Selection frame.

2 Right-click a member selection in the **Selection** frame and select **Filter on Member Properties**.

The Member Properties dialog box is displayed. The controls at the top prompt the user to compose a rule by selecting a member property, operand and value.

- 3 From the list, select a member property for the selection dimension.
- 4 Select an operand from the operand list.
- 5 Enter a value for the member property.
- 6 Click Add, to add the rule to the filter statement.

You must add the individual rule to the filter definition for it to be used. You can define compound and conditional rules by adding multiple rules to the frame, and use Advanced options to connect them:

Advanced Option	Sub menu	Description
Add		Add the current rule to the filtering definition.
Update		Replace the selected rule with the current rule.
Remove		Remove the current rule from the Total Subset Definition.
Remove All		Remove all rules from the Total Subset Definition.
Parenthesis	Add (	Inserts an open parenthesis at the beginning of the currently selected rule.
	Add )	Inserts a close parenthesis at the end of the currently selected rule, but before an operand.
	Remove (	Deletes the open parenthesis from the beginning of the currently selected rule.
	Remove )	Deletes the close parenthesis from the end of the currently selected rule.
Connect	And	Inserts the AND operand at the end of the currently selected rule. The AND operand is used by default when multiple rules are added to the Definition.
	Or	Inserts the OR operand at the end of the currently selected rule.
Move	Move Up	Moves up the currently selected rule in the Total Subset Definition.
	Move Down	Move the currently selected rule down in the Total Subset Definition.

- 7 Optional: To compose compound definition, repeat steps 3 through 6, and click Add to augment the definition.
- 8 Click **OK** to finish your filter definition and return to Dimension Browser.

# **SAP BW Select Top/Bottom**

SAP BW enables you to limit the size and rank the query result set on the data source server.

- To limit and rank SAP BW members as part of the query:
- 1 In **Dimension Browser**, make a member selection or advanced member selection.

Your member selection is displayed in the Selection frame.

2 Right-click a member selection in the Selection frame and select Select Top/Bottom.

The Top/Bottom dialog box is displayed. The controls prompt you to indicate top or bottom, define criteria, and select a dimension member for ranking.

3 Select Top or Bottom.

You cannot select both, as when using Essbase.

4 From the Using Function group, select Percent, Sum, or Count.

You can select only one method for determining rank.

5 Enter a value for the method.

The Percent text area should be a value between one and a hundred. The Sum text area requires you to enter a threshold. All member values summed to and including the threshold are returned. The Count text area requires only an integer indicating how n top or bottom members to return.

6 In Order By, select another cube dimension.

Because all dimensions participate in every intersection, you are required to identify the intersection by which the selected dimension is ranked.

7 **Optional:** Click **Selection** to display the dimension browser for the Order By dimension.

The Dimension Browser dialog box is displayed. You can select a dimension member from the dimension by which to rank the selected dimension, and click OK.

- 8 Click **OK** to finish your Top/Bottom definition and return to Dimension Browser.
- 9 Click OK.

# **Selecting SAP BW Period to Date**

When Period to Date data is configured on the SAP BW server, you can access data as consolidated by a specified date.

- ➤ To select dimension members using SAP BW Period to Date:
- 1 In Dimension Browser, make a member selection or advanced member selection.

Your member selection is displayed in the Selection frame.

2 Right-click a member selection in the Selection frame and select SAP BW Period to Date.

The SAP BW Period to Date dialog box is displayed. The control prompts you to select a period definition from the list.

3 Select a period definition and click OK.

# **Providing SAP BW Variables**

When SAP BW Variables are configured on BEx Query Cube InfoProviders, you are prompted to provide the replacement value for the SAP BW Variable before submitting the query.

Prompting occurs when you click Finish when completing the Document Creation wizard, or when you click OK after modifying a query using the Data Layout interface.

- To provide SAP BW Variable values when prompted:
- 1 In **Database Variables** ServerName, read the record for each variable.

It is important to know the variable type, a characteristic value or a hierarchy node.

2 Click the Edit cell for a variable record.

The Dimension Browser dialog box is displayed. If the record is a characteristic value, you must select one explicit value at the lowest level of the dimension hierarchy. If the variable is a hierarchy node, you can select a value in the dimensional hierarchy.

- 3 Select a characteristic value for the variable type, and click OK.
- 4 Repeat steps 2 and 3 until all variables are assigned values for the query.
- 5 Click OK.

The query is submitted using the specified variable values.

# **Selecting Financial Management Member Lists**

Member Lists are predefined Financial Management variables for frequently changing information.

- To use a Financial Management Member List in a Dimension Browser member selection:
- 1 Right-click a dimension member in the Dimension Browser, and select Member List.
  The Choose Member List dialog box is displayed.
- 2 Select a predefined member list from **Choose Member List**.
- 3 Click OK.

# **Selecting Substitution Variables**

Substitution variables are predefined Essbase variables for frequently changing information.

Substitution variables simplify document maintenance by enabling fluctuating values to be adjusted centrally (in Essbase), and enabling documents to reference the changing value dynamically.

- To use a substitution variable in Dimension Browser member selection:
- 1 Right-click a dimension member in the Dimension Browser, and select Substitution Variable.

The Substitution Variable dialog box is displayed.

- 2 Select a substitution variable from the list of Essbase substitution variables.
- 3 Click OK.

### **Multiple Substitution Variables**

Multiple substitution variables can be used using Subset Member Selections.

### **Tips on Syntax**

Substitution variables have their own rules and syntax requirements:

- The substituted value should be a dimension or a member name, and member values should come from the corresponding dimension.
- Do not use the ampersand (&) as the first character of a member name.

### **Analysis Tools and Substitution Variables**

When member selections defined by substitution variables are used in analysis tool definitions, the system resolves the substitution variable to its current value. This ensures accurate aggregations, comparisons, and calculations regardless of the substitution variable definition.

## **Creating and Selecting Personal Variables**

Personal variables simplify complex member selections. After being defined, you can leverage personal variables when you are presented with the corresponding dimension and database connection. Personal variables are containers for an ad hoc collections of otherwise unrelated dimension members.

Defining a personal variable does not include the personal variable in a query. You must select the personal variable from the Dimension Browser when defining the query.

- To create a personal variable:
- 1 Select File, then Preferences.

The User Preferences dialog box is displayed, with the active user or group displayed in the Active Preferences list.

- 2 Click the **Databases** tab to make it current.
- 3 Select a database connection name, and click Edit.

The Database Preferences dialog box is displayed.

4 Click Connect.

The Personal Variable and Point of View tabs are enabled.

#### 5 Click Personal Variable.

The Personal Variable tab lists all currently defined personal variables for the database connection.

#### 6 Click Add.

The Personal Variable dialog box is displayed.

- 7 Enter a name for the personal variable in Name.
- 8 Select a dimension from the data source from the **Dimension** list.

The Dimension Browser for the selected dimension is displayed.

9 Select the dimension members to be included in the personal variable.

All conventional Dimension Browser methods and options are supported.

#### 10 Click OK.

The Personal Variable tab is displayed and the personal variable definition is listed. Whenever the database connection and dimension is used, the personal variable definition is displayed as a selection option in the Dimension Browser Browse panel.

To use a personal variable in a query, select the personal variable definition from the Dimension Browser **Browse** panel.

## **Creating and Applying Points of View**

POV database preferences enable you to insert dimensions and members that are of interest to you into the documents of others. POV definitions must be defined and activated by database connection.

When a POV is activated, the Use Point of View option in Data Layout and the wizard are enabled. All subsequently created and loaded documents use the specified POV until it is deactivated. You can also deactivate use of POV by deselecting the Data Layout Use Point of View option as needed.

POV definitions consist of axes and dimension member selections. The definition is used when documents are created with the activated POV.

When you apply a POV definition to a document, only the dimension member selections are applied. This prevents points of view from automatically arranging non-functioning layouts (such as moving all dimensions to one axis).

If all POV member selections are custom filters, you may not see obvious changes to your document. You can check to see which POV is applied on the View Pane Information Panel tab, Point of View segment.

Using a POV definition is a three part process. First, you must create a POV definition. Next, you must activate the POV definition. Lastly, you must set a document to use the activated POV definition, or create a document that uses it.

#### To create a POV and activate it:

#### 1 Select File, then Preferences.

The User Preferences dialog box is displayed, with the active user or group displayed in the Active Preferences list.

#### 2 Click Databases.

3 Select a database connection name, and click Edit.

The Database Preferences dialog box is displayed.

4 Click Connect.

The Personal Variable and Point of View tabs are enabled.

5 Click Point of View.

The Point of View tab lists all currently defined POV definitions for the database connection.

6 Click Add.

The Point of View dialog box is displayed.

7 Enter a name for the POV in Name.

Use the Data Layout interface to locate dimensions from this data source on axes and make member selections.

- 8 Define the POV layout, selections, and analysis tools as you would for a query.
- 9 Click OK.

The Point of View tab is displayed and the definition is listed.

10 To activate this POV definition, select the POV name and click Activate.

#### 11 Click OK.

Whenever the database connection is used, you can apply the activated POV definition in lieu of defining its member selections.

To apply an activated POV definition to an open document:

#### 1 Display Data Layout:

- Click the Navigate toolbar button.
- Select View, then Data Layout.

Data Layout is displayed for the current document.

- 2 From the Option button list, select User Point of View.
- 3 Click OK.

The activated point of definition is applied to the current document. You must refresh the content area to display POV selections.

#### 4 To refresh the document, perform one:

- Right-click the content tab for the current document and select Refresh.
- Select View, then Refresh.

- Press F5.
- Right-click the data object and select Refresh Data.
   Activated POV selections are applied to the current document.

### **User POV**

User POV enables users to select members in Filters, Pages, Rows, and Columns (Data layout and/or member selection controls) and apply them to multiple Web Analysis documents.

This is exposed through the current POV functionality, where User POV is the name of another POV that is created and utilized in Web Analysis documents. The User POV exist for all database connections and can be set at user level only.

- To set a User POV:
- 1 Right click a spreadsheet and select Save Selection as User POV to save the dimension member selections to the User POV.
  - This feature is available in Web Analysis Studio and EPM Workspace.
- 2 Select Web Analysis User Preferences, then OLAP Server, then select Save Filters only for User POV.

All Subscription controls have the "Save Selection as a User POV" option. A selection is saved as a filter to the User POV.

If a Subscription control points to multiple ReportDataSrcs, all database connections have their User points of view set for the dimensions of the active control.

To enable a User POV, in Data Layout, select Use User POV

Enabling this item adds a member selection option to the Dim Browser for every dimension in the ReportDataSrc. Selected member(s) in the User POV are utilized in the spreadsheet query.

## **Defining Dynamic Time Series Selections**

You can select Dynamic Time Series (DTS) definitions for query selection statements.

DTS definitions must be created in Essbase before you can make DTS selections. You select the DTS definition and a corresponding Time dimension member that defines a time period.

You can select DTS substitution variables.

*Substitution variables* are predefined placeholders for information that changes frequently. Each substitution variable is identified by a variable name and has a temporary value defining its data type. When the substitution variable is used, the temporary value is replaced by a current value. For substitution variables to be used, they must be stored at the database level in Essbase.

- To define a DTS selection:
- 1 Right-click a Time dimension member in the Dimension Browser, and select **Dynamic Time Series**.

Available DTS definitions are displayed in a drop-down list.

2 Select a DTS definition.

The Dynamic Time Series dialog box is displayed.

- 3 Perform one:
  - Select the **Substitution Variable** tab and select a substitution variable from the list.
  - Select the **Member tab** and select a dimension member representing the specified date in the "X-to-date" definition.
- 4 Click OK.

## **Defining Previous Member Selections**

Selecting Also Select Previous selects a specified number of previous members at one dimension level.

- To define a previous member selection:
- 1 In the Dimension Browser, right-click a dimension member, and select Also Select Previous.
  - The Also Select Previous dialog box is displayed.
- 2 Specify the number of previous members to retrieve, using the list.
- 3 Click OK.

The Dimension Browser is redisplayed. The member that you right-clicked is displayed in the Selections list with the Also Select Previous icon.

## **Selecting Attributes**

Essbase can store dimension member names, locations, relationships, and characteristics of members.

**Example:** The product dimension may indicate that in Women's Apparel, Shirts and Blouses, there is a cotton T-shirt product. An attribute indicates whether each cotton T-shirt is red, cyan, lime, or pink.

**Example:** The Market dimension may indicate that there is a franchise store in Biloxi, Mississippi. An attribute indicates that the store is 2,500 square feet.

Attributes are stored in the same manner as dimension members. Attribute dimensions are displayed beside the conventional dimensions that they modify in Data Layout. It is important to note that attribute dimensions are labeled and function differently though.

To include attribute dimensions in the query, you must select the attribute dimension itself.

To select conventional dimension members using attributes, you must select the conventional dimension, and use the Select Attribute advanced member selection method.

- To select dimension members by their attributes:
- 1 Right-click a dimension member in the Dimension Browser, and select **Select Attribute**.
- 2 Select an attribute dimension from the Select Attribute sub menu.
  The Select Attribute dialog box is displayed for the selected attribute dimension.
- 3 Select a dimension member attribute from the Select Attribute frame.
- 4 Click OK.

## **Turning Off Key Figure Attributes**

- To turn off a key figure attribute:
- 1 Right-click the attribute on the Analyze interface.
- 2 Select Data Display, then Suppress Currency and Units

**Note:** This feature can be applied for all other characteristics too.

## **Creating Calculated and Restricted Key Figures**

- To create or edit key figures:
- 1 Select Analysis Tools then, Calculated Key Figures
- 2 In Calculated Key Figures, select New or a key figure.
- 3 If creating a key figure, replace Untitled with a unique name.
- 4 Select a Function and related information.

Note: Information requested differs depending on the function selected.

Function	Measure	Cube Hierarchy
Avg	х	Х
Var	Х	Х
Max	Х	Х
Median	Х	х
Min	Х	х
Sum	Х	х
Count		х

**Note:** In the Selections box, you can only add members from the same hierarchy of a dimension

5 In Cube Hierarchy, double-click an entry to move it to Selections.

Caution! Only one hierarchy can be used. If you attempt to select another hierarchy, Web Analysis asks if you want to remove all selections made on the other hierarchy.

- 6 Click OK to close Calculated Key Figures
- 7 In Key Figures Browser, select a key figure to move it to Selections and click OK.

7

# **Navigating Documents**

**In This Chapter** 

Navigating Data Objects and Data Sources	81
Navigation Methods	82

## **Navigating Data Objects and Data Sources**

Web Analysis documents contain a variety of non-static data objects:

- Spreadsheets
- Charts
- Pinboards
- SQL Spreadsheets
- Freeform Grids

You can rearrange, expand, change and concentrate dimension intersections; these are called navigation methods because they enable travel through dimensional hierarchies.

Navigation methods vary for data objects and data sources:

 Table 1
 Web Analysis Studio Supported Data Sources

Туре	Data Source
OLAP	Essbase
	IBM DB2 OLAP Server
	SAP BW
Oracle   Hyperion	Financial Management
	Oracle Hyperion Planning
Relational	IBM DB2 Enterprise Server Edition
	Microsoft SQL Server
	Oracle
	Teradata
	Other JDBC RDBMS

OLAP data sources support all navigation methods described in this chapter. Other Oracle | Hyperion data sources and relational data sources support fewer navigation methods.

# **Navigation Methods**

Web Analysis Studio navigation methods include:

Navigation	Description	Method
Swapping and Moving Dimensions	Swap—Switches the placement of two dimensions.  Move—Relocates a dimension on document axes.	Swap—Drag a dimension onto another dimension.  Move—Drag a dimension from one position to another
Dimensions		position.
Paging	Maintains the dimensions on the row and column axes, while changing their intersection with dimensions that differ on the Page axis.	Click or scroll the Page Control panel.
Keep Only	Deselects all other dimension member selections for the selected Dimension, leaving only the selected member.	Right-click a dimension member header, and select Keep Only from the shortcut menu.
Remove Only	Deselects the selected member, removing it from the query result set.	Right-click a dimension member header, and select Remove Only from the shortcut menu.
Drilling	Increases or decreases the level of dimension detail by including or excluding members of the dimensional hierarchy in the display.	Double-click dimension member headers. You can customize the drilling behavior.
Drill Linking	Navigates to other documents or executables.	Click the linked cell to pass the selected cell and the dimension context to another document or data object.
Dragging	Uses the Information panel to rearrange the data object in the content area.	Drag objects on the Information panel.
Undo and Redo	Undo reverses the last executed command, and returns the display to its previous state.	Select <b>Edit</b> , then <b>Undo</b> . You can select to undo the last ten executed commands.
	Redo reverses the negation of the last command.	Select <b>Edit</b> , then <b>Redo</b> . You can select to redo the last ten executed commands.
Custom Controls	You can define document navigation using controls in custom documents.	Drag a component onto a custom document, and associate a data source or behavior with it. See "Creating Subscription Controls" on page 228.

It is important to differentiate these navigation methods:

- Drilling—Conventional drilling navigates to related dimension members.
- Linking (also called drill-linking)—Drill linking passes the selected member to other documents.
- Linked Reporting Objects (LROs)—LROs open executables to display cell-notes, Windows executables, or Web page URLs.

### **Swapping and Moving Dimensions**

You can rearrange intersections by swapping and moving dimensions:

- Swapping switches two dimensions, replacing one with the other.
- Moving relocates a dimension.

Swapping and moving are nearly identical in their use of interface drag methods. They differ in where the dimension is dropped. To swap, drop the dimension on another dimension label. To move, drop the dimension between dimension labels.

- To swap dimensions:
- 1 Click and hold a dimension member.
- 2 Drag the dimension member on to another dimension member.

The two dimensions exchange places.

- To move a dimension:
- 1 Click and hold a dimension member.
- 2 Drag the dimension member to a point between other dimension members and release the mouse button when a bold rule is displayed.


The dimension is relocated to where the rule displayed.

Document creators can lock the ability to swap and move dimensions using Properties.

### **Paging**

Paging maintains the dimensions on the row and column axes, while changing their intersection with dimensions that differ on the Page axis.

You can jump or scroll through pages of intersections using the Page Control panel.



The Page Control panel organizes Page axis intersections so that each page is relevant to a Page dimension member.

- To navigate the Page dimension, perform one action:
- Click the Page Control scroll buttons to move in the page series.
- Enter a page number for the page series and press Enter.
- From the list, select a page dimension member.

### **Pages**

The Page axis is another axis for organizing dimensions. It is sometimes helpful to think of it as the Z axis of a three-dimensional graph.

Visualize a stack of spreadsheets. Traveling back and forth in the stack enables comparison of values on different pages.

If spreadsheets in the stack must be relevant to Page axis dimensions, each page must represent a Page axis dimension member or dimension member combination.

#### **Multiple and Single Drop-Down Lists**

The Page Control panel can display multiple page drop-down lists when you work with page dimension combinations. Multiple-page drop-down lists display all possible page combinations, whether data exists. Single-page drop-down lists omit page combinations that do not contain data. Oracle | Hyperion recommends using one page drop-down list when working with sparsely populated dimensions.

- To separate Page dimensions into multiple drop-down lists, click the Page Control panel Page icon.
- To combine multiple page dimensions into one drop-down list, click the Page icon.

### **Keep Only**

Keep Only deselects all other dimension member selections for the selected Dimension, leaving only the selected member.

To deselect all but one dimension member, right-click the dimension member header, and select **Keep Only** from the shortcut menu.

### **Remove Only**

Remove Only deselects a dimension member, removing it from the query result set.

To remove one dimension member from the query result set, right-click a dimension member header, and select **Remove Only** from the shortcut menu.

### **Drilling**

Drilling increases or decreases the level of document detail by changing the display of dimension members. Because drilling is customizable, the term drilling can mean almost hierarchical navigation prompted by double-clicking a dimension label.

You can customize drilling using three options:

- Drilling options specify the drilling result set.
- Expand on Drill specifies whether the drilling result set replaces or augments the currently displayed dimension members.
- The Selected Member data display option specifies whether the drilled member is included in the drilling result set.

### **Drilling Options**

Web Analysis Studio features these default drilling behaviors:

- Drill Down-Includes member's children.
- Drill Up—Includes member's parents.
- Drill to Top-Includes highest ancestor

You can customize drilling by setting drilling options. Drilling options are set for the current document through the data object shortcut menu (Drill / Drill Options). Drilling options can also be set for all subsequently created documents through Drilling preferences.

<b>Drilling Option</b>	Description
Drill to Next Level	Includes children of drilled member.
Drill to Descendants	Includes all descendants of drilled member.
Drill to Dim Bottom	Includes a list of members on the bottom level of hierarchy without Selected member. The member is replaced with a list of members on the bottom level.
Drill to Siblings	Includes members at one level who share a parent with the drilled member
Drill to Same Level	Includes all members on drilled member's level.  Note: Oracle   Hyperion defines levels as hierarchical layers counted from the lowest descendant (Level 0); other data sources define levels differently. Asymmetric hierarchies may also yield unexpected results
Drill to Same Generation	Includes all members on drilled member's generation  Note: Oracle   Hyperion defines generations as hierarchical layers counted down from the highest ancestor (Generation 0); other data sources define generations differently

Drilling options are data-source specific. Drilling options that are not supported by the data source default to Drill to Next Level.

### **Expand on Drill**

The Expand on Drill drilling option sets the drilling return set to augment or replace currently displayed dimension members. You can set Expand on Drill for the current document through the data object shortcut menu (Drill / Drill Options). Expand on Drill can also be set for all subsequently created documents through Drilling preferences.

When Expand on Drill is selected the drilling return set is added to currently displayed dimension members. When Expand on drill is disabled the drilling return set replaces currently displayed dimension members.

### **Selected Member Data Display Option**

The Selected Member data display option specifies that the query result set should include the member from which advanced member selections are defined.

For example: If you specify Also Select Children on the Year dimension member and Selected Member is enabled, Year and all of its children are returned by the query. When Selected Member is disabled, only the children of year are returned.

This Selected Member functionality also impacts the drilling result set, by including or excluding the drilled member in the drilling result set.

Additionally, you can enable the Selected Member First data display option, to ensure that the drilled member is listed above the drilling result set.

### **Drilling Variations**

These data display and drilling option combinations result in drilling return sets that differ. If you are aware of this dynamic you are better prepared to receive the intended drilling return set.

Drilling Variation	Description
Drilling down with Expand Drilling enabled and Data <b>Display</b> / <b>Selected Members</b> disabled	Augments current member selections with the drilled return set and removes the drilled member.
Drilling down with Expand Drilling enabled and Data <b>Display</b> / <b>Selected Members</b> enabled	Augments current member selections with the drilled return set and includes the drilled member.
Drilling down with Expand Drilling disabled and <b>Data Display</b> / <b>Selected Members</b> disabled	Replaces the current member selections with the drilled return set and removes the drilled member.
Drilling down with Expand Drilling disabled and <b>Data Display</b> / <b>Selected Members</b> enabled	Replaces the current member selections with the drilled return set and includes the drilled member.

### **Drill Linking**

Drill linking enables you to navigate to other documents by double-clicking cells with replaced links.

It is important to distinguish drilling from drill linking. Drilling navigates along the lines of the dimensional hierarchy. Linking passes the current member selection to other documents and executables.

Linking differs from LROs in that linking passes the current member selection. LROs are linked to cell notes, file attachments, and URLs.


To access the Drill Link Options dialog box, right-click and select Drill, then Drill Link Options.

Drill Linking Option	Description
Link From	Indicates the dimensions, attributes, and data on which links can be set.
Link To	Indicates the destination document of the link.
Add	Displays the Open dialog box to select the link destination.
Remove	Removes the link and restores conventional drill navigation.
Bottom	Executes linking only at the lowest dimension level.
Pass Pages	Passes the Page context to the link destination.
Pass Filters	Passes the Filter context to the link destination.

### **Defining Drill Links**

- To define a drill link:
- 1 Right-click the data object and select Drill, then Drill Link Options.
  - The **Drill Link Options** dialog is displayed.
- 2 Click the ellipses (...) (in the Add column) for the dimension on which to place the drill link.
  - The Select a Document dialog is displayed.
- 3 Click the document to be displayed, then click OK. You are returned to the Drill Link Options dialog.
- 4 Select options in the Bottom, Pages, and Filters columns as needed.
  - The Bottom option indicates that the drill link is executed only at the lowest level of the specified dimension. The Pages option passes the Page axis context to the document. The Filter option passes the Filter axis context to the document.
- If you selected the Filters option, the Advanced column is enabled .Click the Advanced ellipses (...) to open the Drill Links Options dialog where all the dimensions with corresponding checkboxes are listed. You can select/deselect filter dimensions for the specific dimension that has a drill link report defined,

or, click the Select All or Deselect All buttons to select or deselect all dimensions respectively.



6 Click OK.

## **Dragging**

You can drag or move dimension member labels between Information panel axis segments:



- To move a dimension using the Information panel:
- 1 Select the View Pane Information Panel tab.
- 2 Click an axis segment icon to expand the segment.
- 3 Click and hold dimension member.
- 4 Drag the dimension member between axes or other dimension members and release the mouse button.

The dimension is relocated.

**Note:** The requirement to have at least one row dimension and one column dimension, may prevent you from dragging dimensions that leave an axis empty. In this case, use Data Layout to rearrange the dimension layout.

### **Undo and Redo**

An index containing the last 10 executed commands is cached on each client. The Undo command reverses the most recent command. The Redo command repeats the last command.

- To undo the last command, perform one action:
- Select Edit, then Undo.
- Click
- To reinstate the last command,
- Select Edit, then Redo.
- Click .
- To undo or redo one of the previous 10 commands, perform these actions:
- 1 Select the undo or redo list from the corresponding toolbar button.
- 2 Select a command from the index.

All commands through that point in the index are undone or redone, as selected.

8

# **Formatting Documents**

#### **In This Chapter**

Formatting Options	91
Other Kinds of Formatting	92
Formatting Order of Precedence	92
Data Display Options	93
Formatting Dialog Box	96
Cell Formatting	99
Sizing Columns	100
Changing and Locking Display Types	101
Spreadsheet Options	101
Charts and Chart Types	102
Chart Properties	103
Selecting Color	110
Font Properties	110
Selecting Graphics	111

## **Formatting Options**

Documents display data values returned from the data source in a data object. Multiple data objects can occupy a document, and each data object's display type can differ:

- Spreadsheet
- Chart
- Pinboard
- SQL Spreadsheet
- Free-form grid

Each display type has formatting options. This chapter describes the formatting options for spreadsheets and charts, as only these two objects can be modified through EPM Workspace.

#### **Related Topics**

"Pinboards" on page 187

"Creating SQL Spreadsheets" on page 196

## **Other Kinds of Formatting**

- Display Type—Converts spreadsheet data objects to charts or pinboards.
- **Data Display options**—Sets document behavior through the data object shortcut menu (or preferences, for subsequently created documents).
- Formatting options—Formats dimension headers and cell ranges. You can restrict formatting by member selection or cell value. Formatting options include currency formatting and positive and negative numeric formatting. See "Formatting Dialog Box" on page 96. Formatting options include:
  - Measures formatting (Available in Web Analysis Studio only)
  - Default formatting preferences
  - Ad hoc formatting
  - Data formatting analysis tool
  - Cell FormattingSee "Formatting Data" on page 98.

The scope of formatting depends on its source. To review all formatting definitions applied to a document, you must consult preferences, the Analysis Tools Manager, the Information Panel, and various document, data object, dimension and cell property settings.

## **Formatting Order of Precedence**

The formatting order of precedence cannot be changed for Database Connection Measures formatting, User Preferences, and Analysis Tools formatting. Formatting is applied in order of precedence:

- 1. **Measures formatting** Applied globally to dimensions on database connections. Settings are saved with the database connection. See "Creating OLAP and Oracle | Hyperion Database Connections" on page 158.
- 2. **Default formatting preferences** Applied globally to column and row headers, and data values. Settings are saved in preference files. See "Default Formatting Preferences" on page 263.
- 3. Formatting Applied ad hoc from the data object shortcut menu on dimension members. It is stored with the document definition and applied as a preliminary Analysis Tool definition. See "Formatting Dialog Box" on page 96.
- 4. **Data formatting analysis tool** Applied after Data Formatting Analysis Tool definitions are created and applied. It is stored with the document and applied from the Analysis Tools Manager. See "Data Formatting" on page 125.

5. Cell formatting — Applied ad hoc to cell ranges, and is stored with the document. See "Formatting Data" on page 98.

#### Preferences and formatting options:

There are some identical formatting options and preferences. Preferences are global settings applied to documents. Preferences, however, can be overridden by database connection formatting and document-based formatting.

The formatting order of precedence can be changed for Database Connection Measures formatting, User Preferences, and Analysis Tools formatting. For example, Analysis Tools formatting can be set to override all Database Connection and User Preferences formatting for a specific report.

Order of formatting precedence:

- 1. Formatting options saved with documents
- 2. Formatting options saved with the database connection
- 3. Formatting options specified by the User Preferences dialog box

## **Data Display Options**

Each display type has data display options specifying document behavior:

- Label mode—Essbase and Financial Management enable administrators to define multiple alias tables. Web Analysis Studio enables you to specify which alias table to use. Alias table selection is saved as a database connection property. See "Setting the Label Mode" on page 94.
- Dimension header sort—Order column and row headers in a query result set using Dimension Header Sort definitions. Dimension Header Sort options are determined by the data source. See "Sorting Dimension Headers" on page 95.
- Suppression—Suppresses rows with missing data, rows with zeroes, and in the case of Essbase, rows with shared members. Suppression can be set from the Data Layout dialog box, Data Display shortcut menu or OLAP Server preferences.

Data Display Option	Description
Selected Member	Displays the explicit member selection made in the query. This member selection can be previewed in the Information panel, or Dimension Browser. Selected Member provides a method for displaying this information in data objects.
Selected Member First	When Selected Member is active, enables you to position the explicit member selection made in the query definition first (from left to right, or top to bottom).
Default Label Mode	Toggles between label modes:  Descriptions IDs Both (Financial Management option)

Data Display Option	Description
Dimension-Specific Label Mode	Toggles between label mode options:  Use Default Descriptions IDs Both (Financial Management option)
Display Entity Currency	When using Financial Management data sources with defined Entity dimension currency information, you can enable the Display Entity Currency option to append Entity dimension members with currency value. This can be set before querying using Data Layout options, after querying using the Data Display shortcut menu, and for all subsequently created documents using OLAP Server preferences. See "Financial Management" on page 169.
Dimension Header Sort	Orders the selected dimension per the order option:  Default Ascending Descending Level (OLAP specific) Generation (OLAP specific) Selection Order (Relational specific) The Default option is the order in which dimension members are naturally ordered by data source outlines. Using this option may offer improved performance.  For a complete description, See "Sorting Dimension Headers" on page 95.
Show Linked Reporting Object Indicators	Shows or hides small cell triangles indicating the presence of Linked Reporting Objects. Triangles persist for related content.
Suppress	Omits data, as specified, from the query result set:  Missing Rows  Missing Columns  Shared Members  Zero Rows

## **Setting the Label Mode**

Alias tables are database tables storing alternate description labels for dimension members.

Essbase and Financial Management enable administrators to define multiple alias tables. Web Analysis Studio enables you to specify which alias table to use. The alias table selection is saved as a database connection property. See "Alias Tables" on page 265.

You can specify to display the member ID or its description label from the alias table.

• The ID number is a column of unique values distinguishing members from all other members.

 Description displays the alias table description. Web Analysis Studio uses the Description label when no label mode is specified.

Financial Management users have an additional label mode option. They can select the Both option to display the ID label and description.

You can set the default label mode before querying using Data Layout options or the last step in the document creation wizard, and after querying using the data object shortcut menu. You can specify which description label to use in dimensions, using Dimension Browser and the data object shortcut menu.

The Description label comes from the alias table setting, saved per database connection and per active user as a database user preference.

- To set the default label mode for the current database connection:
- 1 Right-click dimension header.
- 2 Right-click and select Data Display.
- 3 Select **Default Label Mode** from the drop-down list.
- 4 Select IDs or Descriptions.
- To set the label mode for a dimension:
- 1 Right-click a dimension header.
- 2 Right-click and select **Data Display**.
- 3 Select the dimension-specific Label Mode from the drop-down list.
- 4 Select Use Default, IDs or Descriptions.

Default label mode coordinates the label mode of the selected dimension with all other dimensions displaying the default label mode. Default label mode can be set for all dimensions in a query through Data Layout, and per dimension by Dimension Browser or the Data Display shortcut menu.

### **Sorting Dimension Headers**

You can order column and row headers in a query result set using Dimension Header Sort definitions. Dimension Header Sort options are determined by the data source.

For Example, Essbase enables you to order columns and rows in default, ascending, descending, level or generation order. The default order is the natural order in which dimension members are returned, based on the data source outline.

- To indicate a Dimension Header Sort definition:
- 1 Right-click a dimension member header and select Data Display, then Dimension Header Sort.
  The Dimension Header Sort submenu is displayed.
- 2 Select Default, Ascending, Descending, Level or Generation.

### **Relational Dimension Header Sort**

You can order the result set returned by relational SQL queries in Ascending, Descending, Selection Order or Default order. Default returns members based on the data source outline. Selection Order is the member selection order in Dimension Browser.

Unlike OLAP servers, relational cubes are compiled by Web Analysis Studio, and the label mode, alias tables, and selection order are manually coordinated. Sort by alias may perform comparatively slow, as the default query result set is sorted by ID. Sorting by alias requires a complete client-side re-sort.

The source of the relational dimension header sort impacts performance. Defining a relational dimension header sort using Data Layout, prompts Web Analysis Studio to sort all dimensions as part of the current query result set.

Alternatively, sorting a relational dimension using the data object shortcut menu (Data Display / Dimension Header Sort) requires you to select dimension headers.

Lastly, you can apply dimension header sort definitions to relational generations defined in the Generation Editor. These definitions only impact the Dimension Browser sort order. Using the Order By Mode drop-down list, you can also specify orders by ID or Alias.

## **Formatting Dialog Box**

The Formatting dialog box indicates the members to which these formats are applied:

- Header font properties by member.
- Data value format and font properties by member.
- Edit the dimension members selected for formatting.
- Restore default formatting preferences.

Control	Description
Selections	Lists dimensions and members in the query. The dimensions that appear are based on the context of where the Formatting dialog box was invoked. For example, if Formatting is invoked from the rows, all row dimension and members are displayed. If Formatting is invoked from a cell, all dimensions and members in the query are listed.
Advanced	Shows the Dimension panel that enables you to select or deselect dimensions and apply formatting to specific dimension combinations. This mainly applies when there are two or more dimensions in the columns or rows.
Dynamic References	Provides selection of row or column references instead of selecting members from a report. Formatting is applied regardless of the member selection.
Apply to entire grid	Applies formatting defined to the entire spreadsheet query. When selected, the Selections section is grayed and a Formatting "All Members" item is added to the Analysis Tools Manager.
Header Font tab	Allows formatting of member labels fonts in the row and column headers.
Data Font tab	Allows formatting of data cells fonts. Conditional font or number formatting can be applied to specific data values that meet the defined criteria.

Control	Description
Data Format tab	Provides formatting to specific data values such as currency/prefix/suffix, as well as other numeric formatting. Conditional font or number formatting can be applied to specific data values that meet the defined criteria.
Conditional Formatting	Enables conditional formatting of dimension member selections based on the criteria defined in the operand drop-down list and value text box.
Conditional Formatting  — Operand drop-down list	Specifies the conditional formatting operand: >, >=, =, <=, <, or <>.
Conditional Formatting  — Value Text box	Specifies the conditional formatting value.
Restore Defaults	Restores the settings specified by the Default Formatting preferences.

#### **Formatting Behavior**

The behavior for the members that are selected prior to opening the Formatting dialog:

- When you right-click a column or row header and select Formatting, the context is completed automatically for the row or column member selections. This context can be edited and different member selections can be made.
- When you right-click a cell and select Cell Formatting, the context is completed for the cell intersection of members. This context cannot be edited.
- When you right-click a column or row header and select Analysis Tools, then Format, the Formatting dialog is opened without completed context.
- If the number of members in a dimension on a report exceeds 25, the dimension parent node is collapsed. You can click the node to expand it.
- If there is more than one dimension in the rows or columns, you can select from one dimension only or multiple dimensions.

#### **Using Dynamic References**

Instead of selecting members from a report, you can use Dynamic References to select a row or column reference. Formatting is applied regardless of the member selection. Also:

- If a member is drilled on, its formatting will "carry with it".
- If a swap or pivot is performed, the formatting will "carry" where possible.

#### Topics that discuss formatting:

- "Creating Formatting Definitions" on page 98
- "Formatting Data" on page 98

97

### **Creating Formatting Definitions**

- To create formatting definitions:
- 1 Right-click a column or row dimension header.
- 2 Select Formatting.

The Formatting dialog box is displayed.

- 3 Optional. To display the Dimensions panel, click Advanced.
- 4 To select a dimension, click its check box.

If you select one dimension from the Dimensions panel, the corresponding dimension members are displayed in the Combinations panel.

If you select multiple dimensions from the Dimensions panel, the Combinations panel displays dimension member aggregations.

- 5 To specify dimension members, click the check boxes in the **Combinations** panel.
- 6 To specify a formatting definition, perform an action:
  - To specify header cell font properties for the dimension member selection, click the Header Font tab.
  - To specify data cell font properties for the dimension member selection, click the Data Font tab.
  - To specify leading and trailing text and numeric formatting, click the **Data Format** tab. See "Formatting Data" on page 98.

**Note:** The Data Font and Data Format tabs provide conditional formatting where you can refine formatting definitions. Select **Conditional Formatting**, then select an operand and specify a value.

7 Click **OK** to accept the formatting definition properties for the dimension member selection.

The formatting definition is listed in Analysis Tools Manager for future reference, and the definition is applied to the document.

## **Formatting Data**

You define format definitions in the Data Format tab:

**Note:** For behavior when formatting Date and Text Measures cells, see "Date and Text Cell Behavior" on page 50.

Formatting Options	Description
Conditional Formatting	Enables conditional formatting of dimension member selections based on the criteria defined in the operand drop-down list and value text box.

Formatting Options	Description
Replace Missing With	Enables you to replace missing data with zeros or text that you specify.
Leading and Trailing Formatting	
Currency Symbol	Inserts currency formatting symbols into the Positive Prefix and Negative Prefix text boxes.
Positive Prefix	Specifies the character to precede positive numeric values.
Positive Suffix	Specifies the character to follow positive numeric values.
Negative Prefix	Specifies the character to precede negative numeric values. <b>Caution:</b> The minus sign (-) is the default prefix. Deleting the default prefix without replacing it displays negative values as positive.
Negative Suffix	Specifies the character to follow negative numeric values.
Numeric Formatting	
Grouped Thousands	Displays numeric digits as grouped by thousands.
Minimum Decimals	Indicates the minimum number of decimal places displayed.
Maximum Decimals	Indicates the maximum number of decimal places displayed.
Scale	Enables abbreviated values by tens, hundreds, thousands, ten-thousands, hundred-thousands, millions, and billions.
Use Negative Color	Indicates that negative numbers are signified by a selected color.
Select Negative Color	Enables you to select the color representing negative values.
Date Formatting	Select a date format.
Samples	
Update Samples	Updates the samples panel based on the most recent formatting selections.

# **Cell Formatting**

The Cell Formatting dialog box enables you to format cell ranges ad hoc.

- Format data value font properties for cell ranges.
- Set text and numeric formatting for cell ranges.
- Restore default formatting preferences.

To define cell formatting, right-click a spreadsheet cell and select Cell Formatting:

Controls	Description
Selections	Displays the cell dimension member selection statement.

Controls	Description
Data Font tab	Enables you to select font properties for the cell.
Data Format tab	Enables you to specify text and numeric formatting.
Restore Defaults	Restores the settings specified by the Default Formatting preferences.

## **Sizing Columns**

Columns can be individually sized, uniformly sized, or reset to their default column width.

The Freeze Headers formatting option must be enabled in the preferences or the Spreadsheet Options dialog box before you can size columns.

## **Sizing Individual Columns**

- To size a column:
- Right-click a column header and select Column Sizing, then Custom Width from the shortcut menu. When the Column Width dialog box is displayed, enter the desired column width in pixels. The default is 75 pixels.

## **Sizing All Columns to a Common Width**

- To size all columns uniformly:
- To size one column:
  - Position your mouse over the border between two column headers. When the cursor changes to the double-arrow cursor, drag the column border to adjust the column width.
  - Right-click a column header and select Column Sizing, then Set Column Width from the shortcut menu. When the Column Width dialog box is displayed, enter the desired column width in pixels.
- When you are satisfied the selected column size, right-click that column and select Column Sizing then, Set All Columns To This Width.

The remaining columns are automatically resized to the selected column's width.

### **Autosizing Column Width**

To size all column widths so that headers display without truncation, select Column Sizing, then Autosize from the header shortcut menu.

**Note:** You must save the document before closing it to preserve the column widths.

## **Changing and Locking Display Types**

- To change the current display type, select the Display menu, and select a display type or chart type from the submenu.
- To prevent others from changing the current display type:
- Right-click the current content tab and select Properties. The File Properties dialog box is displayed.
- Select the Advanced tab.
- In Document Usage, select Change Display Type.
- Click OK.

See "Modifying Document Properties" on page 31.

## **Spreadsheet Options**

All spreadsheet formatting options are set using the Spreadsheet Options dialog box, accessed from the spreadsheet data object shortcut menu. You can set these options for all spreadsheets subsequently created using Spreadsheet preferences.

Spreadsheet Option	Description
Display	
Gridlines	Sets the spreadsheet to display table gridlines.
Transparent	Makes the cell background transparent to display a spreadsheet background image.
Row Banding	Sets spreadsheet rows to display alternating banding.
Column Banding	Sets spreadsheet columns to display alternating banding.
Background Color	Opens the Select Color dialog box, to set the background color.
Background Image	Opens the Select Background Image dialog box.
Row Band Color	Opens the Select Color dialog box, to set the color of row banding.
Column Band Color	Opens the Select Color dialog box, to set the color of column banding.
Headers	
Custom Row Height	Sets a fixed height for spreadsheet rows in point size (from 20-200).
Freeze Headers	Holds column dimension headers in place as cells scroll independently. Note: Freeze Headers must be enabled for Column Sizing.
Row Titles	Displays column headers for nested rows.

Spreadsheet Option	Description
Row Header Alignment	Aligns row headers left, center, or right or indents them based on generation.
Indent Amount	Indicates the number of pixels to indent row headers for each level from the top of the dimension hierarchy.
Row Group Alignment drop- down list	Aligns rows as a group center, top, or bottom in a cell.
Header Font	Displays the Font Properties dialog box, enabling the selection of header fonts and font formatting.
Header Background Color	Opens the Select Color dialog box, where you can set the header background color.
Sample Header	Displays the current header formatting.
Column Header Alignment	Justifies column headers; Center (default), Left or Right.
Data	
Align Text	Sets the alignment of textual data values: left, center, and right.
Align Values	Sets the alignment of numeric data values: left, center, and right.
Cell Font	Displays the Font Properties dialog box enabling the selection of data value fonts and font formatting.
	Note: Font sizes are limited to a maximum of 100 points.
Cell Background Color	Opens the Select Color dialog box where you can set the cell background color; does not override banding.
Sample Cell	Displays the current data values formatting.

# **Charts and Chart Types**

Charts are graphic representations of spreadsheet data. Their visual nature expedites quick analysis, color coding, and cues that aid comparisons.

Charts, depending on the chart type, can display one to four dimensions. Pie charts only display one dimension; quadrant charts offer more complex displays.

Charts can be rendered using a variety of chart types:

Chart Type	Compares
Bar	Similar elements, represented as vertical bars.
Line	Items over time.
Spline	Displays the document as a spline chart.
Pie	Contributions.
Area	Items over time.

Chart Type	Compares
Curve Area	Items over time, represented as a curved area.
Horizontal Bar	Similar elements.
Marks	Items over time.
Pareto	Trends in data.
Вох	Displays the document as a box plot chart.
Quadrant	Two members from one dimension over time.
Bubble	Displays the document as a Bubble chart.

Only the first 50 dimension members can be accommodated on chart axes.

### **Pie Charts**

Special Features of Pie Charts:

- Wedge separation
- Pie rotation

Drag pie wedges along the radius of the pie. Click and drag to rotate the pie chart. Only 19 multiple pie charts can be displayed simultaneously on the data object.

### **Quadrant Charts**

In Quadrant charts, at least one dimension must be placed on the column axis and at least two dimensions must be placed on the rows axes. Other dimension-axes arrangements result in error messages.

### **Bubble Charts**

Bubble charts require three dimensions. Only one dimension can be placed on the column axis. One or two dimensions can be placed on the row axis. There must be two columns in the dimension positioned on the columns axis. These columns may be the result of selecting two dimension members, or of including a calculated column with a dimension member. The values in the first two columns provide the X and Y values required to plot the chart.

A third column provides the Z value used to determine the bubble size. If no third column is available, a constant of 100 is used to determine the bubble size.

## **Chart Properties**

Use the data object shortcut menu to access Chart Properties, described in these topics:

- "General Chart Properties" on page 104—Options for effects, object borders, chart backgrounds, and legends.
- "Titles Chart Properties" on page 105—Options for chart titles.
- "Axes Chart Properties" on page 105—options for axes, number formatting, gridlines, scale, and labels.
- "Series Effects Chart Properties" on page 106—Options for chart behavior and border formatting.
- "Series Chart Properties" on page 107—Options for chart object properties.
- "Pie Chart Properties" on page 108—Options for pie charts.
- "Bubble Chart Properties" on page 108—Options for bubble charts.

### **General Chart Properties**

Control	Description
Layout	
Chart Type	Enables you to set the Chart Type: Bar, Line, Spline, Pie, Area, Curve Area, Horizontal Bar, Marks, Pareto, Multi, Box, Quadrant, and Bubble.
Stacked	Enables you to arrange chart objects: Side-by-Side, Stacked, and Stacked 100%.
Left Plot Area Margin	Enables you to specify a left margin for the plot area.
Right Plot Area Margin	Enables you to specify a right margin for the plot area.
Effects	
3D	Represents chart objects in three-dimensional space.
Anti-alias Fonts	Enables and disables the use of anti-alias fonts. Although anti-alias fonts are clearer, they sometimes differ from the original font style.
Cluster (Z-axis)	Arranges chart objects along the Z axis in three-dimensional space.
Show Z-axis Labels	Displays labels along the Z axis (front to back). This feature is only available when the chart is clustered, and for Bar, Horizontal Bar, Pareto and Multichart chart types. Long Z-axis labels may be cut off by chart margins.
Background	
Background Color	Displays the Select Color dialog box where you can set the chart background color.
Plot Area Color	Displays the Select Color dialog box where you can set the plotter background color.
Background Image	Displays the Select Graphic dialog box where you can set the chart background image.
Legend	
Show Legend	Displays a chart legend.
Position	Locates the Legend to the Top, Left, Bottom, or Right of the chart.

Control	Description
Color	Displays the Select Color dialog box to set the legend background color.
Font	Displays the Font Properties dialog box to select font and their formatting.

# **Titles Chart Properties**

Control	Description
Header Title	Sets the text string for the header title.
Footer Title	Sets the text string for the footer title.
Left Title	Sets the text string for the left title.
Right Title	Sets the text string for the right title.
Font	Displays the Font Properties dialog box to select font and their formatting.

# **Axes Chart Properties**

Control	Description
Axis	Indicates the current axis:
	X-axis - Sets the Axes tab to display x-axis parameters.
	Y-axis - Sets the Axes tab to display y-axis parameters.
	Secondary Y-axis - Set the Axes tab to display secondary y-axis parameters. See also Series Tab, Assign to Secondary Y-axis.
Show Axis	Displays the current axis.
Scale	
Auto-calculate	Enables the current axis to be calculated automatically based on data values.
Start at Minimum Value	Indicates whether to start numeric labels with the minimum value.
Minimum	Sets the minimum value on the current axis.
Maximum	Sets the maximum value on the current axis.
Step	Sets the number of increments to scale on the current axis.
Scale	Enables you to indicate the multiple by which to scale the current axis: None, Tens, Hundreds, Thousands, Ten Thousands, Hundred Thousands, Millions, or Billions.
Gridlines	
Show Gridlines	Displays gridlines on the current axis.

Control	Description	
Style	Represents gridlines using one style: Solid Line, Dash, Dot, and Dash Dot.	
Weight	Sets the width of gridlines in pixels (from 1-8).	
Color	Displays the Select Color dialog box where you can select a gridline color.	
Number Format		
Decimal Places:	Enables you to sets the number of decimal places used to represent data values (0-10).	
Format:	Enables you to sets the numeric format for data values: Numeric, Currency, Percent.	
Currency Symbol:	Inserts currency formatting symbols:	
Labels		
Stagger	Alternates labels on two lines to accommodate larger labels.	
Angle	Enables you to indicates the angle at which labels extend from the current axis: 0-360 degrees.	
Font	Displays the Font Properties dialog box to select fonts and their formatting.	

# **Series Effects Chart Properties**

Series Effects chart properties impact all chart object series in general. Series chart properties are applied only to specific series.

Control	Description	
Charting		
Enable Scrolling	Allows you to specify the number of chart object groups to display, and to scroll left to right to display additional groups. Note: Scrolling is not supported on Quadrant, Box, Pie, and Bubble chart types.	
Number of Groups Displayed	Specifies the number of chart object groups to display.	
Chart All Dimensions	Delineates nested dimensions for chart type requirements and displays each combination set as a series.  Chart type requirements differ for dimension member position and number. When dimension members exceed a requirement, surplus dimensions are relocated to the page axis so that the designated chart type can be displayed. Enabling Chart All Dimensions prompts Web Analysis Studio to delineate nested dimensions and display each combination set as a series.	
Borders		
Show Borders	Represents chart objects with a border or outline.	
Style	Represents the chart object border using one style: Solid Line, Dash, Dot, and Dash Dot.	
Width	Sets the width of chart object border in pixels (from 1-8).	
Color	Displays the Select Color dialog box where you can set the border color.	

# **Series Chart Properties**

Control	Description
Series	Indicates the current dimension member chart object series.
Style	
Show Series	Displays the current series.
Туре	Sets the chart type for the series when multiple chart types are enabled: Bar, Line, Area, Spline and Curve Area.
Shape	Sets the series chart object to one shape: Bar, Cylinder, Diamond Bar, or Triangle Bar.
Color	Displays the Fill Properties dialog box where you can set chart object color, pattern fill, or gradient.
Assign to Secondary Y-axis	Displays the current series on the secondary y-axis.
Markers	
Style	Sets the series to one marker: None, Square, Circle, Triangle-Up, Diamond, Cross, Triangle-Down, or Multiple Chart Type.
Image Marker	Displays the Select Graphic dialog box enabling graphics to be used as chart markers. Note: You cannot use animated GIFs as marker images.
Size	Sets the size of the series marker in pixels (1-20).
Point Values	
Show Values	Displays data values with the series.
Font	Displays the Font Properties dialog box where you can select font and their formatting.
Angle:	Indicates the angle at which value labels extend from the current series: 0-360 degrees.
Lines	•
Style	Represents the chart object border using one style: Solid Line, Dash, Dot, and Dash Dot.
Width	Sets the width of chart object border in pixels (from 0-8).
Apply selections to all.	Sets all series to the parameters of the current series.

## **Filling Chart Objects**

Like the Select Color dialog, the Fill Properties dialog enables you to select colors for a series of chart objects. In addition, it differentiates chart objects with a pattern or gradient fill.

- To fill chart objects with a pattern fill:
- 1 Select Chart Properties from the chart shortcut menu.

- Click the Series tab, and Color in the Style group.
  - The Fill Properties dialog is displayed.
- Click the Pattern Fill option and select a pattern. You can combine two colors in the selected pattern.
- Click Color 1 or Color 2 to select a color from the Select Color dialog.
- To fill chart objects with a gradient fill:
- Select **Chart Properties** from the chart shortcut menu.
- Click the Series tab, and Color in the Style group. The Fill Properties dialog is displayed.
- Click Gradient Fill, and select the direction of the gradient. You can combine two colors in the gradient.
- Click Color 1 or Color 2 to select a color from the Select Color dialog.

## **Line Widths of Zero (0)**

Line charts accommodate a line width of zero, enabling a line chart to appear as a marks chart. This applies only to two-dimensional line, quadrant, multichart, spline, area, and curve area chart types.

### **Pie Chart Properties**

Control	Description	
Values		
Values	Indicates the current pie slice.	
Color	Displays the Select Color dialog box to set color, pattern fill or gradient scale for the current slice.	
Labels		
Show Values	Displays data values with pie slices.	
Position	Indicates where to display labels: Inside Slices or Outside Slices.	
Font	Displays the Font Properties dialog box where you can select font and their formatting.	
Show Multiple Pies	Sets Page Dimensions to be displayed as multiple pie charts in one document.	

## **Bubble Chart Properties**


Bubble charts require three dimensions. Only one dimension can be placed on the column axis. Up to two dimensions can be placed on the row axis. There must be two columns in the dimension positioned on the columns axis. These columns may be the result of selecting two dimension members, or the result of including a calculated column with a dimension member. The values in the first two columns provide the X and Y values required to plot the chart.

A third column provides the Z value used to determine the bubble size. If no third column is available, a constant of 100 is used to determine the bubble size.

Control	Description	
Effects		
Marker Style:	Sets the bubble chart to be displayed using these options: none, square, circle, Triangle Up, Diamond, Cross, Triangle Down, or Multi.	
Maximum Size:	Sets the maximum bubble object size in points.	
Show Points	Displays plot points.	
Point Color	Sets the color of the center point.	
Values		
X-member Values:	Indicates the dimension member used to plot x-axis values.	
Y-member Values:	Indicates the dimension member used to plot y-axis values.	
Z values:		
Constant	Sets the constant used to plot the size of bubble chart objects when no third column is available, so that object sizes match.	
Z-member Values:	Indicates the third column used to plot the size of bubble chart objects.	
Scaling		
Minimum Scaling:	Sets the minimum bubble size when the bubble object size has reached the Maximum Size limit.	
Maximum Scaling:	Sets the maximum bubble size when the bubble object size has reached the Maximum Size limit.	
Scale On:	Sets the bubble chart to determine scale using area or diameter.	
Borders		
Show Borders	Displays or hides the bubble borders.	
Use Traffic Lights for Colors	Sets the bubble object border to use colors specified in the traffic lighting definition; only one dimension, with a traffic lighting definition, can be positioned on the rows axis	
Color	Displays the Select Color dialog box.	
Border Width:	Sets the border width in pixels.	

## **Chart Preview**

Clicking Preview displays an abstract of current chart parameters.



## **Selecting Color**

The Select Color dialog box enables you to set object, font, and component colors.

Control	Description	
Swatches Tab	Swatches Tab	
Recent	Displays recently selected colors.	
RGB Float Over Values	Displays the Red-Green-Blue color values when mouse is floated over a color.	
HSB Tab		
Hue	Sets the percentage of hue in the current color.	
Saturation	Sets the percentage of saturation in the current color.	
Brilliance	Sets the percentage of brilliance in the current color.	
Red	Displays the red value of the current color.	
Green	Displays the green value of the current color.	
Blue	Displays the blue value of the current color.	
RGB Tab	RGB Tab	
Red	Displays the red value of the current color.	
Green	Displays the green value of the current color.	
Blue	Displays the blue value of the current color.	
Preview	Displays the application of the current color.	

## **Font Properties**

The Font Properties dialog box enables font selection and formatting.

Control	Description
Font	Sets the font family.
Size	Sets the font point size. Note: Fonts are limited to 100 points in size.
Font Style	
Bold	Displays the <b>bold</b> font.
Italic	Displays the italic font.
Color	Displays the Select Color dialog box, to enable font color selection.
Sample Text	Displays the current font selection.

## **Selecting Graphics**

The Select Graphic dialog box enables you to select the GIF or JPEG files used in Web Analysis Studio.

Control	Description
Center	Centers the selected graphic in the panel.
Stretch	Expands the selected graphic to fill the panel.
Tile	Repeats the selected graphic to fill the panel.
Top-Left	Aligns the graphic in the top left corner of the panel.
Color	Provides a color palate from which a color can be selected.
Load	Displays the Open dialog box, to select the GIF or JPEG graphic file.
Clear	Deletes the previously selected image.

9

## **Managing Analysis Tools**

**In This Chapter** 

Analysis Tools	113
Activating and Deactivating Analysis Tools	115
Editing Definitions	115
Show/Hide Only	115
Traffic Lighting	118
Sorting	121
Restricting Data	122
Retrieve Only Top/Bottom	124
Data Formatting	125
Calculations	126
Creating SAP BW Currency Conversion Definitions	138
Creating SAP RW Unit of Measure Conversion Definitions	138

## **Analysis Tools**

Web Analysis Studio enables you to leverage server-based analytical formatting tools and data source-specific tools from the client. Analysis Tools expedite comparisons, visually organize data, and promote structures and conclusions.

Analysis Tools are data source-specific, and all Analysis Tools are not available in all data objects.

Analysis Tools are centrally organized and applied by the Analysis Tools Manager, accessed using the data object shortcut menu. The Analysis Tools Manager features an Ordered By panel showing the number and order of Analysis Tools definitions activated on the current data object. Toolbar buttons enable you to generate Analysis Tools definitions.

Analysis Tool	Used To:
Traffic Lighting	Color-code dimension member values based on fixed limits or a comparison of values.  Traffic Lighting visually associates member values whether they are sorted or ranked.
Sorting	Order the query result set.
Calculations	Create calculated rows and columns.
Data Formatting	Format data values based on member or value criteria.

Analysis Tool	Used To:
Show/Hide Only	Filter data by color, value and member.
Related Content	Create Related Content links to:
	LROs - cell notes, URLs, and file attachments stored at Essbase intersections
	Oracle Essbase Integration Services drill-through content
	Financial Management cell text and line item details stored at Financial Management intersections
	Oracle   Hyperion Documents content displayed as HTML or PDF
	Oracle Hyperion Application Builder for J2EE content
Restrict Data	Restrict the query result set based on criteria.
Retrieve Only Top/Bottom	Limit and rank the query result set.
Currency Conversion	SAP BW—Converts data value currencies ad hoc during analysis, and to save those conversion definitions as analysis tools.
Unit of Measure Conversion	SAP BW—Converts the data value unit of measure ad hoc during analysis, and to save those conversion definitions as analysis tools.
Edit Selected Definition	Opens the Analysis Tool for the specified definition, enabling you to edit the definition.
Remove Selected Definition	Deletes the selected Analysis Tool definition.
Remove All	Deletes all defined Analysis Tools definitions.

#### **Related Content**

Related Content definitions can be managed from the Related Content dialog box and Analysis Tools Manager. Edits, including remove and remove all, made in the Related Content dialog box, change the content of the related content definition but do not impact the existence of the definition. You can activate, deactivate, reorder, and remove related content in the Analysis Tools Manager, but you cannot edit related content definitions.

## **Ordering Analysis Tools**

The order in which Analysis Tools definitions are applied affects data object behavior. You can edit the order in which Analysis Tools are applied by selecting Analysis Tools definitions and moving them in the Ordered By panel.

## **Default Analysis Tools**

The Analysis Tools Manager displays default formatting, measures formatting, and spreadsheet option definitions at the top of the Ordered by list panel. These definitions, originating from preferences, database connection properties, and data object properties, are applied before subsequent Analysis Tools definitions. They can be edited, but they cannot be removed or disabled.

## **Activating and Deactivating Analysis Tools**

You can activate and deactivate Analysis Tools definitions without removing them from the Analysis Tools Manager. This enables various Analysis Tools combinations to be used.

To deactivate Analysis Tools definitions, select the corresponding Active option in Ordered By.

## **Editing Definitions**

- To edit an Analysis Tools definition:
- Right-click a dimension member header and select Analysis Tools, then Analysis Tools Manager.
  - The Analysis Tools Manager is displayed.
- Select a definition and click Edit.
  - The corresponding Analysis Tool dialog box is displayed.
- Make selections and define parameters as needed.
- Click OK.
  - The Analysis Tools Manager is displayed.
- Click Close.

## **Show/Hide Only**

The Show/Hide Only analysis tool includes or excludes members by member name, traffic lighting color, or data value criteria. It is an effective means of focusing analysis by values.

The Information panel Show/Hide Only segment displays Show/Hide Only definitions that restrict or display information on the current document.

#### Topics that discuss the Show/Hide Only analysis tool:

- "Asymmetrical Analysis" on page 115
- "Multiple Show/Hide Only Definitions" on page 116
- "Differences in Show/Hide Only Definitions" on page 116
- "Creating Show/Hide Only Definitions" on page 117

## **Asymmetrical Analysis**

Asymmetric documents feature nested dimensions that differ (by at least one member) across an axis. Web Analysis Studio accommodates asymmetrical analysis by enabling you to hide specified rows, columns, and chart objects.

## **Multiple Show/Hide Only Definitions**

Multiple Show/Hide Only definitions are applied in order, enabling simultaneous control by member, color, and values.

## **Differences in Show/Hide Only Definitions**

Show/Hide Only definitions are applied differently for each methodology used:

- Show/Hide Only Calculations shows or hides all calculated members.
- Show/Hide Only Members shows or hides dimension members of the dimension header right-clicked in the document.
- Show/Hide Only Values shows or hides dimension members on the axis opposite the dimension header right-clicked in the document.
- Show/Hide Only Colors shows or hides dimension members on the axis opposite the dimension header right-clicked in the document.

Show/Hide Only definitions are created in the Show/Hide Only dialog box:

Control	Description
Select Method	Show - Displays only items satisfying the Show/Hide Only definition criteria.
	Hide - Hides only items satisfying the Show/Hide Only definition criteria.
Where	
Calculations	Shows or Hides all calculated members.
Member	Bases the Show/Hide Only definition on specified dimension members of the current axis.
Values	Tests whether members of the opposite axis contain values satisfying criteria of the current axis.
All Values	Tests whether all members of the opposite axis contain values satisfying criteria of the current axis.
Colors	Tests whether members of the opposite axis contain colors satisfying criteria of the current axis.
All Colors	Tests whether all members of the opposite axis contain colors satisfying criteria of the current axis.
Set Condition	
Operator drop-down list	Select an operator for your criteria: Greater than (>), Greater Than or Equal To (>=), Equal to (=), Less Than or Equal To (<=), Less Than (<), Not Equal To (<>).
Value Text box	Enables you to enter the value for Show/Hide Only Values conditions.
Color	Opens the Select Color dialog box to set the condition color.
Members	Lists available dimension members and attributes to which the Show/Hide Only definition is applied.
Advanced	Aggregates or separates dimension member combinations.
Apply	Applies the definition to the document.

## **Creating Show/Hide Only Definitions**

- To create a Show/Hide Only definition:
- 1 Right-click a dimension member header and select **Analysis Tools**, then **Show/Hide Only**.
  - The Show/Hide Only dialog box is displayed.
- 2 From Select Method, select Show or Hide.
- 3 Define one option:
  - To show or hide only calculated members, click the Where group Calculations option.
  - To show or hide specified members, click the Where group Members option and select dimension members from Members.
  - To show or hide only dimension members if dimension member value satisfies a condition, perform these actions:
    - a. Click the Where group Values option.
    - b. Select dimension members from Members.
    - c. Use the operator list and the value area to define a condition.
  - To show or hide only dimension members when all dimension member values satisfy a condition, perform these actions:
    - a. Click the Where group All Values option.
    - b. Select dimension members from Members.
    - c. Use the operator list and the value area to define a condition.
  - To show or hide only dimension members if dimension member value satisfies a traffic lighting color condition, perform these actions:
    - a. Click the Where group Colors option.
    - b. Select dimension members from Members.
    - c. From the operator list, select Equal To (=) or Not Equal To (<>).
    - d. Click Color. The Select Color dialog box is displayed. Select one defined traffic lighting range color. The color displays in the large square. Click **OK**. The button displays the selected color.
  - To show or hide only dimension members if all dimension member values satisfy a traffic lighting color condition, perform these actions:
    - a. Click the Where group All Colors option.
    - b. Select dimension members from Members.
    - c. From the operator list, select Equal To (=) or Not Equal To (<>).
    - d. Click Color. The Select Color dialog box is displayed. Select one defined traffic lighting range color. The color displays in the large square. Click **OK**. The button displays the selected color.

**Note:** Show/Hide Only Members is applied to the named dimension member, and Show/Hide Only Values and Show/Hide Only Colors is applied to the opposite axis, using the values in the selected axis.

Color options are only enabled when the data object features an active traffic lighting definition. An Advanced option specifies conditions for dimension member combinations. Apply enables you to apply the definition to the current data object, without exiting the dialog box. Drag the dialog box title bar to see the data object underneath.

#### 4 Click OK.

The current definition is added to the Analysis Tools Manager.

5 Click Close.

## **Traffic Lighting**

The Traffic Lighting analysis tool color-codes data cells based on dimension member values. You can base color-coding on a comparison of two dimension members or by fixed limits on one dimension member. Colors graphically associate member values, whether they are sorted or ranked. Traffic Lighting definitions are maintained as the document is pivoted and changed.

The Information panel Traffic Lighting segment displays the Traffic Lighting definitions that color-code the current data object.

Traffic Lighting definitions are created in the Traffic Lighting dialog box:

Control	Description
Apply Traffic Lighting To:	Specifies the dimension to which traffic lighting is applied.
Comparing It To:	Specifies the dimension to which the preceding dimension is compared.
Assign Limits	Specifies the interval, set point, and color parameters that compose the traffic lighting definition.
% Differences	Indicates that the color-coding is based on the percent difference of the compared members. When disabled, color-coding is based on the value difference of the compared members.
Enable Financial Intelligence	Enables Oracle   Hyperion data sources to treat expenses and liabilities as negative values. Works in cooperation with the % differences option to reflect variance and variance percent calculations for the traffic lighting dialog box.
Advanced	Aggregates or separates dimension member combinations.
Apply	Applies the definition to the document.

#### Topics that discuss traffic lighting:

- "Financial Intelligence Variations" on page 119
- "Assign Limits Shortcut Menu" on page 119

- "Creating Traffic Lighting Definitions" on page 120
- "Setting Traffic Lighting Opacity" on page 120

## **Financial Intelligence Variations**

The % Differences and Enable Financial Intelligence options cooperate to provide four calculations for the Traffic Lighting dialog box.

- When neither option is selected, the Traffic Lighting dialog box compares selected members using a conventional **subtraction** calculation.
- When only the % Differences option is selected, the Traffic Lighting dialog box compares the selected members using a conventional **percent difference** calculation.
- When the Enable Financial Intelligence option is selected, the Traffic Lighting dialog compares the selected members using an advanced variance calculation that recognizes expenses and liability dimensions as negative values.
- When both options are selected, the Traffic Lighting dialog compares the selected members
  using an advanced variance percent calculation that recognizes expenses and liability
  dimensions as negative values.

Understanding the calculations and the nature of your dimension metadata helps you to better compare dimensions.

## **Assign Limits Shortcut Menu**

The Assign Limits color band and the Set Point arrows feature context-sensitive shortcut menus:

Control	Description		
Assign Limits Shortcut Menu			
Add Set point	Inserts a set point within the range.		
Set Color	Opens the Select Color dialog box where you can set the range color.		
Set Opacity	Opens the Opacity dialog box, enabling you to determine the percentage of transparency for the selected range color.		
Set Point Shortcut Me	Set Point Shortcut Menu		
Color Above Set point	Sets the set point color to that of values greater than the set-point.		
Color Below Set point	Sets the set point color to that of values less than the set-point.		
Delete Set point	Opens the Confirm Deletion message box where you can confirm intentional deletion of the set point.		

**Note:** Setting traffic lighting colors to colors used by Spreadsheet Options may obscure the color-coding of dimension members.

## **Creating Traffic Lighting Definitions**

- To create a traffic lighting definition:
- 1 Right-click a dimension member header and select Analysis Tools, then Traffic Light.
  - The Traffic Lighting dialog box is displayed.
- 2 Select the dimension member to which traffic lighting is applied, from Apply Traffic Lighting To.
- 3 From Comparing It To, select the dimension member to which the preceding dimension member is compared.
  - Compare to a fixed limit by disabling the % Differences option in the Assign Limits group box, or by selecting Fixed Value from Comparing It To.
  - Select the Advanced option to separate dimension members into combinations. Click it again to select from aggregated dimension members.

The Assign Limits option contains three default set points and colors.

- 4 Right-click ranges to:
  - Insert another set point.
  - Redefine the range color.
  - Set range opacity or transparency.
- 5 Right-click a set point arrow to:
  - Include the set point in the range above.
  - Include the set point in the range below.
  - Delete the set point.
- 6 Click the set point text box to enter or edit set point threshold values.
- 7 Click Apply.
- 8 Click OK.

## **Setting Traffic Lighting Opacity**

The Opacity dialog box enables you to define transparent traffic lighting ranges and set points, and to control the percentage of transparency for these ranges and set points.

This is especially valuable when you want background images to show through spreadsheets with color comparisons and traffic lighting definitions.

- To specify transparency for a traffic lighting range or set point:
- In the Traffic Lighting dialog box, right-click an Assign Limits range or set point and select Set Opacity.
- 2 The Opacity dialog box is displayed.
- 3 Drag the slider bar to the desire percentage of transparency.

- 4 If you want to apply this percentage of transparency to all other ranges and set points, click Apply to All Colors.
- 5 Click OK.

## **Sorting**

The Sorting analysis tool orders specified dimensions of the query result set in ascending or descending alphanumeric order. Sorting definitions are dynamic and are applied as the document is drilled, pivoted, and changed.

The Information panel Sorting segment displays all client-based sorting definitions.

Multiple sorting definitions are applied in the order presented by the Analysis Tools Manager. Sorting definitions applied to axes with equal values may subsequently be rearranged by sorting definitions applied to axes with diverse values. The document display is the result of the cumulative application of all active sorting, client-side and server-side, even though it may appear that only the last sorting definition is applied.

## **Sorting Dialog Box**

Sorting definitions are created in the Sorting dialog box.

Control	Description
Sort On	Specifies the dimension member to which the sorting definition is applied.
Order	
Ascending	Selects ascending alphanumeric order for the result set display.
Descending	Selects descending alphanumeric order for the result set display.
Apply	Apply the definition to the document.

## **Creating Sorting Definitions**

- To create a sorting definition:
- 1 Right-click a dimension member header and select Analysis Tools, then Sort.
  The Sorting dialog box is displayed.
- 2 Select the dimension member to which sorting is applied, from **Sort On**.
- 3 Select Ascending or Descending.
- 4 Click Apply.
- 5 Click OK.

## **Restricting Data**

The Restrict Data analysis tool provides another means of narrowing the return set, by requiring data values to be relevant to rules and operands. Data can be restricted by a comparison between columns or using fixed limits on one column.

The Information panel Restrict Data segment is displayed Essbase Restrict Data definitions for the current document.

Restrict Data is executed by Essbase. This can protect the network server from transmitting, and the client from processing, large result sets.

Although you can apply Restrict Data to the result set of a processed query (using the Analysis Tools shortcut menu), you can also define Restrict Data criteria before submitting a query. The last step in the Document Creation wizard enables you to create Restrict Data definitions.

#### Topics that discuss restricting data:

- "Restrict Data Controls" on page 122
- "Creating Restrict Data Definitions" on page 122

#### **Restrict Data Controls**

Control	Description
Select Column	Displays the Select Column dialog box, enabling you to select a column from the current document.
Operator drop-down list	Select an operator for your criteria: Greater than (>), Greater Than or Equal To (>=), Equal to (=), Less Than or Equal To (<=), Less Than (<), Not Equal To (<>).
Operand drop-down list	<ul> <li>Specifies one of three operands for restricting data:</li> <li>A value Of - Restricts Data to a value or range of values.</li> <li>The Data Value of Column - Displays a secondary Select Column button, enabling you to compare two columns.</li> <li>A Missing Value - Enables restriction of missing values.</li> </ul>
Value Text box	Enables you to enter the value for Restrict Data conditions.

**Note:** Only use one member per dimension in filters when restrict data and /or retrieve top/ bottom is applied. When multiple members are selected per dimension, the application aggregates the results. Because restrict data and retrieve top/bottom are parts of the Essbase query, the aggregation occurs after the query is returned and may result in unexpected result sets.

## **Creating Restrict Data Definitions**

- To create a Restrict Data definition:
- 1 Perform one:

- Right-click a dimension member header and select Analysis Tools, then Restrict Data.
- Right-click a dimension member header and select **Analysis Tools**. When the Analysis Tools Manager is displayed, select **New Restrict Data**.
- Select **Restrict Data** from Data Layout **Options**.
- In the last step of the Document Creation wizard, click Restrict Data.

The Restrict Data dialog box is displayed.

#### 2 Click Select Column.

The Restriction Columns dialog box is displayed.

3 Select the Column to which the Restrict Data definition is applied, and click **OK**.

Focus is returned to the Restrict Data dialog box.

- 4 Select an operator from **Operator**.
- 5 Select an operand from the Operand menu: A Value Of, The Data Value of Column, or A Missing Value.
- 6 Enter a data value in Value, as needed.
- 7 Click Add.

The restriction criteria is listed in the Restriction Definition frame. You can use the Advanced button to create compound definitions with additional criteria.

8 **Optional:** Click **Advanced** to add criteria, update the definition, remove one or all definitions, connect individual definitions with an AND or OR, or move a criteria.

Advanced Option	Sub menu	Description	
Add		Add the current rule to the Total Subset Definition.	
Update		Replace the selected rule with the current rule.	
Validate		Verifies the parenthetical syntax of the Total Subset Definition.	
Remove		Remove the current rule from the Total Subset Definition.	
Remove All		Remove all rules from the Total Subset Definition.	
Connect	And	Inserts the AND operand at the end of the currently selected rule. The AND operand is used by default when multiple rules are added to the Definition.	
	Or	Inserts the OR operand at the end of the currently selected rule.	
Move	Move Up	Moves up the currently selected rule in the Total Subset Definition.	
	Move Down	Move the currently selected rule down in the Total Subset Definition.	

9 Click OK.

## **Retrieve Only Top/Bottom**

The Retrieve Only Top/Bottom analysis tool leverages Essbase server-based sorting and ranking to control the size and order of an OLAP query result set. This can protect the network server from transmitting, and the client from processing, large result sets. The Retrieve Only Top/ Bottom analysis tool is central to top/bottom analysis.

Although you can apply Retrieve Only Top/Bottom to the result set of a processed query (using the Analysis Tools shortcut menu), you can also define Retrieve Only Top/Bottom criteria before submitting a query. Click the Data Layout Options button and select the Retrieve Only Top/ Bottom menu item, to define a Retrieve Only Top/Bottom definition before sending a query. The last step of the Document Creation wizard also enables you to create Retrieve Only Top/ Bottom definitions.

The Information panel Retrieve Only Top/Bottom segment is displayed all Essbase Retrieve Only Top/Bottom definitions for the current document.

## Behavior of multiple row dimension member selection

Retrieve Only Top/Bottom Analysis Tool restricts the use of multiple row dimension member selections, because Top/Bottom applies only to one dimension. When you add a dimension to a row and retrieve the top two members of a column, the Top/Bottom Analysis Tool displays the top two members for each member of the first dimension instead of the top two members of the selected column.

## **Analysis Tools and Multiple Filter Axis Dimension Members**

Multiple filter dimension member selections impact Retrieve Only Top/Bottom.

Multiple filter axis dimension members are aggregated before being sent in a query. Because the client-based aggregation does not exist in the data source server, the query is processed in terms of the data values on the server. The discrepancy between client aggregations and server-based sorting and ranking results in irregular result sets.

Nominate only single filter dimension member selections when using Retrieve Only Top/Bottom and Restrict Data analysis tools.

Control	Description	
Select Column	Specifies the columns to which the Retrieve Only Top/Bottom definition is applied.	
Show	Limits the result set to these criteria:	
Тор	Selects the number of highest data values indicated by the corresponding value text box.	
Bottom	Selects the number of lowest data values indicated by the corresponding value text box.	
Sorting		
Ascending	Displays the result set in ascending alphanumeric order.	

Control	Description	
Descending	Displays the result set in descending alphanumeric order.	
Clear	Deletes all Retrieve Only Top/Bottom definitions.	

## **Creating Retrieve Only Top/Bottom Definitions**

To create a Retrieve Only Top/Bottom definition:

#### 1 Perform one:

- Right-click a dimension member header and select **Analysis Tools**, then **Retrieve Only Top/Bottom**.
- Right-click a dimension member header and select **Analysis Tools**. When the Analysis Tools Manager is displayed, select **New Retrieve Only Top/Bottom**.
- Select **Retrieve Only Top/Bottom** from Data Layout **Options**.
- In the last step of the Document Creation wizard, click Retrieve Only Top/Bottom.
   The Retrieve Only Top/Bottom dialog box is displayed.
- 2 Select the column to which the Retrieve Only Top/Bottom definition is applied from Select Column.
- 3 Limit the result set by selecting Top or Bottom and indicating the number of members in Value.
- 4 Sort the result set by selecting Ascending or Descending.
- 5 Optional: To remove all selections from the current definition and start over, select Clear.
- 6 Click OK.

## **Data Formatting**

Data Formatting options automatically format headers and data values by dimension member and criteria. While formatting options are fixed, the formatting scope varies depending on the formatting source. See "Formatting Order of Precedence" on page 92.

**Note:** For behavior when formatting Date and Text Measures cells, see "Date and Text Cell Behavior" on page 50.

- To create a Data Formatting definition, right-click a dimension member header and select Analysis Tools, then Format.
- To edit Data Formatting definitions, right-click a dimension member header, select Analysis
   Tools, then Analysis Tools Manager, and double-click the desired data formatting
   definition.

For information on creating data formatting definitions, see the Chapter 8, "Formatting Documents" chapter.

## **Calculations**

You can create client-side calculated members, and edit, delete, and analyze these calculations.

The order of calculation definitions in the Analysis Tools Manager establishes a precedent for subsequent compound calculations. You can change the order of calculation definitions, by selecting the definition and clicking the up and down arrow buttons.

The complete list of calculations includes:

- "Absolute Value" on page 127
- "Average" on page 127
- "Cumulative" on page 127
- "Difference from Average" on page 127
- "Divide" on page 128
- "Linear Regression" on page 128
- "Maximum" on page 128
- "Maximum Value" on page 128
- "Minimum" on page 129
- "Minimum Value" on page 129
- "Multiply" on page 129
- "Percent" on page 129
- "Percent Difference from Average" on page 130
- "Percent of Difference" on page 130
- "Percent of Member" on page 130
- "Percent of Total" on page 130
- "Rank Ascending" on page 131
- "Rank Descending" on page 131
- "Subtract" on page 131
- "Sum" on page 131
- "Square Root" on page 131
- "Trend" on page 132
- "Variance" on page 132
- "Variance Percent" on page 132
- "Complex Calculations" on page 132
- "Creating Calculations" on page 133

• "Modifying Calculations" on page 137

#### **Absolute Value**

- Function Performed Returns the absolute value of a numeric value. The absolute value of a number is that number without a negative sign. A negative number becomes positive, while a positive number remains positive.
- Number of Arguments One member or calculation.
- Options Whether missing values should be set to 0 in the calculation and included in the number of arguments.

Example — If Actual is -100, the Absolute Value of Actual is 100.

## **Average**

- Function Performed Sum of all arguments divided by the number of arguments.
- Number of Arguments Two or more members or calculations.
- Options Whether missing values should be set to 0 in the calculation and included in the number of arguments.

Example — If Actual is 100 and Budget is 200, the Average of Actual and Budget is 150.

#### **Cumulative**

- Function Performed Provides a running total.
- Number of Arguments One member or calculation.
- Options Whether missing values should be set to 0 in the calculation.

Example — Consider a spreadsheet with Actual as a column and Colas, Root Beer, and Cream Soda as rows. If the Actual values for these products were 100, 200, and 300, the Cumulative column would be 100, 300, 600.

## **Difference from Average**

- Function Performed Subtracts each argument's average value from each occurrence of the argument.
- Number of Arguments One member or calculation.
- Options Whether missing values should be set to 0 for the purposes of the calculation.

Example — Consider a spreadsheet with Actual as a column and Colas, Root Beer, and Cream Soda as rows. If the Actual values for these products were 100, 200, and 300, the average would be 200. So the Difference from Average column would be -100, 0, 100.

#### **Divide**

- Function Performed Arithmetic division.
- Number of Arguments Two members or calculation.
- Options Whether missing values should be set to zero in the calculation.

## **Linear Regression**

- Function Performed Straight-line linear regression. Looks at all occurrences of the specified argument, and uses a linear regression algorithm to calculate a 'straight line' through the occurrences.
- Number of Arguments One member or calculation.
- Options Whether missing values should be set to 0 in the calculation.

Example — Consider a spreadsheet with Actual as a column and Jan, Feb, Mar as rows. If the Actual values for these time periods were 100, 300, and 600, the Linear Regression column would be 83, 333, 583. Notice that there is now a constant difference between each value (250). All points in the sequence are adjusted. A chart of these numbers would produce a straight line that goes through the original data points.

#### **Maximum**

- Function Performed Given two or more arguments, Maximum returns the name of the member or calculation that has the maximum value.
- Number of Arguments Two or more members or calculations.
- Options Whether missing values should be set to 0 in the calculation.

**Example** — Consider a spreadsheet with East and West as columns and Jan, Feb, Mar as rows. If the East values were 100, 300, and 600 and the West values were 200, 200, 300, the Maximum column would be West, East, East.

#### **Maximum Value**

- Function Performed Given two or more arguments, Maximum Value returns the value of the member or calculation that has the maximum value.
- Number of Arguments Two or more members or calculations.
- Options Whether missing values should be set to 0 in the calculation.

Example — Consider a spreadsheet with East and West as columns and Jan, Feb, Mar as rows. If the East values were 100, 300, and 600 and the West values were 200, 200, 300, the Maximum Value column would be 200, 300, 600.

#### **Minimum**

- Function Performed Given two or more arguments, Minimum returns the name of the member or calculation that has the minimum value.
- Number of Arguments Two or more members or calculations
- Options Whether missing values should be set to 0 in the calculation.

Example — Consider a spreadsheet with East and West as columns and Jan, Feb, Mar as rows. If the East values were 100, 300, and 600 and the West values were 200, 200, 300, the Minimum column would be East, West, West.

#### **Minimum Value**

- Function Performed Given two or more arguments, Minimum Value returns the value of the member or calculation that has the minimum value.
- Number of Arguments Two or more members or calculations
- Options Whether missing values should be set to 0 in the calculation.

Example — Consider a spreadsheet with East and West as columns and Jan, Feb, Mar as rows. If the East values were 100, 300, and 600 and the West values were 200, 200, 300, the Minimum Value column would be 100, 200, 300.

## **Multiply**

- Function Performed Arithmetic multiplication.
- Number of Arguments Two or more members or calculations, or one member or calculation and a constant.
- Options You can specify a constant as an argument if you want to work with one rather than two members or calculations. You can also choose whether missing values should be set to 0 in the calculation.

#### **Percent**

- Function Performed Percentage calculation.
- Number of Arguments Two members or calculations, or one member or calculation and a constant.
- Options You can specify a constant as an argument if you want to work with one rather than two members or calculations. You can also choose whether missing values should be set to 0 in the calculation.

Example — Consider a spreadsheet with Actual and Budget as columns and Jan, Feb, Mar as rows. If the Actual values were 100, 300, and 600 and the Budget values were 200, 200, 400, the Percentage column (Actual % Budget) would be 50, 150, 150.

## **Percent Difference from Average**

- Function Performed Performs the same actions as Difference from Average but displays each result as a percentage of average.
- Number of Arguments One member or calculation.
- Options Whether missing values should be set to 0 in the calculation.

Example — Consider a spreadsheet with Actual as a column and Colas, Root Beer, and Cream Soda as rows. If the Actual values for these products were 100, 200, and 300, the average would be 200. So the Difference from Average (%) column would be -50, 0, 50.

#### **Percent of Difference**

- Function Performed Percentage difference calculation.
- Number of Arguments Two members or calculations, or one member or calculation and a constant.
- Options You can specify a Constant as an argument if you want to compare a member
  with a fixed value. You can also choose whether missing values should be set to 0 in the
  calculation.

Example — Consider a spreadsheet with Actual and Budget as columns and Jan, Feb, Mar as rows. If the Actual values were 100, 300, and 600 and the Budget values were 200, 200, 400, the Percentage difference column (Actual % diff Budget) would be calculated as ((Actual -Budget) / Budget)\*100 and shown as -50, 50, 50.

## **Percent of Member**

- Function Performed Evaluates a dimension member argument as a percentage of another dimension member argument. The second argument is defined by the dimension member intersected on an opposite axis.
- Number of Arguments Two or more members or calculations, or one member or calculation and a constant.
- Options You can choose whether missing values should be set to 0 in the calculation.
- **Procedure** Select a Percent of Member calculation from the Function list, select a dimension member argument, and select a dimension member from the opposite axis using the Opposite Member drop-down list.

#### **Percent of Total**

- Function Performed Percentage of total.
- Number of Arguments One member or calculation.
- Options None.

**Example** — Consider a spreadsheet with Actual as a column and Jan, Feb, Mar as rows. If the Actual values were 100, 300, and 600, the Percentage of Total column would be shown as 10, 30, and 60.

## **Rank Ascending**

- Function Performed Ranking.
- Number of Arguments One member or calculation.
- Options The smallest value is given a ranking of 1.

Example — Consider a spreadsheet with Actual as a column and Jan, Feb, Mar as rows. If the Actual values were 100, 300, and 600, the Rank column would be shown as 3, 2, 1.

## **Rank Descending**

- Function Performed Ranking.
- Number of Arguments One member or calculation.
- Options The largest value is given a ranking of 1.

#### **Subtract**

- Function Performed Arithmetic subtraction.
- Number of Arguments Two members or calculations, or one member or calculation and a constant.
- Options You can choose whether missing values should be set to 0 in the calculation.

## Sum

- Function Performed Arithmetic addition.
- Number of Arguments Two or more members or calculations, or one member or calculation and a constant.
- Options Whether missing values should be set to 0 in the calculation.

## **Square Root**

- Function Performed Returns the square root of a numeric value.
- Number of Arguments One member or calculation.
- Options Whether missing values should be set to 0 in the calculation and included in the number of arguments.

Example — If Actual is 100, the Square Root of Actual is 10.

#### **Trend**

- Function Performed Trend based on straight-line Linear Regression; that is, the slope of
  the 'straight line' that a Linear Regression calculation would plot between the points in the
  original data series.
- Number of Arguments Two or more members or calculation.
- Options Whether missing values should be set to 0 in the calculation

#### **Variance**

- Function Performed Arithmetic subtraction that uses Financial Intelligence account metadata to interpret Financial Management expense and liability items as negative values.
- Number of Arguments Two members or calculations, or one member or calculation and a constant.
- Options You can choose whether missing values should be set to 0 in the calculation.

#### **Variance Percent**

- Function Performed Percentage difference calculation that uses Financial Intelligence
  account metadata to interpret Financial Management expense and liability items as negative
  values.
- Number of Arguments Two members or calculations, or one member or calculation and a constant.
- Options You can specify a Constant as an argument if you want to compare a member
  with a fixed value. You can also choose whether missing values should be set to 0 in the
  calculation.

## **Complex Calculations**

Oracle recommends dividing complex calculations into components and combining the components into a compound calculation.

**Example:** To set up a calculation for  $(A + B) / (C \times 2)$ , where A, B, and C are members, you divide the formula into steps:

- Set up Sum for A + B, and name it Step 1.
- Set up Multiply for C x 2, and name it Step 2.
- Set up Divide for Step 1 result divided by Step 2 result, and name it Step 3.
- Use Show Only Members to hide Step 1 and Step 2. If you want to switch between seeing only members, seeing only calculations, and seeing both, you can use the Hide option in your document right-click menu.

## **Creating Calculations**

You can use a combination of members, functions and/or operators to create a formula using the Functions and Members tabs, as well as the operators buttons. You can create a formula by using members and operators, without functions, or you can combine members, functions and operators in a formula. You also can create and edit advanced expressions by manually entering and editing the formulas.

An editor field, Formula Body, allows you to manually enter and edit the formula using a syntax that resembles multidimensional expressions (MDX) for defining members. However, while the syntax definition for defining members resemble the MDX format, MDX statements are not supported in the Web Analysis calculations. A formula is created by selecting a combination of Function and Member(s). For more information, see Using the Manual Formula Syntax.

Toolbar buttons for Cut, Copy, Paste and Validate are activated when a formula is entered in the Formula Body. The Validate button checks the validity of the formula for any errors and returns an error box to confirm whether validation succeeded or an error exists. The result of the formula is shown in the Formula field and can be inserted into the report by clicking the Insert button. Existing functions can be grouped together in one expression. If you want to switch between seeing only members or only calculations, or both, you can use the Hide option in the shortcut menu on your document.

**Note:** You can select Dynamic row or column references instead of selecting members from the report. The formatting is applied regardless of the member selection. If a calculation refers to a specific column, and that column is deleted through member selection, the calculation is handled correctly. If a swap or pivot is performed, the calculation will "carry" where possible.

- To create a calculation:
- 1 Right-click a dimension member header and select **Analysis Tools**, then **Calculation**.

The Calculation Definition dialog box is displayed, containing three tabs: Functions, Members and Options.

- The **Members** tab is for selecting members and adding them to a formula (for example, [Sales] [COGS], outside a formula function. You can select one or more members in the **Select Members** list, click **Insert** to insert to the formula **Definition**.
- The **Functions** tab is for inserting formula functions into the **Definition** area after selecting a function and members. You can add and remove members and constants to the formula. Once a function is selected, it appears in the **Formula** area. Members (or dynamic references) can be added to the formula by clicking on each member/reference, then clicking on **Add** to add it to the **Arguments** area. The **Formula** area is updated with arguments once they are added. When the formula is complete, it can be inserted to the **Definition** area by clicking **Insert**.
- The Options tab provides Missing Values and Select Positions settings.
- 2 The following areas are displayed for all three tabs:

- Name the name of the formula.
- Definition displays the formula. It allows for manual entry and editing of the formula. The Cut, Copy, Paste, and Validate buttons become enabled.
- Mathematical Operators symbols that provide types of calculations that you can perform on the elements of a formula; addition (+), subtraction (-), multiplication (\*), division (/), parenthesis (( )).
- 3 You can create a formula by using members on the Members tab. Perform the following:
  - In the Select Members area, select members.
  - In Advanced click to list all dimension member combinations and add them to the formula Definition area. When deselected, only members from one dimension are shown.
  - In Dynamic References select to enable the selection of a row or column reference
- 4 Click **Insert** to add the formula.
- 5 To create a formula using functions, in the **Functions** tab, perform the following:
  - a. Select a calculation type from the Function list.
  - b. Replace the undefined arguments, displayed with a (?) in the **Arguments** area, with a member located in the **Select Members** area. Do this by selecting the member and clicking the right arrow button.
  - c. To replace an undefined argument (?) with a value, enter a value in the **Constant** text box, and click the right arrow button.
  - d. To replace an undefined argument from dimension member combinations, select **Advanced** to display dimension member combinations. Click to select a dimension member combinations label, and click the right arrow button to replace an undefined argument (?).
  - e. Select All Members to quickly select all available dimension members.
  - f. Click **Insert** to include the formula in the definition.
  - g. When the calculation is defined, click Apply and OK.

The following list describes the items on the Functions tab.

- **Formula** displays the formula result
- Functions provides pre-written formulas such as adding values, dividing values, calculating averages
- **Select Members** provides members to be included during calculation
- **Advanced** click to select a dimension member combination label. If the row or column context of the calculation has multiple dimensions, **Advanced** shows all dimension in the row or column. When deselected, only members from one dimension are shown.
- All Members select to select all dimension members
- **Dynamic References** enable to select a row or column reference.

- **Constant** type a value to use in a function. For example, instead of Sum("Qtr1", "Qtr2"), you could have Sum("Qtr2", 155)..
- **Optional. Opposite Member** select to evaluate a dimension member argument as a percentage of another dimension member argument. The second argument is defined by the dimension member intersected on an opposite axis
  - Select a Percent of Member calculation from the Function list.
  - Select a dimension member argument.
  - Select a dimension member from the opposite axis using the **Optional Opposite** Member list.

**Note:** The **Opposite Member** list in the arguments frame is enabled only for the Percent of Member Calculation. This control evaluates a dimension member argument as a percentage of another dimension member argument. The second argument is defined by the dimension member intersected on an opposite axis.

#### 6 On the **Options** tab, perform the following:

- Ignore Calculations excludes calculated members from the equation when "All Members" is selected.
- **Optional. Missing Values** provides option for how missing values are treated; include, exclude, or treat as a number that you specify.
  - Include calculates missing values as they are stored.
  - Exclude removes arguments populated by missing values from the calculation.
  - Treat as Number populates the argument with the value indicated. Default is zero (0).
- **Select Position** provides options for specifying the location of the calculated row or column.
  - o Front/Top
  - Back/Bottom
  - Insert Before
  - Insert After
  - Insertion Point If you selected Insert Before or Insert After, select an insertion
    point from the corresponding list. The calculated row or column is inserted before
    or after the specified dimension header.
- Ignore Calculations selected to exclude calculated members from the equation when "All Members" is selected.

#### 7 When the calculation is defined, click Apply and OK.

#### Using the Manual Formula Syntax

If a member name contains unsupported characters or symbols, it should be enclosed in brackets – []; If the name does not contain such symbols, it can be used as is. Some guidelines:

- 1. [New York] + West + East correct
- 2. East + New York incorrect: member name New York contains spaces.
- 3. Old style syntax (member names are separated by ":"). For advanced members, can be used if member names contain "good" symbols only. for example:

```
Qtr1:West + Qtr2:East — correct
```

Qtr3:New York — incorrect

4. For new MDX style syntax, a list of comma – separated member names is included between "('and')". Member names must be included within [] according to the same rules as for simple members. For example:

```
([New York], West) — correct
```

5. Simple and advanced members must not be mixed in one formula body. For example:

```
([New York], West) + East — incorrect
```

6. All members' specification in the script is defined by keyword @selectAllMembers. For example:

```
Average(@selectAllMembers) + 1234 + [East]
```

7. All members' specification can be used in the script several times. For example:

```
Sum(@selectAllMembers) — Sum(@selectAllMembers) — correct, always zero
```

8. Dynamic references are specified by the following way; for rows they are in form @row<ROW NUMBER>, for columns they are @col<COLUMN NUMBER>. For example:

```
@col + @col5 - @col16/100@row2 - @row3
```

9. In one expression, row and column dynamic references should not be mixed. For example:

```
@col + @row1 — incorrect. An error message occurs.
```

10. You can mix members and dynamics references in one expression, with the following restriction: If the axis (row or column) contains several dimensions, an advanced members' specifications must be used. For example:

```
@row1 + [Qtr1] — correct only if row axis contains one dimension – Year
```

11. Opposite members are used only for one function – Percent\_of\_Member. An @ character must precede the opposite member. For example:

## **Modifying Calculations**

- To modify a calculation:
- 1 Right-click a dimension member header and select Analysis Tools, then, Analysis Tools Manager.
  - The Analysis Tools Manager is displayed.
- 2 Click a calculation definition.
- 3 Click Edit.

The Calculation Definition dialog box displays the arguments for the selected calculation definition.

- 4 Optional: To change the calculation definition name, enter a name in Name.
- **Optional:** To move the calculation position, select another option.
- Optional: If you selected Insert Before or Insert After, select an insertion point from the corresponding list.

The calculated row or column is inserted before or after the specified dimension header.

7 Optional: To change the calculation type, select a calculation type from Function.

Changing the calculation type requires that the user to redefine all arguments. For instructions, See To create a calculation:.

- 8 **Optional:** To change the arguments for the calculation, perform one:
  - Click an argument, click a dimension member label, and click the arrow button.
  - Click an argument, enter a value in the Constant text box, and click the arrow button.
  - Select **Advanced** to display dimension member combinations. Click an argument, click a dimension member combination label, and click the arrow button.

The calculation definition is displayed in the Formula group box.

- 9 When the calculation is redefined, click Apply and **OK**.
- 10 Click Close.

## **Essbase Attribute Calculations**

Web Analysis Studio leverages server-based Essbase attribute calculations in the client. Server-based calculations are performed by the server before returning the OLAP query result set. This minimizes the result set and network traffic.

To use attribute calculations, you must use Data Layout to select the attribute calculations dimensions to participate in the query. You must use Dimension Browser to select the server-based calculations to be returned by the query result set.

**Note:** You can reproduce attribute calculations in Web Analysis Studio, but the onus is on you to define these calculations, and the client to process the result set.

Consider the use of attribute members in these calculations:

- You can select, aggregate and document on data sharing common attributes.
- You can select attributes by their data types: text, numeric, Boolean, and data type.
- You can group numeric data types into statistical ranges.
- You can use sum, count, min, max, and average functions on the attribute calculations dimension automatically generated by Essbase.
- You can use numerical attribute values from calculation scripts and member formulas in calculations.
- You can create crosstabs of attribute data for one dimension, and analyze the dimension in terms of each attribute.

## **Creating SAP BW Currency Conversion Definitions**

SAP BW converts data value currencies ad hoc during analysis, and saves conversion definitions as analysis tools. You can activate and deactivate currency conversion definitions without removing them from the Analysis Tools Manager, enabling currency combinations that differ.

- To create a currency conversion definition:
- 1 Right-click a dimension member header and select Analysis Tools, then Currency Conversion.
  - The SAP Currency Conversion dialog box is displayed. Because exchange rates fluctuate, you must indicate the exchange rates and supported currencies for a date. You can use the arrow controls to the left and right of the current month and year, to scroll to another date.
- 2 Scroll to the month and year of a date, and click the cell for the date.
  - The selected date is highlighted.
- 3 In the Select Currency To list, select the currency to which you would like a currency converted.
  - Your options may be limited to the currencies supported by the date of your exchange rate.
- 4 In the Select Currency Rate list, select the exchange rate used to convert currency.
- 5 In the Select Currency From list, select the currency that you would like to convert.
  - Your options may be limited to the currencies supported by the date of your exchange rate.
- 6 Click OK.
  - All data values using the last currency selection are converted to the specified currency, using the specified exchange rate. Repeat this process to convert all data values to one currency.

## **Creating SAP BW Unit of Measure Conversion Definitions**

SAP BW converts data value unit of measure ad hoc during analysis, and saves conversion definitions as analysis tools. You can activate and deactivate unit of measure conversion

definitions without removing them from the Analysis Tools Manager, enabling unit of measure combinations that differ.

Note: To use the Unit of Measure Conversion analysis tool, the 0MATERIAL characteristic must be selected as a data object column, row, or page dimension.

- To convert all units of a measure to another unit of measure:
- 1 Right-click a dimension member header and select Analysis Tools, then Unit of Measure Conversion. The SAP Unit Conversion dialog box is displayed.
- 2 From the **Unit From** list, select a unit of measure that you would like to convert.
- From the Unit To list, select the unit of measure into which you would like your previous selection converted.

The drop-down list displays known conversion rates from your SAP BW 0MAT UNIT table. You must define a logical conversion for the analysis tool to work.

- **Optional:** To define a custom unit of measure conversion using these steps:
  - a. From the **Unit To** list, select **Custom Unit**.
  - b. In Select Custom to Rate, enter a unit name in Unit Name.
  - c. Enter a custom conversion factor in **Conversion Factor**.
- Click OK.

All data values using the specified unit of measure are converted using the standard or custom conversion rate. Repeat this process to convert all data values to one unit of measure. 10

# Exporting Documents and Presentations

#### **In This Chapter**

Smart View	141
Exporting Data Options	142
Exporting All Report Objects to Microsoft Office	144
Exporting a Screen to Microsoft Word or PowerPoint	144
Exporting to the Clipboard	144
Export Data Unformatted	144
Export Options	145
Saving As HTML	146
Emailing Document Links	147

## **Smart View**

Oracle Hyperion Smart View for Office for Office provides a common Microsoft Office interface for these Oracle | Hyperion products:

- Essbase
- Financial Management
- Oracle Hyperion Planning
- Oracle Hyperion Financial Reporting
- Oracle Hyperion Interactive Reporting
- Oracle Hyperion SQR Production Reporting
- Web Analysis

The centralized interface enables simultaneous use of multiple Oracle | Hyperion products, and improves integration with Microsoft Office (2000, 2002, and 2003). The Smart View implementation provides this functionality:

- Imports the current page of the current data object to Excel, Word, or PowerPoint
- Exposes Financial Management and Essbase functions in Excel, Word, and PowerPoint content
- Notifies you when to upgrade to later releases of Smart View.

Smart View enables these import options:

- You can import the current page of the current data object to Word, PowerPoint or Excel as an image. After insertion, you can query the corresponding Web application to refresh the image.
- You can import an entire report with multiple report objects to Microsoft Excel.
- You can import documents to Microsoft Excel as query-ready HTML. When you export content as query-ready HTML, the current page of the current data object is converted to HTML and Oracle | Hyperion-specific formatting is removed. This enables Smart View to requery the data source independent of the Web application.
- You can export documents to Microsoft Excel as formatted HTML. When you export content as Formatted HTML, the current page of the current data object is converted to HTML with the Oracle | Hyperion formatting definitions and calculated members. This formatting content prevents Smart View from directly querying the data source, but enables Oracle | Hyperion content to be leveraged by Office applications.

The following export options are supported in Web Analysis Studio.

- Export image to Microsoft Word and PowerPoint
- Export an image of the report screen to Microsoft Word, or PowerPoint.
- Export formatted HTML files to Microsoft Excel
- Export Query-ready HTML files to Microsoft Excel. Smart View should be installed to enable query-ready export.
- Export all report objects to Microsoft Excel in separate worksheets
- Export next data objects to Microsoft Excel: Spreadsheet, Chart, Pinboard, freeform Grid and SQL spreadsheet. All data object, regardless of their type, get exported as a spreadsheet.

**Note:** Export to Microsoft Excel report can be refreshed against a Web application, but export to Microsoft Word and PowePoint does not support refresh.

Because Excel worksheets prevent users from entering data into read-only cells, some Excel functions such as AutoSum, F9, and some formatting functions are disabled in Smart View. Also note that Microsoft Excel, Word and PowerPoint must be installed on the computer running the Oracle Hyperion Reporting and Analysis client.

## **Exporting Data Options**

You can export spreadsheets, charts or pinboards to Microsoft Excel, Word and PowerPoint. The following table describes the Export Data right-click menu.

Table 2 Export Data Options

Туре	Format	Export Option	Comment
Microsoft Excel	Fully Formatted	Selected Object	Formatted HTML, current page of selected data object.

Туре	Format	Export Option	Comment
		All Objects	Formatted HTML, current pages of all data objects in a report (all in one worksheet; it is not possible to split object to separate worksheets).
	Query Ready	Selected Object	Data object on Essbase data source; re-queries Essbase server from MS Excel, if selected data object based on Essbase data source and exports data object in Query-Ready HTML.
			<b>Note:</b> Query Ready format supports one object per worksheet in Smart View. Therefore, "All Objects" is not available for Query Ready exports.
	Unformatted	Selected Object	Unformatted HTML; current page of selected data object.
		ALI Objects	Unformatted HTML; current pages of all data object in a report.
Microsoft Word	Image	Selected Object	Image; current page of selected data object.
			<b>Note:</b> Image format supports one image per page in Microsoft Word and PowerPoint. Therefore, "All Objects" is not available for Image exports.
		Screen	Image; screen shot of the report.
Microsoft PowerPoint	Image	Select Object	Image; current page of selected data object.
		Screen	Image; screen shot of the report.
File	Image	Selected Object	
		Screen	
	Fully Formatted	Selected Object	
	Unformatted	Selected Objects	
		All Objects	
Clipboard	Fully Formatted	Select Object	
	Unformatted	Selected Object	

## **Exporting All Report Objects to Microsoft Office**

To export all report objects to Microsoft Office, right-click on a report and select Export Data, then Microsoft Excel, then Fully-Formatted, then All Objects.

## **Exporting a Screen to Microsoft Word or PowerPoint**

To export a screen to Microsoft Word or PowerPoint, Right-click on the report and select Export Data, Then select Microsoft Word, then select Image, then select Screen.

**Note:** When exporting to Microsoft Excel, using one of the three methods that populates cells of data (Query Ready, Fully-Formatted, Unformatted), Web Analysis evaluates the number of rows and columns in the data and if they are larger than the number of rows and or/columns in Excel, an error message is displayed and the document is not exported.

## **Exporting to the Clipboard**

Web Analysis Studio can export a page of a data object from an Web Analysis document to the operating system clipboard.

- To export a page of a data object to the clipboard:
- Right-click a data object and select Export Data.
- To export a page of a data object as formatted data, select Formatted, then To Clipboard.

Note that formatted data is converted to HTML with all Web Analysis Studio formatting definitions and calculated members. This enables Oracle Hyperion Smart View for Office to leverage Web Analysis Studio functionality in supported Microsoft Office applications. The data source however cannot update or recognize formatted data generated by Web Analysis Studio.

## **Export Data Unformatted**

Data in a spreadsheet, chart, or pinboard can now be exported unformatted to Excel, Clipboard or to a file. To access this, right click a report object and select Export Data, then Unformatted.

When exporting data to Excel using the Unformatted option (Export Data, then Unformatted, then To Microsoft Excel), filter dimensions with members selected are included in the Excel output. For example, if a Web Analysis document against Essbase Sample Basic has the Scenario dimension in the filter, and the member Budget is selected, the Budget member appears in the Excel output above the column headers.

Note: This feature does not apply to the Query-Ready or Formatted export types.

# **Export Options**

You can export documents and presentations to local computers and mapped drives. All content exported from Web Analysis (both presentations and reports) is appended with extension \*.apt.

#### **Exporting the Current Document**

To export the current document, select File, then Export, then Current Document. In the Save dialog box, indicate the network location to which the file is to be saved and click OK.

## **Exporting Documents and Presentations**

- To export a document or presentation:
- 1 Perform one:
  - Select File, then Export, then Documents.
  - Select File, then Export, then Presentations.
    - The Open dialog box is displayed. It features a selection frame that lists the current folder contents, specified by **Location**.
- 2 If not specified, select Web Analysis Document or Web Analysis Presentation from Files of Type.
- 3 Navigate to the document or presentation you want to open:
  - In Location, type the path to the repository folder whose contents you want displayed, and press Enter.
  - In Location, click the drop-down arrow and select from the location series.
  - When you navigate to another folder, you can click Back to return to the previous folder.
  - Similarly, you can click **Forward** to display the next folder.
  - Click Up to display the contents of the parent folder in the selection frame.
  - Click Favorites to jump to the Favorites folder of the current user.
  - Click the **Favorites** list to jump to the Favorites folder of groups.
  - Click **Home** to jump to and display the contents of the current Home folder in the selection frame.
    - As you navigate, the selection frame lists the files and folders indicated by Files of Type.
- 4 Select a document or presentation:
  - To select one document from the selection frame, click the document name or icon.

- To select a series of documents from the selection frame, click a document name and press and hold **Shift** while selecting another document name. The first selection, the last selection and all documents in between are selected.
- To select multiple documents, not necessarily in a series, hold down **Ctrl** while clicking document names in the selection panel.
- To deselect items, click outside the Name column or on empty space.
- Double-click to select and dismiss the Open dialog box.
- Click OK.

The Save dialog box is displayed. It features a selection frame that lists the contents of the current folder, specified by Look in.

- Navigate to the network location where files are to be saved:
  - Click **Up** to display the contents of the parent folder in the selection frame.
  - Click Home to jump to and display the contents of the current Home folder (set in preferences) in the selection frame.
  - Click Look in to list mapped drives and network folder locations. Click a location name to display its contents in the selection frame.
  - Click the Create New Folder icon to create a folder at the current location.
- Click to select a folder location in the selection frame.
- Optional: Specify a name for the exported file in File name.
- Click Save.

The files selected in the Open dialog box are converted to Web Analysis document definitions and stored at the location specified by the Save dialog box.

Note: The .apt file suffixes are dropped when you export to a folder that has a period (.) in it. To guard against this issue, do not use periods in folder names.

# **Saving As HTML**

- To convert a document to HTML:
- 1 Select File, then Save As HTML.

The Save As HTML menu is displayed.

- Select one:
  - Current Document
  - Presentation

The Save as HTML dialog box is displayed.

Specify a file name and a location for saving the output file, and click Save.

# **Emailing Document Links**

You can email hyperlinks to the URL of the current document.

- To send a document link of the current document by email:
- 1 Select File, then E-mail As Link.

The E-mail As Link submenu is displayed.

- 2 Select one:
  - EPM Workspace—Presents the current document in the EPM Workspace.
  - Web Analysis Studio—Presents the current document in Web Analysis Studio.

    The E-mail dialog box is displayed.
- 3 Enter the email address of recipients under Add and Remove.
- 4 Click Add.

The Email address is displayed in the Recipients' E-mail Address box.

- 5 Enter your email address in **Sender's E-mail Address**.
- 6 Replace the default subject string in Subject.

The Body group box is displayed the document link URL of the current document.

7 Click OK.

# 11

# **Printing**

#### **In This Chapter**

Printing Options	149
Print Dialog Page Tab	150
Print Dialog Header/Footer Tab	150
Printing	154
Printing all Open Reports	154
Print Preview	155

# **Printing Options**

Three printing options:

- Print Screen prints the content area (the current display)
  - Because documents can contain multiple data objects, Print Screen does not specify OLAP pages. To include OLAP pages or object-specific document summaries, use Print Selected Object.
- Print Selected Object prints the specified OLAP pages of the current data object
- Print All Objects prints all data objects in the current Web Analysis document.

The output format is similar to the format of Print Selected Object. Page members can be printed for all report objects for which page members are defined.

#### Output options:

- o Print the content area to the default printer
- o Print the content area to a PDF output file
- o Print the content area to a JPG output file
- o Print the current data object to the default printer
- o Print the current data object to a PDF output file
- Print all objects to the default printer
- o Print all objects to the PDF output file
- Print Preview

The Print dialog box features:

- Page tab Specifies the print output, layout orientation, how to break the output over multiple pages, and whether a document summary page is included.
- Header/Footer tab Defines custom headers and footers for print output.

Selecting the "Allow print settings to be saved with document" option at the bottom of these tabs enables you to save print specifications with the document. Otherwise, print specifications persist only as long as the document is open during the current session.

# **Print Dialog Page Tab**

The Page tab specifies print output, layout orientation, how to break the output over multiple pages, and whether a document summary page is included:

Control	Description
Print To	
Printer	Directs print output to the default printer.
PDF	Saves print output as a PDF file.
JPEG	Saves print output as a JPG file.
Orientation	
Portrait	Prints the document with a portrait orientation.
Landscape	Prints the document with a landscape orientation.
Scale	
page(s) wide page(s) tall.	Fit to page printing. Enables you to determine how document content is broken down into print job pages.
Summary Page	
Include a document page	Automatically inserts a print summary into the printer output when checked.
OLAP Pages	
Page Selection Panel	In Print Current Document context, specifies the OLAP page axis dimensions to print.
Allow print settings to be saved with document	Saves print specifications when the document is saved.
Print Preview	Displays the Print Preview panel.

See also Print Dialog Header/Footer Tab.

# **Print Dialog Header/Footer Tab**

The Header/Footer tab defines custom headers and footers for print output.

Control	Description	
Table Headers		
Include row and column headers on all pages.	Automatically inserts row and column headers on all pages when checked.	
Header		
Font	Opens the Font Properties dialog box, enabling you to set font properties for the current text selection.	
Insert	Adds a dynamic text label to the header at the location in the string specified by the cursor. See "Dynamic Text Labels" on page 151.	
Clear	Deletes the content of the Header text box.	
Header Text box	Adds a header text string.	
Footer		
Font	Set font properties for the current text selection.	
Insert	Adds a dynamic text label to the footer at the location in the string specified by the cursor. See "Dynamic Text Labels" on page 151.	
Clear	Deletes the content of the Footer text box.	
Footer text box	Adds a header text string.	
Allow print settings to be saved with document	Enables you to save print specifications when the document is saved.	
Print Preview	Displays the Print Preview panel.	

See also Print Dialog Page Tab.

# **Dynamic Text Labels**

You can add dynamic text labels to headers and footers, using the Insert button on the Print Dialog Header/Footer Tab. Dynamic text labels update themselves as strings are changed in the repository.

Dynamic Text Tag	Default Tag	Inserts:
Database Note	< <dbnote>&gt;</dbnote>	Database note in the label.
Cell Reference	< <cell 0,0="">&gt;</cell>	Cell reference string in the label.
Page	< <page>&gt;</page>	Page dimension name in the label.
Filter	< <filter 0="">&gt;</filter>	Filter member name in the label.
Document Description	< <rd>&gt;</rd>	Document description string in the label.
Document Name	< <rn>&gt;</rn>	Document name string in the label.

Dynamic Text Tag	Default Tag	Inserts:
Date/Time	< <date,mm-dd-yyyy>&gt;</date,mm-dd-yyyy>	Date/time string in the label.
Connection Name	< <cn>&gt;</cn>	Database connection name string in the label.
Username	< <username>&gt;</username>	User name string in the label.
UserID	< <userid>&gt;</userid>	User ID string in the label.

**Note:** Because custom documents can contain multiple data objects, dynamic text labels reference the current data object (the spreadsheet, chart, pinboard, or SQL spreadsheet with the yellow border).

# **Creating Dynamic Text Labels**

To create dynamic text labels, click the text string where the label is to be added, and select the dynamic text label from **Insert**.

After dynamic text labels are placed in the text box, you can edit the tag to display additional information.

#### **Fixed References**

Because dynamic text labels change as focus is shifted in composite documents, you may want to fix the dynamic reference. Tags can be associated with specified data sources using these modifications:

Dynamic Text Tag	Default Tag	Fixed Reference
Connection Name	< <cn>&gt;</cn>	< <cn datasourcename1="">&gt;</cn>
Cell Reference	< <cell 0,0="">&gt;</cell>	< <cell datasourcename1,0,0="">&gt;</cell>
Filter	< <filter>&gt;</filter>	< <filter datasourcename1,0="">&gt;</filter>
Pages	< <page>&gt;</page>	< <pre>&lt;<page datasourcename1="">&gt;</page></pre>
Database Note	< <dbnote>&gt;</dbnote>	< <dbnote datasourcename1="">&gt;</dbnote>

**Note:** It is not possible to specify a fixed references for a page dimension member.

#### **Time Format Syntax**

Time Format strings specify the format of the dynamic date/time label. The count of the ASCII letter pattern determines the format used.

ASCIISymbol	Meaning	Туре	Example
G	Era	Text	AD
у	Year	Number	2002
M	Month in Year	Text & Number	July & 07
d	Day in Month	Number	10
h	Hour in am/pm (1-12)	Number	12
н	Hour in Day (0-23)	Number	0
m	Minute in Hour	Number	30
S	Second in Minute	Number	55
S	Millisecond	Number	978
Е	Day in Week	Text	Tuesday
D	Day in Year	Number	189
F	Day of Week in Month	Number	2 (meaning 2nd Wed in July)
W	Week in Year	Number	27
W	Week in Month	Number	2
а	am/pm marker	Text	PM
k	Hour in Day (1-24)	Number	24
К	Hour in am/pm (0-11)	Number	0
Z	Time Zone	Text	Pacific Standard Time
' (apostrophe)	Escape for Text	Delimiter	
" (two single quotes)	Single Quote	Literal	1

When four or more Text type letters are used, the full form is provided.

When three or more Text & Number type letters are used, text is provided. When only one or two letters are provided for this type, the number is provided.

Numbers use the minimum number of digits. Year can be truncated to two digits. Shorter numbers are zero-padded.

All other characters are used as quoted text strings.

#### **Examples**

"yyyy.MM.dd G 'at' hh:mm:ss z" returns 1996.07.10 AD at 15:08:56 PDT

"EEE, MMM d, yy" returns Wed, July 10, '96

"h:mm a" returns 12:08 PM

"yyyyy.MMMMM.dd GGG hh:mm aaa" returns 1996.July.10 AD 12:08 PM

# **Printing**

Use this option to print a single report. To print several open reports at one time see "Printing all Open Reports" on page 154.

- To print:
- 1 Select File, then **Print** to display the **Print** dialog box.
- 2 Select one from the Context area:
  - Print Screen prints the content area.
  - Print Selected Objects prints all data objects in a document.

Context determines the scope of the print job. Numerous print options are available on the Page and Headers/Footers tab.

- 3 On the Page tab, select one from Print To:
  - Printer sends the print job to the default printer.
  - PDF File sends the print job to a PDF output file.
  - JPG File sends the print job to a JPG output file (screen only).
     Select other print options on the Print Dialog Page tab and Print Dialog Hea

Select other print options on the **Print Dialog Page** tab and **Print Dialog Headers**/ **Footers** tab.

- 4 Click Print. Depending on your Print To selection, a dialog box is displayed.
- 5 Click OK.

# **Printing all Open Reports**

You can print all open reports at one time and use the print settings that have previously been saved with each report. Conversely, you can apply new print settings to all documents.

- To print:
- 1 From the Navigation bar, select and open reports to print.
- 2 Select File, then Print All.
- 3 Select one from the Context area:
  - Print Screen prints the content area.
  - Print Selected Objects prints the current data object of the current document.
  - Print All Objects prints all data object in a document.

**Context** determines the scope of the print job. Numerous print options are available on the Page and Headers/Footers tabs.

- **Note:** When Print Selected Object or Print All Objects are selected, the OLAP Pages section is enabled. When OLAP Pages are available in prior releases, you can set summary page information in the Summary Page section.
- 4 Select **Utilize Saved Settings** to use the Print settings that have been saved with each report through the Allow print setting to be saved with document check box, or clear the check box to set new Print settings that will apply to all documents.
- 5 On the Page tab, select one from Print To:
  - Printer sends the print job to the default printer.
  - PDF File sends the print job to a PDF output file.
- 6 Click Print.

Depending on your **Print To** list selection, a dialog box is displayed:

- Operating System Print dialog box to select a network printer.
- Operating System Save dialog box to select a network location.
- 7 Click OK.

#### **Print Preview**

- To preview the print job before printing:
- 1 Select one:
  - Print from a data object shortcut menu.
  - Click
  - File, then Print.

The Print dialog box is displayed.

2 Click Print Preview.

The Print Preview dialog box is displayed.

- **Optional:** To magnify or minimize the print preview, select **Zoom** list and select a size ratio option (25%, 50%, 75%, or 100%).
- 4 Click **OK** to return to the Print dialog box.

# **Managing Database Connections**

#### **In This Chapter**

Database Connections	157
Creating OLAP and Oracle   Hyperion Database Connections	158
Database Connection Properties	161
Measures Formatting	162
Integrating OLAP and Relational Data	162
Creating Relational Drill-Through	163
Essbase Database Connections	166
Financial Management	169
SAP BW	172
Creating SAP BW Database Connections	174
SQL Server Analysis Services	175
Relational Access	177
Controlling Query Result Set Size	178
Relational Database Connections	178
Creating Relational Database Connections	181
Editing Database Connections	185
Changing Database Connections for Report Objects	185

# **Database Connections**

Database servers typically use a server name, application name, and database name in the creation of unique identifiers. The nature of these identifiers makes database references less portable. Web Analysis Studio uses user-friendly database aliases instead of long identifiers. Not only are database connection names easier to remember and more economical to employ, they enable the database to be maintained on multiple servers.

In short, database connections are portable files that define the terms, conditions and method for connecting to a data source.

System requirements vary for RDBMS (see the Oracle Enterprise Performance Management System Installation Start Here), and you must compose a database connection string and provide log on credentials to navigate your relational hierarchy. You can also connect to level 2 or level 4 JDBC RDBMS using other relational data objects (SQL Spreadsheet, freeform grid, relational drill-through and Integration Services drill-through).

The View Pane Information Panel tab displays the database connection used by the current data object. The Information panel features two database connection segments:

- The Database segment displays the database connection name for the current data object.
- The Database User Name segment displays the user ID by which access to the database connection is granted.

#### **Database Connections**

Database connections are stored as repository files and adhere to most file management conventions. You can only see the database connections to which you are granted access. Various permissions are needed to read, write, edit, and change database connection properties.

#### **Database Connection Access and Document Permissions**

It is possible to distribute a document or presentation to a user that requires database connections he or she cannot access. Document access is independent of database connection access.

Database connection permissions withholding access prevent access to only one database connection file. You are free to compose another database connection to this data source, or to compose a database connection to an alternate data source. You can leverage the document definition independently of a database connection.

See "Setting File Properties" on page 43.

#### **User and Group Permissions**

You can access database connections assigned directly to you or database connections assigned to a group to which you belong.

When documents are assigned to a group, the database connections that the document uses must also be assigned to the group. Otherwise, group members can access the document, but they cannot access its data values (unless they have individual user access).

To mitigate the risk of conflicting permissions, store documents with the database connections they reference. Whenever possible, distribute documents and database connections to groups. It is easier to set permissions for all files in a folder, and all users in a group than it is to manage permissions for individual files and individual users.

# **Creating OLAP and Oracle | Hyperion Database Connections**

The database connection wizard guides you through the creation of OLAP and Oracle | Hyperion database connections. You must know the name of your server, application, and database, and have log on credentials.

- To create a document using the document creation wizard:
- Perform one:
  - Select File, then New, then Database Connection.
  - Click , and select Database Connection.
- From **Database Connection**, select a database connection:
  - Essbase
  - Financial Management

There is an SAP BW and Relational option. See "SAP BW Features Available in Web Analysis Studio" on page 174 and "Creating Relational Database Connections" on page 181.

The Process bar displays steps for creating a database connection: Server, Database, Formatting, and Drill-through. On the Server page, you must enter the server name of your data source server, and the log on credentials used to access it.

- In the **Database Server** text area, enter the name of the data source server.
- In the Logon Information group, enter a user ID and password for accessing the data source server.

The current user ID and password are entered by default, in case the data source server uses credentials that match.

- **Optional:** If you want to save the credentials, select **Save User ID and Password**.
- Click Next.

Clicking Next queries the data source for application and database information. The content area displays the Database page.

From the list of **Available Databases** on the right, select a database.

Databases are listed by application. When you select the database, the application and database name are loaded into the text area on the left.

Note that Next and Finish are enabled at the lower right of the content area. The last two steps of the database connection wizard are optional. If you do not want to specify Measures Formatting or Relational Drill-through connectivity, click Finish.

- Select one:
  - Click Next, to specify Measures Formatting or Relational Drill-through connectivity.
  - Click Finish, to skip these optional steps. If you click Finish, skip to step 12. Clicking Next queries the specified database for dimension information. The content area displays the Formatting page.
- 9 Optional: To specify measures formatting for the database connection, select a dimension from Formatted Dimension.
- 10 Optional: Specify a Measures formatting definition, by selecting from these options:

Formatting Option	Description	
Formatted Dimension	Specifies the dimension to which the formatted member belongs.	
Advanced Member Selection	Specifies the single member or single advanced member selection to which the formatting definition is applied.	
Leading and Trailing Formatting		
Currency Symbol	Inserts the currency formatting symbols into the Positive Prefix and Negative Prefix text boxes.	
Positive Prefix	Enters character to precede positive numeric values.	
Positive Suffix	Enters character to follow positive numeric values.	
Negative Prefix	Enters character to precede negative numeric values. <b>Warning:</b> The minus sign (-) is the default prefix. Deleting the default prefix without replacing it causes negative values to display positively.	
Negative Suffix	Enters character to follow negative numeric values.	
Numeric Formatting		
Grouped Thousands	Displays numeric digits as grouped by thousands.	
Maximum Decimals	Indicates the maximum number of decimal places to display.	
Minimum Decimals	Indicates the minimum number of decimal places to display.	
Scale	Enables abbreviated value by tens, hundreds, thousands, ten-thousands, hundred-thousands, millions, and billions.	
Use Negative Color	Indicates that negative numbers are signified by a selected color.	
Select Negative Color	Enables you to select the color representing negative values.	
Replace Missing With	Replaces missing values with a text string or zero as indicated by the option.	
Font		
Header Font	Displays the Font Properties dialog box, for specifying Font family, point size, style, and color for the dimension header label.	
Data Font	Displays the Font Properties dialog box, for specifying Font family, point size, style, and color for the cell data values.	

Note that Next and Finish are enabled at the lower right of the content area. The last step of the database connection wizard is optional. If you do not want to specify Relational Drillthrough connectivity, click Finish.

#### 11 Select one:

- Click Next, to specify Relational Drill-through connectivity.
- Click Finish, to skip this optional step.

If you click Next, the content area displays the Drill Through page. See "Creating Relational Drill-Through" on page 163.

After clicking Finish, the Save As dialog box is displayed. It prompts you to navigate to the repository location where you would like the database connection file saved.

- 12 Navigate to the folder into which you want to save your database connection file:
  - Click Up to display the contents of the parent folder in the selection frame.
  - Click Home to jump to and display the contents of the current Home folder (set in preferences) in the selection frame.
  - In Location, type the path to the repository folder whose contents you want displayed, and press Enter.
  - In Location, click the drop-down arrow and select another location from the repository drop-down list.
  - When you navigate to another folder, you can click Previous to return to the last folder displayed in the selection frame.
  - Similarly, you can click Next to display the next folder in the location series. As you navigate, the selection frame lists the files and folders indicated by Files of Type.
- 13 Optional: When you reach the location where you want to save the file, enter a name for the database connection in Filename.
- 14 Click OK.

Your database connection file is saved to the specified repository location.

# **Database Connection Properties**

Database connection properties are set when the database connection is defined. You define database connections using the database connection wizard. Database connection properties include:

- Servername
- Log on credentials
- Application and database names
- Measures formatting
- Relational drill-through connectivity

It is important to differentiate properties.

- Database Connection properties—Define the terms, conditions, and method for connecting to a data source. They are set using the database connection wizard.
- File Properties—Determine identification and access to the database connection. They are set using the File Properties dialog box.
- Data Object Properties—Specify which database connection is used by the data object.
- Preferences—Specify database connection options that are set for each user (such as log on credentials, alias table, POV definitions, and personal variables).

See also "Measures Formatting" on page 162, "Creating OLAP and Oracle | Hyperion Database Connections" on page 158, "Integrating OLAP and Relational Data" on page 162, and "Creating Relational Drill-Through" on page 163.

Note: If you edit the Server Name, Application Name, or Database Name parameter values, you cannot load documents created using parameter values that differ. A better practice is to create a database connection with the desired parameter values.

# **Measures Formatting**

Measures formatting enables you to globally format one dimension used by an OLAP database connection. This global formatting includes leading and trailing characters, numeric formatting of numeric dimension values, and header and data formatting.

Measures formatting options differ from those of data formatting and default formatting preferences. See "Formatting Order of Precedence" on page 92.

You can define measures formatting using an explicit member selection or advanced member selection. Using advanced member selection makes the measures formatting dynamic. As members are added deleted and changed in the database, the formatting maintains itself and does not become obsolete.

See "Creating OLAP and Oracle | Hyperion Database Connections" on page 158.

# **Integrating OLAP and Relational Data**

You can construct liaisons between OLAP and relational data sources, typically called relational drill-through. After relational drill-through is configured, you can drill from the dimension bottom (level 0) of the OLAP database to specified relational data.

Relational drill-through is a client-based integration solution comparable to the server-based Integration Services drill-through.

The Relational Drill-Through dialog box is a graphical user interface for creating SQL relational database queries. You can use complex SQL syntax to specify table joins, and select and order by clauses.

Note: To support a broad array of JDBC relational data sources, relational drill-through does not support queries by levels, generations, or previously selected members.

Relational drill-through is configured as a database connection property of an OLAP database connection. You can set database connection properties through the database connection wizard:

Select File, then New, then Database Connection, then Analytic Services or Financial Management.

- Click , and select Database Connection, then Analytic Services or Financial Management.
- In the View Pane Browser tab, right-click an OLAP database connection in the Selection frame and select Edit. The database connection wizard for the selected database connection is displayed. Relational drill-through is set by the last step in the wizard process.

## **Defining Relational Drill-through**

Upon accessing the Modify Relational Drill-through Connection dialog box, you complete these tasks in the creation of relational drill-through navigation:

- 1. Define a JDBC RDBMS connection, using the Configure JDBC Driver dialog box.
- 2. Test the connection.
- 3. Indicate the relational database table name.
- 4. Update the Columns list.
- 5. Map relational columns to dimensions in the OLAP database.
- 6. Indicate whether to pass filter dimensions or page dimensions and a row limit (if).
- 7. Click Apply.

For instructions for creating relational drill-through navigation, See "Creating Relational Drill-Through" on page 163.

## **Controlling Query Result Set Size**

Query governors vary for relational access methods.

Custom document SQL spreadsheets and relational drill-through methods set query governors in the course of creating the SQL query or relational drill-through definition.

When drilling from OLAP to relational data, passing only the drilled OLAP dimension member to the relational data source may result in a large query result set. To focus and diminish the query result set, you can pass page and filter dimensions specified in the OLAP document.

Other relational access methods rely on the EPM System Configurator (CMC) application to limit the query result set.

# **Creating Relational Drill-Through**

Users with privileges can create relational drill-through connections using the Database Connection wizard. You must know the name of the relational database table that you intend to access before beginning.

To create a relational drill-through definition on an OLAP database connection:

#### 1 Perform one:

- Select File, then New, then Database Connection, then Analytic Services or Financial Management.
- Click , and select Database Connection, then Analytic Services or Financial Management.
- In the View Pane Browser tab, right-click an OLAP database connection in the Selection frame and select Edit. The database connection wizard for the selected database connection is displayed.

The first two options create a database connection. The last option enables you to define relational drill-through on an OLAP database connection.

The Process bar displays the steps for creating a database connection: Server, Database, Formatting, and Drill-through.

This procedure describes the creation of a relational drill-through definition on an OLAP or Oracle | Hyperion database connection. See also "Creating OLAP and Oracle | Hyperion Database Connections" on page 158.

2 On the Server, Database, and Formatting page, click **Next** until the **Drill-through** page is displayed.

Do not click Finish, or the wizard close without defining a drill-through connection.

3 On the Drill-through page, select Define Relational Drill-through Connection.

The Configure JDBC Driver dialog box is displayed. To successfully create a JDBC RDBMS connection, you must know the kind of relational data source you are accessing, the parameters needed to connect to it, and have a user name and password that supports connectivity.

- 4 Select one from **Driver Type**.
  - IBM DB2
  - Microsoft SQL Server
  - Oracle
  - Teradata
  - Other

Your JDBC driver selection populates the **Database Connection String** text area with a relational database connection string. If you selected Other, you must define your own JDBC connection string.

5 In **Database Connection String**, supply values for variables.

Depending on the driver type, there are variables for host name, database name, port, and DSN. You must replace the brackets and the variable.

- 6 Enter a JDBC user name in **Username**.
- 7 Enter a password for the user name in **Password**.
- 8 Click Test Connection to verify connectivity.

If the connection fails, repeat steps 6 through 10 until you can establish successful relational database connectivity. Make sure you remove the brackets from string variables.

After you connect, close the message and click **OK**.

The Modify Relational Drill-through Connection dialog box is displayed. With this dialog box, you can redefine a JDBC RDBMS connection, test the connection, identify a relational table, specify a column, and finally map the column to an OLAP dimension.

- 10 Enter a relational database table name in From.
- 11 Click Update Columns.

Column names for the specified table are displayed in the Column Name list at the bottom of the dialog box.

- 12 Designate the OLAP dimensions from which you connect to these table columns. To do this, you must understand the relationship between OLAP and relational data:
  - a. Click a cell in the Related Dimension column opposite a relational column name to which you would like to connect OLAP data.

The clicked cell presents a drop-down list with the dimension list of the OLAP database connection.

b. Click to select an OLAP dimension.

Repeat the process of mapping relational database columns and OLAP dimensions until your mappings are complete.

#### 13 Optional:

- Click Pass Pages to maintain the current OLAP pages as you drill into relational data.
- Click Pass Filters to maintain the current OLAP filters as you drill into relational data.
- Set row limits for the query result set in the "Max rows to return" text box. This protects server and network resources from being consumed unintentionally by very large query result sets.
- Specify SQL Select, Where, and Order By clauses to narrow the relational query result set.
- 14 Click OK.
- 15 Click Finish.

Your relational drill-through definition is saved as a database connection property.

#### **Essbase Database Connections**

#### **Subtopics**

- **Restrict Data**
- Retrieve Only Top/Bottom
- **Edit Data**
- Suppress Missing Rows, Zeroes, and Shared Members
- Label Mode and Alias Tables
- **Essbase Drill Settings**
- LR0s
- Relational Drill-Through
- Integration Services Drill-through
- **Essbase Advanced Member Selection**
- **Attribute Dimensions and Attribute Calculations**
- Essbase Metadata Security and Web Analysis Document Design

These Essbase features are extended through Web Analysis Studio:

- Restrict Data
- Retrieve Only Top/Bottom
- Edit Data
- Suppress Missing Rows, Zeroes, and Shared Members
- Label Mode and Alias Tables
- **Essbase Drill Settings**
- **LROs**
- Relational Drill-Through
- Integration Services Drill-Through
- Essbase Advanced Member Selection
- Attribute Dimensions and Attribute Calculations
- Essbase Metadata Security and Web Analysis Document Design

#### **Restrict Data**

The Restrict Data Analysis Tool enables you to narrow the return set by requiring data values to be relevant to rules and operands. Data can be filtered by comparison to another column or by fixed limits on one column.

See "Restricting Data" on page 122.

## **Retrieve Only Top/Bottom**

The Retrieve Only Top/Bottom Analysis Tool leverages Essbase sorting and ranking to control the size and order of an OLAP query result set. This protects the network server from transmitting, and the client from processing, large result sets.

See "Retrieve Only Top/Bottom" on page 124.

#### **Edit Data**

Users with permissions can edit data values and write edits back to the Essbase database. After edits are applied, you can recalculate the database and measure the impact of changed values.

See "Editing Data Values" on page 245

# **Suppress Missing Rows, Zeroes, and Shared Members**

Web Analysis Studio leverages Essbase to suppress missing rows, zeroes and shared members from the query result set. This prevents irrelevant information from being returned, reduces network traffic and increases query speed.

**Note:** The design in Suppress Shared Member functionality only works if selecting one of the following: Select Dim Bottom, Also Select Level, Also Select Generation..

#### **Label Mode and Alias Tables**

Label mode enables you to select whether a dimension member is listed by ID number, description, or both. Label mode options are database-specific, and can be set for database connections, documents, and dimensions.

Although the label mode indicates whether the description or ID number is used, it is Essbase alias table definitions that provide the displayed value.

See "Alias Tables" on page 265.

#### **Essbase Drill Settings**

Web Analysis Studio uses Essbase features to provide customizable drilling navigation in three ways:

- The nature of the hierarchical navigation
- Whether the current dimension members are replaced or augmented
- Whether the drilled dimension member is replaced or augmented

See "Drilling Variations" on page 86.

#### **LROs**

Essbase LROs enable user to annotate data values by associating external media with a cell. LRO types include:

- Text documents
- File Attachments
- **URLs**

See "Related Content Definitions" on page 247.

## **Relational Drill-Through**

Web Analysis Studio enables you to drill through to related relational data from the lowest level of the Essbase outline, by defining a link on Essbase database connections. You can pass pages, filters, and row limits to focus and control the relational query result set.

See "Defining Relational Drill-through" on page 163.

## **Integration Services Drill-through**

Integration Services enables you to organize, format, and present relational data as an OLAP cube in Essbase. Web Analysis Studio you to access Integration Services document data through Essbase LROs by drilling on cells marked for Integration Services drill-through.

See "Integration Services Drill-Through" on page 246.

#### **Essbase Advanced Member Selection**

In dimensions with large member sets, you can easily define selections with the Dimension Browser shortcut menu. Right-clicking dimension member names enables selection by familial relationship and database-specific selection options.

See "Advanced Member Selection" on page 61.

#### Attribute Dimensions and Attribute Calculations

Essbase can store dimension member names, locations, and relationships, and characteristics about members. Essbase does not store attribute dimensions as part of the OLAP cube, but instead dynamically calculates them upon request. Attribute dimensions are displayed in dimension hierarchies and used in calculations in the same manner as dimension members, despite being stored differently.

# **Essbase Metadata Security and Web Analysis Document** Design

If metadata security is established, when you create Web Analysis documents against an Essbase cube, adhere to this guideline:

If report member selections contain dimensions that are specified in a METAREAD filter, use dynamic member selections (for example, Children of East) and use only members that users can access. Users accessing a Web Analysis document that contains members that they cannot access receive an Unknown Member error.

For example, If a METAREAD filter applies to the Market dimension and @Children(East) is specified, when users try to open the Web Analysis document with the METAREAD filter, Unknown Member is displayed, because the users cannot access West, South, and Central.

# **Financial Management**

These Financial Management features are extended through the Web Analysis Studio graphical user interface:

- Org by Period
- Financial Management-specific Advanced Member Selection
- Financial Management Cell Text Related Content
- Financial Management Line Item Detail Related Content
- Financial Management Advanced Member Selection Methods
- Financial Management User Defined Fields
- Display Entity Currency

## **Financial Management Related Content**

The Related Content dialog box indicates links to previously configured related content and applications.

When Linked Reporting Object Indicators are enabled, blue triangles are displayed in the spreadsheet cells containing links to related content. Right-clicking these cells and selecting Related Content, displays the Related Content dialog box.

These Financial Management features are accessed as related content:

#### **Cell Text**

Web Analysis Studio users can launch Cell Text notes stored in the Financial Management data source. The text string is read-only.

#### **Line Item Detail**

Web Analysis Studio users can launch Line Item Detail spreadsheets stored in the Financial Management data source. Line Item Detail information is displayed in a read-only relational spreadsheet.

## **Recalculating Financial Management**

Changes to Cell Text and Line Item Detail items are not displayed in Web Analysis Studio until Financial Management is recalculated and the changes registered.

## **Org By Period**

Financial Management Organization by Period functionality allows an organization's latest consolidation structure to coexist with past structures in one application.

Dimension member hierarchies can be consolidated differently during different periods. Organizational structures can change for m reasons, including acquisitions, disposals, mergers, and reorganizations.

Web Analysis Studio users can access Org by Period functionality when Org by Period is configured and set on the Financial Management server.

When querying Financial Management database connections configured with Org by Period, the Data Layout Options button displays an Org by Period menu item. The Org by Period dialog box offers you an interface for enabling Org by Period and selecting three corresponding dimension members.

See "Managing Metadata" in the Oracle Hyperion Financial Management Administrator's Guide.

# **Financial Management Advanced Member Selection**

In dimensions with large member sets, you can easily define selections with the Dimension Browser shortcut menu. Right-clicking dimension member names enables selection by familial relationship and database-specific selection options. See "Advanced Member Selection" on page 61.

Financial Management offers a smaller set of advanced member selection methods than its Essbase counterpart. Typical Financial Management-specific advanced selection methods include:

Method	Description	
All Members	Selects all dimension members. This member selection method is specific to Financial Management.	
Select Dim Top	Selects the highest ancestor.	
Select Dim Bottom	Selects the lowest descendants.	

Method	Description	
Also Select Descendants	Selects the currently selected member and its descendants.	
Member List	Displays the Member List dialog box, for selecting predefined lists of dimension members. This member selection method is specific to Financial Management.	
User Defined Fields 1, 2, and 3	Displays the User Defined Field dialog box, enabling you to select dimension members with User Defined Field values.	
Search	Displays the Search dialog box, used to locate dimension members.	

#### **User Defined Fields**

User Defined Fields are typically defined only for Account, Scenario, Entity, and custom dimensions, and they are limited to 20 characters.

You can compose compound selection statements using values that differ for a User Defined Field (for example, User Defined Field 1= West AND User Defined Field 1= East.).

You cannot define a User Defined Field with an empty string as a value.

# **Display Entity Currency**

Financial Management stores currency metrics in the Value dimension, and as an attribute of the Entity dimension. This enables you to query the data source using a selected currency value, or a default currency value.

When using an Financial Management data source with defined Entity dimension currency information, you can enable the Display Entity Currency option, to append the Entity dimension members with your default currency value. This can be set before querying using Data Layout options, after querying using the Data Display shortcut menu, and for all subsequently created documents using OLAP Server preferences.

#### **Financial Management Conventions**

Financial Management supports 12 dimensions in outlines. Four are custom and eight are predefined: Period, View, Entity, Account, ICP, Scenario, Value, and Year.

#### **No Drill To Top**

If you query Financial Management, you cannot drill to top as you can when querying Essbase. Financial Management tracks parent-child relationships differently than Essbase. The Financial Management hierarchy enables multiple consolidations, which enables the existence of multiple parents for child.

#### **No Edit Data**

You cannot write data back to the Financial Management data source, as you can in Essbase.

#### **Adding and Deleting Dimension Members**

You must click the Reload button before dimensions with added or deleted members can be displayed.

#### **New Financial Management Databases**

Current sessions of Web Analysis Studio cannot interact with Financial Management data sources added during the course of the session. Only those data sources operating when the Web Analysis Studio session is established can communicate with Web Analysis Studio. To connect to new Financial Management databases, log off and log on again.

#### **Deleted Financial Management Users**

After you establish a Web Analysis Studio session with Financial Management, your access is not revoked under the sessions ends (that is, until you log out). This applies even when your user ID is deleted server-side.

#### **SAP BW**

# **SAP BW Pre-requisites**

To access SAP BW data sources you must first install SAP JCo driver on the Web Analysis Studio server. After installation, you must provide these SAP Logon parameters to create an SAP BW database connection:

- Host name or IP address of the SAP BW server
- Router string
- User name and password
- Client number
- System number
- Language

#### **SAP BW Conventions**

SAP BW conventions differ from other data sources. For example, Level 0 is the highest ancestor in SAP, as opposed to the lowest descendant in Essbase. SAP Member Properties are analogous to Essbase attribute dimensions.

Reporting and Analysis supports these SAP InfoProviders:

- InfoCubes
- ODS Objects
- InfoSets
- BEx Query Cubes
- Multiproviders

#### **SAP BW Advanced Member Selection**

In dimensions with large member sets, define selections with the Dimension Browser shortcut menu. Right-clicking dimension member names enables selection by familial relationship and database-specific selection options. See "Advanced Member Selection" on page 61.

Option	Selects
All Members	All dimension members. This member selection method is specific to Financial Management.
Select Dim Top	The highest ancestor, or in multiple hierarchies all top level ancestors.
Select Dim Bottom	All lowest level descendants.
Also Select Descendants	The currently selected member and its descendants.
Select Parent	The direct parent of the currently selected member.
Also Select Ancestors	The currently selected member and its ancestors.
Also Select Children	The currently selected member and its children (one level below).
Also Select Siblings	The currently selected member and members on one level with a shared parent ancestor.
Also Select Level	The currently selected dimension member and all dimension members on one level.
Select At Level	All members at a specified level of the dimension hierarchy. You can specify the level by name or number.
Also Select Previous	A variable number of previous members from the right-clicked member's level. Uses the MDX LAG command to indicate the number of previous members to return.
Also Select Next	A variable number of next members from the right-clicked member's level. Uses the MDX LEAD command to indicate the number of subsequent members to return.
Date Time Series	Time dimension members based on time definition criteria. SAP BW does not return aggregated values for DTS selections, and returns only the members that satisfy the criteria.
Select Top/Bottom	A variable number of dimension members based on their rank by another specified dimension member.
	You can select the top values or the bottom values. Rank can be calculated by percentage, sum, or count. Sum uses a threshold value to select dimension members up to and including the value that exceeds the threshold.
	Result sets may differ from dimension browser preview, due to the influence of custom filter selections on the query.

Option	Selects
Filter on Member Properties	Displays the Member Properties dialog box, for selecting a subset of members by their SAP BW member property values.
Find in Tree	Locates dimension members in large dimensions. Find In Tree expands the dimension hierarchy, but does not add found members to the Selection list.

## **SAP BW Features Available in Web Analysis Studio**

Web Analysis Studio extends these SAP BW features:

- SAP BW Variables
- SAP BW Period To Date
- SAP BW Top Bottom
- SAP BW Member Properties
- Searching for SAP BW Characteristic Values
- SAP BW Currency Conversion
- SAP BW Unit of Measure Conversion

# **Creating SAP BW Database Connections**

Before beginning, you must know the host name of your server or IP address, router string, client number, system number, language, catalogue, and cube, and have log on credentials.

- To create a document using the document creation wizard:
- 1 Perform one:
  - Select File, then New, then Database Connection, then SAP BW
  - Click , and select Database Connection, then SAP BW.

The Process bar is displayed the steps for creating an SAP BW database connection: Server, and Database. The content area displays the Server page.

- 2 In SAP BW Server, enter the host name or IP address of the server.
- 3 In Router String, enter the SAP BW server router string.
- 4 Enter a user ID, password, client number, system number, and language.

The current user ID and password are entered, in case known server credentials are used.

- 5 Optional: To save these credentials, select Save User ID and Password.
- 6 Click Next.

Clicking Next queries the data source for catalogue and cube information. The content area displays the **Database** page.

#### From Available Databases, select a cube.

Cubes are listed by catalogue. When you select the cube, the catalogue and cube name are loaded into the text area on the left.

To search for an InfoProvider:

- Under **Enter search criteria**, enter the criteria by which to search.
- b. Under **Search by label**, select whether to search for the InfoProvider based on the technical name, the description, or both.
- c. Click Search.
- d. Based on the search criteria entered, Web Analysis displays the technical name of the InfoProvider, the description of the InfoProvider, or both under Available Databases.
- Select Finish.

# **SQL Server Analysis Services**

## **SSAS Prerequisites**

To access SSAS, you must first install the SSAS client. For example, 2000 (version 8) from Pivot Table Services install or 2005 (version 5) from OLE DB 9 installer. The other pre-requisites are:

- Install and configure Oracle Hyperion Reporting and Analysis
- User authorization for Web Analysis
- Access to Microsoft SQL Server Analytic Services as a data source
- Access to the SSAS database and/or your own database

#### **SSAS Advanced Member Selections**

Option	Selects	
Also select Children	The currently selected member and its children (one level below).	
Also select Level	The currently selected dimension member and all dimension members on one level.	
Also select Previous	A variable number of previous members from the right-clicked member's level. Uses the MDX LAG command to indicate the number of previous members to return.	
Select Dim Bottom	All lowest level descendants.	
Date Time Series	Time dimension members based on time definition criteria. SSAS does not return aggregated values for DTS selections, and returns only the members that satisfy the criteria.	

Option	Selects	
Select Top/Bottom	A variable number of dimension members based on their rank by another specified dimension member. You can select the top values or the bottom values. Rank can be calculated by percentage, sum, or count. Sum uses a threshold value to select dimension members up to and including the value that exceeds the threshold. Results may differ from dimension browser preview, due to the influence of custom filter selections on the query.	

#### **SSAS Features Available in Web Analysis Studio**

The SSAS features available in Web Analysis Studio are:

- Suppress Missing data or zero
- Select ID/member vs Description/Alias per dimension
- Multiple Hierarchies
- Ragged Hierarchies
- Linked Cubes
- Large Dimensions (1-Million+ Members that is, more than 1 million members)
- Cell-Level & Dimension-Level Security
- Data Mining & Mining Dimensions
- **Connection Pooling**
- MSAS 2005 Aggregates
- Local Cube support
- Server-side Top/Bottom and Hierarchical Sort

## **SQL Server Analysis Services Connectivity**

To connect to Microsoft SQL Server Analysis Services, a database connection is needed. If a database connection exist, proceed to Step 2.

- 1. If no database connection exist:
  - In Web Analysis Studio, select File, then New, then Database Connection, then SSAS.
  - For SSAS Server, User ID, and Password enter the required information and click Next
  - Select a cube and click Finish.
  - Enter a database connection name in the Save dialog box.
- 2. To create a document, select File, then New, then Document Wizard.
- 3. Click **Browse** and select an SSAS database connection.
- 4. Select Auto Populate Dimensions and click Next
- 5. From Filters add one or more dimensions to Rows.
- 6. Double-click a dimension in Rows and select members.

**Note:** You can right click a member to use dynamic member selections.

- 7. From Filters add one or more dimensions to Columns
- 8. Double-click a dimension in columns and select members
- 9. Click Next to select Page members or click Finish to complete.

#### **Relational Access**

There are five methods for accessing relational data from the Web Analysis Studio client:

## **SQL Spreadsheet**

SQL Spreadsheets represent relational data sources as spreadsheet, using standard SQL syntax queries. See Chapter 14, "Creating SQL Spreadsheets."

#### **Freeform Grid**

Freeform grids enable you to combine data values from multiple data sources in one data object. See Chapter 15, "Creating Freeform Grids."

# **Relational Drill-through**

Web Analysis Studio users can construct liaisons between OLAP data and relational data sources. This navigation from OLAP to relational data is called relational drill-through. After configuration, you can drill from the bottom of OLAP dimensions (level 0) to relational data.

Web Analysis Studio stores relational drill-through definitions as database connection properties of an Essbase database connections. The query result set is presented in the format of the SQL Spreadsheet described above. See "Integrating OLAP and Relational Data" on page 162.

#### **Relational Database Connection**

Relational database connections specify a relational database type and login credentials and relational tables, and define the properties of the database connection and cube. Web Analysis Studio clients query the specified relational data source, aggregate the result set, and express data in the format of an OLAP cube.

#### **Integration Services Drill-through**

Integration Services Drill-through is a server-based form of relational drill-through. Like conventional relational drill-through, you can construct liaisons between OLAP and relational

data sources. Unlike conventional relational drill-through, you can drill to the relational document from intersection in the Web Analysis document.

Your Essbase Administrator must establish Integration Services drill-through documents. The relational query is stored as Intersection metadata, and flagged with an LRO indicator. When you double-click flagged cells, the OLAP document navigates to the specified relational document.

See "Integration Services Drill-Through" on page 246.

# **Controlling Query Result Set Size**

Query governors vary for relational access methods.

SQL spreadsheets and relational drill-through methods enable you to declare query governors while creating SQL queries or relational drill-through definitions.

When you drill from OLAP to relational data, passing only the drilled OLAP dimension member to the relational data source may result in a large query result set. To focus and diminish the query result set, you can pass OLAP page and filter dimensions.

Other relational access methods rely on the EPM System Configurator (CMC) application to limit the query result set.

#### **Relational Database Connections**

Before beginning, you must know the kind of supported JDBC RDBMS to which you are connecting, the name of your server and database, and have log on credentials. You also must know the organization and content of relational tables, to select and map column and table selections to a fact table.

# **Connection Page**

The first relational database connection wizard panel, Connection, requires you to configure a JDBC driver by specifying a supported relational database, editing the database connection string, and providing database login credentials.

Text box or Control	Description	
Driver Type	Selects one of the supported relational databases:	
	IBM DB2 7.2 Personal Edition	
	IBM DB2 7.2 fp7 and 8.1 fp2 Workgroup and Enterprise Edition	
	Microsoft SQL Server 2000 sp3	
	• Oracle 8.1.7 and 9.2.1	
	Teradata 4.1	
JDBC Driver	Displays the Java Database Connectivity Driver.	

Text box or Control	Description	
Database Connection String	Provides a sample database connection string syntax. Edit the string until it specifies the RDBMS computer name and database name.	
Username	Indicate a user name for the relational database. <b>Important!</b> You cannot create relational database connections without a user name and password.	
Password	Indicate a password for the user name. <b>Important!</b> You cannot create relational database connections without a user name and password.	
Test Connection	Click to test the relational connection before proceeding.	

#### Important notes on JDBC drivers:

The JDBC driver connects the application server hosting Web Analysis Studio and the relational database, not the client computer. You must ensure that the application server is able to connect.

Web Analysis Studio currently supplies all drivers that Oracle | Hyperion supports.

IBM DB2 is release specific. Oracle | Hyperion provides the JDBC driver for IBM DB2 7. The DB2java.zip client drivers must match the DB2java.zip archive on the IBM DB2 database server. Caution: Be extremely careful when copying files from the RDBMS server to the Web Analysis Studio installation directory! There are extreme consequences if you overwrite the application server local DB2 files used to access configuration information.

The Teradata 4.1 Connection string features four bracketed JDBC connection string parameters. Brackets and parameter names must be replaced with values.

Parameters	Description
{host-name}	Server domain name
{port}	TCP/IP port number
{DSN}	Data source name
{database name}	A database name

Note: JDBC driver archives must be explicitly referenced by file name within the classpath of the Webapp application server.

## **Select Fact Table Page**

The second relational database connection wizard panel, Select Fact Table, provides filters for locating a fact table by schema and finally table name.

Text box or Control	Select
Schema Filter	A schema type from the corresponding drop-down list.
Table Type Filter	A table filter from the corresponding drop-down list.

Text box or Control	Select
Retrieve Table List	This button retrieves the list of relational tables.

# **Relational Cube Editor**

The third relational database connection wizard panel, Relational Cube Editor, diagrams the relational cube as a node tree.

Default Node	Shortcut Menu	Right-click node and select menu command to:
Relational Cube		
	Rename Cube	Specifies the relational database connection name.
Dimensions		
	Add Dimension	Creates a dimension.
Defined Dimension		
	Add Generation	Specifies a relational column as a dimension generation.
	Rename Dimension	Specifies a name for the dimension.
	Delete Dimension	Removes the dimension from the node hierarchy.
	Preview	Displays a node tree of the selected dimension hierarchy.
Defined Generation		
	Edit Generation	Changes properties for that generation.
	Rename Generation	Specifies a name for that generation.
	Delete Generation	Removes that generation from the node hierarchy.
	Move Up	Moves that generation up in the node hierarchy.
	Move Down	Moves that generation down in the node hierarchy.
	Preview	Displays a node tree of the selected dimension hierarchy.
Measures		
	Edit Measures	Specifies columns as measures.
	Rename	Specifies another name for the measures dimension.
	Preview	Displays a node tree of the selected dimension hierarchy.
Defined Measure		
	Rename Member	Specifies a name for the measure.

Default Node	Shortcut Menu	Right-click node and select menu command to:
	Delete Measure	Removes the measure from the node hierarchy.
	Preview	Displays a node tree of the selected dimension hierarchy.
	Order By Mode	Indicates the label used to determine Dimension Header Sorting. Options include ID and Alias.
	Dimension Header Sort	Indicates the order that relational members are displayed by the Dimension Browser dialog box. Subsequent users must use this dialog box to select members from the relational data source. Options include:
		Default (Natural ordering based on outline)
		Ascending
		Descending
Properties		Displays the properties of the currently selected node.

#### Important notes on relational table properties:

To protect open documents and to expedite network traffic, there is only one cached JDBC connection per user per relational database connection. Therefore, relational database connection edits are not implemented until you log off Web Analysis Studio and log back on.

## **Creating Relational Database Connections**

To create a relational database connection:

#### Perform one:

- Select File, then New, then Database Connection, then Relational.
- Click , and select Database Connection, then Relational.

The Process bar displays the steps for creating relational database connections: Connection, Select Fact Table, and Define Cube. To successfully create a JDBC RDBMS connection, you must know the kind of relational data source you are accessing, the parameters needed to connect to it, and have a user name and password that supports connectivity.

#### Select one from **Driver Type**:

- IBM DB2
- Microsoft SQL Server
- Oracle
- Teradata

Your JDBC driver selection populates the Database Connection String text area with a relational database connection string.

Replace **Database Connection String** variables with values.

Depending on the driver type, there are variables for host name, database name, port, and DSN. You must replace the brackets and the variable.

- Enter a JDBC user name in Username.
- Enter a password in **Password**.
- Click Test Connection.

If the connection fails, repeat steps 6 through 10 until you can establish successful relational database connectivity. Make sure you remove brackets from string variables.

After connecting, close the Test Connection message and click Next.

Step 2: Select Fact Table you must select a relational fact table from a list. Schema filters and table type filters are available to narrow long lists of tables.

**Note:** Before you can use a schema filter, it must be mapped to the RDBMS database user name used to log on to the database. This user name is specified on the previous wizard page, Configure JDBC Drivers.

- Select a schema from Schema Filter.
- Select a table type from **Table Type Filter**.
- 10 Click Retrieve Table List to query the relational database for tables meeting filter requirements, and display the result set.

To select the fact table, you must understand the relational database. If necessary, ask the relational database administrator to identify the fact table. The fact table must contain at least one column of numeric data that can be used as a measures dimension.

11 Select a table to be used as the fact table from the table result set, and click Next.

Step 3 Relational Cube Editor diagrams the relational cube as a node tree in the same manner that the Dimension Browser presents OLAP cubes. Click to select a node. Double-click to expand and collapse nodes. Right-click to edit dimensions and measures.

12 Right-click Measures and select Edit Measures.

The Measure Editor dialog box enables you to define relational columns as measures by moving them from the Available Columns list to the Measures Members list. You can also rename the measures dimension, specify the default dimension, add measures to the cube, and specify aggregation methods for measures dimensions.

13 Select a column with a numeric data type from Available Columns, and click the right arrow (>) to move the column to **Measure Members**.

Note that the selected measure is designated as the default measure dimensions.

- 14 Optional: When Measure Members contains multiple measures, you can specify the measure used as the default measure by clicking an option in Default.
- 15 Optional: To change the measure name, double-click Member Name, and type a name. Member names must be unique to each other and the name of the measures dimension for SQL parsing to be successful.

- 16 Optional: To indicate another member aggregation method, click Aggregation Type and select from these aggregation methods. When no aggregation type is specified Sum is used by default:
  - Sum
  - Count
  - Min
  - Max
  - Avg
- 17 When all fact table columns used as measures are specified, click **OK**.

The **Relational Cube Editor** is displayed. Note that the Measures node can be expanded to display the measures dimension.

18 Right-click **Dimensions** and select **Add Dimension**.

The New Dimension Name dialog box is displayed.

19 Enter a dimension name to define, and click **OK**.

The Generation Editor dialog box is displayed. It enables you to create a generation for the dimension, to name the generation, to indicate the ID and alias tables used for return values, and to relate the dimension back to the fact table.

20 Enter a dimension generation name in **Generation Name**.

Note that Select Member ID and Description Columns displays the fact table by default.

- 21 To narrow the list of tables, select a filter from **Table Type**.
- 22 Select a table from Table.
- 23 Indicate the ID aliases column in the top Column list.
- 24 Indicate the Descriptions aliases column in the bottom Column list.

By identifying common table columns, you relate the defined dimension generation to the fact table. Typically, several sets of common columns are used to identify a circuit to the fact table.

Ask the relational database administrator for a description of relational tables and their columns to discern common table columns.

Start by identifying tables sharing columns with the dimension generation table. Find tables sharing columns with the fact table. Determine if tables that share columns with the dimension generation also share columns with the fact table. If they do, your relationship is mapped. If not, you must continue comparing columns until you can map a bridge between the dimension generation and the fact table.

Note that **Define Fact Table Mappings** displays the dimension and the fact table by default. Unless they share a common column, you must select a Table Type filter, a table, and a column that matches the dimension generation. If they do share a common column, you need only indicate that column in the Column drop-down list.

When a table and column are selected, a line is added to Define Fact Table Mappings below until the dimension generation and fact table relationship is mapped.

Keep these considerations in mind as you make your selections.

- Question marks (?) indicate unspecified columns.
- Left and right Column lists must display common columns.
- Each **Define Fact Table Mappings** line should display column sets that differ from the line above.
- To improve performance, specify as few column sets as is possible.
- 25 In Define Fact Table Mappings, select a table from Table that has a column that matches Column.

The specified table and column display on a line below.

- 26 Select a Column at right that matches the Column at left.
- 27 Repeat steps 25 and 26 until a relationship between the dimension generation and the fact table is mapped, and click **OK**.

The **Relational Cube Editor** is the current dialog box again. Note that the Dimension, generation and Measures nodes can be expanded, by clicking the plus sign (+), to display the relational cube structure.

- 28 Optional: To add generations to one dimension, right-click the dimension name and select Add Generation. The Generation Editor is displayed again. Repeat steps 20-27.
- 29 **Optional**: To reorder the generations in the dimension hierarchy, right-click a generation name and select **Move Up** or **Move Down**.

The generation node moves in the specified direction in the dimension hierarchy.

- 30 Optional: To add dimensions to one relational cube, right-click Dimensions and select Add Dimension. Repeat steps 18-29.
- 31 When all measures, dimensions, and generations are defined and ordered, click Finish.

The **Save As** dialog box is displayed. It prompts you to navigate to the repository location where the database connection is saved.

- 32 Navigate to the folder into which you want to save your database connection file:
  - Click **Up** to display the contents of the parent folder in the selection frame.
  - Click **Home** to jump to and display the contents of the current Home folder (set in preferences) in the selection frame.
  - In Location, type the path to the repository folder whose contents you want displayed, and press Enter.
  - In Location, click the drop-down arrow and select another location from the repository.
  - When you navigate to another folder, you can click **Previous** to return to the last folder.
  - Similarly, you can click Next to display the next folder in the location series.
     As you navigate, the selection frame lists the files and folders indicated by Files of Type.
- 33 When you reach the location where you want to save the file, enter a name for the database connection in **Filename**, and click **OK**.

Your relational database connection file is saved to the specified repository location. You can use it to create documents, just as you would OLAP database connection.

## **Editing Database Connections**

You edit database connections to select other data sources or change formatting preferences.

- ➤ To edit database connections:
- In Web Analysis Studio, navigate the repository to locate the database connection file.
- 2 Select the database connection file, then right click and select Edit to display the Database Connection wizard.
- 3 Change items as desired.
  - You can select different servers and databases.
- Click Finish to save the changes and close the Database Connection wizard.

## **Changing Database Connections for Report Objects**

- To change the database connection that a report object (that is, spreadsheet, chart, or pinboard) uses:
- 1 Open a Web Analysis document; if it contains multiple report objects, select a report object to edit by clicking on it.
- Click to display the View Pane.
- Right click Database (database node) in the View Pane and select Change Database. The Open dialog box is displayed.
- Select a database connection and click **OK** to change the database connection for the report object.


# **Creating Pinboards**

#### **In This Chapter**

Pinboards	187
Pinboard Designer	188
Creating a Pinboard	189
Modifying Pinboards	190
Creating a Pinboard Series	190
Creating Pins	190
Creating Image Pins	192
Creating Color Pins.	193

## **Pinboards**

Pinboards are custom graphic representations of multiple dimensions. Pinboard dimensions are represented by a graphic, pin icons on the graphic, and the color (or state) of the pins.



#### **Pinboards Prerequisites**

Because pins dynamically change image or color based on traffic lighting cues, you must establish traffic light definitions for the corresponding spreadsheet before designing the pinboard.

#### **Creating a Pinboard Series**

A pinboard series enables drilling from one pinboard to another. You create the first pinboard in the series and use the Pinboard Designer shortcut menu to designate subsequent pinboards. The subsequent pinboards are generated using the children of the previous pinboard's pins. If the current pinboard represents the dimension bottom, no subsequent pinboard can be created in this series. See "Creating a Pinboard Series" on page 190.

#### **Creating Pins**

You can use the default pins provided with Web Analysis Studio or create your own pins using the Pin Designer. Pins can change an image or color based on traffic lighting. See "Creating Pins" on page 190.

#### **Traffic Lighting Control Panel**

Only the pinboard display type displays a traffic lighting control panel when multiple traffic lighting definitions exist in the document. The traffic lighting control panel enables you to scroll through the series of traffic lighting definitions.

Note: If a traffic lighting definition exists on the opposite axis (row versus column, or column versus row), it will be listed in the traffic lighting control panel, however it cannot be used to define a pinboard on the selected axis. Only traffic lighting definitions that exist on the same axis as the selected axis can be used to define a pinboard.

#### **Select Traffic Lighting Dimension Dialog Box**

The Select Traffic Lighting Dimension dialog box prompts you to create a pinboard from another display type without traffic lighting. After selecting the dimension to which a traffic lighting definition is applied, the Traffic Lighting dialog box is displayed to finish the definition.

## **Pinboard Designer**

The Pinboard Designer interface includes:

- Pinboard panel—positions pin graphics relative to the background.
- Image Source group—Specifies the background.
- Member Selections group—Specifies dimension members used as pins.

- Null Pins group—Indicates how to display members with null values.
- Select Pin Images group—Specifies the kind of pin to display for each traffic lighting color.

## **Creating a Pinboard**

- To create a pinboard:
- 1 Open spreadsheet with a traffic lighting definition.
- 2 Select Display, then Pinboard.

**Note:** If a pinboard is defined for the document, it is displayed as a result of your selection. When no pinboard is defined, the Pinboard Designer is displayed. To edit a Pinboard, right-click the data object and select Edit Pinboard.

Pinboard Designer is displayed, automatically displaying column dimension members as pins and traffic lighting ranges as pin colors in the Select Pin Images group.

3 In the Image Source group, click Set Background.

The Open dialog is displayed.

4 Navigate to a GIF or JPEG file to use as the background. Select the file name, and click **OK**.

The selected image is displayed in the Pinboard Designer panel.

- 5 Optional: To set the image to fill the Pinboard panel, select Stretch to Fit.
- **Optional:** To change the dimension member selections, perform one:
  - Click the Member Selections list to select other traffic lighted column dimension members.
  - Click **Add Members** to display the Dimension Browser, and change dimension member selections.
  - Click Add Calculations to create pins from calculated members.
  - Right-click a pin and select Delete Pin, to remove pins without redefining the member selection statement.
- 7 Optional: To specify to hide pins with null values, select Hide Null Pin.
- Optional: You can also select a special color for pins with null values, by clicking Select Null Pin Color.

The Select Null Pin Color dialog box is displayed, enabling you to select a color, and click OK. See "Selecting Color" on page 110. The selected color is displayed in the box beside the button, after selection.

The specified dimension members are rendered with default pins on the Pinboard panel. The Select Pin Images group reflects the traffic lighting range colors. You can also specify pin images that differ for each traffic lighting range, or a different part of the current pin image to reflect the traffic lighting range color.

See "Creating Image Pins" on page 192, or "Creating Color Pins" on page 193.

- Drag pin images on the Pinboard background to position them.
- 10 Click Pinboard Designer **OK** to display the finished pinboard.

## **Modifying Pinboards**

You must have the correct permissions to change pinboards.

To edit a pinboard, select Edit Pinboard from the data object shortcut menu and modify options.

## **Creating a Pinboard Series**

- To create a pinboard series:
- Create the starting pinboard and its pins.

The starting pinboard must feature pins with descendants.

- Right-click a pin on the Pinboard Designer and select the Next Pinboard menu command.
  - Pinboard Designer displays a subsequent pinboard using the children of the previous pinboard pins.
- Set the background image, and pin images. Position these pins.
- Repeat until all pinboards in the series are specified.

This table describes the Pinboard Designer shortcut menu commands that help to define Pinboard series:

Command	Description
Next Pinboard	Go to the next pinboard in the series. If no next pinboard exists, create one using the children of the previous pinboard pins.
Previous Pinboard	Go to the previous pinboard in the series.
Starting Pinboard	Go to the first pinboard created.
Delete Pinboard	Delete the current pinboard.
Delete Pin	Delete the current pin.

## **Creating Pins**

Pin options:

- A default pin, , is provided by Web Analysis Studio.
- An Image Pin, , displays pin images that differ per an associated traffic lighting definition.
- A Color Pin, , changes its active color per the traffic lighting definition.

#### **Selecting Pins**

The Select Pin Images dialog box presents pin graphics available for use in the current pinboard. You can add pins, edit pins (using Pin Designer), or delete pins from the list. The default pin cannot be deleted.

- To select a pin for a traffic lighting range:
- 1 Click a Pin from Pinboard Designer Select Pin Images.

The Select Pin Images dialog box is displayed.

2 Select a pin from the list and click **OK**.

The selected pin is displayed next to the traffic light range it represents.

#### **Creating Pins**

- To add a pin image and set it to a traffic lighting range:
- 1 Click a Pin from Pinboard Designer Select Pin Images.

The Select Pin Images dialog box is displayed.

2 Click Add.

The Pin Designer dialog box is displayed.

3 In Pin Image, click Load.

The Open dialog is displayed.

4 Navigate to a GIF or JPEG file to use as the pin image. Select the file name, and click **OK**.

The selected image is displayed in the Pin Designer panel.

Before a pin can be added to the selection list, the point of the pin and its active color must be defined. This is accomplished using the Pin Designer shortcut menu:

Optional: To set the point of the pin, right-click the pin image where you think the point should be, and select Hotspot.

The grid to the left demonstrates how the pin is positioned relative to this point.

Optional: To set the Active Color, right-click a prominent color in the pin image, and select Active Color. The Active Color panel reflects this selection. You should only elect an Active color when you are going to use one pin image for every traffic lighting range. This enables the selected color to adopt the color of the traffic lighting range.

Click OK.

The pin is displayed in the Select Pin Images dialog box.

Select the pin from the list and click **OK**.

The pin is displayed next to the traffic light range it represents.

#### **Editing Pins**

To redefine pin location point or active color, you can edit pins.

To edit a pin, access the Select Pin Images dialog box, select the pin and click Edit.

See "Creating Pins" on page 191.

#### **Deleting Pins**

To delete a pin, access the Select Pin Images dialog box, select the pin and click Delete.

## **Creating Image Pins**

Image pins display pin images that differ per an associated traffic lighting definition. You create Image pins by indicating the pin image to use for corresponding traffic lighting ranges.

Pins on the Pinboard panel may not accurately reflect all pin images and traffic lighting ranges until the Pinboard is finished and displayed as a document.

If you select duplicate images for traffic lighting conditions, you must set the pin Active Color property to differentiate traffic lighting conditions. See "Creating Color Pins" on page 193.

- To create an image pin:
- Click a Pin from the Pinboard Designer Select Pin Images.

The Select Pin Images dialog box is displayed.

- Click Add.
- The Pin Designer dialog box is displayed.
- In Pin Image, click Load.

The Open dialog is displayed.

Navigate to a GIF or JPEG file to use as the pin image. Select the file name, and click OK.

The selected image is displayed in the Pin Designer panel.

Before a pin can be added to the selection list, the point of the pin and its active color must be defined. This is accomplished using the Pin Designer shortcut menu:

Optional: To set the point of the pin, right-click the pin image where you think the point should be, and select Hotspot.

The grid to the left demonstrates how the pin is positioned relative to this point.

7 Click OK.

The pin is displayed in the Select Pin Images dialog box.

8 Select the pin from the list, and click **OK**.

The pin is displayed next to the traffic light range it represents.

9 Repeat steps 1 through 8 for each traffic lighting range.

The traffic lighting definition displays the corresponding pin for each traffic lighting range, when the Pinboard is in Analyze mode.

## **Creating Color Pins**

Color pins change their active color per the traffic lighting definition. You create Color pins by indicating the pin image to use for corresponding traffic lighting conditions, and indicating the Active Color.

Pins on the Pinboard panel may not accurately reflect all pin images and traffic lighting conditions until the Pinboard is finished and displayed as a document.

Pins on the Pinboard Panel may not accurately reflect all pin images and traffic lighting ranges until the Pinboard is finished and displayed as a document.

- To create a color pin:
- 1 Click a Pin from Pinboard Designer Select Pin Images.

The Select Pin Images dialog box is displayed.

- 2 Click Add.
- 3 The Pin Designer dialog box is displayed.
- 4 In Pin Image, click **Load**.

The Open dialog is displayed.

5 Navigate to a GIF or JPEG file to use as the pin image. Select the file name, and click OK.

The selected image is displayed in the Pin Designer panel.

Before a pin can be added to the selection list, the point of the pin and its active color must be defined. This is accomplished using the Pin Designer shortcut menu:

Optional: To set the point of the pin, right-click the pin image where you think the point should be, and select Hotspot.

The grid to the left demonstrates how the pin is positioned relative to this point.

To set the Active Color, right-click a prominent color in the pin image, and select Active Color.

The Active Color panel reflects this selection. By electing an Active color, you indicate that this color is replaced by the traffic lighting range color.

Click OK.

The pin is displayed in the Select Pin Images dialog box.

Select the pin from the list, and click **OK**.

The pin is displayed next to the traffic light range it represents.

10 Click another Pin from Pinboard Designer Select Pin Images.

The Select Pin Images dialog box is displayed.

11 Select a matching pin image, and click **OK**.

The pin is displayed next to another traffic light range. The Active Color of this pin is replaced by the color of the range.

12 Repeat steps 10 and 11 for all traffic lighting ranges, and click **OK**.



# Creating SQL Spreadsheets

#### **In This Chapter**

SQL Spreadsheets	195
Creating SQL Spreadsheets	196
Creating SQL Spreadsheets with SQL Query Builder Wizard	197
Enter SQL Query Dialog Box.	199
SQL Query Builder Wizard	200
Creating a SQL Subscription Control	203

## **SQL Spreadsheets**

SQL Spreadsheet data objects enable you to query a relational data source, and display the returned data values on a custom document.

Prerequisites for SQL Spreadsheets:

- SQL Spreadsheets can only be created on a custom document.
- You must understand how to compose a SQL query to create a SQL spreadsheet.
- You must be able to connect to a relational data source using supported JDBC drivers.

To create a SQL Spreadsheet you are required to specify:

- Data source that provides data values
- SQL spreadsheet data object that displays these values
- Query that gets data values from the data source and returns them to the data object.

Note: If you import a Web Analysis document that contains an SQL Spreadsheet (exported and imported via APT file format) from one environment to another, the password in the target environment will not be decrypted properly. Therefore, you will have to edit SQL query settings to specify a valid password. To change the password for SQL Spreadsheet, right-click on the Spreadsheet and open the Open Query dialog box. Enter the password into the JDBC password text field.

The process of creating SQL spreadsheets assumes that you know your JDBC driver, database application, and logon credentials. The process also assumes that you can compose the SQL query for the SQL spreadsheet data object, or be able to use a SQL Query Builder to create a query.

There are four alternatives for accessing relational data in Web Analysis Studio:

- You can create a relational database connection to be used by regular spreadsheets, charts, and pinboards. See "Creating Relational Database Connections" on page 181.
- Free-form grids enable you to combine data values from multiple data sources in one data object. Free-form grids leverage custom document database connections. See "Creating Freeform Grids" on page 205.
- You can create a relational drill-through connection from an OLAP database connection to a relational data source. See "Creating Relational Drill-Through" on page 163.
- You can leverage predefined Integration Services drill-through documents using the Related Content dialog box. See "Integration Services Drill-Through" on page 246.

Note: To troubleshoot SQL queries, copy the SQL statement from the Enter SQL Query dialog box and run it in an RDBMS SQL tool. Compare the result sets.

## **Creating SQL Spreadsheets**

- To create a SQL spreadsheet:
- Start Web Analysis Studio.
- Perform one:
  - Select File, then New, then Document.
  - Click 🛂
  - Click , and select Document.
  - In the View Pane Browser tab, right-click a document and select Edit.
  - Press Ctrl+N.

The Document Designer is displayed.

Drag the SQL Spreadsheet icon from the component toolbar to a document panel.

The Enter SQL Query dialog box is displayed.

Select a supported JDBC driver type from the JDBC Driver drop-down list.

You can select from Microsoft SQL Server, IBM DB2, Oracle, JDBC-ODBC Bridge, and Other.

When the selection is made, a driver name populates the corresponding Driver text box. If Other is selected, you must enter a driver name definition.

When the selection is made, a sample database connection string syntax populates the corresponding JDBC Connection String text box. When Other is selected, you must enter a JDBC database connection string.

Edit the sample database connection string syntax so that it specifies your RDBMS computer name and database name.

- Enter a user name and password for the relational data source in the corresponding text boxes, or select **Username/Password** to enter your current logon credentials.
- 7 **Optional:** Define query governor parameters for row limits and fetch size.

The default settings limit the result set to 250 rows, being fetched 100.

- Define a SQL query, using one of these methods:
  - Enter a SQL query, using standard SQL syntax, in the panel at the bottom of the dialog
  - Click Query Builder to display the SQL Query Builder Wizard. See "SQL Query Builder Wizard" on page 200.
- Click OK.

The query is sent to the relational data source and a SQL spreadsheet is displayed on the document panel.

## **Creating SQL Spreadsheets with SQL Query Builder Wizard**

The SQL Spreadsheet component offers advanced features for creating dynamic SQL queries and subsequently dynamic relational spreadsheets. You can quickly and conveniently compose SQL queries using the SQL Query Builder Wizard.

- ➤ To create a SQL spreadsheet:
- 1 Start Web Analysis Studio.
- Perform one:
  - Select File, then New, then Document.
  - Click 🕍
  - Click , and select Document.
  - In the View Pane Browser tab, right-click a document and select Edit.
  - Press Ctrl+N.

The Document Designer is displayed.

Drag the SQL Spreadsheet icon from the component toolbar to a document panel.

The Enter SQL Query dialog box is displayed.

Select a supported JDBC driver type from the JDBC Driver list.

You can select from Microsoft SQL Server, IBM DB2, Oracle, JDBC-ODBC Bridge, and Other.

When the selection is made, a driver name populates the corresponding Driver text box. If Other is selected, you must enter a driver name definition.

When the selection is made, a sample database connection string syntax populates the corresponding JDBC Connection String text box. When Other is selected, you must enter a JDBC database connection string.

- Edit the sample database connection string syntax so that it specifies your RDBMS computer name and database name.
- Enter a user name and password for the relational data source in the corresponding text boxes, or select **Username/Password** to enter your current logon credentials.
- **Optional:** Define query governor parameters for row limits and fetch size.

The default settings limit the result set to 250 rows, being fetched 100.

You could define a SQL query by entering standard SQL syntax, in the panel at the bottom of the dialog box, but use the SQL Query Builder as described in these steps.

Click Query Builder to display the SQL Query Builder Wizard.

The SQL Query Builder dialog box features tabs corresponding to aspects of your relational data source:

- **Tables**—specifies the relational table(s) to query.
- Columns—specifies the columns to be returned by the query.
- Filters—narrows the focus of the SQL query by specifying filter criterion for Where clauses.
- **Groups**—organizes relational data on the server before it is returned.
- **Sorting**—orders relational data in ascending or descending order per column.
- Mappings—relates relational columns in the SQL query result set to multidimensional dimensions from an OLAP data source.
- Click Tables, and select one or more tables.

To select a table, click the table name in **Available Tables**, and click one of the arrow buttons. The selection moves to Selected Tables. You can also move selected tables up and down in order.

10 Click Columns, and select one or more columns.

To select a column, click the column name in Available Columns, and click one of the arrow buttons in the center of the tab. The selection moves to Selected Columns.

11 Optional: To change a column name, or apply a function call to the column, click Add Column Advanced, the middle button on the Columns tab before moving the column to the Selected Columns frame.

Add Columns Advanced on the Columns tab displays the Select Column Advanced dialog box, enabling you to apply function calls to a selected column (on the Columns tab) or manually enter a RDBMS supported function call. You can select from these functions: None, Average, Count, Maximum, Minimum, or Sum.

If you would like to change the column name in the SQL spreadsheet display, enter an alternate name in Displayed As.

12 Optional: To define Where clauses for the SQL query, click Filters.

The Filters tab enables you to define complex Where clauses by selecting parameters from drop-down lists. Select parameters from four columns: Operator, Column, Comparator, and Value.

To define a Where clause:

- a. Click **Add** to add a row to the Filters frame.
- b. Click the Column cell in the row and select a column name from the list.
- c. To filter the selected column, click the Comparator cell. You can select from these options:
  - Enter a constant.
  - Right-click and select the value of another column member.
  - Enter a dynamic text label, a variable that is dynamically replaced with a value at runtime. See "Dynamic Text Labels" on page 202.
- d. Click the Value cell and select a filter value. This limits the return set to those rows that satisfy filter criteria.

You can compose compound statements by adding additional rows, selecting operands from the Operator column and parentheses from the (and) lists.

Note that Select Distinct changes the selection statement to a SELECT DISTINCT statement.

13 Optional: To define a dynamic SQL spreadsheet, enter dynamic text labels for values on Filters.

You can enter Dynamic Text Labels that reference data, metadata, fixed references and time format syntaxes. See, "Dynamic Text Labels" on page 202.

- 14 Optional: To define a GROUP BY clause for the SQL query, click Groups.
- 15 Optional: To define a SORT clause for the SQL query, click Sorting.
- 16 Optional: To map columns in your relational data sources to similar OLAP dimensions, click Mappings.

You can associate columns in your relational data sources with similar dimensions in an OLAP data source, by mapping columns to OLAP dimensions. These mappings, used when drill linking from an OLAP source to a SQL data object, enable the OLAP query to pass its Where clauses to corresponding relational columns.

17 Click **OK** to query the relational data source and display a SQL spreadsheet.

#### **Enter SQL Query Dialog Box**

The Enter SQL Query dialog box enables you to define a relational SQL query that supports the SQL Spreadsheet custom document component. The Enter SQL Query dialog box prompts you to specify a supported JDBC driver, JDBC connection string, log on credentials, and a SQL query. You can compose the SQL query using standard SQL syntax in the panel at the bottom of the dialog box, or you can use a SQL Query Builder Wizard. You can also define row limits and fetch limit parameters for the SQL query.

Control	Description
JDBC Driver	Enables you to select a supported JDBC driver from a drop-down list:
Configuration	IBM DB2
	Microsoft SQL Server
	Oracle
	Teradata
	<ul> <li>JDBC-ODBC Bridge—leverages a Microsoft Windows ODBC driver as a JDBC connection. To use this option, you must manually configure the JDBC Connection String using JDBC:ODBC:<dsn> (where DSN is the ODBC connection name).</dsn></li> </ul>
	Other—Specifies alternative JDBC driver parameters.
JDBC Connection String	A sample database connection string syntax is provided in this text box. You must edit the string so that it specifies your RDBMS computer name and database name. In the case of Other, you must enter a database connection string syntax.
JDBC Username	Indicate a user name for the relational database. You cannot create a relational database connection without specifying a password.
JDBC Password	Indicate a password for the user name. <b>Important!</b> Web Analysis Studio requires this text box to be populated. You cannot create a relational database connection without specifying a user name and password.
JDBC Row Limit	Enables you to enter an optional query governor limiting the result set to a number of rows.
JDBC Fetch Size	Enables you to enter an optional query governor limiting the number of rows returned at time. In other words, transactions limited to the fetch size are conducted until the overall row limit is reached.
SQL Query Panel	Enables you to enter a SQL query manually.
Query Builder	Displays the SQL Query Builder Wizard, enabling you to make selections from tabs that are subsequently parsed into a SQL query.

# **SQL Query Builder Wizard**

The SQL Query Builder wizard specifies the elements used in a SQL syntax query. This is helpful if you are familiar with your relational data source, but do not know SQL syntax.

SQL Query Builder Tab	Procedure and Controls	Description
Tables		
	Select tables in the Available Tables panel and move them to the Selected Tables panel using <b>Add</b> and <b>Remove</b> in the middle.	Prompts you to select tables from the relational data source, prescribed on the Enter SQL Query dialog box, for use in a SQL query.
	To reorder the table selections, select a table in the Selected Table panel and click the up and down arrow buttons.	
Columns		

SQL Query Builder Tab	Procedure and Controls	Description	
	Select columns in the Available Columns panel and move them to the Selected Columns panel using <b>Add</b> and <b>Remove</b> in the middle.	Prompts you to select columns from the relational tables for use in a SQL query.	
	To reorder the Column selections, select a column in the Selected Column panel and click the up and down arrow buttons.		
	Select Column Advanced	Displays the Select Column Advanced dialog box, enabling you to select a function call, compose an expression, or enter an alternative column label.	
Filters			
	Click <b>Add</b> to enter a Where clause. Click each column cell and make a selection from the drop-down list.	Prompts you to define filter selections for the Where clause on the SQL query. To focus and diminish the query result set, you can define dimension criteria (filters).	
	Dynamic Text Labels	You can also employ the powerful dynamic text labels used by the Print function and the Custom Document Label component in your SQL expressions.	
	Select Distinct	Sets up the query to return only distinct rows; eliminates duplicate rows.	
Groups			
	Select columns in the Available Group By Columns panel and move them to the Selected Group By Columns panel using <b>Add</b> and <b>Remove</b> in the middle.	Prompts you to define GROUP BY selections for the SQL query. Groupings sort rows based on column members but do not order the rows.	
	To reorder the column selections, select a column in the Selected Group By Column panel and click the up and down arrow buttons.		
Sorting			
	Select columns in the Available Sort Columns panel and move them to the Selected Sort Columns panel using <b>Add Sort Ascending</b> and <b>Add Sort Descending</b> in the middle.	Prompts you to define sorting criteria for the SQL query result set in Ascending or Descending order.  Sorting results are influenced by the order of tables, columns, and filters on their corresponding tabs.	
	To reorder the Column selections, select a column in the Selected Sort Column panel and click the up and down arrow buttons.		
Mappings			
	Enter the OLAP dimension name to the right of the relational column supporting drill linking.	Prompts you to define (or map) drill links to or from relational columns to OLAP dimensions in other documents.	

#### **Select Column Advanced Dialog Box**

The Select Column Advanced dialog box specifies a function call, composes an expression, or enters an alternative column label in a SQL Spreadsheet query. You can access the Select Column Advanced dialog box only from the Columns tab of the SQL Query Builder Wizard.

Control	Description
Function	Enables you to enter a function call related to the column selected on the Column tab of the SQL Query Builder wizard.
	• None
	Average
	Count
	Maximum
	Minimum
	• Sum
Expression	Enables you to manually enter a RDBMS supported function call for the column selected on the Column tab of the SQL Query Builder wizard.
Displayed As	Enters an alternative column label in the SQL Spreadsheet query for the column selected on the Column tab of the SQL Query Builder wizard.

#### **Dynamic Text Labels**

Dynamic text labels are variables that are dynamically replaced with values at runtime. Dynamic text labels display the latest information without being manually updated

You can use Dynamic Text Labels in these ways:

- To create dynamically updated labels on custom documents, add dynamic text labels to custom document label objects using the shortcut menu. See "Creating Dynamic Text Labels" on page 233.
- To create dynamically updated headers and footers for your JPG output, PDF output and hardcopy printing, use dynamic text labels in the Print dialog box Headers/Footers tab. See "Print Dialog Header/Footer Tab" on page 150.
- To create dynamic SQL statements, include dynamic text labels in your SQL filter clauses as values.

Dynamic Text Tag	Default Tag	Description
Cell Reference	< <cell 0,0="">&gt;</cell>	Inserts a cell reference string in the label object.
Filter	< <filter 0="">&gt;</filter>	Inserts the filter member name in the label object.

After dynamic text labels are entered, you can edit the tag to display additional information.

#### **Dynamic Text Labels for SQL Spreadsheets**

Dynamic Text Labels are used primarily in custom report label objects and in the Headers/ Footers tab.

Two dynamic text labels are supported with SQL Spreadsheets: filter and Cell of the print dialog box. Because SQL spreadsheet objects cannot be selected on Web Analysis documents as on standard OLAP spreadsheets, charts, and pinboard, filter and cell functions must use fixed references to their data source. For example, the filter function must contain ReportSQLDataSrc, which is selected when a SQL subscription control is defined:

```
<<filter ReportSQLDataSrc1, 0>
```

A reference without a data-source specification (for example, <<filter 0>>) does not function with SQL spreadsheets.

#### **Cell Functions**

Cell functions insert cell reference strings in label objects. The fixed reference format for the function is:

```
<<cell SQLDataSourceName1, row, column>>
```

#### Where

row is the numerical row reference on the spreadsheet and column is the numerical column reference on the spreadsheet

#### **Filter Functions**

Filter functions insert filter member names in label objects. The fixed reference format for the function is:

```
<<filter SOLDataSourceName1,n>>
```

#### Where

*n* is the filter number in the order that is displayed in the SQL WHERE clause:

```
SELECT MONTH, PRODUCT, CITY, SALES, COGS FROM DETAILS WHERE PRODUCT =
'100-10' AND MONTH = 'Aug'
<<filter ReportSQLDataSrc1, 0>> returns 100-10
<<filter ReportSOLDataSrc1, 1>> returns Aug
```

## **Creating a SQL Subscription Control**

- To create a SQL subscription control for a SQL Spreadsheet:
- 1 Start Web Analysis Studio.

You must open a document containing a SQL Spreadsheet or create a SQL spreadsheet after entering Document Designer.

#### Select File , then New, then Document.

The Document Designer is displayed.

- 3 Drag the **SQL Subscription Object** icon from the component toolbar to a document panel.
- Select the SQL spreadsheet data source for the subscription object.

The Select Column dialog box is displayed, prompting the user to select a column from the relational data source. The members of this column populate the drop-down list of the control.

Select the asterisk character (\*) to return all column members.

Select the relational data source column, and click **OK**.

The SQL Subscription Control is displayed on the document panel. The control functionality takes effect when you return to Analyze mode.

# **15**

# Creating Freeform Grids

#### **In This Chapter**

Freeform Grids	205
Creating Freeform Grids	206
Formatting Freeform Grids	208
Creating Formulas for Freeform Grids	209
Controlling Freeform Grid Content with Data Objects	211

#### **Freeform Grids**

Freeform grids present OLAP, relational, and manually entered data on one data object, and enable you to leverage these data sources in integrated dynamic calculations.

Freeform grids are comprised of only rows and columns. There is no visual representation of page dimensions participating in cell intersections. You can still use OLAP database connections with dimension members assigned to the Page axis, but you cannot navigate through these page dimensions unless you create additional subscription controls. In short, only the first page of a multidimensional cube is displayed.

#### Freeform Grid prerequisites:

- Freeform Grids can only be created on a custom document.
- You must understand how to compose a SQL query to access relational data sources.
- You must be able to connect to a relational data source using supported JDBC drivers.

There are four alternatives for accessing relational data in Web Analysis Studio:

- You can create a relational database connection to be used by regular spreadsheets, charts, and pinboards. See "Creating Relational Database Connections" on page 181.
- SQL Spreadsheet data objects enable you to query a relational data source, and display the
  returned data values on a custom document. See "Creating SQL Spreadsheets" on page
  196.
- You can create a relational drill-through connection from an OLAP database connection to a relational data source. See "Creating Relational Drill-Through" on page 163.
- You can leverage predefined Integration Services drill-through connections using the Related Content dialog box. See "Integration Services Drill-Through" on page 246.

To create freeform grids you are required to specify:

- The data sources providing data values
- The Freeform Grid data object that displays these values
- The queries retrieving data values.

The process of creating freeform grids assumes that you know your data sources and logon credentials. Freeform grid querying methods are not unique; you can use the database connections established for other data objects.

## **Creating Freeform Grids**

- To create a freeform grid:
- Start Web Analysis Studio.
- Perform one:
  - Select File, then New, then Document.
  - Click 🔛
  - Click , and select Document.
  - In the View Pane Browser tab, right-click a document and select Edit.
  - Press Ctrl+N.

The Document Designer is displayed.

Drag the Freeform Grid icon from the component toolbar to a document panel.

An empty freeform grid and the Set Grid Size dialog box are displayed. Note that the grid can consists of only row and column axes.

- Enter the number of rows in Number of Rows.
- Enter the number of columns in **Number of Columns**.
- Click OK.

The grid is reset to the indicated number of rows and columns.

Optional: To move the freeform grid object, click and drag the component with the Move cursor to another location on the document panel.

The conventional cursor is transformed into the Move cursor when it is floated over a selected component. Be careful not to drag over a blue selection handle, as this resizes the component instead of moving it.

- Optional: To resize the freeform grid object, click and drag the blue selection handles on the sides and corners of the selected grid component.
- Optional: To anchor the freeform grid object to document panel borders, right-click the component and select Anchor, and an anchor option: Top, Bottom, Left, Right, Slack, None.

The Anchor property orients selected components to an edge of the panel containing them. Using Slack, you can realign objects to occupy empty space. It is best to design documents in terms of container panels and orient components relative to these panels. Components that are placed with an absolute alignment in the context of the main document panel, maintain their position even as other components fluctuate. This may cause the overlapping and shifting of components.

#### 10 When the custom document is laid out correctly, click Analyze.

The remaining customization is done in the Analyze interface.

Data sources are anchored at cells in a freeform grid. This is done by selecting a cell and composing a query.

#### 11 To specify an OLAP or Oracle | Hyperion data source, perform these tasks:

a. Right-click a cell and select Add Data Source.

The Select Data Source dialog box is displayed.

- b. You can select a database connection, or select < Add Data Source > to define a database connection, and click OK.
  - i. If you selected < Add Data Source >, the Open dialog box is displayed. Select a database connection, and click OK. The Data Layout dialog box is displayed, so that you can create a query for the selected cell. Assign dimensions to axes, make members selections, and click OK.
    - Note that you cannot page dimension member selections assigned to the Pages axis, unless you create a subscription control using a matching data source and page dimensions.
  - ii. If you selected a database connection, the cell is populated based on the selected database connection.

#### 12 To specify a relational data source:

- a. Right-click a cell and select Add SQL Query.
  - The Enter SQL Query dialog box is displayed.
- b. Enter the JDBC connection information, log on credentials, query governor parameters and SQL statement, and click **OK**. See "Creating SQL Spreadsheets" on page 196.
  - The query is submitted to the corresponding data source, and the result set origin is displayed at the origin of the selection set.
- 13 To manually enter data values in the freeform grid, click a cell and enter text.

See "Formatting Freeform Grids" on page 208 and "Creating Formulas for Freeform Grids" on page 209.

### **Formatting Freeform Grids**

You cannot format freeform grids. They inherit formatting definitions from the database connections that they use. You can, however, show and hide numerous aspects of the freeform grid data object:

- To show or hide a freeform grid component, right-click the freeform grid and select one:
- Show/Hide Formula Bar.
- Show/Hide Headers
- Show/Hide Horizontal Gridlines
- Show/Hide Vertical Gridlines
- To insert a row or column in a freeform grid, right-click the freeform grid and select **Insert** Row or Insert Column.
- To remove a row in a freeform grid, right-click the freeform grid and select Remove Row or Remove Column.
- To resize row height or column width:
- In Analyze mode, float the cursor between two header cells until the cursor changes to the Resize cursor.
- 2 Drag column borders left or right, and drag row borders up and down.
- When the column or row is sized correctly, release your mouse.
- To hide a column or a row, size the header down to 0 pixels.

Note: Conversely, if you encounter missing columns or rows, you should assume that the header is sized down to 0 pixels to hide the content of that column or row.

- To insert multiple rows and columns in a freeform grid:
- Click to return to **Document Designer**.
- Right-click the grid and select Properties.

The Set Grid Size dialog box is displayed.

Enter a number of rows and columns, and click **OK**.

The grid is reset to the indicated number of rows and columns.

Click to return to Analyze mode.

### **Creating Formulas for Freeform Grids**

Freeform grids leverage diverse data sources in integrated dynamic calculations. Cell references use syntax that matches those supported by Microsoft Excel, where the column letter and the row number indicate the cell address.

Example: =SUM(B8:C8) adds the data values from the cell on the eighth row of the B column to the eighth row of the C column.

Note: Formula cell addresses are absolute. They do not dynamically change themselves to accommodate the displacement caused by adding or removing rows or columns. As a result, you should not compose freeform grid formulas until you are finished with all other grid formatting.

You can enter these functions in cells or the Formula bar.

- OPERATOR\_ADD=+
- OPERATOR\_SUBSTRACT=-
- OPERATOR DIVIDE=/
- OPERATOR\_MULTIPLY=\*
- OPERATOR\_POWER=^
- OPERATOR\_EQUAL==
- OPERATOR\_DIFFERENT=<>
- OPERATOR\_GREATER\_OR\_EQUAL=>=
- OPERATOR\_LESS\_OR\_EQUAL=<=
- OPERATOR\_GREATER=>
- OPERATOR\_LESS=<
- CONDITION IF=IF
- CONDITION\_THEN=THEN
- CONDITION\_ELSE=ELSE
- FUNCTION\_LN=LN
- FUNCTION\_LOG=LOG10
- FUNCTION\_EXP=EXP
- FUNCTION\_SQRT=ROOT
- FUNCTION\_COS=COS
- FUNCTION\_SIN=SIN
- FUNCTION\_TAN=TAN
- FUNCTION\_ACOS=ACOS
- FUNCTION\_ASIN=ASIN

- FUNCTION\_ATAN=ATAN
- FUNCTION\_COSH=COSH
- FUNCTION\_SINH=SINH
- FUNCTION\_TANH=TANH
- FUNCTION\_INTEGER=INT
- FUNCTION ABS=ABS
- FUNCTION\_NOT=NOT
- JEKS\_FUNCTION\_SUM=SUM
- JEKS\_FUNCTION\_RAND=RAND
- JEKS\_FUNCTION\_MODULO=MOD
- JEKS\_FUNCTION\_FACT=FACT
- JEKS\_FUNCTION\_IF=IF
- JEKS\_FUNCTION\_AND=AND
- JEKS\_FUNCTION\_OR=OR
- JEKS\_FUNCTION\_TRUE=TRUE
- JEKS\_FUNCTION\_FALSE=FALSE
- JEKS\_FUNCTION\_DATE=DATE
- JEKS\_FUNCTION\_DATEVALUE=DATEVALUE
- JEKS\_FUNCTION\_NOW=NOW
- JEKS\_FUNCTION\_TIME=TIME
- JEKS\_FUNCTION\_TIMEVALUE=TIMEVALUE
- JEKS\_FUNCTION\_YEAR=YEAR
- JEKS\_FUNCTION\_MONTH=MONTH
- JEKS\_FUNCTION\_DAY=DAY
- JEKS\_FUNCTION\_WEEKDAY=WEEKDAY
- JEKS\_FUNCTION\_HOUR=HOUR
- JEKS\_FUNCTION\_MINUTE=MINUTE
- JEKS\_FUNCTION\_SECOND=SECOND
- JEKS\_FUNCTION\_CHAR=CHAR
- JEKS\_FUNCTION\_FIND=FIND
- JEKS\_FUNCTION\_CODE=CODE

These conditional operators are also supported:

- IF
- THEN

## **Controlling Freeform Grid Content with Data Objects**

Due to the variety of data sources available, freeform grids do not offer the navigation methods and Analysis Tools available to other data objects. Instead of navigating directly on the freeform grid, you may use another data object that shares the data source to control grid content.

Because the freeform grid shows only the first Page dimension, you can use other custom document components (such as subscription controls) to navigate through Page axis dimension members.

To control freeform grid content using another data object, you must perform these steps:

- 1. Create a custom document with a freeform grid.
- 2. Switch to Analyze mode, right-click and add a data source to the grid.
- 3. Return to Document Designer, and add another data object to the custom document.
- The second data object must use the data source used by the freeform grid.
- Switch to Analyze mode again.

At this point, you have a custom document with a freeform grid and another data object, both of which use a common database connection. You can now apply client-side formatting and analysis tools definitions to the data object. Because the freeform grid's database connection and query match those used by the data object, it reflects all changes to the data object. When you are done formatting the content, you have three options:

- You can leave the data object on the document, as a control.
- You can delete the data object. The grid maintains its state based on the database connection and query, but you cannot revise the grid.
- You can hide the data object by sizing it down, or obscuring it behind another component (send to back). Later, if you revise the grid, you can use the data object control again.

**Note:** Formula cell addresses are absolute. They do not dynamically change themselves to accommodate the displacement caused by navigation from a second data object sharing one database connection. Changing the content of a freeform grid, may render formulas obsolete.

- To control freeform grid content using another data object:
- Start Web Analysis Studio.
- Perform one:
  - Select File, then New, then Document.
  - Click 🔀
  - Click , and select Document.

- In the View Pane Browser tab, right-click a document and select Edit.
- Press Ctrl+N.

The Document Designer is displayed.

Drag the Freeform Grid icon from the component toolbar to a document panel.

An empty freeform grid and the Set Grid Size dialog box are displayed. Note that the grid can consists of only row and column axes.

Enter the number of rows and columns in the corresponding text area, and click **OK**.

The grid is reset to the indicated number of rows and columns. Note that the freeform grid is selected, and displays blue selection handles.

Click .

Data sources are anchored at cells in a freeform grid. This is done by selecting a cell and composing a query.

To specify an OLAP or Oracle | Hyperion data source, right-click a cell and select Add Data Source.

The Select Data Source dialog box is displayed. You can select a database connection, or select < Add Data Source > to select another database connection. When you are done the query is submitted and the result set is displayed in the freeform grid. It is important to note the name of the data source displayed at the result set origin.

- Click 🔀 7
- Drag the **Spreadsheet** icon from the component toolbar to the document panel.

The Data Object Properties dialog box is displayed.

Select the data source used by the freeform grid for this data object, and click **OK**.

This is the data source displayed at the result set origin on the freeform grid.

10 Click

Your custom document contains a freeform grid and another data object, both of which use a common database connection. You can now apply client-side formatting and analysis tools definitions to the data object. Because the freeform grid's database connection and query matches those used by the data object, it reflects all changes to the data object.

# **Creating Custom Documents**

#### **In This Chapter**

Comparing Web Analysis Studio and EPM Workspace	213
Document Designer	215
Custom Document Components	217
Formatting Components	220
Creating Hotspots	225
Creating Split Panels	225
Linking Components by Query	226
Linking Selected Dimensions	227
Creating Subscription Controls	228
Creating Selection Buttons	231
Creating Dynamic Text Labels	
Custom Document Components	236

### **Comparing Web Analysis Studio and EPM Workspace**

Web Analysis Studio is a Java applet that enables you to create, analyze, present, and report multidimensional content. The studio offers the complete Web Analysis feature set to designers creating content (including dashboards).

EPM Workspace is a DHTML based, zero-footprint client that provides a user interface for viewing and interacting with content created by authoring studios and enables users to create queries against relational and multidimensional data sources. It is engineered for information consumers who do not require advanced design and content-creation capabilities.

#### **Differences between the Two Clients**

- The scrolling feature on charts is not available in EPM Workspace.
- Because Java fonts and HTML fonts are not one-to-one equivalent, font styles and sizes may differ.
- Label Text and Text Area static placement may not be observed and it is recommended that you use the anchoring feature as much as possible.
- EPM Workspace does not render these designer components:
  - Tab selection controls

- Slider selection controls
- Splitter panels

Note: Splitter panel render in HTML as a two pane panel, however splitter bar and One-Touch Expandable functionality not render in HTML.

- These Service Buttons do not function in EPM Workspace:
  - Assign Edit Data
  - Close Report
  - Data Layout
  - Desktop
  - File Open
  - Home
  - Launch Executable
  - Logout
  - Print
  - Save As
  - Send to Clipboard
  - Send to Excel
  - Toggle Info Panel
  - Toggle Masthead
  - Toggle Menu
  - Toggle Status Bar
  - Toggle Toolbar
  - User Preferences

### Font List Differences Between Web Analysis Studio and EPM **Workspace**

Font availability dependencies in Web Analysis Studio and EPM Workspace:

- Web Analysis Studio—Font list is generated from client machine installed fonts
- EPM Workspace—Font list is generated from Web Analysis server machine installed fonts

Note: If a document is created in Web Analysis Studio that uses a font that is installed only on the client machine and is not installed on the Web Analysis server, EPM Workspace users cannot see that font.

## **Document Designer**

The Document Designer creates custom documents. When in Document Designer, the process bar displays the Design label, and a component toolbar is displayed below the menu bar. Document Designer access is controlled cumulatively by user and group roles.

#### **Accessing Document Designer**

You can create custom documents from scratch, the current document, or from document that you can access.

- ➤ To initiate Document Designer:
- Select File, then New, then Document.
- In Analyze, click , and select Document.
- In Analyze, click
- Press Ctrl+N.
- Press F12.
- To initiate Document Designer for the current document in Analyze, click **Switch to Document Designer**.
- To open document in Document Designer, perform these actions:
- 1 Select View, then View Pane, or press F6.

The View Pane is displayed.

- 2 Click the Repository tab.
- 3 Navigate to the document to edit in Document Designer.
- 4 Right-click the document name, and select Edit.

The document is opened in Document Designer, and assigned default object properties. For a description of default object properties, See "Formatting Components" on page 220.

#### **Setting Document Designer Options**

Before designing custom documents, set these options:

- To show or hide the Document Designer point grid on the master panel, select View, then Grid Toggle.
- To set the color for the Document Designer grid points on the master panel:
- Select View, then Grid Color.

The Select Color dialog box is displayed.

Select a color from the Swatches tab, and click OK.

For a complete description of color options, See "Selecting Color" on page 110.

- To set a background image for the Document Designer master panel:
- Select View, then Load Image.

The Select Graphic dialog box is displayed. You can select a color to fill the panel, or a graphic background for the panel (using Load). The Style group box controls image placement inside the master panel. Clear resets the panel to the default grey background.

- Select one Style option:
  - Center—Centers the image horizontally on the master panel.
  - Stretch—Stretches the image to the height and width of the master panel.
  - Tile—Repeats the image across the master panel until the area is covered.
  - Top-Left—Anchors the image in the top left corner of the master panel.
- Click Load.

The Open dialog box is displayed.

- Navigate to a network location and select a JPG or GIF file.
- 5 Click Open.

The image is displayed on the master panel as specified by the Style option.

#### **Design for HTML**

When creating custom Web Analysis documents, you can restrict objects and functionality that do not appear in the EPM Workspace rendering of Web Analysis documents. Incompatible controls such as Tab Control and Slider Bar, and some Service Buttons, are disabled and not available to add to a Web Analysis document.

- To create Web Analysis documents for EPM Workspace HTML rendering:
- 1 From the main menu, select Edit, then Design for HTML.
- Select Design for HTML option and click OK.

Note: Incompatible EPM Workspace objects are not enabled ("Comparing Web Analysis Studio and EPM Workspace" on page 213 for a list of incompatible objects).

If objects are overlayed (For Example, a Text Label placed on top of a Spreadsheet), the overlaying objects that do not render in HTML and are highlighted with a (red) border.

**Note:** If incompatible controls are added when this mode is deselected, "Design for HTML mode" is enabled and the control is highlighted with a (red) border

#### **Accessing the Palette Tab**

The Palette tab is one of three View Pane tabs.

It lists custom document components as a node tree. You can expand, collapse, and explore the node tree to identify components by name, understand how they are nested, and display component properties.

To display a node tree of custom document components, select View, then View Pane (or press **F6**), and click

## **Custom Document Components**

Web Analysis Studio provides an inventory of coding-free components for custom documents. Twenty-one components can be added to custom documents multiple times, and customized using various options. This provides numerous creative opportunities for custom document designers:

#### **Containers**

The Panel Object and Split Panel Object control space and layers on custom documents. Design documents using container panels and orient components inside these panels.

#### **Content Panels**

There are four additional panels that provide specialized content:

- Label Object—contains static or dynamic text for titles, labels, or captions.
- Text Area Object—uses dynamic text to annotate documents.
- Image Objects—contains graphics for backgrounds, pictures, illustrations, and graphic controls.
- HTML Browser Object—displays static HTML.

These panels function without additional coding. The label object supports the dynamic text labels used in Printing headers and footers, and SQL spreadsheets.

#### **Four Data Objects**

Data objects representing four display types are next on the component toolbar:

- Chart—displays the query result set as a chart.
- **Spreadsheet**—displays the query result set as a spreadsheet.
- Freeform Grid—displays content from multiple data sources in one spreadsheet.

Pinboard—displays the query result set as a pinboard.

The SQL Spreadsheet data object is in the last segment of the component toolbar. See also Chapter 15, "Creating Freeform Grids."

#### **Subscription Controls**

A variety of controls enable you to navigate dimensional hierarchies, browse documents, and execute commands:

- Combo Box Subscription—displays a member drop-down list.
- Radio Button Group Subscription—enables you to select one dimension member option from a series.
- Check Box Group Subscription—enables you to select multiple dimension members.
- Tab Group Subscription—enables you to select one dimension member tab from a series.
- Multi-level Combo Box Subscription—enables you to select from interdependent dropdown lists, whose members change based on previous selections.
- Slider Subscription—enables you to select one dimension member from a series.
- Selection Button Subscription—displays a control that applies dimension member selections to data objects using a matching data source.
- Alias Controller Object—enables you to toggle the data object between alias table labels.
- Services Button Object—executes a command. Also used to create hotspots.

All subscription buttons can control data objects that share a common database connection query.

#### **SQL Spreadsheet and SQL Subscription**

Two components present and control SQL query result sets:

- SQL Spreadsheet Objects—displays a SQL query from a relational data source.
- SQL Subscription Objects—displays a relational subscription button.

See Chapter 14, "Creating SQL Spreadsheets."

#### **Creating Container Panels**

Design custom documents using container panels. As they are added to panels, components are anchored to one panel edge. Using Slack alignment, you can realign objects to occupy all empty space.

Components placed with absolute alignment in the main document panel maintain their position as other components fluctuate. This may cause overlapping and shifting components. To prevent this, subdivide custom document space using panels, and anchor these panels to the master panel. Subsequently added components in container panels maintain their arrangement.

#### **Adding Custom Document Components**

To add custom document components to a document, drag them from the component toolbar to a document panel.

#### **Undo and Redo**

The Undo command reverses the effect of the previous command, returning the display to its prior state. The Redo command reverses Undo, and reinstates the command executed before Undo. Document Designer records the last ten design actions in a series, and enables you to select multiple commands to undo or redo.

To undo or redo multiple commands, select them from the Undo and Redo drop-down lists.

# **Selecting Components**

To make a component current, click it. The current component is outlined in blue.

## **Selecting Multiple Components**

- To select multiple components:
- Hold Ctrl while clicking the components.
- Click and drag a box around multiple components.

#### **Sizing Components**

To size a selected component, drag the blue selection handles on the corners and edges of the selection outline.

## **Moving Components**

To move selected component, drag the component with the Move cursor,  $\updownarrow$ , to another location.

The conventional cursor is transformed into the Move cursor when it is floated over a selected component. Be careful not to drag over a blue selection handle, as this resizes the component instead of moving it.

## **Cutting, Copying, Pasting, and Deleting Components**

To edit custom documents, right-click a selected custom document component, and select Edit, then Cut, Copy, Paste, or Delete from the shortcut menu.

You can also select a component by clicking it and using these hot keys:

- Undo-Ctrl+Z
- Redo—Ctrl+Y
- Cut—Ctrl+X
- Copy—Ctrl+C
- Paste—Ctrl+V
- Delete—Press Delete.

## **Formatting Components**

Components feature a shortcut menu, the primary means of formatting and editing. All menus are identical with the exception of component-specific Custom Settings commands:

Command	Submenu	Description	
Bring to Front		Brings the selected object to the top and front when objects are layered.	
Send to Back		Sends the selected object to the bottom and back when objects are layered.	
Edit			
	Cut	Removes the selected object to the clipboard.	
	Сору	Saves the selected object to the clipboard.	
	Paste	Pastes content from the clipboard into the selected object.	
	Delete	Deletes the selected component.	
Opaque		Makes the selected object opaque when selected, or transparent when deselected.	

Command	Submenu	Description
Border		
	Etched	Sets object borders to an etched style.
	Line	Sets object borders to a solid line.
	Lowered Bevel	Sets object borders to a lowered bevel style.
	Raised Bevel	Sets object borders to a raised bevel style.
	None	Removes object borders.
	Set Border Color	Sets line border color.
	Set Border Size	Sets the (interior) component line border width in pixels. Zero (0) means no border.
Anchor		
	Тор	Affixes objects to the top edge of the panel.
	Bottom	Affixes objects to the bottom edge of the panel.
	Left	Affixes objects to the left edge of the panel.
	Right	Affixes objects to the right edge of the panel.
	Slack	Sizes the component to fill unused space.
	None	Positions the component, using the underlying pixel grid.
Align		
	Top Edges	Aligns the top edge of all selected components. Moves all selected components vertically to the current position of the top edge of the top object.
	Vertical Centers	Aligns the center point of all selected components. Center in this case is the vertical center (left and right edges of components). Moves all selected components vertically to a median determined using the top edge of the top component and the bottom edge of the bottom component.
	Bottom Edges	Aligns the bottom edges of all selected components. Moves all selected components vertically to the current position of the bottom edge of the bottom object.
	Left Edges	Aligns the left edge of all selected components. Moves selected components horizontally to the current position of the left edge of the left object.
	Horizontal Centers	Aligns the center point of all selected components. Center in this case is the horizontal center (top and bottom edges of components). Moves all selected components horizontally to a median determined using the left edge of the left component and the right edge of the right component.
	Right Edges	Aligns the right edge of all selected components. Moves all selected components horizontally to the current position of the right edge of the right object.
Distribute		
	Top Edges	Evenly spaces the top edge of three or more components vertically.

Command	Submenu	Description	
	Vertical Centers	Evenly spaces the center point of three or more components. Center in this case is the vertical center (left and right edges of components). Moves all selected components vertically to a median determined using the top edge of the top component and the bottom edge of the bottom component.	
	Bottom Edges	Evenly spaces the bottom edge of three or more components vertically.	
	Left Edges	Evenly spaces the left edge of three or more components horizontally.	
	Horizontal Centers	Evenly spaces the center point of three or more components. Center in this case is the horizontal center (top and bottom edges of components). Moves all selected components horizontally to a median determined using the left edge of the left component and the right edge of the right component.	
	Right Edges	Evenly spaces the right edge of three or more components horizontally.	
Custom Settings		Displays additional component-specific commands. Options are described in component profiles.	
Font Properties		Displays the Font Properties dialog box to format caption fonts.	
Properties		Displays the component-specific property dialog box, or a series of dialog boxes.	

## **Default Object Properties**

Default properties are assigned to documents imported into Document Designer:

Property	Default	Implications	
Opaque	Enabled	The object obscures other objects behind it.	
Border	Etched	All objects feature a default border.	
Anchor	Slack	Change the alignment property, if you intend to resize the data object.	
Data Object Properties	Data Source	Be aware that all objects using one data source are coordinated. Navigation in object affects all objects using one data source.	
	Display Type	e To change display type, select Properties from the shortcut menu.	

# **Setting the Background**

To create a uniform background for the custom document, you must create a panel object, and anchor the panel to fill all slack space. You can set the background to a color or arrangement of images. Every custom document begins with a master panel. See "Setting Document Designer Options" on page 215.

- To set a background image for a panel:
- Right-click a panel, and select Properties.

The Select Graphic dialog box is displayed. You can select a background color, or a graphic background for the panel (using Load). The Style group box controls image placement. Clear resets the panel to the default grey background.

#### Select one Style option:

- Center—Centers the image horizontally on the master panel.
- Stretch—Stretches the image to the height and width of the master panel.
- Tile—Repeats the image across the master panel until the area is covered.
- Top-Left—Anchors the image in the top left corner of the master panel.

#### Click Load.

The Open dialog box is displayed.

- Navigate to a network location containing graphic JPG or GIF files, and select a file.
- Click Open.

The image is displayed on the master panel as specified by the Style option.

#### **Aligning Components**

Components are positioned relative to the panel containing them. Document designers edit relative component positioning and spacing using alignment controls.

To align components, right-click the component and select a shortcut menu option.

#### **Anchor Options**

The Anchor property orients selected components to an edge of the panel containing them. Using Slack alignment, you can realign objects to occupy empty space.

Design documents using container panels and orient components inside these panels. Components placed with absolute alignment in the main document panel maintain their position as other components fluctuate. This may cause overlapping and shifting components.

#### **Relative Alignment**

Anchored components can also be positioned relative to other components. For example, selection buttons anchored to the left edge of the panel may nevertheless be unevenly spaced.

Align and Distribute controls position components and space components relative to edges or center points.

#### **Spacing Options**

Spacing components using the Distribution feature does account for object size or space between objects, only for space between edges or center points.

Spacing between object sizes that differ may vary, even when an edge of three or more components is evenly spaced.

# **Alignment Options**

Shortcut Command	Description	
Anchor		
Тор	Affixes objects to the top edge of the panel.	
Bottom	Affixes objects to the bottom edge of the panel.	
Left	Affixes objects to the left edge of the panel.	
Right	Affixes objects to the right edge of the panel.	
Slack	Sizes the component to fill unused space.	
None	Positions the component, using the underlying pixel grid.	
Align		
Top Edges	Aligns the top edge of all selected components. Moves all selected components vertically to the current position of the top edge of the top object.	
Vertical Centers	Aligns the center point of all selected components. Center in this case is the vertical center, evenly spaced from the left and right edges of components. Moves all selected components vertically to a median determined us the center of the top component and the center of the bottom component.	
Bottom Edges	Aligns the bottom edge of all selected components. Moves all selected components vertically to the current position of the bottom edge of the bottom object.	
Left Edges	Aligns the left edge of all selected components. Moves all selected components horizontally to the current position of the left edge of the left object.	
Horizontal Centers	Aligns the center point of all selected components. Center in this case is the horizontal center, evenly spaced from the top and bottom edges of components. Moves all selected components horizontally to a median determined using the center of the left component and the center of the farthest right component.	
Right Edges	Aligns the right edge of all selected components. Moves all selected components horizontally to the current position of the right edge of the farthest right object.	
Distribute		
Top Edges	Evenly spaces the top edge of three or more components vertically.	
Vertical Centers	Evenly spaces the center point of three or more components. Center in this case is the vertical center, evenly spaced from the left and right edges of components. Moves all selected components vertically to a median determined using the center of the top component and the center of the bottom component.	
Bottom Edges	Evenly spaces the bottom edge of three or more components vertically.	
Left Edges	Evenly spaces the left edge of three or more components horizontally.	

Shortcut Command	Description
Horizontal Centers	Evenly spaces the center point of three or more components. Center in this case is the horizontal center, evenly spaced from the top and bottom edges of components. Moves all selected components horizontally to a median determined using the center of the farthest left component and the center of the farthest right component.
Right Edges	Evenly spaces the right edge of three or more components horizontally.

# **Creating Hotspots**

- To create a hotspot:
- 1 Drag a Services button from the component toolbar to the document panel.

The Service Properties dialog box is displayed.

2 Select a service type from the Select Service Type list.

The Service button features a gray color and border and an opaque text label by default.

- 3 If you do not want a text label, delete the default label text.
- 4 To indicate a border color, click the Color button.

The Select Color dialog box is displayed, enabling the selection of a color for the button and the border.

5 Click **OK** to return to the Service Properties dialog box.

The button and the border displays the selected color. If you want transparent hotspots with colored borders, you must finish creating the service button, and disable the opaque property on the service button shortcut menu.

6 Click OK.

The Service button can be sized and located, for component.

**Note:** Use the Bring to Front shortcut menu command to locate hotspots on other objects.

# **Creating Split Panels**

- To create a split panel (a panel with a movable splitter bar):
- 1 In Document Designer, drag a Split Panel object from the component toolbar onto the content area.

The Split Panel Properties dialog box is displayed.

- Select a horizontal or vertical splitter bar from the Orientation radio button group.
- 3 Optional: In the Sizing group, select One-Touch Expandable to add controls to the splitter bar.

The Splitter bar is the slider that divides the split panel. When the One-Touch Expandable option is selected, two arrow controls move the splitter bar in opposing directions with one click.

Optional: In the Background Images group, click Left/Right or Top/Bottom, to display the Select Graphic dialog box for that half of the Split Panel.

You can set a color for the specified half of the split panel, or load a background image in it. See "Selecting Graphics" on page 111.

Click OK.

#### **Nesting Split Panels**

By dragging a Split Panel object onto another Split Panel object, you can nest split panels inside one another. This enables you to use horizontal and vertical splitter bars simultaneously.

#### **Retrieving Focus From Slack Space Split Panels**

Focus must be removed from the split panel before the slider bar can be adjusted. When the split panel alignment is set to Slack Space, the split panel controls the document, and you cannot click outside the split panel. In this case, click the Splitter bar until the Split panel is deselected.

## **Linking Components by Query**

To create a document you are required to specify:

- Data source—Provides data values
- Data object—Displays these values
- Query—Gets data values from the data source and returns them to the data object.

To set properties customizing these elements:

- Database Connection Properties indicate the type of data source, logon credentials, database applications, dimension formatting and drill-through properties.
- Each data object can be set to a display types that features formatting options.
- Queries can be explicit, requesting information on dimension members, or dynamic, requesting information about dimension member that satisfies a set of criteria.

In Document Designer, the query definition is referred to as the data source.

#### **Common Data Sources**

Components using one data source are coordinated. Component navigation requires all components using one data source to follow common lines of navigation.

To link dimension in data objects in one document, use Custom Settings. See "Linking Selected Dimensions" on page 227.

#### **Unlinking Components**

If you do not want coordinated components, assign another data source to an object. Identical data sources with names that differ are treated separately.

## **Linking Selected Dimensions**

Use Custom Settings to link dimensions in data objects in one document.

Dimensional linking enables data objects sharing dimensions to remain coordinated regardless of data source. Links are unidirectional; navigation on a data object triggers coordinated navigation on other data objects linked to it. Data objects without defined links do not mutually trigger navigation.

To locate data object custom settings, enter Document Designer and right click a data object.

Data Object Custom Settings	Description	
Add/Show Data Source Link	Places the data objects in the current document into Data Source Link mode.	
Remove Data Source Link	Deletes all data source links in the selected data object.	

- To link selected dimensions of data objects in one document:
- 1 Enter Document Designer.
- Right-click the data object from which links are to be driven.

Links are unidirectional. Bidimensional and multidimensional links must be created by repeating this procedure on each data object. Components using one data source are also coordinated, but these links are not dimension-specific.

Select Custom Settings, then Add/Show Data Source Link.

The data object borders are red, green or black.

- Red borders—Indicate the data objects share a data source.
- Green borders—Indicate the data objects available for dimensional linking.
- Black borders—Indicate the data objects with previously defined links.

Black-bordered objects cannot be used to define links. You must remove the link definitions before defining link definitions.

Red-bordered objects share a data source. All dimensions are coordinated.

Click a green-bordered object.

The Select Dimensions dialog box is displayed.

Click a check box to select a dimension.

You can select multiple dimensions.

6 Click OK.

> You are returned to Document Designer. You must return to Analyze before demonstrating linking behavior.

## **Creating Subscription Controls**

You can create five controls using one procedure:

- Combo Box Subscription
- Radio Button Group Subscription
- **Check Box Group Subscription**
- **Tab Group Subscription**
- Slider Subscription

There are alternative procedures for customizing:

- Multi-level Combo Box Subscription
- Selection Button Subscription
- **SQL Subscription Objects**

There is also a procedure for making subscription controls dependent on other subscription controls.

#### **Subscription Control Dialog Sequence**

After creating a control, an automated dialog sequence helps you set properties:

- The Select Data Source prompts you to relate the control to a data source (query).
- The Select Dimension dialog box prompts you to select a dimension from the query.
- The Select Member dialog box prompts you to specify members and formatting options.

#### **Creating Subscription Controls**

- To create subscription controls:
- Drag a Subscription control object from the component toolbar to the content area of the custom document.

The Select Data Source dialog box is displayed.

Click to select a data source.

The Make Dependent option makes the subscription controls dependent on other controls sharing this data source. See "Creating Dependent Subscription Controls" on page 231.

#### Click OK.

The Select Dimension dialog box is displayed.

#### Select a dimension name, and click OK.

The Select Member dialog box is displayed.

#### Click Add.

The Dimension Browser for the selected dimension is displayed.

#### Make member selections, and click **OK**.

Selected members display in the Select Member dialog box. You can also select font properties, color properties, and rename the dimension member labels. The first dimension member in the panel is used as the button label, so it is often helpful to rename the member to a more descriptive label.

These optional subscription control procedures are also available:

- **Ordering Dimension Member Controls**
- **Indenting Dimension Member Controls**
- **Changing Data Sources**
- Creating Dynamic Dimension Member Controls
- **Creating Dependent Subscription Controls**

#### 7 Click OK.

The dimension member control is displayed on the custom document.

#### **Ordering Dimension Member Controls**

To reorder member controls, select a member name and use the arrow buttons to move the member in the index order. The order of members is reflected in the custom document when you Click OK.

## **Indenting Dimension Member Controls**

When creating check box and radio button group subscription controls, you can indent dimension member controls a number of pixels based on each members level from the top of the dimension hierarchy.

To indent dimension member controls, open Select Members and select Indent Members.

#### **Saving Subscription Control Selections to User POVs**

User POVs enable users to select members in Filters, Pages, Rows, and Columns (Data Layout and/or member selection controls) and apply them to multiple Web Analysis documents.

All Subscription controls have "Save Selection as User POV" option. When a selection is made on the control, it is automatically saved to the User POV as a filter. If the Subscription control points to multiple ReportDataSrcs, all of the underlying Database Connections have their User points of view set for the dimension that the control applies to.

In order for a Web Analysis document to utilize the User POV selection, the option "Use User POV" must be enabled in the Data Layout / Options dialog.

## **Enabling a Subscription Control to "Activate from Service Button**"

This feature allows for Subscription Control member selections to be made, and performs a data retrieval by clicking the Service Button. Users can make multiple Subscription Control selections without retrieving data for each selection. Subscription Control's Properties / Select Members dialog has a option to "Activate From Service Button". A Service Button for "Apply Subscriptions" must be added to the Web Analysis document to perform data retrieval after making Subscription Control selections.

#### **Changing Data Sources**

To change the data source for a dimension member control, click Relink.

The Select Data Source dialog box is displayed.

## **Creating Dynamic Dimension Member Controls**

You can define dimension member controls using an explicit selection or advanced member selection, and use advanced member selections to populate the control. Using advanced member selection to populate a control makes the control dynamic. As members are added deleted and changed in the database, the control maintains itself and does not become obsolete.

For example, you can create a Product dimension member control. You can make a children of Product dimension member control, and you can make a control that displays the Children of Product, whatever they are.

To create a dynamic dimension member control, select **Dynamic** in **Member**. Dynamic dimension members must utilize an advanced member selection.

## **Creating Dependent Subscription Controls**

You can make subscription controls dependent on other controls sharing a data source. This enables you to create a chain of dependent subscription controls, where dimension member selections in a subscription control prompt the display of the selection's children in dependent controls. Multiple dependent controls can be created to reflect the depth of the dimension hierarchy.

Because check box subscription controls enable multiple member selection, they cannot be used by dependent subscription controls. You are warned when you attempt to delete a subscription control with dependent controls, as dependent controls do not function without the primary subscription control.

- To create a dependent subscription control for a subscription control:
- 1 Drag a subscription control object from the Custom Document component toolbar to a document panel. The Select Data Source dialog box is displayed.
- 2 Select Make Dependent.

Primary subscription controls are displayed.

Click to select a subscription control and click **OK**.

The dependent subscription control is displayed on the custom document. It is populated with the children of the primary subscription control when selections are made.

## **Creating Selection Buttons**

The Selection Button object creates a control button coordinated with other objects in the document using a common data source. Selection button properties differ from other subscription controls.

- To create a selection button:
- Drag the Selection Button object from the component toolbar to the content area of the custom

The Select Data Source dialog box is displayed.

Click to select a data source.

The selection button is coordinated with the data objects sharing one data source.

The Make Dependent option makes the control dependent on other controls sharing this data source. See "Creating Dependent Subscription Controls" on page 231.

Click OK.

The Select Dimension dialog box is displayed.

Select a dimension name, and click OK.

The Select Member dialog box is displayed.

Click Add.

The Dimension Browser for the selected dimension is displayed.

Make member selections, and click OK.

The selected members display in the Select Member dialog box. You can select font properties, color properties, and rename the dimension member labels. The first dimension member in the panel is used as the button label, so it is often helpful to rename the member to a more descriptive label.

You can define dimension member controls using an explicit selection or advanced member selection. In addition, you can use advanced member selections to populate the control. Using advanced member selection to populate a control makes the control dynamic. As members are added deleted and changed in the database, the control maintains itself and does not become obsolete.

These optional subscription control procedures are also available:

- **Ordering Dimension Member Controls**
- **Creating Extended Mode Controls**
- **Renaming Dimension Member Buttons**
- Click OK.

#### **Ordering Dimension Member Controls**

To reorder member controls, select a member name and use the arrow buttons to move the member on the index panel. The order of members is reflected in the custom document, when you click OK.

#### **Creating Extended Mode Controls**

The Extended Mode option enables you to make live member selections, when you review the custom document. Clicking the selection button in Analyze presents another Select Member dialog box that contains options for defined member selections. You can select and display members ad hoc.

To create an extended mode dimension member control, select **Extended Mode**.

#### **Renaming Dimension Member Buttons**

You can rename member text labels on custom controls (combo box, radio button group, check box, tab series, slider bar, and selection button) in the course of setting the data source (query), selecting a dimension from the query, and specifying members.

To rename member text labels, click **Rename Button** on the Select Member dialog box. When the Enter Member's Display Name dialog box is displayed, enter a text label and click OK.

## **Creating Dynamic Text Labels**

- To create dynamic text labels:
- 1 In Document Designer, drag a label object from the component toolbar onto the content area of the custom document.
  - The Insert Text dialog box is displayed.
- Right-click Caption and select a dynamic text label from the shortcut menu.
- 3 Click OK.

## **Dynamic Text Labels**

Dynamic text labels are variables that are dynamically replaced with values at runtime. Dynamic text labels display the latest information without being manually updated

You can use Dynamic Text Labels to create these dynamically updated components:

- Labels—Add dynamic text labels to label objects using the shortcut menu. See "Label Object" on page 237.
- Headers and footers—For your JPG, PDF and hardcopy output, use dynamic text labels in the Print dialog box Headers/Footers tab. See "Print Dialog Header/Footer Tab" on page 150.
- SQL statements—Include dynamic text labels in your SQL filter clauses as values. See "SQL Spreadsheets" on page 195.

Dynamic Text Tag	Default Tag	Inserts this item in the label object:
Database Note	< <dbnote>&gt;</dbnote>	A database note
Cell Reference	< <cell 0,0="">&gt;</cell>	A cell reference string
Page	< <page>&gt;</page>	A page dimension name

Dynamic Text Tag	Default Tag	Inserts this item in the label object:	
Filter	< <filter 0="">&gt;</filter>	A filter member name	
Document Description	< <rd>&gt;</rd>	A document description string	
Document Name	< <rn>&gt;</rn>	A document name string	
Date/Time	< <date,mm-dd-yyyy>&gt;</date,mm-dd-yyyy>	A date/time string	
Connection Name	< <cn>&gt;</cn>	A database connection name string	
Username	< <username>&gt;</username>	A user name string	
UserID	< <userid>&gt;</userid>	A User ID string	

After dynamic text labels are placed in the Insert Text dialog box, you can edit tags to display additional information.

For information on Dynamic Text Labels for SQL Spreadsheet, See "Dynamic Text Labels for SQL Spreadsheets" on page 203.

#### **Fixed References**

Because dynamic text labels change as focus is shifted in composite documents, you may want to fix dynamic references. Tags can be associated with specified data sources using these modifications:

Dynamic Text Tag	Default Tag	Fixed Reference
Connection Name	< <cn>&gt;</cn>	< <cn datasourcename1="">&gt;</cn>
Cell Reference	< <cell 0,0="">&gt;</cell>	< <cell datasourcename1,0,0="">&gt;</cell>
Filter	< <filter>&gt;</filter>	< <filter datasourcename1,0="">&gt;</filter>
Pages	< <page>&gt;</page>	< <pre>&lt;<page datasourcename1="">&gt;</page></pre>
Database Note	< <dbnote>&gt;</dbnote>	< <dbnote datasourcename1="">&gt;</dbnote>

**Note**: It is not possible to specify a fixed references for a page dimension member.

## **Time Format Syntax**

Time Format strings specify the format of the dynamic date/time label. The number and order of ASCII characters determines the format used:

ASCII Symbol	Meaning	Туре	Example
G	Era	Text	AD

ASCII Symbol	Meaning	Туре	Example
у	Year	Number	2002
M	Month in Year	Text & Number	July & 07
d	Day in Month	Number	10
h	Hour in am/pm (1-12)	Number	12
Н	Hour in Day (0-23)	Number	0
m	Minute in Hour	Number	30
S	Second in Minute	Number	55
S	Millisecond	Number	978
Е	Day in Week	Text	Tuesday
D	Day in Year	Number	189
F	Day of Week in Month	Number	2 (meaning 2nd Wed in July)
W	Week in Year	Number	27
W	Week in Month	Number	2
a	am/pm marker	Text	PM
k	Hour in Day (1-24)	Number	24
К	Hour in am/pm (0-11)	Number	0
Z	Time Zone	Text	Pacific Standard Time
' (apostrophe)	Escape for Text	Delimiter	
' '(single quote)	Single Quote	Literal	1

When four or more characters are used, a completely spelled value is returned.

When three or more Text & Number types letters are used, text is provided. When only one or two letters are provided for this type, the number is provided.

Numbers use the minimum number of digits. Year can be truncated to two digits. Shorter numbers are zero-padded.

All other characters are used as quoted text strings.

#### **Examples**

"yyyy.MM.dd G 'at' hh:mm:ss z" returns 1996.07.10 AD at 15:08:56 PDT

"EEE, MMM d, yy" returns Wed, July 10, '96

"h:mm a" returns 12:08 PM


## **Custom Document Components**

This section describes each custom document component:

- Panel Object
- Split Panel Object
- Label Object
- Text Area Object
- **Image Objects**
- **HTML Browser Object**
- Combo Box Subscription
- Radio Button Group Subscription
- **Check Box Group Subscription**
- **Tab Group Subscription**
- Slider Subscription
- **Selection Button Subscription**
- Multi-level Combo Box Subscription
- Alias Controller Object
- Services Button Object
- **SQL Spreadsheet Objects**
- **SQL Subscription Objects**

#### **Panel Object**

The Panel object creates an empty container for dividing space in the document.



Panel object properties are set using the Select Graphic dialog box. See "Adding Custom Document Components" on page 219.

## **Using Panels for Object Placement**

To fit Web Analysis documents to any screen resolution and to help with object-placement differences between Web Analysis Studio and EPM Workspace, use a panel or split panel object. On the panels, the report designer sets the anchor to Top, Bottom, Left, Right, or Slack:

- Top or Bottom—Anchors the object to the top or bottom of the panel respectively. Thus, the object expands its width to the panel size; however, the height does not change.
- Left or Right—Anchors the object to the left or right of the panel respectively. Thus, the object expands its height to the panel size; however, the width does not change.
- Slack —Consumes all available space in the panel. Thus, it expands its height and width to the panel size.

#### **Split Panel Object**

The Split Panel object creates two coordinated panels separated by a splitter bar. See "Creating Split Panels" on page 225


Control	Description
Orientation	
Horizontal	Sets the Splitter bar to a horizontal orientation that coordinates a top and bottom panel.
Vertical	Sets the Splitter bar to a vertical orientation that coordinates a left and right panel.
Properties	
One-touch Expandable	Enables the Splitter bar to jump to the opposite panel with one click.
Set Current Sizes As Preferred	Enables you to position the Splitter bar using the pixel grid. The Split Panel definition is updated when you click <b>OK</b> , and this setting is refreshed each time the dialog is displayed.
Background Images	
Left	Displays the Select Graphic dialog box to set the background image of the left panel when the Splitter bar is vertical.
Right	Displays the Select Graphic dialog box to set the background image of the right panel when the Splitter bar is vertical.
Тор	Displays the Select Graphic dialog box to set the background image of the top panel when the Splitter bar is horizontal.
Bottom	Displays the Select Graphic dialog box to set the background image of the bottom panel when the Splitter bar is horizontal.

## **Label Object**

The Label object creates static or dynamic text for use as a title, label, or caption. You can enter label text in the Label Caption dialog box. See "Adding Custom Document Components" on page 219 or "Creating Dynamic Text Labels" on page 233.

#### **Text Area Object**

The Text Area object creates a dynamic text box used for annotating documents.



You are prompted to populate the text object with a default text string with the Enter Default Text dialog box.

#### **Image Objects**


The Image object creates a graphic. This enables you to create backgrounds, pictures, illustrations, and graphic controls.

# DRACLE' | Hyperion

Image object properties are set using the Select Graphic dialog box. Graphic controls are created in conjunction with the Services Button object. See "Creating Hotspots" on page 225 or "Services Button Object" on page 241.

#### **HTML Browser Object**

The HTML Browser object creates a pane for displaying static HTML. The HTML is not interactive. Selecting Properties from the component shortcut menu displays the HTML Object Properties dialog box, used to specify a URL.



#### **Combo Box Subscription**

The Combo Box Subscription object creates a drop-down list coordinated with other objects using a data source. See "Creating Subscription Controls" on page 228.

## **Radio Button Group Subscription**

The Radio Button Group Subscription object creates a radio button group (option button group) that is coordinated with other objects using a common data source. See "Creating Subscription Controls" on page 228.

## **Check Box Group Subscription**

The Check Box object creates check boxes coordinated with other objects using a common data source. See "Creating Subscription Controls" on page 228.

#### **Tab Group Subscription**

The Tab Group Subscription object creates a tab series coordinated with other objects using a common data source.

The shortcut menu for Tab Group Subscription objects contains a special Custom Settings command. Tab Groups are typically positioned on one side of a coordinated rectangular data object, visually suggesting that the tab emerges from that side of the rectangle. The Orientation options indicate the side of the data object on which the tabs are positioned:

- Top
- Bottom
- Left
- Right

**Note:** The tab group area must be resized to display correctly.

See "Creating Subscription Controls" on page 228.

#### **Slider Subscription**

The Slider Subscription creates a bar control coordinated with other objects using a common data source. The shortcut menu for Slider Subscription objects contains a special Custom Settings command:

Custom Setting	Description
Orientation	The alignment of the slider subscription in relation to the document
Horizontal	Parallel with the ground alignment
Vertical	Straight up alignment
Show Ticks	Shows or hides the member points on the slider bar track
Show Track	Shows or hides the slider bar track
Show Labels	Show or hides the member labels on the slider bar track
Snap to Ticks	Requires the slider to snap to tick points on the slider bar track

See "Creating Subscription Controls" on page 228.

#### **Selection Button Subscription**

The Selection Button object creates a control button (command button) coordinated with objects using a common data source.

The Select Member dialog box Extended Mode option enables you to make live member selections when reviewing the custom document. Clicking the selection button in Analyze presents another Select Member dialog box, containing check boxes for defined member selections. You can select and display these members ad hoc. See "Creating Dependent Subscription Controls" on page 231.

#### **Multi-level Combo Box Subscription**

The Multi-Level Combo Box Subscription object creates multiple coordinated drop-down lists representing the dimensional hierarchy. They are also coordinated with other objects using a common data source.

The combo boxes cascade. Selections made in a previous combo box populate subsequent dialog boxes with hierarchical descendents. Use the Custom Setting shortcut menu command to indicate the number of levels to cascade from the initial dimension member selection.

Multi-Level Combo Box Subscription objects feature a special Custom Settings shortcut menu command:

Custom Settings	Description
Orientation	Arranges the cascading multiple combo boxes horizontally or vertically.
	Note: The component area must be resized to display correctly. Also consider that asymmetric hierarchies require a component area providing for the greatest number of combo boxes.
Horizontal	Parallel with the ground alignment
Vertical	Straight up alignment
Set Depth	Displays the Enter Maximum Depth dialog box, used to indicate the number of levels from the member the multi-level combo box should cascade (the number of subsequent combo boxes)

#### **Alias Controller Object**

The Alias Controller object enables custom document you to specify the alias table to use when the label mode is set to Descriptions (for the coordinated data object). The Alias Controller and the data object (Chart, Spreadsheet, or Pinboard) must be configured to share a common data source.

Use the Select Data Source dialog box to select a data source for the Alias Controller object. You can access the Select Data Source dialog box by dragging an Alias Controller object into the Document panel, or by selecting Properties from the Alias Controller object shortcut menu.

# **Services Button Object**

The Services Button object creates a button that callsWeb Analysis Studio services. Services are application actions or behaviors. The Select Service dialog box sets Services Button object properties.

Select Service Control	Services Button Action	
Logout	Initiates logging off or existing fromWeb Analysis Studio	
Previous Tab	Navigates to the previous tab series option	
Home	Displays the Web Analysis Studio Home page	
File Open	Opens the Open dialog box	
Print	Opens the Print dialog box	
Open Document	Opens a specified document without use of the Open dialog box	
Edit Data	Puts the current document in edit data mode	
Dimension Browser	Displays the dimension browser for a selected dimension of a related data object	
Close Document	Closes the specified document	
Save	Saves the current document	
Toggle Toolbar	Shows or hides the toolbar for the current document	
Toggle Information Panel	Shows or hides the View Pane Information Panel for the data object	
Toggle Menu	Shows or hides the current document's menu bar	
Send to Clipboard	Exports the current page of the current data object of the current document to the operating system clipboard	
Member Search	Displays the Search dialog box, used to locate members in large dimension hierarchies	
	See "Searching for Members" on page 63	
Change Display Type	Changes the data object display type	
Display Type drop-down list	Specifies the display type, which is applied by the Change Display Type service button	
Next Tab	Navigates to the next tab series option	
Desktop	Displays the Web Analysis Studio desktop	
User Preferences	Opens the User Preferences dialog box	
Reload Document	Reloads the current document	
Essbase Calculation Script	Triggers the specified calculation script of an Essbase data source	
	The calculation script consolidates the OLAP cube, reflecting changes implemented through edit data mode or an update	
Open Presentation	Opens a specified presentation	

Select Service Control	Services Button Action
Assign Edit Data	Initiates edit data mode for a specified data object
Launch Executable	Opens a specified application executable
Data Layout	Opens the Data Layout dialog box for the current data object
Save As	Opens the Save dialog box
Toggle Masthead	Shows or hides the masthead for the current document
Toggle Status Bar	Shows or hides the Status bar for the current document
Send to Excel	Exports the current page of the current data object of the current document to Microsoft Excel
Apply Subscriptions	Performs a data retrieval when subscription controls that have "Activate From Service Button" are enabled
Launch External Browser	Launches a browser session for the specified URL
	This URL enables passing of an SSO token, similar to related content URLs, using the token syntax \$SSO_TOKEN\$
	Valid in both EPM Workspace and Web Analysis Studio

Services Button Properties	Description
Enter Text Label	Applies a static text caption to the Services button
Font	Opens the Font Properties dialog box for formatting the caption font
Color	Opens the Select Color dialog box for selecting button and border color
Select Graphic	Opens the Select Graphic dialog box for setting the Services button background image
Clear Graphic	Deletes the Services button background image

#### **Hotspots**

A hotspot is an area that is linked to a Web Analysis Studio service. It is an invisible button that performs a predefined action. You can create a hotspot by making services buttons transparent. The invisible service button can be located over a graphic image, giving the appearance that an area of the image triggers the service.

Designers control the level of transparency. The hotspot can be completely invisible, display a border, or display a border and a text label. Completely opaque Service buttons are considered buttons, not hotspots. see "Creating Hotspots" on page 225.

#### **Services Button Custom Settings**

Services buttons feature a Custom Settings shortcut menu command:

Services Button Custom Setting	Description	
Location		
Leading	Positions icon before the text label	
Trailing	Positions icon after the text label	
Horizontal Text Alignment		
Left	Positions the text label to the left side of the Services button	
Center	Horizontally centers the text label on the Services button	
Right	Positions the text label to the right side of the Services button	
Vertical Text Alignment		
Тор	Positions the text label to the top of the Services button	
Center	Vertically centers the text label on the Services button	
Bottom	Positions the text label to the bottom of the Services button	

## **SQL Spreadsheet Objects**

SQL Spreadsheet objects represent relational data sources as a spreadsheet, using standard SQL syntax queries. A SQL Subscription object enables you to create coordinated controls for the SQL spreadsheet. See "SQL Spreadsheets" on page 195.

#### **SQL Subscription Objects**

The SQL Subscription control enables you to select relational column definitions from a dropdown list. The control is coordinated with a SQL Spreadsheet object using a matching relational data source (SQL query). The shortcut menu for SQL Subscription objects contains a Custom Settings command that indicates the type of subscription control used to present dimension member selections:

- Combo box
- Radio button group
- Slider
- Tab group

See "Creating a SQL Subscription Control" on page 203.

#### **Minimizing Document Load Times**

Here are some general design recommendations for improving Web Analysis document load times. Please note that these recommendations do not represent limitations of the product, but general guidelines to allow a document to load faster. All references to a "query" are referring to one Report Data Source in a document.

- No more than four (4) queries per document.
- No more than 100,000 of cells returned on a query.
- No more than four (4) OLAP selection/subscription controls that have "dynamic" enabled per Web Analysis document and should only contain a maximum of 5000 members for each.
- No more than 1000 pages on a query.
  - No more than twenty (20) Traffic Lighting definitions with a maximum of seven (7) levels per query.
  - No more than twenty (20) Show/Hide definitions per query.
  - No more than twenty (20) Calculations per query.
  - No more than twenty (20) Data Formatting definitions per query.
  - Only one (1) Retrieve Top/Bottom per query.
  - No more than twenty (20) Restrict Data conditions per query.
- No more than 1/2 MB of total size of graphics on a Web Analysis document. This includes graphics used on pinboards.
- When LROs or Integration Services Drill Through report are not necessary, disable the Show Linked Reporting Object Indicators to improve performance.
- When using advanced member selections to apply database formatting on a database connection, limit the use on small outlines no more than 10,000 members.



# **Editing Data Values**

#### **In This Chapter**

Initiating Data Mode and Editing Data	245
Copying, Cutting, and Pasting To and From Microsoft Excel	246
Tips for Edit Data Mode	246
Integration Services Drill-Through	246
Accessing Related Content	247
Related Content Definitions	247

# **Initiating Data Mode and Editing Data**

Users with permissions can edit cell values and write edits back to Essbase. You can initiate Edit Data mode only from the spreadsheet display type.

- To initiate Edit Data mode and Edit Data.
- Right-click a cell and select Edit Data

The Edit Data Bar is displayed at the bottom of the content area and features these controls:

Button	Control	Description
x	Close and Disable Edit Data mode	Closes Edit Data mode.
	Send/Commit changes to database server	Applies edits to the database.
	Calculate database	Prompts the database server to recalculate the database.
ф	Refresh Data	Reload the last saved data values.

- Double-click a cell to edit its data value.
- Double-click a cell to edit its data value.

The cell border becomes gray, and cell formatting is disabled.

- Enter a data value and click outside the cell.
- Click Send/Commit changes to the database server.

Only authorized users can successfully write changes to the database. The Confirmation dialog box is displayed if write-back is successful.

- 6 Optional: To recalculate the database, click Calculate database.
- 7 To exit Edit Data mode, click Close and Disable Edit Data mode.

# **Copying, Cutting, and Pasting To and From Microsoft Excel**

When in Edit Data, you can cut, copy and paste a range of cells from a Microsoft Excel spreadsheet into the Web Analysis Studio spreadsheet. These edits can be posted to Essbase. You can also cut, copy, and paste between values in Web Analysis Studio.

You can use these keyboard shortcuts:

- Copy—Select a range of cells and press Ctrl+C
- Cut—Select a range of cells and press Ctrl+X
- Paste—Select a range of cells and press Ctrl+V

## **Tips for Edit Data Mode**

- You cannot edit calculated members, because these values do not reside in the database.
- You cannot edit attribute dimensions, because these values do not reside in the database.
- Dimensions composed of implied shares (or user-defined hierarchies) aggregate differently than conventional dimension hierarchies. Therefore, the implied share may overwrite data edits made to the Parent of an implied share as the model is pivoted.

**Example:** Actual and Budget are implied shares of the Parent, Scenario. Scenario, however, is a categorical label, not an aggregation of Actual and Budget measures.

## **Integration Services Drill-Through**

Integration Services drill-through is a server-based form of relational drill-through. As with conventional relational drill-through, you can construct liaisons between OLAP data and relational data sources. With Integration Services drill-through, you can also drill to the relational document from an intersection in the Web Analysis Studio document.

Your Essbase Administrator must establish Integration Services drill-through documents. The relational query is stored as intersection-specific metadata and flagged as a linked documenting object. When you double-click flagged cells, the OLAP document navigates to the specified relational document.

Web Analysis Studio enables read access to Integration Services through the Related Content dialog box.

Linked documenting object indicators, blue triangles, indicate related content such as drillthrough documents. Each Integration Services drill-through document is unique to the drilled intersection.

To access an Integration Services document, double-click cells displaying linked documenting object indicators, and select the drill-through document from the Related Content dialog box.

## **Accessing Related Content**

You can use EPM Workspace to create and retrieve related content definitions, Related content can include, but is not limited to:

- LROs cell notes, URLs, and file attachments stored at Essbase intersections
- Integration Services drill-through content
- Financial Management cell text and line item details stored at Financial Management intersections
- Financial Reporting content displayed as HTML or PDF

EPM Workspace passes the context of the current document to other Web Analysis documents. This enables the related content target to reflect the current POV.

When passing context to Oracle | Hyperion Documents, only dimensions in the current Oracle Hyperion Documents POV are imported.

After they are defined, Related Content definitions can be managed from the Related Content dialog box.

- To access related content definitions:
- 1 Perform one:
  - Click a cell displaying an LRO indicator.
  - Right-click a cell displaying an LRO indicator and select Related Content from the shortcut menu.

The Related Content dialog box is displayed.

To display the corresponding content, click a related content definition, or click Launch.

If necessary, select one client option from the shortcut menu, or the Launch drop-down list.

#### **Related Content Definitions**

You can apply related content definitions to specified cell intersections.

When the Related Content dialog box is displayed, it lists all related content definitions for that intersection. Related content definitions defined for cell intersections are differentiated by italicized text.

# **Related Content Dialog Box**

The Related Content dialog box lists previously configured related content links. EPM Workspace allows for creating cell notes in the Related Content dialog box. Related Content Cell Notes are defined using the Cell Note dialog box.

Control	Used To:
Delete All	Delete all related content definitions for the current selection.



# Accessing External Media

#### **In This Chapter**

Importing Documents and Presentations	249
Integration Services Drill-Through	251
Accessing Related Content	252
Related Content Definitions	252
Creating Related Content Definitions	253
IROs.	255

This chapter provides information on accessing external media.

# **Importing Documents and Presentations**

You can import previously exported documents and presentations from local computers and mapped drives. All content exported from Web Analysis (both presentations and reports) is appended with extension \*.apt.

- To import a document or presentation:
- Select File, then Import, then From Local File.

The Import wizard is displayed. The Import wizard has two steps: Choose Files and Map Resources.

#### Perform one:

- Enter the fully qualified path from your client to a file you would like to import in Select a file to Import.
- Click the ellipses (...) button to Browse to the file using the Open dialog box.

#### Perform one:

- Enter the path from the root directory to the repository location to save the imported file.
- Click the ellipses (...) button to Browse to the repository location using the Open dialog box.
- **Optional:** Select one:

- Click Create entire to recreate the database connections and documents used by the file, from xml definitions in the file.
- Click **Map to existing files** to use database connections and documents currently in the repository, instead of generating duplicates.

If no selection is made, Map to existing is used by default.

In Step 2, you must map database connections, and for presentations, you must map document playlists back to repository documents.

#### 5 **Optional:** To locate a database connection for an unmapped document, perform these tasks:

a. Click a document row with a < Missing > status.

Three command buttons are enabled at the bottom of the dialog box.

b. Click Locate.

The Open dialog box is displayed, with the Files of type set to database connections.

c. Navigate to a database connection, select it, and click OK.

The Open dialog box is dismissed. The Step 2 frame displays the document database connection status as OK.

#### **Optional:** To create a database connection for an unmapped document:

a. Click a document row with a < Missing > status.

Three command buttons are enabled at the bottom of the dialog box.

b. Click Create New.

The Database Editor dialog box is displayed with the Server tab current.

c. Enter a server name in Database Server.

Web Analysis Studio enters the cached user ID and password information in the Login Information group.

- d. Optional: Replace User ID and Password credentials.
- e. Click Connect.

The Database tab is enabled.

f. Click the Database tab to make it current.

The Database tab features Application and Database areas and a Available Database selection frame listing the databases on the connected data source.

g. In **Available Database**, select a database application.

The selection populates the corresponding area.

- h. **Optional:** To define measures formatting criterion, click **Formatting**. See "Creating OLAP and Oracle | Hyperion Database Connections" on page 158.
- i. Optional: To define a relational drill-through connection to a relational data source, click the Relational Drill-through tab. See "Creating Relational Drill-Through" on page 163.

Click OK.

The Database Editor dialog box is dismissed. The Step 2 frame displays the document database connection status as OK.

- Optional: To restore the original database connection exported with the document:
  - a. Click a document row with a < Missing > status.

Three command buttons are enabled at the bottom of the dialog box.

- b. Click Restore.
- c. The Save As dialog box prompts you for a location to which database connections and document definitions are saved. Navigate to a repository location, enter a file name, and click OK.

The Step 2 frame displays the document database connection status as <Creating>. The connection is not created until you map all document rows.

- Repeat steps 5, 6, and 7 until all documents are mapped to a database connection.
- Click Finish.
- 10 When database connections are mapped for all imported documents in the selected repository folder, click Close.

# **Integration Services Drill-Through**

Integration Services drill-through is a server-based form of relational drill-through. As with conventional relational drill-through, you can construct liaisons between OLAP data and relational data sources. With Integration Services drill-through, you can also drill to the relational document from an intersection in the Web Analysis Studio document.

Your Essbase Administrator must establish Integration Services drill-through documents. The relational query is stored as intersection-specific metadata and flagged as a linked documenting object. When you double-click flagged cells, the OLAP document navigates to the specified relational document.

Web Analysis Studio enables read access to Integration Services through the Related Content dialog box.

Linked documenting object indicators, blue triangles, indicate related content such as drillthrough documents. Each Integration Services drill-through document is unique to the drilled intersection.

To access an Integration Services document, double-click cells displaying linked documenting object indicators, and select the drill-through document from the **Related** Content dialog box.

## **Accessing Related Content**

You can use EPM Workspace to create and retrieve related content definitions. Related content can include, but is not limited to:

- LROs cell notes, URLs, and file attachments stored at Essbase intersections
- Oracle Essbase Integration Services drill-through content
- Financial Management cell text and line item details stored at Financial Management intersections
- Oracle Hyperion Financial Reporting content displayed as HTML or PDF

EPM Workspace passes the context of the current document to other Web Analysis documents. This enables the related content target to reflect the current POV.

When passing context to Oracle | Hyperion Documents, only dimensions in the current Oracle | Hyperion Documents POV are imported.

After they are defined, Related Content definitions can be managed from the Related Content dialog box.

**Note:** Using the following special characters in a Web Analysis report name will result in "Invalid argument" when attempting to launch the link in Workspace: left bracket "(", twiddle "~" and dash "-".

- To access related content definitions:
- 1 Perform one:
  - Click a cell displaying an LRO indicator.
  - Right-click a cell displaying an LRO indicator and select Related Content from the shortcut menu.

The Related Content dialog box is displayed.

2 To display the corresponding content, click a related content definition, or click **Launch**.

If necessary, select one client option from the shortcut menu, or the Launch drop-down list.

#### **Related Content Definitions**

You can apply related content definitions to specified cell intersections.

When the Related Content dialog box is displayed, it lists all related content definitions for that intersection. Related content definitions defined for cell intersections are differentiated by italicized text.

## **Related Content Dialog Box**

The Related Content dialog box lists previously configured related content links. EPM Workspace allows for creating cell notes in the Related Content dialog box. Related Content Cell Notes are defined using the Cell Note dialog box.

Control	Used To:
Delete All	Delete all related content definitions for the current selection.

## **Creating Related Content Definitions**

Creating related content definitions is a two-part process, as described in these topics:

- 1. "Specifying Related Content Dimension Members" on page 253
- 2. "Defining Related Content" on page 254

## **Specifying Related Content Dimension Members**

- To apply a related content definition to a cell, right-click the cell and select **Related** Content.
- To apply a related content definition to all cells in a row or column by dimension member, right-click the dimension member row or column header.
- To apply a related content definition to a selection statement:
- 1 Right-click the dimension member row or column header.
- 2 Select Related Content.

The Related Content dialog box is displayed.

To edit the dimension member selection displayed in Apply to, click Edit.

The Edit Selections dialog box is displayed.

- 4 To display **Dimensions**, click **Advanced**.
- Click a check box to select dimension members.

If you select one dimension from the Dimensions panel, the corresponding dimension members are displayed in the Combinations panel.

If you select multiple dimensions from the Dimensions panel, Combinations displays dimension member aggregations.

6 To specify the dimension member, click check boxes in **Combinations**.

Selections display in **Selections**. Click Remove to delete the current selection, or Remove All to delete all member selections and start over.

7 When dimension member selections are defined, click OK.

The Edit Selections dialog box is dismissed, and the Related Content dialog box is displayed. The **Apply To** panel displays the dimension member selection. You can now create a related content definition, using the next procedure.

## **Defining Related Content**

- To create a related content definition:
- 1 Right-click the cell or dimension member header in which the related content is to be embedded.
- 2 Select Related Content.

The Related Content dialog box is displayed.

3 Click the Add Related Content icon.

The Add Related Content dialog box is displayed. In the Available panel, applications are listed as nodes. Each node can be expanded to list available application content.

- 4 To locate application content, perform one:
  - Double-click a node name to expand the node.
  - Click a node plus sign (+) to expand the node.

Notice that applications such as Web Analysis Studio enable you to specify the client with which the content displays.

- 5 Click to select the application content.
- 6 To move the selection to Selected Related Content, click Add.

If the "Show Properties When Adding Content" option, at the bottom of the Add Related Content dialog box, is selected the Related Content Properties dialog box is displayed.

- 7 Optional: To set Related Content Properties for Selected Related Content, perform one:
  - Select a related content definition and click **Properties**.
  - Right-click a related content definition and select **Properties**.

The Related Content Properties dialog box is displayed.

You can optionally set properties:

- To change the related content definition name, enter a name in Label.
- To indicate how related content is displayed, select options in Client Options. The document's related content can be displayed in HTML or PDF.

- To edit the URL of the related content definition, edit the URL of the corresponding tab.
- 8 Click **OK** to close the Related Content Properties dialog box.
- 9 Click OK to close the Add Related Content dialog box.

The related content definition is displayed in the Related Content dialog box.

10 Click Close.

The document displays the LRO indicator(s).

### LR0s

LROs embed cell notes, URLs, and file attachments in document cells. LROs are connections to external media stored in Essbase.

LROs are available to Essbase users who enabled the Essbase Grid API feature.

An LRO indicator triangle indicates the presence of a drillable LRO. LROs are embedded in, and move with, multidimensional intersections.

You can display or hide Linked Documenting Object indicators using the Data Display shortcut menu.

Linked Reporting Objects can only be applied to cell intersections, unlike other related content definitions (which can be applied to cells, rows, columns, or selection statements).

## **Creating LROs**

**Note:** You must first configure and enable the Essbase Grid API, before you can create LROs. The Workspace can only crate cell note LROs.

- To create a cell note:
- 1 Right-click the cell in which the LRO is to be embedded.
- 2 Select Related Content

The Related Content dialog box is displayed.

- 3 Click one the Add Note icon.
- 4 Enter cell note information.
- 5 Click OK.
- 6 Click OK.

The document displays the LRO indicator.

## **Accessing LROs**

- To access an LRO:
- 1 Perform one:
  - Click a cell displaying an LRO indicator.
  - Right-click a cell displaying an LRO indicator and select **Related Content** from the shortcut menu.

The Related Content dialog box is displayed.

2 To display the corresponding content, double-click a related content definition, or click **Launch**.

# **Setting Preferences**

### **In This Chapter**

Working with Preference Files.	257
Finding Preferences	259
General Preferences	260
Folders Preferences	261
Look and Feel Preferences	262
Drilling Preferences	263
Default Formatting Preferences	263
OLAP Server Preferences	264
Database Preferences	265
POV Definitions	267
Personal Variables	268

## **Working with Preference Files**

You can customize the Web Analysis display and set behavior for documents by setting preferences.

To display the User Preferences dialog box, select File, then Preferences.

Preferences are stored in the repository as a preference file. Although multiple preference files can be defined, only one can be current, or active. Multiple users can share a common active preference file, also called shared preferences.

User preference files for a user are located in a user's Profiles folder and are named "Analyzer Preferences"; for example, Users/username/Profiles/Analyzer Preferences. When user preferences are modified, all changes are saved to this file.

An administrator can create a shared preference file that other users can select as their active preferences.

**Note:** Shared preference files can be created and edited only in Web Analysis Studio.

At the top of the User Preferences dialog box, the Active Preferences controls specify the current preference file. Changing active preferences does not impact currently opened documents in the content area. Preferences are only applied to subsequently opened and created documents.

**Note:** Some preferences may take effect only when documents are reloaded.

Topics that discuss preference files:

- "Setting Active Preferences" on page 258
- "Creating Preference Files" on page 259
- "Editing Shared Preference Files" on page 259
- "Managing Shared Preference Files" on page 259

## **Setting Active Preferences**

- To set active preferences, perform one:
- To use the preference file in your Users/username/Profiles directory, click Use My Preferences.
- To use another preference file, click Use Shared Preferences, and click Browse to navigate to the preference file.

## **Preferences and Formatting Options**

There are some identical formatting options and preferences. Preferences are global settings applied to documents. Preferences, however, can be overridden by database connection formatting and document-based formatting.

Order of Formatting Precedence

- Formatting options saved with documents
- 2. Formatting options saved with the database connection
- Formatting options specified in the User Preferences dialog box

See "Formatting Order of Precedence" on page 92.

Spreadsheet preferences and chart preferences are identical to spreadsheet options and chart properties. They are only applied to subsequently created documents, however. See "Spreadsheet Options" on page 101 and "Charts and Chart Types" on page 102.

## **Creating Preference Files**

Administrators can create preference files that users can select as shared preferences in Web Analysis Studio and EPM Workspace. The default folder for shared preferences is Users/ {Profiles}.

- To create a preference file that can be shared by users:
- Select File, then New, then Preferences.
  - The Save As dialog box is displayed.
- Navigate to a repository folder and enter a file name.
- Click **OK** to display **User Preferences**.
- Edit user preferences, and click **OK** to save changes.

## **Editing Shared Preference Files**

- To change preferences settings in a shared preference file:
- In Web Analysis Studio, navigate the repository to locate a shared preference file and select it.
- Right-click the preference file and select Edit to open User Preferences.
- Change user preferences, and click **OK** to save the changes and close **User Preferences**.

## **Managing Shared Preference Files**

Preference files can be shared among users to utilize as their active preferences.

- To enable user access to shared preference files:
- In Oracle Hyperion Enterprise Performance Management Workspace, navigate to a preference file, rightclick it, and select Properties.
- In Properties, under General Properties, click Edit Permissions.
- Assign users, groups, or roles to the file (in the same manner as you would permissions to repository objects).

## **Finding Preferences**

Preferences are organized onto nine (9) tabs. Click a tab to make it current.

Panel	Preferences
General	Home Page and Startup
Folders	Reports folder, Databases Folder, Desktop Folder, and Favorites Folder

Panel	Preferences
Look and Feel	Use of Data Layout in documents, Desktop Wallpaper, and Interface Elements
Drilling	Drilling Methods, Linking, Append or Replace Member Selections (Expand on Drill)
Spreadsheet	Spreadsheet Options
Chart	Chart Properties
Default Formatting	Leading and Trailing Formatting, Replace Missing With, and Numeric Formatting
OLAP Server	Suppression, Show Linked Document Object Indicators, Financial Management Entity Currency (Financial Intelligence)
Databases	Database Alias Table, Default Log on, POV Definitions, Personal Variable Definitions

### **General Preferences**

General preferences are divided into three groups:

- Home Page Preferences
- Startup Preferences

## **Home Page Preferences**

The toolbar and the Go menu offer single-click access to a Web Analysis Studio Home page. The home page should be a frequently used repository location.

You can specify the desktop or a document as the Web Analysis Studio Home page. The specified document is displayed when you click the Home toolbar button.

- To set the Web Analysis Studio Home page using preferences:
- Select File, then Preferences.

The User Preferences dialog box is displayed. Note that you are setting the Home page for active preferences. If it is a shared preference, you are setting the Home page for all users sharing this preference file.

- 2 Click to make General the current tab.
- 3 In **Home Page**, perform one:
  - Click Use Desktop to set the Desktop Folder, as specified by Folder preferences, as the Home Page.
  - Click Use Current Document to set the current document as the Home Page.
  - Click the ellipses (...) button to select a repository location from the Open dialog box as the Home Page.
  - Enter a repository location in the text area to be used as the Home Page.
- 4 Click OK.

- To go to the Web Analysis Studio **Home Page** in Analyze:
- Click 🚨.
- Select Go, then Home.
- Press Alt+Home.

## **Startup Preferences**

Startup preferences enable you to specify the document or document group to be displayed at startup:

- The Analyze mode interface (None)
- The Open dialog box
- The Web Analysis Studio Home Page
- A presentation
- A document
- ➤ To set startup preferences:
- 1 Select File, then Preferences.

The User Preferences dialog box is displayed. Note that you are setting the startup option for active preferences. If it is a shared preference, you are setting the startup option for all users sharing this preference file.

- 2 Click to make General the current tab.
- 3 In **Startup**, select one:
  - None
  - Start in Open Dialog
  - Home Page
  - Document
- 4 **Optional**: If you select **Document**, you must also specify which document to use:
  - Click the ellipses (...) button to select a repository location from the Open dialog box as the Startup document.
  - Enter a repository location in the text area to be used as the Startup Document. You can specify a document or a presentation as the startup document.
- 5 Click OK.

## **Folders Preferences**

Folders preferences display the repository locations currently set as these folders for the active user or group:

- Reports folder
- Databases folder
- Desktop folder
- Favorites folder

You can only reset the folder locations for the active user.

Note: As with all file systems, though the default directories, folders, and files were designed for a purpose there is nothing to prevent you from diverging from this original design. See "User and Group Folders" on page 41.

### ➤ To reset Folder preferences:

### Select File, then Preferences.

The User Preferences dialog box is displayed. Note that you are setting folders for active preferences. If it is a shared preference, you are setting folders for all users sharing this preference file.

- Click to make Folders the current tab.
- Perform one:
  - In a text area, enter a repository location to be used for the corresponding folder.
  - Alternatively, click the ellipses (...) button and select a repository location from the Open dialog box, to be used for the corresponding folder.
- Click OK.

## **Look and Feel Preferences**

Look and Feel preferences are organized into three groups:

Look and Feel Preferences	Description
New Documents	Specifies Web Analysis Studio behavior for opening a database connection.
	When disabled (default), opening a database connection through the Open Menu, Open toolbar button or View Pane shortcut menu, results in a Auto-Populate Dimension document. Auto-Populate Dimension documents assume use of the highest aggregate members of the time and measures dimensions to populate the rows and columns axes of a spreadsheet.
	When enabled, the use of a spreadsheet is still assumed, but you must assign dimensions to axes with Data Layout as part of creating a document.
Desktop	Sets the desktop wallpaper graphic, using the Select Graphic dialog box.

Look and Feel Preferences	Description
Display	Sets interface elements to be displayed by default:
	Content tabs
	Main menu (menu bar)
	Toolbar
	Masthead
	Filter panel
	View pane
	Status bar
	Multi-page drop-down

## **Drilling Preferences**

Drilling preferences are organized into these three groups:

Drilling Preferences	Description
Method	Sets drilling navigation through the dimension hierarchy to one of these menu options:
	Next Level - Returns the next lowest level.
	Descendants - Returns all descendants.
	Dimension Bottom - Returns the lowest level (level 0).
	Siblings - Returns members on one level that share a parent.
	Same Level - Returns members on one level
	Same Generation - Returns members equidistant from the highest ancestor.
Linking	Sets drilling navigation to Pass Page dimension and/or Pass Filter dimension context during drill-through operations to other documents:
	Pass Pages - sets drill linking to pass the page dimension member context.
	Pass Filters - sets drill linking to pass the filter dimension member context.
Expand On Drill	Augments the drilled member with the drilling result set. See "Drilling" on page 84.

## **Default Formatting Preferences**

Formatting options format headers and data based on dimension member selections.

While the formatting options are fixed, the scope of the formatting varies depending on the source of the formatting. See Chapter 8, "Formatting Documents."

Formatting Options	Description
Leading and Trailing Formatting	

Formatting Options	Description
Currency Symbol	Inserts currency formatting symbols into the Positive Prefix and Negative Prefix text boxes: Dollar (\$), Cents (¢), Pound (£), Euro ( € ), Deutschmark (DM), Franc (F), and Yen (¥).
Positive Prefix	Enters character to precede positive numeric values.
Positive Suffix	Enters character to follow positive numeric values.
Negative Prefix	Enters character to precede negative numeric values. <b>Warning:</b> The minus sign (-) is the default prefix. Deleting the default prefix without replacing it causes negative values to display positively.
Negative Suffix	Enters character to follow negative numeric values.
Numeric Formatting	
Grouped Thousands	Displays numeric digits as grouped by thousands.
Minimum Decimals	Indicates the minimum number of decimal places to display.
Maximum Decimals	Indicates the maximum number of decimal places to display.
Scale	Enables abbreviated values by tens, hundreds, thousands, ten-thousands, hundred-thousands, millions, and billions.
Use Negative Color	Indicates that negative numbers are signified by a selected color.
Select Negative Color	Enables you to select the color representing negative values.
Samples	
Update Samples	Updates the samples panel based on the most recent formatting selections.
Replace Missing With	Replaces missing values with a text string or zero.
	● Zero
	● Text

## **OLAP Server Preferences**

OLAP server preferences set features of the OLAP server from Web Analysis Studio.

OLAP Server Preferences	Description
Suppress	Omits components, as selected, from the query result set:
	Missing Rows
	Shared Members
	Zero Rows
Show Linked Reporting Object Indicators	Enables and disables the display of LRO icons (triangles).

OLAP Server Preferences	Description
Display Entity Currency	When using a Financial Management data source with defined Entity dimension currency information, you can enable the Display Entity Currency option, to append the Entity dimension members with your currency value. This can be set before querying using Data Layout options, after querying using the Data Display shortcut menu, and for all subsequently created documents using OLAP Server preferences. See "Financial Management" on page 169.
Save Filters only for User POV	User POV enables users to select members in Filters, Pages, Rows, and Columns (Data Layout and/or member selection controls) and applies them to multiple Web Analysis documents.
	All Subscription controls have Save Selection as a User POV option. A selection is saved as a filter to the User POV.

Essbase imposes a maximum limit of 256 columns. Web Analysis Studio sets a column limit of 50,000 data cells for a query. There is also a query governor that enables you to set limits on the number of cells returned by a query; the default is also 50,000 data cells.

### **Database Preferences**

Databases preferences provide an inventory of database servers and database connections available to the current user by listing the database connection name, description, alias table, and repository location for available database connections.

To review the database preferences for a database connection, you must select the database connection name from the list and click Edit. The Database Preferences dialog box is displayed. It has three tabs:

- General
- Point of View
- Personal Variable

You must click Connect to connect to the data source and retrieve the values for these settings. If you are unable to connect, you may browse to another database connection file.

See also "Creating and Applying Points of View" on page 74 and "Creating and Selecting Personal Variables" on page 73.

## **Alias Tables**

Alias tables are database tables that store aliases, or alternate description labels, for dimensions or members. Only Essbase enables you to define multiple alias tables. Web Analysis Studio enables you to specify which alias table to use. The alias table selection is saved as a Database user preference.

Label mode enables you to select whether a dimension member is listed by ID number, description, or both. Label mode options are data source-specific, and can be set for database connections, documents, and dimensions.

Although the label mode indicates whether the description or ID number is used, it is the database alias table that provides the displayed value.

You can set the alias table before opening a document using Database preferences.

You can set a default label mode before querying the data source using Data Layout options, and after querying using Data Display options on the Main Display panel shortcut menu.

You can specify which description label to use in dimensions, using Dimension Browser and using Data Display options on the data object shortcut menu.

## **Setting Alias Tables and Default Logon Method**

- To specify a default alias table for a database connection:
- 1 Select File, then Preferences.

The User Preferences dialog box is displayed. Note that you are setting the default alias table for active preferences. If it is a shared preference, you are setting the default alias table for all users sharing this preference file.

- Click to make **Databases** the current tab.
- Optional: To edit database preferences for a database connection, select the database connection from the list and click Edit.
- Optional: To add a database connection to the list, click Add.

The Database Preferences dialog box is displayed. It has three tabs: General, Point of View, and Personal Variables. Note that the Point of View and Personal Variable tabs are disabled until a database connection is identified.

- **Optional**: To identify a database connection file, perform one:
  - Click the Browse button and navigate to an database connection file in the repository. Select the file and click the Open dialog box **OK**.
  - Enter the repository location and file name for a database connection file in the text area.

If you cannot access database connections, See Chapter 12, "Managing Database Connections," or consult your Web Analysis Studio administrator.

Click Connect, to retrieve the latest values.

You may be prompted by the Database Login dialog box, to log on to the data source. Enter logon credentials, and click OK.

When you connect to the data source, the Database File Location text area is disabled, and Connect is converted to Disconnect. If you are using a data source that supports POV, Personal Variables and Alias Tables, these controls are enabled.

- Select an alias table from Alias Table.
- Select one of these options from the Default Logon group:

Default Logon Options	Description
Use User's ID and Password	Connects to the database connection using the Web Analysis Studio user ID and password.
Prompt for User ID and Password	Connects to the database connection by prompting the user for a Web Analysis Studio user ID and password.
Enter User ID and Password	Connects to the database connection using a user ID and password for the database connection, if it varies from the Web Analysis Studio Login parameters. You must enter values in the corresponding text areas.

#### 9 Click OK.

Whenever the specified database connection is used, the selected label mode is also used. Subsequent label mode selections made in the Data Layout or the Dimension Browser overwrite these default settings.

### **POV Definitions**

POV database preferences insert dimensions and members that are of interest to you into the documents of others. POV definitions are defined and activated by database connection.

When a POV is activated, the Use Point of View option in Data Layout and the Document Creation wizard are enabled. All subsequently created and loaded documents use the specified POV until it is deactivated. You can also deactivate use of POV by deselecting the Data Layout Use Point of View option as needed.

POV definitions consist of axes and dimension member selections. The definition is used when documents are created with the activated POV.

When you apply a POV definition to a document, only the dimension member selections are applied. This prevents points of view from automatically arranging non-functioning layouts (such as moving all dimensions to one axis).

If all POV member selections are custom filters, you may not see obvious changes to your document. You can check to see which POV is applied on the View Pane Information Panel tab, Point of View segment.

Using a POV definition is a three part process. First, you must create a POV definition. Next, you must activate the POV definition. Lastly, you must set a document to use the activated POV definition, or create a document that uses it.

Consider these four (4) benefits:

### **Generic and Specific Documents**

Document designers in large enterprises can create a set of generic documents, knowing that individual users can superimpose diverse and user-specific member selections into these documents.

## **Replacing Member Selection Statements**

You can apply the complex calculations and analysis tool definitions of others' documents to the dimensions and members they track, using points of view. This eliminates the need for the user to investigate and recreate these analyses.

## **Default Dimension Layout and Member Selections for New Documents**

When points of view are activated, the document-creation process is simplified. Data Layout is loaded with the dimension member selections designated by the current POV.

### Session-based Points of View

Session-based. POV definitions are saved and recalled as part of individual database connections. This enables them to be used on all documents using the corresponding database connection.

## **Reloading Documents**

You must reload the document for the applied POV definition to be displayed.

### **POV Definitions and Personal Variables**

POV definitions replace all member selections for corresponding dimensions and database connections. Personal variables can instead augment member selections for one dimension.

You can also leverage personal variables in the creation of POV definitions.

See "Creating and Applying Points of View" on page 74.

## **Personal Variables**

Personal variables enable you to define and name complex member selections. After being defined, you can select personal variables when they are presented (with the corresponding dimension and database connection).

## **Generic and Specific Documents**

Other users can create personal variables using matching name, dimension, and database connection that contain the dimensions members that are of interest to them.

This technique enables everyone to create hybrid documents that feature generic and userspecific content.

## **POV Definitions and Personal Variables**

POV definitions replace all member selections for corresponding dimensions and database connections. Personal variables can instead augment member selections for one dimension.

You can also leverage personal variables in the creation of POV definitions. See "Creating and Selecting Personal Variables" on page 73.



## Web Analysis Administration

### **In This Chapter**

Defining the Behavior of Drill Link Reports When the Target Report is Closed	271
Web Analysis Utilities	271
Improving Web Analysis Studio Responsiveness	273
Improving Web Analysis Studio Performance	274
Importing ARU Files to Set User and Active Preferences	274
Rename Utility	281

## **Defining the Behavior of Drill Link Reports When the Target Report is Closed**

When drilling from one report to another using the Drill Link capability, you can define the behavior of what occurs when the target report (the report that was opened when drill linking for the source report) is closed. By default, when any report is closed, the active report becomes the report that was most recently opened.

To set a Drill Link "target" report to return to the "source" report when it is closed, set the following in the EPM System Configurator (CMC) application to "true". The default behavior is "false". This feature applies only to drill link reports; not reports opened through Service Buttons or AIS Drill Through reports.

ReturnToDrillSource=true

## **Web Analysis Utilities**

Topics that explain Web Analysis utilities:

- "Repository Password Encryption Utility" on page 271
- "Web Analysis Configuration Test Servlet" on page 272

## **Repository Password Encryption Utility**

When moving, migrating, and upgrading repositories, users may change the repository user ID and password values listed in the EPM System Configurator (CMC) application. Because these file values are viewable over the Web using the Configuration Test Servlet, a method exists to encrypt password values.

- To change and encrypt repository passwords:
- Stop the application server.
- From release 11.x, property settings are managed via the EPM System Configuration Module.

The location in Workspace is \\WebAnalysis Web-Application (select Properties).

- In the Repos Config section, locate these variables:
  - db.user=<userID>
  - db.password=<encrypted password>
  - db.password-encrypted=true
- Edit values for user ID and password.

Note that the password is not encrypted.

- Change the db.password-encrypted value to false.
- Save your changes.
- Navigate to \\WebAnalysis\conf\ and run EncryptUtil.bat or EncryptUtil.sh.

You may use alternative methods to execute this file. EncryptUtil locates the user ID, password, and encryption variable, encrypts the password, and resets db.passwordencrypted to true.

To review the changes, open the EPM System Configurator (CMC) application.

Restart the application server.

## **Web Analysis Configuration Test Servlet**

Use Web Analysis Configuration Test Servlet to diagnose and resolve connectivity issues. The servlet displays links that centrally report environmental variables and EPM System Configurator (CMC) application parameters, and test connectivity to the class factory, the repository, the external authentication configuration file, and the Essbase driver.

- To launch Configuration Test Servlet:
- Log on to Workspace and click Navigate, then Administer, then Reporting and Analysis and then Web Application.
- Right-click WebAnalysis Web-Application and then select Properties.
- On Debug Configuration tab, set disableConfigServlet to No (the default value is Yes).
- Restart the WebAnalysis Web-application.
- 5 Open a Web browser, and then connect to: http://servername:port/WebAnalysis/config http://servername:port/WebAnalysis/config

Configuration Test Servlet provides links to configuration information:

- "List Environment Variables" on page 273
- "Services Framework Test" on page 273
- "Test Pages for Essbase, Financial Management, and SAP BW ODBO" on page 273

Tip: Use the browser's Back button or the Available Tests link at the page bottom to return to the Configuration Test Servlet home page.

### **List Environment Variables**

The List Environment Variables page provides information about Java system properties and system environment variables, such as user.name, Java.class.path, Java.home, HYPERION\_HOME, LOGONSERVER, and CLASSPATH.

### **Services Framework Test**

The Test ATF Configuration page retrieves information from the repository and tests the repository connection. The last line on the page indicates whether the test executed successfully. If the test failed, a stack trace is displayed to help you troubleshoot problems.

### Test Pages for Essbase, Financial Management, and SAP BW ODBO

The test pages for Essbase, Financial Management, and SAP BW ODBO, provide this configuration information:

- **ADM Environment Variables**
- ADM Property File Locations (click a link to view the property file)
- **ADM Jar Locations**
- Version Information

You use these pages to test your connectivity (using ADM) to Essbase, Oracle Hyperion Financial Management, and SAP BW ODBO.

## **Improving Web Analysis Studio Responsiveness**

- To improve the performance and applet load time of Web Analysis Studio through Windows Control Panel, increase the maximum amount of memory allocated to the plug-in.
- Select Start, then Control Panel, then Java Plug-In to open the Java plug-in console.

**Note:** If multiple Java Plug-in versions are installed, select the version that Web Analysis Studio uses.

Select the Advanced tab, and add these parameters to Java Runtime Parameters:

For information on parameters, see the JRE documentation

## **Improving Web Analysis Studio Performance**

McAfee virus scans on servers and clients decrease performance. McAfee's Internet WebScanX, which searches internet files for viruses, scans AnalyzerClient.jar, which resides in the internet cache of the PC, every time Oracle Hyperion Web Analysis Studio is launched.

- To improve Web Analysis Studio performance:
- 1 Run the SysInternal Filemon program (from http://www.sysinternals.com) to determine which file analyzers are using and exclude those folder and files.
- 2 Disable WebScanx on AnalyzerClient.jar.
- 3 Disable Allow Scanning Inside Archives.

## **Importing ARU Files to Set User and Active Preferences**

Web Analysis user preferences can be imported from an .ARU (XML format) file using a command-line utility.

The supporting import functionalities are discussed in these topics:

- "Creating Personal Variables" on page 276
- "Removing Personal Variables" on page 276
- "Creating POV Definitions" on page 277
- "Removing POV Definitions" on page 278
- "Adding Personal Database Connections" on page 278
- "Setting User Preferences" on page 279
- "Setting Active Preferences" on page 258

Note: Member names that contain special characters need modification; for example, <member Name="P&O" /> should be <member Name="P&amp ; O" />

## **Processing Order**

The ARU file is processed in this order:

- 1. Add database connection.
- 2. Remove Personal Variables
- 3. Remove POV
- 4. Add/replace Personal Variables

- 5. Add/replace POV
- 6. Define user preferences

## **Importing ARU Files**

To import and execute an ARU file using the command line, enter this command:

```
ARUUtil.bat [ServerURL] [UserID] [ImportFile] [LogFile]
```

All arguments needed for the ARUUtil.bat are defined in ARUImport.properties.

Note: ARUUtil.bat (and .sh) is located in BIPLUS\_HOME/bin and ARUImport.properties is located in BIPLUS\_HOME/common/config.

Here is sample content of ARUImport.properties:

ServerURL=http://localhost:16000/WebAnalysis/processor UserID=hyper1 Password=hyper1 ImportFile=D:\Welcome\createluser.xml LogFile=d:\Welcome\Import.log Encryption=false

Property	Description
ServerURL	URL of started Web Analysis
UserID	Provisioned user name
Password	Provisioned user password
ImportFile	File path to import
LogFile	File path to log status messages

**Note:** Login credentials of a user with administrators privileges must be used.

## **ARU Import File Format Supported Tags**

- AnalyzerAdmin
- ModifyUsers
- User
- AddPersonalVariable
- Member
- AddPointOfView
- AxisSelections

- Dimension
- RemovePersonalVariable
- RemovePointOfView
- Settings
- Database

Note: For database connection references in the 'Database' tag, when creating Point of View and Personal Variables, users need to have either a link to the database connection or the database connection file in their database folder (for example, Users/
<username>/Databases). Alternately, the 'Database' tag can contain a full folder path reference to the database connection file name. For example: Database=''/
Users/bi\_admin/Databases/darobert2\_sample\_basic''

## **Creating Personal Variables**

To create a Personal Variable, use this file format:

```
<?xml version="1.0" encoding="UTF-8"?>
<AnalyzerAdmin>
<ModifyUsers>
<User LoginID="hyper1">
<AddPersonalVariable Name="MarketPV" Database="DB_connection_name" Dimension="Market">
<Member Name="Market" SelectionMode="CHILDREN"/>
<Member Name="East" SelectionMode="CHILDREN"/>
</AddPersonalVariable>
</User>
</ModifyUsers>
</AnalyzerAdmin>
```

User and LoginID define the user login for which the Personal Variable is added. If a database connection exist with a specified name (see Database) for a specified user, a Personal Variable is added. The database connection file name is formed from the Database property by replacing «:» on «\_». The connection file is searched in the Database folder of the specified user. If a connection file does not exist, the operation aborts. If a Personal Variable exists for the database connection, it is replaced by the new definition.

AddPersonalVariable initiates a request to create a Personal Variable. Member identifies the members within the dimension that make up the Personal Variable, and the selection mode for each member. Selection modes are: MEMBER, CHILDREN, DESCENDANT, PARENT, ANCESTOR, SIBLING, DIMBOTTOM, DIMTOP, LEVEL, GENERATION, and PREVIOUS. Default selection mode is MEMBER.

### **Removing Personal Variables**

To remove a Personal Variable, use this file format:

```
<?xml version="1.0" encoding="UTF-8"?>
<AnalyzerAdmin>
<ModifyUsers>
```

```
<User LoginID="vefim">
<RemovePersonalVariable Name="MarketPV" Database="DB_connection_name"/>
</User>
</ModifyUsers>
</AnalyzerAdmin>
```

RemovePersonalVariable deletes the Personal Variable named MarketPV which is defined against database *DB\_connection\_name:Sample:Basic*.

Name defines the name of the Personal Variable to delete. Database defines the database connection file name.

## **Creating POV Definitions**

To create a POV, use this file:

```
<?xml version="1.0" encoding="UTF-8"?>
<AnalyzerAdmin>
<ModifyUsers>
<User LoginID="vefim">
<AddPointOfView Name="BatchPOV" Database="DB_connection_name" Active="True">
<AxisSelections Axis="Columns">
<Dimension Name="Market">
<Member Name="East"/>
<Member Name="West" SelectionMode="CHILDREN"/>
</Dimension>
<Dimension Name="Product">
<Member Name="Product" SelectionMode="CHILDREN"/>
</Dimension>
</AxisSelections>
<AxisSelections Axis="Rows">
<Dimension Name="Year">
<Member Name="Year" SelectionMode="CHILDREN"/>
</Dimension>
</AxisSelections>
<AxisSelections Axis="Pages">
<Dimension Name="Scenario">
<Member Name="Scenario" SelectionMode="CHILDREN"/>
</Dimension>
</AxisSelections>
</AddPointOfView>
</User>
</ModifyUsers>
</AnalyzerAdmin>
```

AddPointOfView initiates a request to create a POV. The Name and Database name for the POV must be provided. The user may optionally indicate whether this POV should be active. Default Active value is False. If a POV of the same name exists for the database connection, it is replaced by the new definition.

AxisSelections identifies the axis to which the dimension selections are to be applied. Axes are Rows, Columns, Pages, and Filters. Default axis is Filters.

Dimension defines the dimension to be placed on the axis.

Member identifies the members within the specified dimension to be placed on the axis. Selection modes are: MEMBER, CHILDREN, DESCENDANT, PARENT, ANCESTOR, SIBLING, DIMBOTTOM, DIMTOP, LEVEL, GENERATION, and PREVIOUS. The default selection mode is MEMBER.

## **Removing POV Definitions**

To remove a POV definition, use this file format:

```
<?xml version="1.0" encoding="UTF-8"?>
<AnalyzerAdmin>
<ModifyUsers>
<User LoginID="vefim">
<RemovePointOfView Name="123" Database="DB_connection_name"/>
</User>
</ModifyUsers>
</AnalyzerAdmin>
```

RemovePointOfView requests to delete the POV named 123 which is defined against database DB\_connection\_name:Sample:Basic.

## **Adding Personal Database Connections**

To add a personal database connection, use this file format:

```
<?xml version="1.0" encoding="UTF-8"?>
<AnalyzerAdmin>
<ModifyUsers>
<User LoginID="hyper1">
<Database Name="DBName" Server="epmsd030" Database="Sample" Cube="Basic"</pre>
AliasTable="Long Names" Type="1" User="admin" Password="password" LoginMode="1">
</User>
</ModifyUsers>
</AnalyzerAdmin>
```

Database requests to add a database connection. If a database connection file with the same name exists, the operation is aborted.

Database Attributes	Description	Permitted values	Example
Name	Connection File name—File is created in /Users/ user_name/Databases/.  user_name—User's name, defined in tag User. For this, user connection is created.		
Server	Essbase server host name		
Database	Application Name		
Cube	Cube Name		
AliasTable	Which alias to use		

Database Attributes	Description	Permitted values	Example
Туре	Type of connection to create. Only Analytic Services connections can be created.	1	
User	User's login for connection		
Password	Password for connection		
LoginMode	Login mode of DB connection	1 - Use User's ID and Password;	1 - Example, ["hyper1", "hyper1"]
		2 - Prompt for User ID and Password;	2 – always show dialog "Database Logon"
		3 - Enter User ID and Password	3 - Use specified in User, Password properties values

## **Setting User Preferences**

**Note:** Some user preferences cannot be imported.

Import user preferences using this syntax:

```
<?xml version="1.0" encoding="UTF-8"?>
<AnalyzerAdmin>
<ModifyUsers>
<User LoginID="hyper1">
<Settings MissingZero="0" MissingText="n/a" PageComboBoxesStyle="0" ShowInfoPanel="0"</pre>
ShowFilterPanel="1" ShowToolbar="1" ShowMenu="0" DrillType="0" DrillMethod="1"
Wallpaper="" TileWallpaper="1" StretchWallpaper="0"/>
</User>
</ModifyUsers>
</AnalyzerAdmin>
```

### **Supported Preferences**

- DrillMethod
- UseGridAPI
- ShowCurrency
- Wallpaper
- SuppressMissing
- ShowGridLines
- MissingZero
- MissingText
- HomePage

- DefaultView
- ShowInfoPanel
- ShowFilterPanel
- ShowToolbar
- ShowMenu
- PageComboBoxesStyle
- DrillType

## **Setting Active Preferences**

Each user's Web Analysis preference file is located under /Users/username/Profiles and is invisible to all users. An administrator can copy, paste and maintain all user preference files. In addition, the /Users/{Profiles} folder is the common profiles directory, from which users can select any preference file to use as their active preference.

To set active preferences for a user during ARU import, the repository location of the file must be specified.

To set active preferences for a user, use this syntax:

```
<?xml version="1.0" encoding="UTF-8"?>
  <AnalyzerAdmin>
    <ModifyUsers>
      <User LoginID="PersParamEditor1">
        <SetGroupPrefs Name="/Users/&lt;Profiles&gt;/GlobalAdmin2Prefs4" />
      <User LoginID="Analyst3">
        <SetGroupPrefs Name="/Users/&lt;Profiles&gt;/GlobalAdmin2Prefs4" />
      <User LoginID="DataEditor1">
        <SetGroupPrefs Name="/Users/&lt;Profiles&gt;/GlobalAdmin2Prefs4" />
      <User LoginID="DataSourcePublisher1">
        <SetGroupPrefs Name="/Users/&lt;Profiles&gt;/GlobalAdmin2Prefs4" />
      </User>
    </ModifyUsers>
  </AnalyzerAdmin>
<SetGroupPrefs Name="\Users\<Profiles>\group_prefs1"/>
```

### **Notes**

- In XML files, you must use < instead of < and &gt; instead of >.
- 2. If more than one SetGroupPrefs element is specified for a user, the last preference file specified is established for that user.

## **Rename Utility**

The Rename Utility is a standalone application designed to update objects in a Web Analysis repository based on the data source metadata changes. For example, if a member name, and/or dimension name changes in an Essbase® or Essbase cube, the utility searches the repository and changes all objects (such as documents and database connections) to reflect the metadata changes. The metadata change mapping must be created in a map file, as there is no direct link to the data source to detect the changes.

Please note, the utility supports only Essbase and Essbase data sources.

These objects are updated:

- Documents
- Database formatting
- Essbase and Essbase database connections
- Personal variable definitions
- POV definitions

These metadata changes are supported:

- Renaming references to existing dimensions (name and alias/description)
- Renaming references to existing members (name and alias/description)
- Adding references to new dimensions (default member selected)

**Note:** The Rename Utility installer is not included as part of the Web Analysis installer. See "Rename Utility Installation" on page 282.

## **Rename Utility Important Considerations**

- The Rename Utility modifies the content of various tables within the Web Analysis repository. You must back up *all* repositories before running this utility.
- The map file must correctly reflect old and new mapping names. If errors exist, these results may occur
  - Errors in old names:
    - No member is found; nothing is renamed
    - The wrong member is found; the wrong member is renamed
  - o Errors in new names:
    - A name does not match a member. When the document is executed, an error message is displayed, and the member is removed from the document.
    - (A name matches a member (the wrong member). When the document is executed, an error message is not displayed, but the wrong member is selected).

## **Rename Utility Files**

The Rename Utility files can be executed from the folder in which the utility resides, which is <code>installation\_folder\renamer</code>.

Table 3 Rename Utility Folder Structure

Files	Description
\renamer	Contains all necessary files to execute the Rename Utility
AnalyzerResource.jar	From the current install
AnalyzerServer_*.jar	
AnalyzerServer.jar	
sqlbuilder.jar	Utility dependency
renamer-map.xml	Map file used to define all of the dimensions and members to rename; see the "Rename Utility Map File" on page 283
Renamer.properties	Provides default choices to the input fields in the Rename Utility; see "Renamer.properties" on page 287
renamer-services.xml	Defines ATF services by the Rename Utility.
RenameUtil.bat	Utility start scripts for Windows or UNIX platforms, respectively
RenameUtil.sh	
\renamer\renamer	Contains repository profiles used to connect to the supported database types
common.profile	
db2.profile	
mssqldb.profile	
oracle.profile	

## **Rename Utility Installation**

- ➤ To install the Rename Utility:
- 1 Back up all repositories before using the Rename Utility.
- 2 Install Web Analysis.
- 3 Uncompress rename\_utility.zip to the Rename Utility folder (for example, C:\renamer).
- 4 Copy these files from the Web Analysis WEB-INF\lib folder to the Rename Utility folder:
  - AnalyzerServer.jar
  - AnalyzerResource\_\*.jar
  - log4j-1.2.8.jar

- Verify that the JAVA\_HOME environment variable exists and points to a Java 1.4 runtime home folder (for example, C:\jdk1.4.2).
  - You can also edit RenameUtil.bat or RenameUtil.sh to set the JAVA\_HOME environment.
- **Optional:** Edit Renamer.properties to set the default choices for running the Rename Utility as described in "Renamer.properties" on page 287.
- 7 Launch the start script (RenameUtil.bat or RenameUtil.sh).

## **Rename Utility Map File**

The Rename Utility map file defines the dimensions and members to be renamed in the repository. It is an XML file that defines the complete logical path to each dimension and member. Here is a sample map file (with line numbers) along with a description of each section:

```
[01] <map name="Rename Map 01">
[02]
     <server name="essbase9x"</pre>
[03]
        <serverAlias>essbase9x.hyperion.comserverAlias>essbase9x.hyperion.com>
[04]
        <application name="Sample">
[05]
           <database name="Basic">
[06]
             <dim oldName="Year" newName="NewYear" />
[07]
[80]
            <dim oldName="Market" newName="NewMarket"</pre>
[09]
               oldAlias="Market" newAlias="My New Market">
[10]
               <member oldName="South" newName="NewSouth"/>
[11]
               <member oldName="East" newName="NewEast"/>
[12]
               oldAlias="Eastern" newAlias="New Eastern">
[13]
[14]
            </dim>
[15]
[16]
            <newDim name="NewDim" alias="NewDim Alias" />
[17]
            <newDim name="Attr" alias="Attribute" parentDim="product">
[18]
[19]
[20]
             <newDim name="Features" alias="Prod Features">
               <attrDim name="Attr1"/>
[21]
               <attrDim name="Attr2"/>
[22]
[23]
               <attrDim name="Attr3"/>
[24]
             </newDim>
[25]
           </database>
[26]
[27]
        </application>
[28]
     </server>
[29]
[30]
     <server name="server2">
[31]
        <...>
[xx] </server>
[xy]
[xz] < /map>
```

### map Element

The topmost element of the map file must be the <map> element shown on line [01]. It must have a name attribute, which can be any text enclosed in quotes. There can be only one <map> element in a map file. This element is used internally to contain the list of servers included in this map file. It can contain only one or more <server> elements.

#### server Element

This element identifies an Essbase server that has renamed dimensions or members. Examples are shown on lines [02] and [30]. As shown in the example, there can be multiple server elements in a map file. It has the single attribute name which is required. This name must match the server name in the Essbase database connection stored in the Web Analysis repository. No DNS or hosts lookup is performed, and no IP address translation is done. Thus, <server name="127.0.0.1"> is not the same as <server name="localhost">. The server element can contain only one or more application elements.

#### serverAlias Element

This element enables the user to specify alternate names that identify the Essbase server. For example, the server, ess9x might also be known as ess9x.hyperion.com,172.27.31.126, or localhost. Using serverAlias elements in the map file allows the dimension and member mappings for a server to be applied to that server, regardless of how it is referenced in the repository. An example is shown on line [03]. This example associates all dimensions and members for the server essbase9x with the alternate name essbase9x.hyperion.com. The serverAlias element does not have attributes and its body specifies the server alias.

#### application Element

This element identifies a specific instance of an Essbase application. An example is shown on line [04]. The application element has one attribute, name, which is required. This name must match the application name in the Essbase database connection stored in the Web Analysis repository. The application element can contain only one or more database elements.

#### database Element

This element identifies a specific instance of an Essbase database. An example is shown on line [05]. The database element has one attribute, name, which is required. This name must match the database name in the Essbase database connection stored in the Web Analysis repository. The database element must contain one or more dim or newDim elements.

#### dim Element

This element identifies a specific instance of an Essbase dimension within a unique database. Examples are shown on lines [07] and [09]. The dim element must contain the attribute oldName to identify the dimension. There are three optional attributes for each element:

- newName—New name for this dimension
- oldAlias—Current alias for this dimension
- newAlias—New alias for this dimension

If there is no newName or newAlias attribute for the dimelement, it is not renamed. An example of this could be the case when a dimension name did not change, but members within that dimension were renamed. The oldAlias attribute should be included if it is defined in the outline, so that top level member selections using the alias can be identified. This is necessary because in Essbase, the top level member of a dimension uses the dimension name and alias. Because members may be stored by name or alias in repository objects, oldName and oldAlias must be included for all dimelements. This element can contain zero or moremember elements only. This would be the case if only the dimension name or alias changed, but no members in that dimension were renamed.

#### member Element

This element identifies a specific instance of an Essbase member within a unique dimension. Examples are shown on lines [11] and [12]. The member element must contain the attribute oldName to identify the member. There are three optional attributes for each element:

- newName—New name for this member
- oldAlias—Current alias for this member
- newAlias—New alias for this member

The oldAlias attribute should be included if it is defined in the outline, so that member selections using the alias can be identified. Because members may be stored by name or alias in repository objects, oldName and oldAlias must be included for all member elements. This element may not contain other elements.

#### newDim Element

This element identifies a specific instance of a new Essbase dimension within a unique database. The newDim element must contain the attribute name to uniquely name the dimension. An optional attribute alias may exist to define an alias for this dimension. An example of this is shown on line [16].

If the dimension is an attribute dimension, the required XML attribute parentDim must be included in the element to associate the attribute dimension with its parent dimension. An example of this is shown above on line [18].

Finally, if the dimension has associated attribute dimensions, they must be defined in attrDim elements. This is the only case when the newDim element may contain child elements, and there can be multiple attrDim elements in it.

### attrDim Element

This element identifies a specific instance of an Oracle Essbase attribute dimension to associate with a new dimension. Examples are shown on lines [21], [22], and [23]. The attrDim element must contain the attribute name to uniquely identify the attribute dimension. This element cannot contain other elements.

## **Using the Rename Utility**

- To use the Rename Utility:
- Make a backup of the Web Analysis repository.
- Create a map file that defines old and new values in the data source that need to be replaced in the Web Analysis repository. See "Rename Utility Map File" on page 283.
- 3 Launch the start script (RenameUtil.bat or RenameUtil.sh).
- Select the Repository Type (Microsoft SQL Server, DB2, MySQL or Oracle).
- Enter the necessary RDBMS Repository connection fields:
  - Server Name
  - Database Name / Tablespace Name (Oracle)
  - Port Number
  - SID (Oracle only)
  - Web Analysis User
  - Oracle Hyperion Web Analysis Password
- Select the map file location.
- Click Finish.

The Confirm tab is displayed with connection confirmation and map file verification.

Click Rename.

A confirmation message is displayed.

Click Yes to proceed with processing.

The process begins with all activity listed in the Confirm tab. For example:

```
Preparing rename mapping rules...
Reading rename mappings from renamer-map.xml
Building list of rename mappings.
Processing Web Analysis Reports
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/Product Sales" (ID =
214)
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/Product
Profitability" (ID = 217)
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/Regional Analysis" (ID =
220)
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/KPI Scorecard" (ID = 223)
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/Expense Analysis" (ID =
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/State Rankings" (ID =
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/High\Low States" (ID =
232)
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/Margin Chart" (ID = 235)
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/Product Share" (ID = 238)
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/Product Budget" (ID =
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/Sales Forecast" (ID =
244)
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/Profit vs Sales" (ID =
247)
Report "/Groups/Everyone/Reports/_Sample Reports/Samples/KPI Details" (ID = 250)
```

## **Renamer.properties**

The Renamer.properties file provides the default choices displayed by the Rename Utility in the Hyperion Web Analysis Renamer dialog box.

Use of Renamer.properties is optional; it eliminates the need to enter information that is repeated each time the utility is run. If properties are not included in Renamer.properties, the corresponding input fields are left blank. Users can enter values for fields from within the Renamer Utility.Renamer.properties provides descriptive comments and sample entries for each property, and contains these variables:

Variable Name	Description
# MapFile	Map file name
# ReposServer	Server name where the repository exist
# ReposType	Type of repository selected
# ReposSID	Repository SID
# ReposName	Repository database name
# ReposUser	User name
# ReposPassword	User password

## Glossary

! See bang character.

**#MISSING** See missing data.

**access permissions** A set of operations that a user can perform on a resource.

**accessor** Input and output data specifications for datamining algorithms.

**account blocking** The process by which accounts accept input data in the consolidated file. Blocked accounts do not receive their value through the additive consolidation process.

**account eliminations** Accounts which have their values set to zero in the consolidated file during consolidation.

**account type** A property that determines how an account's value flows over time and its sign behavior. Account type options can include expense, income, asset, liability, and equity.

**accountability map** A visual, hierarchical representation of the responsibility, reporting, and dependency structure of the accountability teams (also known as critical business areas) in an organization.

**active service** A service whose Run Type is set to Start rather than to Hold.

**active-active high availability system** A system in which all the available members can service requests, and no member is idle. An active-active system generally provides more scalability options than an active-passive system. Contrast with active-passive high availability system.

**active-passive high availability system** A system with active members, which are always servicing requests, and passive members that are activated only when an active member fails. Contrast with active-active high availability system.

**activity-level authorization** Defines user access to applications and the types of activities they can perform on applications, independent of the data that will be operated on.

**ad hoc report** An online analytical query that an end user creates dynamically.

**adapter** Software that enables a program to integrate with data and metadata from target and source systems.

**adaptive states** Interactive Reporting Web Client level of permission.

adjustment See journal entry.

**Advanced Relational Access** The integration of a relational database with an Essbase multidimensional database so that all data remains in the relational database and is mapped to summary-level data in the Essbase database.

**agent** An Essbase server process that starts and stops applications and databases, manages connections from users, and handles user-access security. The agent is referred to as ESSBASE.EXE.

aggregate cell A cell comprising several cells. For example, a data cell that uses Children(Year) expands to four cells containing Quarter 1, Quarter 2, Quarter 3, and Quarter 4 data.

**aggregate function** A type of function, such as sum or calculation of an average, that summarizes or performs analysis on data.

**aggregate limit** A limit placed on an aggregated request line item or aggregated metatopic item.

aggregate storage database The database storage model designed to support large-scale, sparsely distributed data which is categorized into many, potentially large dimensions. Upper level members and formulas are dynamically calculated, and selected data values are aggregated and stored, typically with improvements in overall aggregation time.

**aggregate view** A collection of aggregate cells based on the levels of the members within each dimension. To reduce calculation time, values are pre-aggregated and stored as aggregate views. Retrievals start from aggregate view totals and add up from there.

**aggregation** The process of rolling up and storing values in an aggregate storage database; the stored result of the aggregation process.

**aggregation script** In aggregate storage databases only, a file that defines a selection of aggregate views to be built into an aggregation.

**alias table** A table that contains alternate names for members.

**alternate hierarchy** A hierarchy of shared members. An alternate hierarchy is based upon an existing hierarchy in a database outline, but has alternate levels in the dimension. An alternate hierarchy allows the same data to be seen from different points of view.

**ancestor** A branch member that has members below it. For example, the members Qtr2 and 2006 are ancestors of the member April.

appender A Log4j term for destination.

**application** 1) A software program designed to run a specific task or group of tasks such as a spreadsheet program or database management system; 2) A related set of dimensions and dimension members that are used to meet a specific set of analytical requirements, reporting requirements, or both.

**application administrator** A person responsible for setting up, configuring, maintaining, and controlling an application. Has all application privileges and data access permissions.

**application currency** The default reporting currency for the application.

**Application Migration Utility** A command-line utility for migrating applications and artifacts.

application server cluster A loosely joined group of application servers running simultaneously, working together for reliability and scalability, and appearing to users as one application server instance. See also vertical application cluster and horizontal application cluster.

**area** A predefined set of members and values that makes up a partition.

**arithmetic data load** A data load that performs operations on values in the database, such as adding 10 to each value.

**artifact** An individual application or repository item; for example, scripts, forms, rules files, Interactive Reporting documents, and financial reports. Also known as an object.

**assemblies** Installation files for EPM System products or components.

**asset account** An account type that stores values that represent a company's assets.

**assignment** The association of a source and destination in the allocation model that controls the direction of allocated costs or revenue flow.

**asymmetric topology** An Oracle Fusion Middleware Disaster Recovery configuration that is different across tiers on the production site and standby site. For example, an asymmetric topology can include a standby site with fewer hosts and instances than the production site.

**attribute** A characteristic of a dimension member. For example, Employee dimension members may have attributes of Name, Age, or Address. Product dimension members can have several attributes, such as a size and flavor.

**attribute association** A relationship in a database outline whereby a member in an attribute dimension describes a characteristic of a member of its base dimension. For example, if product 100-10 has a grape flavor, the product 100-10 has the Flavor attribute association of grape. Thus, the 100-10 member of the Product dimension is associated with the Grape member of the Flavor attribute dimension.

Attribute Calculations dimension A system-defined dimension that performs these calculation operations on groups of members: Sum, Count, Avg, Min, and Max. This dimension is calculated dynamically and is not visible in the database outline. For example, using the Avg member, you can calculate the average sales value for Red products in New York in January.

**attribute dimension** A type of dimension that enables analysis based on the attributes or qualities of dimension members.

**attribute reporting** A reporting process based on the attributes of the base dimension members. See also base dimension.

**attribute type** A text, numeric, Boolean, date, or linked-attribute type that enables different functions for grouping, selecting, or calculating data. For example, because the Ounces attribute dimension has the type numeric, the number of ounces specified as the attribute of each product can be used to calculate the profit per ounce for that product.

**authentication** Verification of identity as a security measure. Authentication is typically based on a user name and password. Passwords and digital signatures are forms of authentication.

**authentication service** A core service that manages one authentication system.

**auto-reversing journal** A journal for entering adjustments that you want to reverse in the next period.

**automated stage** A stage that does not require human intervention; for example, a data load.

**axis** 1) A straight line that passes through a graphic used for measurement and categorization; 2) A report aspect used to arrange and relate multidimensional data, such as filters, pages, rows, and columns. For example, for a data query in Simple Basic, an axis can define columns for values for Qtr1, Qtr2, Qtr3, and Qtr4. Row data would be retrieved with totals in the following hierarchy: Market, Product.

**backup** A duplicate copy of an application instance.

**balance account** An account type that stores unsigned values that relate to a particular time.

**balanced journal** A journal in which the total debits equal the total credits.

bang character (!) A character that terminates a series of report commands and requests information from the database. A report script must be terminated with a bang character; several bang characters can be used within a report script.

**base currency** The currency in which daily business transactions are performed.

**base dimension** A standard dimension that is associated with one or more attribute dimensions. For example, assuming products have flavors, the Product dimension is the base dimension for the Flavors attribute dimension.

**base entity** An entity at the bottom of the organization structure that does not own other entities.

**batch calculation** Any calculation on a database that is done in batch; for example, a calculation script or a full database calculation. Dynamic calculations are not considered to be batch calculations.

**batch file** An operating system file that can call multiple ESSCMD scripts and run multiple sessions of ESSCMD. On Windows-based systems, batch files have BAT file extensions. On UNIX, batch files are written as a shell script.

**Batch Loader** An FDM component that enables the processing of multiple files.

**batch POV** A collection of all dimensions on the user POV of every report and book in the batch. While scheduling the batch, you can set the members selected on the batch POV.

batch processing mode A method of using ESSCMD to write a batch or script file that can be used to automate routine server maintenance and diagnostic tasks. ESSCMD script files can execute multiple commands and can be run from the operating system command line or from within operating system batch files. Batch files can be used to call multiple ESSCMD scripts or run multiple instances of ESSCMD.

**block** The primary storage unit which is a multidimensional array representing the cells of all dense dimensions.

**block storage database** The Essbase database storage model categorizing and storing data based on the sparsity of data values defined in sparse dimensions. Data values are stored in blocks, which exist only for sparse dimension members for which there are values.

**Blocked Account** An account that you do not want calculated in the consolidated file because you want to enter it manually.

**book** 1) In Financial Reporting, a container that holds a group of similar documents. Books may specify dimension sections or dimension changes; 2) In Data Relationship Management, a collection of exports that can be run together as a group. Export results can be combined together or output separately.

**book POV** The dimension members for which a book is run.

**bookmark** A link to a reporting document or a Web site, displayed on a personal page of a user. The types of bookmarks are My Bookmarks and image bookmarks.

**bounding rectangle** The required perimeter that encapsulates the Interactive Reporting document content when embedding Interactive Reporting document sections in a personal page, specified in pixels for height and width or row per page.

**broadcast message** A simple text message sent by an administrator to a user who is logged on to a Planning application. The message details information such as system availability, notification of application refresh, or application backups.

**build method** A method used to modify database outlines. Choice of a build method is based on the format of data in data source files.

**business process** A set of activities that collectively accomplish a business objective.

**business rules** Logical expressions or formulas that are created within an application to produce a desired set of resulting values.

**cache** A buffer in memory that holds data temporarily.

**calc script** A set of commands that define how a database is consolidated or aggregated. A calculation script may also contain commands that specify allocation and other calculation rules separate from the consolidation process.

**Calculated Accounts** Accounts with formulas that you cannot alter. These formulas are fixed to maintain the accounting integrity of the model that you are building. For example, the formula for Net Income, a Calculated Account, is modeled into Strategic Finance and cannot be changed in historical or forecast periods.

**calculated member in MaxL DML** A member designed for analytical purposes and defined in the optional WITH section of a MaxL DML query.

**Calculation Manager** A module of Enterprise Performance Management Architecture (EPMA) that Planning and Financial Management users can use to design, validate, and administrate business rules in a graphical environment. *c* 

**calculation status** A consolidation status that indicates that some values or formula calculations have changed. You must reconsolidate to get the correct values for the affected entity.

**calendar** User-defined time periods and their relationship to each other. Q1, Q2, Q3, and Q4 comprise a calendar or fiscal year.

**cascade** The process of creating multiple reports for a subset of member values.

**Catalog pane** An area that displays a list of elements available to the active section. If Query is the active section, a list of database tables is displayed. If Pivot is the active section, a list of results columns is displayed. If Dashboard is the active section, a list of embeddable sections, graphic tools, and control tools are displayed.

**categories** Groupings by which data is organized. For example, Month.

cause and effect map A map that depicts how the elements that form your corporate strategy relate and how they work together to meet your organization's strategic goals. A Cause and Effect map tab is automatically created for each Strategy map.

**CDF** See custom-defined function.

**CDM** See custom-defined macro.

**cell** 1) The data value at the intersection of dimensions in a multidimensional database; the intersection of a row and a column in a worksheet; 2) A logical group of nodes belonging to one administrative domain.

**cell note** A text annotation for a cell in an Essbase database. Cell notes are a type of LRO.

**CHANGED status** Consolidation status that indicates data for an entity has changed.

**chart template** A template that defines the metrics to display in Workspace charts.

**child** A member with a parent above it in the database outline.

**choice list** A list of members that a report designer can specify for each dimension when defining the report's point of view. A user who wants to change the point of view for a dimension that uses a choice list can select only the members specified in that defined member list or those members that meet the criteria defined in the function for the dynamic list.

**clean block** A data block in which the database is fully calculated, if a calculation script calculates all dimensions at once, or if the SET CLEARUPDATESTATUS command is used in a calculation script.

**cluster** An array of servers or databases that behave as a single resource which share task loads and provide failover support; eliminates one server or database as a single point of failure in a system.

**cluster interconnect** A private link used by a hardware cluster for heartbeat information, to detect node failure.

cluster services Software that manages cluster member operations as a system. With cluster services, you can define a set of resources and services to monitor through a heartbeat mechanism between cluster members and to move these resources and services to a different cluster member as efficiently and transparently as possible.

**clustered bar charts** Charts in which categories are viewed side-by-side; used only with vertical bar charts.

code page A mapping of bit combinations to a set of text characters. Different code pages support different sets of characters. Each computer contains a code page setting for the character set requirements of the language of the computer user. In the context of this document, code pages map characters to bit combinations for non-Unicode encodings. See also encoding.

**column** In Data Relationship Management, a field of data associated with an import source or the results of a query, compare, validation, or export.

**committed access** An Essbase Kernel Isolation Level setting that affects how Essbase handles transactions. Under committed access, concurrent transactions hold long-term write locks and yield predictable results.

**computed item** A virtual column (as opposed to a column that is physically stored in the database or cube) that can be calculated by the database during a query, or by Interactive Reporting Studio in the Results section. Computed items are calculations of data based on functions, data items, and operators provided in the dialog box and can be included in reports or reused to calculate other data.

**connection file** See Interactive Reporting connection file (.oce)

**consolidated file (Parent)** A file into which all of the business unit files are consolidated; contains the definition of the consolidation.

**consolidation** The process of aggregating data from dependent entities to parent entities. For example, if the dimension Year consists of the members Qtr1, Qtr2, Qtr3, and Qtr4, its consolidation is Year.

**consolidation file (\*.cns)** A graphical interface that enables you to add, delete, or move Strategic Finance files in the consolidation process using either a Chart or Tree view. It also enables you to define and modify the consolidation.

consolidation rule The rule that is executed during the consolidation of the node of the hierarchy. This rule can contain customer-specific formulas appropriate for the correct consolidation of parent balances. Elimination processing can be controlled within these rules.

**content** Information stored in the repository for any type of file.

**content browser** A component that earbles users to browse and select content to be placed on a Workspace Page.

**context variable** A variable that is defined for a particular task flow to identify the context of the taskflow instance.

**contribution** The value added to a parent from a child entity. Each child has a contribution to its parent.

**controls groups** Groupings used in FDM to maintain and organize certification and assessment information, especially helpful for meeting Sarbanes-Oxley requirements.

conversion rate See exchange rate.

**cookie** A segment of data placed on your computer by a Web site.

**correlated subqueries** Subqueries that are evaluated once for every row in the parent query; created by joining a topic item in the subquery with a topic in the parent query.

**critical business area (CBA)** An individual or a group organized into a division, region, plant, cost center, profit center, project team, or process; also called accountability team or business area.

**critical success factor (CSF)** A capability that must be established and sustained to achieve a strategic objective; owned by a strategic objective or a critical process and is a parent to one or more actions.

crosstab reporting Reporting that categorizes and summarizes data in table format. The table cells contain summaries of the data that fit within the intersecting categories. For example, a crosstab report of product sales information could show size attributes, such as Small and Large, as column headings and color attributes, such as Blue and Yellow, as row headings. The cell in the table where Large and Blue intersect could contain the total sales of all Blue products that are sized Large.

**cube** A block of data that contains three or more dimensions. An Essbase database is a cube.

**cube deployment** In Essbase Studio, the process of setting load options for a model to build an outline and load data into an Essbase application and database.

**cube schema** In Essbase Studio, the metadata elements, such as measures and hierarchies, representing the logical model of a cube.

**currency conversion** A process that converts currency values in a database from one currency into another. For example, to convert one U. S. dollar into the European euro, the exchange rate (for example, 0.923702) is multiplied by the dollar (1\* 0.923702). After conversion, the European euro amount is .92.

**Currency Overrides** A feature allowing the selected input method for any input period to be overridden to enable input of that period's value as Default Currency/Items. To override the input method, enter a pound sign (#) before or after the number.

**currency partition** A dimension type that separates local currency members from a base currency, as defined in an application. Identifies currency types, such as Actual, Budget, and Forecast.

custom calendar Any calendar created by an administrator.

**custom dimension** A dimension created and defined by users. Channel, product, department, project, or region could be custom dimensions.

**custom property** A property of a dimension or dimension member that is created by a user.

**custom report** A complex report from the Design Report module, composed of any combination of components.

**custom-defined function (CDF)** Essbase calculation functions developed in Java and added to the standard Essbase calculation scripting language using MaxL. See also custom-defined macro.

**custom-defined macro (CDM)** Essbase macros written with Essbase calculator functions and special macro functions. Custom-defined macros use an internal Essbase macro language that enables the combination of calculation functions and they operate on multiple input parameters. See also custom-defined function.

**cycle through** Perform multiple passes through a database while calculating it.

**dashboard** A collection of metrics and indicators that provide an interactive summary of your business. Dashboards enable you to build and deploy analytic applications.

**data cache** A buffer in memory that holds uncompressed data blocks.

data cell See cell.

data file cache A buffer in memory that holds compressed data (PAG) files.

**data form** A grid display that enables users to enter data into the database from an interface such as a Web browser, and to view and analyze data or related text. Certain dimension member values are fixed, giving users a specific view into the data.

**data function** Function that computes aggregate values, including averages, maximums, counts, and other statistics that summarize groupings of data.

**data load location** In FDM, a reporting unit responsible for submitting source data into the target system. Typically, one FDM data load location exists for each source file loaded to the target system.

**data load rules** A set of criteria that determines how to load data from a text-based file, a spreadsheet, or a relational data set into a database.

**data lock** A feature that prevents changes to data according to specified criteria, such as a period or scenario.

**data mining** The process of searching through an Essbase database for hidden relationships and patterns in a large amount of data.

 $\mbox{\bf data \ model} \ \ A \ representation \ of \ a \ subset \ of \ database \ tables.$ 

data value See cell.

**database connection** A file that stores definitions and properties used to connect to data sources and enables database references to be portable and widely used.

date measure In Essbase, a member tagged as Date in the dimension where measures are represented. The cell values are displayed as formatted dates. Dates as measures can be useful for analysis types that are difficult to represent using the Time dimension. For example, an application may need to track acquisition dates for a series of capital assets, but the acquisition dates span too large a period to allow for feasible Time dimension modeling. See also typed measure.

**Default Currency Units** The unit scale of data. For example, If you select to define your analysis in thousands and enter 10, this unit is interpreted as 10,000.

**dense dimension** In block storage databases, a dimension likely to contain data for every combination of dimension members. For example, time dimensions are often dense because they can contain all combinations of all members. Contrast with sparse dimension.

**dependent entity** An entity that is owned by another entity in the organization.

derived text measure In Essbase Studio, a text measure whose values are governed by a predefined rule expressed as a range. For example, a derived text measure, called Sales Performance Index, based on a measure Sales, could consist of the values High, Medium, and Low. This derived text measure is defined to display High, Medium, and Low depending on the range in which the corresponding sales values fall. See also text measure.

**descendant** Any member below a parent in the database outline. In a dimension that includes years, quarters, and months, the members Qtr2 and April are descendants of the member Year.

**Design Report** An interface in Web Analysis Studio for designing custom reports, from a library of components.

**destination** 1) In Business Rules, a block of the database where calculated values are stored; 2) In Profitability and Cost Management, the association of a source and destination in the allocation model that controls the direction of allocated costs or revenue flow.

**destination currency** The currency to which balances are converted. You enter exchange rates and convert from the source currency to the destination currency. For example, when you convert from EUR to USD, the destination currency is USD.

**detail chart** A chart that provides the detailed information that you see in a Summary chart. Detail charts appear in the Investigate Section in columns below the Summary charts. If the Summary chart shows a Pie chart, then the Detail charts below represent each piece of the pie.

**dimension** A data category used to organize business data for the retrieval and preservation of values. Dimensions usually contain hierarchies of related members grouped within them. For example, a Year dimension often includes members for each time period, such as quarters and months.

**dimension build** The process of adding dimensions and members to an Essbase outline.

**dimension build rules** Specifications, similar to data load rules, that Essbase uses to modify an outline. The modification is based on data in an external data source file.

**dimension tab** In the Pivot section, the tab that enables you to pivot data between rows and columns.

**dimension table** 1) A table that includes numerous attributes about a specific business process; 2) In Essbase Integration Services, a container in the OLAP model for one or more relational tables that define a potential dimension in Essbase.

**dimension type** A dimension property that enables the use of predefined functionality. Dimensions tagged as time have a predefined calendar functionality.

**dimensionality** In MaxL DML, the represented dimensions (and the order in which they are represented) in a set. For example, the following set consists of two tuples of the same dimensionality, because they both reflect the dimensions (Region, Year): { (West, Feb), (East, Mar) }

**direct rate** A currency rate that you enter in the exchangerate table. The direct rate is used for currency conversion. For example, to convert balances from JPY to USD, in the exchange-rate table, enter a rate for the period/scenario where the source currency is JPY and the destination currency is USD.

**dirty block** A data block containing cells that have been changed since the last calculation. Upper-level blocks are marked as dirty if their child blocks are dirty (that is, if they have been updated).

**Disaster Recovery** The ability to safeguard against natural or unplanned outages at a production site by having a recovery strategy for applications and data to a geographically separate standby site.

**display type** One of three Web Analysis formats saved to the repository: spreadsheet, chart, and pinboard.

**dog-ear** The flipped page corner in the upper-right corner of the chart header area.

**domain** In data mining, a variable representing a range of navigation within data.

**drill-down** Navigation through the query result set using the dimensional hierarchy. Drilling down moves the user perspective from aggregated data to detail. For example, drilling down can reveal hierarchical relationships between years and quarters or quarters and months.

**drill-through** The navigation from a value in one data source to corresponding data in another source.

**driver** In Profitability and Cost Management, an allocation method that describes the mathematical relationship between the sources that use the driver and the destinations to which those sources allocate cost or revenue. For Business Modeling, see also cost driver and activity driver.

**duplicate alias name** A name that occurs more than once in an alias table and can be associated with more than one member in a database outline. Duplicate alias names can be used with duplicate member outlines only.

duplicate member name Multiple occurrences of a member name in a database, with each occurrence representing a different member. For example, a database has two members named New York. One member represents New York state and the other member represents New York city.

**duplicate member outline** A database outline containing duplicate member names.

**Dynamic Calc and Store members** Members in a block storage outline that Essbase calculates only upon the first retrieval of the value. Essbase then stores the calculated value in the database. Subsequent retrievals do not require calculating.

**Dynamic Calc members** Members in a block storage outline that Essbase calculates only at retrieval time. Essbase discards calculated values after completing the retrieval request.

**dynamic calculation** In Essbase, a calculation that occurs only when you retrieve data on a member that is tagged as Dynamic Calc or Dynamic Calc and Store. The member's values are calculated at retrieval time instead of being precalculated during batch calculation.

**dynamic hierarchy** In aggregate storage database outlines only, a hierarchy in which members are calculated at retrieval time.

**dynamic member list** A system-created named member set that is based on user-defined criteria. The list is refreshed automatically whenever it is referenced in the application. As dimension members are added and deleted, the list automatically reapplies the criteria to reflect the changes.

**dynamic reference** A pointer in the rules file to header records in a data source.

**dynamic report** A report containing data that is updated when you run the report.

**Dynamic Time Series** A process that performs period-to-date reporting in block storage databases.

**dynamic view account** An account type indicating that account values are calculated dynamically from the data that is displayed.

**Eliminated Account** An account that does not appear in the consolidated file.

**elimination** The process of zeroing out (eliminating) transactions between entities within an organization.

**employee** A user responsible for, or associated with, specific business objects. Employees need not work for an organization; for example, they can be consultants. Employees must be associated with user accounts, for authorization purposes.

**encoding** A method for mapping bit combinations to characters for creating, storing, and displaying text. Each encoding has a name; for example, UTF-8. Within an encoding, each character maps to a specific bit combination; for example, in UTF-8, uppercase A maps to HEX41. See also code page, locale.

**ending period** A period enabling you to adjust the date range in a chart. For example, an ending period of "month" produces a chart showing information through the end of the current month.

**Enterprise View** An Administration Services feature that enables management of the Essbase environment from a graphical tree view. From Enterprise View, you can operate directly on Essbase artifacts.

**entity** A dimension representing organizational units. Examples: divisions, subsidiaries, plants, regions, products, or other financial reporting units.

**EPM Oracle home** A subdirectory of Middleware home containing the files required by EPM System products. The EPM Oracle home location is specified during installation with EPM System Installer.

**EPM Oracle instance** A directory containing active, dynamic components of EPM System products (components that can change during run-time). You define the EPM Oracle instance directory location during configuration with EPM System Configurator.

**Equity Beta** The riskiness of a stock, measured by the variance between its return and the market return, indicated by an index called "beta." For example, if a stock's return normally moves up or down 1.2% when the market moves up or down 1%, the stock has a beta of 1.2.

**essbase.cfg** An optional configuration file for Essbase. Administrators may edit this file to customize Essbase Server functionality. Some configuration settings may also be used with Essbase clients to override Essbase Server settings.

**EssCell** A function entered into a cell in Essbase Spreadsheet Add-in to retrieve a value representing an intersection of specific Essbase database members.

**ESSCMD** A command-line interface for performing Essbase operations interactively or through batch script files.

**ESSLANG** The Essbase environment variable that defines the encoding used to interpret text characters. See also encoding.

**ESSMSH** See MaxL Shell.

**exceptions** Values that satisfy predefined conditions. You can define formatting indicators or notify subscribing users when exceptions are generated.

exchange rate type An identifier for an exchange rate. Different rate types are used because there may be multiple rates for a period and year. Users traditionally define rates at period end for the average rate of the period and for the end of the period. Additional rate types are historical rates, budget rates, forecast rates, and so on. A rate type applies to a specific time.

**expense account** An account that stores periodic and year-to-date values that decrease net worth if they are positive.

**Extensible Markup Language (XML)** A language comprising a set of tags used to assign attributes to data that can be interpreted between applications according to a schema.

external authentication Logging on to Oracle EPM System products with user information stored outside the application. The user account is maintained by the EPM System, but password administration and user authentication are performed by an external service, using a corporate directory such as Oracle Internet Directory (OID) or Microsoft Active Directory (MSAD).

**externally triggered events** Non-time-based events for scheduling job runs.

**Extract, Transform, and Load (ETL)** Data-source-specific programs for extracting data and migrating it to applications.

**extraction command** An Essbase reporting command that handles the selection, orientation, grouping, and ordering of raw data extracted from a database; begins with the less-than (<) character.

**fact table** The central table in a star join schema, characterized by a foreign key and elements drawn from a dimension table. This table typically contains numeric data that can be related to all other tables in the schema.

**failover** The ability to switch automatically to a redundant standby database, server, or network if the primary database, server, or network fails or is shut down. A system that is clustered for failover provides high availability and fault tolerance through server redundancy and fault-tolerant hardware, such as shared disks.

**Favorites gadget** A gadget that contains links to Reporting and Analysis documents and URLs. See also gadget.

**file delimiter** A character, such as a comma or tab, that separates fields in a data source.

**filter** A constraint on data sets that restricts values to specific criteria; for example, to exclude certain tables, metadata, or values, or to control access.

**flow account** An unsigned account that stores periodic and year-to-date values.

**footer** Text or images at the bottom of report pages, containing dynamic functions or static text such as page numbers, dates, logos, titles or file names, and author names.

**format string** 1) In Essbase, a method for transforming the way cell values are displayed; 2) In Data Relationship Management, a parameter of a Format or Formatted Date derived property that indicates the format in which a property value should be returned.

**formula** In Data Relationship Management, business logic used by a derived property to dynamically calculate a property value.

**frame** An area on the desktop. Two main areas: the navigation and workspace frames.

**free-form grid** An object for presenting, entering, and integrating data from different sources for dynamic calculations.

**free-form reporting** Creating reports by entering dimension members or report script commands in worksheets.

**function** In Data Relationship Management, a syntactic element of a derived property formula that accepts parameters and returns dynamic values.

**gadget** A simple, specialized, lightweight application that provides easy viewing of EPM content and enables access to core Reporting and Analysis functionality.

**geneology data** Additional data that is optionally generated after allocation calculations. This data enables reporting on all cost or revenue flows from start to finish through all allocation steps.

**generation** A layer in a hierarchical tree structure that defines member relationships in a database. Generations are ordered incrementally from the top member of the dimension (generation 1) down to the child members. Use the unique generation name to identify a layer in the hierarchical tree structure.

**generic jobs** Non-SQR Production Reporting or non-Interactive Reporting jobs.

**global report command** A command in a running report script that is effective until it is replaced by another global command or the file ends.

**grid POV** A means for specifying dimension members on a grid without placing dimensions in rows, columns, or page intersections. A report designer can set POV values at the grid level, preventing user POVs from affecting the grid. If a dimension has one grid value, you put the dimension into the grid POV instead of the row, column, or page.

**group** A container for assigning similar access permissions to multiple users.

**GUI** Graphical user interface

hardware cluster a collection of computers that provides a single view of network services (for example, an IP address) or application services (such as databases and Web servers) to clients of these services. Each node in a hardware cluster is a standalone server that runs its own processes. These processes can communicate with one another to form what looks like a single system that cooperatively provides applications, system resources, and data to users.

**high availability** A system attribute that enables an application to continue to provide services in the presence of failures. This is achieved through removal of single points of failure, with fault-tolerant hardware, as well as server clusters; if one server fails, processing requests are routed to another server.

**Historical Average** An average for an account over a number of historical periods.

**holding company** An entity that is part of a legal entity group, with direct or indirect investments in all entities in the group.

**horizontal application server cluster** A cluster with application server instances on different machines.

**host** A server on which applications and services are installed.

**host properties** Properties pertaining to a host, or if the host has multiple Oracle EPM homes, to an Oracle EPM home.

**Hybrid Analysis** An analysis mapping low-level data stored in a relational database to summary-level data stored in Essbase, combining the mass scalability of relational systems with multidimensional data.

**hyperlink** A link to a file, a Web page, or an intranet HTML page.

**Hypertext Markup Language (HTML)** A programming language specifying how Web browsers display data.

**identity** A unique identification for a user or group in external authentication.

**image bookmarks** Graphic links to Web pages or repository items.

**IMPACTED status** A status that indicates changes in child entities consolidating into parent entities.

**implied share** A member with one or more children but only one that is consolidated, so the parent and child share a value.

**import format** In FDM, the definition of the structure of the source file that enables the loading of a source data file to an FDM data-load location.

**inactive group** A group for which an administrator has deactivated system access.

**INACTIVE status** A status that indicates entities deactivated from consolidation for the current period.

**inactive user** A user whose account was deactivated by an administrator.

**income account** An account storing periodic and year-to-date values that, if positive, increase net worth.

index 1) A method where Essbase uses sparse-data combinations to retrieve data in block storage databases. 2)The index file.

index cache A buffer containing index pages.

**index entry** A pointer to an intersection of sparse dimensions. Index entries point to data blocks on disk and use offsets to locate cells.

**index file** An Essbase file storing block storage data retrieval information, residing on disk, and containing index pages.

**index page** A subdivision in an index file. An index page contains pointers to data blocks.

**input data** Data loaded from a source rather than calculated.

**installation assemblies** Product installation files that plug in to EPM System Installer.

**integration** A process that is run to move data between Oracle's Hyperion applications using Shared Services. Data integration definitions specify the data moving between a source application and a destination application, and they enable the data movements to be grouped, ordered, and scheduled.

**intelligent calculation** A calculation method tracking updated data blocks since the last calculation.

Interactive Reporting connection file (.oce) Files encapsulating database connection information, including the database API (ODBC, SQL\*Net, and so on), database software, the database server network address, and database user name. Administrators create and publish Interactive Reporting connection (.oce) files.

intercompany elimination See elimination.

intercompany matching The process of comparing balances for pairs of intercompany accounts within an application. Intercompany receivables are compared to intercompany payables for matches. Matching accounts are used to eliminate intercompany transactions from an organization's consolidated totals.

**intercompany matching report** A report that compares intercompany account balances and indicates whether the accounts are in balance.

**interdimensional irrelevance** A situation in which a dimension does not intersect with other dimensions. Because the data in the dimension cannot be accessed from the nonintersecting dimensions, the nonintersecting dimensions are not relevant to that dimension.

**intersection** A unit of data representing the intersection of dimensions in a multidimensional database; also, a worksheet cell.

**intrastage assignment** An assignment in the financial flow to an object within the same stage.

**introspection** A deep inspection of a data source to discover hierarchies based on the inherent relationships in the database. Contrast with scraping.

**Investigation** See drill-through.

**isolation level** An Essbase Kernel setting that determines the lock and commit behavior of database operations. Choices are: committed access and uncommitted access.

**iteration** A pass of the budget or planning cycle in which the same version of data is revised and promoted.

**Java application server cluster** An active-active application server cluster of Java Virtual Machines (JVMs).

Java Database Connectivity (JDBC) A client-server communication protocol used by Java-based clients and relational databases. The JDBC interface provides a call-level API for SOL-based database access.

**job output** Files or reports produced from running a job.

**jobs** Documents with special properties that can be launched to generate output. A job can contain Interactive Reporting, SQR Production Reporting, or generic documents.

**join** A link between two relational database tables or topics based on common content in a column or row. A join typically occurs between identical or similar items within different tables or topics. For example, a record in the Customer table is joined to a record in the Orders table because the Customer ID value is the same in each table.

**journal entry (JE)** A set of debit-credit adjustments to account balances for a scenario and period.

JSP Java Server Page.

**KeyContacts gadget** A gadget that contains a group of Smart Space users and provides access to Smart Space Collaborator. For example, you can have a KeyContacts gadget for your marketing team and another for your development team. See also gadget.

**latest** A spreadsheet keyword used to extract data values from the member defined as the latest time period.

layer 1) The horizontal location of members in a hierarchical structure, specified by generation (top down) or level (bottom up); 2) Position of objects relative to other objects. For example, in the Sample Basic database, Qtr1 and Qtr4 are in the same layer, so they are also in the same generation, but in a database with a ragged hierarchy, Qtr1 and Qtr4 might not be in same layer, though they are in the same generation.

**layout area** An area on a Workspace Page where content can be placed.

**legend box** A box containing labels that identify the data categories of a dimension.

**level** A layer in a hierarchical tree structure that defines database member relationships. Levels are ordered from the bottom dimension member (level 0) up to the parent members.

**level 0 block** A data block for combinations of sparse, level 0 members.

level 0 member A member that has no children.

**liability account** An account type that stores "point in time" balances of a company's liabilities. Examples: accrued expenses, accounts payable, and long-term debt.

**lifecycle management** The process of migrating an application, a repository, or individual artifacts across product environments.

line item detail The lowest level of detail in an account.

**lineage** The relationship between different metadata elements showing how one metadata element is derived from one or more other metadata elements, ultimately tracing the metadata element to its physical source. In Essbase Studio, a lineage viewer displays the relationships graphically. See also traceability.

**link** 1) A reference to a repository object. Links can reference folders, files, shortcuts, and other links; 2) In a taskflow, the point where the activity in one stage ends and another begins.

**link condition** A logical expression evaluated by the taskflow engine to determine the sequence of launching taskflow stages.

**linked data model** Documents that are linked to a master copy in a repository

**linked partition** A shared partition that enables you to use a data cell to link two databases. When a user clicks a linked cell in a worksheet, Essbase opens a new sheet displaying the dimensions in the linked database. The user can then drill down those dimensions.

**linked reporting object (LRO)** A cell-based link to an external file such as cell notes, URLs, or files with text, audio, video, or pictures. (Only cell notes are supported for Essbase LROs in Financial Reporting.) Contrast with local report object.

**load balancer** Hardware or software that directs the requests to individual application servers in a cluster and is the only point of entry into the system.

**load balancing** Distribution of requests across a group of servers, which helps to ensure optimal end user performance.

**local currency** An input currency type. When an input currency type is not specified, the local currency matches the entity's base currency.

**local report object** A report object that is not linked to a Financial Reporting report object in Explorer. Contrast with linked reporting object.

**local results** A data model's query results. Results can be used in local joins by dragging them into the data model. Local results are displayed in the catalog when requested.

**locale** A computer setting that specifies a location's language, currency and date formatting, data sort order, and the character set encoding used on the computer. Essbase uses only the encoding portion. See also encoding, ESSLANG.

**locale header record** A text record at the beginning of some non-Unicode-encoded text files, such as scripts, that identifies the encoding locale.

**location alias** A descriptor that identifies a data source. The location alias specifies a server, application, database, user name, and password. Location aliases are set by DBAs at the database level using Administration Services Console, ESSCMD, or the API.

**locked** A user-invoked process that prevents users and processes from modifying data.

**locked data model** A data model that cannot be modified by a user.

**LOCKED status** A consolidation status indicating that an entity contains data that cannot be modified.

**Log Analyzer** An Administration Services feature that enables filtering, searching, and analysis of Essbase logs.

**logic group** In FDM, one or more logic accounts generated after a source file is loaded into FDM. Logic accounts are calculated accounts derived from the source data.

**logical Web application** An aliased reference used to identify the internal host name, port, and context of a Web application. In a clustered or high-availability environment, this is the alias name that establishes a single internal reference for the distributed components. In EPM System, a nonclustered logical Web application defaults to the physical host running the Web application.

**LRO** See linked reporting object.

**managed server** An application server process running in its own Java Virtual Machine (JVM).

manual stage A stage that requires human intervention.

**Map File** A file that stores the definition for sending data to or retrieving data from an external database. Map files have different extensions (.mps to send data; .mpr to retrieve data).

**Map Navigator** A feature that displays your current position on a Strategy, Accountability, or Cause and Effect map, indicated by a red outline.

**Marginal Tax Rate** The rate used to calculate the after-tax cost of debt; represents the tax rate applied to the last earned income dollar (the rate from the highest tax bracket into which income falls) and includes federal, state, and local taxes. Based on current level of taxable income and tax bracket, you can predict marginal tax rate.

Market Risk Premium The additional rate of return paid over the risk-free rate to persuade investors to hold "riskier" investments than government securities. Calculated by subtracting the risk-free rate from the expected market return. These figures should closely model future market conditions.

master data model An independent data model that is referenced as a source by multiple queries. When used, "Locked Data Model" is displayed in the Query section's Content pane; the data model is linked to the master data model displayed in the Data Model section, which an administrator may hide.

mathematical operator A symbol that defines how data is calculated in formulas and outlines. Can be any of the standard mathematical or Boolean operators; for example, +, -, \*, /, and %.

**MaxL** The multidimensional database access language for Essbase, consisting of a data definition language (MaxL DDL) and a data manipulation language (MaxL DML). See also MaxL DDL, MaxL DML, and MaxL Shell

MaxL DDL The data definition language used by Essbase for batch or interactive system-administration tasks.

**MaxL DML** The data manipulation language used in Essbase for data query and extraction.

MaxL Perl Module A Perl module (essbase.pm) that is part of Essbase MaxL DDL. This module can be added to the Perl package to provide access to Essbase databases from Perl programs.

MaxL Script Editor A script-development environment in Administration Services Console. MaxL Script Editor is an alternative to using a text editor and the MaxL Shell for administering Essbase with MaxL scripts.

MaxL Shell An interface for passing MaxL statements to Essbase Server. The MaxL Shell executable file is located in the Essbase bin directory (UNIX: essmsh; Windows: essmsh.exe).

MDX (multidimensional expression) A language used for querying and calculation in multidimensional-compliant databases.

measures Numeric values in an OLAP database cube that are available for analysis. Measures are margin, cost of goods sold, unit sales, budget amount, and so on. See also fact table.

**member** A discrete component within a dimension. A member identifies and differentiates the organization of similar units. For example, a time dimension might include members Jan, Feb, and Qtr1.

member list A named system- or user-defined group that references members, functions, or member lists within a dimension.

member load In Essbase Integration Services, the process of adding dimensions and members (without data) to Essbase outlines.

member selection report command A type of Report Writer command that selects member ranges based on outline relationships, such as sibling, generation, and level.

member-specific report command A type of Report Writer formatting command that is executed as it is encountered in a report script. The command affects only its associated member and executes the format command before processing the member.

merge A data load option that clears values only from the accounts specified in the data load file and replaces them with values in the data load file.

metadata A set of data that defines and describes the properties and attributes of the data stored in a database or used by an application. Examples of metadata are dimension names, member names, properties, time periods, and security.

metadata elements Metadata derived from data sources and other metadata that is stored and cataloged for Essbase Studio use.

metadata sampling The process of retrieving a sample of members in a dimension in a drill-down operation.

metadata security Security set at the member level to restrict users from accessing certain outline members.

metaoutline In Essbase Integration Services, a template containing the structure and rules for creating an Essbase outline from an OLAP model.

**Middleware home** A directory that includes the Oracle WebLogic Server home and can also include the EPM Oracle home and other Oracle homes. A Middleware home can reside on a local file system or on a remote shared disk that is accessible through NFS.

**migration audit report** A report generated from the migration log that provides tracking information for an application migration.

**migration definition file (.mdf)** A file that contains migration parameters for an application migration, enabling batch script processing.

**migration log** A log file that captures all application migration actions and messages.

**migration snapshot** A snapshot of an application migration that is captured in the migration log.

**MIME Type** An attribute that describes the data format of an item, so that the system knows which application should open the object. A file's MIME (Multipurpose Internet Mail Extension) type is determined by the file extension or HTTP header. Plug-ins tell browsers which MIME types they support and which file extensions correspond to each MIME type.

**mining attribute** In data mining, a class of values used as a factor in analysis of a set of data.

**minireport** A report component that includes layout, content, hyperlinks, and the query or queries to load the report. Each report can include one or more minireports.

**minischema** A graphical representation of a subset of tables from a data source that represents a data modeling context.

missing data (#MISSING) A marker indicating that data in the labeled location does not exist, contains no value, or was never entered or loaded. For example, missing data exists when an account contains data for a previous or future period but not for the current period.

model 1) In data mining, a collection of an algorithm's findings about examined data. A model can be applied against a wider data set to generate useful information about that data; 2) A file or content string containing an application-specific representation of data. Models are the basic data managed by Shared Services, of two major types: dimensional and nondimensional application objects; 3) In Business Modeling, a network of boxes connected to represent and calculate the operational and financial flow through the area being examined.

**multidimensional database** A method of organizing, storing, and referencing data through three or more dimensions. An individual value is the intersection point for a set of dimensions. Contrast with relational database.

**Multiload** An FDM feature that allows the simultaneous loading of multiple periods, categories, and locations.

**My Workspace Page** Customizable Workspace Pages created by users. They are marked specially so that they can be easily accessed from one single place without having to navigate the repository.

**named set** In MaxL DML, a set with its logic defined in the optional WITH section of a MaxL DML query. The named set can be referenced multiple times in the query.

**native authentication** The process of authenticating a user name and password from within the server or application.

**nested column headings** A report column heading format that displays data from multiple dimensions. For example, a column heading that contains Year and Scenario members is a nested column. The nested column heading shows Q1 (from the Year dimension) in the top line of the heading, qualified by Actual and Budget (from the Scenario dimension) in the bottom line of the heading.

**NO DATA status** A consolidation status indicating that this entity contains no data for the specified period and account.

**non-dimensional model** A Shared Services model type that includes application objects such as security files, member lists, calculation scripts, and Web forms.

**non-unique member name** See duplicate member name.

**null value** A value that is absent of data. Null values are not equal to zero.

numeric attribute range A feature used to associate a base dimension member that has a discrete numeric value with an attribute that represents a value range. For example, to classify customers by age, an Age Group attribute dimension can contain members for the following age ranges: 0-20, 21-40, 41-60, and 61-80. Each Customer dimension member can be associated with an Age Group range. Data can be retrieved based on the age ranges rather than on individual age values.

**ODBC** Open Database Connectivity. A database access method used from any application regardless of how the database management system (DBMS) processes the information.

**OK status** A consolidation status indicating that an entity has already been consolidated, and that data has not changed below it in the organization structure.

**OLAP Metadata Catalog** In Essbase Integration Services, a relational database containing metadata describing the nature, source, location, and type of data that is pulled from the relational data source.

**OLAP model** In Essbase Integration Services, a logical model (star schema) that is created from tables and columns in a relational database. The OLAP model is then used to generate the structure of a multidimensional database. See also online analytical processing (OLAP).

online analytical processing (OLAP) A multidimensional, multiuser, client-server computing environment for users who analyze consolidated enterprise data in real time. OLAP systems feature drill-down, data pivoting, complex calculations, trend analysis, and modeling.

Open Database Connectivity (ODBC) Standardized application programming interface (API) technology that allows applications to access multiple third-party databases.

**Oracle home** A directory containing the installed files required by a specific product, and residing within the directory structure of Middleware home. See also Middleware home.

organization An entity hierarchy that defines each entity and their relationship to others in the hierarchy.

**origin** The intersection of two axes.

outline The database structure of a multidimensional database, including all dimensions, members, tags, types, consolidations, and mathematical relationships. Data is stored in the database according to the structure defined in the outline.

outline synchronization For partitioned databases, the process of propagating outline changes from one database to another database.

P&L accounts (P&L) Profit and loss accounts. P&L refers to a typical grouping of expense and income accounts that comprise a company's income statement.

page A display of information in a grid or table often represented by the Z-axis. A page can contain data from one field, derived data from a calculation, or text.

page file An Essbase data file.

page heading A report heading type that lists members represented on the current page of the report. All data values on the page have the members in the page heading as a common attribute.

page member A member that determines the page axis.

palette A JASC-compliant file with a .PAL extension. Each palette contains 16 colors that complement each other and can be used to set the dashboard color elements.

parallel calculation A calculation option. Essbase divides a calculation into tasks and calculates some tasks simultaneously.

parallel data load In Essbase, the concurrent execution of data load stages by multiple process threads.

parallel export The ability to export Essbase data to multiple files. This may be faster than exporting to a single file, and it may resolve problems caused by a single data file becoming too large for the operating system to handle.

parent adjustments The journal entries that are posted to a child in relation to its parent.

parents The entities that contain one or more dependent entities that report directly to them. Because parents are entities associated with at least one node, they have entity, node, and parent information associated with them.

partition area A subcube within a database. A partition is composed of one or more areas of cells from a portion of the database. For replicated and transparent partitions, the number of cells within an area must be the same for the data source and target to ensure that the two partitions have the same shape. If the data source area contains 18 cells, the data target area must also contain 18 cells to accommodate the number of values.

**partitioning** The process of defining areas of data that are shared or linked between data models. Partitioning can affect the performance and scalability of Essbase applications.

pattern matching The ability to match a value with any or all characters of an item entered as a criterion. Missing characters may be represented by wild-card values such as a question mark (?) or an asterisk (\*). For example, "Find all instances of apple" returns apple, but "Find all instances of apple\*" returns apple, applesauce, applecranberry, and so on.

**percent consolidation** The portion of a child's values that is consolidated to its parent.

**percent control** The extent to which an entity is controlled within the context of its group.

**percent ownership** The extent to which an entity is owned by its parent.

**performance indicator** An image file used to represent measure and scorecard performance based on a range you specify; also called a status symbol. You can use the default performance indicators or create an unlimited number of your own.

**periodic value method (PVA)** A process of currency conversion that applies the periodic exchange rate values over time to derive converted results.

**permission** A level of access granted to users and groups for managing data or other users and groups.

**persistence** The continuance or longevity of effect for any Essbase operation or setting. For example, an Essbase administrator may limit the persistence of user name and password validity.

**personal pages** A personal window to repository information. You select what information to display and its layout and colors.

**personal recurring time events** Reusable time events that are accessible only to the user who created them.

**personal variable** A named selection statement of complex member selections.

**perspective** A category used to group measures on a scorecard or strategic objectives within an application. A perspective can represent a key stakeholder (such as a customer, employee, or shareholder/financial) or a key competency area (such as time, cost, or quality).

**pinboard** One of the three data object display types. Pinboards are graphics composed of backgrounds and interactive icons called pins. Pinboards require traffic lighting definitions.

**pins** Interactive icons placed on graphic reports called pinboards. Pins are dynamic. They can change images and traffic lighting color based on the underlying data values and analysis tools criteria.

**pivot** Alter the perspective of retrieved data. When Essbase first retrieves a dimension, it expands data into rows. You can then pivot or rearrange the data to obtain a different viewpoint.

**planner** A user who can input and submit data, use reports that others create, execute business rules, use task lists, enable email notification for themselves, and use Smart View. Planners comprise the majority of users.

**planning unit** A data slice at the intersection of a scenario, version, and entity; the basic unit for preparing, reviewing, annotating, and approving plan data.

**plot area** The area bounded by X, Y, and Z axes; for pie charts, the rectangular area surrounding the pie.

**plug account** An account in which the system stores any outof-balance differences between intercompany account pairs during the elimination process.

**post stage assignment** Assignments in the allocation model that are assigned to locations in a subsequent model stage.

**POV** (**point of view**) A feature for setting data focus by selecting members that are not already assigned to row, column, or page axes. For example, selectable POVs in FDM could include location, period, category, and target category. In another example, using POV as a filter in Smart View, you could assign the Currency dimension to the POV and select the Euro member. Selecting this POV in data forms displays data in Euro values.

**precalculation** Calculating the database before user retrieval.

precision Number of decimal places displayed in numbers.

**predefined drill paths** Paths used to drill to the next level of detail, as defined in the data model.

**presentation** A playlist of Web Analysis documents, enabling reports to be grouped, organized, ordered, distributed, and reviewed. Includes pointers referencing reports in the repository.

**preserve formulas** User-created formulas kept within a worksheet while retrieving data.

**primary measure** A high-priority measure important to your company and business needs. Displayed in the Contents frame.

**Process Monitor Report** A list of locations and their positions within the FDM data conversion process. You can use the process monitor report to monitor the status of the closing process. The report is time-stamped. Therefore, it can be used to determine to which locations at which time data was loaded.

**product** In Shared Services, an application type, such as Planning or Performance Scorecard.

**Production Reporting** See SQR Production Reporting.

**project** An instance of Oracle's Hyperion products grouped together in an implementation. For example, a Planning project may consist of a Planning application, an Essbase cube, and a Financial Reporting Server instance.

**provisioning** The process of granting users and groups specific access permissions to resources.

**proxy server** A server acting as an intermediary between workstation users and the Internet to ensure security.

**public job parameters** Reusable named job parameters created by administrators and accessible to users with requisite access privileges.

**public recurring time events** Reusable time events created by administrators and accessible through the access control system.

**PVA** See periodic value method.

**qualified name** A member name in a qualified format that differentiates duplicate member names in a duplicate member outline. For example, [Market].[East].[State]. [New York] or [Market].[East].[City].[New York].

**query governor** An Essbase Integration Server parameter or Essbase Server configuration setting that controls the duration and size of queries made to data sources.

**reciprocal assignment** An assignment in the financial flow that also has the source as one of its destinations.

**reconfigure URL** A URL that is used to reload servlet configuration settings dynamically when users are already logged on to the Workspace.

**record** In a database, a group of fields making up one complete entry. For example, a customer record may contain fields for name, address, telephone number, and sales data.

**recurring template** A journal template for making identical adjustments in every period.

**recurring time event** An event specifying a starting point and the frequency for running a job.

**redundant data** Duplicate data blocks that Essbase retains during transactions until Essbase commits updated blocks.

**regular journal** A feature for entering one-time adjustments for a period. A regular journal can be balanced, balanced by entity, or unbalanced.

**Related Accounts** Accounts related to the main account and grouped under the same main account number. The account structure groups all main and related accounts under the same main account number. The main account is distinguished from related accounts by the first suffix of the account number.

**relational database** A type of database that stores data in related two-dimensional tables. Contrast with multidimensional database.

**replace** A data load option that clears existing values from all accounts for periods specified in the data load file and loads values from the data load file. If an account is not specified in the load file, its values for the specified periods are cleared.

**replicated partition** A portion of a database, defined through Partition Manager, used to propagate an update to data mastered at one site to a copy of data stored at another site. Users can access the data as though it were part of their local database.

**Report Extractor** An Essbase component that retrieves report data from the Essbase database when report scripts are run.

**report object** In report designs, a basic element with properties defining behavior or appearance, such as text boxes, grids, images, and charts.

**report script** A text file containing Essbase Report Writer commands that generate one or more production reports.

**Report Viewer** An Essbase component that displays complete reports after report scripts are run.

**reporting currency** The currency used to prepare financial statements, and converted from local currencies to reporting currencies.

**repository** Storage location for metadata, formatting, and annotation information for views and queries.

**resources** Objects or services managed by the system, such as roles, users, groups, files, and jobs.

**restore** An operation to reload data and structural information after a database has been damaged or destroyed, typically performed after shutting down and restarting the database.

**restructure** An operation to regenerate or rebuild the database index and, in some cases, data files.

**result frequency** The algorithm used to create a set of dates to collect and display results.

**review level** A Process Management review status indicator representing the process unit level, such as Not Started, First Pass, Submitted, Approved, and Published.

**Risk Free Rate** The rate of return expected from "safer" investments such as long-term U.S. government securities.

**role** The means by which access permissions are granted to users and groups for resources.

roll-up See consolidation.

root member The highest member in a dimension branch.

**runtime prompt** A variable that users enter or select before a business rule is run.

**sampling** The process of selecting a representative portion of an entity to determine the entity's characteristics. See also metadata sampling.

**saved assumptions** User-defined Planning assumptions that drive key business calculations (for example, the cost per square foot of office floor space).

**scaling** Scaling determines the display of values in whole numbers, tens, hundreds, thousands, millions, and so on.

**scenario** A dimension for classifying data; for example, Actuals, Budget, Forecast1, or Forecast2.

**schema** In relational databases, a logical model that represents the data and the relationships between the data.

**scope** The area of data encompassed by any Essbase operation or setting; for example, the area of data affected by a security setting. Most commonly, scope refers to three levels of granularity, where higher levels encompass lower levels. The levels, from highest to lowest: the entire system (Essbase Server), applications on Essbase Server, or databases within Essbase Server applications. See also persistence.

**score** The level at which targets are achieved, usually expressed as a percentage of the target.

**scorecard** A business object that represents the progress of an employee, strategy element, or accountability element toward goals. Scorecards ascertain this progress based on data collected for each measure and child scorecard added to the scorecard.

**scraping** An inspection of a data source to derive the most basic metadata elements from it. Contrast with introspection.

**secondary measure** A low-priority measure, less important than primary measures. Secondary measures do not have Performance reports but can be used on scorecards and to create dimension measure templates.

**security agent** A Web access management provider (for example, Oracle Access Manager, Oracle Single Sign-On, or CA SiteMinder) that protects corporate Web resources.

**security platform** A framework enabling Oracle EPM System products to use external authentication and single sign-on.

**serial calculation** The default calculation setting. Divides a calculation pass into tasks and calculates one task at a time.

**services** Resources that enable business items to be retrieved, changed, added, or deleted. Examples: Authorization and Authentication.

**servlet** A piece of compiled code executable by a Web server.

**shared disks** See shared storage.

**shared member** A member that shares storage space with another member of the same name, preventing duplicate calculation of members that occur multiple times in an Essbase outline.

**Shared Services Registry** The part of the Shared Services repository that manages EPM System deployment information for most EPM System products, including installation directories, database settings, computer names, ports, servers, URLs, and dependent service data.

**shared storage** A set of disks containing data that must be available to all nodes of a failover cluster; also called shared disks.

**Shared Workspace Pages** Workspace Pages shared across an organization that are stored in a special System folder and can be accessed by authorized users from the Shared Workspace Pages Navigate menu.

**sibling** A child member at the same generation as another child member and having the same immediate parent. For example, the members Florida and New York are children of East and each other's siblings.

**silent response files** Files providing data that an installation administrator would otherwise be required to provide. Response files enable EPM System Installer or EPM System Configurator to run without user intervention or input.

**single point of failure** Any component in a system that, if it fails, prevents users from accessing the normal functionality.

**single sign-on (SSO)** The ability to log on once and then access multiple applications without being prompted again for authentication.

smart tags Keywords in Microsoft Office applications that are associated with predefined actions available from the Smart Tag menu. In Oracle EPM System products, smart tags can also be used to import Reporting and Analysis content and to access Financial Management and Essbase functions.

**SmartCut** A link to a repository item, in URL form.

snapshot Read-only data from a specific time.

**source currency** The currency from which values originate and are converted through exchange rates to the destination currency.

**sparse dimension** In block storage databases, a dimension unlikely to contain data for all member combinations when compared to other dimensions. Contrast with dense dimension. For example, not all customers have data for all products.

**SPF files** Printer-independent files created by an SQR Production Reporting server, containing a representation of the actual formatted report output, including fonts, spacing, headers, footers, and so on.

**Spotlighter** A tool that enables color coding based on selected conditions.

**SQL spreadsheet** A data object that displays the result set of a SQL query.

**SQR Production Reporting** A specialized programming language for data access, data manipulation, and creating SQR Production Reporting documents.

**stage** 1) A task description that forms one logical step within a taskflow, usually performed by an individual. A stage can be manual or automated; 2) For Profitability, logical divisions within the model that represent the steps in the allocation process within your organization.

**stage action** For automated stages, the invoked action that executes the stage.

**staging area** A database that you create to meet the needs of a specific application. A staging area is a snapshot or restructured version of one or more RDBMS.

**staging table** A database that you create to meet the needs of a specific application. A staging area is a snapshot or restructured version of one or more RDBMSs.

**standard dimension** A dimension that is not an attribute dimension.

**standard journal template** A journal function used to post adjustments that have common adjustment information for each period. For example, you can create a standard template that contains the common account IDs, entity IDs, or amounts, and then use the template as the basis for many regular journals.

**Status bar** The bar at the bottom of the screen that displays helpful information about commands, accounts, and the current status of your data file.

**stored hierarchy** In aggregate storage databases outlines only, a hierarchy in which the members are aggregated according to the outline structure. Stored hierarchy members have certain restrictions; for example, they cannot contain formulas.

**strategic objective (S0)** A long-term goal defined by measurable results. Each strategic objective is associated with one perspective in the application, has one parent, the entity, and is a parent to critical success factors or other strategic objectives.

**Strategy map** Represents how the organization implements high-level mission and vision statements into lower-level, constituent strategic goals and objectives.

**structure view** Displays a topic as a simple list of component data items.

**Structured Query Language** A language used to process instructions to relational databases.

**Subaccount Numbering** A system for numbering subaccounts using nonsequential whole numbers.

**subscribe** Flags an item or folder to receive automatic notification whenever the item or folder is updated.

**Summary chart** In the Investigates Section, a chart that rolls up detail charts shown below in the same column, plotting metrics at the summary level at the top of each chart column.

**supervisor** A user with full access to all applications, databases, related files, and security mechanisms for a server.

**supporting detail** Calculations and assumptions from which the values of cells are derived.

**suppress rows** A setting that excludes rows containing missing values and underscores characters from spreadsheet reports.

**symmetric multiprocessing (SMP)** A server architecture that enables multiprocessing and multithreading. Performance is not significantly degraded when a large number of users simultaneously connect to an single instance.

symmetric topology An Oracle Fusion Middleware Disaster Recovery configuration that is identical across tiers on the production site and standby site. In a symmetric topology, the production site and standby site have the identical number of hosts, load balancers, instances, and applications. The same ports are used for both sites. The systems are configured identically and the applications access the same data.

**sync** Synchronization of Shared Services and application models.

**synchronized** The condition that exists when the latest version of a model resides in both the application and in Shared Services. See also model.

**system extract** A feature that transfers data from application metadata into an ASCII file.

**tabs** Navigable views of accounts and reports in Strategic Finance.

**target** Expected results of a measure for a specified period of time (day, quarter, and so on).

task list A detailed status list of tasks for a particular user.

**taskflow** The automation of a business process in which tasks are passed from one taskflow participant to another according to procedural rules.

taskflow definition Business processes in the taskflow management system that consist of a network of stages and their relationships; criteria indicating the start and end of the taskflow; and information about individual stages, such as participants, associated applications, associated activities, and so on.

**taskflow instance** A single instance of a taskflow including its state and associated data.

taskflow management system A system that defines, creates, and manages the execution of a taskflow, including definitions, user or application interactions, and application executables.

**taskflow participant** The resource that performs the task associated with the taskflow stage instance for both manual and automated stages.

Taxes - Initial Balances Strategic Finance assumes that the Initial Loss Balance, Initial Gain Balance, and Initial Balance of Taxes Paid entries have taken place in the period before the first Strategic Finance time period.

TCP/IP See Transmission Control Protocol/Internet Protocol.

text measure In Essbase, a member tagged as Text in the dimension where measures are represented. The cell values are displayed as predefined text. For example, the text measure Satisfaction Index may have the values Low, Medium, and High. See also typed measure, text list, derived text measure.

time dimension The time period that the data represents, such as fiscal or calendar periods.

time events Triggers for job execution.

time scale A scale that displays metrics by a specific time span, such as monthly or quarterly.

time series reporting A process for reporting data based on a calendar date (for example, year, quarter, month, or week).

**Timeline Viewer** An FDM feature that enables users to view dates and times of completed process flow steps for specific locations.

Title bar A bar that displays the Strategic Finance name, the file name, and the scenario name Version box.

toast message A message that fades in the lower-right corner of the screen.

token An encrypted identification of one valid user or group on an external authentication system.

top and side labels Column and row headings on the top and sides of a Pivot report.

top-level member A dimension member at the top of the tree in a dimension outline hierarchy, or the first member of the dimension in sort order if there is no hierarchical relationship among dimension members. If a hierarchical relationship exists, the top-level member name is generally the same as the dimension name.

trace allocations A Profitability feature that enables you to visually follow the flow of financial data, either forwards or backwards, from a single intersection throughout the model.

trace level The level of detail captured in a log file.

traceability The ability to track a metadata element to its physical source. For example, in Essbase Studio, a cube schema can be traced from its hierarchies and measure hierarchies to its dimension elements, date/time elements, measures, and, ultimately, to its physical source elements. See also lineage.

traffic lighting Color-coding of report cells, or pins based on a comparison of two dimension members, or on fixed limits.

transformation 1) A process that transforms artifacts so that they function properly in the destination environment after application migration; 2) In data mining, the modification of data (bidirectionally) flowing between the cells in the cube and the algorithm.

translation See currency conversion.

Transmission Control Protocol/Internet Protocol (TCP/IP) A standard set of communication protocols linking computers with different operating systems and internal architectures. TCP/IP utilities are used to exchange files, send mail, and store data to various computers that are connected to local and wide area networks.

transparent login A process that logs in authenticated users without launching the login screen.

**transparent partition** A shared partition that enables users to access and change data in a remote database as though it is part of a local database.

triangulation A means of converting balances from one currency to another through a third common currency. For example, to convert balances from the Danish krone to the British pound, balances could be converted from the krone to the euro and from the euro to the pound.

**triggers** An Essbase feature whereby data is monitored according to user-specified criteria that, when met, cause Essbase to alert the user or system administrator.

trusted user Authenticated user.

**tuple** MDX syntax element that references a cell as an intersection of a member from each dimension. If a dimension is omitted, its top member is implied. Examples: (Jan); (Jan, Sales); ( [Jan], [Sales], [Cola], [Texas], [Actual] ).

**two-pass** An Essbase property that is used to recalculate members that are dependent on the calculated values of other members. Two-pass members are calculated during a second pass through the outline.

**unary operator** A mathematical indicator (+, -, \*, /, %) associated with an outline member. The unary operator defines how the member is calculated during a database rollup.

**Unicode-mode application** An Essbase application wherein character text is encoded in UTF-8, enabling users with computers set up for different languages to share application data.

**unique member name** A nonshared member name that exists only once in a database outline.

**unique member outline** A database outline that is not enabled for duplicate member names.

**upgrade** The process of deploying a new software release and moving applications, data, and provisioning information from an earlier deployment to the new deployment.

**upper-level block** A type of data block wherein at least one of the sparse members is a parent-level member.

**user directory** A centralized location for user and group information, also known as a repository or provider. Popular user directories include Oracle Internet Directory (OID), Microsoft Active Directory (MSAD), and Sun Java System Directory Server.

**user variable** A variable that dynamically renders data forms based on a user's member selection, displaying only the specified entity. For example, a user variable named Department displays specific departments and employees.

**user-defined attribute (UDA)** An attribute, associated with members of an outline to describe a characteristic of the members, that can be used to return lists of members that have the specified associated UDA.

**user-defined member list** A named, static set of members within a dimension defined by the user.

**validation** The process of checking a business rule, report script, or partition definition against the outline to ensure that the object being checked is valid.

**validation rules** Rules used in FDM to enforce data integrity. For example, in FDM, validation rules ensure that certain conditions are met after data is loaded from FDM to the target application.

**value dimension** A dimension that is used to define input value, translated value, and consolidation detail.

**variance** The difference between two values (for example, between planned and actual values).

**version** A possible outcome used within the context of a scenario of data. For example, Budget - Best Case and Budget - Worst Case where Budget is scenario and Best Case and Worst Case are versions.

**vertical application server cluster** A cluster with multiple application server instances on the same machine.

view A year-to-date or periodic display of data.

**visual cue** A formatted style, such as a font or a color, that highlights specific data value types. Data values may be dimension members; parent, child, or shared members; dynamic calculations; members containing a formula; readonly data cells; read-and-write data cells; or linked objects.

**WebLogic Server home** A subdirectory of Middleware home containing installed files required by a WebLogic Server instance. WebLogic Server home is a peer of Oracle homes.

weight A value assigned to an item on a scorecard that indicates the relative importance of that item in the calculation of the overall scorecard score. The weighting of all items on a scorecard accumulates to 100%. For example, to recognize the importance of developing new features for a product, the measure for New Features Coded on a developer's scorecard would be assigned a higher weighting than a measure for Number of Minor Defect Fixes.

wild card Character that represents any single character (?) or group of characters (\*) in a search string.

**WITH section** In MaxL DML, an optional section of the query used for creating reusable logic to define sets or members. Sets or custom members can be defined once in the WITH section and then referenced multiple times during a query.

workbook An entire spreadsheet file with many worksheets.

workflow The steps required to process data from start to finish in FDM. The workflow consists of Import (loading data from the GL file), Validate (ensures that all members are mapped to a valid account), Export (loads the mapped members to the target application), and Check (verifies accuracy of data by processing data with user-defined validation rules).

**Workspace Page** A page created with content from multiple sources including documents, URL, and other content types. Enables a user to aggregate content from Oracle and non-Oracle sources.

**write-back** The ability for a retrieval client, such as a spreadsheet, to update a database value.

ws.conf A configuration file for Windows platforms.

wsconf\_platform A configuration file for UNIX platforms.

**XML** See Extensible Markup Language.

**XOLAP** An Essbase multidimensional database that stores only the outline metadata and retrieves all data from a relational database at query time. XOLAP supports aggregate storage databases and applications that contain duplicate member names.

Y axis scale A range of values on Y axis of charts displayed in Investigate Section. For example, use a unique Y axis scale for each chart, the same Y axis scale for all Detail charts, or the same Y axis scale for all charts in the column. Often, using a common Y axis improves your ability to compare charts at a glance.

**Zero Administration** A software tool that identifies version number of the most up-to-date plug-in on the server.

**ZoomChart** A tool for viewing detailed information by enlarging a chart. A ZoomChart enables you to see detailed numeric information on the metric that is displayed in the chart.