

Weblogic Configuration
Oracle FLEXCUBE Universal Banking
Release 12.1.0.0.0
[October] [2015]



Table of Contents

1.	CONFIGURING SSL ON ORACLE WEBLOGIC	1-1
1.1	INTRODUCTION	1-1
1.2	SETTING UP SSL ON ORACLE WEBLOGIC	1-1
1.3	CERTIFICATES AND KEYPAIRS	1-1
2.	CHOOSING THE IDENTITY AND TRUST STORES.....	2-2
2.1	INTRODUCTION	2-2
3.	OBTAINING THE IDENTITY STORE	3-1
3.1	CREATING IDENTITY STORE WITH SELF-SIGNED CERTIFICATES	3-1
3.1.1	<i>Creation of Self-signed Certificate</i>	<i>3-1</i>
3.2	CREATING IDENTITY STORE WITH TRUSTED CERTIFICATES ISSUED BY CA.....	3-3
3.2.1	<i>Creation of Public and Private Key Pair.....</i>	<i>3-3</i>
3.2.2	<i>Generating CSR.....</i>	<i>3-5</i>
3.2.3	<i>Obtaining Trusted Certificate from CA</i>	<i>3-5</i>
3.2.4	<i>Importing Certificate into Identity Store.....</i>	<i>3-5</i>
4.	CONFIGURING IDENTITY AND TRUST STORES FOR WEBLOGIC	4-1
4.1	ENABLING SSL ON ORACLE WEBLOGIC SERVER.....	4-1
4.2	CONFIGURING IDENTITY AND TRUST STORES	4-1
5.	SETTING SSL ATTRIBUTES FOR MANAGED SERVERS	5-1
5.1	SETTING SSL ATTRIBUTES FOR PRIVATE KEY ALIAS AND PASSWORD.....	5-1
6.	TESTING CONFIGURATION.....	6-1
6.1	TESTING CONFIGURATION	6-1
7.	CREATING RESOURCES ON WEBLOGIC	7-1
7.1	INTRODUCTION.....	7-1
7.2	RESOURCE ADMINISTRATION	7-1
7.2.1	<i>Creating Data Source</i>	<i>7-1</i>
7.2.2	<i>JMS Server Creation.....</i>	<i>7-28</i>
7.2.3	<i>JMS Modules Creation</i>	<i>7-37</i>
7.2.4	<i>Subdeployment Creation.....</i>	<i>7-44</i>
7.2.5	<i>JMS Queue Creation.....</i>	<i>7-51</i>
7.2.6	<i>JMS Connection Factory Creation</i>	<i>7-58</i>
7.3	CONFIGURING WEBLOGIC FOR PMGATEWAY	7-68
7.4	CONFIGURING WEBLOGIC FOR ORACLE FLEXCUBE	7-68
7.5	SETUP/CONFIGURE MAIL SESSION IN WEBLOGIC	7-73
7.5.1	<i>Creating JavaMail Session</i>	<i>7-73</i>
7.5.2	<i>Configuration of the TLS/SSL Trust Store for Weblogic Server</i>	<i>7-79</i>

1. Configuring SSL on Oracle Weblogic

1.1 Introduction

This chapter details out the configurations for SSL on Oracle Weblogic application server.

1.2 Setting up SSL on Oracle Weblogic

To setup SSL on Oracle Weblogic application server, you need to perform the following tasks:

1. Obtain an identity (private key and digital certificates) and trust (certificates of trusted certificate authorities) for Oracle Weblogic application server.
2. Store the identity and trust. Private keys and trust CA certificates are stored in keystores.
3. Configure the identity and trust the keystores for Oracle Weblogic application server in the administration console.
4. Set SSL attributes for the private key alias and password in Oracle Weblogic administration console.

1.3 Certificates and Keypairs

Certificates are used for validating the authenticity of the server. Certificates contains the name of the owner, certificate usage, duration of validity, resource location or distinguished name (DN), which includes the common name (CN - web site address or e-mail address depending of the usage) and the certificate ID of the person who certified (signs) these information. It also contains the public key and a hash to ensure that the certificate has not been tampered with. A certificate is insecure until it is signed. Signed certificates cannot be modified.

A certificate can be self signed or obtained from a reputable certificate authority such as Verisign, Inc., Entrust.net, Thawte, GeoTrust or InstantSSL.

SSL uses a pair of cryptographic keys - a **public key** and a **private key**. These keys are similar in nature and can be used alternatively. What one key encrypts can be decrypted by the other key of the pair. The private key is kept secret, while the public key is distributed using the certificate.

A **keytool** stores the keys and certificates in a **keystore**. The default keystore implementation implements it as a file. It protects private keys with a password. The different entities (key pairs and the certificates) are distinguished by a unique 'alias'. Through its keystore, Oracle Weblogic server can authenticate itself to other parties.

In Java, a keystore is a 'java.security.KeyStore' instance that you can create and manipulate using the **keytool** utility provided with the Java Runtime.

There are two keystores to be managed by Oracle Weblogic server to configure SSL.

- Identity Keystore: Contains the key pairs and the Digital certificate. This can also contain certificates of intermediate CAs.
- Trust Keystore: Contains the trusted CA certificates.

2. Choosing the Identity and Trust Stores

2.1 Introduction

Oracle Financial Services Software recommends that the choice of Identity and Trust stores be made up front. Oracle Weblogic server supports the following combinations of Identity and Trust stores:

- Custom Identity and Command Line Trust
- Custom Identity and Custom Trust
- Custom Identity and Java Standard Trust
- Demo Identity and Demo Trust

Oracle Financial Services does not recommend choosing Demo Identity and Demo Trust for production environments.

It is recommended to separate the identity and trust stores, since each Weblogic server tends to have its own identity, but might have the same set of trust CA certificates. Trust stores are usually copied across Oracle Weblogic servers, to standardize trust rules; it is acceptable to copy trust stores since they contain public keys and certificates of CAs. Unlike trust stores, identity stores contain private keys of the Oracle Weblogic server, and hence should be protected against unauthorized access.

Command Line Trust, if chosen requires the trust store to be specified as a command line argument in the Weblogic Server startup script. No additional configuration of the trust store is required in the Weblogic Server Administration Console.

Java Standard Trust would rely on the cacerts files provided by the Java Runtime. This file contains the list of trust CA certificates that ship with the Java Runtime, and is located in the 'JAVA_HOME/jre/lib/security' directory. It is highly recommended to change the default Java standard trust store password from 'changeit' (without quotes), and the default access permission of the file. Certificates of most commercial CAs are already present in the Java Standard Trust store. Therefore, it is recommended to use the Java Standard Trust store whenever possible. The rest of the document will assume the use of Java Standard Trust, since most CA certificates are already present in it.

One can also create custom trust stores containing the list of certificates of trusted CAs.

For further details on identity and trust stores, please refer the Oracle Weblogic Server documentation on Securing Oracle Weblogic Server.

3. Obtaining the Identity Store


3.1 Creating Identity Store with Self-Signed Certificates

Self-signed certificates are acceptable for use in a testing or development environment. Oracle Financial Services does not recommend the use of self-signed certificates in a production environment.

In order to create a self-signed certificate, the `genkeypair` option provided by the `keytool` utility of Sun Java 6 needs to be utilized.

3.1.1 Creation of Self-signed Certificate

Browse to the `bin` folder of JRE from the command prompt and type the following command.

 The items highlighted in blue are placeholders, and should be replaced with suitable values when running the command.

```
keytool -genkeypair -alias alias -keyalg RSA -keysize 1024 -sigalg  
SHA1withRSA -validity 365 -keystore keystore
```

In the above command,

1. ***alias*** is used to identify the public and private key pair created. This alias is required later when configuring the SSL attributes for the managed servers in Oracle Weblogic Server.
2. ***keystore*** is used to specify the location of the JKS file. If no JKS file is present in the path provided, one will be created.

The command will prompt for the following attributes of the certificate and keystore:

1. **Keystore Password:** Specify a password that will be used to access the keystore. This password needs to be specified later, when configuring the identity store in Oracle Weblogic Server.
2. **Key Password:** Specify a password that will be used to access the private key stored in the keystore. This password needs to be specified later, when configuring the SSL attributes of the managed server(s) in Oracle Weblogic Server.
3. **First and Last Name (CN):** Enter the domain name of the machine used to access FLEXCUBE UBS, for instance, `www.example.com`
4. **Name of your Organizational Unit:** The name of the department or unit making the request, for example, BPD. Use this field to further identify the SSL Certificate you are creating, for example, by department or by physical server.
5. **Name of your Organization:** The name of the organization making the certificate request, for example, Oracle Financial Services. It is recommended to use the company or organization's formal name, and this name entered here must match the name found in official records.

6. **Name of your City or Locality:** The city in which your organization is physically located, for example Mumbai.
7. **Name of your State or Province:** The state/province in which your organization is physically located, for example Maharashtra.
8. **Two-Letter Country Code for this Unit:** The country in which your organization is physically located, for example US, UK, IN etc.



The key generation algorithm has been specified as RSA, the key size as 1024 bits, the signature algorithm as SHA1withRSA, and the validity days as 365. These can be changed to suitable values if the need arises. For further details, please refer to the documentation of the keytool utility in the JDK utilized by Oracle Weblogic Server.

Example

Listed below is the result of a sample execution of the command:

```
D:\Oracle\weblogic11g\jrocket_160_05_R27.6.2-20\bin>keytool -
genkeypair -alias selfcert -keyalg RSA -keysize 1024 -sigalg
SHA1withRSA -validity 365 -keystore D:\keystores\FCUBSKeyStore.jks
Enter keystore password:<Enter a password to protect the keystore>
Re-enter new password:<Confirm the password keyed above>
What is your first and last name?
  [Unknown]:  cvrhp0729.i-flex.com
What is the name of your organizational unit?
  [Unknown]:  BPD
What is the name of your organization?
  [Unknown]:  Oracle Financial Services
What is the name of your City or Locality?
  [Unknown]:  Mumbai
What is the name of your State or Province?
  [Unknown]:  Maharashtra
What is the two-letter country code for this unit?
  [Unknown]:  IN
Is CN=cvrhp0729.i-flex.com, OU=BPD, O=Oracle Financial Services,
L=Mumbai, ST=Maharashtra, C=IN correct?
  [no]:  yes

Enter key password for <selfcert>
      (RETURN if same as keystore password):<Enter a password to
protect the key>
Re-enter new password:<Confirm the password keyed above>
```

3.2 Creating Identity Store with Trusted Certificates Issued by CA

3.2.1 Creation of Public and Private Key Pair

Browse to the bin folder of JRE from the command prompt and type the following command.



The items highlighted in blue are placeholders, and should be replaced with suitable values when running the command.

```
keytool -genkeypair -alias alias -keyalg keyalg -keysize keysize -  
sigalg sigalg -validity valDays -keystore keystore
```

In the above command,

1. *alias* is used to identify the public and private key pair created. This alias is required later when configuring the SSL attributes for the managed servers in Oracle Weblogic Server.
2. *keyalg* is the key algorithm used to generate the public and private key pair. The RSA key algorithm is recommended.
3. *keysize* is the size of the public and private key pairs generated. A key size of 1024 or more is recommended. Please consult with your CA on the key size support for different types of certificates.
4. *sigalg* is the algorithm used to generate the signature. This algorithm should be compatible with the key algorithm and should be one of the values specified in the Java Cryptography API Specification and Reference.
5. *valdays* is the number of days for which the certificate is to be considered valid. Please consult with your CA on this period.
6. *keystore* is used to specify the location of the JKS file. If no JKS file is present in the path provided, one will be created.

The command will prompt for the following attributes of the certificate and keystore:

1. **Keystore Password:** Specify a password that will be used to access the keystore. This password needs to be specified later, when configuring the identity store in Oracle Weblogic Server.
2. **Key Password:** Specify a password that will be used to access the private key stored in the keystore. This password needs to be specified later, when configuring the SSL attributes of the managed server(s) in Oracle Weblogic Server.
3. **First and Last Name (CN):** Enter the domain name of the machine used to access FLEXCUBE UBS, for instance, www.example.com
4. **Name of your Organizational Unit:** The name of the department or unit making the request, for example, BPD. Use this field to further identify the SSL Certificate you are creating, for example, by department or by physical server.

5. **Name of your Organization:** The name of the organization making the certificate request, for example, Oracle Financial Services. It is recommended to use the company or organization's formal name, and this name entered here must match the name found in official records.
6. **Name of your City or Locality:** The city in which your organization is physically located, for example Mumbai.
7. **Name of your State or Province:** The state/province in which your organization is physically located, for example Maharashtra.
8. **Two-letter Country Code for this Unit:** The country in which your organization is physically located, for example US, UK, IN etc.

Example

Listed below is the result of a sample execution of the command:

```
D:\Oracle\weblogic11g\jrocket_160_05_R27.6.2-20\bin>keytool -
genkeypair -alias cvrhp0729 -keyalg RSA -keysize 1024 -sigalg
SHA1withRSA -validity 365 -keystore D:\keystores\FCUBSKeyStore.jks


Enter keystore password:<Enter a password to protect the keystore>
Re-enter new password:<Confirm the password keyed above>
What is your first and last name?
  [Unknown]:  cvrhp0729.i-flex.com
What is the name of your organizational unit?
  [Unknown]:  BPD
What is the name of your organization?
  [Unknown]:  Oracle Financial Services
What is the name of your City or Locality?
  [Unknown]:  Mumbai
What is the name of your State or Province?
  [Unknown]:  Maharashtra
What is the two-letter country code for this unit?
  [Unknown]:  IN
Is CN=cvrhp0729.i-flex.com, OU=BPD, O=Oracle Financial Services,
L=Mumbai, ST=Maharashtra, C=IN correct?
  [no]:  yes

Enter key password for <cvrhp0729>
  (RETURN if same as keystore password):<Enter a password to
protect the key>
Re-enter new password:<Confirm the password keyed above>
```

3.2.2 Generating CSR

To purchase an SSL certificate, one needs to generate a Certificate Signing Request (CSR) for the server where the certificate will be installed.

A CSR is generated from the server and is the server's unique "fingerprint". The CSR includes the server's public key, which enables server authentication and secure communication.

 If the keystore file or the password is lost and a new one is generated, the SSL certificate and the private key will no longer match. A new SSL Certificate will have to be requested.

The CSR is created by running the following command in the bin directory of the JRE:

```
keytool -certreq -alias alias -file certreq_file -keystore keystore
```

In the above command,

1. *alias* is used to identify the public and private key pair. The private key associated with the alias will be utilized to create the CSR. Specify the alias of the key pair created in the previous step.
2. *certreq_file* is the file in which the CSR will be stored.
3. *keystore* is the location of the keystore containing the public and private key pair.

Example

Listed below is the result of a sample execution of the command

```
D:\Oracle\Weblogic11g\jrocket_160_05_R27.6.2-20\bin>keytool -certreq -
alias cvrhp0729 -file D:\keystores\certreq.csr -keystore
D:\keystores\FCUBSKeyStore.jks

Enter keystore password: [Enter the password used to access the
keystore]

Enter key password for <cvrhp0729> [Enter the password used to access
the key in the keystore]
```

3.2.3 Obtaining Trusted Certificate from CA

The processes of obtaining a trusted certificate vary from one CA to another. The CA might perform additional offline verification. Consult the CA issuing the certificate for details on the process to be followed for submission of the CSR and for obtaining the certificate.

3.2.4 Importing Certificate into Identity Store

Store the certificate obtained from the CA in the previous step, in a file, preferably in PEM format. Other formats like the p7b file format would require conversion to the PEM format. Details on performing the conversion are not listed here. Please refer to the Oracle Weblogic Server documentation on Securing Oracle Weblogic Server, for details on converting a Microsoft p7b file to the PEM format.

The command to be executed for importing a certificate into the identity store depend on whether the trust store chosen (in the earlier step; see section 2 of this document). It is highly recommended to verify the trust path when importing a certificate into the identity store. The commands provided below assume the use of the Java Standard Trust store.

Importing the Intermediate CA certificate

Most Certificate Authorities do not use the root CA certificates to issue identity certificates for use by customers. Instead, Intermediate CAs issue identity certificates in response to the submitted CSRs.

If the Intermediate CA certificate is absent in the Java Standard Trust store, the trust path for the certificate will be incomplete for the certificate, resulting in warnings issued by Weblogic Server during runtime. To avoid this, the intermediate CA certificate should be imported into the identity keystore. Although the intermediate CA certificate can be imported into the Java Standard Trust store, this is not recommended unless the intermediate CA can be trusted.

The following command should be executed to import the intermediate CA certificate into the keystore.

```
keytool -importcert -alias alias -file cert_file -trustcacerts -keystore  
keystore
```

In the above command,

1. *alias* is used to identify the public and private key pair. Specify the alias of the key pair used to create the CSR in the earlier step.
2. *cert_file* is the location of the file containing the intermediate CA certificate in a PKCS#7 format (PEM or DER file).
3. *keystore* is the location of the keystore containing the public and private key pair.



The trustcacerts flag is used to consider other certificates (higher intermediaries and the root CA) in the chain of trust. If no chain of trust is established during verification, the certificate will be displayed and one would be prompted to verify it. It is recommended that due diligence be observed, when the prompt is displayed to verify a certificate when a chain of trust is absent.

Listed below is a sample execution of the command

```
D:\Oracle\weblogic11g\jrocket_160_05_R27.6.2-20\bin>keytool -  
importcert -alias verisigntrialintermediateca -file  
D:\keystores\VerisignIntermediateCA.cer -trustcacerts -keystore  
D:\keystoreworkarea\FCUBSKeyStore.jks  
  
Enter keystore password:<Enter the password used to access the  
keystore>  
  
Certificate was added to keystore
```

Importing the Identity certificate

The following command should be executed to import the identity certificate into the keystore.

```
keytool -importcert -alias alias -file cert_file -trustcacerts -keystore  
keystore
```

In the above command,

1. *alias* is used to identify the public and private key pair. Specify the alias of the key pair used to create the CSR in the earlier step.

2. **cert_file** is the location of the file containing the PKCS#7 formatted reply from the CA, containing the signed certificate.
3. **keystore** is the location of the keystore containing the public and private key pair.

The trustcacerts flag is used to consider other certificates (intermediate CAs and the root CA) in the chain of trust. If no chain of trust is established during verification, the certificate will be displayed and one would be prompted to verify it. It is recommended that due diligence be observed, when the prompt is displayed to verify a certificate when a chain of trust is absent.


Listed below is a sample execution of the command

```
D:\Oracle\weblogic11g\jrockit_160_05_R27.6.2-20\bin>keytool -
importcert -alias cvrhp0729 -file D:\keystores\cvrhp0729.cer -
trustcacerts -keystore D:\keystoreworkarea\FCUBSKeyStore.jks

Enter keystore password:<Enter the password used to access the
keystore>

Enter key password for <cvrhp0729>:<Enter the password used to access
the private key>

Certificate reply was installed in keystore
```

 The previous set of commands assumed the presence of the appropriate root CA certificate (in the chain of trust) in the Java Standard Trust store, i.e. in the cacerts file. If the CA issuing the identity certificate (for the Weblogic Server) does not have the root CA certificate in the Java Standard Trust store, one can opt to import the root CA certificate into cacerts, or into the identity store, depending on factors including trustworthiness of the CA, necessity of transporting the trust store across machine, among others.

4. Configuring Identity and Trust Stores for Weblogic

4.1 Enabling SSL on Oracle Weblogic Server

To configure SSL on Oracle Weblogic server, login in to the Admin Console and follow the steps given below:

1. Under 'Change Center', click the button 'Lock & Edit'.
2. Expand 'Servers' node.
3. Select the name of the server for which you want to enable SSL (example - exampleserver).
4. Go to 'Configuration' and select General' tab.
5. Select the option 'SSL Listen Port Enabled' and specify the SSL listen port.
6. Against 'Listen Address', specify the hostname of the machine in which the application server is installed.

4.2 Configuring Identity and Trust Stores

To configure the Identity and Trust stores in Oracle Weblogic Server, log in to the Admin Console of Weblogic Server.

1. Under 'Change Center', click the button 'Lock & Edit'.
2. Expand 'Servers' node.
3. Select the name of the server for which you want to configure the keystores (example - exampleserver).
4. Go to 'Configuration' and select 'Keystores' tab.
5. In the filed 'Keystores', select the method for storing and managing private keys/digital certificate pairs and trusted CA certificates. This choice should match the one made in Section 2 of this document (Choosing the Identity and Trust Stores).
6. In the 'Identity' section, provide the following details:
 - **Custom Identity Keystore File Name:** Fully qualified path to the Identity keystore.
 - **Custom Identity Keystore Type:** Set this attribute to JKS, the type of the keystore. If left blank, it is defaulted to JKS (Java KeyStore).
 - **Custom Identity Keystore PassPhrase:** The password you enter when reading or writing to the keystore. This attribute is optional or required depending on the type of keystore. All keystores require the passphrase in order to write to the keystore. However, some keystores do not require the passphrase to read from the keystore. Oracle Weblogic server only reads from the keystore. So whether or not you define this property depends on the requirements of the keystore.
7. In the 'Trust' section, provide the following details:

If you choose **Java Standard Trust**, specify the password used to access the trust store.

If you choose **Custom Trust**, the following attributes have to be provided:

- **Custom Trust Keystore:** The fully qualified path to the trust keystore.
- **Custom Trust Keystore Type:** Set this attribute to JKS, the type of the keystore. If left blank, it defaults to JKS (Java KeyStore).
- **Custom Trust Keystore Passphrase:** The password you enter when reading or writing to the keystore. This attribute is optional or required depending on the type of keystore. All keystores require the passphrase in order to write to the keystore. However, some keystores do not require the passphrase to read from the keystore. Oracle Weblogic Server only reads from the keystore. So, whether or not you define this property depends on the requirements of the keystore.



When identity and trust stores are of the JKS format, the passphrases are not required.

5. Setting SSL attributes for Managed Servers

5.1 Setting SSL Attributes for Private Key Alias and Password

To configure the private key alias and password, log in to the Oracle Weblogic Server Admin Console.

1. Under '**Change Center**', click the button 'Lock & Edit'.
2. Expand '**Servers**' node.
3. Select the name of the server for which you want to configure keystores (example - exampleserver).
4. Go to '**Configuration**' and select '**SSL**' tab.
5. Select 'Keystores' from '**Identity and Trust Locations**'.
6. Under 'Identity' section, specify the following details:
 - **Private Key Alias**: set this attribute to the alias name defined for the key pair when creating the key pair in the Identity keystore.
 - **Private Key Passphrase**: The password defined for the key pair (alias_password), at the time of its creation. . Confirm the password.
7. Click '**Save**'.
8. Under '**Change Center**', click '**Activate changes**'.
9. Go to **controls** tab, check the appropriate server and click '**Restart SSL**'. Confirm when it prompts.

6. Testing Configuration

6.1 Testing Configuration

Once the Oracle Weblogic has been configured for SSL, deploy the application in the usual manner. After deployment, you can test the application in SSL mode. To launch the application in SSL mode you need to enter the URL in the following format:

https://(Machine Name):(SSL_Listener_port_no)/(Context_root)



It is recommended that the Oracle FLEXCUBE UBS web application be accessed via the HTTPS channel, instead of the HTTP channel.

7. Creating Resources on Weblogic

7.1 Introduction

This document explains the steps to be executed to deploy the FCUBS application and gateway application in application server.

7.2 Resource Administration

This section deals with the process of resource administration on Oracle Weblogic.

All the resources mention in “Resources To be Created” document are need to be created before deployment. One example for each category is explained in the following subsections.

7.2.1 Creating Data Source

The method for creating data sources is explained under the following headings.

7.2.1.1 Prerequisites

You need to create the data source with OCI enabled. For this, download Oracle Instant Client and install it. The details are given below.

Package	Download Location	Remarks
Oracle Instant Client Package	http://www.oracle.com/technetwork/database/features/instant-client/index-097480.html	Install Oracle Instant Client in a local directory. While configuring Weblogic for Windows or Unix/Linux box, you need to provide the directory path where Instant Client is installed.

You need to do the data source configuration with OCI driver enabled. The configurations are given below.

- Oracle Weblogic on Windows Box:
 - Set {ORACLE_HOME} in the environment variable.
 - Update the Environment Variable Path as {ORACLE_HOME}/Instance Client. This is required to load all the .dll files.
 - Ensure that the *ojdbc*.jar* file in {WL_HOME}/server/lib/*ojdbc*.jar* is the same as the file {ORACLE_HOME}/jdbc/lib/*ojdbc*.jar*. This is required for ensuring compatibility.
 - Update PATH in *StartWebLogic.bat* or in *setDomainEnv.bat*. This must be the path of directory where Oracle Instant Client is installed.
- Oracle Weblogic on Unix/Linux Box:

- Set {ORACLE_HOME} in the environment variable.
- Update the environment variable LD_LIBRARY_PATH as {ORACLE_HOME}/lib. This is to load all the .so files.
- Ensure that the ojdbc*.jar file in {WL_HOME}/server/lib/ojdbc*.jar is the same as the file {ORACLE_HOME}/jdbc/lib/ojdbc*.jar. This is to ensure compatibility.
- Update LD_LIBRARY_PATH in StartWeblogic.sh or in setDomainEnv.sh. This must be the path of directory where Oracle Instant Client is installed.
- If you are still not able to load the .so files, then you need to update the EXTRA_JAVA_PROPERTIES by setting Djava.library.path as {ORACLE_HOME}/lib in StartWebLogic.sh or in setDomainEnv.sh.


7.2.1.2 Non-XA Enabled Data Source

Follow the steps given below:

1. Start the Administrative Console of Weblogic application server. You can start this by entering Oracle Weblogic Admin Console URL in the address bar in an internet browser.


http://10.10.10.10:1001/console

Eg: http://10.10.10.10:1001/console



2. Specify the Weblogic administrator user name and password. Click 'Log In'.

3. Navigate to Oracle Weblogic home page.



4. Click 'LOCK & EDIT'.

Following screen is displayed:

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main content area is titled "Summary of JDBC Data Sources" and includes a "Configuration" tab. Below the tab, there is a descriptive paragraph and a "Customize this table" section. A table titled "Data Sources (Filtered - More Columns Exist)" displays two data sources:

Name	Type	JNDI Name	Targets
FCUBS113	Generic	jdbc/FCdevOS	ManagedServer1
FCUBS113Branch	Generic	jdbc/FCdevOSBranch	ManagedServer1


On the left side of the console, there is a "Domain Structure" tree showing the hierarchy of resources, including "Data Sources". Below the tree, there are sections for "How to...", "System Status", and "Health of Running Servers". The "System Status" section shows a bar chart with "OK (2)" highlighted in green. The bottom of the console displays the version "WebLogic Server Version 10.3.6.0" and copyright information.

5. Expand 'Services' and then 'Data Sources' under it. Click 'Lock & Edit' button.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main content area displays the 'Summary of JDBC Data Sources' page. On the left, the 'Domain Structure' tree is expanded to 'Services' > 'Data Sources'. The 'Change Center' shows 'No pending changes exist'. The 'System Status' section indicates 'Health of Running Servers' with 'OK (2)'. The 'Data Sources (Filtered - More Columns Exist)' table is shown below:

Name	Type	JNDI Name	Targets
Generic Data Source			
GridLink Data Source			
Multi Data Source	Generic	jdbc/foDevDS	ManagedServer1
<input type="checkbox"/> FCUBS113Branch	Generic	jdbc/foDevDSBranch	ManagedServer1

- To create a new data source, click 'New' and select 'Generic Data Source'. The following screen is displayed.




- Specify the following details:


JDBC Datasource Name	Name of the data source
JNDI Name	JNDI name which will be used for lookup
Database Type	Type of the database which is Oracle

- Click 'Next'.


The following screen is displayed:



9. Select the database driver as shown in the figure. Click 'Next'.



10. Uncheck 'Support Global Transactions'. Click 'Next'. The following screen is displayed:




11. This screen defines the connection properties. Set the details as shown below:

12. Specify the Database Name, Host Name, Port of the database server to connect, Database User Name and Password. Confirm the password.


13. Click 'Next'.

The following screen is displayed.




14. Specify the Driver Class Name (Eg: oracle.jdbc.OracleDriver)
15. Specify the URL.
16. jdbc:oracle:thin:@10.10.10.10:1001:<INSTANCE_NAME>Specify the Database Username (Eg: FCPB1121) and password.
17. Confirm the password.
18. Click 'Test Configuration' tab.

If the connection is established successfully, the message 'Connection test succeeded' is displayed.



19. Click 'Next'.

The following screen is displayed:




20. Check the boxes against the required servers. Click 'Finish'. The following screen is displayed:

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main content area is titled "Summary of JDBC Data Sources" and includes a "Configuration" tab. Below the tab, there is a table of data sources with checkboxes for selection. The table has columns for Name, Type, JNDI Name, and Targets.

Name	Type	JNDI Name	Targets
<input type="checkbox"/> FCUBS113	Generic	jdbc/fgdev05	ManagedServer1
<input type="checkbox"/> FCUBS113Branch	Generic	jdbc/fgdev05Branch	ManagedServer1
<input type="checkbox"/> FLEXTST.WORLD	Generic	FLEXTST.WORLD	AdminServer

On the left side of the console, there are several panels: "Change Center" (with "Activate Changes" and "Undo All Changes" buttons), "Domain Structure" (showing a tree view with "Data Sources" selected), "How to I..." (with links for creating and deleting data sources), and "System Status" (showing health indicators for running servers: Failed (0), Critical (0), Overloaded (0), Warning (0), and OK (2)).

21. Click 'Activate Changes' button. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.




22. The datasource has been created.

7.2.1.3 Non-XA Enabled Data Source


1. Follow the steps given below: Start the Administrative Console of Weblogic application server. You can start this by entering Oracle Weblogic Admin Console URL in the address bar in an internet browser.

http://10.10.10.10:1001/console Eg: http://10.10.10.10:1001/console



2. Specify the Weblogic administrator user name and password. Click 'Log In'.

3. Navigate to Oracle WebLogic home page.



The following screen is displayed:

The screenshot displays the Oracle WebLogic Server Administration Console interface. The main content area is titled "Summary of JDBC Data Sources" and includes a "Configuration" tab. Below the tab, there is a descriptive paragraph about JDBC data sources and a "Customize this table" section. A table titled "Data Sources (Filtered - More Columns Exist)" lists two data sources: FCUBS113 and FCUBS113Branch, both of Generic type, with their respective JNDI names and targets.

Summary of JDBC Data Sources

A JDBC data source is an object bound to the JNDI tree that provides database connectivity through a pool of JDBC connections. Applications can look up a data source on the JNDI tree and then borrow a database connection from a data source.

This page summarizes the JDBC data source objects that have been created in this domain.

Customize this table

Data Sources (Filtered - More Columns Exist)

Name	Type	JNDI Name	Targets
FCUBS113	Generic	jdbc/FCdevOS	ManagedServer1
FCUBS113Branch	Generic	jdbc/FCdevOSBranch	ManagedServer1

Showing 1 to 2 of 2. Previous | Next

Showing 1 to 2 of 2. Previous | Next


Oracle WebLogic Server Administration Console
 Home Log Out Preferences Record Help
 Welcome, weblogic Connected to: fcubs113_domain
 Summary of JDBC Data Sources
 Configuration Monitoring
 Change Center
 View changes and restarts
 No pending changes exist. Click the Release Configuration button to allow others to edit the domain.
 Lock & Edit
 Release Configuration
 Domain Structure
 fcubs113_domain
 Environment
 Deployments
 Services
 Messaging
 Data Sources
 Persistent Stores
 Foreign JNDI Providers
 Work Contexts
 XML Registries
 XML Entity Caches
 JCDM
 Mail Sessions
 File T3
 How do I...
 Create JDBC generic data sources
 Create JDBC GridLink data sources
 Create JDBC multi data sources
 Delete JDBC data sources
 Delete JDBC multi data sources
 System Status
 Health of Running Servers
 Failed (0)
 Critical (0)
 Overloaded (0)
 Warning (0)
 OK (2)
 WebLogic Server Version: 10.3.4.0
 Copyright © 1996, 2010, Oracle and/or its affiliates. All rights reserved.
 Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.
 http://10.184.74.143:8888/console/console.portal?_rfpb=true&_pageLabel=UserPreferencesPageGeneral
 Local intranet 100%

- Expand 'Services' and then 'Data Sources' under it. Click 'Lock & Edit' button.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main content area is titled 'Summary of JDBC Data Sources' and includes a 'Configuration' tab. A 'Change Center' on the left indicates 'No pending changes exist' and features a 'Lock & Edit' button. The 'Domain Structure' tree on the left shows the path: fcuhs113_domain > Environment > Deployments > Services > Data Sources. Below the tree is a 'How do I...' section with links to create or delete generic and GridLink data sources. The 'System Status' section shows 'Health of Running Servers' with a bar chart indicating 2 OK servers. The main table, 'Data Sources (Filtered - More Columns Exist)', lists two data sources:

	Type	JNDI Name	Targets
Generic Data Source			
GridLink Data Source			
Multi Data Source	Generic	jdbc/fcdevOS	ManagedServer1
<input type="checkbox"/> FCUBS113Branch	Generic	jdbc/fcdevOSBranch	ManagedServer1


- To create a new data source, click 'New' and select 'Generic Data Source'.



- Specify the following details:


JDBC Datasource Name	Name of the Datasource
JNDI Name	JNDI for lookup
Database Type	Oracle

7. Click 'Next'.




8. Select the database driver as shown in the figure. Click 'Next'.

Following screen is displayed:




9. Select Logging Last Resource then uncheck 'Support Global Transactions'. Click 'Next'. The following screen is displayed:



10. This screen defines the connection properties. Set the details as given below:
11. Specify the Database Name, Host Name, Port of the database server to connect, Database User Name and Password. Confirm the password.

12. Click 'Next'. The following screen is displayed.



13. Specify the Driver Class Name (Eg: oracle.jdbc.OracleDriver)

14. Specify the URL.

Default URL: jdbc:oracle:thin:@10.10.10.10:1001:<INSTANCE_NAME>.


Change the default URL to: jdbc:oracle:oci:@10.10.10.10:1010:<INSTANCE_NAME>

15. Specify the Database Username (Eg: testdb) and password.


16. Confirm the password.

17. Click 'Test Configuration' tab.


18. If the connection is established successfully, the message 'Connection test succeeded' is displayed.



19. Click 'Next'. The following screen is displayed:




20. Check the boxes against the required servers. Click 'Finish'. The following screen is displayed:




21. Click 'Activate Changes' button. Click 'Activate Changes' button on the left pane.

The message 'All the changes have been activated. No restarts are necessary' is displayed.



22. 'FCUBSDS' datasource is created.

23. Click the datasource, and then click on the Connection Pool tab.



24. Select the statement cache type as 'LRU'.

25. Specify the statement cache size as '200'.

26. Click 'Save'.



Note the following

- You need to create another data source for Oracle FCUBS with the JNDI name '<Non-XA FCUBS HOST JNDI name>_ASYNC' for batch process. For example, if the Oracle FCUBS HOST Non XA data source JNDI name is 'jdbc/fcjdevDS', then you need to create another data source for FCUBS with the JNDI name 'jdbc/fcjdevDS_ASYNC'.
- While creating a branch using the 'Branch Parameters Maintenance' (STDBRANC) screen, if you have created a data source for the branch, then you need to create a corresponding ASYNC data source with the JNDI name '<Non-XA FCUBS BRANCH JNDI name>_ASYNC'.


7.2.2 JMS Server Creation

Follow the steps given below:


1. Start the Administrative Console of Weblogic application server. You can start this by entering Oracle Weblogic Admin Console URL in the address bar in an internet browser.

<http://10.10.10.10:1001/console> Eg: <http://10.10.10.10:1001/console>


Following screen is displayed:




2. Specify the Weblogic administrator user name and password. Click 'Log In'.
3. Navigate to Oracle Weblogic home page.




4. Following screen is displayed:



5. Expand 'Services' and then 'Messaging' and 'JMS Server' under it. Click 'Lock & Edit' button.




6. Click 'New'.



7. Specify the following details:


JMS Server Name	Specify the name of JMS Server.
-----------------	---------------------------------

8. Click 'Create a new Store' button. The following screen is displayed.



9. Select 'File Store' as the type and click 'Next'.


Following screen is displayed:




10. To identify the new File Store, specify the following properties:

- Specify the file store name as FCUBS_FileStore.
- Select a server. For this file store, you may select ManagedServer1 (created by the user).
- Specify the existing Directory as C:/FCUBS_FileStore.
- Click 'OK'.


The following screen is displayed with message 'File store created successfully'.



11. Click 'Next'.



12. Select the target managed server. Click 'Finish'.



13. The message 'JMS Server created successfully' is displayed.

14. Click 'Activate Changes' under Change Center. The message 'All changes have been activated. No restarts are necessary' is displayed.

7.2.3 JMS Modules Creation

Follow the steps given below:

1. Navigate to the WEBLOGIC Home Page. Click 'JMS Modules' on domain structure by expanding 'Messaging'.

The following screen is displayed:

Oracle WebLogic Server Administration Console

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: fcubs113_domain

Home > Summary of JDBC Data Sources > FLEXTTEST.WORLD > Summary of JMS Servers > Summary of JDBC Data Sources > FLEXTTEST.WORLD > Summary of JMS Servers > JMS Modules

JMS Modules

JMS system resources are configured and stored as modules similar to standard J2EE modules. Such resources include queues, topics, connection factories, templates, destination keys, quota, distributed queues, distributed topics, foreign servers, and JMS store-and-forward (SAF) parameters. You can administratively configure and manage JMS system modules as global system resources.

This page summarizes the JMS system modules that have been created for this domain.

Customize this table

JMS Modules

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

Name	Type
There are no items to display	

Showing 0 to 0 of 0 Previous | Next

Showing 0 to 0 of 0 Previous | Next

WebLogic Server Version: 10.3.4.0
Copyright © 1996-2010, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.


2. For creating New JMS System Modules, click 'Lock & Edit' button.

The screenshot displays the Oracle WebLogic Server Administration Console interface. The browser window title is "JMS Modules - fcubs113_domain - WLS Console - Windows Internet Explorer". The address bar shows the URL: http://110.184.74.143:8888/console/console.portal?_rfpb=true&_pageLabel=http://110.184.74.143:8888/console/console.portal?_rfpb=true&_pageLabel=JmsModulesTablePage. The page content includes:

- Change Center:** A section on the left with the heading "View changes and restarts". It contains a "Lock & Edit" button and a "Release Configuration" button. Below this is the "Domain Structure" tree, which is expanded to show "JMS Modules".
- System Status:** A section on the left showing the "Health of Running Servers" with a progress bar and status indicators for Failed (0), Critical (0), Overloaded (0), Warning (0), and OK (2).
- JMS Modules Page:** The main content area. It features a "Lock & Edit" button at the top left. Below it is a table with columns "Name" and "Type". The table is currently empty, displaying "There are no items to display".

At the bottom of the console, there is a footer with the text: "WebLogic Server Version 10.3.4.0. Copyright © 1996, 2010, Oracle and/or its affiliates. All rights reserved. Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners."

3. Click 'New' button. The following screen is displayed.



Enter the System Module Name as FCUBS_SystemModule.

Enter the Description File Name as FCUBS_SystemModule.

4. Click 'Next'.

The following screen is displayed.

The screenshot displays the Oracle WebLogic Server Administration Console interface. The browser window title is "Create JMS System Module - fcubs113_domain - WLS Console - Windows Internet Explorer". The URL is "http://10.104.74.143:8888/console/console.portal?CreateJMSSystemModulePortlet_actionOverride=/com/bea/console/actions/jms/modules/system/createmodule/selectTargets".

The main content area is titled "Create JMS System Module". It includes a breadcrumb trail: "Home > Summary of JDBC Data Sources > FLEXTTEST.WORLD > Summary of JMS Servers > Summary of JDBC Data Sources > FLEXTTEST.WORLD > Summary of JMS Servers > JMS Modules".

Below the breadcrumb, there are navigation buttons: "Back", "Next", "Finish", and "Cancel".

The main instruction reads: "The following properties will be used to target your new JMS system module. Use this page to select the server or cluster on which you would like to deploy this JMS system module. You can reconfigure targets later if you wish."

Under the heading "Targets:", there is a table with the following content:

Servers	
<input type="checkbox"/>	AdminServer
<input checked="" type="checkbox"/>	ManagedServer1


Below the table are navigation buttons: "Back", "Next", "Finish", and "Cancel".

On the left side of the console, there are several panels:


- Change Center:** "View changes and restarts". "No pending changes exist. Click the Release Configuration button to allow others to edit the domain." Buttons: "Lock & Edit", "Release Configuration".
- Domain Structure:** A tree view showing the hierarchy: "fcubs113_domain" > "Environment" > "Deployments" > "Services" > "Messaging" > "JMS Servers" > "Store-and-Forward Agents" > "JMS Modules" > "Path Services" > "Bridges" > "Data Sources" > "Persistent Stores" > "Foreign JNDI Providers" > "Work Contexts".
- How do I...:** A list of links: "Configure JMS system modules", "Configure JMS servers".
- System Status:** "Health of Running Servers". A progress bar shows: "Failed (0)", "Critical (0)", "Overloaded (0)", "Warning (0)", "OK (2)".

At the bottom of the console, there is a footer with the text: "WebLogic Server Version 10.3.4.0. Copyright © 1996, 2010, Oracle and/or its affiliates. All rights reserved. Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners."

5. Check the box against the server created. Click 'Next'. The following screen is displayed.




6. Click 'Finish' button. The following screen is displayed.



7. Click 'Activate Changes' button on the left pane.

The message 'All the changes have been activated. No restarts are necessary' is displayed.




7.2.4 Subdeployment Creation

Follow the steps given below:

1. Navigate to the WEBLOGIC Home Page. Click 'JMS Modules' on domain structure by expanding 'Messaging'.

The following screen is displayed:



2. Click 'Lock & Edit' button.

3. Select the JMS module created earlier.

The screenshot displays the Oracle WebLogic Server Administration Console interface. The main content area is titled "Settings for FCUBS_SystemModule" and includes tabs for Configuration, Subdeployments, Targets, Security, and Notes. The Configuration tab is active, showing details for the JMS system module "FCUBS_SystemModule".

Settings for FCUBS_SystemModule

Configuration | Subdeployments | Targets | Security | Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name: FCUBS_SystemModule The name of this JMS system module. More Info...

Descriptor File Name: jms/FCUBS_SystemModule-jms.xml The name of the JMS module descriptor file. More Info...

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

Customize this table

Summary of Resources

<input type="checkbox"/>	Name	Type	JNDI Name	Subdeployment	Targets
There are no items to display					

Showing 0 to 0 of 0 Previous | Next

System Status: Health of Running Servers: Failed (0), Critical (0), Overloaded (0), Warning (0), OK (2)

4. Click 'Subdeployments' tab.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The browser window title is "Settings for FCUBS_SystemModule - fcubs113_domain - WLS Console - Windows Internet Explorer". The URL is "http://10.104.74.143:8888/console/console.portal?_rfpb=true&_pageLabel=JMSSystemModuleSubDeploymentTabPage&handle=com.bea.console.handles.JMSHandle%28%22%22". The console header shows "ORACLE WebLogic Server Administration Console" and "Welcome, weblogic | Connected to: fcubs113_domain".


The main content area is titled "Settings for FCUBS_SystemModule" and has tabs for "Configuration", "Subdeployments", "Targets", "Security", and "Notes". The "Subdeployments" tab is active. Below the tabs, there is a text block: "This page displays subdeployments created for a JMS system module. A subdeployment is a mechanism by which JMS module resources (such as queues, topics, and connection factories) are grouped and targeted to a server resource (such as JMS servers, server instances, or cluster)."

Below the text, there is a section "Customize this table" with a "Subdeployments" table. The table has columns for "Name", "Resources", and "Targets". The table is currently empty, with the message "There are no items to display".

On the left side of the console, there are several panels: "Change Center" (with "View changes and restarts" and "Release Configuration" buttons), "Domain Structure" (a tree view showing the hierarchy of the domain), "How do I..." (with links to "Configure subdeployments in JMS system modules" and "Configure JMS system modules"), and "System Status" (showing the health of running servers: Failed (0), Critical (0), Overloaded (0), Warning (0), and OK (2)).


At the bottom of the console, there is a footer with the text: "WebLogic Server Version: 10.3.4.0 Copyright © 1996, 2010, Oracle and/or its affiliates. All rights reserved. Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners."

5. Click 'New'. The following screen is displayed.




6. Specify the Subdeployment Name as 'FCUBS'. Then click 'Next'.

The following screen will be displayed.




7. Select the JMS Server (as created by the user).
8. Click 'Finish' button.

9. Following screen is displayed.




10. Click 'Activate Changes'. Following screen is displayed.



7.2.5 JMS Queue Creation

1. Select the JMS Module created earlier.



2. You need to set the configuration for FCUBS_SystemModule is to be set.
3. Click 'Configuration'. Then click 'Lock & Edit'.

The Following screen is displayed.

The screenshot displays the Oracle WebLogic Server Administration Console interface. The browser window title is "Settings for FCUBS_SystemModule - fcubs113_domain - WLS Console - Windows Internet Explorer". The address bar shows the URL: `http://10.104.74.143:8888/console/console.portal?_rfpb=true&_pageLabel=JMSSystemModuleConfigGeneralPage`. The console header includes "ORACLE WebLogic Server Administration Console" and "Welcome, weblogic | Connected to: fcubs113_domain".


The main content area is titled "Settings for FCUBS_SystemModule" and has tabs for "Configuration", "Subdeployments", "Targets", "Security", and "Notes". The "Configuration" tab is active, showing general information about the JMS system module. It includes fields for "Name" (FCUBS_SystemModule) and "Descriptor File Name" (jms/FCUBS_SystemModule-jms.xml). Below this is a "Summary of Resources" section with a table that currently contains no items.

On the left side, there are several panels:


- Change Center:** Shows "View changes and restarts" with a "Release Configuration" button.
- Domain Structure:** A tree view showing the hierarchy from "fcubs113_domain" down to "Work Contexts".
- How do I...:** A list of help topics related to configuring JMS system modules.
- System Status:** A "Health of Running Servers" section showing a bar chart with 2 servers in "OK" status.

The footer of the console displays "WebLogic Server Version: 10.3.4.0" and copyright information for Oracle Corporation.

4. Click 'New'. The following screen is displayed.




5. Select the 'Queue' option. Then click 'Next'.



For creating new JMS System Module Resources, follow the steps given below:

- Enter the Name of the Queue as 'NOTIFY_DEST_QUEUE'.
- Enter the JNDI Name as 'NOTIFY_DEST_QUEUE'.
- Select the Template as 'None'.
- Click 'Next'.

Following screen is displayed.




6. Select the managed server created by the user. Click 'Finish' button.

The screenshot shows the Oracle WebLogic Server Administration Console. The main content area is titled "Settings for FCUBS_SystemModule" and includes a "Configuration" tab. A message states: "The JMS Queue was created successfully". Below this, there is a "Summary of Resources" table with the following data:

Name	Type	JNDI Name	Subdeployment	Targets
NOTIFY_DEST_QUEUE	Queue	NOTIFY_DEST_QUEUE	FCUBS	FCUBS_JMServer

The left sidebar contains navigation menus for "Change Center", "Domain Structure", "How do I...", and "System Status". The "System Status" section shows "Health of Running Servers" with 2 servers in "OK" status.

- The JMS Queue has been created successfully. Click 'Activate Changes' under 'Change Center'.



- Click 'New' to create more Queues. You may follow the same steps to create other queues.

7.2.6 JMS Connection Factory Creation

After creating the queues, you need to create the connection factory. To perform this, follow the steps given below:

1. Click 'New'.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main content area is titled "Settings for FCUBS_SystemModule" and includes tabs for Configuration, Subdeployments, Targets, Security, and Notes. The "Configuration" tab is active, displaying general information about the JMS system module and its resources. A "Summary of Resources" table is present, with a "New" button highlighted in the header. The table contains one resource:

<input type="checkbox"/>	Name	Type	JNDI Name	Subdeployment	Targets
<input type="checkbox"/>	NOTIFY_DEST_QUEUE	Queue	NOTIFY_DEST_QUEUE	FCUBS	FCUBS_JMServer

At the bottom of the table, there is another "New" button. The left sidebar shows the "Domain Structure" tree with "FCUBS_SystemModule" selected under "JMS Modules". The "System Status" section shows the health of running servers as "OK (2)".


The following screen is displayed:

The screenshot displays the Oracle WebLogic Server Administration Console in a web browser. The main content area is titled "Create a New JMS System Module Resource" and features a wizard interface. The "Choose the type of resource you want to create." step is active, showing a list of resource types with radio buttons:

- Connection Factory**: Defines a set of connection configuration parameters that are used to create connections for JMS clients. [More Info...](#)
- Queue**: Defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to a queue is distributed to only one consumer. [More Info...](#)
- Topic**: Defines a publish/subscribe destination type, which are used for asynchronous peer communications. A message delivered to a topic is distributed to all topic consumers. [More Info...](#)
- Distributed Queue**: Defines a set of queues that are distributed on multiple JMS servers, but which are accessible as a single, logical queue to JMS clients. [More Info...](#)
- Distributed Topic**: Defines a set of topics that are distributed on multiple JMS servers, but which are accessible as a single, logical topic to JMS clients. [More Info...](#)
- Foreign Server**: Defines foreign messaging providers or remote WebLogic Server instances that are not part of the current domain. [More Info...](#)
- Quota**: Controls the allotment of system resources available to destinations. [More Info...](#)
- Destination Sort Key**: Defines a unique sort order that destinations can apply to arriving messages. [More Info...](#)
- JMS Template**: Defines a set of default configuration settings for multiple destinations. [More Info...](#)
- SAF Imported Destinations**: Defines a collection of imported store-and-forward (SAF) destinations. A SAF destination is a representation of a queue or topic in a remote server instance or cluster that is imported into the local cluster or server instance, so that the local server instance or cluster can send messages to the remote server instance or cluster. [More Info...](#)


On the left side, the "Domain Structure" tree shows the hierarchy: fcu113_domain > Environment > Services > Messaging > JMS Servers > Store-and-Forward Agents > JMS Modules > Path Services > Bridges > Data Sources > Persistent Stores > Foreign JNDI Providers > Work Contexts. Below this, the "System Status" section shows the "Health of Running Servers" with indicators for Failed (0), Critical (0), and Overloaded (0).

2. Select 'Connection Factory'. Click 'Next'.




3. Enter the Name of the Connection Factory as 'NotifyDestQCF'.
4. Enter the JNDI Name as 'NotifyDestQCF'.
5. Check the box 'XA Connection Factory Enabled'.
6. Click 'Next'.

The following screen is displayed:




7. Click 'Advanced Targeting'. The following screen is displayed.



8. Select the 'Subdeployments' as FCUBS.
9. Under JMS Servers, check the box against 'Managed Server'.


10. Click 'Finish'. The following screen is displayed:




11. The message 'Connection Factory created successfully' is displayed.

12. Click on the Connection Factory 'NotifyDestQCF' to have XA Connection Factory enabled.

The following screen will be displayed.




13. Click 'Transactions' Tab. The following screen is displayed.



14. Check the box 'XA Connection Factory Enabled'.


15. Click 'Save'. The following screen is displayed.



16. The message 'Settings updated successfully' is displayed.

17. Click 'Activate Changes' button under 'Change Center'.

The message 'All the changes have been activated. No restarts are necessary' is displayed.



7.3 Configuring Weblogic for PMGateway


To deploy and run PMGateway application in weblogic server following configuration needs to be done

Copy runtime12.jar from database servers ORACLE_HOME/sqlj/lib to application servers library path WEBLOGIC_HOME/user_projects/domains/<app-domain>/lib

7.4 Configuring Weblogic for Oracle FLEXCUBE

This section explains the steps for configuring Oracle WebLogic application server for Oracle FLEXCUBE. Follow the steps given below:

1. Select the domain from the domain structure as shown below. (Eg: fcubs113_domain).



The following screen is displayed:

The screenshot displays the Oracle WebLogic Server Administration Console in a web browser. The browser's address bar shows the URL: `http://10.104.74.143:8888/console/console.portal?_rfpb=true&_pageLabel=DomainConfigGeneralPage&DomainConfigGeneralPageHandle=com.bea.console.handles.JMDFHand`. The page title is "Settings for fcubs113_domain - fcubs113_domain - WLS Console - Windows Internet Explorer".


The console interface includes a navigation pane on the left with sections for "Change Center", "Domain Structure", "How do I...", and "System Status". The "System Status" section shows the "Health of Running Servers" with a bar chart indicating 2 servers are in an "OK" state.

The main content area is titled "Settings for fcubs113_domain" and contains a "Configuration" tab with sub-tabs for "General", "JTA", "JPA", "EJBs", "Web Applications", "Logging", and "Log Filters". The "General" sub-tab is active, showing the following configuration options:


- Name:** fcubs113_domain (The name of this WebLogic Server domain. [More Info...](#))
- Enable Administration Port** (Specifies whether the domain-wide administration port should be enabled for this WebLogic Server domain. Because the administration port uses SSL, enabling the administration port requires that SSL must be configured for all servers in the domain. [More Info...](#))
- Administration Port:** 9002 (The common secure administration port for this WebLogic Server domain. (Requires you to enable the administration port.) [More Info...](#))
- Production Mode:** true (Specifies whether all servers in this domain run in production mode. Once enabled, this can only be disabled in the admin server startup command line. [More Info...](#))
- Enable Exalogic Optimizations** (Specifies whether optimizations for Oracle Exalogic should be enabled. Optimizations include improved thread management and request processing, and reduced lock contention. This attribute should be enabled only when configuring a WebLogic domain for Oracle Exalogic. For more information, see "Enabling Exalogic-Specific Enhancements in Oracle WebLogic Server 11g Release 1 (10.3.4)" in the Oracle Exalogic Deployment Guide. [More Info...](#))
- Enable Cluster Constraints** (Specifies that deployments targeted to a cluster succeed only if all servers in the cluster are running. [More Info...](#))
- Enable on-demand deployment of internal applications** (Specifies whether internal applications such as the console, uddi, wlstclient, and uddiexplorer are deployed on demand (first access) instead of during server startup. [More Info...](#))
- Enable Oracle Guardian Agent** (Specifies whether the Guardian Agent is deployed when starting servers in the current domain. [More Info...](#))

At the bottom of the configuration area, there is an "Advanced" section and a "Save" button.

2. Under 'configuration' tab ,Select 'Web Applications'. The following screen is displayed.




3. Scroll down and ensure that the details are as shown in the figure. The remaining portion of the screen is given below:



4. Check the options 'JSP Compiler Backwards Compatible' and 'Archived Real Path Enabled'.
5. Click 'Save'.

6. The following screen is displayed:



7. Ensure that the message 'Settings are updated successfully' is displayed.

8. Click the button 'Active Changes'.


7.5 Setup/Configure Mail Session in Weblogic

This section describes the set of configurations changes required in Oracle Weblogic Server when Oracle FLEXCUBE UBS is configured to generate and send passwords to users via e-mail.

7.5.1 Creating JavaMail Session

To configure mail session, follow the steps below.

1. Expand 'Services' on the left pane of the application server. Click 'Mail Sessions'.



2. Click 'Lock & Edit'.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The browser window title is "Summary of Mail Sessions - fcubs113_domain - WLS Console - Windows Internet Explorer". The URL is "http://10.194.74.143:8888/console/console.portal?_rfpb=true&_pageLabel=MailMailSessionTablePage".

The main content area is titled "Summary of Mail Sessions" and contains the following text:

Mail sessions facilitate the process of using the JavaMail APIs, which provide applications and other J2EE modules with access to Internet Message Access Protocol (IMAP)- and Simple Mail Transfer Protocol (SMTP)-capable mail servers on your network or the Internet.

This page summarizes the mail sessions that have been configured in the current WebLogic Server domain.

Below the text is a section titled "Customize this table" with a "Mail Sessions" table. The table has three columns: "Name", "Properties", and "JNDI Name". The table is currently empty, displaying "Showing 0 to 0 of 0" and "Previous | Next" navigation links. Above the table are "New", "Clone", and "Delete" buttons. Below the table are "New", "Clone", and "Delete" buttons.

On the left side of the console, there is a "Change Center" section with a "Lock & Edit" button highlighted. Below it is a "Domain Structure" tree view showing the hierarchy of the domain, including "Messaging", "JMS Servers", "Store-and-Forward Agents", "JMS Modules", "Path Services", "Bridges", "Data Sources", "Persistent Stores", "Foreign JNDI Providers", "Work Contexts", "XML Registries", "XML Entity Caches", "JCOM", and "Mail Sessions".

At the bottom of the console, there is a "System Status" section showing the health of running servers. The status is "OK (2)".

The footer of the console displays the following information:

WebLogic Server Version: 10.3.4.0
Copyright © 1996, 2010, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

3. Following screen is displayed; Click 'New' for creating a new session.

The screenshot displays the Oracle WebLogic Server Administration Console. The browser window title is "Summary of Mail Sessions - fcubs113_domain - WLS Console - Windows Internet Explorer". The URL is "http://10.184.74.143:8888/console/console.portal?_nfpb=true&_pageLabel=MailCreateMailSession".

The console interface includes a navigation bar with "Home", "Log Out", "Preferences", "Record", and "Help". The user is logged in as "weblogic" and connected to the "fcubs113_domain".

The main content area is titled "Summary of Mail Sessions". It contains the following text:

Mail sessions facilitate the process of using the JavaMail APIs, which provide applications and other J2EE modules with access to Internet Message Access Protocol (IMAP)- and Simple Mail Transfer Protocol (SMTP)-capable mail servers on your network or the Internet.

This page summarizes the mail sessions that have been configured in the current WebLogic Server domain.

Below the text is a section titled "Customize this table" with a sub-section "Mail Sessions (Filtered - More Columns Exist)". It features a table with the following structure:

<input type="checkbox"/>	Name ↕	Properties	JNDI Name
There are no items to display			

Buttons for "New", "Clone", and "Delete" are present above and below the table. The table also shows "Showing 0 to 0 of 0" and "Previous | Next" navigation options.


On the left side of the console, there are several panels:

- Change Center:** "No pending changes exist. Click the Release Configuration button to allow others to edit the domain." Buttons: "Lock & Edit", "Release Configuration".
- Domain Structure:** A tree view showing the hierarchy of the domain, including Messaging, JMS Servers, Store-and-Forward Agents, JMS Modules, Path Services, Bridges, Data Sources, Persistent Stores, Foreign JNDI Providers, Work Contexts, XML Registries, XML Entity Caches, JCOM, and Mail Sessions.
- How do I...:** A list of links: "Configure access to JavaMail", "Target mail sessions", "Delete mail sessions".
- System Status:** "Health of Running Servers" with a progress bar showing: Failed (0), Critical (0), Overloaded (0), Warning (0), and OK (2).

At the bottom of the console, there is a footer with the text: "WebLogic Server Version: 10.3.4.0. Copyright © 1996-2010, Oracle and/or its affiliates. All rights reserved. Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners."

The browser status bar at the bottom shows "Waiting for http://10.184.74.143:8888/console/console.portal?_nfpb=true&_pageLabel=MailCreateMailSession..." and "Local intranet" with a 100% zoom level.

4. Following screen is displayed.




5. Specify the required details to create a session. Sample details are given below:

Name

FCUBSMailSession

JNDI Name

mail/FCUBSMail

 This JNDI name needs to be maintained in fcubs.properties file with encrypted format.

Java Mail Properties

mail.host=<HOST_MAIL_SERVER>

Eg: samplename.mail.com

mail.smtps.port=<SMTPS_SERVER_PORT>

Eg: 1010

mail.transport.protocol=<MAIL_TRANSFER_PROTOCOL>

Eg: smtps


mail.smtps.auth=true

mail.smtps.host==<HOST_SMTPS_MAIL_SERVER>

Eg: samplename.mail.com

6. Click 'Next'.

The following screen is displayed.



7. Check the box against the required servers and click 'Finish' to complete the configuration.




'fcubs.properties' file needs to be updated with the encrypted values of

- SMTP_HOST
- SMTP_USER
- SMTP_PASSWORD
- SMTP_JNDI

This can be achieved using the Oracle FLEXCUBE UBS Installer.

8. Click 'Active Changes' button to activate the current mail session settings.



7.5.2 Configuration of the TLS/SSL Trust Store for Weblogic Server

As described in the previous section, Oracle FLEXCUBE UBS uses SMTPS to send outgoing mails. SMTPS uses SSL to ensure transport-level security of the mail messages and hence, the certificate of the mail server needs to be imported into the trust store(s) of the Managed Servers where Oracle FLEXCUBE UBS is deployed.

The certificate of the mail server needs to be specifically imported into the trust store configured for the Managed Server(s), as configured in the Oracle FLEXCUBE UBS Installation guide titled 'SSL Configuration On Weblogic' (SSL_Configuration).

For further details on importing the certificate of the mail server into the trust store, refer to the documentation for the Sun Java keytool utility (Key and Certificate Management tool).



Weblogic Configuration
[October] [2015]
Version 12.1.0.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.