

Oracle Linux for MICROS Base Workstation Configurations

Oracle Linux for MICROS Base Workstation Configurations											
Model	W55A	KDC210	WS610	WS620	WS650	WS625E	WS625X	WS655X	WS310/310R	ES400	ES410
Processors	Intel Atom N450	Intel Atom Z8350	Intel Atom E3827	Intel Celeron 3765U	Intel Core i5 5350U	Intel Celeron 4205U	Intel Celeron 4305UE	Intel Core i5-8365UE	Intel Atom E3930	Intel Atom E3930	Intel Atom E3950
Memory	512M DDR2	4G LPDDR3	4G DDR3	4G DDR3L	8G DDR3L	4G DDR4	8G DDR4	8G DDR4	4GB DDR3L	4GB DDR3	4GB DDR3
Storage	64G CF	64G eMMC	32G M0.297 SSD	128G M.2 SATA SSD	256G M.2 SATA SSD	64G M.2 SATA SSD	128G M.2 NVME SSD	256G M.2 NVME SSD	64GB eMMC SSD	64G M.2 SATA SSD	128G M.2 SATA SSD
Display Size	15.1" 1024x768	-	15.6" 1920x1080	15.6" 1920x1080	15.6" 1920x1080	15.6" 1920x1080	15.6" 1920x1080	15.6" 1920x1080	10.1" 1280x800	23.8" 1920x1080	23.8" 1920x1080
Touch/Non-Touch	5-Wire Resistive	-	PCAP Touch	PCAP Touch	PCAP Touch	PCAP Touch	PCAP Touch	PCAP Touch	PCAP Touch	Non-Touch LCD or PCAP Touch	PCAP Touch
USB Type-C	-	-	-	-	-	1x	1x	1x	1x	1x	1x
10/100/1G Ethernet	1x	1x	1x	1x	1x	1x	2x	2x	1x	1x	1x
Standard USB	4x USB 2.0	2x USB 2.0 1x USB 3.0	2x USB 2.0 2x USB 3.0	2x USB 2.0 2x USB 3.0	2x USB 2.0 2x USB 3.0	4x USB 3.0	4x USB 3.0	4x USB 3.0	2x USB 2.0	2x USB 2.0	2x USB 2.0
12V/24V PUSB	-	-	-	24V PUSB	24V PUSB	-	12V PUSB & 24V PUSB	12V PUSB & 24V PUSB	-	-	-
IDN (RJ45)	1x	-	1x	1x	1x	1x	1x	1x	1x	1x	1x
Serial Ports	3x	1x	3x (2 Power)	2x (1Power)	2x (1 Power)	2x (1 Power)	2x (1 Power)	2x (1 Power)	1x	1x	1x
12V Output	1x	-	1x	1x	1x	1x	1x	1x	-	-	-
Customer Display support	1x	-	1x	1x	1x	1x	1x	1x	Integrated CFD	-	-
MICROS Cash Drawer	2x	-	2x	2x	2x	2x	2x	2x	2x	-	-