Gateway Documentation - FCISCIFFundMapping
Oracle FLEXCUBE Investor Servicing
Release 12.1.0.0.0
[October][2015]

Table Of Contents

1. Background **1**

2. FCISCIFFundMapping **2**

2.1.AuthorizeCIFFundMapping **2**

2.1.1.UT-AuthorizeCIFFundMapping-Req-Full-MSG.xsd 2

2.1.2.UT-AuthorizeCIFFundMapping-Req-IO-MSG.xsd 14

2.1.3.UT-AuthorizeCIFFundMapping-Res-Full-MSG.xsd 23

2.1.4.UT-AuthorizeCIFFundMapping-Res-PK-MSG.xsd 37

2.2.CreateCIFFundMapping **47**

2.2.1.UT-CreateCIFFundMapping-Req-Full-MSG.xsd 47

2.2.2.UT-CreateCIFFundMapping-Req-IO-MSG.xsd 60

2.2.3.UT-CreateCIFFundMapping-Res-Full-MSG.xsd 67

2.2.4.UT-CreateCIFFundMapping-Res-PK-MSG.xsd 82

2.3.DeleteCIFFundMapping **91**

2.3.1.UT-DeleteCIFFundMapping-Req-Full-MSG.xsd 91

2.3.2.UT-DeleteCIFFundMapping-Req-IO-MSG.xsd 104

2.3.3.UT-DeleteCIFFundMapping-Res-Full-MSG.xsd 112

2.3.4.UT-DeleteCIFFundMapping-Res-PK-MSG.xsd 126

2.4.ModifyCIFFundMapping **135**

2.4.1.UT-ModifyCIFFundMapping-Req-Full-MSG.xsd 135

2.4.2.UT-ModifyCIFFundMapping-Req-IO-MSG.xsd 148

2.4.3.UT-ModifyCIFFundMapping-Res-Full-MSG.xsd 156

2.4.4.UT-ModifyCIFFundMapping-Res-PK-MSG.xsd 170

2.5.QueryCIFFundMapping **181**

2.5.1.UT-QueryCIFFundMapping-Req-IO-MSG.xsd 181

2.5.2.UT-QueryCIFFundMapping-Res-Full-MSG.xsd 188

ORACLE

1. Background

Integration of different applications and solutions is a key area in today's systems.A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCISCIFFundMapping of UT Module

2. FCISCIFFundMapping

2.1.AuthorizeCIFFundMapping

2.1.1.UT-AuthorizeCIFFundMapping-Req-Full-MSG.xsd

AUTHORIZECIFFUNDMAPPING_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-Full

CIFNUMBER

MEDIA

LOCATION

ADDRESSLINE1

ADDRESSLINE2

ADDRESS3

ADDRESS4

ZIPCODE

CTRY

CONTACTPERSON

TELEPHONE1

TELEPHONE2

CELLPHONENUMBER

CUST_NAME

FUNDID

FUNDNAME

FUNDIDENTIFICATIONNO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

AUTHORIZECIFFUNDMAPPING_FSFS_REQ

Attribute	Description
Name	AUTHORIZECIFFUNDMAPPING_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description

Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of AuthorizeCIFFundMapping

Cifaddr-Full

Attribute	Description
Name	Cifaddr-Full
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

ADDRESSLINE1

Attribute	Description
Name	ADDRESSLINE1
Datatype	String
Description	Indicates Address Line 1
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ADDRESSLINE2

Attribute	Description
Name	ADDRESSLINE2
Datatype	String
Description	Indicates Address Line 2
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	Indicates City
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	Indicates State
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

ZIPCODE

Attribute	Description
Name	ZIPCODE
Datatype	String
Description	Indicates Zip Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

CTRY

Attribute	Description
Name	CTRY
Datatype	String
Description	Indicates Country
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CONTACTPERSON

Attribute	Description
Name	CONTACTPERSON
Datatype	String
Description	Indicates Contact Person
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>70</td></tr></table>

TELEPHONE1

Attribute	Description
Name	TELEPHONE1
Datatype	String
Description	Indicates Telephone Number 1
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TELEPHONE2

Attribute	Description
Name	TELEPHONE2
Datatype	String
Description	Indicates Telephone Number 2
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

CELLPHONENUMBER

Attribute	Description
Name	CELLPHONENUMBER
Datatype	String
Description	Indicates Mobile Number
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

CUST_NAME

Attribute	Description
Name	CUST_NAME
Datatype	String
Description	Indicates Customer Name
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>100</td></tr></table>

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

FUNDNAME

Attribute	Description
Name	FUNDNAME
Datatype	String
Description	Indicates UI Fund Name
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

FUNDIDENTIFICATIONNO

Attribute	Description
Name	FUNDIDENTIFICATIONNO
Datatype	String
Description	Indicates Fund Identification Number

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

2.1.2.UT-AuthorizeCIFFundMapping-Req-IO-MSG.xsd

AUTHORIZECIFFUNDMAPPING_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-IO

CIFNUMBER

MEDIA

LOCATION

FUNDID

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZECIFFUNDMAPPING_IOPK_REQ

Attribute	Description
Name	AUTHORIZECIFFUNDMAPPING_IOPK_REQ

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of AuthorizeCIFFundMapping

Cifaddr-IO

Attribute	Description
Name	Cifaddr-IO
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location

Restrictions	

Restrictions	Description
maxLength	15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	

Restrictions	Description
maxLength	6

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

2.1.3.UT-AuthorizeCIFFundMapping-Res-Full-MSG.xsd

AUTHORIZECIFFUNDMAPPING_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-Full

CIFNUMBER

MEDIA

LOCATION

ADDRESSLINE1

ADDRESSLINE2

ADDRESS3

ADDRESS4

ZIPCODE

CTRY

CONTACTPERSON

TELEPHONE1

TELEPHONE2

CELLPHONENUMBER

CUST_NAME

FUNDID

FUNDNAME

FUNDIDENTIFICATIONNO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZECIFFUNDMAPPING_FSFS_RES

Attribute	Description
Name	AUTHORIZECIFFUNDMAPPING_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Cifaddr-Full

Attribute	Description
Name	Cifaddr-Full
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

ADDRESSLINE1

Attribute	Description
Name	ADDRESSLINE1
Datatype	String
Description	Indicates Address Line 1
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESSLINE2

Attribute	Description
Name	ADDRESSLINE2
Datatype	String
Description	Indicates Address Line 2
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	Indicates City
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	Indicates State
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ZIPCODE

Attribute	Description
Name	ZIPCODE
Datatype	String
Description	Indicates Zip Code
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

CTRY

Attribute	**Description**
Name	CTRY
Datatype	String
Description	Indicates Country
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CONTACTPERSON

Attribute	**Description**
Name	CONTACTPERSON
Datatype	String
Description	Indicates Contact Person
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 70

TELEPHONE1

Attribute	**Description**
Name	TELEPHONE1
Datatype	String
Description	Indicates Telephone Number 1
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TELEPHONE2

Attribute	**Description**
Name	TELEPHONE2
Datatype	String
Description	Indicates Telephone Number 2
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15

CELLPHONENUMBER

Attribute	Description
Name	CELLPHONENUMBER
Datatype	String
Description	Indicates Mobile Number
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

CUST_NAME

Attribute	Description
Name	CUST_NAME
Datatype	String
Description	Indicates Customer Name
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	

Restrictions	Description
maxLength	6

FUNDNAME

Attribute	Description
Name	FUNDNAME
Datatype	String
Description	Indicates UI Fund Name
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

FUNDIDENTIFICATIONNO

Attribute	Description
Name	FUNDIDENTIFICATIONNO
Datatype	String
Description	Indicates Fund Identification Number
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4.UT-AuthorizeCIFFundMapping-Res-PK-MSG.xsd

AUTHORIZECIFFUNDMAPPING_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-PK

CIFNUMBER

LOCATION

MEDIA

FUNDID

Cifaddr-IO

CIFNUMBER

MEDIA

LOCATION

FUNDID

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZECIFFUNDMAPPING_IOPK_RES

Attribute	Description
Name	AUTHORIZECIFFUNDMAPPING_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description

Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Cifaddr-PK

Attribute	Description
Name	Cifaddr-PK
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

Cifaddr-IO

Attribute	Description
Name	Cifaddr-IO
Datatype	

Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.CreateCIFFundMapping

2.2.1.UT-CreateCIFFundMapping-Req-Full-MSG.xsd

CREATECIFFUNDMAPPING_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-Full

CIFNUMBER

MEDIA

LOCATION

ADDRESSLINE1

ADDRESSLINE2

ADDRESS3

ADDRESS4

ZIPCODE

CTRY

CONTACTPERSON

TELEPHONE1

TELEPHONE2

CELLPHONENUMBER

CUST_NAME

FUNDID

FUNDNAME

FUNDIDENTIFICATIONNO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

CREATECIFFUNDMAPPING_FSFS_REQ

Attribute	Description
Name	CREATECIFFUNDMAPPING_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreateCIFFundMapping

Cifaddr-Full

Attribute	Description
Name	Cifaddr-Full
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number

Restrictions	

Restrictions	Description
maxLength	12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	

Restrictions	Description
maxLength	15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	

Restrictions	Description
maxLength	15

ADDRESSLINE1

Attribute	Description
Name	ADDRESSLINE1
Datatype	String
Description	Indicates Address Line 1
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESSLINE2

Attribute	Description
Name	ADDRESSLINE2
Datatype	String
Description	Indicates Address Line 2
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESS3

Attribute	Description

Name	ADDRESS3
Datatype	String
Description	Indicates City
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ADDRESS4

Attribute	**Description**
Name	ADDRESS4
Datatype	String
Description	Indicates State
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ZIPCODE

Attribute	**Description**
Name	ZIPCODE
Datatype	String
Description	Indicates Zip Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

CTRY

Attribute	**Description**
Name	CTRY
Datatype	String
Description	Indicates Country
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CONTACTPERSON

Attribute	**Description**

Name	CONTACTPERSON
Datatype	String
Description	Indicates Contact Person
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TELEPHONE1

Attribute	**Description**
Name	TELEPHONE1
Datatype	String
Description	Indicates Telephone Number 1
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TELEPHONE2

Attribute	**Description**
Name	TELEPHONE2
Datatype	String
Description	Indicates Telephone Number 2
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

CELLPHONENUMBER

Attribute	**Description**
Name	CELLPHONENUMBER
Datatype	String
Description	Indicates Mobile Number
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

CUST_NAME

Attribute	**Description**

Name	CUST_NAME
Datatype	String
Description	Indicates Customer Name
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

FUNDNAME

Attribute	**Description**
Name	FUNDNAME
Datatype	String
Description	Indicates UI Fund Name
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

FUNDIDENTIFICATIONNO

Attribute	**Description**
Name	FUNDIDENTIFICATIONNO
Datatype	String
Description	Indicates Fund Identification Number
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	Indicates Maker

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

2.2.2.UT-CreateCIFFundMapping-Req-IO-MSG.xsd

CREATECIFFUNDMAPPING_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-IO

CIFNUMBER

MEDIA

LOCATION

FUNDID

CREATECIFFUNDMAPPING_IOPK_REQ

Attribute	Description
Name	CREATECIFFUNDMAPPING_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description

Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateCIFFundMapping

Cifaddr-IO

Attribute	Description
Name	Cifaddr-IO
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

2.2.3.UT-CreateCIFFundMapping-Res-Full-MSG.xsd

CREATECIFFUNDMAPPING_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-Full

CIFNUMBER

MEDIA

LOCATION

ADDRESSLINE1

ADDRESSLINE2

ADDRESS3

ADDRESS4

ZIPCODE

CTRY

CONTACTPERSON

TELEPHONE1

TELEPHONE2

CELLPHONENUMBER

CUST_NAME

FUNDID

FUNDNAME

FUNDIDENTIFICATIONNO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECIFFUNDMAPPING_FSFS_RES

Attribute	Description
Name	CREATECIFFUNDMAPPING_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Cifaddr-Full

Attribute	Description
Name	Cifaddr-Full
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

ADDRESSLINE1

Attribute	Description
Name	ADDRESSLINE1
Datatype	String
Description	Indicates Address Line 1
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESSLINE2

Attribute	Description
Name	ADDRESSLINE2
Datatype	String
Description	Indicates Address Line 2
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	Indicates City
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	Indicates State
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ZIPCODE

Attribute	Description
Name	ZIPCODE
Datatype	String
Description	Indicates Zip Code
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

CTRY

Attribute	**Description**
Name	CTRY
Datatype	String
Description	Indicates Country
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CONTACTPERSON

Attribute	**Description**
Name	CONTACTPERSON
Datatype	String
Description	Indicates Contact Person
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 70

TELEPHONE1

Attribute	**Description**
Name	TELEPHONE1
Datatype	String
Description	Indicates Telephone Number 1
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TELEPHONE2

Attribute	**Description**
Name	TELEPHONE2
Datatype	String
Description	Indicates Telephone Number 2
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15

CELLPHONENUMBER

Attribute	Description
Name	CELLPHONENUMBER
Datatype	String
Description	Indicates Mobile Number
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

CUST_NAME

Attribute	Description
Name	CUST_NAME
Datatype	String
Description	Indicates Customer Name
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	

Restrictions	Description
maxLength	6

FUNDNAME

Attribute	Description
Name	FUNDNAME
Datatype	String
Description	Indicates UI Fund Name
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

FUNDIDENTIFICATIONNO

Attribute	Description
Name	FUNDIDENTIFICATIONNO
Datatype	String
Description	Indicates Fund Identification Number
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.UT-CreateCIFFundMapping-Res-PK-MSG.xsd

CREATECIFFUNDMAPPING_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-PK

CIFNUMBER

LOCATION

MEDIA

FUNDID

Cifaddr-IO

CIFNUMBER

MEDIA

LOCATION

FUNDID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECIFFUNDMAPPING_IOPK_RES

Attribute	Description
Name	CREATECIFFUNDMAPPING_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Cifaddr-PK

Attribute	**Description**

Name	Cifaddr-PK
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

Cifaddr-IO

Attribute	Description
Name	Cifaddr-IO
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String

Description	Indicates CIF Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.DeleteCIFFundMapping

2.3.1.UT-DeleteCIFFundMapping-Req-Full-MSG.xsd

DELETECIFFUNDMAPPING_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-Full

CIFNUMBER

MEDIA

LOCATION

ADDRESSLINE1

ADDRESSLINE2

ADDRESS3

ADDRESS4

ZIPCODE

CTRY

CONTACTPERSON

TELEPHONE1

TELEPHONE2

CELLPHONENUMBER

CUST_NAME

FUNDID

FUNDNAME

FUNDIDENTIFICATIONNO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

DELETECIFFUNDMAPPING_FSFS_REQ

Attribute	Description
Name	DELETECIFFUNDMAPPING_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeleteCIFFundMapping

Cifaddr-Full

Attribute	Description
Name	Cifaddr-Full
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

ADDRESSLINE1

Attribute	Description
Name	ADDRESSLINE1
Datatype	String
Description	Indicates Address Line 1
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ADDRESSLINE2

Attribute	Description
Name	ADDRESSLINE2
Datatype	String
Description	Indicates Address Line 2

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 105

ADDRESS3

Attribute	**Description**
Name	ADDRESS3
Datatype	String
Description	Indicates City
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ADDRESS4

Attribute	**Description**
Name	ADDRESS4
Datatype	String
Description	Indicates State
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ZIPCODE

Attribute	**Description**
Name	ZIPCODE
Datatype	String
Description	Indicates Zip Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

CTRY

Attribute	**Description**
Name	CTRY
Datatype	String
Description	Indicates Country

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CONTACTPERSON

Attribute	**Description**
Name	CONTACTPERSON
Datatype	String
Description	Indicates Contact Person
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 70

TELEPHONE1

Attribute	**Description**
Name	TELEPHONE1
Datatype	String
Description	Indicates Telephone Number 1
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TELEPHONE2

Attribute	**Description**
Name	TELEPHONE2
Datatype	String
Description	Indicates Telephone Number 2
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

CELLPHONENUMBER

Attribute	**Description**
Name	CELLPHONENUMBER
Datatype	String
Description	Indicates Mobile Number

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

CUST_NAME

Attribute	Description
Name	CUST_NAME
Datatype	String
Description	Indicates Customer Name
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>100</td></tr></table>

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

FUNDNAME

Attribute	Description
Name	FUNDNAME
Datatype	String
Description	Indicates UI Fund Name
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

FUNDIDENTIFICATIONNO

Attribute	Description
Name	FUNDIDENTIFICATIONNO
Datatype	String
Description	Indicates Fund Identification Number
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

2.3.2.UT-DeleteCIFFundMapping-Req-IO-MSG.xsd

DELETECIFFUNDMAPPING_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-IO

CIFNUMBER

MEDIA

LOCATION

FUNDID

DELETECIFFUNDMAPPING_IOPK_REQ

Attribute	Description
Name	DELETECIFFUNDMAPPING_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of DeleteCIFFundMapping

Cifaddr-IO

Attribute	Description
Name	Cifaddr-IO
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	Restrictions: maxLength — Description: 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	Restrictions: maxLength — Description: 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	Restrictions: maxLength — Description: 15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	Restrictions: maxLength — Description: 6

2.3.3.UT-DeleteCIFFundMapping-Res-Full-MSG.xsd

DELETECIFFUNDMAPPING_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-Full

CIFNUMBER

MEDIA

LOCATION

ADDRESSLINE1

ADDRESSLINE2

ADDRESS3

ADDRESS4

ZIPCODE

CTRY

CONTACTPERSON

TELEPHONE1

TELEPHONE2

CELLPHONENUMBER

CUST_NAME

FUNDID

FUNDNAME

FUNDIDENTIFICATIONNO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECIFFUNDMAPPING_FSFS_RES

Attribute	Description
Name	DELETECIFFUNDMAPPING_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Cifaddr-Full

Attribute	Description
Name	Cifaddr-Full
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

ADDRESSLINE1

Attribute	Description
Name	ADDRESSLINE1
Datatype	String
Description	Indicates Address Line 1
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESSLINE2

Attribute	Description
Name	ADDRESSLINE2
Datatype	String
Description	Indicates Address Line 2
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	Indicates City
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	Indicates State
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ZIPCODE

Attribute	Description
Name	ZIPCODE
Datatype	String
Description	Indicates Zip Code
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

CTRY

Attribute	**Description**
Name	CTRY
Datatype	String
Description	Indicates Country
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CONTACTPERSON

Attribute	**Description**
Name	CONTACTPERSON
Datatype	String
Description	Indicates Contact Person
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 70

TELEPHONE1

Attribute	**Description**
Name	TELEPHONE1
Datatype	String
Description	Indicates Telephone Number 1
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TELEPHONE2

Attribute	**Description**
Name	TELEPHONE2
Datatype	String
Description	Indicates Telephone Number 2
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15

CELLPHONENUMBER

Attribute	Description
Name	CELLPHONENUMBER
Datatype	String
Description	Indicates Mobile Number
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

CUST_NAME

Attribute	Description
Name	CUST_NAME
Datatype	String
Description	Indicates Customer Name
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	

Restrictions	Description
maxLength	6

FUNDNAME

Attribute	Description
Name	FUNDNAME
Datatype	String
Description	Indicates UI Fund Name
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

FUNDIDENTIFICATIONNO

Attribute	Description
Name	FUNDIDENTIFICATIONNO
Datatype	String
Description	Indicates Fund Identification Number
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.4.UT-DeleteCIFFundMapping-Res-PK-MSG.xsd

DELETECIFFUNDMAPPING_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-PK

CIFNUMBER

LOCATION

MEDIA

FUNDID

Cifaddr-IO

CIFNUMBER

MEDIA

LOCATION

FUNDID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECIFFUNDMAPPING_IOPK_RES

Attribute	Description
Name	DELETECIFFUNDMAPPING_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Cifaddr-PK

Attribute	**Description**

Name	Cifaddr-PK
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

Cifaddr-IO

Attribute	Description
Name	Cifaddr-IO
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String

Description	Indicates CIF Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.ModifyCIFFundMapping

2.4.1.UT-ModifyCIFFundMapping-Req-Full-MSG.xsd

MODIFYCIFFUNDMAPPING_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-Full

CIFNUMBER

MEDIA

LOCATION

ADDRESSLINE1

ADDRESSLINE2

ADDRESS3

ADDRESS4

ZIPCODE

CTRY

CONTACTPERSON

TELEPHONE1

TELEPHONE2

CELLPHONENUMBER

CUST_NAME

FUNDID

FUNDNAME

FUNDIDENTIFICATIONNO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

MODIFYCIFFUNDMAPPING_FSFS_REQ

Attribute	Description
Name	MODIFYCIFFUNDMAPPING_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ModifyCIFFundMapping

Cifaddr-Full

Attribute	Description
Name	Cifaddr-Full
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

ADDRESSLINE1

Attribute	Description
Name	ADDRESSLINE1
Datatype	String
Description	Indicates Address Line 1
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ADDRESSLINE2

Attribute	Description
Name	ADDRESSLINE2
Datatype	String
Description	Indicates Address Line 2

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ADDRESS3

Attribute	**Description**
Name	ADDRESS3
Datatype	String
Description	Indicates City
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ADDRESS4

Attribute	**Description**
Name	ADDRESS4
Datatype	String
Description	Indicates State
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ZIPCODE

Attribute	**Description**
Name	ZIPCODE
Datatype	String
Description	Indicates Zip Code
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

CTRY

Attribute	**Description**
Name	CTRY
Datatype	String
Description	Indicates Country

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CONTACTPERSON

Attribute	**Description**
Name	CONTACTPERSON
Datatype	String
Description	Indicates Contact Person
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 70

TELEPHONE1

Attribute	**Description**
Name	TELEPHONE1
Datatype	String
Description	Indicates Telephone Number 1
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TELEPHONE2

Attribute	**Description**
Name	TELEPHONE2
Datatype	String
Description	Indicates Telephone Number 2
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

CELLPHONENUMBER

Attribute	**Description**
Name	CELLPHONENUMBER
Datatype	String
Description	Indicates Mobile Number

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

CUST_NAME

Attribute	**Description**
Name	CUST_NAME
Datatype	String
Description	Indicates Customer Name
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description** maxLength / 6

FUNDNAME

Attribute	**Description**
Name	FUNDNAME
Datatype	String
Description	Indicates UI Fund Name
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

FUNDIDENTIFICATIONNO

Attribute	**Description**
Name	FUNDIDENTIFICATIONNO
Datatype	String
Description	Indicates Fund Identification Number
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

2.4.2.UT-ModifyCIFFundMapping-Req-IO-MSG.xsd

MODIFYCIFFUNDMAPPING_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-IO

CIFNUMBER

MEDIA

LOCATION

FUNDID

MAKER

MAKERSTAMP

MODIFYCIFFUNDMAPPING_IOPK_REQ

Attribute	Description
Name	MODIFYCIFFUNDMAPPING_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ModifyCIFFundMapping

Cifaddr-IO

Attribute	Description
Name	Cifaddr-IO
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	Restrictions: maxLength = 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	Restrictions: maxLength = 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	Restrictions: maxLength = 15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	Restrictions: maxLength = 6

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

2.4.3.UT-ModifyCIFFundMapping-Res-Full-MSG.xsd

MODIFYCIFFUNDMAPPING_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-Full

CIFNUMBER

MEDIA

LOCATION

ADDRESSLINE1

ADDRESSLINE2

ADDRESS3

ADDRESS4

ZIPCODE

CTRY

CONTACTPERSON

TELEPHONE1

TELEPHONE2

CELLPHONENUMBER

CUST_NAME

FUNDID

FUNDNAME

FUNDIDENTIFICATIONNO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCIFFUNDMAPPING_FSFS_RES

Attribute	Description
Name	MODIFYCIFFUNDMAPPING_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Cifaddr-Full

Attribute	Description
Name	Cifaddr-Full
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

ADDRESSLINE1

Attribute	Description
Name	ADDRESSLINE1
Datatype	String
Description	Indicates Address Line 1
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ADDRESSLINE2

Attribute	Description
Name	ADDRESSLINE2
Datatype	String
Description	Indicates Address Line 2
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	Indicates City

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ADDRESS4

Attribute	**Description**
Name	ADDRESS4
Datatype	String
Description	Indicates State
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ZIPCODE

Attribute	**Description**
Name	ZIPCODE
Datatype	String
Description	Indicates Zip Code
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

CTRY

Attribute	**Description**
Name	CTRY
Datatype	String
Description	Indicates Country
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CONTACTPERSON

Attribute	**Description**
Name	CONTACTPERSON
Datatype	String
Description	Indicates Contact Person

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 70

TELEPHONE1

Attribute	**Description**
Name	TELEPHONE1
Datatype	String
Description	Indicates Telephone Number 1
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TELEPHONE2

Attribute	**Description**
Name	TELEPHONE2
Datatype	String
Description	Indicates Telephone Number 2
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

CELLPHONENUMBER

Attribute	**Description**
Name	CELLPHONENUMBER
Datatype	String
Description	Indicates Mobile Number
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

CUST_NAME

Attribute	**Description**
Name	CUST_NAME
Datatype	String
Description	Indicates Customer Name

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

FUNDNAME

Attribute	**Description**
Name	FUNDNAME
Datatype	String
Description	Indicates UI Fund Name
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

FUNDIDENTIFICATIONNO

Attribute	**Description**
Name	FUNDIDENTIFICATIONNO
Datatype	String
Description	Indicates Fund Identification Number
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.4.UT-ModifyCIFFundMapping-Res-PK-MSG.xsd

MODIFYCIFFUNDMAPPING_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-PK

CIFNUMBER

LOCATION

MEDIA

FUNDID

Cifaddr-IO

CIFNUMBER

MEDIA

LOCATION

FUNDID

MAKER

MAKERSTAMP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCIFFUNDMAPPING_IOPK_RES

Attribute	Description
Name	MODIFYCIFFUNDMAPPING_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Cifaddr-PK

Attribute	Description
Name	Cifaddr-PK
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

LOCATION

Attribute	Description

Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

Cifaddr-IO

Attribute	**Description**
Name	Cifaddr-IO
Datatype	
Description	

CIFNUMBER

Attribute	**Description**
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	

2.5.QueryCIFFundMapping

2.5.1.UT-QueryCIFFundMapping-Req-IO-MSG.xsd

- *QUERYCIFFUNDMAPPING_IOFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Cifaddr-IO*
      - *CIFNUMBER*
      - *MEDIA*
      - *LOCATION*
      - *FUNDID*

QUERYCIFFUNDMAPPING_IOFS_REQ

Attribute	Description
Name	QUERYCIFFUNDMAPPING_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	Indicates Module Id
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of QueryCIFFundMapping

Cifaddr-IO

Attribute	Description
Name	Cifaddr-IO
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	

Restrictions	Description
maxLength	12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	

Restrictions	Description
maxLength	15

LOCATION

Attribute	Description

Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

2.5.2.UT-QueryCIFFundMapping-Res-Full-MSG.xsd

QUERYCIFFUNDMAPPING_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cifaddr-IO

CIFNUMBER

MEDIA

LOCATION

FUNDID

Cifaddr-Full

CIFNUMBER

MEDIA

LOCATION

ADDRESSLINE1

ADDRESSLINE2

ADDRESS3

ADDRESS4

ZIPCODE

CTRY

CONTACTPERSON

TELEPHONE1

TELEPHONE2

CELLPHONENUMBER

CUST_NAME

FUNDID

FUNDNAME

FUNDIDENTIFICATIONNO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYCIFFUNDMAPPING_IOFS_RES

Attribute	Description
Name	QUERYCIFFUNDMAPPING_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	Indicates Module Id
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Cifaddr-IO

Attribute	Description
Name	Cifaddr-IO
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media
Restrictions	**Restrictions** / **Description**: maxLength / 15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	**Restrictions** / **Description**: maxLength / 15

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	**Restrictions** / **Description**: maxLength / 6

Cifaddr-Full

Attribute	Description
Name	Cifaddr-Full
Datatype	
Description	

CIFNUMBER

Attribute	Description
Name	CIFNUMBER
Datatype	String
Description	Indicates CIF Number
Restrictions	**Restrictions** / **Description**: maxLength / 12

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	Indicates Media

Restrictions	

Restrictions	Description
maxLength	15

LOCATION

Attribute	Description
Name	LOCATION
Datatype	String
Description	Indicates Location
Restrictions	

Restrictions	Description
maxLength	15

ADDRESSLINE1

Attribute	Description
Name	ADDRESSLINE1
Datatype	String
Description	Indicates Address Line 1
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESSLINE2

Attribute	Description
Name	ADDRESSLINE2
Datatype	String
Description	Indicates Address Line 2
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	Indicates City
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	Indicates State
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ZIPCODE

Attribute	Description
Name	ZIPCODE
Datatype	String
Description	Indicates Zip Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

CTRY

Attribute	Description
Name	CTRY
Datatype	String
Description	Indicates Country
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CONTACTPERSON

Attribute	Description
Name	CONTACTPERSON
Datatype	String
Description	Indicates Contact Person
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TELEPHONE1

Attribute	Description
Name	TELEPHONE1
Datatype	String
Description	Indicates Telephone Number 1
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TELEPHONE2

Attribute	Description
Name	TELEPHONE2
Datatype	String
Description	Indicates Telephone Number 2
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

CELLPHONENUMBER

Attribute	Description
Name	CELLPHONENUMBER
Datatype	String
Description	Indicates Mobile Number
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

CUST_NAME

Attribute	Description
Name	CUST_NAME
Datatype	String
Description	Indicates Customer Name
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>100</td></tr></table>

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	Indicates Fund ID
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

FUNDNAME

Attribute	Description
Name	FUNDNAME
Datatype	String
Description	Indicates UI Fund Name
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

FUNDIDENTIFICATIONNO

Attribute	Description
Name	FUNDIDENTIFICATIONNO
Datatype	String
Description	Indicates Fund Identification Number
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates Maker
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates Checker
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Checker Date
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	Indicates Modification Number
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

Gateway Documentation - FCISCIFFundMapping
[October] [2015]

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.