

Gateway Documentation - FCISPolicyStatusChange
Oracle FLEXCUBE Investor Servicing
Release 12.1.0.0.0
[October][2015]



Table Of Contents

1. Background	1
2. FCISPolicyStatusChange	2
2.1.AuthorizePolicyStatusChange	2
2.1.1.LE-AuthorizePolicyStatusChange-Req-Full-MSG.xsd	2
2.1.2.LE-AuthorizePolicyStatusChange-Req-IO-MSG.xsd	18
2.1.3.LE-AuthorizePolicyStatusChange-Res-Full-MSG.xsd	26
2.1.4.LE-AuthorizePolicyStatusChange-Res-PK-MSG.xsd	44
2.2.CreatePolicyStatusChange	54
2.2.1.LE-CreatePolicyStatusChange-Req-Full-MSG.xsd	54
2.2.2.LE-CreatePolicyStatusChange-Req-IO-MSG.xsd	70
2.2.3.LE-CreatePolicyStatusChange-Res-Full-MSG.xsd	80
2.2.4.LE-CreatePolicyStatusChange-Res-PK-MSG.xsd	98
2.3.DeletePolicyStatusChange	110
2.3.1.LE-DeletePolicyStatusChange-Req-Full-MSG.xsd	110
2.3.2.LE-DeletePolicyStatusChange-Req-IO-MSG.xsd	127
2.3.3.LE-DeletePolicyStatusChange-Res-Full-MSG.xsd	134
2.3.4.LE-DeletePolicyStatusChange-Res-PK-MSG.xsd	152
2.4.ModifyPolicyStatusChange	161
2.4.1.LE-ModifyPolicyStatusChange-Req-Full-MSG.xsd	161
2.4.2.LE-ModifyPolicyStatusChange-Req-IO-MSG.xsd	177
2.4.3.LE-ModifyPolicyStatusChange-Res-Full-MSG.xsd	188
2.4.4.LE-ModifyPolicyStatusChange-Res-PK-MSG.xsd	206
2.5.QueryPolicyStatusChange	219
2.5.1.LE-QueryPolicyStatusChange-Req-IO-MSG.xsd	220
2.5.2.LE-QueryPolicyStatusChange-Res-Full-MSG.xsd	226

1. Background

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCISPolicyStatusChange of LE Module

2. FCISPolicyStatusChange

2.1.AuthorizePolicyStatusChange

2.1.1.LE-AuthorizePolicyStatusChange-Req-Full-MSG.xsd

AUTHORIZEPOLICYSTATUSCHANGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-Full

POLICYNUMBER

RULEEFFECTIVEDATE

APPLICATIONDATE

OLDPOLICYSTATUS

NEWPOLICYSTATUS
DESCRIPTION
REDEMPTIONTXNGEN
SURRENDERMONEYPAYABLE
ADJTXNTYPE
OFFSETVALUE
BACKDATESURRENDER
AVERAGESALARY
DATEOFDEATH
ALLOWSURRENDER
ALLOWCLOSURE
ALLOWTRANSFER
TRANSACTION_DESC
LANGDESC
REMARKS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Policy
 PHID
 PRODID
 POLICYENDDATE
 POLICYBASECCY
Subtype
 BRANCHCODE
 ACCOUNTTYPE
 ACCOUNTNUMBER
 ACCOUNTCURRENCY

BANKCODE

IBAN

ACCOUNTNAME

AUTHORIZEPOLICYSTATUSCHANGE_FSFS_REQ

Attribute	Description
Name	AUTHORIZEPOLICYSTATUSCHANGE FSFS REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of AuthorizePolicyStatusChange

Policy-Status-Change-Full

Attribute	Description
Name	Policy-Status-Change-Full
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
-----------	-------------

Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

OLDPOLICYSTATUS

Attribute	Description	
Name	OLDPOLICYSTATUS	
Datatype	String	
Description	Indicates Old Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

NEWPOLICYSTATUS

Attribute	Description	
Name	NEWPOLICYSTATUS	
Datatype	String	
Description	Indicates New Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute		
	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

TRANSACTION_DESC

Attribute	Description	
Name	TRANSACTION_DESC	
Datatype	String	
Description	Indicates Transaction Description	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

LANGDESC

Attribute	Description	
Name	LANGDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Policy

Attribute	Description	
Name	Policy	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PHID

Attribute	Description	
Name	PHID	
Datatype	String	
Description	Indicates Policy Holder	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PRODID

Attribute	Description	
Name	PRODID	
Datatype	String	
Description	Indicates Product Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

POLICYENDDATE

Attribute	Description	
Name	POLICYENDDATE	
Datatype	String	
Description	Indicates Policy End Date	
Attribute		
	Attribute	Description
	minOccurs	0

POLICYBASECCY

Attribute	Description	
Name	POLICYBASECCY	
Datatype	String	
Description	Indicates Policy Base Currency	
Restrictions		
	Restrictions	Description
	maxLength	3

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

BRANCHCODE

Attribute	Description
------------------	--------------------

Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

ACCOUNTTYPE

Attribute	Description	
Name	ACCOUNTTYPE	
Datatype	String	
Description	Indicates Account Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

ACCOUNTCURRENCY

Attribute	Description	
Name	ACCOUNTCURRENCY	
Datatype	String	
Description	Indicates Account Currency	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description	BANK LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE = PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

ACCOUNTNAME

Attribute	Description	
Name	ACCOUNTNAME	
Datatype	String	
Description	Indicates Account Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

2.1.2.LE-AuthorizePolicyStatusChange-Req-IO-MSG.xsd

AUTHORIZEPOLICYSTATUSCHANGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-IO

POLICYNUMBER

RULEEFFECTIVEDATE

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZEPOLICYSTATUSCHANGE_IOPK_REQ

Attribute	Description
Name	AUTHORIZEPOLICYSTATUSCHANGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of AuthorizePolicyStatusChange

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description				
Name	POLICYNUMBER				
Datatype	String				
Description	Indicates Policy Number				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>16</td></tr> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description	Indicates Checker				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>12</td></tr> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description	Checker Date				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

2.1.3.LE-AuthorizePolicyStatusChange-Res-Full-MSG.xsd

AUTHORIZEPOLICYSTATUSCHANGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME
VALUE
FCUBS_BODY
Policy-Status-Change-Full
POLICYNUMBER
RULEEFFECTIVEDATE
APPLICATIONDATE
OLDPOLICYSTATUS
NEWPOLICYSTATUS
DESCRIPTION
REDEMPTIONTXNGEN
SURRENDERMONEYPAYABLE
ADJTXNTYPE
OFFSETVALUE
BACKDATESURRENDER
AVERAGESALARY
DATEOFDEATH
ALLOWSURRENDER
ALLOWCLOSURE
ALLOWTRANSFER
TRANSACTION_DESC
LANGDESC
REMARKS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Policy
PHID

PRODID

POLICYENDDATE

POLICYBASECCY

Subtype

BRANCHCODE

ACCOUNTTYPE

ACCOUNTNUMBER

ACCOUNTCURRENCY

BANKCODE

IBAN

ACCOUNTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEPOLICYSTATUSCHANGE_FSFS_RES

Attribute	Description
Name	AUTHORIZEPOLICYSTATUSCHANGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
------------------	--------------------

Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Policy-Status-Change-Full

Attribute	Description
Name	Policy-Status-Change-Full
Datatype	
Description	

POLICYNUMBER

Attribute	Description				
Name	POLICYNUMBER				
Datatype	String				
Description	Indicates Policy Number				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>16</td></tr> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

OLDPOLICYSTATUS

Attribute	Description				
Name	OLDPOLICYSTATUS				
Datatype	String				
Description	Indicates Old Policy Status				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>4</td></tr> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

NEWPOLICYSTATUS

Attribute	Description
Name	NEWPOLICYSTATUS
Datatype	String
Description	Indicates New Policy Status

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	

Attribute		
	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

TRANSACTION_DESC

Attribute	Description	
Name	TRANSACTION_DESC	
Datatype	String	
Description	Indicates Transaction Description	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	255

LANGDESC

Attribute	Description	
Name	LANGDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Policy

Attribute	Description	
Name	Policy	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PHID

Attribute	Description	
Name	PHID	
Datatype	String	
Description	Indicates Policy Holder	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PRODID

Attribute	Description	
Name	PRODID	
Datatype	String	
Description	Indicates Product Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

POLICYENDDATE

Attribute	Description	
Name	POLICYENDDATE	
Datatype	String	
Description	Indicates Policy End Date	
Attribute		
	Attribute	Description
	minOccurs	0

POLICYBASECCY

Attribute	Description	
Name	POLICYBASECCY	
Datatype	String	
Description	Indicates Policy Base Currency	
Restrictions		
	Restrictions	Description
	maxLength	3

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

ACCOUNTTYPE

Attribute	Description	
Name	ACCOUNTTYPE	
Datatype	String	
Description	Indicates Account Type	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

ACCOUNTCURRENCY

Attribute	Description	
Name	ACCOUNTCURRENCY	
Datatype	String	
Description	Indicates Account Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description	BANK LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE = PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

IBAN

Attribute	Description
Name	IBAN
Datatype	String
Description	IBAN Number

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	40

ACCOUNTNAME

Attribute	Description	
Name	ACCOUNTNAME	
Datatype	String	
Description	Indicates Account Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4.LE-AuthorizePolicyStatusChange-Res-PK-MSG.xsd

AUTHORIZEPOLICYSTATUSCHANGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-PK

POLICYNUMBER

RULEEFFECTIVEDATE

Policy-Status-Change-IO

POLICYNUMBER

RULEEFFECTIVEDATE

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEPOLICYSTATUSCHANGE_IOPK_RES

Attribute	Description
Name	AUTHORIZEPOLICYSTATUSCHANGE_IOPK_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Policy-Status-Change-PK

Attribute	Description
Name	Policy-Status-Change-PK
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description
Name	POLICYNUMBER
Datatype	String
Description	Indicates Policy Number

Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.CreatePolicyStatusChange

2.2.1.LE-CreatePolicyStatusChange-Req-Full-MSG.xsd

CREATEPOLICYSTATUSCHANGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-Full

POLICYNUMBER
RULEEFFECTIVEDATE
APPLICATIONDATE
OLDPOLICYSTATUS
NEWPOLICYSTATUS
DESCRIPTION
REDEMPTIONTXNGEN
SURRENDERMONEYPAYABLE
ADJTXNTYPE
OFFSETVALUE
BACKDATESURRENDER
AVERAGESALARY
DATEOFDEATH
ALLOWSSURRENDER
ALLOWCLOSURE
ALLOWTRANSFER
TRANSACTION_DESC
LANGDESC
REMARKS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Policy
 PHID
 PRODID
 POLICYENDDATE
 POLICYBASECCY
Subtype

BRANCHCODE

ACCOUNTTYPE

ACCOUNTNUMBER

ACCOUNTCURRENCY

BANKCODE

IBAN

ACCOUNTNAME

CREATEPOLICYSTATUSCHANGE_FSFS_REQ

Attribute	Description
Name	CREATEPOLICYSTATUSCHANGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	String				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreatePolicyStatusChange

Policy-Status-Change-Full

Attribute	Description
Name	Policy-Status-Change-Full
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

OLDPOLICYSTATUS

Attribute	Description	
Name	OLDPOLICYSTATUS	
Datatype	String	
Description	Indicates Old Policy Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

NEWPOLICYSTATUS

Attribute	Description	
Name	NEWPOLICYSTATUS	
Datatype	String	
Description	Indicates New Policy Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description
-----------	-------------

Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description
------------------	--------------------

Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

TRANSACTION_DESC

Attribute	Description	
Name	TRANSACTION_DESC	
Datatype	String	
Description	Indicates Transaction Description	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

LANGDESC

Attribute	Description	
Name	LANGDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Policy Remarks

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Policy

Attribute	Description
Name	Policy
Datatype	
Description	

Attribute		
	Attribute	Description
	minOccurs	0

PHID

Attribute	Description	
Name	PHID	
Datatype	String	
Description	Indicates Policy Holder	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PRODID

Attribute	Description	
Name	PRODID	
Datatype	String	
Description	Indicates Product Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

POLICYENDDATE

Attribute	Description	
Name	POLICYENDDATE	
Datatype	String	
Description	Indicates Policy End Date	
Attribute		
	Attribute	Description
	minOccurs	0

POLICYBASECCY

Attribute	Description	
Name	POLICYBASECCY	
Datatype	String	
Description	Indicates Policy Base Currency	
Restrictions		
	Restrictions	Description
	maxLength	3

Subtype

Attribute	Description
------------------	--------------------

Name	Subtype	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

ACCOUNTTYPE

Attribute	Description	
Name	ACCOUNTTYPE	
Datatype	String	
Description	Indicates Account Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

ACCOUNTCURRENCY

Attribute	Description	
Name	ACCOUNTCURRENCY	
Datatype	String	

Description	Indicates Account Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description	BANK LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE = PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

ACCOUNTNAME

Attribute	Description	
Name	ACCOUNTNAME	
Datatype	String	
Description	Indicates Account Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

2.2.2.LE-CreatePolicyStatusChange-Req-IO-MSG.xsd

[CREATEPOLICYSTATUSCHANGE_IOPK_REQ](#)

[FCUBS_HEADER](#)

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-IO

POLICYNUMBER

RULEEFFECTIVEDATE

APPLICATIONDATE

NEWPOLICYSTATUS

SURRENDERMONEYPAYABLE

ADJTXNTYPE

OFFSETVALUE

BACKDATESURRENDER

AVERAGESALARY

DATEOFDEATH

REMARKS

Subtype

ACCOUNTNUMBER

IBAN

CREATEPOLICYSTATUSCHANGE_IOPK_REQ

Attribute	Description
Name	CREATEPOLICYSTATUSCHANGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreatePolicyStatusChange

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
-----------	-------------

Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

NEWPOLICYSTATUS

Attribute	Description	
Name	NEWPOLICYSTATUS	
Datatype	String	
Description	Indicates New Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute	Attribute	Description
	minOccurs	0

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

2.2.3.LE-CreatePolicyStatusChange-Res-Full-MSG.xsd

CREATEPOLICYSTATUSCHANGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-Full

POLICYNUMBER

RULEEFFECTIVEDATE

APPLICATIONDATE

OLDPOLICYSTATUS

NEWPOLICYSTATUS

DESCRIPTION

REDEMPTIONTXNGEN

SURRENDERMONEYPAYABLE

ADJTXNTYPE

OFFSETVALUE

BACKDATESURRENDER

AVERAGESALARY

DATEOFDEATH

ALLOWSURRENDER

ALLOWCLOSURE

ALLOWTRANSFER

TRANSACTION_DESC

LANGDESC

REMARKS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Policy

PHID

PRODID

POLICYENDDATE

POLICYBASECCY

Subtype

BRANCHCODE

ACCOUNTTYPE

ACCOUNTNUMBER

ACCOUNTCURRENCY

BANKCODE

IBAN

ACCOUNTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEPOLICYSTATUSCHANGE_FSFS_RES

Attribute	Description
-----------	-------------

Name	CREATEPOLICYSTATUSCHANGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	Indicates Module Id				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Policy-Status-Change-Full

Attribute	Description
Name	Policy-Status-Change-Full
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

OLDPOLICYSTATUS

Attribute	Description
Name	OLDPOLICYSTATUS
Datatype	String
Description	Indicates Old Policy Status

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

NEWPOLICYSTATUS

Attribute	Description	
Name	NEWPOLICYSTATUS	
Datatype	String	
Description	Indicates New Policy Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description
Name	AVERAGESALARY
Datatype	Decimal
Description	Indicates Average Salary

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute		
	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	1,0

TRANSACTION_DESC

Attribute	Description	
Name	TRANSACTION_DESC	
Datatype	String	
Description	Indicates Transaction Description	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

LANGDESC

Attribute	Description	
Name	LANGDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Policy

Attribute	Description	
Name	Policy	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PHID

Attribute	Description	
Name	PHID	
Datatype	String	
Description	Indicates Policy Holder	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

PRODID

Attribute	Description	
Name	PRODID	
Datatype	String	
Description	Indicates Product Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

POLICYENDDATE

Attribute	Description	
Name	POLICYENDDATE	
Datatype	String	
Description	Indicates Policy End Date	
Attribute		
	Attribute	Description
	minOccurs	0

POLICYBASECCY

Attribute	Description	
Name	POLICYBASECCY	
Datatype	String	
Description	Indicates Policy Base Currency	
Restrictions		
	Restrictions	Description
	maxLength	3

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

ACCOUNTTYPE

Attribute	Description	
Name	ACCOUNTTYPE	
Datatype	String	
Description	Indicates Account Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

ACCOUNTCURRENCY

Attribute	Description	
Name	ACCOUNTCURRENCY	
Datatype	String	
Description	Indicates Account Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	BANK LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE = PARENTBANKCODE AND DELETEDSTATUS = 0

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	40

ACCOUNTNAME

Attribute	Description	
Name	ACCOUNTNAME	
Datatype	String	
Description	Indicates Account Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.LE-CreatePolicyStatusChange-Res-PK-MSG.xsd

[CREATEPOLICYSTATUSCHANGE_IOPK_RES](#)

[FCUBS_HEADER](#)

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Policy-Status-Change-PK
POLICYNUMBER
RULEEFFECTIVEDATE
Policy-Status-Change-IO
POLICYNUMBER
RULEEFFECTIVEDATE
APPLICATIONDATE
NEWPOLICYSTATUS
SURRENDERMONEYPAYABLE
ADJTXNTYPE

OFFSETVALUE

BACKDATESURRENDER

AVERAGESALARY

DATEOFDEATH

REMARKS

Subtype

ACCOUNTNUMBER

IBAN

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEPOLICYSTATUSCHANGE_IOPK_RES

Attribute	Description
Name	CREATEPOLICYSTATUSCHANGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	Indicates Module Id				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PK Response	

Policy-Status-Change-PK

Attribute	Description
------------------	--------------------

Name	Policy-Status-Change-PK
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

NEWPOLICYSTATUS

Attribute	Description
Name	NEWPOLICYSTATUS
Datatype	String
Description	Indicates New Policy Status

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description
Name	BACKDATESURRENDER
Datatype	Decimal
Description	Indicates Back Date Surrender

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute		
	Attribute	Description
	minOccurs	0

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	40

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.DeletePolicyStatusChange

2.3.1.LE-DeletePolicyStatusChange-Req-Full-MSG.xsd

DELETPOLICYSTATUSCHANGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Policy-Status-Change-Full
 POLICYNUMBER
 RULEEFFECTIVEDATE
 APPLICATIONDATE
 OLDPOLICYSTATUS
 NEWPOLICYSTATUS
 DESCRIPTION
 REDEMPTIONTXNGEN
 SURRENDERMONEYPAYABLE
 ADJTXNTYPE
 OFFSETVALUE
 BACKDATESURRENDER
 AVERAGESALARY
 DATEOFDEATH
 ALLOWSURRENDER
 ALLOWCLOSURE

ALLOWTRANSFER

TRANSACTION_DESC

LANGDESC

REMARKS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Policy

PHID

PRODID

POLICYENDDATE

POLICYBASECCY

Subtype

BRANCHCODE

ACCOUNTTYPE

ACCOUNTNUMBER

ACCOUNTCURRENCY

BANKCODE

IBAN

ACCOUNTNAME

DELETEPOLICYSTATUSCHANGE_FSFS_REQ

Attribute	Description
Name	DELETEPOLICYSTATUSCHANGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeletePolicyStatusChange

Policy-Status-Change-Full

Attribute	Description
Name	Policy-Status-Change-Full
Datatype	
Description	

POLICYNUMBER

Attribute	Description				
Name	POLICYNUMBER				
Datatype	String				
Description	Indicates Policy Number				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>16</td></tr> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

OLDPOLICYSTATUS

Attribute	Description				
Name	OLDPOLICYSTATUS				
Datatype	String				
Description	Indicates Old Policy Status				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>4</td></tr> </table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

NEWPOLICYSTATUS

Attribute	Description
-----------	-------------

Name	NEWPOLICYSTATUS	
Datatype	String	
Description	Indicates New Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description
------------------	--------------------

Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description
------------------	--------------------

Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute		
	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

TRANSACTION_DESC

Attribute	Description
Name	TRANSACTION_DESC
Datatype	String
Description	Indicates Transaction Description

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

LANGDESC

Attribute	Description	
Name	LANGDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Policy

Attribute	Description	
Name	Policy	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PHID

Attribute	Description	
Name	PHID	
Datatype	String	
Description	Indicates Policy Holder	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PRODID

Attribute	Description	
Name	PRODID	
Datatype	String	
Description	Indicates Product Name	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	10

POLICYENDDATE

Attribute	Description	
Name	POLICYENDDATE	
Datatype	String	
Description	Indicates Policy End Date	
Attribute	Attribute	Description
	minOccurs	0

POLICYBASECCY

Attribute	Description	
Name	POLICYBASECCY	
Datatype	String	
Description	Indicates Policy Base Currency	
Restrictions	Restrictions	Description
	maxLength	3

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

ACCOUNTTYPE

Attribute	Description	
Name	ACCOUNTTYPE	
Datatype	String	

Description	Indicates Account Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

ACCOUNTCURRENCY

Attribute	Description	
Name	ACCOUNTCURRENCY	
Datatype	String	
Description	Indicates Account Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description	BANK LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE = PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

IBAN

Attribute	Description
------------------	--------------------

Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	40

ACCOUNTNAME

Attribute	Description	
Name	ACCOUNTNAME	
Datatype	String	
Description	Indicates Account Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

2.3.2.LE-DeletePolicyStatusChange-Req-IO-MSG.xsd

DELETPOLICYSTATUSCHANGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-IO

POLICYNUMBER

RULEEFFECTIVEDATE

DELETEDPOLICYSTATUSCHANGE_IOPK_REQ

Attribute	Description
Name	DELETEDPOLICYSTATUSCHANGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of DeletePolicyStatusChange

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description
------------------	--------------------

Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

2.3.3.LE-DeletePolicyStatusChange-Res-Full-MSG.xsd

DELETEPOLICYSTATUSCHANGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-Full

POLICYNUMBER
RULEEFFECTIVEDATE
APPLICATIONDATE
OLDPOLICYSTATUS
NEWPOLICYSTATUS
DESCRIPTION
REDEMPTIONTXNGEN
SURRENDERMONEYPAYABLE
ADJTXNTYPE
OFFSETVALUE
BACKDATESURRENDER
AVERAGESALARY
DATEOFDEATH
ALLOWSURRENDER
ALLOWCLOSURE
ALLOWTRANSFER
TRANSACTION_DESC
LANGDESC
REMARKS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Policy
PHID
PRODID
POLICYENDDATE
POLICYBASECCY

Subtype

BRANCHCODE

ACCOUNTTYPE

ACCOUNTNUMBER

ACCOUNTCURRENCY

BANKCODE

IBAN

ACCOUNTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEPOLICYSTATUSCHANGE_FSFS_RES

Attribute	Description
Name	DELETEPOLICYSTATUSCHANGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	Indicates Module Id				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

Policy-Status-Change-Full

Attribute	Description
------------------	--------------------

Name	Policy-Status-Change-Full
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

OLDPOLICYSTATUS

Attribute	Description	
Name	OLDPOLICYSTATUS	
Datatype	String	
Description	Indicates Old Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

NEWPOLICYSTATUS

Attribute	Description	
Name	NEWPOLICYSTATUS	
Datatype	String	
Description	Indicates New Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute		
	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

TRANSACTION_DESC

Attribute	Description	
Name	TRANSACTION_DESC	
Datatype	String	
Description	Indicates Transaction Description	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

LANGDESC

Attribute	Description
Name	LANGDESC
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Policy

Attribute	Description	
Name	Policy	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PHID

Attribute	Description	
Name	PHID	
Datatype	String	
Description	Indicates Policy Holder	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PRODID

Attribute	Description	
Name	PRODID	
Datatype	String	
Description	Indicates Product Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

POLICYENDDATE

Attribute	Description	
Name	POLICYENDDATE	
Datatype	String	
Description	Indicates Policy End Date	
Attribute		
	Attribute	Description
	minOccurs	0

POLICYBASECCY

Attribute	Description	
Name	POLICYBASECCY	
Datatype	String	
Description	Indicates Policy Base Currency	
Restrictions		
	Restrictions	Description
	maxLength	3

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

ACCOUNTTYPE

Attribute	Description	
Name	ACCOUNTTYPE	
Datatype	String	
Description	Indicates Account Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

ACCOUNTCURRENCY

Attribute	Description	
Name	ACCOUNTCURRENCY	
Datatype	String	
Description	Indicates Account Currency	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description	BANK LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE = PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	40

ACCOUNTNAME

Attribute	Description
Name	ACCOUNTNAME

Datatype	String	
Description	Indicates Account Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.4.LE-DeletePolicyStatusChange-Res-PK-MSG.xsd

DELETPOLICYSTATUSCHANGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-PK

POLICYNUMBER

RULEEFFECTIVEDATE

Policy-Status-Change-IO

POLICYNUMBER

RULEEFFECTIVEDATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEPOLICYSTATUSCHANGE_IOPK_RES

Attribute	Description
Name	DELETEPOLICYSTATUSCHANGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
------------------	--------------------

Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Policy-Status-Change-PK

Attribute	Description
Name	Policy-Status-Change-PK
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policiy Number	
Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.ModifyPolicyStatusChange

2.4.1.LE-ModifyPolicyStatusChange-Req-Full-MSG.xsd

MODIFYPOLICYSTATUSCHANGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-Full

POLICYNUMBER

RULEEFFECTIVEDATE

APPLICATIONDATE
OLDPOLICYSTATUS
NEWPOLICYSTATUS
DESCRIPTION
REDEMPTIONTXNGEN
SURRENDERMONEYPAYABLE
ADJTXNTYPE
OFFSETVALUE
BACKDATESURRENDER
AVERAGESALARY
DATEOFDEATH
ALLOWSURRENDER
ALLOWCLOSURE
ALLOWTRANSFER
TRANSACTION_DESC
LANGDESC
REMARKS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Policy
 PHID
 PRODID
 POLICYENDDATE
 POLICYBASECCY
Subtype
 BRANCHCODE
 ACCOUNTTYPE

ACCOUNTNUMBER

ACCOUNTCURRENCY

BANKCODE

IBAN

ACCOUNTNAME

MODIFYPOLICYSTATUSCHANGE_FSFS_REQ

Attribute	Description
Name	MODIFYPOLICYSTATUSCHANGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ModifyPolicyStatusChange

Policy-Status-Change-Full

Attribute	Description
Name	Policy-Status-Change-Full
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
-----------	-------------

Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

OLDPOLICYSTATUS

Attribute	Description	
Name	OLDPOLICYSTATUS	
Datatype	String	
Description	Indicates Old Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

NEWPOLICYSTATUS

Attribute	Description	
Name	NEWPOLICYSTATUS	
Datatype	String	
Description	Indicates New Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute		
	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

TRANSACTION_DESC

Attribute	Description	
Name	TRANSACTION_DESC	
Datatype	String	
Description	Indicates Transaction Description	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

LANGDESC

Attribute	Description	
Name	LANGDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Policy

Attribute	Description	
Name	Policy	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PHID

Attribute	Description	
Name	PHID	
Datatype	String	
Description	Indicates Policy Holder	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PRODID

Attribute	Description	
Name	PRODID	
Datatype	String	
Description	Indicates Product Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

POLICYENDDATE

Attribute	Description	
Name	POLICYENDDATE	
Datatype	String	
Description	Indicates Policy End Date	
Attribute		
	Attribute	Description
	minOccurs	0

POLICYBASECCY

Attribute	Description	
Name	POLICYBASECCY	
Datatype	String	
Description	Indicates Policy Base Currency	
Restrictions		
	Restrictions	Description
	maxLength	3

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

BRANCHCODE

Attribute	Description
------------------	--------------------

Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

ACCOUNTTYPE

Attribute	Description	
Name	ACCOUNTTYPE	
Datatype	String	
Description	Indicates Account Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

ACCOUNTCURRENCY

Attribute	Description	
Name	ACCOUNTCURRENCY	
Datatype	String	
Description	Indicates Account Currency	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description	BANK LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE = PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

ACCOUNTNAME

Attribute	Description	
Name	ACCOUNTNAME	
Datatype	String	
Description	Indicates Account Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

2.4.2.LE-ModifyPolicyStatusChange-Req-IO-MSG.xsd

MODIFYPOLICYSTATUSCHANGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Policy-Status-Change-IO
 POLICYNUMBER
 RULEEFFECTIVEDATE
 DESCRIPTION
 REDEMPTIONTXNGEN
 SURRENDERMONEYPAYABLE
 ADJTXNTYPE
 OFFSETVALUE
 BACKDATESURRENDER
 AVERAGESALARY
 DATEOFDEATH
 ALLOWSURRENDER
 ALLOWCLOSURE
 ALLOWTRANSFER
 MAKER
 MAKERSTAMP

Subtype

ACCOUNTNUMBER

IBAN

MODIFYPOLICYSTATUSCHANGE_IOPK_REQ

Attribute	Description
Name	MODIFYPOLICYSTATUSCHANGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ModifyPolicyStatusChange

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

DESCRIPTION

Attribute	Description
-----------	-------------

Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description
------------------	--------------------

Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute		
	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	40

2.4.3.LE-ModifyPolicyStatusChange-Res-Full-MSG.xsd

MODIFYPOLICYSTATUSCHANGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Policy-Status-Change-Full
POLICYNUMBER
RULEEFFECTIVEDATE
APPLICATIONDATE
OLDPOLICYSTATUS
NEWPOLICYSTATUS
DESCRIPTION
REDEMPTIONTXNGEN
SURRENDERMONEYPAYABLE
ADJTXNTYPE
OFFSETVALUE
BACKDATESURRENDER
AVERAGESALARY

DATEOFDEATH
ALLOWSURRENDER
ALLOWCLOSURE
ALLOWTRANSFER
TRANSACTION_DESC
LANGDESC
REMARKS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Policy
 PHID
 PRODID
 POLICYENDDATE
 POLICYBASECCY
Subtype
 BRANCHCODE
 ACCOUNTTYPE
 ACCOUNTNUMBER
 ACCOUNTCURRENCY
 BANKCODE
 IBAN
 ACCOUNTNAME
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYPOLICYSTATUSCHANGE_FSFS_RES

Attribute	Description
Name	MODIFYPOLICYSTATUSCHANGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Policy-Status-Change-Full

Attribute	Description
Name	Policy-Status-Change-Full
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
-----------	-------------

Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

OLDPOLICYSTATUS

Attribute	Description	
Name	OLDPOLICYSTATUS	
Datatype	String	
Description	Indicates Old Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

NEWPOLICYSTATUS

Attribute	Description	
Name	NEWPOLICYSTATUS	
Datatype	String	
Description	Indicates New Policy Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

TRANSACTION_DESC

Attribute	Description	
Name	TRANSACTION_DESC	
Datatype	String	
Description	Indicates Transaction Description	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

LANGDESC

Attribute	Description	
Name	LANGDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Policy

Attribute	Description	
Name	Policy	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PHID

Attribute	Description	
Name	PHID	
Datatype	String	
Description	Indicates Policy Holder	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PRODID

Attribute	Description	
Name	PRODID	
Datatype	String	
Description	Indicates Product Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

POLICYENDDATE

Attribute	Description	
Name	POLICYENDDATE	
Datatype	String	
Description	Indicates Policy End Date	
Attribute		
	Attribute	Description
	minOccurs	0

POLICYBASECCY

Attribute	Description	
Name	POLICYBASECCY	
Datatype	String	
Description	Indicates Policy Base Currency	
Restrictions		
	Restrictions	Description
	maxLength	3

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

BRANCHCODE

Attribute	Description
------------------	--------------------

Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

ACCOUNTTYPE

Attribute	Description	
Name	ACCOUNTTYPE	
Datatype	String	
Description	Indicates Account Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	16

ACCOUNTCURRENCY

Attribute	Description	
Name	ACCOUNTCURRENCY	
Datatype	String	
Description	Indicates Account Currency	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description	BANK LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE = PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

ACCOUNTNAME

Attribute	Description	
Name	ACCOUNTNAME	
Datatype	String	
Description	Indicates Account Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

MODIFYPOLICYSTATUSCHANGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Policy-Status-Change-PK

POLICYNUMBER

RULEEFFECTIVEDATE

Policy-Status-Change-IO

POLICYNUMBER

RULEEFFECTIVEDATE

DESCRIPTION

REDEMPTIONTXNGEN

SURRENDERMONEYPAYABLE

ADJTXNTYPE

OFFSETVALUE

BACKDATESURRENDER

AVERAGESALARY

DATEOFDEATH

ALLOWSURRENDER

ALLOWCLOSURE

ALLOWTRANSFER

MAKER

MAKERSTAMP

Subtype

ACCOUNTNUMBER

IBAN

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYPOLICYSTATUSCHANGE_IOPK_RES

Attribute	Description
Name	MODIFYPOLICYSTATUSCHANGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
------------------	--------------------

Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

Policy-Status-Change-PK

Attribute	Description
Name	Policy-Status-Change-PK
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policiy Number	
Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Surrender Money Payable Description

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute		
	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	1,0

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	40

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description
------------------	--------------------

Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.QueryPolicyStatusChange

*QUERYPOLICYSTATUSCHANGE_IOFS_REQ**FCUBS_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION**SOURCE_OPERATION**SOURCE_USERID**DESTINATION**MULTITRIPID**FUNCTIONID**ACTION**MSGSTAT**PASSWORD**ADDL**PARAM**NAME**VALUE**FCUBS_BODY**Policy-Status-Change-IO**POLICYNUMBER**RULEEFFECTIVEDATE***QUERYPOLICYSTATUSCHANGE_IOFS_REQ**

Attribute	Description
Name	QUERYPOLICYSTATUSCHANGE_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of QueryPolicyStatusChange

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policiy Number	
Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

2.5.2.LE-QueryPolicyStatusChange-Res-Full-MSG.xsd

QUERYPOLICYSTATUSCHANGE_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Policy-Status-Change-IO
POLICYNUMBER
RULEEFFECTIVEDATE
Policy-Status-Change-Full
POLICYNUMBER
RULEEFFECTIVEDATE
APPLICATIONDATE
OLDPOLICYSTATUS
NEWPOLICYSTATUS
DESCRIPTION
REDEMPTIONTXNGEN
SURRENDERMONEYPAYABLE
ADJTXNTYPE
OFFSETVALUE
BACKDATESURRENDER
AVERAGESALARY
DATEOFDEATH
ALLOWSURRENDER
ALLOWCLOSURE
ALLOWTRANSFER
TRANSACTION_DESC

LANGDESC

REMARKS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Policy

PHID

PRODID

POLICYENDDATE

POLICYBASECCY

Subtype

BRANCHCODE

ACCOUNTTYPE

ACCOUNTNUMBER

ACCOUNTCURRENCY

BANKCODE

IBAN

ACCOUNTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYPOLICYSTATUSCHANGE_IOFS_RES

Attribute	Description
-----------	-------------

Name	QUERYPOLICYSTATUSCHANGE IOFS RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here. 231	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Policy-Status-Change-IO

Attribute	Description
Name	Policy-Status-Change-IO
Datatype	
Description	

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

Policy-Status-Change-Full

Attribute	Description
Name	Policy-Status-Change-Full
Datatype	
Description	

POLICYNUMBER

Attribute	Description
Name	POLICYNUMBER
Datatype	String
Description	Indicates Policy Number

Restrictions		
	Restrictions	Description
	maxLength	16

RULEEFFECTIVEDATE

Attribute	Description
Name	RULEEFFECTIVEDATE
Datatype	String
Description	Indicates Rule Effective Date

APPLICATIONDATE

Attribute	Description
Name	APPLICATIONDATE
Datatype	String
Description	Indicates Application Date

OLDPOLICYSTATUS

Attribute	Description	
Name	OLDPOLICYSTATUS	
Datatype	String	
Description	Indicates Old Policy Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

NEWPOLICYSTATUS

Attribute	Description	
Name	NEWPOLICYSTATUS	
Datatype	String	
Description	Indicates New Policy Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Surrender Money Payable Description	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	60

REDEMPTIONTXNGEN

Attribute	Description	
Name	REDEMPTIONTXNGEN	
Datatype	Decimal	
Description	Indicates Redemption Txn Generate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	1

SURRENDERMONEYPAYABLE

Attribute	Description	
Name	SURRENDERMONEYPAYABLE	
Datatype	String	
Description	Indicates Surrender Money Payable, P for Product, C for Client	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H

ADJTXNTYPE

Attribute	Description	
Name	ADJTXNTYPE	
Datatype	String	
Description	Indicates Adjust Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OFFSETVALUE

Attribute	Description	
Name	OFFSETVALUE	
Datatype	Decimal	
Description	Indicates Offset Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

BACKDATESURRENDER

Attribute	Description	
Name	BACKDATESURRENDER	
Datatype	Decimal	
Description	Indicates Back Date Surrender	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

AVERAGESALARY

Attribute	Description	
Name	AVERAGESALARY	
Datatype	Decimal	
Description	Indicates Average Salary	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

DATEOFDEATH

Attribute	Description	
Name	DATEOFDEATH	
Datatype	String	
Description	Indicates Date of death	
Attribute	Attribute	Description
	minOccurs	0

ALLOWSURRENDER

Attribute	Description	
Name	ALLOWSURRENDER	
Datatype	String	
Description	Indicates Allow Surrender, 1 for Yes, 0 for No	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	1,0

ALLOWCLOSURE

Attribute	Description	
Name	ALLOWCLOSURE	
Datatype	String	
Description	Indicates Allow Closure, 1 for Yes, 0 for No	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

ALLOWTRANSFER

Attribute	Description	
Name	ALLOWTRANSFER	
Datatype	String	
Description	Indicates Allow Transfer, 1 for Yes, 0 for no	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	1,0

TRANSACTION_DESC

Attribute	Description	
Name	TRANSACTION_DESC	
Datatype	String	
Description	Indicates Transaction Description	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

LANGDESC

Attribute	Description	
Name	LANGDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Policy Remarks	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	Indicates Maker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	Indicates Checker	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Checker Date	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Policy

Attribute	Description	
Name	Policy	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PHID

Attribute	Description	
Name	PHID	
Datatype	String	
Description	Indicates Policy Holder	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

PRODID

Attribute	Description	
Name	PRODID	
Datatype	String	
Description	Indicates Product Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

POLICYENDDATE

Attribute	Description	
Name	POLICYENDDATE	
Datatype	String	
Description	Indicates Policy End Date	
Attribute	Attribute	Description
	minOccurs	0

POLICYBASECCY

Attribute	Description	
Name	POLICYBASECCY	
Datatype	String	
Description	Indicates Policy Base Currency	
Restrictions	Restrictions	Description
	maxLength	3

Subtype

Attribute	Description	
Name	Subtype	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

ACCOUNTTYPE

Attribute	Description	
Name	ACCOUNTTYPE	
Datatype	String	
Description	Indicates Account Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description	Indicates Account Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

ACCOUNTCURRENCY

Attribute	Description	
Name	ACCOUNTCURRENCY	
Datatype	String	
Description	Indicates Account Currency	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description	BANK LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE = PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

IBAN

Attribute	Description	
Name	IBAN	
Datatype	String	
Description	IBAN Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	40

ACCOUNTNAME

Attribute	Description	
Name	ACCOUNTNAME	
Datatype	String	
Description	Indicates Account Name	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.