

Gateway Documentation - FCISPolicyTxn
Oracle FLEXCUBE Investor Servicing
Release 12.1.0.0.0
[October][2015]



Table Of Contents

1. Background		1
2. FCISPolicyTxn		2
2.1. QueryPolicyTxn		2
2.1.1. UT-QueryPolicyTxn-Req-IO-MSG.xsd		2
2.1.2. UT-QueryPolicyTxn-Res-Full-MSG.xsd		10

1. Background

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCISPolicyTxn of UT Module

2. FCISPolicyTxn

2.1.QueryPolicyTxn

2.1.1.UT-QueryPolicyTxn-Req-IO-MSG.xsd

QUERYPOLICYTXN_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Query-Policy-Transaction-IO

POLICYTXNNUMBER

POLICYNUMBER

PRODUCTID

TXNTYPE

POLICYHOLDERID

TXNREFERENCENUMBER

MAKER_ID

AUTH_STAT

TXNDATE

QUERYPOLICYTXN_IOFS_REQ

Attribute	Description
Name	QUERYPOLICYTXN_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of QueryPolicyTxn

Query-Policy-Transaction-IO

Attribute	Description
Name	Query-Policy-Transaction-IO
Datatype	
Description	

POLICYTXNNUMBER

Attribute	Description	
Name	POLICYTXNNUMBER	
Datatype	String	
Description	Indicates Policy Transaction Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

POLICYNUMBER

Attribute	Description
Name	POLICYNUMBER
Datatype	String
Description	Indicates Policy Number

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

PRODUCTID

Attribute	Description	
Name	PRODUCTID	
Datatype	String	
Description	Indicates Product Id	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

TXNTYPE

Attribute	Description	
Name	TXNTYPE	
Datatype	String	
Description	Indicates Transaction Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

POLICYHOLDERID

Attribute	Description	
Name	POLICYHOLDERID	
Datatype	String	
Description	Indicates Policy Holder Id	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

TXNREFERENCENUMBER

Attribute	Description	
Name	TXNREFERENCENUMBER	
Datatype	String	
Description	Indicates Transaction Reference Number	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

MAKER_ID

Attribute	Description	
Name	MAKER_ID	
Datatype	String	
Description	Indicates Maker ID	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description	Indicates Auth Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

TXNDATE

Attribute	Description	
Name	TXNDATE	
Datatype	String	
Description	Indicates Transaction Date	
Attribute		
	Attribute	Description
	minOccurs	0

2.1.2.UT-QueryPolicyTxn-Res-Full-MSG.xsd

QUERYPOLICYTXN_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Query-Policy-Transaction-IO
POLICYTXNNUMBER
POLICYNUMBER
PRODUCTID
TXNTYPE
POLICYHOLDERID
TXNREFERENCENUMBER
MAKER_ID
AUTH_STAT
TXNDATE
Query-Policy-Transaction-Full
POLICYTXNNUMBER
POLICYNUMBER

PRODUCTID
TXNTYPE
POLICYHOLDERID
TXNREFERENCENUMBER
MAKER_ID
AUTH_STAT
TXNDATE
Policy-Transaction-Details
POLICYTXNNUMBER
POLICYNUMBER
PRODUCTID
TXNTYPE
TXNDATE
POLICYHOLDERID
TXNREFERENCENUMBER
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
AUTH_STAT
MOD_NO
RECORD_STAT
OPERATE
STATUS
AGENTCODE
BRANCHCODE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

QUERYPOLICYTXN_IOFS_RES

Attribute	Description
Name	QUERYPOLICYTXN_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain FLEXCUBE.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain FCUBS and FCIS if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the unique message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely Message ID to Correlation ID (M2C) and Correlation ID to Correlation ID (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	Indicates Module Id	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	

Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be FLEXCUBE. In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are SUCCESS, WARNING and FAILURE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

Query-Policy-Transaction-IO

Attribute	Description
Name	Query-Policy-Transaction-IO
Datatype	
Description	

POLICYTXNNUMBER

Attribute	Description	
Name	POLICYTXNNUMBER	
Datatype	String	
Description	Indicates Policy Transaction Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

POLICYNUMBER

Attribute	Description
Name	POLICYNUMBER
Datatype	String
Description	Indicates Policy Number

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

PRODUCTID

Attribute	Description	
Name	PRODUCTID	
Datatype	String	
Description	Indicates Product Id	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

TXNTYPE

Attribute	Description	
Name	TXNTYPE	
Datatype	String	
Description	Indicates Transaction Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

POLICYHOLDERID

Attribute	Description	
Name	POLICYHOLDERID	
Datatype	String	
Description	Indicates Policy Holder Id	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

TXNREFERENCENUMBER

Attribute	Description	
Name	TXNREFERENCENUMBER	
Datatype	String	
Description	Indicates Transaction Reference Number	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

MAKER_ID

Attribute	Description	
Name	MAKER_ID	
Datatype	String	
Description	Indicates Maker ID	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description	Indicates Auth Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

TXNDATE

Attribute	Description	
Name	TXNDATE	
Datatype	String	
Description	Indicates Transaction Date	
Attribute		
	Attribute	Description
	minOccurs	0

Query-Policy-Transaction-Full

Attribute	Description
Name	Query-Policy-Transaction-Full
Datatype	
Description	

POLICYTXNNUMBER

Attribute	Description
------------------	--------------------

Name	POLICYTXNNUMBER	
Datatype	String	
Description	Indicates Policy Transaction Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

PRODUCTID

Attribute	Description	
Name	PRODUCTID	
Datatype	String	
Description	Indicates Product Id	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

TXNTYPE

Attribute	Description	
Name	TXNTYPE	
Datatype	String	
Description	Indicates Transaction Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

POLICYHOLDERID

Attribute	Description
------------------	--------------------

Name	POLICYHOLDERID	
Datatype	String	
Description	Indicates Policy Holder Id	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

TXNREFERENCENUMBER

Attribute	Description	
Name	TXNREFERENCENUMBER	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

MAKER_ID

Attribute	Description	
Name	MAKER ID	
Datatype	String	
Description	Indicates Maker ID	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description	Indicates Auth Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

TXNDATE

Attribute	Description
------------------	--------------------

Name	TXNDATE	
Datatype	String	
Description	Indicates Transaction Date	
Attribute	Attribute	Description
	minOccurs	0

Policy-Transaction-Details

Attribute	Description	
Name	Policy-Transaction-Details	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

POLICYTXNNUMBER

Attribute	Description	
Name	POLICYTXNNUMBER	
Datatype	String	
Description	Indicates Policy Transaction Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

POLICYNUMBER

Attribute	Description	
Name	POLICYNUMBER	
Datatype	String	
Description	Indicates Policy Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

PRODUCTID

Attribute	Description	
Name	PRODUCTID	
Datatype	String	
Description	Indicates Product Id	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	10

TXNTYPE

Attribute	Description	
Name	TXNTYPE	
Datatype	String	
Description	Indicates Transaction Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

TXNDATE

Attribute	Description	
Name	TXNDATE	
Datatype	String	
Description	Indicates Transaction Date	
Attribute	Attribute	Description
	minOccurs	0

POLICYHOLDERID

Attribute	Description	
Name	POLICYHOLDERID	
Datatype	String	
Description	Indicates Policy Holder Id	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TXNREFERENCENUMBER

Attribute	Description	
Name	TXNREFERENCENUMBER	
Datatype	String	
Description	Indicates Transaction Reference Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

MAKER_ID

Attribute	Description	
Name	MAKER_ID	
Datatype	String	
Description	Indicates Maker ID	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

MAKER_DT_STAMP

Attribute	Description	
Name	MAKER_DT_STAMP	
Datatype	String	
Description	Indicates Maker DT Stamp	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER_ID

Attribute	Description	
Name	CHECKER_ID	
Datatype	String	
Description	Indicates Checker ID	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

CHECKER_DT_STAMP

Attribute	Description	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description	Indicates Checker DT Stamp	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description	Indicates Auth Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

MOD_NO

Attribute	Description	
Name	MOD_NO	
Datatype	Decimal	
Description	Indicates Mod NO	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	38

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description	Indicates Record Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

OPERATE

Attribute	Description	
Name	OPERATE	
Datatype	String	
Description	Indicates Operate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	0

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates SI Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

AGENTCODE

Attribute	Description	
Name	AGENTCODE	
Datatype	String	
Description	Indicates Agent Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	BRANCH LOV, COLUMN - BANKCODE, TABLE - BANKTBL, CRITERIA BANKCODE not equal to PARENTBANKCODE AND DELETEDSTATUS = 0	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.