

SOA Suite Setup for BPEL Process Flow
Oracle FLEXCUBE Investor Servicing
Release 12.1.0.0.0
[October] [2015]



Table of Contents

1. PREFACE	1-1
1.1 BACKGROUND	1-1
1.2 AUDIENCE	1-1
1.3 ORGANIZATION	1-1
1.4 ACRONYMS AND ABBREVIATIONS	1-1
2. REPOSITORY CREATION UTILITY (RCU)	2-1
2.1 INTRODUCTION	2-1
2.2 RUNNING RCU UTILITY	2-1
3. ORACLE WEBLOGIC 11GR1 (10.3.6).....	3-1
3.1 INTRODUCTION	3-1
3.2 DOWNLOAD URL FROM ORACLE	3-1
4. ORACLE SOA SUITE 11GR1(11.1.1.7).....	4-1
4.1 INTRODUCTION	4-1
4.2 DOWNLOAD URL FROM ORACLE	4-1
5. DOMAIN CONFIGURATION WITH ORACLE SOA SUITE	5-1
5.1 INTRODUCTION	5-1
5.2 NEW DOMAIN CONFIGURATION	5-1
6. ORACLE HTTP SERVER INSTALLATION AND CONFIGURATION.....	6-1
6.1 INTRODUCTION	6-1
6.2 INSTALLATION & CONFIGURATION	6-1
7. GENERATING SELF SIGNED CERTIFICATE AND CONFIGURING SSL	7-1
7.1 ORAPKI UTILITY TO CREATE WALLET AND SELF SIGNED CERTIFICATE.....	7-1
8. PRE-DEPLOYMENT TASKS	8-5
8.1 FCIS AND BPEL INTEGRATION	8-5
8.1.1 Custom Provider Configuration	8-5
8.1.2 JPS Configuration	8-9
8.1.3 WorkFlow Identity Configuration.....	8-10
8.1.4 Security Policy Configuration.....	8-18
8.1.5 Custom Escalation Configuration.....	8-23
8.1.6 CIS Configuration.....	8-24
8.1.7 Configuring DBAdapter.....	8-28

1. Preface

1.1 Background

This document provides an overview of configuring SOA suite for Oracle FLEXCUBE Investor Servicing BPEL process deployment.

Refer to the Oracle documentation for HA and other configuration patterns.

1.2 Audience

The audience for this document will be the development groups of BPEL process flows FLEXCUBE Investor Servicing.

1.3 Organization

This manual is organized as follows:

- The chapter 2 (Repository Creation Utility (RCU)) guides you through the use of repository creation utility
- Subsequent chapters contain implementation specific information

1.4 Acronyms and Abbreviations

Acronym/Abbreviation	Description
BPEL	Business Process Execution Language
HA	High Availability

2. Repository Creation Utility (RCU)

2.1 Introduction

You can use Oracle Repository Creation Utility (RCU) to create schemas that are required for SOA suite installation.

Refer to the Oracle certification matrix for qualified databases.


2.2 Running RCU Utility

For running RCU utility, follow the steps given below.


1. Download the RCU utility from the following URL.

http://download.oracle.com/otn/nt/middleware/11g/ofm_rcu_win32_11.1.1.2.1_disk1_1of1.zip

2. Unzip the contents into a folder.



3. Run the *rcu.bat* from the extracted folder.



4. Select 'Create Repository' option and click 'Next' button.

Repository Creation Utility - Step 2 of 7: Database Connection Details

Database Connection Details

Database Type: Oracle Database

Host Name: ddhp0240.i-flex.com
For RAC database, specify VIP name or one of the Node name as Host name.

Port: 1521

Service Name: orcl.i-flex.com

Username: SYS
User with DBA or SYSDBA privileges. Example:sys

Password: ••••••••

Role: SYSDBA
One or more components may require SYSDBA role for the operation to succeed.

Messages:

Help < Back Next > Finish Cancel

5. Provide oracle database connection properties. SYS credentials are required. Once you have specified the details, click 'Next' button.


Repository Creation Utility - Checking Prerequisites

Checking Global Prerequisites


✓ Initializing repository configuration metadata	00:02.266(sec)
✓ Obtain properties of the specified database	00:00.110(ms)
✓ Check requirement for specified database	00:00.437(ms)
✓ Execute pre create operations	00:00.984(ms)

Operation completed. Click OK to continue to next page.


OK



6. Create a new prefix in order to add multiple SOA schemas in the same instance.
7. On selecting SOA & BPM Infrastructure, by default 'AS Common Schemas' and 'Metadata Services' check-boxes are checked. Do not uncheck these options.
8. If you do not wish to use 'Business Activity Monitoring', you may uncheck it.




Click 'OK'.




Note: It is important to remember the password or passwords that you enter during the process.


9. Specify the passwords and click 'Next' button.




10. Click 'Next'.




11. Click 'OK'.



12. Tablespaces creation.



13. Summary .



14. Completion Summary

3. Oracle Weblogic 11gR1 (10.3.6)


3.1 Introduction


Oracle Weblogic 11gR1 is the j2ee container for soa suite

The version required is 10.3.6


3.2 Download URL from Oracle

1. http://www.oracle.com/technology/software/products/ias/htdocs/wls_main.html
2. Download based on your needs (Windows / Linux / Generic)
3. The installation process might slightly vary depending on the platform OS
4. This step may be skipped if the weblogic installation is available
5. Run the <...wls1032_win32...>.exe





6. Click 'Next'.



7. Specify the middleware home the same will be used during SOA suite installation.

Oracle Installer - WebLogic 10.3.2.0

Register for Security Updates

Provide your email address to be informed of security issues, install the product, and initiate configuration manager. <http://www.oracle.com/support/policies.html>


Email:

Easier for you if you use your My Oracle Support email address/username.


☒ I wish to receive security updates via My Oracle Support

My Oracle Support Password:


8. Register for security updates if needed




9. Choose typical or custom to customize installation




10. If custom , customize installation




11. Select Bundled JDK that is needed





12. Click 'Next'.




13. Install Node manager if remote start and monitoring is required needed.









4. Oracle SOA Suite 11gR1(11.1.1.7)


4.1 Introduction


Oracle SOA suite 11gR1 (11.1.1.7) is required for running FCIS BPEL Process flows

The version required is 11.1.1.7

4.2 Download URL from Oracle

1. http://www.oracle.com/technology/software/products/ias/htdocs/wls_main.html
2. Download based on your needs (Windows / Linux / Generic)
3. The installation process might slightly vary depending on the platform / mode of installation (package / net..)
4. Unzip to a folder and run from Disk1 folder setup.exe






The screenshot shows a window titled "Oracle Universal Installer". The text inside the window is as follows:


```
Starting Oracle Universal Installer...

Checking if CPU speed is above 300 MHz .   Actual 2327 MHz   Passed
Checking swap space: must be greater than 500 MB .   Actual 4092 MB   Passed
Checking monitor: must be configured to display at least 256 colors Higher than
256 .   Actual 65536   Passed
Preparing to launch Oracle Universal Installer from C:\DOCUME~1\piyushko\LOCALS
~1\Temp\1\OraInstall2010-04-05_07-26-39AM. Please wait ...
Please specify JRE/JDK location < Ex. /home/jre >, <location>/bin/java should e
xist : C:/Program Files/Java/jdk1.6.0_16/jre
-
```


5. Specify JRE/JDK location for installation to proceed.




6. Click 'Next'.




7. Click 'Next'.




8. Specify the same middleware home that was used for Weblogic server.




9. Click 'Install'.





10. Click 'Next'.



5. Domain Configuration with Oracle SOA suite


5.1 Introduction


New domain can be configured or an existing domain can be extended with Oracle SOA suite components.

5.2 New Domain Configuration


1. Run Config command

<middleware_home> wlsserver_10.3\common\bin\config or
<middleware_home> \Oracle_SOA1\common\bin\config





2. Create a new domain or extend an existing domain to include soa suite components.



3. On selecting Oracle SOA suite it automatically selects Oracle WSM Policy Manager, Oracle JRF
4. Select Oracle Enterprise Manager for managing / monitoring BPEL processes

Fusion Middleware Configuration Wizard

Specify Domain Name and Location

ORACLE

Enter the name and location for the domain and its applications:

Domain name:

Domain location:

Application location:

Fusion Middleware Configuration Wizard

Configure Administrator User Name and Password

ORACLE

Discard Changes

*User name: weblogic


*User password: *****

*Confirm user password: *****

Description: This user is the default administrator.

Exit Help Previous Next

5. Configure Administrator user / password.



6. Select jdk depending on the startup mode.

Fusion Middleware Configuration Wizard

Configure JDBC Component Schema

ORACLE

Note: Change only the input fields below that you wish to modify and values will be applied to all selected rows.

Vendor: DBMS/Service:

Driver: Host Name:

Schema Owner: Port:

Schema Password:

☐ Configure selected component schemas as RAC multi data source schemas in the next panel.

	Component Schema	DBMS/Service	Host Name	Port	Schema Owner	Schema Password
<input type="checkbox"/>	SOA Infrastructure	orcl	dbhost.example.com	1521	DEV_SOAINFRA	
<input type="checkbox"/>	User Messaging Service	orcl	dbhost.example.com	1521	DEV_ORASDPM	
<input type="checkbox"/>	OWSM MDS Schema	orcl	dbhost.example.com	1521	DEV_MDS	
<input type="checkbox"/>	SOA MDS Schema	orcl	dbhost.example.com	1521	DEV_MDS	

7. Configure schema components.
8. Select all the check boxes.

Fusion Middleware Configuration Wizard

Configure JDBC Component Schema

ORACLE

Note: Change only the input fields below that you wish to modify and values will be applied to all selected rows.

Vendor: DBMS/Service:

Driver: Host Name:

Schema Owner: Port:

Schema Password:

☐ Configure selected component schemas as RAC multi data source schemas in the next panel.

	Component Schema	DBMS/Service	Host Name	Port	Schema Owner	Schema Password
<input checked="" type="checkbox"/>	SOA Infrastructure	orcl	dbhost.example.com	1521	DEV_SOAINFRA	
<input checked="" type="checkbox"/>	User Messaging Service	orcl	dbhost.example.com	1521	DEV_ORASDPM	
<input checked="" type="checkbox"/>	OWSM MDS Schema	orcl	dbhost.example.com	1521	DEV_MDS	
<input checked="" type="checkbox"/>	SOA MDS Schema	orcl	dbhost.example.com	1521	DEV_MDS	

9. Provide the db parameters used during schema creation (RCU Utility)

Fusion Middleware Configuration Wizard

Configure JDBC Component Schema

ORACLE

Note: Change only the input fields below that you wish to modify and values will be applied to all selected rows.

Vendor:
Oracle

DBMS/Service:
ORCL.I-FLEX.COM

Driver:
*Oracle's Driver (Thin) for Service connections; Versions:9.0.1,9.2.0

Host Name:
ddhp0240.i-flex.com

Schema Owner:
Varies among component schemas

Port:
1521

Schema Password:

☐ Configure selected component schemas as RAC multi data source schemas in the next panel.


	Component Schema	DBMS/Service	Host Name	Port	Schema Owner	Schema Password
<input checked="" type="checkbox"/>	SOA Infrastructure	ORCL.I-FLEX.COM	ddhp0240.i-flex.com	1521	DEV_SOAINFRA	*****
<input checked="" type="checkbox"/>	User Messaging Service	ORCL.I-FLEX.COM	ddhp0240.i-flex.com	1521	DEV_ORASDPM	*****
<input checked="" type="checkbox"/>	OWSM MDS Schema	ORCL.I-FLEX.COM	ddhp0240.i-flex.com	1521	DEV_MDS	*****
<input checked="" type="checkbox"/>	SOA MDS Schema	ORCL.I-FLEX.COM	ddhp0240.i-flex.com	1521	DEV_MDS	*****

Exit


Help

Previous


Next




10. Test the database connectivity





11. Select the Administration Server & Managed Server



12. Configure the Administration Server & Managed Server.







6. Oracle HTTP server Installation and Configuration

6.1 Introduction


Oracle HTTP server is typically configured in front of weblogic application server , The choice of deployment and SSL terminator will depend on the deployment configuration expected .

Download URL – Please check for appropriate version , The version depicted here is 11.1.1.7


<http://www.oracle.com/technology/software/index.html>

6.2 Installation & Configuration


1. Run setup.exe




2. Select Install & Configure




3. Check if prerequisite checks are passed.



4. Select the middleware home where weblogic server is already installed.




5. Choose components Oracle HTTP Server / Oracle Webcache.



6. Specify weblogic domain details.

Oracle Fusion Middleware 11g Web Tier Utilities Installation - Step 6 of 14

Specify WebLogic Domain



[Welcome](#)
[Install and Configure](#)
[Prerequisite Checks](#)
[Specify Installation Location](#)
[Configure Components](#)
[Specify WebLogic Domain](#)
[Specify Component Details](#)
[Web Cache Administrator](#)
[Configure Ports](#)
[Specify Security Updates](#)
[Installation Summary](#)
[Installation Progress](#)
[Configuration Progress](#)
[Installation Complete](#)

Domain Host Name:
Domain Port No:
User Name:
Password:

[Help](#) [< Back](#) [Next >](#) [Finish](#) [Cancel](#)

Elapsed Time: 45m 28s

7. Location where components to be installed.

Oracle Fusion Middleware 11g Web Tier Utilities Installation - Step 7 of 14

Specify Component Details

ORACLE 11g
FUSION MIDDLEWARE

[Welcome](#)
[Install and Configure](#)
[Prerequisite Checks](#)
[Specify Installation Location](#)
[Configure Components](#)
[Specify WebLogic Domain](#)
[Specify Component Details](#)
[Web Cache Administrator](#)
[Configure Ports](#)
[Specify Security Updates](#)
[Installation Summary](#)
Installation Progress
Configuration Progress
Installation Complete

Instance Home Location:


Instance Name:

OHS Component Name:


Web Cache Component Name:

Elapsed Time: 45m 58s

8. Credentials for web cache administrator.



9. Port configuration – Use specify port if custom ports are to be configured for various services.



10. If you are an administrator and require security updates from oracle , provide details and subscribe.

Oracle Fusion Middleware 11g Web Tier Utilities Installation - Step 10 of 14

Specify Security Updates

ORACLE 11g
FUSION MIDDLEWARE

Provide your email address to be informed of security issues, install the product and initiate configuration manager. [View details.](#)

Email:

Easier for you if you use your My Oracle Support email address/username.

☐ I wish to receive security updates via My Oracle Support.

My Oracle Support Password:

Installation Summary

Installation Progress


Configuration Progress

Installation Complete


Help < Back Next > Finish Cancel

Elapsed Time: 47m 13s


11. Review installation summary.




12. Review installation progress.



13. Review configuration progress.



14. Installation complete.



7. Generating Self Signed Certificate and Configuring SSL

Self signed certificates are used for development environment , for production environment certificate from a issuing authorities like (verisign / thwarte..) are to be used.

7.1 Orapki Utility to Create Wallet and Self Signed Certificate

This document gives details of using orapki utility for creating wallet and self signed certificates.

1. Orapki Utility

With

- Oracle Client < bin>
- WLS <<middleware>/oracle_common/bin

2. Wallet creation

```
orapki wallet create -wallet D:\oracle2\Middleware\wallet\ -pwd welcome123 -auto_login
```

3. Generating self signed certificatey

```
orapki wallet add -wallet D:\oracle2\Middleware\wallet\ -dn "CN=cvrze0013.i-flex.com,OU=BPD,O=Oracle,L=iflexpark,ST=Karnataka,C=IN" -keysize 1024 -self_signed -validity 365 -pwd welcome123
```

4. Add wallet to ssl.conf

ssl.conf can be located in
<middleware_home>/<ohs_home>/instances/<instance_name>/config/OHS/<ohsname>

E.g

```
<middleware_home>Oracle_WT1/instances/instance1/config/OHS/ohs1/ssl.conf
```

```
# SSL Certificate Revocation List Check
```

```
# Valid values are On and Off
```

```
SSLCRLCheck Off
```

```
#Path to the wallet
```

```
SSLWallet /data1/appsrvrs/wls1032/Oracle/Middleware/wallet
```

```
<FilesMatch "\.(cgi|shtml|phtml|php)$">
```

```
SSLOptions +StdEnvVars
```


</FilesMatch>

5. Mod_wl_ohs.conf modification to forward request to weblogic server

Mod_wl_ohs.conf can be located in

<middleware_home>/<ohs_home>/instances/<instance_name>/config/OHS/<ohsname>

E.g

<middleware_home>Oracle_WT1/instances/instance1/config/OHS/ohs1/mod_wl_ohs.conf

Sample configuration given below , please modify as per the application context and ports configured.



This is a template to configure mod_weblogic.

```
LoadModule weblogic_module "${ORACLE_HOME}/ohs/modules/mod_wl_ohs.so"
```

This empty block is needed to save mod_wl related configuration from EM to this file when changes are made at the Base Virtual Host Level

```
<IfModule weblogic_module>
```

```
#   WebLogicHost <WEBLOGIC_HOST>
```

```
#   WebLogicPort <WEBLOGIC_PORT>
```

```
#   Debug ON
```

```
#   WLLogFile /tmp/weblogic.log
```

```
#   MatchExpression *.jsp
```

```
</IfModule>
```

```
# <Location /weblogic>
```

```
#   SetHandler weblogic-handler
```

```
#   PathTrim /weblogic
```

```
#   ErrorPage http://WEBLOGIC_HOME:WEBLOGIC_PORT/
```

```
# </Location>
```

```
<Location /console>
```

```
    SetHandler weblogic-handler
```

```
    WebLogicHost localhost
```

```

        WeblogicPort 9001
    </Location>
    <Location /em>
        SetHandler weblogic-handler
        WebLogicHost localhost
        WeblogicPort 9001
    </Location>
    <Location /consolehelp>
        SetHandler weblogic-handler
        WebLogicHost localhost
        WeblogicPort 9001
    </Location>
    <Location /FCJNeoWeb>
        SetHandler weblogic-handler
        WebLogicHost localhost
        WeblogicPort 9003
    </Location>
    <Location /FCJNeoFgl>
        SetHandler weblogic-handler
        WebLogicHost localhost
        WeblogicPort 9003
    </Location>
    <Location /ELGatewayClient>
        SetHandler weblogic-handler
        WebLogicHost localhost
        WeblogicPort 9003

```

</Location>

8. Pre-Deployment Tasks

This section explains the Pre-Deployment tasks which need to be carried manually for FCIS + BPEL Integration.


8.1 FCIS and BPEL Integration

If the EAR has been created with BPEL as a PlugIn then along with FCIS EAR file, Installer creates two JAR files named as FCBPELCIS.jar and FCUBSAuthenticationProvider.jar. Before deploying FCIS EAR file following tasks should be completed.


8.1.1 Custom Provider Configuration

Custom Provider configuration has to be done from the weblogic console of SOA or manually update the config.xml of the soa domain.


1. Along with FCIS Ear file, Installer creates FCUBSAuthenticationProvider.jar file. Copy this files to <MIDDLEWARE_HOME>\wlserver_10.3\server\lib\mbeantypes
2. Restart the Admin Server
3. Login to the Console
4. Click on Security Realms.




5. Click on myrealm.



- Click on Providers tab and click on new button to create new authentication provider.
- Give Provider name as FCJCustomProvider and type as FCUBSUserAuthenticator.






(Click Reorder to bring provider to first of all providers)


8. Click on FCJCustomProvider.

9. In Common tab change the control flag to "SUFFICIENT"



10. In Provider Specific tab

- Set JNDIName as Flexcube JNDI Name.
- If external authentications used in FCIS then Fill the Ldap/MSAD related fields.



11. For manually editing the config.xml go to <ORACLE_HOME>\Middleware\user_projects\domains\base_domain\config\ path. Open config.xml file. The following codes need to be added at proper locations in the config.xml.
- search for < realm> tag and add the following code between <realm> and </ realm> tags. This should be the first child of the realm Node.

```
<sec:authentication-provider xmlns:n1="http://fcubs.ofss.com/security" xsi:type="n1:fcubs-user-authenticatorType">
```

```
<sec:name>FCJCustomProvider</sec:name>
```

```
<sec:control-flag>SUFFICIENT</sec:control-flag>
```

```
<n1:msad-or-ldap-login-required>true</n1:msad-or-ldap-login-required>
```

```
<n1:external-password-required>true</n1:external-password-required>
```

```
<n1:authentication-type>MSAD</n1:authentication-type>
```

```
<n1:ldap-server-ip-and-port>LDAP://localhost:389</n1:ldap-server-ip-and-port>
```

```
<n1:ldap-ssl-enabled>true</n1:ldap-ssl-enabled>
```

```
<n1:security-authentication-type>simple</n1:security-authentication-type>
```

```
<n1:ldap-domain-name>I-FLEX.COM</n1:ldap-domain-name>
```

```
<n1:ldap-server-time-out-duration>0</n1:ldap-server-time-out-duration>
```

```
</sec:authentication-provider>
```

- Make sure tag values matches the value given during Property file creation.

8.1.2 JPS Configuration

Go to <ORACLE_HOME>\Middleware\user_projects\domains\base_domain\config\fmwconfig path. Open jps-config.xml file. The following codes need to be added at proper locations in the jps-config.xml.

Search for <serviceProviders> tag and add the following code between <serviceProviders> and </serviceProviders> tags.

```
<serviceProvider type="IDENTITY_STORE" name="custom.provider"
class="oracle.security.jps.internal.idstore.generic.GenericIdentityStoreProvide
r">
```

```
<description>DB IdentityStore Provider</description>
```

```
</serviceProvider>
```

Search for <serviceInstances> tag and add the following code between <serviceInstances> and </serviceInstances> tags.

```
<serviceInstance name="idstore.custom" provider="custom.provider"
location="dumb">
```

```
<description>Custom Identity Store Service Instance</description>
```

```
<property name="idstore.type" value="CUSTOM"/>
```

```
<property name="ADF_IM_FACTORY_CLASS"
value="com.ofss.fcc.bpel.security.idm.providers.stddb.FCIdentityStoreFactory"/>
```

```
<property name="DATASOURCE_NAME" value="jdbc/fcjddevDS"/>
```

```
</serviceInstance>
```

Make sure JNDI given ie jdbc/fcjddevDS matches the value given during Property file creation.

Search for <jpsContexts default="default"> tag and make the following changes in the code between <jpsContexts default="default"> and </jpsContexts> as highlighted below.

```
<jpsContext name="flex">
```

```
<serviceInstanceRef ref="credstore"/>
```

```
<serviceInstanceRef ref="keystore"/>
```

```
<serviceInstanceRef ref="policystore.xml"/>
```

```
<serviceInstanceRef ref="audit"/>
```


```
<serviceInstanceRef ref="idstore.custom"/>
```

```
</jpsContext>
```



8.1.3 Workflow Identity Configuration

Workflow Identity Configuration needs to be done from Enterprise Manager Console of SOA.


1. Login to EM Console
2. Expand SOA and right click on soa-infra(soa-server1). Go to Administration and click on System MBean Browser.




3. Expand oracle.as.soainfra.config > Server : soa_server1(Managed Server Name) > WorkflowIdentityConfig. And Click on **human-workflow** and select **Operation** tab from right side and select **createConfiguration** option.




4. Click on **Invoke** option.




5. The following Confirm message will be displayed.




6. Refresh the MBean Browser and expand **WorkflowIdentityConfig.ConfigurationType**. New Configuration will be available with name **NO_REALM**.



- Click on **NO_REALM**. And Click on **Attributes** tab. Change default attribute of NO_REALM to true from false.



8. Click on **Operations** tab. And Click on **setRealmName**.



9. Enter the value as 'flexcube' or 'flexcube1'. and Click on **invoke**.

Operation: setRealmName Invoke Revert Return

MBean Name: oracle.as.soainfra.config:Location=soa_server1,WorkflowIdentityConfig=human-workflow,
name=flexcube,type=WorkflowIdentityConfig.ConfigurationType,Application=soa-infra

Operation Name: setRealmName

Description: The realm name associated with this configuration

Return Type: boolean

Parameters

Name	Type	Value
p1	java.lang.String	flexcube

Return Value

10. Refresh the MBean Browser. Expand **flexcube** ☐

WorkflowIdentityConfig.ConfigurationType.ProviderType and Click on **oracle.soa.management.config.identity.ProviderType@....** Click on **Attributes** tab. And provide the following values.

- Change Name to JspProvider1 or JspProvider2.
- Verify value of PropertyType and Service. PropertyType should be **JPS** and Service should be **Identity**.


System MBean Browser

Application Defined MBeans: WorkflowIdentityConfig.....ProviderType:oracle.....ProviderType@6fcd2 Apply Revert

Show MBean Information

Name	Description	Access	Value
1. className	The class name of the provider.	R	
2. ConfigMBean	If true, it indicates that this MBean is a Config MBean.	R	true
3. Connection	Name of the MBean for managing the associated Connection.	R	
4. eventProvider	If true, it indicates that this MBean is an event provider as defined by JSR-77.	R	true
5. eventTypes	All the event's types emitted by this MBean.	R	inv.attribute.change
6. Name	The name of the provider.	RW	JspProvider1
7. objectName	The MBean's unique JMX name	R	oracle.as.soainfra.config:WorkflowIdentityConfig=human-workflow,name=flexcube,type=WorkflowIdentityConfig.ConfigurationType,Application=soa-infra
8. Properties	Names of the MBeans for managing the associated properties.	R	
9. ProviderType	The provider type for this provider configuration.	R	JPS
10. ReadOnly	If true, it indicates that this MBean is a read only MBean.	R	false
11. RestartNeeded	Indicates whether a restart is needed.	R	false
12. RoleControls	Name of the MBean for managing the associated Role Control.	R	
13. Service	The associated service.	R	Identity
14. SystemMBean	If true, it indicates that this MBean is a System MBean.	R	false
15. UserControls	Name of the MBean for managing the associated User Control.	R	


11. Select createProperty option from **Operations** tab and click on **Invoke**. It will create new Property under JspProvider1




12. Select the newly create property and change the Name and Value using **setName** and **setValue** option from **Operation** tab.

- Name should be **jpsContextName**
- Value should be **flex**.

NOTE: the value **flex** given above should be same as the value given for jpsContext in section JPS Configuration earlier in this document.




13. Click on jazzn.com .Click on **Attributes** tab. Change value of Default attribute to false.




14. Restart both Weblogic and SOA Server. After restart of the server verify the details. Final structure should be similar to attached screen.



2. Right click on soa-infra and select security ☐ Application Policies




3. Click on Create and to create a new Application Grant.






4. Create a super user BPELADMIN by clicking Add Button in Grantee Tab.






5. Now Click on add button under Permission to add privileges for the user and select from permission and search to get permission and resource name.






6. Click on required permissions and click ok to set permission for the user.
7. Similarly select all other permissions available and add.
8. Click OK to apply permission to the user. It should look like below



8.1.5 Custom Escalation Configuration


Security Policy Configuration needs to be done from the Enterprise Manager console of the SOA.

1. Login to Enterprise Manager Console.
2. Right click on soa-infra and select SOA Administration ☐ Workflow Config.
3. Click on Task TAB.



4. Click on Add Function and Enter the below details
 - Function Name : CUSTOM_ESCALATION
 - Classpath : com.ofss.fcc.bpel.cac.FCBPELTaskAssignmentComponent

5. Click on OK, then click on Apply.



8.1.6 CIS Configuration

Along with FCIS Ear file, Installer creates BPELCIS.jar file.

- Create separate jar files for FCBPELCIS.jar as follows.
1. Create two separate folders (ie.cac,cis)and copy the jar file on both folders.
 2. Rename the jar in cac folder as FCBPELCAC.jar
 3. From the cis folder,open the jarfile and delete cac folder from com/ofss/fcc/bpel to create actual FCBPELCIS.jar
 4. From the cac folder,open the jarfile and delete dao and security folders from /ofss/fcc/bpel to create actual FCBPELCAC.jar
- Open this FCBPELCAC JAR file and open CIS.Properties file which is available under **com\ofss\fcc\bpel\cac** folder.
 - set the **JNDI.name** value to the JNDI name given during Property file creation.
 - open **classes folder** from

<MIDDLEWARE_HOME>Oracle_SOA1\soa\modules\oracle.soa.ext_11.1.x. and

extract FCBPELCAC.jar contents to classes folder.Make sure the classes folder

contains the folder structure like com\ofss\fcc\bpel\cac and

under that, files

CISProperties.properties,

FCBPELTaskAssignmentComponent.class,

FCBPELTaskAssignmentComponent\$1.class

- Now copy FCBPELCIS.jar from cis folder to
<MIDDLEWARE_HOME>/user_projects/domains/<DOMAIN_NAME>/lib
- Add grants jazn-policy for BPELADMIN user for application soa-infra in system-jazn-data.xml as attached(Search for bpeladmin and BPELADMIN)



system-jazn-data.xml

Like

<grant>

<grantee>

<principals>

<principal>

<class>weblogic.security.principal.WLSUserImpl</class>

<name>bpeladmin</name>

</principal>

</principals>

</grantee>

<permissions>

<permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>

<name>workflow.admin</name>

</permission>

<permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>

<name>workflow.admin.evidenceStore</name>

</permission>

<permission>


```

        <class>oracle.security.jps.JpsPermission</class>
        <name>soadeploy</name>
    </permission>
    <permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>
    <name>workflow.mapping.publicFlexField</name>
</permission>
<permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>
    <name>workflow.admin.activityGuide</name>
</permission>
<permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>
    <name>workflow.mapping.*</name>
</permission>
<permission>
    <class>oracle.rules.adf.permission.RulesEditorPermission</class>
    <name>RulesEditorPermission</name>
    <actions>access</actions>
</permission>
</permissions>
</grant>
<grant>
    <grantee>
        <principals>

```

```

        <principal>
            <class>weblogic.security.principal.WLSUserImpl</class>
            <name>BPELADMIN</name>
        </principal>
    </principals>
</grantee>
<permissions>
    <permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>
        <name>workflow.admin</name>
    </permission>
    <permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>
        <name>workflow.admin.evidenceStore</name>
    </permission>
    <permission>
        <class>oracle.security.jps.JpsPermission</class>
        <name>soadeploy</name>
    </permission>
    <permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>
        <name>workflow.mapping.publicFlexField</name>
    </permission>
    <permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>

```

```

        <name>workflow.admin.activityGuide</name>
    </permission>
    <permission>

<class>oracle.bpel.services.workflow.permission.WorkflowPermission</class>

        <name>workflow.mapping.*</name>
    </permission>
    <permission>

        <class>oracle.rules.adf.permission.RulesEditorPermission</class>
        <name>RulesEditorPermission</name>
        <actions>access</actions>
    </permission>
</permissions>
</grant>

```

Restart the Server.

8.1.7 **Configuring DBAdapter**

In order to configure DBAdapter, follow the steps given below.

1. Log in to 'Weblogic Console' and click 'Deployment' under 'Domain Structure'.

Summary of Deployments

This page displays a list of Java EE applications and stand-alone application modules that have been installed to this domain. Installed applications and modules can be started, stopped, updated (redeployed), or deleted from the domain by first selecting the application name and using the controls on this page.

To install a new application or module for deployment to targets in this domain, click the Install button.

Customize this table

Deployments

Name	State	Health	Type	Deployment Order
adf.oracle.domain(1.0.11.1.1.2.0)	Active		Library	100
adf.oracle.domain.webapp(1.0.11.1.1.2.0)	Active		Library	100
AdiAdapter	Active	OK	Resource Adapter	324
Db2z	Active	OK	Enterprise Application	313
DefaultTaskFlow	Prepared	OK	Enterprise Application	100
composer	Active	OK	Enterprise Application	315
DbAdapter	Active	OK	Resource Adapter	322
DefaultTaskFlow	Active	OK	Enterprise Application	314
GMS Application (1.1.1.1.1.0)	Active	OK	Web Application	5
efc	Active	Warning	Enterprise Application	100
em	Active	OK	Enterprise Application	400
email	Active		Library	100
emxas	Active		Library	100

In the Deployments table, select 'DbAdapter'. You will be navigated to 'Settings for DbAdapter'.

Settings for DbAdapter

Overview | Deployment Plan | **Configuration** | Security | Targets | Control | Testing | Monitoring | Notes

General | Properties | **Outbound Connection Pools** | Admin Objects | Workload | Instrumentation

This page displays a table of Outbound Connection Pool groups and instances for this resource adapter. The top level entries in the table represent Outbound Connection Pool groups. Groups are listed by connection factory interface and the instances are listed by their JNDI names. Expand a group to obtain configuration information for a Connection Pool instance within an Outbound Connection Pool group. Click the name of a group or instance to configure it. Automatically generated Connection Pools are not displayed in the table below.

Outbound Connection Pool Configuration Table

Groups and Instances	Connection Factory Interface
java.resource.cc.ConnectionFactory	java.resource.cc.ConnectionFactory

2. Click 'Configuration' tab and select 'Outbound Connection Pools' under it.

3. Under 'Groups and Instances', click and expand 'javax.resource.cci.ConnectionFactory'.
4. Click 'New' and select 'javax.resource.cci.ConnectionFactory' in Outbound Connection Group.
5. Define 'JNDI Name' as 'eis/DB/FCCDEV' and click on 'Finish'.

Note: The 'jndi name' should be the same as the one in 'Dbutility sub-process'.

6. Click on 'DbAdapter' again. The new JNDI name is listed.
7. Click on the hyperlink 'eis/DB/FCCDEV'.
8. Click the 'Property Value' field for the 'DataSourceName' and update the application JNDI reference (given in 'fcubs.properties' file) and then press 'Enter' key.
9. Save and restart the Adminserver.



SOA Suite Setup for BPEL Process Flow
[October] [2015]
Version 12.1.0.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.