Oracle® Hospitality e7 Point-of-Sale Security Guide Release 4.2 E67882-01

May 2016



Copyright © 2004, 2016, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Pı	refacereface	iv
	Audience	iv
	Customer Support	iv
	Documentation	iv
	Revision History	iv
1	e7 Point-of-Sale Security Overview	1-1
	Basic Security Considerations	1-1
	Overview of e7 Point-of-Sale Security	1-1
	e7 Component Model	1-1
	Understanding the e7 Point-of-Sale Environment	1-2
	Recommended Deployment Configurations	1-3
	e7 Security	1-4
	Operating System Security	1-4
	Database Encryption Implementation	1-5
	Network Encryption Implementation	1-6
2	Performing a Secure e7 Point-of-Sale Installation	2-1
	Pre-Installation Configuration	2-1
	e7 Point-of-Sale Installation	2-1
	Post-Installation Configuration	2-1
	Generate Encryption Key	2-1
	Configure Restaurant and Employee Access Control Settings	2-1
3	Implementing e7 Point-of-Sale Security	3-1
	Encryption Key Maintenance	
	Employee and Job Category Access Control	3-1
	Masking Employee Categories	3-1
	Masking Job Categories	3-2
	Configuring Access to Configurator Sections	3-2
	Enable Microsoft Windows Complex Passwords	3-2

Preface

This document provides security reference and guidance for the following e7 Point-of-Sale components:

- e7 Point-of-Sales
- e7 Gift Card Interface
- e7 Transaction Services
- e7 Credit Card Interface
- e7 Fiscal Interface

Audience

This document is intended for:

- System administrators installing e7 Point-of-Sale.
- End users of e7 Point-of-Sale.

Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL: https://support.oracle.com

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received and any associated log files
- Screen shots of each step you take

Documentation

Oracle Hospitality product documentation is available on the Oracle Help Center at http://docs.oracle.com/en/industries/hospitality/

Revision History

Date	Description of Change
May 2016	Initial publication

iv Preface

1 e7 Point-of-Sale Security Overview

This chapter provides an overview of Oracle Hospitality e7 Point-of-Sale security and explains the general principles of application security.

Basic Security Considerations

The following principles are fundamental to using any application securely:

- **Keep software up to date.** This includes the latest product release and any patches that apply to it.
- **Limit privileges as much as possible.** Users should be given only the access necessary to perform their work. User privileges should be reviewed periodically to determine relevance to current work requirements.
- **Monitor system activity.** Establish who should access which system components, and how often, and monitor those components.
- Install software securely. For example, use firewalls, secure protocols using TLS (SSL), and secure passwords. See Performing a Secure e7 Point-of-Sale Installation for more information.
- **Learn about and use the e7 Point-of-Sale security features.** See Implementing e7 Point-of-Sale Security for more information.
- Use secure development practices. For example, take advantage of existing database security functionality instead of creating your own application security. See "Security Considerations for Developers" for more information.
- **Keep up to date on security information.** Oracle regularly issues security-related patch updates and security alerts. You must install all security patches as soon as possible. See the "Critical Patch Updates and Security Alerts" Web site: http://www.oracle.com/technetwork/topics/security/alerts-086861.html


Overview of e7 Point-of-Sale Security


Oracle Hospitality e7 uses a role-based access control for employees to configure the system.

For credit card transactions, sensitive account data (SAD) may be transmitted between e7 nodes, the e7 PC, and the credit card processor. Messages are encrypted when transmitting SAD. When storing cardholder data in the e7 database, the data is first encrypted using a key managed by the administrator.

e7 Component Model

The following diagram models the interaction between e7 components, optional peripherals, and optionally the Enterprise Back Office backend database.






Understanding the e7 Point-of-Sale Environment

When planning your e7 Point-of-Sale implementation, consider the following:

- Which resources need to be protected?
 - o You need to protect customer data, such as credit-card numbers.
 - o You need to protect internal data, such as proprietary source code.
 - You need to protect system components from being disabled by external attacks or intentional system overloads.
- Who are you protecting data from? For example, you need to protect your subscribers' data from other subscribers, but someone in your organization might need to access that data to manage it. You can analyze your workflows to determine who needs access to the data; for example, it is possible that a system administrator can manage your system components without needing to access the system data.

• What will happen if protections on strategic resources fail? In some cases, a fault in your security scheme is nothing more than an inconvenience. In other cases, a fault might cause great damage to you or your customers.

Understanding the security ramifications of each resource will help you protect it properly



The blue lines represent encrypted credit card transactions to the host. The red lines represent other traffic.

e7 Security

Oracle Hospitality e7 includes:

- Credit Card Drivers that communicate with several host processors. When
 configuring the system, administrators typically only need to configure one
 driver to communicate with the processor used by the restaurant.
- Several interface drivers that perform a variety of point-of-sales functions. When configuring the database, administrators only need to configure the drivers that relate to the functions used by the restaurant.

Operating System Security

The follow table lists the recommendation settings and actions to secure Microsoft Windows operating systems. You do not need to follow these recommendations for Microsoft Windows Compact Edition.

Setting	Description	
Microsoft Updates	Not configured. Windows Malicious Software Removal Toolx64 (kb890830) not installed.	
Clear Virtual Memory Pagefile on shutdown	Enabled	
Autoplay	Disabled for e7admin. Enabled for new accounts.	
Firewall	On	
Restore Points	Disabled	
Power control settings		
Turn off the display	Never	
Put the computer to sleep	Never	
Hard disk / Turn off hard disk after	Never	
Wireless Adapter Settings / Power Saving Mode	Maximum Performance	
Sleep / Sleep after	Never	
Sleep / Allow hybrid sleep	Off	
Sleep / Hibernate after	Never	
USB / USB selective suspend setting	Disabled	
Power buttons and lid / Power button action	Shut down	
PCI Express / Link State Power Management	Off	

Setting	Description	
Performance Options		
Visual Effects	Adjust for best performance.	
Advanced / Processor scheduling	Programs	
Data Execution Prevention	Turn on DEP for essential Windows programs and services only.	
Local Area Connection 1 Properties		
Internet Protocol Version 6 (TCP/IPv6)	Deselected	
Internet Protocol Version 4 (TCP/IPv4)	IP: 192.168.100.250 Subnet mask: 255.255.255.0	
Global policy settings		
Always use classic logon	Enabled	
Enforce password history	Enabled and set to 4.	
Maximum password age	60	
Password must meet complexity	Enabled	
Audit account logon events policy	Enabled for both Success and Failure.	
Audit logon events policy	Enabled for both Success and Failure.	
Shutdown settings		
Allow system to be shut down without having to log on	Disabled	
Do not display Install Updates and Shut Down Option	Enabled	
Do not adjust default option to Install Updates and Shut down in the	Enabled	

Database Encryption Implementation

Oracle Hospitality e7 encrypts sensitive data fields in the database using a 3DES encryption algorithm and a key derived from a randomly created passphrase.

A user creates the passphrase by clicking **Generate New Key** in the Configurator, and the passphrase is stored in the SYSTEM_DETAIL table in the e7 database using the Rijndael algorithm with a hard-coded key and hard-coded initialization vector (IV). Throughout the e7 GUI and documentation, the passphrase is referred to as the "encryption key" or "key".

The following database fields are encrypted due to their containing payment account data:

Table	Column
ReferenceDbDetailTable	ExpDate
	RefEntry
ReferenceTransDetailTable	ExpDate
	RefEntry
CcBatchItemTable	Track2Data
	CardAccountNumber
	ExpirationDate
	CustomerName
CcBatchTransferItemStatusTable	CardAccountNumber
	ExpirationDate
Credit Auth Db Detail Table	ExpDate
	AcctNum
	Track2
	CustName
	AcctNum

- The e7 application uses the SpecialBytes class found within the MicrosSystems.E7.MicrosData assembly to encapsulate encryption operations. The SpecialBytes class contains routines for managing the passphrase as well as encrypting and decrypting data using the passphrase.
- e7 creates a key using the passphrase and uses the SHA1Managed class to create a hash of the passphrase. e7 then passes the hash to the 3DES algorithm for use as the key.
- When a user changes the key, each node decrypts existing data using the old key and then encrypts data using the new key.
- Users can use unmanaged function calls to Microsoft CryptoAPI with a 3DES algorithm and hard-coded key data to read and write data that was encrypted and stored in e7 versions older than 3.0.

Network Encryption Implementation

e7 uses symmetric encryption to encrypt the payload of messages containing credit card and gift card account information that are transmitted among e7 nodes.

- e7 performs encryption using a 3DES algorithm. The application creates a password using hard-coded seed data, and then uses an MD5 hash algorithm with the password to create a key.
- e7 applies encryption to Credit Card Server and TIFManager datagram messages.

2 Performing a Secure e7 Point-of-Sale Installation

For information about installing e7, see the *Oracle Hospitality e7 Point-of-Sale Installation Guide*

Pre-Installation Configuration

If you are upgrading from one of the following versions:

- 1.0
- 1.5 and 1.5 Patch 1
- 2.0
- 2.0, 2.0 Patch 1, and 2.0 Patch 2
- 2.7

You must remove historical sensitive data. See the *Oracle Hospitality e7 Point-of-Sale PA-DSS Implementation Guide* for more information and instructions about removing historical sensitive data and securing your system for processing credit card payments.

e7 Point-of-Sale Installation

e7 does not have options or customizations during installation. Follow the instructions in the *Oracle Hospitality e7 Point-of-Sale Installation Guide* when installing on the workstations and optionally the PC server.

Post-Installation Configuration

Generate Encryption Key

You must generate an encryption key after completing all installation processes.

- 1. Make sure there are no open checks in the system and no offline workstations, or the operation will fail.
- 2. In the e7 Configurator, click **Restaurant**, click **Credit Cards**, and then click **Generate Key**.
- 3. On the Generate Encryption Key dialog box, click **Yes**, and then confirm that you want to generate the key.

Configure Restaurant and Employee Access Control Settings

See the Oracle Hospitality e7 Point-of-Sale PA-DSS Implementation Guide for more information about securing the restaurant and employee accounts.

3 Implementing e7 Point-of-Sale Security

Encryption Key Maintenance

Change the passphrase used by e7 to generate the Triple-DES 128-bit encryption key at least once per calendar year. You do not need to generate the key more than once in the store.

- 1. Make sure there are no open checks in the system and no offline workstations, or the operation will fail.
- 2. In the e7 Configurator, click **Restaurant**, click **Credit Cards**, and then click **Generate Key**.
- 3. On the Generate Encryption Key dialog box, click **Yes**, and then confirm that you want to generate the key.

Employee and Job Category Access Control

Warning: If you are not careful when configuring access control, you may lock yourself out and require reloading the database from a backup or a full reinstallation.

Masking Employee Categories

You can configure an employee category hierarchy and select **Hide from others** to restrict employee access to employee records belonging to the employee category to which they belong and to employee categories lower in the hierarchy.

For example, if you have the following employee categories:

Object Number	Employee Category
1	Superuser
2	Management
3	Front of House

An employee belonging to the Management category can view their Management and Front of House employee records. This access control also:

- Prevents changing the Number field of the employee category to prevent employees from modifying the hierarchy.
- Allows employees to modify the Password ID and Alternate Password ID fields for themselves and for employees belonging to lower employee categories.
- Removes hidden jobs from the **Default job** and **Job** drop-down lists in the Job Information tab.

To configure the employee category hierarchy:

- 1. Navigate to **Employees** from the menu, select an employee category, and then click the **General** tab.
- 2. Enter the hierarchy level in the **Number** field, where 1 is the highest level.
- 3. Select **Hide from others**.

Masking Job Categories

You can configure a job category hierarchy and select **Hide from others** to restrict employee access to job records belonging to the job category to which they belong and to job categories lower in the hierarchy.

For example, if you have the following job categories:

Object Number	Job Category	Jobs
1	Superuser	Superuser, Administrator
2	Management	Manager, Shift Manager
3	Front of House	Bar, Bar/Manager, Cashier, Host/Bus, QSR, Runner, Server

An employee working as a Manager can view and edit the Manager job record and Front of House job records such as the Bar.

To configure the job category hierarchy:

- Navigate to **Jobs** from the menu, select a job category, and then click the **General** tab.
- 2. Enter the hierarchy level in the **Number** field, where 1 is the highest level.
- 3. Select **Hide from others**.

Configuring Access to Configurator Sections

You can configure access to specific forms in the e7 Configurator by job.

- 1. Navigate to **Configurator Access** from the menu.
- 2. Click **Add Record** to add a new access control rule.
- 3. Select a **Job**, and then select **Prevent form access**.
- 4. Select the form you want to prevent the job from accessing.

Enable Microsoft Windows Complex Passwords

- 1. Run gpedit.msc as an administrator.
- Double-click Computer Configuration, double-click Windows Settings, doubleclick Security Settings, double-click Account Policies, and then double-click Password Policy.
- 3. Set the following values:
 - Enforce password history: 4 passwords remembered
 - Maximum password age: 60 days
 - Minimum password age: 0 days
 - Minimum password length: 8 characters
 - Password must meet complexity requirements: Enabled